HotProtein: A Novel Framework for Protein Thermostability Prediction and Editing

Abstract

The molecular basis of protein thermal stability is only partially understood and has major significance for drug and vaccine discovery. The lack of datasets and standardized benchmarks considerably limits learning-based discovery methods. We present `HotProtein`, a large-scale protein dataset with *growth temperature* annotations of thermostability, containing 182K amino acid sequences and 3K folded structures from 230 different species with a wide temperature range $-20^\circ\text{C} \sim 120^\circ\text{C}$. Due to functional domain differences and data scarcity within each species, existing methods fail to generalize well on our dataset. We address this problem through a novel learning framework, consisting of (1) Protein structure-aware pre-training (SAP) which leverages 3D information to enhance sequence-based pre-training; (2) Factorized sparse tuning (FST) that utilizes low-rank and sparse priors as an implicit regularization, together with feature augmentations. Extensive empirical studies demonstrate that our framework improves thermostability prediction compared to other deep learning models. Finally, we propose a novel editing algorithm to efficiently generate positive amino acid mutations that improve thermostability.

1 Introduction

Proteins are the bio-polymers responsible for executing most biological phenomena and, through evolution, have had their sequences optimized to carry out specific functions within specific cellular environments. A protein's stability is a multidimensional property that depends on a series of factors [2, 3] such as pH, salinity, and temperature

Figure 1: Overheat deactivates proteins [1].

(thermostability shown in Figure 1), making it hard to adapt a protein to function outside of its endogenous cellular environment. Protein engineering is the field where natural proteins are mutated to improve their stability in exogenous environments and their overall fitness for a particular function. In protein engineering, one of the initial goals for most engineering campaigns is to improve the thermal stability of protein [4, 5, 6]. Thermally stabilized proteins are more robust and therefore enable downstream applications in the food [7], biofuel [8], detergent [9], chemical [10], and pharmaceutical industry [11], drug design [12, 13], and bioremediation of environmental pollutants [14, 15]. Thus, to accelerate the engineering of a target protein it is critical to understand and accurately predict thermal stability changes of mutations. There has been a substantial effort from the community to quantitatively understand and model protein thermostability [*e.g.,* 2, 3, 16, 17, 18, 19]. However, the generalizability of them is still unsatisfactory, and laborious experimental methods such as directed evolution are often preferred.

Submitted to NeurIPS 2022 AI for Science Workshop.

To enhance the capabilities of learning-based approaches, we present a large-scale, standardized protein benchmark, *i.e.,* HotProtein, with *organism-level* temperature annotations which is a lower bound of protein's melting temperature [20]. It consists of 182K protein sequences and 3K folded structures from 230 different species, covering a broad temperature range of $-20°$C-120$°$C. However, similar to [3], naively trained deep models even on our dataset do not enable generalization to unseen proteins. The presumed reasons are (1) the considerable functional heterogeneity in proteins that arise from the environmental conditions and evolutionary history and (2) the scarcity of high-quality thermostability experimental data due to the massive cost and labor required to generate such data.

To tackle these pain points, we propose a novel algorithmic pipeline to improve thermostability prediction. First, we enrich our sequence embeddings by infusing 3D structural information in a contrastive manner–we call this structure-aware pre-training (SAP). Then, we further fine-tune our model with a factorized sparse tuning (FST) approach. Here, we utilize factorized low-rank and sparse priors as implicit regularizers and leverage feature augmentation, such as mix-up [21] and worse-case augmentations [22]. FST greatly boosts the performance of tuned predictors, suggesting improved data efficiency and robustness against domain shifts [23, 24]. Extensive evaluations on both HotProtein and the other existing protein datasets verify our proposals' effectiveness.

Finally, to identify the top mutational predictions likely to improve thermal stability for a target protein, we develop a new optimization-based editing framework on top of a classifier or regressor, that attempts to mimic the process of directed evolution while limiting the stochasticity [16]. Unlike existing protein engineering approaches [25, 26, 27] that directly utilize the predictions to generate mutational designs, our proposal maximizes the model's objective to approach a more thermostable label to identify input mutated sequences. Our contributions can be summarized as follows:

* ⋆ We collect and present a large-scale protein dataset, *i.e.,* HotProtein, with organism-level temperature annotations. We use the organism's environmental growth temperature to label and classify all proteins within each organism, which we use for thermostability prediction and editing. It contains 182K amino acid sequences and 3K folded 3D structures of proteins from 230 different species, covering five thermostability types, *e.g.,*, Cryophilic, Psychrophilic, Mesophilic, Thermophilic, and Hyperthermophilic.
* ⋆ We introduce a protein structure-aware pre-training by injecting 3D structural information into sequence embeddings in a contrastive fashion. It enhances the diversity and expressivity of the protein representations, resulting in improved thermostability predicting performance.
* ⋆ We propose a robust and data-efficient tuning framework that performs weight updates in the factorized and sparse subspace together with augmented feature embedding. This leads to substantial performance improvements against data scarcity and severe distribution shifts.
* ⋆ We formulate the search for thermal stabilizing mutations as an optimization problem: for a target protein and a trained predictor, we built an editing framework that optimizes the input protein sequences to identify thermostabilizing mutations.
* ⋆ Extensive experiments conducted on both thermostability prediction and protein editing tasks, consistently demonstrate the superiority of our proposals over various existing approaches [28]. For example, when fine-tuned on experimentally determined T_m dataset, FireProtDB, our editing suggester achieves 53.93% ($\uparrow 8.96\%$) precision in positive mutation classification, 50.79 ($\uparrow 6.54$) Spearman ρ correlation coefficient in the temperature regression, and 54.24% ($\uparrow 1.83\%$) successful rate in generating positive single mutations.

2 The HotProtein Dataset

To obtain thermostable labels for an organism's proteome, we collect the raw data from the NCBI BioProject [31], which offers an organizational framework to access the (meta-)data about research projects, which is deposited or planned for deposition, into archival repositories.

Preprocess. From the NCBI bioproject XML file[1], we filter organisms where the environmental data (*i.e.,* "OptimumTemperature" and "TemperatureRange") is available. After removing duplicate

---

[1] https://ftp.ncbi.nlm.nih.gov/bioproject/bioproject.xml

Figure 2: The overview of `HotProtein` dataset. Figures A.1 ∼ 3), B.1 ∼ 3), and C.1 ∼ 2) collect the statistics of HP-S^{2}C2, HP-S^{2}C5, and HP-S respectively. The *left* figure records the density distribution of each category over the protein's **growth (organism-level) temperature**. The density in a bin is computed as $\frac{\text{\# proteins within the bin}}{\text{\# proteins in the category}}$. {1026} indicates that there are 1026 proteins in the corresponding class "Hot". The *upper right* figure is the predicted template modeling (P-TM) score from AlphaFoldv2 [29, 30], reflecting the quality of folded protein structures. A larger P-TM suggests a better quality and P-TM ≥ 0.8 (red lines) is a normal threshold for satisfied folded structures. The *bottom right* figure presents the species distribution of the three datasets, and # species in certain categories is included in the brackets.

organism entries (keeping the first entry), this provides us with $1,733$ unique entries. Next, we proceed to download these organisms' proteomes from UniProt[2] via their taxids and bin the proteomes based on the "TemperatureRange" classification of that organism. Finally, we remove all proteins over $1,500$ amino acids in length and utilize CD-Hit[3] to cluster protein sequences across organisms within a "TemperatureRange" class at a sequence similarity threshold of 50%. In each cluster, we only keep proteins whose sequence lengths are between $200 \sim 550$.

Annotation and Folding. To further increase the fidelity of our annotations, we remove organisms from each "TemperatureRange" bin where the "OptimumTemperature" does not fall within the the corresponding limits: ❶ *Hyperthermophilic* (> 75 Celsius), ❷ *Thermophilic* ($45 \sim 75$ Celsius), ❸ *Mesophilic* ($25 \sim 45$ Celsius), ❹ *Psychrophilic* ($5 \sim 25$ Celsius), and ❺ *Cryophilic* ($-20 \sim 5$ Celsius). The filtered proteomes and their corresponding annotations form the `HotProtein` dataset and are utilized throughout the classification and regression tasks in our study.

For a random subset of the `HotProtein` dataset (~ 3K), we predict structure with AlphaFoldV2 [29, 30] to obtain their 3D coordinates. The official implementation is adopted. We report the predicted template modeling (P-TM) scores for each folded structure in Figure 2 A.3) and B.3). The P-TM score is a rough approximation of the folding quality [29], and ≥ 0.8 indicates a satisfying protein structure in common sense.

Properties. As described in Figure 2, we generate four distinct testbeds from the `HotProtein` dataset that differed in scale: (1) HP-S^{2}C2 has 1026 "hot" ($\geq 45°$C) and 939 "cold" ($< 45°$C) proteins from 61 and 4 species, respectively. Both sequence and structure statistics of these proteins are provided. (2) HP-S^{2}C5 consists of both sequences and structures for {73, 387, 195, 196, 189} proteins sampled from the five categories, from *Cryophilic* to *Hyperthermophilic*. (3) HP-S is the entire sequence `HotProtein` dataset. It contains {6390, 34946, 30333, 79087, 31549} sequences from {3, 32, 31, 116, 48} different species, of five classes ordered from *Cryophilic* to *Hyperthermophilic*. (4) Moreover, HP-SC2 as a 2-class variant is created by merging *Hyperthermophilic* and *Thermophilic* as "hot" class and the other three as "cold" class. **Note that all temperature annotations are organism-level, serving as a lower bound of for a protein's melting temperature**.

---

[2]https://www.uniprot.org/help/uniprotkb
[3]http://weizhong-lab.ucsd.edu/cd-hit/

Figure 3: The overall pipeline of our proposals. The *left* describes the protein structure-aware pre-training (SAP); The *right* presents the factorized sparse tuning (FST).

3 Methodology

Denote the thermostability dataset by $\mathcal{D} = \{\boldsymbol{x}_i, y_i\}_{i=1}^{N}$, where $\boldsymbol{x}_i$ stands for the input while y_i is the thermostability critical temperature (either real value or class index). Here we describe 1) how we pretrain the model $\mathcal{F}$, and 2) how we finetune to pretrained model to fit $\mathcal{D}$.

3.1 Protein Structure-Aware Pre-training

Previous protein pre-trained models [*e.g.,* 32, 33, 34, 35] mainly focus on masking prediction tasks and amino acid representations. These models achieve considerable improvements on amino acid prediction tasks, *e.g.,* contact prediction, mask prediction [36], mutational effect prediction [35]. On the other hand, directly learning universal protein embedding is potentially useful for protein prediction tasks. Inspired by recent sentence representation learning works [37] and 3D structure-aware pre-training model [38], we propose a contrastive loss for representation learning.

Contrastive Loss Design. Denote the model as $\mathcal{F}$, our contrastive loss function is defined as:

$$\mathcal{L}_{\text{InfoNCE}}(\boldsymbol{x}_i, \text{Neg}(\boldsymbol{x}_i)) = -\log \frac{\exp(\mathcal{F}'(\boldsymbol{x}_i) \cdot \mathcal{F}''(\boldsymbol{x}_i)/\tau)}{\exp(\mathcal{F}'(\boldsymbol{x}_i) \cdot \mathcal{F}''(\boldsymbol{x}_i)/\tau) + Z(\boldsymbol{x}_i, \text{Neg}(\boldsymbol{x}_i))}, \quad (1)$$

where $Z(\boldsymbol{x}_i, \text{Neg}(\boldsymbol{x}_i)) = \sum_{\boldsymbol{x}_j \in \text{Neg}(\boldsymbol{x}_i)} \exp(\mathcal{F}'(\boldsymbol{x}_i) \cdot \mathcal{F}'^{\text{mom}}(\boldsymbol{x}_j)/\tau)$. Here, $\mathcal{F}'(\boldsymbol{x}_i)$ and $\mathcal{F}''(\boldsymbol{x}_i)$ are two copies of randomly perturbed models by injecting independent dropout noises into $\mathcal{F}(\boldsymbol{x}_i)$, and $\text{Neg}(\cdot)$ presents a set of negative examples, and $\mathcal{F}^{\text{mom}}$ is a slowly updated momentum model (see below) and τ is the temperature value. Notice that random mutating amino acid could introduce unknown changes [39, 40], we add perturbations to hidden representations and inject layer-wise dropout noise [41] with a rate 0.05 in practice, and follow the hyperparameter configurations in [42].

Leverage 3D Information. We combine an additional 3D structure model using 3D inputs with the sequence-based model, to enhance the performance. We therefore slightly change Equation 1 into,

$$\mathcal{L}_{\text{3D}}(\boldsymbol{x}_i, \text{Neg}(\boldsymbol{x}_i)) = -\log \frac{\exp(\mathcal{F}'(\boldsymbol{x}_i) \cdot \mathcal{F}''_{\text{3D}}(\boldsymbol{x}_i)/\tau)}{\exp(\mathcal{F}'(\boldsymbol{x}_i) \cdot \mathcal{F}''_{\text{3D}}(\boldsymbol{x}_i)/\tau) + Z(\boldsymbol{x}_i, \text{Neg}(\boldsymbol{x}_i))}, \quad (2)$$

$$Z(\boldsymbol{x}_i, \text{Neg}(\boldsymbol{x}_i)) = \sum_{\boldsymbol{x}_j \in \text{Neg}(\boldsymbol{x}_i)} \left\{ \exp(\mathcal{F}'(\boldsymbol{x}_i) \cdot \mathcal{F}'^{\text{mom}}_{\text{3D}}(\boldsymbol{x}_j)/\tau) + \exp(\mathcal{F}'_{\text{3D}}(\boldsymbol{x}_i) \cdot \mathcal{F}'^{\text{mom}}(\boldsymbol{x}_j)/\tau) \right\},$$

where $\mathcal{F}_{\text{3D}}$ stands for the 3D structure model which uses 3D coordinates as inputs, $\mathcal{F}^{\text{mom}}_{\text{3D}}$ is its momentum model. The memory bank logs the negative examples from both the sequence and 3D models. In short, a pair for sequence and 3D model representation is regarded as the positive pair, and we aim at injecting 3D representation information into the sequence model.

3.2 Factorized Sparse Tuning Under Data Scarcity and Distribution Shift

In real-world application domains, it is extremely challenging or even infeasible to collect a sufficient large-scale (engineered) protein dataset, due to the massive time and resource cost of transformation, protein expression, and purification. Therefore, data scarcity is one of the crucial bottlenecks in predicting protein properties. Another obstacle lies in the substantial data distribution shifts. For examples, normal functional protein regions are formed by around 100 amino acids [43], while COVID-19 related proteins usually contain more than $1,000$ amino acids [44]. Meantime, proteins with different (sometimes even the same [44]) functionalities have distinctive and idiographic structures, sharing few common characteristics. To tackle these two issues, we propose a factorized sparse

145 tuning pipeline (FST). It leverages the low-rank and sparse priors as implicit regularizations for
146 enhanced data-efficiency [*e.g.,* 45, 46, 47, 48, 49, 50] and robustness to domain shifts [23].

147 **Enforcing the Low-rank Prior through Factorization.** Given a pre-trained model $W_p \in \mathbb{R}^{m \times n}$, we
148 perform a low-rank decomposition to its weight update ΔW represented as $W_p + \Delta W = W_p + UV$,
149 where $U \in \mathbb{R}^{m \times r}$, $V \in \mathbb{R}^{r \times n}$, and the rank $r \ll \min\{d, k\}$. Usually, $r = 4$ or 8 (*i.e.,* 0.6% of total
150 parameters) is sufficient to achieve a great performance in our case. During forward, the input is
151 fed into both dense pre-training W_p and its low-rank representation UV. The obtained features are
152 summed in a coordinate-wise manner, as demonstrated in Figure 3 (*right*). Take the original feature
153 $h = W_p \boldsymbol{x}$ as an example. Our modified features can be described as below:

$$\hat{h} = W_p \boldsymbol{x} + \Delta W \boldsymbol{x} = W_p \boldsymbol{x} + UV \boldsymbol{x}. \tag{3}$$

154 As for the backpropagation, W_p is frozen and low-rank matrices $\{U, V\}$ receive gradient updates.
155 We adopt Xavier normal [51] and zero initialization for U and V respectively, and therefore the
156 low-rank update is zero in the beginning. As suggested by [52], $UV \boldsymbol{x}$ can be scaled via an extra
157 hyperparameter α, which works similarly to the learning rate. In our case, we find α is not sensitive
158 and set it as 4, *i.e.,* the default value used in [52].

159 **Enforcing the Sparsity Prior.** We introduce the sparsity into tuning processes as an implicit structural
160 prior by modeling a sparse weight update with $S \in \mathbb{R}^{m \times n}$. As indicated in Figure 3, our refined
161 features $\tilde{h}$ are depicted as follows:

$$\tilde{h} = W_p \boldsymbol{x} + (UV + S)\boldsymbol{x}, \quad S = \begin{cases} s_{i,j}, & (i, j) \in \Omega \\ 0, & (i, j) \in \Omega^{\mathrm{C}} \end{cases}, \tag{4}$$

162 where a "residual" feature $S\boldsymbol{x}$ is point-wisely added to $\hat{h}$ from Equation 3, $i \in \{1, 2, \cdots, m\}$,
163 and $j \in \{1, 2, \cdots, n\}$. The set Ω determines the position of trainable $s_{i,j}$ and pruned elements,
164 where the latter is 0 across the whole training. We compute the initial sparse matrix of S by i) first
165 solving a robust principal component decomposition [53] of W_p with an efficient algorithm (*i.e.,*
166 GreBsmo [54]), and ii) then eliminating the elements with the least magnitude of obtained sparse
167 solutions. In this way, the step i) produces the initial values of $s_{i,j}$ and the step ii) constructs the set
168 Ω, where we observe $|\Omega| = 64$ (*i.e.,* 0.01% of total parameters) is good enough in our case. As also
169 revealed in [55], combining the low-rank and sparse weight updates is capable of delivering superior
170 performance, compared to either of them.

171 **Feature Augmentation.** Another group of common fixes to data scarcity and domain shift problems
172 is data augmentation [56]. However, most of existing data-level augmentations are unrealistic to
173 protein sequences, including regional dropout [54, 57] and CutMix [58] in computer vision; synonym
174 replacement [59, 60, 61], random insertion, swap, and deletion [62] in natural language processing.
175 The reason is that even a single amino acid mutation for the protein sequence may dramatically
176 change its functionality [40, 39]. To avoid ambiguity, we utilize feature-level augmentations which
177 manipulate the model's intermediate feature embedding. Specifically, we examine two effective
178 mechanisms: (1) *Mixup* feature augmentation. It creates a fused feature $\tilde{h}_{\mathrm{aug}} = \lambda \times \tilde{h}_1 + (1 - \lambda) \times \tilde{h}_2$
179 and its associated soft label $y_{\mathrm{aug}} = \lambda \times y_1 + (1 - \lambda) \times y_2$, where $\{\tilde{h}_1, y_1\}$, $\{\tilde{h}_2, y_2\}$ are {feature
180 embedding, label} of two different sequences and $\lambda = 0.2$ in our experiments. (2) *Worst-case* feature
181 augmentation. It injects worst-case noises δ and builds an augmented feature $\tilde{h}_{\mathrm{aug}} = \tilde{h} + \delta$, where
182 δ is generated by $\max_\delta \mathcal{L}(\mathcal{F}(\boldsymbol{x}, \tilde{h} + \delta), y)$ with the gradient ascent [22]. $\mathcal{L}$, $\mathcal{F}$ and $\boldsymbol{x}$ denote the
183 objective function, model, and input sequence, respectively.

4 Experiments

4.1 Implementation Details

186 **Metrics.** The performance is evaluated on the test splits. {Accuracy, Precision} and {Spearman,
187 Pearson} correlation coefficients are used for classification and regression tasks. For `HP-S`^{2}`C2` and
188 `HP-S`^{2}`C5`, 10-fold evaluation is conducted; while on `HP-S` and `HP-SC2`, we run three replicates with
189 different random seeds. Average performance and its 95% confidence intervals are reported. **Training**
190 **details** are provided in Appendix C.

Table 1: Performance of predicting thermostability with classification. Accuracy (%) is reported for all three datasets, and Precision (%) is calculated for the 2-class classification on HP-S^{2}C2 and HP-SC2. "FST", "Aug.", and "SAP" denote factorized sparse tuning, feature augmentation, and protein structure-aware pre-training, respectively. FST adopts $(r, |\Omega|) = (4, 64)$ on HP-S^{2}C2/C5 and $(r, |\Omega|) = (8, 64)$ on HP-S/SC2. N.A. means "not applicable". 95% confidence interval are computed via the 10-fold evaluation on HP-S^{2}C2/C5 and 3 replicates on HP-S/SC2.

Methods	HP-S^{2}C2		HP-S^{2}C5	HP-S	HP-SC2	
	Accuracy	Precision	Accuracy	Accuracy	Accuracy	Precision
3D GCN [63]	78.88±1.57	73.39±2.76	67.40±2.11	N.A.	N.A.	N.A.
TAPE [64]	83.31±1.10	76.42±3.06	66.44±2.30	64.75±0.23	76.37±0.25	80.64±0.50
ESM-IF1 [38]	79.08±0.85	76.49±3.96	58.75±2.46	N.A.	N.A.	N.A.
ESM-1B [28]	91.19±0.47	84.18±1.71	83.26±1.54	69.50±0.16	86.24±0.22	88.14±1.62
ESM-1B + Aug.	91.74±0.79	86.09±2.12	84.32±1.41	69.54±0.39	86.26±0.22	88.27±1.43
ESM-1B + FST	91.85±0.45	84.85±1.04	85.96±1.13	72.97±0.28	87.54±0.38	88.71±1.73
ESM-1B + FST + Aug.	91.91±0.64	86.10±1.14	86.08±1.33	73.09±0.10	87.50±0.12	88.83±1.27
ESM-1B + FST + Aug. + SAP	**92.36±0.58**	**86.51±1.67**	**86.25±1.03**	**73.21±0.13**	**87.57±0.10**	**89.07±1.29**

Table 2: Performance of thermostability regression. Correlation coefficients are reported for all three datasets. 95% confidence interval are computed via the 10-fold evaluation on HP-S^{2}C2/C5 and 3 replicates on HP-S.

Methods	HP-S^{2}C2		HP-S^{2}C5		HP-S	
	Spearman	Pearson	Spearman	Pearson	Spearman	Pearson
3D GCN [63]	0.490±0.019	0.469±0.019	0.291±0.053	0.301±0.074	N.A.	N.A.
TAPE [64]	0.432±0.061	0.386±0.065	0.367±0.063	0.364±0.047	0.504±0.013	0.453±0.031
ESM-IF1 [38]	0.589±0.040	0.547±0.036	0.373±0.036	0.377±0.035	N.A.	N.A.
ESM-1B [28]	0.890±0.018	0.893±0.0238	0.712±0.043	0.804±0.023	0.807±0.001	0.809±0.001
ESM-1B + Aug.	0.895±0.014	0.909±0.010	0.714±0.034	0.811±0.034	0.808±0.002	0.809±0.001
ESM-1B + FST	0.898±0.008	0.900±0.009	0.742±0.039	0.815±0.024	0.819±0.002	0.825±0.004
ESM-1B + FST + Aug.	0.892±0.011	0.912±0.013	0.747±0.026	0.818±0.025	0.820±0.001	0.825±0.003
ESM-1B + FST + Aug. + SAP	**0.906±0.010**	**0.923±0.012**	**0.754±0.035**	**0.837±0.019**	**0.823±0.001**	**0.827±0.003**

4.2 Predicting Thermostability via Classification and Regression

Comparison to Existing Approaches. We evaluate our proposals and compare with existing approaches on HP-S^{2}C2/C5 and HP-S/SC2 for both classification and regression tasks. 3D GCN [63] and TAPE [64] are classical structure- and sequence-based models, while ESM-IF1 [38] and ESM-1B [28] emerges recently as current state-of-the-art approaches, dealing with structure and sequence inputs respectively. From results shown in Table 1 and 2, several consistent observations can be drawn: ❶ *Compared with baselines.* Our proposal, *i.e.,* ESM-1B+FST+Aug.+SAP, greatly surpasses various baseline by a margin of $\{1.17\% \sim 13.48\%$ accuracy, $2.33\% \sim 13.12\%$ precision, $0.016 \sim 0.474$ Spearman, and $0.030 \sim 0.537$ Pearson correlation$\}$ on HP-S^{2}C2, $\{2.99\% \sim 27.50\%$ accuracy, $0.042 \sim 0.463$ Spearman, and $0.033 \sim 0.536$ Pearson correlation$\}$ on HP-S^{2}C5, $\{3.71\% \sim 8.46\%$ accuracy, $0.016 \sim 0.319$ Spearman, and $0.018 \sim 0.374$ Pearson correlation$\}$ on HP-S, and $\{1.33\% \sim 11.2\%$ accuracy and $0.93\% \sim 8.43\%$ precision on HP-SC2. These generalization improvements on hold-out proteins validate the effectiveness of our methods in tackling the functional domain shift and data-scarcity issues, *i.e.,* pre-training on a general-purpose dataset UniRef50 (22M samples) and tuning on the specific-domain dataset HotProtein (182K samples). Moreover, our methods perform much stably in general, evidenced by the reduced confidence interval of multiple runs. ❷ *Structure versus sequence-based models.* On the classification task, sequence-based models like ESM-1B and TAPE show clear performance advantages in most cases. As for the regression task, ESM-1B achieves an overwhelming superiority among the four baseline approaches, while the next best model is ESM-IF1 which takes protein structures as inputs. It suggests that powerful mechanisms for utilizing 3D structure information are still missing on our challenging HotProtein dataset. We make a pioneer attempt by leveraging 3D information to enhance sequence-based models. ❸ *Does SAP, FST, and Aug helps?* We examine these three components in an incremental manner and we observe: i) the performance gains from SAP demonstrate the benefits of treating 3D protein structures as auxiliary information; ii) Both Aug. & FST strengthen the model tuning and a combination of them enjoys extra improvements; iii) Among these ingredients of our proposal, FST contributes the most to superior performance. Specifically, Aug consistently obtains improvements in terms of the average performance; FST usually leads to statistically significant improvements with respect to the 95% confidence interval, especially on the HP-S/SC2 dataset. ❹ *Small v.s. large datasets.* Feature level augmentations are more beneficial for small-scale datasets, while FST and SAP bring performance gains for both small and large datasets.

Table 3: Ablation study on proposed components. Accuracy (%) for classification and Spearman & Pearson correlation coefficients for regression are reported. 95% confidence interval are computed via the 10-fold evaluation on HP-S^{2}C5 and 3 replicates on HP-S.

Methods		HP-S^{2}C5			HP-S		
		Accuracy	Spearman	Pearson	Accuracy	Spearman	Pearson
Based on ESM-1B [28]		83.26±1.54	0.712±0.043	0.804±0.022	69.50±0.16	0.807±0.001	0.809±0.001
Feature Aug.	Random	82.97±1.46	0.708±0.043	**0.814±0.023**	69.46±0.28	0.807±0.001	**0.809±0.001**
	Mixup	83.94±1.43	**0.720±0.042**	0.810±0.027	69.27±0.27	0.805±0.001	0.806±0.003
	Worst-case	**84.32±1.41**	0.714±0.034	0.811±0.034	**69.54±0.39**	**0.808±0.002**	**0.809±0.001**
# Rank in FST	$r = 4$	**85.96±1.13**	**0.742±0.039**	**0.815±0.024**	72.75±0.17	0.818±0.001	0.821±0.002
	$r = 8$	85.00±2.16	0.703±0.032	0.801±0.017	72.97±0.28	0.819±0.002	**0.825±0.004**
	$r = 16$	83.75±1.92	0.725±0.040	0.788±0.019	**73.20±0.40**	**0.821±0.001**	**0.825±0.002**
Sparsity in FST	$|\Omega| = 16$	85.19±1.02	0.702±0.034	0.794±0.027	72.82±0.43	0.815±0.004	0.822±0.005
	$|\Omega| = 32$	85.57±1.16	0.706±0.035	0.767±0.060	72.85±0.49	0.818±0.002	0.820±0.002
	$|\Omega| = 64$	**85.96±1.13**	**0.742±0.039**	**0.815±0.024**	**72.97±0.28**	**0.819±0.002**	**0.825±0.004**
	$|\Omega| = 128$	85.79±1.08	0.729±0.042	0.807±0.029	72.75±0.49	0.818±0.004	0.822±0.006
3D infor. in SAP	w.o.	83.89±1.10	0.718±0.023	0.815±0.019	69.80±0.48	0.808±0.001	0.811±0.002
	w.	**85.58±1.42**	**0.727±0.035**	**0.817±0.022**	**71.52±2.29**	0.815±0.001	0.819±0.003

Ablation Study. A comprehensive ablation is presented in Table 3, where we inspect different feature augmentations, the rank number in FST, the sparsity in FST, and the necessity of 3D infor. in SAP, on top of the vanilla ESM-1B model. ❶ *Diverse feature augmentations.* Besides mixup and worst-case feature augmentations, a straightforward baseline ("Random") that applies a Gaussian noise from $\mathcal{N}(0, 0.1^2)$ to features, is also implemented. We see: random feature augmentation usually incurs a performance degradation; mixup benefits models tuned on the small-scale dataset (HP-S^{2}C5), while hurts on the large-scale dataset (HP-S); worst-case feature augmentations consistently improve the generalization of tuned models on both HP-S^{2}C5 and HP-S, which is adopted by default in all other experiments of Table 1, 2, and 4. ❷ *The # rank in FST.* The larger dataset prefers FST with a higher rank such as $r = 8$ or 16, compared to the smaller dataset in which FST with $r = 4$ works the best. The finding is coincided with the ones in [52, 65]. ❸ *The sparsity in FST.* FST with $|\Omega| = 64$ is a "sweet point". Superfluous tuning elements in Ω may lead to inferior results. ❹ *3D infor. in SAP.* Directly introducing a contrastive loss in Equation 1 to the pre-training, has already boosted ESM-1B's performance, implying an improved protein embedding learning. Coupling the 3D information of protein structures, obtains an additional quality bonus for the pre-training.

More ablation studies. We summarize the results of additional ablation studies here and refer readers to the Appendix D for details: ❶ We achieve the best results on extra test benchmarks and class-balanced test sets. ❷ SAP outperforms other approaches to inject structure information. ❷ Training from scratch yields worse results than pretraining. ❸ On ESM-1B, we test several other baselines. We notice that additional ℓ_2 or ℓ_1 regularization, end-to-end fine-tuning, partially frozen tuning, and other feature aggregation methods all come to worse results than our current ESM-1B.

4.3 Protein Editing Towards Improved Thermostability

Based on the models we trained in previous sections, three approaches for protein editing are proposed. We first describe the setting we use to edit protein, and then report the performance of different models for three settings, classification, regression and `Editing`. To demonstrate the effectiveness of protein editing towards improved thermostability, we further evaluate our proposals on FireProtDB[4] which is a manually curated database of the protein stability data for single-point mutants. It contains 0.2K natural protein amino acid sequences, *i.e.,* $\mathcal{P} = \{p^{(i)}\}$, $i \in \{1, \cdots, x\}$, and their 3.9K mutated sequences, *i.e.,* $\hat{\mathcal{P}} = \{\hat{p}_j^{(i)}\}$, $i \in \{1, \cdots, x\}$ and $j \in \{1, \cdots, n^{(i)}\}$, where $n^{(i)}$ is the number of mutated variants for the original protein sequence $p^{(i)}$. We take $\mathcal{P}$ as the training set and $\hat{\mathcal{P}}$ as the hold-out testing set. Detailed configurations are referred to the Appendix C.

Figure 4: Visualization of an AI design that thermostabilized a protein. The amino acid "N" was predicted by the MutCompute web server to be mutated to a "K", which was experimentally shown to improve thermostability by $8.6°C$ and was critical for the engineering of FAST-PETase[14]. ThermoPETase structure (left) (PDB: 6ij6) and the mutated one (right) was obtained via [66].

----
[4] https://loschmidt.chemi.muni.cz/fireprotdb/

Table 4: Evaluation of protein editing suggestions. Accuracy (%) and Precision (%) for classifiers , Kendall τ & Spearman ρ rank correlation coefficients for regressors , and successful rate (%) for adversarially learned mutations of protein sequences are reported. 95% confidence interval is computed via three trials.

FireProtDB		Classifier		Regressors		Learned Mutations
		Accuracy	Precision	Kendall τ	Spearman ρ	Successful Rate
Zero shot	TAPE	44.75	30.18	0.07	5.64	34.78
	ESM-1B	62.26	41.73	8.34	9.49	40.39
	Ours	66.18	43.60	13.65	19.96	43.46
Fine-tune on $\mathcal{P}$	TAPE	55.18±0.38	38.85±0.36	32.33±1.35	43.78±1.87	44.59±0.45
	ESM-1B	69.30±0.53	44.97±0.47	34.76±1.42	44.25±1.89	52.41±0.38
	Ours	**71.42**±**0.34**	**53.93**±**0.39**	**36.97**±**0.78**	**50.79**±**1.22**	**54.24**±**0.41**

Editing Suggestions via Classifiers. We deliver the protein editing suggestion via proposed classifiers. The five-class classification is performed in both fine-tuning and testing stages with $\mathcal{P}$ and $\hat{\mathcal{P}}$, respectively. Furthermore, we regard a mutation as *positive* if $\hat{p}_j^{(i)}$ is predicted to a class that has higher temperatures than the category of its original counterpart $p^{(i)}$ (*e.g.,* from *Psychrophilic* to *Mesophilic*); otherwise, we label the mutation as *negative*. Then, we compute the associated accuracy and precision to evaluate the quality of editing suggestions from our proposals.

Editing Suggestions via Regressors. We can also suggest possible editing via regressors. Specifically, we fine-tune models to regress the protein's temperature in $\mathcal{P}$, predict the possible temperature of their mutated variants in $\hat{\mathcal{P}}$, and measure the ordinal association between prediction and ground truth temperatures of $\hat{\mathcal{P}}$.

Optimizing Editing Suggestions. Instead of classifying whether the mutation increases or decreases the thermostability, we propose an efficient editing algorithm, by optimizing towards an improved thermostability: $\max_{|\mathcal{M}| \leq n} \mathcal{L}(\mathcal{F}(\mathcal{M}(\boldsymbol{x})), y_t)$, where $\boldsymbol{x}$ is the input, y_t denotes the target label of the class with a higher temperature (*e.g.,* from *Mesophilic* to *Thermophilic*), $\mathcal{M}$ stands for the mutation function whose number of mutated amino acids $|\mathcal{M}|$ is constrained by n, $\mathcal{F}$ and $\mathcal{L}$ is our classifier and the objective function. In practice, we set y_t as the highest-temperature class, *Hyperthermophilic*. We set $\mathcal{L}$ as probability change times the saliency score following PWWS [67]. More are in Sec. C.1.

Experimental Results. As demonstrated in Table 4, ❶ ESM-1B outperforms TAPE when it is zero-shot transferred to test data. Ours performs the best. We achieve 66.13% accuracy, 13.65% Kendall correlation, and 19.96% Spearman correlation, which is 3.86%, 5.31%, 10.47% relative higher than the ESM-1B baseline. ❷ After finetuning on $\mathcal{P}$, ESM-1B obtains slightly better results than TAPE on both regression and classification metrics. Our model still outperforms both in all the tested cases. ❸ When we do protein editing after fine-tuning, ours achieves the best (54.24% successful rate, 3.49% relative improvements than ESM-1B). It indicates that a better classifier also benefits protein engineering. Visualization of an edited protein is displayed in Figure 4.

5 Conclusion

Predicting thermostabilizing mutations is a primary goal of most protein engineering campaigns. However, the lack of thermally annotated protein data and effective algorithms has hindered the development of a thermostability prediction model that can generalize across protein-space. This work provides attempts to address both points via a large-scale protein dataset (`HotProtein`) with *species-specific, lower-bound thermostability annotations* and a novel algorithmic framework designed to tackle the intrinsic challenges of functional domain shifts and data scarcity in thermostability protein engineering. Extensive results validate that our dataset and algorithmic framework provide meaningful improvements over baseline models. Lastly, based on established superior predictors, we search a protein's single-point mutation landscape towards identifying thermostabilizing variants. We will keep updating `HotProtein` by collecting more sequences, improving our sequence-clustering and filtering, and folding more structures.

Related Works. Due to space limitations, we place discussions about protein engineering background, directed evolution, guided directed evolution, other protein thermostability datasets, sequence-/structure-based protein models, and sparse & low-rank subspace fine-tuning in Appendix A.

References

[1] Emanuele Paci and Martin Karplus. Unfolding proteins by external forces and temperature: the importance of topology and energetics. *Proceedings of the National Academy of Sciences*, 97(12):6521–6526, 2000.

[2] Fabrizio Pucci, Jean Marc Kwasigroch, and Marianne Rooman. Scoop: an accurate and fast predictor of protein stability curves as a function of temperature. *Bioinformatics*, 33(21):3415–3422, 2017.

[3] Huali Cao, Jingxue Wang, Liping He, Yifei Qi, and John Z Zhang. Deepddg: predicting the stability change of protein point mutations using neural networks. *Journal of chemical information and modeling*, 59(4):1508–1514, 2019.

[4] GD Haki and SK Rakshit. Developments in industrially important thermostable enzymes: a review. *Bioresource technology*, 89(1):17–34, 2003.

[5] Marieke E Bruins, Anja EM Janssen, and Remko M Boom. Thermozymes and their applications. *Applied biochemistry and biotechnology*, 90(2):155–186, 2001.

[6] Sven Frokjaer and Daniel E Otzen. Protein drug stability: a formulation challenge. *Nature reviews drug discovery*, 4(4):298–306, 2005.

[7] Swati Kapoor, Aasima Rafiq, and Savita Sharma. Protein engineering and its applications in food industry. *Critical reviews in food science and nutrition*, 57(11):2321–2329, 2017.

[8] Jie Huang, Peng Zhao, Xin Jin, Yiwen Wang, Haotian Yuan, and Xinyuan Zhu. Enzymatic biofuel cells based on protein engineering: recent advances and future prospects. *Biomaterials science*, 8(19):5230–5240, 2020.

[9] C Von der Osten, S Branner, S Hastrup, L Hedegaard, MD Rasmussen, H Bisgaard-Frantzen, S Carlsen, and JM Mikkelsen. Protein engineering of subtilisins to improve stability in detergent formulations. *Journal of biotechnology*, 28(1):55–68, 1993.

[10] Changhee Cho, So Young Choi, Zi Wei Luo, and Sang Yup Lee. Recent advances in microbial production of fuels and chemicals using tools and strategies of systems metabolic engineering. *Biotechnology advances*, 33(7):1455–1466, 2015.

[11] Amro Abd-Al-Fattah Amara. Pharmaceutical and industrial protein engineering: where we are? *Pakistan Journal of Pharmaceutical Sciences*, 26(1), 2013.

[12] Carla CCR De Carvalho. Enzymatic and whole cell catalysis: finding new strategies for old processes. *Biotechnology advances*, 29(1):75–83, 2011.

[13] Marirosa Mora and John L Telford. Genome-based approaches to vaccine development. *Journal of Molecular Medicine*, 88(2):143–147, 2010.

[14] Hongyuan Lu, Daniel J Diaz, Natalie J Czarnecki, Congzhi Zhu, Wantae Kim, Raghav Shroff, Daniel J Acosta, Bradley R Alexander, Hannah O Cole, Yan Zhang, et al. Machine learning-aided engineering of hydrolases for pet depolymerization. *Nature*, 604(7907):662–667, 2022.

[15] Miguel Alcalde, Manuel Ferrer, Francisco J Plou, and Antonio Ballesteros. Environmental biocatalysis: from remediation with enzymes to novel green processes. *TRENDS in Biotechnology*, 24(6):281–287, 2006.

[16] Fabrizio Pucci and Marianne Rooman. Stability curve prediction of homologous proteins using temperature-dependent statistical potentials. *PLoS computational biology*, 10(7):e1003689, 2014.

[17] Gang Li, Kersten S Rabe, Jens Nielsen, and Martin KM Engqvist. Machine learning applied to predicting microorganism growth temperatures and enzyme catalytic optima. *ACS synthetic biology*, 8(6):1411–1420, 2019.

[18] Fabrizio Pucci and Marianne Rooman. Physical and molecular bases of protein thermal stability and cold adaptation. *Current opinion in structural biology*, 42:117–128, 2017.

[19] Soroosh Pouyan, Milad Lagzian, and Mohammad Hossein Sangtarash. Enhancing thermostabilization of a newly discovered α-amylase from bacillus cereus gl96 by combining computer-aided directed evolution and site-directed mutagenesis. *International Journal of Biological Macromolecules*, 197:12–22, 2022.

[20] Anna Jarzab, Nils Kurzawa, Thomas Hopf, Matthias Moerch, Jana Zecha, Niels Leijten, Yangyang Bian, Eva Musiol, Melanie Maschberger, Gabriele Stoehr, et al. Meltome atlas—thermal proteome stability across the tree of life. *Nature methods*, 17(5):495–503, 2020.

[21] Vikas Verma, Alex Lamb, Christopher Beckham, Amir Najafi, Ioannis Mitliagkas, David Lopez-Paz, and Yoshua Bengio. Manifold mixup: Better representations by interpolating hidden states. In *International Conference on Machine Learning*, pages 6438–6447. PMLR, 2019.

[22] Tianlong Chen, Yu Cheng, Zhe Gan, Jianfeng Wang, Lijuan Wang, Zhangyang Wang, and Jingjing Liu. Adversarial feature augmentation and normalization for visual recognition. *arXiv preprint arXiv:2103.12171*, 2021.

[23] Tao Li, Yingwen Wu, Sizhe Chen, Kun Fang, and Xiaolin Huang. Subspace adversarial training. *arXiv preprint arXiv:2111.12229*, 2021.

[24] Tianlong Chen, Yu Cheng, Zhe Gan, Jingjing Liu, and Zhangyang Wang. Data-efficient gan training beyond (just) augmentations: A lottery ticket perspective. *Advances in Neural Information Processing Systems*, 34, 2021.

[25] Vincent GH Eijsink, Sigrid Gåseidnes, Torben V Borchert, and Bertus Van Den Burg. Directed evolution of enzyme stability. *Biomolecular engineering*, 22(1-3):21–30, 2005.

[26] Rafael Couñago, Stephen Chen, and Yousif Shamoo. In vivo molecular evolution reveals biophysical origins of organismal fitness. *Molecular cell*, 22(4):441–449, 2006.

[27] Hein J Wijma, Robert J Floor, and Dick B Janssen. Structure-and sequence-analysis inspired engineering of proteins for enhanced thermostability. *Current opinion in structural biology*, 23(4):588–594, 2013.

[28] Alexander Rives, Joshua Meier, Tom Sercu, Siddharth Goyal, Zeming Lin, Jason Liu, Demi Guo, Myle Ott, C Lawrence Zitnick, Jerry Ma, et al. Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. *Proceedings of the National Academy of Sciences*, 118(15), 2021.

[29] Mohammed AlQuraishi. Alphafold at casp13. *Bioinformatics*, 35(22):4862–4865, 2019.

[30] John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with alphafold. *Nature*, 596(7873):583–589, 2021.

[31] Tanya Barrett, Karen Clark, Robert Gevorgyan, Vyacheslav Gorelenkov, Eugene Gribov, Ilene Karsch-Mizrachi, Michael Kimelman, Kim D Pruitt, Sergei Resenchuk, Tatiana Tatusova, et al. Bioproject and biosample databases at ncbi: facilitating capture and organization of metadata. *Nucleic acids research*, 40(D1):D57–D63, 2012.

[32] Alexander Rives, Joshua Meier, Tom Sercu, Siddharth Goyal, Zeming Lin, Jason Liu, Demi Guo, Myle Ott, C. Lawrence Zitnick, Jerry Ma, and Rob Fergus. Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. *bioRxiv*, 2019.

[33] Jesse Vig, Ali Madani, Lav R Varshney, Caiming Xiong, Richard Socher, and Nazneen Fatema Rajani. Bertology meets biology: Interpreting attention in protein language models. *arXiv preprint arXiv:2006.15222*, 2020.

[34] Roshan Rao, Jason Liu, Robert Verkuil, Joshua Meier, John F. Canny, Pieter Abbeel, Tom Sercu, and Alexander Rives. Msa transformer. *bioRxiv*, 2021.

[35] Joshua Meier, Roshan Rao, Robert Verkuil, Jason Liu, Tom Sercu, and Alexander Rives. Language models enable zero-shot prediction of the effects of mutations on protein function. *bioRxiv*, 2021.

[36] Nadav Brandes, Dan Ofer, Yam Peleg, Nadav Rappoport, and Michal Linial. Proteinbert: A universal deep-learning model of protein sequence and function. *Bioinformatics*, 38(8):2102–2110, 2022.

[37] Tianyu Gao, Xingcheng Yao, and Danqi Chen. Simcse: Simple contrastive learning of sentence embeddings. *arXiv preprint arXiv:2104.08821*, 2021.

[38] Chloe Hsu, Robert Verkuil, Jason Liu, Zeming Lin, Brian Hie, Tom Sercu, Adam Lerer, and Alexander Rives. Learning inverse folding from millions of predicted structures. *bioRxiv*, 2022.

[39] David Shortle. One sequence plus one mutation equals two folds. *Proceedings of the National Academy of Sciences*, 106(50):21011–21012, 2009.

[40] Marcus Resch, Harald Striegl, Eva Maria Henssler, Madhumati Sevvana, Claudia Egerer-Sieber, Emile Schiltz, Wolfgang Hillen, and Yves A Muller. A protein functional leap: how a single mutation reverses the function of the transcription regulator tetr. *Nucleic acids research*, 36(13):4390–4401, 2008.

[41] Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *The journal of machine learning research*, 15(1):1929–1958, 2014.

[42] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 9729–9738, 2020.

[43] Milo M. Lin and Ahmed H. Zewail. Hydrophobic forces and the length limit of foldable protein domains. *Proceedings of the National Academy of Sciences*, 109:9851–9856, 2012.

[44] Xuhua Xia. Domains and functions of spike protein in sars-cov-2 in the context of vaccine design. *Viruses*, 13(1):109, 2021.

[45] Najeeb Khan and Ian Stavness. Sparseout: Controlling sparsity in deep networks. In *Canadian conference on artificial intelligence*, pages 296–307. Springer, 2019.

[46] Shai Shalev-Shwartz and Shai Ben-David. *Understanding machine learning: From theory to algorithms*. Cambridge university press, 2014.

[47] Carl Rasmussen and Zoubin Ghahramani. Occam's razor. *Advances in neural information processing systems*, 13, 2000.

[48] Wenda Zhou, Victor Veitch, Morgane Austern, Ryan P Adams, and Peter Orbanz. Non-vacuous generalization bounds at the imagenet scale: a pac-bayesian compression approach. *arXiv preprint arXiv:1804.05862*, 2018.

[49] Sanjeev Arora, Rong Ge, Behnam Neyshabur, and Yi Zhang. Stronger generalization bounds for deep nets via a compression approach. In *International Conference on Machine Learning*, pages 254–263. PMLR, 2018.

[50] Shuai Zhang, Meng Wang, Sijia Liu, Pin-Yu Chen, and Jinjun Xiong. Why lottery ticket wins? a theoretical perspective of sample complexity on sparse neural networks. *Advances in Neural Information Processing Systems*, 34, 2021.

[51] Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pages 249–256. JMLR Workshop and Conference Proceedings, 2010.

[52] Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*, 2021.

[53] Emmanuel J Candès, Xiaodong Li, Yi Ma, and John Wright. Robust principal component analysis? *Journal of the ACM (JACM)*, 58(3):1–37, 2011.

[54] Tianyi Zhou and Dacheng Tao. Greedy bilateral sketch, completion & smoothing. In *Artificial Intelligence and Statistics*, pages 650–658. PMLR, 2013.

[55] Xiyu Yu, Tongliang Liu, Xinchao Wang, and Dacheng Tao. On compressing deep models by low rank and sparse decomposition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 7370–7379, 2017.

[56] Connor Shorten and Taghi M Khoshgoftaar. A survey on image data augmentation for deep learning. *Journal of big data*, 6(1):1–48, 2019.

[57] Zhun Zhong, Liang Zheng, Guoliang Kang, Shaozi Li, and Yi Yang. Random erasing data augmentation. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pages 13001–13008, 2020.

[58] Sangdoo Yun, Dongyoon Han, Seong Joon Oh, Sanghyuk Chun, Junsuk Choe, and Youngjoon Yoo. Cutmix: Regularization strategy to train strong classifiers with localizable features. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 6023–6032, 2019.

[59] Oleksandr Kolomiyets, Steven Bethard, and Marie-Francine Moens. Model-portability experiments for textual temporal analysis. In *Proceedings of the 49th annual meeting of the association for computational linguistics: human language technologies*, volume 2, pages 271–276. ACL; East Stroudsburg, PA, 2011.

[60] Xiang Zhang, Junbo Zhao, and Yann LeCun. Character-level convolutional networks for text classification. *Advances in neural information processing systems*, 28, 2015.

[61] William Yang Wang and Diyi Yang. That's so annoying!!!: A lexical and frame-semantic embedding based data augmentation approach to automatic categorization of annoying behaviors using# petpeeve tweets. In *Proceedings of the 2015 conference on empirical methods in natural language processing*, pages 2557–2563, 2015.

[62] Jason Wei and Kai Zou. Eda: Easy data augmentation techniques for boosting performance on text classification tasks. *arXiv preprint arXiv:1901.11196*, 2019.

[63] Vladimir Gligorijević, P Douglas Renfrew, Tomasz Kosciolek, Julia Koehler Leman, Daniel Berenberg, Tommi Vatanen, Chris Chandler, Bryn C Taylor, Ian M Fisk, Hera Vlamakis, et al. Structure-based protein function prediction using graph convolutional networks. *Nature communications*, 12(1):1–14, 2021.

[64] Roshan Rao, Nicholas Bhattacharya, Neil Thomas, Yan Duan, Peter Chen, John Canny, Pieter Abbeel, and Yun Song. Evaluating protein transfer learning with tape. *Advances in neural information processing systems*, 32, 2019.

[65] Xuxi Chen, Tianlong Chen, Yu Cheng, Weizhu Chen, Zhangyang Wang, and Ahmed Hassan Awadallah. Dsee: Dually sparsity-embedded efficient tuning of pre-trained language models, 2021.

[66] Andrew Waterhouse, Martino Bertoni, Stefan Bienert, Gabriel Studer, Gerardo Tauriello, Rafal Gumienny, Florian T Heer, Tjaart A P de Beer, Christine Rempfer, Lorenza Bordoli, et al. Swiss-model: homology modelling of protein structures and complexes. *Nucleic acids research*, 46(W1):W296–W303, 2018.

[67] Shuhuai Ren, Yihe Deng, Kun He, and Wanxiang Che. Generating natural language adversarial examples through probability weighted word saliency. In *Proceedings of the 57th annual meeting of the association for computational linguistics*, pages 1085–1097, 2019.

[68] Brian Kuhlman, Gautam Dantas, Gregory C Ireton, Gabriele Varani, Barry L Stoddard, and David Baker. Design of a novel globular protein fold with atomic-level accuracy. *science*, 302(5649):1364–1368, 2003.

[69] Po-Ssu Huang, Scott E Boyken, and David Baker. The coming of age of de novo protein design. *Nature*, 537(7620):320–327, 2016.

[70] Brian Kuhlman and Philip Bradley. Advances in protein structure prediction and design. *Nature Reviews Molecular Cell Biology*, 20(11):681–697, 2019.

[71] Vladimir Gligorijevic, Daniel Berenberg, Stephen Ra, Andrew Watkins, Simon Kelow, Kyunghyun Cho, and Richard Bonneau. Function-guided protein design by deep manifold sampling. *bioRxiv*, 2021.

[72] Richard W Shuai, Jeffrey A Ruffolo, and Jeffrey J Gray. Generative language modeling for antibody design. *bioRxiv*, 2021.

[73] Alex Hawkins-Hooker, David T Jones, and Brooks Paige. Msa-conditioned generative protein language models for fitness landscape modelling and design. In *Machine Learning for Structural Biology Workshop, NeurIPS*, 2021.

[74] Samuel C Hoffman, Vijil Chenthamarakshan, Kahini Wadhawan, Pin-Yu Chen, and Payel Das. Optimizing molecules using efficient queries from property evaluations. *Nature Machine Intelligence*, 4(1):21–31, 2022.

[75] Christoffer Norn, Basile IM Wicky, David Juergens, Sirui Liu, David Kim, Doug Tischer, Brian Koepnick, Ivan Anishchenko, Foldit Players, David Baker, et al. Protein sequence design by conformational landscape optimization. *Proceedings of the National Academy of Sciences*, 118(11):e2017228118, 2021.

[76] Sheng Wang, Siqi Sun, Zhen Li, Renyu Zhang, and Jinbo Xu. Accurate de novo prediction of protein contact map by ultra-deep learning model. *PLoS computational biology*, 13(1):e1005324, 2017.

[77] Kevin Karplus. Sam-t08, hmm-based protein structure prediction. *Nucleic acids research*, 37(suppl_2):W492–W497, 2009.

[78] David T Jones and Shaun M Kandathil. High precision in protein contact prediction using fully convolutional neural networks and minimal sequence features. *Bioinformatics*, 34(19):3308–3315, 2018.

[79] Diego del Alamo, Davide Sala, Hassane Mchaourab, and Jens Meiler. Sampling the conformational landscapes of transporters and receptors with alphafold2. *bioRxiv*, 2021.

[80] Raghav Shroff, Austin W Cole, Daniel J Diaz, Barrett R Morrow, Isaac Donnell, Ankur Annapareddy, Jimmy Gollihar, Andrew D Ellington, and Ross Thyer. Discovery of novel gain-of-function mutations guided by structure-based deep learning. *ACS synthetic biology*, 9(11):2927–2935, 2020.

[81] Inyup Paik, Phuoc HT Ngo, Raghav Shroff, Daniel J Diaz, Andre C Maranhao, David JF Walker, Sanchita Bhadra, and Andrew D Ellington. Improved bst dna polymerase variants derived via a machine learning approach. *Biochemistry*, 2021.

[82] Stefano Panno, Slavica Matić, Antonio Tiberini, Andrea Giovanni Caruso, Patrizia Bella, Livio Torta, Raffaele Stassi, and Salvatore Davino. Loop mediated isothermal amplification: principles and applications in plant virology. *Plants*, 9(4):461, 2020.

[83] Frances H Arnold. Directed evolution: bringing new chemistry to life. *Angewandte Chemie International Edition*, 57(16):4143–4148, 2018.

[84] Kevin K Yang, Zachary Wu, and Frances H Arnold. Machine-learning-guided directed evolution for protein engineering. *Nature methods*, 16(8):687–694, 2019.

[85] Bruce J Wittmann, Yisong Yue, and Frances H Arnold. Informed training set design enables efficient machine learning-assisted directed protein evolution. *Cell systems*, 12(11):1026–1045, 2021.

[86] Thaiesha A Wright, Jamie M Stewart, Richard C Page, and Dominik Konkolewicz. Extraction of thermodynamic parameters of protein unfolding using parallelized differential scanning fluorimetry. *The journal of physical chemistry letters*, pages 553–558, 2017.

[87] Chi-Wei Chen, Jerome Lin, and Yen-Wei Chu. istable: off-the-shelf predictor integration for predicting protein stability changes. In *BMC bioinformatics*, volume 14, pages 1–14. BioMed Central, 2013.

[88] Emidio Capriotti, Piero Fariselli, and Rita Casadio. I-mutant2. 0: predicting stability changes upon mutation from the protein sequence or structure. *Nucleic acids research*, 33(suppl_2):W306–W310, 2005.

[89] Carlos HM Rodrigues, Douglas EV Pires, and David B Ascher. Dynamut: predicting the impact of mutations on protein conformation, flexibility and stability. *Nucleic acids research*, 46(W1):W350–W355, 2018.

[90] Douglas EV Pires, David B Ascher, and Tom L Blundell. Duet: a server for predicting effects of mutations on protein stability using an integrated computational approach. *Nucleic acids research*, 42(W1):W314–W319, 2014.

[91] Vijaya Parthiban, M Michael Gromiha, and Dietmar Schomburg. Cupsat: prediction of protein stability upon point mutations. *Nucleic acids research*, 34(suppl_2):W239–W242, 2006.

[92] Elizabeth H Kellogg, Andrew Leaver-Fay, and David Baker. Role of conformational sampling in computing mutation-induced changes in protein structure and stability. *Proteins: Structure, Function, and Bioinformatics*, 79(3):830–838, 2011.

[93] Douglas EV Pires, David B Ascher, and Tom L Blundell. mcsm: predicting the effects of mutations in proteins using graph-based signatures. *Bioinformatics*, 30(3):335–342, 2014.

[94] Manuel Giollo, Alberto JM Martin, Ian Walsh, Carlo Ferrari, and Silvio CE Tosatto. Neemo: a method using residue interaction networks to improve prediction of protein stability upon mutation. *BMC genomics*, 15(4):1–11, 2014.

[95] Hahnbeom Park, Philip Bradley, Per Greisen Jr, Yuan Liu, Vikram Khipple Mulligan, David E Kim, David Baker, and Frank DiMaio. Simultaneous optimization of biomolecular energy functions on features from small molecules and macromolecules. *Journal of chemical theory and computation*, 12(12):6201–6212, 2016.

[96] Joost Schymkowitz, Jesper Borg, Francois Stricher, Robby Nys, Frederic Rousseau, and Luis Serrano. The foldx web server: an online force field. *Nucleic acids research*, 33(suppl_2):W382–W388, 2005.

[97] Yves Dehouck, Aline Grosfils, Benjamin Folch, Dimitri Gilis, Philippe Bogaerts, and Marianne Rooman. Fast and accurate predictions of protein stability changes upon mutations using statistical potentials and neural networks: Popmusic-2.0. *Bioinformatics*, 25(19):2537–2543, 2009.

[98] Emmi Jokinen, Markus Heinonen, and Harri Lähdesmäki. mgpfusion: predicting protein stability changes with gaussian process kernel learning and data fusion. *Bioinformatics*, 34(13):i274–i283, 2018.

[99] Catherine L Worth, Robert Preissner, and Tom L Blundell. Sdm—a server for predicting effects of mutations on protein stability and malfunction. *Nucleic acids research*, 39(suppl_2):W215–W222, 2011.

[100] Bian Li, Yucheng T Yang, John A Capra, and Mark B Gerstein. Predicting changes in protein thermodynamic stability upon point mutation with deep 3d convolutional neural networks. *PLoS computational biology*, 16(11):e1008291, 2020.

[101] Emmanuel Paradis and Klaus Schliep. ape 5.0: an environment for modern phylogenetics and evolutionary analyses in r. *Bioinformatics*, 35(3):526–528, 2019.

[102] Felix Krueger and Simon R Andrews. Bismark: a flexible aligner and methylation caller for bisulfite-seq applications. *bioinformatics*, 27(11):1571–1572, 2011.

[103] Ramin Dehghanpoor, Evan Ricks, Katie Hursh, Sarah Gunderson, Roshanak Farhoodi, Nurit Haspel, Brian Hutchinson, and Filip Jagodzinski. Predicting the effect of single and multiple mutations on protein structural stability. *Molecules*, 23(2):251, 2018.

[104] Lei Jia, Ramya Yarlagadda, and Charles C Reed. Structure based thermostability prediction models for protein single point mutations with machine learning tools. *PloS one*, 10(9):e0138022, 2015.

[105] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

[106] Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.

[107] Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Russ R Salakhutdinov, and Quoc V Le. Xlnet: Generalized autoregressive pretraining for language understanding. *Advances in neural information processing systems*, 32, 2019.

[108] Ahmed Elnaggar, Michael Heinzinger, Christian Dallago, Ghalia Rihawi, Yu Wang, Llion Jones, Tom Gibbs, Tamas Feher, Christoph Angerer, Martin Steinegger, et al. Prottrans: towards cracking the language of life's code through self-supervised deep learning and high performance computing. *arXiv preprint arXiv:2007.06225*, 2020.

[109] Adam Riesselman, Jung-Eun Shin, Aaron Kollasch, Conor McMahon, Elana Simon, Chris Sander, Aashish Manglik, Andrew Kruse, and Debora Marks. Accelerating protein design using autoregressive generative models. *BioRxiv*, page 757252, 2019.

[110] Dhananjay Kimothi, Akshay Soni, Pravesh Biyani, and James M Hogan. Distributed representations for biological sequence analysis. *arXiv preprint arXiv:1608.05949*, 2016.

[111] Amy X Lu, Haoran Zhang, Marzyeh Ghassemi, and Alan Moses. Self-supervised contrastive learning of protein representations by mutual information maximization. *BioRxiv*, 2020.

[112] Tristan Bepler and Bonnie Berger. Learning protein sequence embeddings using information from structure. *arXiv preprint arXiv:1902.08661*, 2019.

[113] Ethan C Alley, Grigory Khimulya, Surojit Biswas, Mohammed AlQuraishi, and George M Church. Unified rational protein engineering with sequence-based deep representation learning. *Nature methods*, 16(12):1315–1322, 2019.

[114] Baris E Suzek, Yuqi Wang, Hongzhan Huang, Peter B McGarvey, Cathy H Wu, and UniProt Consortium. Uniref clusters: a comprehensive and scalable alternative for improving sequence similarity searches. *Bioinformatics*, 31(6):926–932, 2015.

[115] Martin Steinegger and Johannes Söding. Clustering huge protein sequence sets in linear time. *Nature communications*, 9(1):1–8, 2018.

[116] Sara El-Gebali, Jaina Mistry, Alex Bateman, Sean R Eddy, Aurélien Luciani, Simon C Potter, Matloob Qureshi, Lorna J Richardson, Gustavo A Salazar, Alfredo Smart, et al. The pfam protein families database in 2019. *Nucleic acids research*, 47(D1):D427–D432, 2019.

[117] Brian L Hie, Duo Xu, Varun R Shanker, Theodora UJ Bruun, Payton A Weidenbacher, Shaogeng Tang, and Peter S Kim. Efficient evolution of human antibodies from general protein language models and sequence information alone. *bioRxiv*, 2022.

[118] Sylvestre-Alvise Rebuffi, Hakan Bilen, and Andrea Vedaldi. Learning multiple visual domains with residual adapters. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pages 506–516, 2017.

[119] Neil Houlsby, Andrei Giurgiu, Stanislaw Jastrzebski, Bruna Morrone, Quentin De Laroussilhe, Andrea Gesmundo, Mona Attariyan, and Sylvain Gelly. Parameter-efficient transfer learning for nlp. In *International Conference on Machine Learning*, pages 2790–2799. PMLR, 2019.

[120] Xiang Lisa Li and Percy Liang. Prefix-tuning: Optimizing continuous prompts for generation. *arXiv preprint arXiv:2101.00190*, 2021.

[121] Brian Lester, Rami Al-Rfou, and Noah Constant. The power of scale for parameter-efficient prompt tuning. *arXiv preprint arXiv:2104.08691*, 2021.

[122] Demi Guo, Alexander M Rush, and Yoon Kim. Parameter-efficient transfer learning with diff pruning. *arXiv preprint arXiv:2012.07463*, 2020.

[123] Song Han, Huizi Mao, and William J Dally. Deep compression: Compressing deep neural networks with pruning, trained quantization and huffman coding. *arXiv preprint arXiv:1510.00149*, 2015.

[124] Beidi Chen, Tri Dao, Kaizhao Liang, Jiaming Yang, Zhao Song, Atri Rudra, and Christopher Re. Pixelated butterfly: Simple and efficient sparse training for neural network models. *arXiv preprint arXiv:2112.00029*, 2021.

[125] Junxian He, Chunting Zhou, Xuezhe Ma, Taylor Berg-Kirkpatrick, and Graham Neubig. Towards a unified view of parameter-efficient transfer learning. *arXiv preprint arXiv:2110.04366*, 2021.

[126] Chunyuan Li, Heerad Farkhoor, Rosanne Liu, and Jason Yosinski. Measuring the intrinsic dimension of objective landscapes. *arXiv preprint arXiv:1804.08838*, 2018.

[127] Samet Oymak, Zalan Fabian, Mingchen Li, and Mahdi Soltanolkotabi. Generalization guarantees for neural networks via harnessing the low-rank structure of the jacobian. *arXiv preprint arXiv:1906.05392*, 2019.

[128] Guy Gur-Ari, Daniel A Roberts, and Ethan Dyer. Gradient descent happens in a tiny subspace. *arXiv preprint arXiv:1812.04754*, 2018.

[129] Ziheng Wang, Jeremy Wohlwend, and Tao Lei. Structured pruning of large language models. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 6151–6162, 2020.

[130] Beidi Chen, Tri Dao, Eric Winsor, Zhao Song, Atri Rudra, and Christopher Ré. Scatterbrain: Unifying sparse and low-rank attention approximation. *arXiv preprint arXiv:2110.15343*, 2021.

[131] Jianlin Su, Jiarun Cao, Weijie Liu, and Yangyiwen Ou. Whitening sentence representations for better semantics and faster retrieval. *arXiv preprint arXiv:2103.15316*, 2021.

[132] Leslie N Smith and Nicholay Topin. Super-convergence: Very fast training of neural networks using large learning rates. In *Artificial intelligence and machine learning for multi-domain operations applications*, volume 11006, page 1100612. International Society for Optics and Photonics, 2019.

[133] Ilya Loshchilov and Frank Hutter. Fixing weight decay regularization in adam. 2018.

[134] Carol A Rohl, Charlie EM Strauss, Kira MS Misura, and David Baker. Protein structure prediction using rosetta. In *Methods in enzymology*, volume 383, pages 66–93. Elsevier, 2004.

[135] Brandon Frenz, Steven M Lewis, Indigo King, Frank DiMaio, Hahnbeom Park, and Yifan Song. Prediction of protein mutational free energy: benchmark and sampling improvements increase classification accuracy. *Frontiers in bioengineering and biotechnology*, page 1175, 2020.

[136] Rahul Nikam, A Kulandaisamy, K Harini, Divya Sharma, and M Michael Gromiha. Prothermdb: thermodynamic database for proteins and mutants revisited after 15 years. *Nucleic Acids Research*, 49(D1):D420–D424, 2021.

[137] Jan Stourac, Juraj Dubrava, Milos Musil, Jana Horackova, Jiri Damborsky, Stanislav Mazurenko, and David Bednar. Fireprotdb: database of manually curated protein stability data. *Nucleic acids research*, 49(D1):D319–D324, 2021.

[138] Julia Koehler Leman, Brian D Weitzner, Steven M Lewis, Jared Adolf-Bryfogle, Nawsad Alam, Rebecca F Alford, Melanie Aprahamian, David Baker, Kyle A Barlow, Patrick Barth, et al. Macromolecular modeling and design in rosetta: recent methods and frameworks. *Nature methods*, 17(7):665–680, 2020.