Utilizing Optimal Local Updates to Resolve the Imbalance Dilemma in Collaborative Learning

Abstract

Collaborative learning (CL) is a framework to jointly learn a model without directly data sharing. As for the training in such a distributed scenario, participants rather than the centre server perform most of the computation. After multiple local updates of stochastic gradient descent (SGD), the centre server aggregates the gradients to update the model. However, the non-iid distributed training data poses a dilemma for global model convergence and individual contribution evaluation. To address above challenges, we open up a new path from Gradient Signal to Noise Ratio (GSNR) perspective. Specifically, we first theoretically prove the maximal GSNR depends on the optimal number of local updates. Subsequently, in conjunction with existing methods of altering gradient calculation, we propose an algorithm (i.e., GSNR+) to determine the optimal number of local updates for each individual, thereby accelerating the global convergence rate. Moreover, our proposed GSNR+ is compatible with most existing CL methods. In addition, according to the positive correlation between GSNR and the quality of shared information, we derive a function to evaluate the contribution of different individuals (i.e., local datasets). Through extensive experimental evaluation, it has been demonstrated that GSNR+ algorithms outperform multiple SOTA algorithms and GSNR is a reasonable metric for local contribution.

1 Introduction

Collaborative learning (CL), also known as federated learning (FL) McMahan et al. (2017); Li et al. (2020a) or distributed learning (DL) Mangasarian (1995), focuses on a practical scenario with multiple participants to collaboratively train a model without directly data sharing. Current CL algorithms send most of computation to each participant, and a centre server aggregates the corresponding gradients to perform model updates. Different from the typical centralized optimization problem, CL decomposes the optimization problem into several sub-optimization problems, and distributes them to different participants to solve them separately with their own dataset. Moreover, these local datasets often follow non-iid distributions in reality. During the training phase, each participant solves the sub-problem via stochastic gradient decent (SGD) , and sends back the corresponding results for aggregation. One of the most popular CL algorithms is FedAvg McMahan et al. (2017), and it typically accelerates model training through multiple local updates. Although it has shown great performance in many practical applications, there're still mysteries in this area, especially in non-iid cases, and many previous literatures Haddadpour & Mahdavi (2019); Khaled et al. (2020); Li et al. (2020c) make efforts to analyze the convergency or even to accelerate it.

In such an active area, one of the key challenges is the non-iid distributed information. On one hand, such imbalance breaks the unbiased optimization procedure when we utilize multiple local steps. While on the other hand, unbalanced information distribution makes it difficult to evaluate the contribution of different participants. The former slows down the CL-based model convergence, i.e., a key factor of the efficiency. The latter is associated with contribution evaluation involving malicious data tampering detection, contribution-based profit distribution, incentive mechanism design, etc. Especially in the current data-driven age Sim et al. (2020), contribution evaluation is particularly important. In addition to separately pursuing the two goals of accelerating model convergence efficiency and improving contribution evaluation accuracy, these two goals even conflict with each

other. For example, most of previous literature Karimireddy et al. (2020); Acar et al. (2021) focus on the efficiency of CL problems, they craft a drift estimation for client variance reduction or utilize regularization terms to improve the consistency. However, an elaborated gradient estimation entangles the information from different participants, and thus it makes the evaluation process more difficult.

To solve the above challenges, we innovatively open up new solutions from the perspective of Gradient Signal to Noise Ratio (GSNR). As illustrated in Fig. 1, imbalanced information distribution forces the local updates from a specific participant to be decomposed into two components: the signal component and the noise component. More specifically, the signal component is parallel to the global gradient, while the noise component is orthogonal to it[1]. According to the understanding of the GSNR perspective, we propose GSNR+ algorithms to maximize GSNR with the optimal number of local updates based on natural gradients[2]. While being compatible with GSNR+ algorithms to accelerate model convergence, we also propose a method to calculate GNSR, achieving the goal of contribution evaluation.

Regarding GSNR in CL, intuitively, two cases are included. Regarding an informative participant (i.e., large GSNR), the corresponding model requires more local updates to learn complex knowledge. Conversely, with regard to a participant with poor information (i.e., small GSNR), the model tends to converge, and too many local updates can lead to overconfident Yang et al. (2021). Therefore, for multiple participants with different GSNR involved in CL, the participants should individually decide the number of local updates according to their own GNSR personality, thereby speeding up the global convergence efficiency.

Figure 1: The Overview of Gradient Signal to Noise Ratio (GSNR): a local step can be decomposed into two component: signal and noise, the former parallels to the optimal update with global data, and the latter orthogonal to it.

In addition to personalizing the number of local updates to optimize model convergence efficiency, the newly proposed GSNR strategy is orthogonal to existing methods, which mostly depends on modifying gradients calculating. Hence, GSNR+ algorithms can be combined with these methods so as to further improve them.

In summary, our contributions in this paper are as follows:

- We theoretically demonstrate GSNR depends on the number of local updates, and the optimal local steps causes the largest GSNR, which leads to fast and stable convergence.
- We analyse existing CL algorithms with a new framework. Moreover, based on such framework, we propose an algorithm GSNR+, which can be combined with most of current CL algorithms to calculate its optimal local updates.
- We derive a function $r(\boldsymbol{w})$ to calculate GSNR, which evaluates the contribution of different participants with the parameters $\boldsymbol{w}$ directly from local datasets.
- We confirm our theoretical results on CIFAR-10 and CIFAR-100 datasets, experiments indicate that GSNR+ algorithms can achieve faster convergence and better test accuracy, especially the information unevenly distributed among all participants, and the distribution of $r(\boldsymbol{w})$ can evaluate the quality of different datasets.

Related Work. There has been a lot of literature devoted to improving CL, including performance Karimireddy et al. (2020); Li et al. (2020c); Wang et al. (2020a); Reddi et al. (2021) robustness Mohri et al. (2019); Fang et al. (2020); Li et al. (2021), and data privacy Melis et al. (2019); Zhu et al. (2019); Bagdasaryan et al. (2018). Regarding GSNR, Rainforth et al. (2018); Liu et al. (2020) try to analyse the generalization and variational bounds with such a concept. In this work, we focus on the relationship between GSNR and the optimal local updates in CL scenarios.

---

[1] Previous investigations Karimireddy et al. (2020); Acar et al. (2021) try to control the gradient variance across different participants, but they actually maximize GSNR by restricting the noise component.

[2] The natural gradients refer to gradients that depend only on the associated local dataset.

To control the noise component (client drift), Karimireddy et al. (2020) proposes a specific gradient computing method based on variance reduction. Li et al. (2020b) indicates that under non-iid CL conditions, a large number of local steps lead to divergence or instability. While Wang et al. (2020b) tries to stabilize the training procedure with a new average strategy. On the other hand, Wang et al. (2019) proposes a practical optimization problem with resources constraint, and it determines the number of local steps for each participant according to the resource constraints.

A similar work Khaled et al. (2020) derives an upper bound of local steps by total iterations T and the number of participants M, which proposes a theoretical analysis of local updates. But, they treat each participant equally, and fail to propose a method to calculate the optimal steps directly from the heterogeneous data. More discussion of related work can be found in Appendix A.

2 PRELIMINARY

2.1 FEDERATED AVERAGING (FEDAVG)

In this work, we consider the following collaborative optimization problem:

$$\min_{\boldsymbol{w}} \overline{F(\boldsymbol{w})} := \mathbb{E}_{\boldsymbol{\xi}}[F(\boldsymbol{w}, \boldsymbol{\xi})] = \mathbb{E}_C[\mathbb{E}_{\boldsymbol{\xi}}[F(\boldsymbol{w}, \boldsymbol{\xi})] \mid C] = \sum_{k=1}^{K} P(C = C_k) \cdot \mathbb{E}_{\boldsymbol{\xi}}[F(\boldsymbol{w}, \boldsymbol{\xi}|C_k)], \quad (1)$$

where $F(\boldsymbol{w}, \ \cdot \ )$ is a specified loss function with model $\boldsymbol{w}$, K is the number of participants, and $P(C)$ is a discrete probability distribution of choosing different dataset. Usually, $P(C)$ is a uniform distribution or proportional to local data quantity, and $\boldsymbol{\xi}|C_k$ is a random sample drawn from the dataset of k-th participant, i.e., $\boldsymbol{\xi}|C_k \sim p(\boldsymbol{x}|C_k)$.

Regarding traditional machine learning, the global dataset is gathered from all participants, and the goal is to minimize

$$F(\boldsymbol{w}) = \mathbb{E}_{\boldsymbol{\xi}}[F(\boldsymbol{w}, \boldsymbol{\xi})], \quad (2)$$

where $\boldsymbol{\xi}$ is a random sample of global dataset, i.e., the gathered data. However, in most cases, due to the privacy requests, we can't gather data from different participants. Thus, we separate the target function as Eq. (1), and send the initial model $\boldsymbol{w}_1$ to each participant, then they do the optimization locally, and send back the corresponding results. We finally obtain the results by Eq. (1).

If each participant does only one step optimization, according to the property of conditional expectation, minimizing Eq. (1) is equivalent to minimizing Eq. (2). But this procedure puts a lot of pressure on communication, so researchers propose to do more local steps for efficiency. Hence, for the k-th participant, the optimization procedure of a typical round can be viewed as

$$\boldsymbol{w}_{i+1}^k \leftarrow \boldsymbol{w}_i^k - \eta \mathbb{E}_{\boldsymbol{\xi}|C_k}[\nabla_{\boldsymbol{w}} F(\boldsymbol{w}_i^k, \boldsymbol{\xi}|C_k)], \ i = 1, \cdots, n.$$

Then the centre server aggregates local models $\boldsymbol{w}_{n+1}^1, \cdots, \boldsymbol{w}_{n+1}^K$ to update the global model by

$$\overline{\boldsymbol{w}} = \sum_{k=1}^{K} p_k \boldsymbol{w}_{n+1}^k, \quad (3)$$

where we denote p_k for $P(C = C_k)$ for convenience.

2.2 WASSERSTEIN DISTANCE

Wasserstein distance (Villani (2009)) is a metric in probabilistic space inspired by the problem of optimal transport. It is a distance between probability distributions that takes geometric information into account. The general wasserstein distance is defined as

$$\boldsymbol{W}_p(\boldsymbol{\mu}, \boldsymbol{\nu}) = \inf_{\boldsymbol{\gamma} \in \boldsymbol{\Gamma}(\boldsymbol{\mu}, \boldsymbol{\nu})} \mathbb{E}_{(\boldsymbol{x}, \boldsymbol{y}) \sim \boldsymbol{\gamma}}[\|\boldsymbol{x} - \boldsymbol{y}\|_p],$$

which is difficult to find a closed form solution. However, if we chose 2-norm as the geometric measure and simplify the problem to Gaussian distribution, the distance has an analytic solution

$$d^2 = \|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|_2^2 + tr((\boldsymbol{\Sigma}_1^{\frac{1}{2}} - \boldsymbol{\Sigma}_2^{\frac{1}{2}})^2), \quad (4)$$

where we define $d := \boldsymbol{W}_2(\mathcal{N}(\boldsymbol{\mu}_1, \boldsymbol{\Sigma}_1), \mathcal{N}(\boldsymbol{\mu}_2, \boldsymbol{\Sigma}_2))$.

3 MAXIMIZE GSNR WITH OPTIMAL LOCAL UPDATES

In this section, we investigate the relationship between local updates and GSNR, then propose a method to calculate the optimal number of local steps. As Sec. 4 will introduce, GSNR can be calculated by the ratio between the norm of global gradient, which is a constant for all participants, and the distance between global and local gradients. Therefore, to maximize GSNR is equivalent to minimize the distance between global and local gradients. Furthermore, the minimal distance, i.e., the largest GSNR, depends on the optimal local updates.

On the other hand, as mentioned in Section 2.1, our main target is to gather data so as to optimize Eq. (2) centralizedly. But in practice, due to some real restrictions, we can only optimize Eq. (1) distributedly. Thus, we treat the former procedure as an optimal optimization procedure. Based upon this idea, for accelerating convergence, our practical optimization problem also requires to minimize the distance between practical and optimal optimization path, which is determined by the corresponding gradients.

The distance between practical and optimal path can be formalized as

$$D = \boldsymbol{W}_2(p_{\overline{\boldsymbol{w}}}(\boldsymbol{w}), p_{\boldsymbol{w}_g}(\boldsymbol{w})), \tag{5}$$

where $\boldsymbol{w}_g$ is the optimal optimization path based on the global data distribution, i.e., the distribution of data gathered from all participants, while $\overline{\boldsymbol{w}}$ is the corresponding practical path defined by Eq. (3). According to Eq. (3), due to the conditional independence of the data from different participants, the random vector $\overline{\boldsymbol{w}}$ is a convex combination of a set of independent random vectors, hence the distribution $p_{\overline{\boldsymbol{w}}}(\boldsymbol{w})$ is identified by convolution of corresponding distribution functions, and such a distribution contains all details of each participant. Intuitively, if a specific participant attempts to minimize Eq. (5), it has to gather all information from others, which violates the privacy requests. Then we need to derive an upper bound of Eq. (5) as

$$D = \boldsymbol{W}_2(p_{\overline{\boldsymbol{w}}}(\boldsymbol{w}), p_{\boldsymbol{w}_g}(\boldsymbol{w})) = \inf_{\boldsymbol{\gamma} \in \boldsymbol{\Gamma}(p_{\overline{\boldsymbol{w}}}, p_{\boldsymbol{w}_g})} \mathbb{E}_{(\boldsymbol{x}, \boldsymbol{y}) \sim \boldsymbol{\gamma}}[\|\boldsymbol{x} - \boldsymbol{y}\|_2]$$

$$\leq \sum_{k=1}^{K} p_k \inf_{\boldsymbol{\gamma_k} \in \boldsymbol{\Gamma}(p_{\boldsymbol{w}_{n+1}^k}, p_{\boldsymbol{w}_g})} \mathbb{E}_{(\boldsymbol{x}, \boldsymbol{y}) \sim \boldsymbol{\gamma_k}}[\|\boldsymbol{x} - \boldsymbol{y}\|_2], \tag{6}$$

where we split $\|\boldsymbol{x} - \boldsymbol{y}\|_2$ as $\|\sum_{k=1}^{K} p_k(\boldsymbol{x}_k - \boldsymbol{y})\|_2$, and each pair $(\boldsymbol{x}_k, \boldsymbol{y})$ is supported on $\boldsymbol{\Gamma}(p_{\boldsymbol{w}_{n+1}^k}, p_{\boldsymbol{w}_g})$. Then the inequality depends on triangle inequality and the fact $\boldsymbol{w}_{n+1}^k$ is mutual independent. The upper bound is obvious, since by optimal transport, comprehensively considering all mounds is better than the sum of separate consideration.

By upper bound (6), the distance between practical and optimal optimization path is upper bounded. In other words, while minimizing upper bound (6), the target distance (5) is also approximately minimized. Specifically, the target gap vanishes as the upper bound approaches to 0. Regarding Eq. (6), it is the sum of the distance between each independent local distribution $p_{\boldsymbol{w}_{n+1}^k}$ and the global distribution $p_{\boldsymbol{w}_g}$, then due to the rotating symmetry, we can minimize upper bound (6) separately for each participant. Hence, without loss of generality, we only consider a specific participant in collaborative learning in the rest of this paper.

Based on former analysis, for maximizing GSNR, each participant needs to greedily optimize its local gradient distribution to minimize the distance $\boldsymbol{W}_2(p_{\boldsymbol{w}_{n+1}^k}(\boldsymbol{w}), p_{\boldsymbol{w}_g}(\boldsymbol{w}))$. As the initial values, i.e., $\boldsymbol{w}_1^k$, for all participants are identical, the main target is to estimate the gradient distribution of different participants. Then we make following assumption.

Assumption 3.1. (Bounded variance) The variance of stochastic gradients are uniformly bounded, i.e., $\mathbb{E}_{\boldsymbol{\xi}|C_i} \|\nabla_{\boldsymbol{w}} F(\boldsymbol{w}, \boldsymbol{\xi}|C_i) - \boldsymbol{\mu}_i\|^2 \leq \sigma^2$, $\forall i, \boldsymbol{w}$, where $\boldsymbol{\mu}_i := \mathbb{E}_{\boldsymbol{\xi}|C_i}[\nabla_{\boldsymbol{w}} F(\boldsymbol{w}, \boldsymbol{\xi}|C_i)]$.

Under such an assumption, the mini-batch stochastic gradient descent converges to joint normal distribution. The detailed proofs can be found in Appendix B.

Lemma 3.2. *With Assumption 3.1, let $\boldsymbol{\xi}_{i,b}|C_k$ be a sample from k-th local dataset uniformly at random, $\boldsymbol{g} = (\boldsymbol{g}_1, \boldsymbol{g}_2, \cdots, \boldsymbol{g}_n)$ be a finite dimensional gradient vector, where $\boldsymbol{g}_i = \frac{1}{B} \sum_{b=1}^{B} \nabla_{\boldsymbol{w}} F(\boldsymbol{w}_i, \boldsymbol{\xi}_{i,b}|C_k)$, $i \in \{1, \cdots, n\}$, then $\sqrt{B}(\boldsymbol{g} - \mathbb{E}[\boldsymbol{g}])$ converges to normal distribution.*

Lemma 3.2 implies that, with mini-batch stochastic gradient descent, the sum of local updates converges to a Gaussian distribution, i.e., $\bar{\boldsymbol{g}} = \boldsymbol{w}_{n+1} - \boldsymbol{w}_1 = \sum_{i=1}^n \boldsymbol{g}_i = \mathbb{1}^T \boldsymbol{g}$, where $\bar{\boldsymbol{g}}$ is a linear transformation of a joint Gaussian vector, thus it approximately conforms to Gaussian distribution. Then we need to calculate the mean vector and the covariance matrix, both of which are the key parameters of Gaussian distribution. For such a purpose, we have another assumption of smoothness.

Assumption 3.3. (Smoothness) The target function $F(\boldsymbol{w}, \cdot): R^m \to R$ is twice differentiable, and the expected matrix norm of hessian matrix $H(F(\boldsymbol{w}, \cdot))$ is bounded, i.e., $\mathbb{E}_{\boldsymbol{\xi}}\|H(F(\boldsymbol{w}, \boldsymbol{\xi}))\|^2 \leq L^2$, where $\boldsymbol{\xi}$ is randomly sampled from a specific dataset.

Note that Assumption 3.3 is weaker than L-smooth Assumption. In other words, if a function $F(\boldsymbol{w}, \cdot)$ is L-smooth, it conforms to Assumption 3.3, but not vice versa.

Assumption 3.3 always holds for typical machine learning tasks, e.g., logistic regression, soft-max classification and so on. With these assumptions, we have the following lemma.

Lemma 3.4. *If Assumption 3.1 and 3.3 hold, let $\{\eta_r\}_{r=1}^{+\infty}$ be a sequence of real number such that $\lim_{r \to +\infty} \eta_r = 0$, and $\{\varepsilon_r\}_{r=1}^{+\infty}$ be a sequence of random vectors, where $\varepsilon_r = \hat{\boldsymbol{g}} - \bar{\boldsymbol{g}}$, and $\hat{\boldsymbol{g}} = \sum_{i=1}^n \nabla_{\boldsymbol{w}} F(\boldsymbol{w}_1, \boldsymbol{\xi}_i)$, $\bar{\boldsymbol{g}} = \sum_{i=1}^n \nabla_{\boldsymbol{w}} F(\boldsymbol{w}_i, \boldsymbol{\xi}_i)$ with $\boldsymbol{w}_i = \boldsymbol{w}_{i-1} - \eta_r \boldsymbol{g}_{i-1}, i \in \{2, \cdots, n\}$ respectively, then we have $\varepsilon_r \xrightarrow{L} 0$, which implies $\hat{\boldsymbol{g}} \xrightarrow{L} \bar{\boldsymbol{g}}$.*

Lemma 3.4 implies that if we introduce learning rate decay[3], then

$$\forall \epsilon, \quad \lim_{r \to +\infty} Pr(\|\bar{\boldsymbol{g}} - \hat{\boldsymbol{g}}\| > \epsilon) = 0. \tag{7}$$

In a typical communication round r, the optimization process implies that $\boldsymbol{w}_{n+1} - \boldsymbol{w}_1 = \eta_r \bar{\boldsymbol{g}}$. While based on Eq. (7), we can use $\eta_r \hat{\boldsymbol{g}} = \eta_r \sum_{i=1}^n \nabla_{\boldsymbol{w}} F(\boldsymbol{w}_1, \boldsymbol{\xi}_i)$ to estimate $\eta_r \bar{\boldsymbol{g}}$.

Specifically, since $\boldsymbol{w}_1$ is a constant vector and $\boldsymbol{\xi}_i$ is iid sampled from the dataset in different local steps, $\{\nabla_{\boldsymbol{w}} F(\boldsymbol{w}_1, \boldsymbol{\xi}_i) | i \in \{1, \cdots, n\}\}$ are also iid random vectors. Therefore, based on the sum of independent random variables, we have $\boldsymbol{\mu} = \mathbb{E}[\eta_r \hat{\boldsymbol{g}}] = n\eta_r \mathbb{E}_{\boldsymbol{\xi}}[F(\boldsymbol{w}_1, \boldsymbol{\xi})]$, and $\boldsymbol{\Sigma} = Cov(\eta_r \hat{\boldsymbol{g}}, \eta_r \hat{\boldsymbol{g}}) = n\eta_r^2 \boldsymbol{\Sigma}_1$.

Additionally, $\boldsymbol{\Sigma}$ is a second order term. To simplify the analysis, we need to convert coefficient n to n^2. As mentioned before, $\boldsymbol{\Sigma}_1$ is the covariance matrix of a mean vector distribution, hence it depends on the batch size B. Let $B = \hat{B}/n$, then we obtain $\boldsymbol{\Sigma} = n^2\eta^2 \boldsymbol{\Sigma}_1/\hat{B}$.

For convenience, in the rest of our work, we use $\boldsymbol{\mu}_*$ and $\boldsymbol{\Sigma}_*$ to denote the corresponding mean vector and covariance matrix of gradients estimated by a specific dataset. Similarly, as we can change the local batch size for simplifying computation, we ignore the differences between B and $\hat{B}$. Then the optimal local steps implied by following theorem.

Theorem 3.5. *With Assumption 3.1 and 3.3, for one global step, the optimal local steps is*

$$n_1^{opt} = \max(0, \frac{\boldsymbol{\mu}_l^T \boldsymbol{\mu}_g + \frac{tr((\boldsymbol{\Sigma}_l \boldsymbol{\Sigma}_g)^{\frac{1}{2}})}{B}}{\|\boldsymbol{\mu}_l\|^2 + \frac{tr(\boldsymbol{\Sigma}_l)}{B}}),$$

and the optimal distance is $(\Delta_1^{opt})^2 = \eta_r^2 \Delta^2$,

$$\Delta^2 = \|\boldsymbol{\mu}_g\|^2 + \frac{tr(\boldsymbol{\Sigma}_g)}{B} - \frac{\left(\boldsymbol{\mu}_l^T \boldsymbol{\mu}_g + \frac{tr((\boldsymbol{\Sigma}_l \boldsymbol{\Sigma}_g)^{\frac{1}{2}})}{B}\right)^2}{\|\boldsymbol{\mu}_l\|^2 + \frac{tr(\boldsymbol{\Sigma}_l)}{B}},$$

where $\boldsymbol{\mu}_l$, $\boldsymbol{\Sigma}_l$ represent mean vector and covariance matrix of gradients estimated by local dataset with initial value $\boldsymbol{w}_1$, while $\boldsymbol{\mu}_g$, $\boldsymbol{\Sigma}_g$ represent the corresponding global statistics.

Corollary 3.6. *For m global steps, where m is a constant, the optimal local steps to minimize the distance is $n_m^{opt} = m \cdot n_1^{opt}$ and the optimal distance is $(\Delta_m^{opt})^2 = m^2 \cdot (\Delta_1^{opt})^2$.*

On one hand, according to Theorem 3.5 and Corollary 3.6, the optimal local steps is independent of the learning rate η_r, and it is only determined by the differences between global and local gradient

---

[3]For example, $\eta_r = \eta_0 \alpha^r$ refers to a widely used learning rate decay method with a decay rate $\alpha < 1$

Algorithm 1 Example of GSNR+ in conjunction with FedAvg

Input: initial model $\boldsymbol{w}_1$, learning rate η_0, sample size B, chosen global steps M
for $r = 1$ **to** R **do**
    Sample clients $\boldsymbol{S} \subseteq \{1, \cdots, K\}$
    Server: send $\boldsymbol{w}_1$ and η_r to each client $i \in \boldsymbol{S}$
    On each active client i **in parallel**: initialize local model $\boldsymbol{w}^i \leftarrow \boldsymbol{w}_1$, compute $\tilde{\boldsymbol{g}}_i$ and
    $diag(\tilde{\boldsymbol{\Sigma}}_i)$, and send them to the server
    Server: compute $n_{1,i}^{opt}$ with Theorem 3.5 for each client i, and send it to each client i
    On each active client i **in parallel**:
        for $k = 1$ **to** $M \cdot n_{1,i}^{opt}$ **do**
            $\boldsymbol{w}^i \leftarrow \boldsymbol{w}^i - \eta_r \bar{\boldsymbol{g}}_i$
        end for
    Server: $\boldsymbol{w}_1 \leftarrow \sum_{i=1}^{|\tilde{\boldsymbol{S}}|} \tilde{p}_i \boldsymbol{w}^i$, where $\tilde{\boldsymbol{S}} = \{i | i \in \boldsymbol{S}, n_{1,i}^{opt} > 0\}$, and $\tilde{p}_i$ is the corresponding probability ratio, i.e., $p_i / \sum_{k \in \tilde{\boldsymbol{S}}} p_k$
end for

---

distribution. On the other hand, the distance between optimal path and the practical path is related to η_r. Hence, with a sufficient small η_r, the gap vanishes. That's the reason why current literature argues FedAvg with a small learning rate is equivalent to stochastic gradient descent, and the diminishing learning rate is crucial for the convergence of CL Khaled et al. (2019); Li et al. (2020c).

To estimate the optimal local steps, we need to compute the mean vectors and covariance matrix for both local distribution and global distribution by the samples from each participant. In practice, we use sample mean vector and sample covariance matrix to estimate the parameters of local distribution, i.e., for a participant k with model $\boldsymbol{w}_1$, the corresponding statistics are $\tilde{\boldsymbol{g}}_k = \frac{1}{B} \sum_{b=1}^{B} \boldsymbol{g}_{k,b}$ and $\tilde{\boldsymbol{\Sigma}}_k = \frac{1}{B} \sum_{b=1}^{B} (\boldsymbol{g}_{k,b} - \tilde{\boldsymbol{g}}_k)(\boldsymbol{g}_{k,b} - \tilde{\boldsymbol{g}}_k)^T$, where $\boldsymbol{g}_{b,k} = \nabla_{\boldsymbol{w}} F(\boldsymbol{w}_1, \boldsymbol{\xi}_b | C_k)$. While for the server, based on the theorem of conditional random variables, the corresponding global statistics are

$$\tilde{\boldsymbol{g}} = \mathbb{E}_C[\tilde{\boldsymbol{g}} | C] = \sum_{k=1}^{K} p_k \tilde{\boldsymbol{g}}_k, \tag{8}$$

$$\tilde{\boldsymbol{\Sigma}} = \mathbb{E}_C[\tilde{\boldsymbol{\Sigma}} | C] + Cov_C(\tilde{\boldsymbol{g}} | C) = \sum_{k=1}^{K} p_k \tilde{\boldsymbol{\Sigma}}_k + \sum_{k=1}^{K} p_k [(\tilde{\boldsymbol{g}}_k - \tilde{\boldsymbol{g}})(\tilde{\boldsymbol{g}}_k - \tilde{\boldsymbol{g}})^T]. \tag{9}$$

In practice, as the covariance matrix increases the communication traffic and the calculation of matrix introduces lots of computation, we need to simplify the procedure. Specifically, in Theorem 3.5, we mainly need the trace of covariance matrix. According to Balduzzi et al. (2017), we know that the covariance matrix of gradients is a sparse matrix. Meanwhile, the estimate error can be scaled by the batch size B. Therefore, we can instead utilize the principal diagonal element of $\tilde{\boldsymbol{\Sigma}}_k$ for efficiency. Based on former analysis, we propose an algorithm GSNR+ to calculate the optimal local steps, and Algorithm 1 is a typical example of GSNR+ in conjunction with FedAvg[4].

Partial participation. In distributed scenario, the active participants are usually not 100%, so we cannot obtain perfect information of global gradient. However, We claim that our GSNR+ algorithms can also adapt to this situation, because such imperfect information encourages us to transform Eq. (5) with triangle inequality to

$$\boldsymbol{W}_2(p_{\bar{\boldsymbol{w}}}(\boldsymbol{w}), p_{\boldsymbol{w}_g}(\boldsymbol{w})) \leq \boldsymbol{W}_2(p_{\bar{\boldsymbol{w}}}(\boldsymbol{w}), p_{\hat{\boldsymbol{w}}}(\boldsymbol{w})) + \boldsymbol{W}_2(p_{\hat{\boldsymbol{w}}}(\boldsymbol{w}), p_{\boldsymbol{w}_g}(\boldsymbol{w})),$$

where $\hat{\boldsymbol{w}}$ is the average parameters of active clients (i.e., a subset of total clients). With a specific client set $\boldsymbol{S}$, $\delta = \boldsymbol{W}_2(p_{\hat{\boldsymbol{w}}}(\boldsymbol{w}), p_{\boldsymbol{w}_g}(\boldsymbol{w}))$ is a constant, and $\boldsymbol{W}_2(p_{\bar{\boldsymbol{w}}}(\boldsymbol{w}), p_{\hat{\boldsymbol{w}}}(\boldsymbol{w}))$ can be bounded similar with inequality (6). Thus, with some tolerance δ, we can similarly minimize Eq. (5) with the new upper bound, but the performance decreases as the ratio of active clients declines.

---

[4]Note that our proposed GSNR+ is a compatible method, and the referred FedAvg can also be replaced by other methods (e.g., FedProx).

Convergence analysis. The convergence of GSNR+ algorithms is obvious, as we just change the number of local steps. Moreover, If $E_{max} = \max\{E_i\}_{i=1}^{K}$, we can easily transform the convergence analysis of GSNR+ algorithm to its original version by the inequality $E_i \leq E_{max}$. Therefore, the convergent property of GSNR+ algorithm is resemble to its original version.

4 CALCULATE GSNR BY LOCAL GRADIENTS

In this section, we first analyse the optimal local steps as well as the optimal distance between the local gradient distribution and the global gradient distribution, and then derive a method to calculate GSNR by the optimal distance. However, due to the limited space, the detail analysis between GSNR and the optimization procedure can be found in Appendix C.

Regarding the optimal local steps n_1^{opt} and the corresponding optimal distance $(\Delta)^2$, let $L = \|\boldsymbol{\mu}_g\|^2 + \frac{tr(\boldsymbol{\Sigma}_g)}{B}$, $M = \boldsymbol{\mu}_l^T \boldsymbol{\mu}_g + \frac{tr((\boldsymbol{\Sigma}_l \boldsymbol{\Sigma}_g)^{\frac{1}{2}})}{B}$, and $N = \|\boldsymbol{\mu}_l\|^2 + \frac{tr(\boldsymbol{\Sigma}_l)}{B}$, we can rewrite $n_1^{opt} = \max(0, \frac{M}{N})$ and $(\Delta)^2 = L - \frac{M^2}{N}$.

Global Step

$\eta^2 \Delta^2$

θ

Local Steps

Figure 2: An overview for GSNR: the GSNR can be calculated by the statistics of global gradient distribution and local gradient distribution.

Then we define a matrix as follows:

$$\boldsymbol{R}_* = \begin{pmatrix} u_*^1 & & & & \\ & u_*^2 & & & \\ & & \ddots & & \\ & & & u_*^t & \\ \hline & & & & \left(\frac{1}{B}\boldsymbol{\Sigma}_*\right)^{\frac{1}{2}} \end{pmatrix}$$

where μ_*^i is the component of $\boldsymbol{\mu}_* = (\mu_*^1, \cdots, \mu_*^t)$.

On one hand, $L = \|\boldsymbol{R}_g\|_F^2$ is related to the global distribution, which is a constant for each participant.[5] On the other hand, $N = \|\boldsymbol{R}_l\|_F^2$ only depends on local distribution, thus it can be viewed as a normalization coefficient. Hence, the two variables n_1^{opt} and $(\Delta)^2$ mainly depend on the value of M, the inner product of two matrixes, i.e., $< \boldsymbol{R}_l, \boldsymbol{R}_g >_F$, which represents the similarity of the corresponding matrixes.

Based on former analysis, we derive a method to calculate GSNR as Definition 4.1.

Definition 4.1. Gradient Signal to Noise Ratio (GSNR). For a local dataset $\boldsymbol{D}_l$ and a global dataset $\boldsymbol{D}_g$, with a loss function $F(\boldsymbol{w}, \, \cdot \,)$, the GSNR of model $\boldsymbol{w}$ is defined as

$$r(\boldsymbol{w}) = \max(0, \frac{< \boldsymbol{R}_l, \boldsymbol{R}_g >_F}{\sqrt{\|\boldsymbol{R}_l\|_F^2 \|\boldsymbol{R}_g\|_F^2 - < \boldsymbol{R}_l, \boldsymbol{R}_g >_F^2}}).$$

Specifically, Fig. 2 illustrates an example for Definition 4.1. In Fig. 2, we imagine a similar case in Euclid space, which is a space that is most familiar to us. In this case, angle θ can be viewed as the similarity between global and local gradient vectors. In Euclid space, the minimum distance from a point to a line is the segment vertical to the line, thus the black dash line is orthogonal to local gradient vector. Hence, $\frac{\eta^2(\|\boldsymbol{\mu}_g\|^2 + tr(\boldsymbol{\Sigma}_g)/B)}{\eta^2 \Delta^2} = \sec^2 \theta$. As for GSNR, defined as the magnitude ratio between the parallel component and the orthogonal component, it can be viewed as the $\cot \theta$. Then according to trigonometric transformation, i.e., $\cot^2 \theta = \sec^2 \theta - 1$, we can obtain Definition 4.1.

5 EXPERIMENT

We run our experiments on the well known real world datasets CIFAR-10 and CIFAR-100 mentioned in Krizhevsky et al. (2009) to validate our design.

Setup. For non-iid settings, we utilize 3 methods for data partition: First, we follow the settings in Hsu et al. (2019) to generate non-iid data across different participants by Dirichlet distribution, where

---

[5]$\| \cdot \|_F$ and $< \cdot, \cdot >_F$ are Frobenius inner product and Frobenius norm respectively.

α is a parameter represents the level of non-iid. Second, we propose NonBalance and Pareto for imbalanced partition, which simulates the imbalanced distributed information in practical scenario. Due to the limited space, the details of different methods can be found in Appendix D. For all experiments, we use LeNet for CIFAR-10 and VGG-16 for CIFAR-100.

Table 1: Best test accuracy on CIFAR-10. We distributed the data among 30 clients, utilize batch size of 64, and set local steps $E_{const} = 40$ for different algorithms.

Algorithms	IID	$\alpha = 5$	$\alpha = 0.5$	$\alpha = 0.1$	Label 2	NonBalance
FedAvg	64.09%	64.13%	57.20%	51.04%	53.05%	58.25%
FedProx	63.86%	61.63%	56.69%	49.57%	52.55%	59.35%
Scaffold	**64.14%**	63.21%	56.78%	44.08%	42.71%	53.70%
GSNR+FedAvg	63.59%	64.04%	59.53%	52.61%	**54.77%**	**61.45%**
GSNR+FedProx	63.86%	**64.47%**	**60.31%**	**53.64%**	53.05%	60.33%

To ensure all methods are comparable, we need to set the total computation, i.e., total local steps, to be equal. So in GSNR+ algorithms, we set the local steps for different participant to be $E_k = NE_{const} \frac{n_{1,k}^{opt}}{\sum_{i=1}^{K} n_{1,i}^{opt}}$, where N and E_{const} represents the number of active participants and the local steps of baseline algorithms respectively. Note that E_k is a redistribution of local steps.

The necessity of optimal local updates. To understand the necessity of optimal local updates, we calculate the entropy of the local steps, i.e., $H = \sum_{k=1}^{K} p(C_k) \log p(C_k)$, where $p(C_k) = \frac{n_{1,k}^{opt}}{\sum_{i=1}^{K} n_{1,i}^{opt}}$, and the results are illustrated in Fig. 3. Specifically, the dashed blue line on the top is the uniform distribution of local steps, which is the maximum entropy distribution of discrete variables, and it represents the equal local steps among all participants. Moreover, when the degree of non-iid increases, the computation is allocated

Figure 3: The entropy of local steps for different scenarios.

Figure 4: Test Accuracy of different settings with Momentum-SGD.

more concentrated, i.e., a smaller entropy. On the contrary, the entropy converge to its maximum (i.e., equal local steps) when the data distributed closer to iid. Additionally, the corresponding test accuracy is illustrated in Table 1, which indicates that the re-allocation of local steps improves the test performance.

(a) IID   (b) NonBalance   (a) GSNR   (b) Test Accuracy

Figure 5: The variation of GSNR when we change the labels of a specific participant.

Figure 6: An imbalanced scenario with Pareto partition on CIFAR-100 dataset.

Performance improvements of GSNR+ algorithms. During experiments, we set $\mu = 0.01$ for FedProx, and compare the performance of different algorithms. Then according to Table 1, GSNR+ algorithm achieves best test accuracy among all algorithms, especially data distributed more heterogeneously. Besides, Fig. 4 illustrates the test accuracy when we use Momentum SGD as local optimizer, and GSNR+FedAvg converges faster and achieves better accuracy with different local steps (Scaffold fails to work when we set local steps to be 25). Moreover, in practice, Pareto's Law is a common principle, which means a small number of participants possess a large number of information, and we propose a method to simulate such a scenario on CIFAR-100, a more informative dataset. Fig. 6(b) indicates that GSNR+ algorithm converges faster and reaches a better test accuracy.

Table 2: Communication rounds to reach 0.5 test accuracy for classification on NonBalance CIFAR-10 of 100 participants as we vary the number of active clients.

	Active Clients		
	10%	20%	100%
FedAvg	210 (1.0×)	140 (1.0×)	100 (1.0×)
FedNova	235 (0.9×)	140 (1.0×)	80 (1.2×)
Scaffold	230 (0.9×)	-	-
GSNR+FedAvg	**150 (1.4×)**	**80 (1.7×)**	**55 (1.8×)**

Meanwhile, the GSNR of different participants are resemble to the label distribution (the histogram on the bottom of Fig. 6(a)), which means GSNR can distinguish the information quality between different clients. Furthermore, Table 2 indicates that the growth of active clients speeds up the convergence of different algorithms. Particularly, GSNR+ algorithm gains more benefit from global information as its convergence rate increases from 1.4 times FedAvg to 1.8 times when active clients grows from 10% to 100%.

| (a) IID | (b) Dirichlet(1.0) | (c) Dirichlet(0.5) | (d) Label 2 |

Figure 7: The GSNR of different clients in the experiments in Table 1, we observe that GSNR is larger and almost the same among all participants when data is iid distributed, then it gets smaller and heterogeneous as the non-iid level grows. Finally, when data partition method is Label 2, GSNR is small but similar to each other again, which probably indicates that data distributed with some symmetries in regard to the information.

Evaluate local contributions with GSNR. Fig. 7 displays the variation of GSNR when we utilize Dirichlet method with different α. And the results demonstrate that when the level of non-iid grows, GSNR of different clients vary dramatically, which represents the contribution of different clients are different. Moreover, combined GSNR with Table 1, both of the convergence rate and the test accuracy are better than others when we considerate such differences. Further more, to investigate the performance of data evaluation, we change the labels l of client 0 to be $(l + k) \bmod 10$. So that the client provides a label flipping attack as Hitaj et al. (2017). Fig. 5 illustrates the changes of GSNR when we change the labels, and the red dashed line box represents the original GSNR when the labels are unchanged. Specifically, we observe that it's easy to discover the malicious client when data is iid distributed, while it becomes difficult when data distributed heterogeneously. It's consistent with our intuition, since in non-iid settings, it's difficult to distinguish new knowledge from harmful information without detailed communication. However, despite the difficulties, we observe that the GSNR dramatically decreases when we make a malicious change to the labels. Additionally, we observe GSNR+ algorithms are more robust to malicious changes, due to the limited space, we send these experiments to Appendix D.

6 CONCLUSION

In this paper, we have investigated the CL problem via a new perspective, i.e., GSNR. Our theoretical analysis indicates that under non-iid scenarios, the local updates can be decomposed into signal and noise components, and we can maximize GSNR with the optimal local updates. Based on theoretical analysis, we further propose an algorithm GSNR+ to be compatible with current CL algorithms, which achieves better performance with an elaborate allocation of local steps. Moreover, we derive a method to calculate GSNR directly from the local datasets, which can be utilized to evaluate the local contributions of different participants. Finally, extensive experimental results demonstrates the beneficial effect of optimizing CL from the new perspective of GSNR, and also open up a promising new direction for follow-up research.

REFERENCES

Durmus Alp Emre Acar, Yue Zhao, Ramon Matas Navarro, Matthew Mattina, Paul N. Whatmough, and Venkatesh Saligrama. Federated learning based on dynamic regularization. In *Proceedings of ICLR*. OpenReview.net, 2021.

Eugene Bagdasaryan, Andreas Veit, Yiqing Hua, Deborah Estrin, and Vitaly Shmatikov. How To Backdoor Federated Learning. In *Proceedings of AISTATS*, pp. 2938–2948, 2018.

David Balduzzi, Marcus Frean, Lennox Leary, J. P. Lewis, Kurt Wan-Duo Ma, and Brian McWilliams. The shattered gradients problem: If resnets are the answer, then what is the question? In *Proceedings of ICML*, 2017.

Minghong Fang, Xiaoyu Cao, Jinyuan Jia, and Neil Zhenqiang Gong. Local Model Poisoning Attacks to Byzantine-Robust Federated Learning. In *Proceedings of USENIX Security*, pp. 1605–1622, 2020.

Farzin Haddadpour and Mehrdad Mahdavi. On the Convergence of Local Descent Methods in Federated Learning. *CoRR*, abs/1910.14425, 2019.

Farzin Haddadpour, Mohammad Mahdi Kamani, Mehrdad Mahdavi, and Viveck R. Cadambe. Trading redundancy for communication: Speeding up distributed SGD for non-convex optimization. In *Proceedings of ICML*, volume 97, pp. 2545–2554. PMLR, 2019.

Briland Hitaj, Giuseppe Ateniese, and Fernando Pérez-Cruz. Deep Models Under the GAN: Information Leakage from Collaborative Deep Learning. In *Proceedings of CCS*, pp. 603–618. ACM, 2017.

Tzu-Ming Harry Hsu, Hang Qi, and Matthew Brown. Measuring the effects of non-identical data distribution for federated visual classification. *CoRR*, abs/1909.06335, 2019.

Yihan Jiang, Jakub Konečný, Keith Rush, and Sreeram Kannan. Improving federated learning personalization via model agnostic meta learning. *CoRR*, abs/1909.12488, 2019.

Sai Praneeth Karimireddy, Satyen Kale, Mehryar Mohri, Sashank J. Reddi, Sebastian U. Stich, and Ananda Theertha Suresh. SCAFFOLD: Stochastic Controlled Averaging for Federated Learning. In *Proceedings of ICML*, pp. 5132–5143, 2020.

Ahmed Khaled, Konstantin Mishchenko, and Peter Richtárik. First Analysis of Local GD on Heterogeneous Data. *CoRR*, abs/1909.04715, 2019.

Ahmed Khaled, Konstantin Mishchenko, and Peter Richtárik. Tighter Theory for Local SGD on Identical and Heterogeneous Data. In *Proceedings of AISTATS*, pp. 4519–4529, 2020.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Viraj Kulkarni, Milind Kulkarni, and Aniruddha Pant. Survey of personalization techniques for federated learning. *CoRR*, abs/2003.08673, 2020.

Tian Li, Anit Kumar Sahu, Ameet Talwalkar, and Virginia Smith. Federated Learning: Challenges, Methods, and Future Directions. *IEEE Signal Processing Magazine*, 37(3):50–60, 2020a.

Tian Li, Anit Kumar Sahu, Manzil Zaheer, Maziar Sanjabi, Ameet Talwalkar, and Virginia Smith. Federated Optimization in Heterogeneous Networks. In *Proceedings of MLSys*, 2020b.

Tian Li, Shengyuan Hu, Ahmad Beirami, and Virginia Smith. Ditto: Fair and Robust Federated Learning Through Personalization. In *Proceedings of ICML*, pp. 6357–6368, 2021.

Xiang Li, Kaixuan Huang, Wenhao Yang, Shusen Wang, and Zhihua Zhang. On the Convergence of FedAvg on Non-IID Data. In *Proceedings of ICLR*, 2020c.

Jinlong Liu, Yunzhi Bai, Guoqing Jiang, Ting Chen, and Huayan Wang. Understanding Why Neural Networks Generalize Well Through GSNR of Parameters. In *Proceedings of ICLR*, 2020.

LO Mangasarian. Parallel gradient distribution in unconstrained optimization. *SIAM Journal on Control and Optimization*, 33(6):1916–1925, 1995.

Yishay Mansour, Mehryar Mohri, Jae Ro, and Ananda Theertha Suresh. Three approaches for personalization with applications to federated learning. *CoRR*, abs/2002.10619, 2020.

Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Agüera y Arcas. Communication-Efficient Learning of Deep Networks from Decentralized Data. In *Proceedings of AISTATS*, pp. 1273–1282, 2017.

Luca Melis, Congzheng Song, Emiliano De Cristofaro, and Vitaly Shmatikov. Exploiting Unintended Feature Leakage in Collaborative Learning. In *Proceedings of IEEE SP (Oakland)*, pp. 691–706, 2019.

Mehryar Mohri, Gary Sivek, and Ananda Theertha Suresh. Agnostic Federated Learning. In *Proceedings of ICML*, pp. 4615–4625, 2019.

Yurii Nesterov. Introductory lectures on convex programming volume i: Basic course. *Lecture notes*, 3(4):5, 1998.

Tom Rainforth, Adam R. Kosiorek, Tuan Anh Le, Chris J. Maddison, Maximilian Igl, Frank Wood, and Yee Whye Teh. Tighter Variational Bounds are Not Necessarily Better. In *Proceedings of ICML*, pp. 4274–4282, 2018.

Sashank J. Reddi, Zachary Charles, Manzil Zaheer, Zachary Garrett, Keith Rush, Jakub Konečný, Sanjiv Kumar, and Hugh Brendan McMahan. Adaptive Federated Optimization. In *Proceedings of ICLR*, 2021.

Khe Chai Sim, Petr Zadrazil, and Françoise Beaufays. An investigation into on-device personalization of end-to-end automatic speech recognition models. In *Interspeech 2019, 20th Annual Conference of the International Speech Communication Association, Graz, Austria, 15-19 September 2019*, pp. 774–778. ISCA, 2019.

Rachael Hwee Ling Sim, Yehong Zhang, Mun Choon Chan, and Bryan Kian Hsiang Low. Collaborative machine learning with incentive-aware model rewards. In *Proceedings of ICML*, volume 119 of *Proceedings of Machine Learning Research*, pp. 8927–8936. PMLR, 2020.

Cédric Villani. *Optimal transport: old and new*, volume 338. 2009.

Hongyi Wang, Mikhail Yurochkin, Yuekai Sun, Dimitris S. Papailiopoulos, and Yasaman Khazaeni. Federated Learning with Matched Averaging. In *Proceedings of ICLR*, 2020a.

Jianyu Wang, Qinghua Liu, Hao Liang, Gauri Joshi, and H. Vincent Poor. Tackling the Objective Inconsistency Problem in Heterogeneous Federated Optimization. In *Proceedings of NeurIPS*, 2020b.

Shiqiang Wang, Tiffany Tuor, Theodoros Salonidis, Kin K. Leung, Christian Makaya, Ting He, and Kevin Chan. Adaptive Federated Learning in Resource Constrained Edge Computing Systems. *IEEE Journal on Selected Areas in Communications*, 37(6):1205–1221, 2019.

Yuzhe Yang, Kaiwen Zha, Ying-Cong Chen, Hao Wang, and Dina Katabi. Delving into deep imbalanced regression. In *Proceedings of ICML*, volume 139, pp. 11842–11851. PMLR, 2021.

Dong Yin, Ashwin Pananjady, Maximilian Lam, Dimitris S. Papailiopoulos, Kannan Ramchandran, and Peter L. Bartlett. Gradient diversity: a key ingredient for scalable distributed learning. In *Proceedings of AISTATS*, volume 84, pp. 1998–2007. PMLR, 2018.

Hao Yu, Sen Yang, and Shenghuo Zhu. Parallel restarted SGD with faster convergence and less communication: Demystifying why model averaging works for deep learning. In *Proceedings of AAAI*, pp. 5693–5700. AAAI Press, 2019.

Ligeng Zhu, Zhijian Liu, and Song Han. Deep Leakage from Gradients. In *Proceedings of NeurIPS*, pp. 14747–14756, 2019.

A RELATED WORK

Gradient Diversity. Gradient diversity is a key ingredient of collaborated learning, which captures the differences between the datasets possessed by different participants. Yin et al. (2018) employs gradient diversity to investigate the relationship between batch size and the convergence rate in parallel SGD. Yu et al. (2019) analyses why periodical model averaging is suitable for deep learning, and provides a deep understanding of model averaging. Haddadpour et al. (2019) try to mitigate gradient diversity through sharing a small batch of data among all participants, but it also introduces a higher privacy risk. Acar et al. (2021) introduces a dynamic regularization term to resolve the problem of gradient divergence. However, most of previous literatures try to solve gradient diversity through gradient calculating, such as gradient prediction, regularization, personalized target function and so on. However, the influence of local steps gains less attention. In this paper, we propose a new tool to analyse the optimization procedure by Gradient Signal to Noise Ratio, it can reduce the required communication rounds via an elaborate configuration of local steps and propose a method to evaluate the quality of different datasets.

Personalization in collaborated learning. Another important problem in collaborated learning is personalization. Formally, personalization transform the optimization problem from global distribution $p(\boldsymbol{\xi})$ to a specific local distribution $p(\boldsymbol{\xi} \,|\, C_i)$ on client i, it scarifies the global performance in order to gain more benefit in local scenario. Kulkarni et al. (2020) reviews the investigations of personalization, and the situations are divided into three categories: device heterogeneity, data heterogeneity and model heterogeneity, while the last one is the motivation of personalization. Mansour et al. (2020) proposes three methods to achieve personalization, these methods try to balance the performance on global data distribution as well as local data distribution. Sim et al. (2019) proposes a method to optimize global model and local model separately in order to make local model more personalized. Jiang et al. (2019) propose three objectives to make personalization easily. However, personalization is an important topic in collaborated learning since different participants confront different problems, but if we greedily utilize global information for personalization, there is likely to appear Prisoner's Dilemma, the collective benefit for all participants is not optimal and therefore, the profit for each participant can probably be improved either. Hence, cooperation is also important, the important problem for personalization is to search optimum on conditional data distribution $p(\boldsymbol{\xi} \,|\, C_i)$ combined with cooperation.

B PROOFS OF LEMMA AND THEOREM

B.1 PROOF OF LEMMA 3.2

Proof. For any constant n, gradient vector $\boldsymbol{g}$ can be rewritten as

$$\boldsymbol{g} = \frac{1}{B} \sum_{b=1}^{B} (\nabla_{\boldsymbol{w}} F(\boldsymbol{w}_1, \boldsymbol{\xi}_{1,b}|C_k), \cdots, \nabla_{\boldsymbol{w}} F(\boldsymbol{w}_n, \boldsymbol{\xi}_{n,b}|C_k)),$$

let $\tilde{\boldsymbol{g}}_b = (\nabla_{\boldsymbol{w}} F(\boldsymbol{w}_1, \boldsymbol{\xi}_{1,b}|C_k)), \cdots, \nabla_{\boldsymbol{w}} F(\boldsymbol{w}_n, \boldsymbol{\xi}_{n,b}|C_k)))$, we further have

$$\boldsymbol{g} = \frac{1}{B} \sum_{b=1}^{B} \tilde{\boldsymbol{g}}_b,$$

then with Assumption 3.1 and n is a constant, $\tilde{\boldsymbol{g}}_b$ is subject to some complex distribution with bounded covariance matrix. As $\boldsymbol{\xi}_{i,b}|C_k$ is sampled from the same distribution independently, $\boldsymbol{g}$ is the mean vector of $\tilde{\boldsymbol{g}}_1, \cdots, \tilde{\boldsymbol{g}}_B$, which are iid random vectors.
Therefore, due to the classical Central Limit Theory (CLT), with B growing large, $\sqrt{B}(\boldsymbol{g} - \mathbb{E}[\boldsymbol{g}])$ converges to $\mathcal{N}(\boldsymbol{0}, \boldsymbol{\Sigma})$ in distribution, where $\boldsymbol{\Sigma}$ is the covariance matrix of $\boldsymbol{g}$. $\qquad\square$

B.2 PROOF OF LEMMA 3.4

Proof. First, we prove $\lim_{r \to +\infty} \mathbb{E}\|\boldsymbol{\varepsilon}_r\| = 0$.

Regarding the gradient $\boldsymbol{g}_i$, $i \in \{1, \cdots, n\}$, due to the smoothness of $\nabla_{\boldsymbol{w}} F(\boldsymbol{w}_i, \boldsymbol{\xi})$, we can expand $\boldsymbol{g}_i$ based on Lagrange's mean value theorem as

$$\boldsymbol{g}_i = \nabla_{\boldsymbol{w}} F(\boldsymbol{w}_i, \boldsymbol{\xi}_i) = \nabla_{\boldsymbol{w}} F(\boldsymbol{w}_1, \boldsymbol{\xi}_i) + H(F(\tilde{\boldsymbol{w}}_i, \boldsymbol{\xi}_i))(\boldsymbol{w}_i - \boldsymbol{w}_1) = \boldsymbol{g}_{1,i} + H(F(\tilde{\boldsymbol{w}}_i, \boldsymbol{\xi}_i))(\boldsymbol{w}_i - \boldsymbol{w}_1),$$
(10)

where $\tilde{\boldsymbol{w}} := \lambda \boldsymbol{w}_i + (1 - \lambda)\boldsymbol{w}_1$, $\lambda \in [0, 1]$, and $\boldsymbol{g}_{1,i}$ represents the gradient at $\boldsymbol{w}_1$ with samples $\boldsymbol{\xi}_i$, which is an unbiased estimator of $\boldsymbol{g}_1$. Note that when $i \neq j$, $\boldsymbol{g}_{1,i}$ is independent of $\boldsymbol{g}_{1,j}$. Then

$$\mathbb{E}\|\boldsymbol{g}_i - \boldsymbol{g}_{1,i}\| = \mathbb{E}\|H(F(\tilde{\boldsymbol{w}}_i, \boldsymbol{\xi}_i))(\boldsymbol{w}_i - \boldsymbol{w}_1)\| \overset{(a)}{\leq} \mathbb{E}\|H(F(\tilde{\boldsymbol{w}}_i, \boldsymbol{\xi}_i))\|\|(\boldsymbol{w}_i - \boldsymbol{w}_1)\| \quad (11)$$

$$\overset{(b)}{\leq} \sqrt{\mathbb{E}\|H(F(\tilde{\boldsymbol{w}}_i, \boldsymbol{\xi}_i))\|^2 \mathbb{E}\|\boldsymbol{w}_i - \boldsymbol{w}_1\|^2} \overset{(c)}{\leq} L \cdot \sqrt{\mathbb{E}\|\eta_r \sum_{j=1}^{i-1} \boldsymbol{g}_j\|^2}$$

$$\overset{(d)}{\leq} L^2 \cdot \eta_r \sqrt{(i-1) \sum_{j=1}^{i-1} \mathbb{E}\|\boldsymbol{g}_j\|^2} \overset{(e)}{\leq} (i-1)\eta_r L G,$$

where (a) follows from sub-multiplicative property of matrix norm, (b) is based on Cauchy–Schwarz inequality, (c) is an immediate consequence of Assumption 3.3 and the local optimization process, (d) comes from the fact $\|\sum_{i=1}^n \boldsymbol{a}_i\|^2 \leq n \sum_{i=1}^n \|\boldsymbol{a}_i\|^2$, and (e) is based on Assumption 3.1, where $G^2 := \sigma^2 + \mu^2$, $\mu = \max(\{\|\boldsymbol{\mu}_i\|\}_{i \in \{1, \cdots, n\}})$. Hence,

$$\mathbb{E}\|\boldsymbol{\varepsilon}_r\| = \mathbb{E}\|\hat{\boldsymbol{g}} - \bar{\boldsymbol{g}}\| = \mathbb{E}\|\sum_{i=1}^n (\boldsymbol{g}_i - \boldsymbol{g}_{1,i})\| \leq \sum_1^n \mathbb{E}\|\boldsymbol{g}_i - \boldsymbol{g}_{1,i}\|$$

$$\leq (\sum_{i=1}^n (i-1))\eta_r L G = \frac{n(n-1)}{2}\eta_r L G$$

where the first inequality follows from the triangle inequality, and the second inequality is based on Eq. (11).

As n represents the number of local steps, which is a constant, $\mathbb{E}\|\boldsymbol{\varepsilon}_r\|$ is upper bounded by $\eta_r \cdot M$, where M is a bounded value. Therefore,

$$0 \leq \lim_{r \to +\infty} \mathbb{E}\|\boldsymbol{\varepsilon}_r\| \leq \lim_{r \to +\infty} \eta_r \cdot M = 0. \quad (12)$$

Formula (12) implies $\boldsymbol{\varepsilon}_r$ converge to 0 in mean, hence $\boldsymbol{\varepsilon}_r \overset{L}{\to} 0$, which immediately completes the proof.

$\square$

B.3 PROOF OF THEOREM 3.5

Proof. Implied by Lemma 3.2, one global step is a specific case, and the global gradient distribution converges to $\mathcal{N}(\eta_r \boldsymbol{\mu}_g, \frac{\eta_r^2 \boldsymbol{\Sigma}_g}{B})$. While for n local steps, based on Lemma 3.2 and Lemma 3.4, it approximately conforms to $\mathcal{N}(n\eta\boldsymbol{\mu}_l, n^2\eta^2 \frac{\boldsymbol{\Sigma}_l}{B})$. Then according to Eq. (4), to minimize the path gap, we can build an optimization problem as

$$\min_n \quad d^2 = \|\eta\boldsymbol{\mu}_g - n\eta\boldsymbol{\mu}_l\|^2 + tr(\boldsymbol{M}^2) \quad (13)$$

$$\text{s.t.} \quad \boldsymbol{M} = \left(\frac{\eta^2 \boldsymbol{\Sigma}_g}{B}\right)^{\frac{1}{2}} - \left(\frac{n^2\eta^2 \boldsymbol{\Sigma}_l}{B}\right)^{\frac{1}{2}}$$

$$n \geq 0.$$

Note that Eq. (13) is a quadratic function of n, which immediately completes the proof. $\square$

B.4 PROOF OF COROLLARY 3.6

Proof. In this case, we slightly change the global gradients distribution to $\mathcal{N}(k\boldsymbol{\mu}_g, \frac{k^2\boldsymbol{\Sigma}_g}{B})$, and reformulate problem (13) as

$$\min_n \quad d^2 = k^2(\|\eta\boldsymbol{\mu}_g - \frac{n}{k}\eta\boldsymbol{\mu}_l\|^2 + tr(\boldsymbol{M}^2))$$

$$\text{s.t.} \quad \boldsymbol{M} = \left(\frac{\eta^2\boldsymbol{\Sigma}_g}{B}\right)^{\frac{1}{2}} - \left(\frac{\left(\frac{n}{k}\right)^2\eta^2\boldsymbol{\Sigma}_l}{B}\right)^{\frac{1}{2}}$$

$$n \geq 0,$$

let $\tilde{d} = \frac{d}{k}$ and $\tilde{n} = \frac{n}{k}$, the new problem is reduce to problem (13), then we conclude the proof immediately. □

C DETAIL ANALYSIS OF GSNR

Figure 8: A similar case in Euclid space for easy comprehension: as optimal optimization path is discrete, there is an optimal distance between global step and multiple local steps. Further more, when global steps converge to the optimum, the local steps converge to the nearest point to optimum.

Figure 9: A representative scenario of GSNR: $r(\boldsymbol{w})$ is a random variable with regard to $\boldsymbol{w}$. If we get closer to the optimum of C_2, GSNR of C_1 will increase and the GSNR of C_2 will decrease. While if we get closer to the optimum of C_1, the situation changes in the opposite way.

According to Fig. 8, the stochastic gradient descent algorithm converges to the ϵ-neighborhood of optimum after a constant steps (usually more than $\mathcal{O}(\frac{1}{\epsilon})$ Nesterov (1998)), we refer this constant as the optimal m_{opt}. As in Fig. 8, with a determined expected difference between global distribution and local distribution, i.e., GSNR is a constant during a specific round, set the target global steps as m_{opt} is the optimal choice. In this case, $n_{m_{opt}}^{opt}$ lead to minimum expected distance between global optimum and the practical optimization path, and the distance become even larger with one more or less step. However, it's complicated to determine the definite number of these steps, we instead apply our theorems to a specific m, which is usually a large number, and the theorems still make a progress to improve the algorithms, for both achieving better accuracy and saving computing resources, especially in non-iid setting.

Then we focus on the definition of GSNR in Definition 4.1. Cauchy-Schwarz inequality implies that $\Delta^2 \geq 0$, and the equality holds when local distribution is the same as the global distribution, i.e., the data is iid distributed among different participants. With Δ^2 decreases, which implies local data distribution approaches the global data distribution, n_1^{opt} gradually increases. When Δ^2 reaches its minimum 0, n_1^{opt} attains its maximum value 1. This phenomenon reflects that the more similarity between local dataset and the global dataset, i.e., the larger GSNR the local dataset achieves, the more local steps we need for optimization procedure, which is heuristically experimented in Li et al. (2020c).

While in the distributed scenario, the global data grouped into several local datasets, and almost each dataset posses some bias. Due to the exitance of bias, we can make a orthogonal decomposition (see Fig. 2 for detail). The green vector, parallels with ideal path, represent the signal component, and it determines the contribution of local updates for minimizing global targets. While the red vector, orthogonal to ideal path, represent noise component, it is the main cause to lead the model to local optimum, which is usually different from global optimum. This situation can be even worse in extreme non-iid case.

In practice, $r(\boldsymbol{w})$ quantifies the heterogeneity of the local data distribution. Note that $n_1^{opt} \geq 0$, when $n_1^{opt} = 0$, from its definition, we know that $< \boldsymbol{R}_l, \boldsymbol{R}_g >_F = 0$, hence the systematic error Δ^2 achieves its maximum $\|\boldsymbol{R}_g\|_F^2$, and $r(\boldsymbol{w})$ attains its minimum 0. In another case, when local dataset is the same as the global dataset, i.e., $\Delta^2 = 0$, $r(\boldsymbol{w}) \to +\infty$, we treat this scenario as a noiseless optimization procedure, and the data is iid distributed among each participant. Therefore, $r(\boldsymbol{w}) \in (0, +\infty)$.

With former analysis, we know $r(\boldsymbol{w}) \in (0, +\infty)$. On one hand, as the data is iid distributed among each participant, i.e., GSNR tends to $+\infty$, the distributed optimization is a noiseless procedure, thus the local steps only affect the random error during training, and this can be overcome by a large batch size. On the other hand, as GSNR is 0, the fact means $< \boldsymbol{R}_l, \boldsymbol{R}_g >_F \leq 0$, the angle between expected local gradient and the global gradient is greater than $90°$. In other words, for current optimization, local data distribution is independent of global data distribution, thus for global optimization, it is no better than a random guess, then its signal component will be set to 0, which leads GSNR to 0.

As for the relationship between GSNR and the parameters $\boldsymbol{w}$, Fig. 9 displays a representative scenario. Due to the randomness of SGD, the parameters after $\boldsymbol{w}_1$ with another aggregation can be either $\boldsymbol{w}_2$ or $\boldsymbol{w}_2'$. On one hand, if the parameters is $\boldsymbol{w}_2$, which means we get closer to the optimum of client C_2, there are different changes of the GSNR for different clients: for C_1, the GSNR increases, while for C_2, the vector is almost orthogonal to global optimization vector, which implies its GSNR is closer to 0. On the other hand, if the parameters is $\boldsymbol{w}_2'$, another parameter closer to optimum of C_1, the phenomenon is slightly different: GSNR of C_1 decreases and the GSNR of C_2 increases. Hence, during the training process, $r(\boldsymbol{w})$ is a random variable correlated with the random process $\boldsymbol{w}$, and if we tend to use GSNR to evaluate different datasets possessed by different participants, we need to observe its statistics, i.e., mean or median.

D DETAILS OF EXPERIMENTS

D.1 DIFFERENT METHODS OF DATA PARTITION

Dirichlet partition. we follow the settings in Hsu et al. (2019) to generate non-iid data across different participants by Dirichlet distribution. The prior distribution is set to be Uniform, and then the parameter α represents the level of concentration. With $\alpha \to +\infty$, the data distributions of all participants tends to be identical, hence the data is iid distributed among different clients. While $\alpha \to 0$, each participant only possesses data chose from the same class, i.e., one label data for each participant. As for **Label 2.**, it is a specific partition method in Hsu et al. (2019), and each client owns 2 classes data.

NonBalance partition. For NonBalance partition, we tend to simulate the practical scenario of non-balanced information. We divide all participants into three categories: abundant information, medium information and less information, which represent the clients possess data chosen from different number of labels. For clients with abundant information, we random chose data from all labels, and the number of them only account for 10% of total clients. For the clients with medium information, we random chose 50% classes for each client, then distributed data randomly according to its chosen labels, and the ratio of them is 40%. Finally, for the clients with less information, the number of labels reduces to 20%, and the ratio of them raises to 50%.

Pareto partition. In practice, Pareto distribution is very common, it represents the long tailed distribution of practical scenario such as the degree of nodes in complex network, the distribution of social wealth, the distribution of followers in social network and so on. Hence, we design Pareto partition to simulate the so called Two-Eight distribution. First, we sample N points from pareto

distribution,

$$p(x) = \begin{cases} \frac{k \cdot x_{min}^k}{x^{k+1}}, & \text{if } x \geq x_{min} \\ 0, & \text{otherwise.} \end{cases}$$

Where N represents the number of clients. Denote the data points as $\boldsymbol{X} = \{x_i\}_{i=1}^N$, and we normalize x_i with $\tilde{x}_i = x_i / \max(\boldsymbol{X})$ to guarantee all data distributed in [0, 1]. Finally, we use $\tilde{x}_i$ as the ratio of classes possessed by different clients for random sampling, and set the minimum number of labels among all clients to be 1.

D.2 ADDITIONAL EXPERIMENTS

(a) GSNR on IID CIFAR-10 with Changing labels. (b) GSNR on NonBalance CIFAR-10 with Changing labels. (c) GSNR on IID CIFAR-10 with Random input. (d) GSNR on NonBalance CIFAR-10 with Random input.

(e) Test accuracy on IID CIFAR-10 with Changing labels. (f) Test accuracy on Non-Balance CIFAR-10 with Changing labels. (g) Test accuracy on IID CIFAR-10 with Random input. (h) Test accuracy on Non-Balance CIFAR-10 with Random input.

Figure 10: We make different malicious changes to client 0 in different partition methods. In (a) and (b), we change the labels l of client 0 to $l + 3$. While in (c) and (d), the labels remain unchanged, and we change the input data to be a uniform distribution $U(-1, 1)$. (e)-(h) are the corresponding test accuracy of different scenarios.

Fig. 10 displays the change of GSNR and corresponding test accuracy when we apply different malicious change to a client. Interestingly, compare Fig. 10(a) and 10(b) with Fig. 10(c) and 10(d), we can discover that the decrease of GSNR for random input is larger than label changing. Specifically, it is consistent with our intuition, since malicious attack of label changing contains more information than random input. Simply put, after label changing, the model still obtains the information that such data belong to a same class even. For example, if we change all labels of 'cat' to 'dog', we still know the data of 'cat' belongs to a same class, though we call them 'dog' now. On the contrary, the change of random input cannot provide this information.