Amortized Variational Inference in Hierarchical Models

Abstract

It is difficult to use subsampling with variational inference in hierarchical models since the number of local latent variables scales with the dataset. Thus, inference in hierarchical models remains a challenge at large scale. It is helpful to use a variational family with structure matching the posterior, but optimization is still slow due to the huge number of local distributions. Instead, this paper suggests an amortized approach where shared parameters simultaneously represent all local distributions, and a "feature pooling" network is learned to represent conditionally i.i.d. observations. This approach is similarly accurate as using a given joint distribution (e.g., a full-rank Gaussian) but is feasible on datasets that are several orders of magnitude larger. It is also dramatically faster than using a structured variational distribution.

1   Introduction

Hierarchical Bayesian models are a general framework where parameters of "groups" are drawn from some shared distribution, and then observed data is drawn from a distribution specified by each group's parameters. After data is observed, the inference problem is to infer both the parameters for each group and the shared parameters. These models have proven useful in various domains [10] including hierarchical regression amd classification [9], topic models [4, 16, 3], polling [8, 18], epidemiology [17], ecology [6], psychology [29], matrix-factorization [27], and collaborative filtering [19, 25].

A proven technique for scaling variational inference (VI) to large datasets is subsampling. The idea is that if the target model has the form $p(z, y) = p(z) \prod_i p(y_i | z)$ then an unbiased gradient can be estimated while only evaluating $p(z)$ and $p(y_i | z)$ at a few i [13, 15, 23, 21, 28, 12].

This paper addresses hierarchical models of the form $p(\theta, z, y) = p(\theta) \prod_i p(z_i, y_i | \theta)$, where only y is observed. There are two challenges. First, the number of local latent variables z_i increases with the dataset, meaning the posterior distribution increases in dimensionality. Second, there is often a dependence between z_i and θ which must be captured to get strong results [12].

Our solution takes three steps. First, in the true posterior, the different latent variables z_i are conditionally independent given θ, which suggests using a variational family of the same form. We confirm this intuition by showing that for any joint variational family $q(\theta, z)$, one can define a corresponding "branch" family $q(\theta) \prod_i q(z_i | \theta)$ such that inference will be equally accurate (Theorem 2). We call inference using such a family the "branch" approach.

Second, we observe that if using the branch approach, the optimal local variational parameters can be computed only from θ and local data (Equation (12)). Thus, we propose to amortize the computation of the local variational parameters by learning a network to approximately solve that optimization.

We show that when the target distribution is symmetric over latent variables, this will be as accurate as the original joint family, assuming a sufficiently capable amortization network (Claim 5).

Third, we note that in many real hierarchical models, there are many i.i.d. data generated from each local latent variable. This presents a challenge for learning an amortization network, since the full network should deal with different numbers of data points and naturally reflect the symmetry between the inputs (that is, without having to relearn the symmetry.) We propose an approach where a preliminary "feature" network processes each datum, after which they are combined with a pooling operation which forms the input for a standard network (Section 6). This is closely related to the "deep sets" [31] strategy for permutation invariance.

We validate these methods on a synthetic model where exact inference is possible, and on a user-preference model for the MovieLens dataset with 162K users who make 25M ratings of different movies. At small scale (2.5K ratings), we show similar accuracy using a dense joint Gaussian, a branch distribution, or our amortized approach. At moderate scale (180K ratings), joint inference is intractable. Branch distributions gives a meaningful answer, and the amortized approach is comparable or better. At large scale (18M ratings) the amortized approach is thousands of nats better on test-likelihoods even after branch distributions were trained for almost ten times as long as the amortized approach took to converge (Figure 6).

2   Hierarchical Branched Distributions

Figure 1: The graphical model for the HBDs. On the left, we have plate notation for the generic HBD from eq. (3). Note, we can have an edge from θ to y_{ij} (we skip it for clarity.) On the right, we have an example model with $N = 3$.

We focus on two-level hierarchical distributions. A generic model of this type is given by

$$p(\theta, z, y|x) = p(\theta) \prod_{i=1}^{N} p(z_i|\theta)p(y_i|\theta, z_i, x_i), \tag{1}$$

where θ and $z = \{z_i\}_{i=1}^{N}$ are latent variables, $y = \{y_i\}_{i=1}^{N}$ are observations, and $x = \{x_i\}_{i=1}^{N}$ are covariates. As the visual representations of these models resemble branches, we refer them as *hierarchical branch distributions (HBDs)*.

Symmetric.   We call an HBD symmetric if the conditionals are symmetric, i.e., if $z_i = z_j, x_i = x_j$, and $y_i = y_j$, it implies that

$$p(z_i|\theta) = p(z_j|\theta), \text{ and}$$
$$p(y_i|\theta, z_i, x_i) = p(y_j|\theta, z_j, x_j). \tag{2}$$

Locally i.i.d.   Often local observations y_i (and x_i) are a collection of conditionally i.i.d observations. Then, an HBD takes the form of

$$p(\theta, z, y|x) = p(\theta) \prod_{i=1}^{N} p(z_i|\theta) \prod_{j=1}^{n_i} p(y_{ij}|\theta, z_i, x_{ij}), \tag{3}$$

where $y_i = \{y_{ij}\}_{j=1}^{n_i}$ and $x_i = \{x_{ij}\}_{j=1}^{n_i}$ are collections of conditionally i.i.d observations and covariates; $n_i \geq 1$ is the number of observations for branch i.

No local covariates. Some applications do not involve the covariates x_i. In such cases, HBDs have a simplified form of

$$p(\theta, z, y) = p(\theta) \prod_{i=1}^{N} p(z_i|\theta) p(y_i|\theta, z_i).$$ (4)

In this paper, we will be using eq. (1) and eq. (3) to refer HBDs—the results extend easily to case where there are no local covariates. (For instance, in Section 5, we amortize using (x_i, y_i) as inputs. When there are no covariates, we can amortize with just y_i.)

2.1 Related Work

Bayesian inference in hierarchical models is an old problem. The most common solutions are Markov chain Monte Carlo (MCMC) and VI. A key advantage of VI is that gradients can sometimes be estimated using only a subsample of data. Hoffman et al. [13] observe that inference in *hierarchical* models is still slow at large scale, since the number of parameters scales with the dataset. Instead, they assume that θ and z_i from eq. (1) are in conjugate exponential families, and observe that for a mean-field variational distribution $q(\theta) \prod_i q(z_i)$, the optimal $q(z_i)$ can be calculated in closed form for fixed $q(\theta)$. This is highly scalable, though it is limited to factorized approximations and requires a conditionally conjugate target model.

A structured variational approximation like $q(\theta) \prod_i q(z_i|\theta)$ can be used which reflects the dependence of z_i on θ [12, 26, 2]. However, this still has scalability problems in general since the number of parameters grows in the size of the data (section 7). To the best of our knowledge, the only approach that avoids this is the framework of structured stochastic VI [12], which assumes the target is conditionally conjugate, and that for a fixed θ an optimal "local" distribution $q(z_i|\theta)$ can be calculated from local data. Hoffman and Blei [12] address matrix factorization models and latent Dirichlet allocation, using Gibbs sampling to compute the local distributions. Our approach is not strictly an instance of this framework, as we do not assume conjugacy or that amortization can exactly recover optimal local distributions [12, Eq. 7]. Still the spirit is the same, and our approach should be seen as part of this line of research.

3 Joint approximations for HBD

When dealing with HBDs, a non-structured distribution does not scale. To see this, consider the naive VI objective—Evidence Lower Bound (ELBO, $\mathcal{L}$). Let q_ϕ^{Joint} be a joint variational approximation over θ and z; we use sans-serif font for random variables. Then,

$$\mathcal{L}\left(q_\phi^{\text{Joint}}\|p\right) = \mathbb{E}_{q_\phi^{\text{Joint}}(\theta, z)}\left[\log \frac{p(\theta, z, y|x)}{q_\phi^{\text{Joint}}(\theta, z)}\right],$$ (5)

where ϕ are variational parameters. Usually the above expectation is not tractable and one uses a Monte-Carlo estimator. A single sample estimator is given by

$$\widehat{\mathcal{L}} = \log \frac{p(\theta, z, y|x)}{q_\phi^{\text{Joint}}(\theta, z)},$$ (6)

where $(\theta, z) \sim q_\phi^{\text{Joint}}$ and $\widehat{\mathcal{L}}$ is unbiased. Since q_ϕ^{Joint} need not factorize, even a single estimate requires sampling all the latent variables at each step. This is problematic when there are a large number of local latent variables. One encounters the same scaling problem when taking the gradient of the ELBO. We can estimate the gradient using any of the several available estimators [21, 15, 23, 24]; however, none of them scale if q_ϕ^{Joint} does not factorize [13].

4 Branch approximations for HBD

It is easy to see that the posterior distribution of the HBD eq. (1) takes the form

$$p(\theta, z|y, x) = p(\theta|y, x) \prod_{i=1}^{N} p(z_i|\theta, y_i, x_i).$$

As such, it is natural to consider variational distributions that factorize the same way (see fig. 2.) In this section, we confirm this intuition—we start with any joint variational family which can have any dependence between θ and $z_1, \cdots, z_N$. Then, we define a corresponding "branch" family where $z_1, \cdots, z_N$ are conditionally independent given θ. We show that inference using the branch family will be at least as accurate as using the joint family. We formalize the idea of branch distribution in the next definition.

Definition 1. Let q_ϕ^{Joint} be any variational family with parameters ϕ. We define $q_{v,w}^{\text{Branch}}$ to be a corresponding branch family if, for all ϕ, there exists $(v, \{w_i\}_{i=1}^N)$, such that,

$$q_{v,w}^{\text{Branch}}(\theta, z) = q_v(\theta) \prod_{i=1}^{N} q_{w_i}(z_i|\theta) = q_\phi^{\text{Joint}}(\theta) \prod_{i=1}^{N} q_\phi^{\text{Joint}}(z_i|\theta). \tag{7}$$

Given a joint distribution, a branch distribution can always be defined by choosing w and v_i as the components of ϕ that influence $q_\phi^{\text{Joint}}(\theta)$ and $q_\phi^{\text{Joint}}(z_i|\theta)$, respectively, and choosing $q_w(\theta)$ and $q_{w_i}(z_i|\theta)$ correspondingly. However, the choice is not unique (for instance, the parameterization can require transformations—different transformations can create different variants.)

Figure 2: Graphical model for $q_{v,w}^{\text{Branch}}$ as in eq. (7).

The idea to use $q_{v,w}^{\text{Branch}}$ is natural [12, 2]. However, one might question if the branch variational family is as good as the original q_ϕ^{Joint}; in theorem 2, we establish that this is indeed true.

Theorem 2. Let p be a HBD, and $q_\phi^{\text{Joint}}(\theta, z)$ be a joint approximation family parameterized by ϕ. Choose a corresponding branch variational family $q_{v,w}^{\text{Branch}}(\theta, z)$ as in definition 1. Then,

$$\min_{v,w} KL\left(q_{v,w}^{\text{Branch}} \| p\right) \leq \min_{\phi} KL\left(q_\phi^{\text{Joint}} \| p\right).$$

We stress that $q_{v,w}^{\text{Branch}}$ is a new variational family derived from but not identical to q_ϕ^{Joint}. Theorem 2 implies that we can optimize a branched variational family $q_{v,w}^{\text{Branch}}$ without compromising the quality of approximation (see Appendix B for proof.) In the following corollary, we apply Theorem 2 to a joint Gaussian to show that using a branch Gaussian will be equally accurate.

Corrolary 3. Let p be a HBD, and let $q_\phi^{\text{Joint}}(\theta, z) = \mathcal{N}\left((\theta, z)|\mu, \Sigma\right)$ be a joint Gaussian approximation (with $\phi = (\mu, \Sigma)$). Choose a variational family

$$q_{v,w}^{\text{Branch}}(\theta, z) = \mathcal{N}(\theta|\mu_0, \Sigma_0) \prod_{i=1}^{N} \mathcal{N}(z_i|\mu_i + A_i\theta,\ \Sigma_i)$$

with $v = (\mu_0, \Sigma_0)$ and $w_i = (\mu_i, \Sigma_i, A_i)$. Then, $\min_{v,w} KL\left(q_{v,w}^{\text{Branch}} \| p\right) \leq \min_{\phi} KL\left(q_\phi^{\text{Joint}} \| p\right).$

In the above corollary, the structured family $q_{v,w}^{\text{Branch}}$ is chosen such that it can represent any branched Gaussian distribution. Notice, the mean of the conditional distribution is an affine function of θ. This affine relationship appears naturally when you factorize the joint Gaussian over (θ, z). For more details see Appendix D.

4.1 Subsampling in branch distributions

In this section, we show that if p is an HBD and $q_{v,w}^{\text{Branch}}$ is as in definition 1, we can estimate ELBO using local observations and scale better. Consider the ELBO

$$\mathcal{L}\left(q_{v,w}^{\text{Branch}} \| p\right) = \mathbb{E}_{q_{v,w}^{\text{Branch}}(\theta, z)} \left[\log \frac{p(\theta, z, y|x)}{q_{v,w}^{\text{Branch}}(\theta, z)}\right]$$

$$= \mathbb{E}_{q_v(\theta)} \left[\log \frac{p(\theta)}{q_v(\theta)}\right] + \sum_{i=1}^{N} \mathbb{E}_{q_v(\theta)} \mathbb{E}_{q_{w_i}(z_i|\theta)} \left[\log \frac{p(z_i, y_i|\theta, x_i)}{q_{w_i}(z_i|\theta)}\right]. \tag{8}$$

$$\begin{aligned} &\texttt{JointELBO}(\phi, y, x) \\ &\quad \theta, z \sim q_\phi^{\text{Joint}}(\theta, z) \\ &\quad \widehat{\mathcal{L}} \leftarrow \log \frac{p(\theta, z, y | x)}{q_\phi^{\text{Joint}}(\theta, z)} \end{aligned}$$

(a) Estimation with q_ϕ^{Joint} as in eq. (6)

$$\begin{aligned} &\texttt{BranchELBO}(v, w, y, x) \\ &\quad \theta \sim q_v(\theta) \\ &\quad z_i \sim q_{w_i}(z_i | \theta) \text{ for } i \in \{1, \cdots, N\}. \\ &\quad \widehat{\mathcal{L}} \leftarrow \log \frac{p(\theta)}{q_v(\theta)} + \sum_{i=1}^{N} \log \frac{p(z_i, y_i | \theta, x_i)}{q_{w_i}(z_i | \theta)} \end{aligned}$$

(b) Estimation with $q_{v,w}^{\text{Branch}}$ as in eq. (9)

$$\begin{aligned} &\texttt{SubSampledBranchELBO}(v, w, y, x) \\ &\quad \theta \sim q_v(\theta) \\ &\quad B \sim \texttt{Minibatch(B)} \\ &\quad z_i \sim q_{w_i}(z_i | \theta) \text{ for } i \in B \\ &\quad \widehat{\mathcal{L}} \leftarrow \log \frac{p(\theta)}{q_v(\theta)} + \frac{N}{|B|} \sum_{i \in B} \log \frac{p(z_i, y_i | \theta, x_i)}{q_{w_i}(z_i | \theta)} \end{aligned}$$

(c) Estimation with $q_{v,w}^{\text{Branch}}$ as in eq. (10)

$$\begin{aligned} &\texttt{AmortizedSubSampledBranchELBO}(v, u, y, x) \\ &\quad \theta \sim q_v(\theta) \\ &\quad B \sim \texttt{Minibatch(B)} \\ &\quad w_i \leftarrow \texttt{net}_u(x_i, y_i) \text{ for } i \in B \\ &\quad z_i \sim q_{w_i}(z_i | \theta) \text{ for } i \in B \\ &\quad \widehat{\mathcal{L}} \leftarrow \log \frac{p(\theta)}{q_v(\theta)} + \frac{N}{|B|} \sum_{i \in B} \log \frac{p(z_i, y_i | \theta, x_i)}{q_{w_i}(z_i | \theta)} \end{aligned}$$

(d) Estimation with $q_{v,u}^{\text{Amort}}$ for p as in eq. (2)

Figure 3: Pseudo codes for ELBO estimation with different variational methods; $w = \{w_i\}_{i=1}^N$, $y = \{y_i\}_{i=1}^N$, and $y_i = \{y_{ij}\}_{j=1}^{n_i}$ (x is defined similar to y.) (a) Estimates ELBO for a joint approximation; (b) to (d) estimate ELBO for branch approximations; (c, d) use subsampling to estimate ELBO; (d) uses amortized conditionals; (a) to (c) work for any HBD, and (d) assumes p is a symmetric HBD as in eq. (2). For models where $n_i > 1$, we use the $\texttt{net}_u$ as in fig. 4. Minibatch is some distribution over the set of possible minibatches and $|B|$ denotes the number of samples in a minibatch B.

Without assuming special structure (e.g. conjugacy) the above expectations will not be available in closed form. To estimate the ELBO, let $(\theta, \{z_i\}_{i=1}^N) \sim q_{v,w}^{\text{Branch}}$. Then, an unbiased estimator is

$$\widehat{\mathcal{L}} = \log \frac{p(\theta)}{q_v(\theta)} + \sum_{i=1}^{N} \left[\log \frac{p(z_i, y_i | \theta, x_i)}{q_{w_i}(z_i | \theta)} \right]. \tag{9}$$

Unlike the joint estimator of eq. (6), one can subsample the terms in eq. (9) to create a new unbiased estimator. Let B be randomly selected minibatch of indices from $\{1, 2, \ldots, N\}$. Then,

$$\widehat{\mathcal{L}} = \log \frac{p(\theta)}{q_v(\theta)} + \frac{N}{|\mathsf{B}|} \sum_{i \in \mathsf{B}} \left[\log \frac{p(z_i, y_i | \theta, x_i)}{q_{w_i}(z_i | \theta)} \right], \tag{10}$$

is another unbiased estimator of ELBO. In figs. 3b and 3c, we present the complete pseudocodes for ELBO estimation with and without subsampling in branch distributions.

Unsurprisingly, the same summation structure appears for gradients estimators of branch ELBO, allowing for efficient gradient estimation. With subsampled evaluation and training, branch distributions are immensely computationally efficient—in our experiments, we scale to models with 10^3 *times* more latent variables by switching to branch approximations (see fig. 6).

While branch distributions are immensely more scalable than joint approximations, the number of parameters still scales as $\mathcal{O}(N)$. In the next section, we demonstrate that for symmetric HBDs, we can share parameters for the local conditionals (amortize) to allow further scalability.

5 Amortized branch approximations

In this section, we discuss how one can amortize the local conditionals of a branch approximations when the target HBD is symmetric (see eq. (2).) We first formally introduce the amortized branch distributions in the next definition and then justify the amortization for symmetric HBD.

Definition 4. Let q_ϕ^{Joint} be a joint approximation and let $q_{v,w}^{\text{Branch}}$ be as in definition 1. Suppose $\texttt{net}_u(x_i, y_i)$ is some parameterized map (with parameters u) from local observations (x_i, y_i) to space of w_i. Then,

$$q_{v,u}^{\text{Amort}}(\theta, z) = q_v(\theta) \prod_{i=1}^{N} q_{\texttt{net}_u(x_i, y_i)}(z_i | \theta) \tag{11}$$

152 is a corresponding amortized branch distribution.

153 The idea to amortize is natural once you examine the optimization for symmetric HBDs. Consider
154 the optimization for objective in eq. (8).

$$\max_{v,w} \mathcal{L}\left(q_{v,w}^{\text{Branch}}\|p\right) = \max_{v,w} \left[\underset{q_v(\theta)}{\mathbb{E}} \left[\log \frac{p\left(\theta\right)}{q_v\left(\theta\right)}\right] + \sum_{i=1}^{N} \underset{q_v(\theta)}{\mathbb{E}} \underset{q_{w_i}(\mathsf{z}_i|\theta)}{\mathbb{E}} \left[\log \frac{p\left(\mathsf{z}_i, y_i|\theta, x_i\right)}{q_{w_i}\left(\mathsf{z}_i|\theta\right)}\right] \right]$$

$$= \max_{v} \left[\underset{q_v(\theta)}{\mathbb{E}} \left[\log \frac{p\left(\theta\right)}{q_v\left(\theta\right)}\right] + \sum_{i=1}^{N} \max_{w_i} \underset{q_v(\theta)}{\mathbb{E}} \underset{q_{w_i}(\mathsf{z}_i|\theta)}{\mathbb{E}} \left[\log \frac{p\left(\mathsf{z}_i, y_i|\theta, x_i\right)}{q_{w_i}\left(\mathsf{z}_i|\theta\right)}\right] \right].$$

155 The crucial observation in the above equation is that for any given v, the optimal solution of inner
156 optimization depends only on local data points (x_i, y_i), i.e.,

$$w_i^* = \operatorname*{argmax}_{w_i} \underset{q_v(\theta)}{\mathbb{E}} \underset{q_{w_i}(\mathsf{z}_i|\theta)}{\mathbb{E}} \left[\log \frac{p\left(\mathsf{z}_i, y_i|\theta, x_i\right)}{q_{w_i}\left(\mathsf{z}_i|\theta\right)}\right]. \tag{12}$$

157 Now, notice that if p and $q_{v,w}^{\text{Branch}}$ have symmetric conditionals, then, for each i, we solve the same
158 optimization over w_i, just with different parameters y_i and x_i. Thus, one could replace the optimiza-
159 tion over w_i with an optimization over a parameterized function from (x_i, y_i) to the space of w_i.
160 Formally, when the network $\texttt{net}_u$ is sufficiently capable, we make the following claim.

161 **Claim 5.** Let p be a symmetric HBD and let q_ϕ^{Joint} be some joint approximation. Let $q_{v,u}^{\text{Amort}}$ be as
162 in definition 1. Suppose that for all v, there exists a u, such that,

$$\texttt{net}_u(x_i, y_i) = \operatorname*{argmax}_{w_i} \underset{q_v(\theta)}{\mathbb{E}} \underset{q_{w_i}(\mathsf{z}_i|\theta)}{\mathbb{E}} \left[\log \frac{p\left(\mathsf{z}_i, y_i|\theta, x_i\right)}{q_{w_i}\left(\mathsf{z}_i|\theta\right)}\right]. \tag{13}$$

163 Then,

$$\min_u KL\left(q_{v,u}^{\text{Amort}}\|p\right) \leq \min_\phi KL\left(q_\phi^{\text{Joint}}\|p\right) \tag{14}$$

164

165 Note, we only amortize the conditional distribution $q_{w_i}\left(z_i|\theta\right)$ and leave $q_v\left(\theta\right)$ unchanged. In prac-
166 tice, of course, we do not have perfect amortization functions. The quality of the amortization
167 depends on our ability to parameterize and optimize a powerful neural network. In other words, we
168 make the following approximation

$$\texttt{net}_u(x_i, y_i) \approx \operatorname*{argmax}_{w_i} \underset{q_v(\theta)}{\mathbb{E}} \underset{q_{w_i}(\mathsf{z}_i|\theta)}{\mathbb{E}} \left[\log \frac{p\left(\mathsf{z}_i, y_i|\theta, x_i\right)}{q_{w_i}\left(\mathsf{z}_i|\theta\right)}\right]. \tag{15}$$

169 In our experiments, we found the amortized approaches work well even with moderately sized net-
170 works. Due to parameter sharing, the amortized approaches converge much faster than other alter-
171 natives (especially, true for larger models; see fig. 6 and table 2).

6 Amortized branch approximations for i.i.d. observations

173 In the previous section, we discussed how we could amortize branch approximations for symmetric
174 HBDs. However, in some applications, the construction of amortization network $\texttt{net}_u$ is not as
175 straightforward. Consider the case when we have a varying number of local i.i.d observations for
176 each local latent variable. In this section, we highlight the problem with naive amortization for
177 locally i.i.d HBDs, and present a simple solution to alleviate them.

178 Mathematically, for locally i.i.d HBDs we have $y_i = \{y_{ij}\}_{j=1}^{n_i}$ and $x_i = \{x_{ij}\}_{j=1}^{n_i}$, such that the
179 conditional over y_i factorizes as

$$p\left(y_i|x_i, z_i, \theta\right) = \prod_{j=1}^{n_i} p\left(y_{ij}|x_{ij}, z_i, \theta\right).$$

180 Now, if x_i and y_i are directly input to the amortization network $\texttt{net}_u$, the input size to the network
181 would change for different i (notice we have n_i observations for i^{th} local variable.) Another problem
182 is that the optimal variational parameters are invariant to the order in which the i.i.d. observations
183 are presented. For instance, consider two data points: $(x_i, y_i) = [(x_{i1}, y_{i1}), \ldots, (x_{in_i}, y_{in_i})]$ and
184 $(x_i', y_i') = [(x_{in_i}, y_{in_i}), \ldots, (x_{i1}, y_{i1})]$. A naive amortization scheme will evaluate very different
185 conditionals for these two data points because $\texttt{net}_u(x_i, y_i)$ and $\texttt{net}_u(x_i', y_i')$ will be different.

Table 1: All variational families used in our experiments. Σ denotes a generic covariance matrix and σ^2 denotes a diagonal covariance.

Gaussian Family	q_ϕ^{Joint} as in eq. (5)	$q_{v,w}^{\text{Branch}}$ as in eq. (7)	$q_{v,u}^{\text{Amort}}$ as in definition 4
Dense	$\mathcal{N}(\theta, z \mid \mu, \Sigma)$	$\mathcal{N}(\theta \mid \mu_0, \Sigma_0) \prod_{i=1}^{N} \mathcal{N}(z_i \mid \mu_i + A_i\theta, \Sigma_i)$	$\mathcal{N}(\theta \mid \mu_0, \Sigma_0) \prod_{i=1}^{N} \mathcal{N}(z_i \mid \mu_i + A_i\theta, \Sigma_i)$
	$\phi = (\mu, \Sigma)$	$v = (\mu_0, \Sigma_0), w_i = (\mu_i, A_i, \Sigma_i)$	$v = (\mu_0, \Sigma_0), (\mu_i, A_i, \Sigma_i) = \texttt{net}_u(x_i, y_i)$
Block Diagonal	$\mathcal{N}(\theta \mid \mu_0, \Sigma_0)\mathcal{N}(z \mid \mu_1, \Sigma_1)$	$\mathcal{N}(\theta \mid \mu_0, \Sigma_0) \prod_{i=1}^{N} \mathcal{N}(z_i \mid \mu_i, \Sigma_i)$	$\mathcal{N}(\theta \mid \mu_0, \Sigma_0) \prod_{i=1}^{N} \mathcal{N}(z_i \mid \mu_i, \Sigma_i)$
	$\phi = (\mu_0, \mu_1, \Sigma_0, \Sigma_1)$	$v = (\mu_0, \Sigma_0), w_i = (\mu_i, \Sigma_i)$	$v = (\mu_0, \Sigma_0), (\mu_i, \Sigma_i) = \texttt{net}_u(x_i, y_i)$
Diagonal	$\mathcal{N}(\theta, z \mid \mu, \sigma^2)$	$\mathcal{N}(\theta \mid \mu_0, \sigma_0^2) \prod_{i=1}^{N} \mathcal{N}(z_i \mid \mu_i, \sigma_i^2)$	$\mathcal{N}(\theta \mid \mu_0, \sigma_0^2) \prod_{i=1}^{N} \mathcal{N}(z_i \mid \mu_i, \sigma_i^2)$
	$\phi = (\mu, \sigma^2)$	$v = (\mu_0, \sigma_0^2), w_i = (\mu_i, \sigma_i^2)$	$v = (\mu_0, \sigma_0^2), (\mu_i, \sigma_i^2) = \texttt{net}_u(x_i, y_i)$

To deal with both issues: variable length input and permutation invariance, we suggest learning a "feature network" and "pooling function" based amortization network; this is reminiscent of "deep sets" [31] albeit here intended not just to enforce permutation invariance but also to deal with inputs of different sizes. Firstly, a feature network $\texttt{feat\_net}$ takes each (x_{ij}, y_{ij}) pair and returns a vector of features e_j. Secondly, a pooling function $\texttt{pool}$ takes the collection $\{e_j\}_{j=1}^{n_i}$ and achieves the two aims. First, it collapses n_i feature vectors into a single fixed-sized feature e (with the same dimensions as e_j). Second, pooling is invariant by construction to the order of observations (for example, pooling function would take a dimension-wise mean or sum across j.) Finally, this pooled feature vector e is input to another network $\texttt{param\_net}$ that returns the final parameters w_i. The pseudocode for a $\texttt{net}_u$ with feature networks is available in fig. 4. In table 3, in appendix, we summarize the applicability of proposed variational methods to different HBD variants.

$\texttt{net}_u(x_i, y_i)$
    for j **in** $\{1, 2, \ldots, n_i\}$
        $e_j \leftarrow \texttt{feat\_net}_u(x_{ij}, y_{ij})$
    $e \leftarrow \texttt{pool}(\{e_j\}_{j=1}^{n_i})$
    $w_i \leftarrow \texttt{param\_net}_u(e)$
    return w_i

Figure 4: Psuedocode for $\texttt{net}_u$ for locally i.i.d symmetric HBD.

7 Experiments

We conduct experiments on a synthetic and a real-world problem. For each, we consider three inference methods: using a joint distribution, using a branch variational approximation, and using our amortized approach. For each method, we consider three variational approximations a completely diagonal Gaussian, a block-diagonal Gaussian (with blocks for θ and z) and a dense Gaussian; see fig. 5 for a visual. (For each choice of a joint distribution, the corresponding $q_{v,w}^{\text{Branch}}$ is used for the branch variational approximation and the corresponding $q_{v,u}^{\text{Amort}}$ for the amortized approach; see table 1 for details.)

Figure 5: Visualization of covariances of dense, block-diagonal, and diagonal Gaussians. For each, we experiment with q_ϕ^{Joint}, $q_{v,w}^{\text{Branch}}$, and $q_{v,u}^{\text{Amort}}$ methods.

We provide complete experimental details in Appendix F. In Appendix A, we discuss some of the observations we had during experimentation involving parameterization, $\texttt{feat-net}$ architecture, batch-size selection, initialization, and gradient estimators.

7.1 Synthetic problem

The aim of the synthetic experiment is to work with models where we have access to closed-form posterior (and the marginal likelihood.) If the variational family contains the posterior, one can expect the methods to perform close to ideal (provided we can optimize well.)

For our experiments, we use the following hierarchical regression model

$$p(\theta, z, y \mid x) = \mathcal{N}(\theta \mid 0, I) \prod_{i=1}^{N} \mathcal{N}(z_i \mid \theta, I) \prod_{j=1}^{n_i} \mathcal{N}(y_{ij} \mid x_{ij}^\top z_i), I), \tag{16}$$

where $\mathcal{N}$ denotes a Gaussian distribution, and I is an identity matrix (see Appendix F.2 for posterior and the marginal closed-form expressions.)

To demonstrate the performance of our methods, we experiment with three different problems scale (correspond to three different models with $N = 10$, 1K, and 100K.) Synthetic data is created using forward sampling for each of the scale variants independently. We avoid any test data and metrics for the synthetic problem as the log-marginal is known in closed form. The inference results are present in fig. 7 (in appendix.) In all cases, amortized distributions perform favorably when compared to branch and joint distributions.

7.2 MovieLens

Next, we test our method on the MovieLens25M [11], a dataset of 25 million movie ratings for over 62,000 movies, rated by 162,000 users, along with a set of features (tag relevance scores [30]) for each movie.

Purely, to make experiments more efficient on GPU hardware, we pre-process the data to drop users with more than 1,000 ratings—leaving around 20M ratings. Also, for the sake of efficiency, we PCA the movie features to reduce their dimensionality to 10. We used a train-test split such that, for each user, one-tenth of the ratings are in the test set. This gives us $\approx$ 18M ratings for training (and $\approx$ 2M ratings for testing.)

We use the hierarchical model

$$p(\theta, z, y | x) = \mathcal{N}(\theta | 0, I) \prod_{i=1}^{N} \mathcal{N}(z_i | \mu(\theta), \Sigma(\theta)) \prod_{j=1}^{n_i} \mathcal{B}(y_{ij} | \text{sigmoid}(x_{ij}^\top z_i)), \tag{17}$$

where θ represents distribution over user preferences; for instance, θ might represent that users who like action films tend to also like thrillers but tend to dislike musicals; z_i determine the user specific preference; x_{ij} are the features of the j^{th} movie rated by user i; y_{ij} is the binary movie ratings; n_i is the number of movies rated by user i, and $\mathcal{B}$ denotes a Bernoulli distribution. Here, μ and Σ are functions of θ, such that, for $\theta = [\theta_\mu, \theta_\Sigma]$, we have

$$\mu(\theta) = \theta_\mu, \qquad \text{and} \qquad \Sigma(\theta) = \text{tril}(\theta_\Sigma)^\top \text{tril}(\theta_\Sigma)$$

where tril is a function that transforms an unconstrained vector into a lower-triangular positive Cholesky factor. As movie features $x_{ij} \in \mathbb{R}^{10}$, we have $\theta_\mu \in \mathbb{R}^{10}, \theta_\Sigma \in \mathbb{R}^{55}$, and $z_i \in \mathbb{R}^{10}$. Note that as Σ depends on θ, and the likelihood is Bernoulli, the model is non-conjugate.

For inference, we use the methods as described in table 1. Note, we hold the amortization network architecture constant across the scales–the number of parameters remains fixed for $q_{v,u}^{\text{Amort}}$ (for all Gaussian variants) while the number of parameters scale as $\mathcal{O}(N)$ for $q_{v,w}^{\text{Branch}}$ (see appendix D for more details.)

Table 2: Inference results for the MovieLens25M problem. For both metrics, we draw a fresh batch of 10,000 samples from the final posterior. All values are in nats (higher is better).

Metric		Final ELBO			Test likelihood		
$\approx$ # train ratings		2.5K	180K	18M	2.5K	180K	18M
Methods (see table 1)							
Dense	q_ϕ^{Joint}	-1572.31			-166.37		
	$q_{v,w}^{\text{Branch}}$	-1572.39	-1.0368e+05	-1.1413e+07	-166.66	-11054.43	-1.3046e+06
	$q_{v,u}^{\text{Amort}}$	-1572.45	-1.0352e+05	-1.0665e+07	-166.64	-10976.38	-1.1476e+06
Block	q_ϕ^{Joint}	-1579.04			-167.36		
Diagonal	$q_{v,w}^{\text{Branch}}$	-1579.05	-1.0350e+05	-1.1078e+07	-166.97	-10987.17	-1.2538e+06
	$q_{v,u}^{\text{Amort}}$	-1579.06	-1.0353e+05	-1.0665e+07	-166.96	-10975.96	-1.1484e+06
Diagonal	q_ϕ^{Joint}	-1592.59			-167.39		
	$q_{v,w}^{\text{Branch}}$	-1592.64	-1.0428e+05	-1.1325e+07	-167.31	-10977.95	-1.2713e+06
	$q_{v,u}^{\text{Amort}}$	-1592.64	-1.0430e+05	-1.0736e+07	-167.29	-10980.75	-1.1497e+06

In fig. 6, we plot the training time ELBO trace, and in table 2, we present the final training ELBO and test likelihood values. We approximate the test likelihood $p(y^{\text{test}}|x^{\text{test}}, x, y)$ with $\mathbb{E}_q\left[p(y^{\text{test}}|x^{\text{test}}, q)\right]$, and draw a fresh batch of 10,000 samples to approximate the expectation (see Appendix F for complete details.) For the smaller model, the amortized and branch approaches perform similar to the joint approach for all three variational approximations; this supports theorem 2 and claim 5. For the moderate size model, the branch and amortize approaches are very comparable to each other, while joint approaches fail to scale. For the large model (18M ratings), amortized approaches are significantly better than branch methods. We conjecture this is because parameter sharing in amortized approaches improves convergence for models where batch size is smaller compared to total iterates–true only for large model.

Figure 6: Training ELBO trace for the MovieLens25M problem. Top to bottom: dense, block diagonal, and diagonal Gaussian (for each, we have q_ϕ^{Joint}, $q_{v,w}^{\text{Branch}}$, and $q_{v,u}^{\text{Amort}}$ method.) Left to right: small, moderate, and large scale of the MovieLens25M problem. For clarity, we plot the exponential moving average of the training ELBO trace with a smoothing value of 0.001. These traces correspond to the values reported in table 2.

8 Discussion

In this paper, we present structured amortized variational inference scheme that can scale to large hierarchical models without losing benefits of joint approximations. Such models are ubiquitous in social sciences, ecology, epidemiology, and other fields. Our ideas can not only inspire further research in inference but also provide a formidable baseline for applications.

References

[1] Abhinav Agrawal, Daniel R. Sheldon, and Justin Domke. Advances in black-box VI: normalizing flows, importance weighting, and optimization. In *NeurIPS 2020*, 2020.

[2] Luca Ambrogioni, Kate Lin, Emily Fertig, Sharad Vikram, Max Hinne, Dave Moore, and Marcel Gerven. Automatic structured variational inference. In *International Conference on Artificial Intelligence and Statistics*, pages 676–684. PMLR, 2021.

[3] David M Blei. Probabilistic topic models. *Communications of the ACM*, 55(4):77–84, 2012.

[4] David M Blei, Andrew Y Ng, and Michael I Jordan. Latent dirichlet allocation. *the Journal of machine Learning research*, 3:993–1022, 2003.

[5] James Bradbury, Roy Frostig, Peter Hawkins, Matthew James Johnson, Chris Leary, Dougal Maclaurin, George Necula, Adam Paszke, Jake VanderPlas, Skye Wanderman-Milne, and Qiao Zhang. JAX: composable transformations of Python+NumPy programs, 2018. URL http://github.com/google/jax.

[6] Noel Cressie, Catherine A Calder, James S Clark, Jay M Ver Hoef, and Christopher K Wikle. Accounting for uncertainty in ecological analysis: the strengths and limitations of hierarchical statistical modeling. *Ecological Applications*, 19(3):553–570, 2009.

[7] Justin Domke. Provable smoothness guarantees for black-box variational inference. In *International Conference on Machine Learning*, pages 2587–2596. PMLR, 2020.

[8] Andrew Gelman. *Red state, blue state, rich state, poor state: Why Americans vote the way they do-expanded edition*. Princeton University Press, 2009.

[9] Andrew Gelman and Jennifer Hill. *Data analysis using regression and multilevel/hierarchical models*. Cambridge university press, 2006.

[10] Andrew Gelman and Aki Vehtari. What are the most important statistical ideas of the past 50 years? *arXiv preprint arXiv:2012.00174*, 2020.

[11] F Maxwell Harper and Joseph A Konstan. The movielens datasets: History and context. *Acm transactions on interactive intelligent systems (tiis)*, 5(4):1–19, 2015.

[12] Matthew D. Hoffman and David M. Blei. Stochastic structured variational inference. In Guy Lebanon and S. V. N. Vishwanathan, editors, *Proceedings of the Eighteenth International Conference on Artificial Intelligence and Statistics, AISTATS 2015, San Diego, California, USA, May 9-12, 2015*, volume 38 of *JMLR Workshop and Conference Proceedings*. JMLR.org, 2015. URL http://proceedings.mlr.press/v38/hoffman15.html.

[13] Matthew D Hoffman, David M Blei, Chong Wang, and John Paisley. Stochastic variational inference. *Journal of Machine Learning Research*, 14(5), 2013.

[14] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. 2015.

[15] Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

[16] John D Lafferty and David M Blei. Correlated topic models. *Advances in neural information processing systems*, 18:147–154, 2006.

[17] Andrew B Lawson. *Bayesian disease mapping: hierarchical modeling in spatial epidemiology*. Chapman and Hall/CRC, 2008.

[18] Jeffrey R Lax and Justin H Phillips. The democratic deficit in the states. *American Journal of Political Science*, 56(1):148–166, 2012.

[19] Yew Jin Lim and Yee Whye Teh. Variational bayesian approach to movie rating prediction. In *Proceedings of KDD cup and workshop*, volume 7, pages 15–21. Citeseer, 2007.

[20] George Papamakarios, Eric Nalisnick, Danilo Jimenez Rezende, Shakir Mohamed, and Balaji Lakshminarayanan. Normalizing flows for probabilistic modeling and inference. *arXiv preprint arXiv:1912.02762*, 2019.

[21] Rajesh Ranganath, Sean Gerrish, and David Blei. Black Box Variational Inference. In *AISTATS*, 2014.

[22] Danilo Rezende and Shakir Mohamed. Variational inference with normalizing flows. In *International Conference on Machine Learning*, pages 1530–1538. PMLR, 2015.

[23] Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. In *ICML*, 2014.

[24] Geoffrey Roeder, Yuhuai Wu, and David Duvenaud. Sticking the landing: Simple, lower-variance gradient estimators for variational inference. In *NIPS*, 2017.

[25] Ruslan Salakhutdinov and Andriy Mnih. Bayesian probabilistic matrix factorization using markov chain monte carlo. In *Proceedings of the 25th international conference on Machine learning*, pages 880–887, 2008.

[26] Rishit Sheth and Roni Khardon. Monte carlo structured svi for two-level non-conjugate models. *arXiv preprint arXiv:1612.03957*, 2016.

[27] Michael E Tipping and Christopher M Bishop. Probabilistic principal component analysis. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 61(3):611–622, 1999.

[28] Michalis Titsias and Miguel Lázaro-Gredilla. Doubly stochastic variational bayes for non-conjugate inference. In *International conference on machine learning*, pages 1971–1979. PMLR, 2014.

[29] Robert J Vallerand. Toward a hierarchical model of intrinsic and extrinsic motivation. *Advances in experimental social psychology*, 29:271–360, 1997.

[30] Jesse Vig, Shilad Sen, and John Riedl. The tag genome: Encoding community knowledge to support novel interaction. *ACM Transactions on Interactive Intelligent Systems (TiiS)*, 2(3): 1–44, 2012.

[31] Manzil Zaheer, Satwik Kottur, Siamak Ravanbakhsh, Barnabas Poczos, Russ R Salakhutdinov, and Alexander J Smola. Deep sets. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper/2017/file/f22e4747da1aa27e363d86d40ff442fe-Paper.pdf.