Explaining the Decisions of Neural Networks with Latent Sympathetic Examples

Abstract

Neural networks make mistakes. The reason why a mistake is made often remains a mystery. As such neural networks often are considered a black box. It would be useful to have a method that can give an explanation that is intuitive to a user as to why an image is misclassified. In this paper we develop a method for explaining the mistakes of a classifier model by visually showing what must be added to an image such that it is correctly classified. Our work combines the fields of adversarial examples, generative modeling and a correction technique based on difference target propagation to create an technique that creates explanations of why an image is misclassified. In this paper we explain our method and demonstrate it on MNIST and CelebA. This approach could aid in demystifying neural networks for a user.

1 Introduction

Given the increasingly widespread use of deep learning in real-world applications, it is becoming important to be able to understand why a neural network makes a mistake when it happens.

For example, suppose a self-driving car, controlled by a neural network, makes a sudden decision to stop in the middle of the road, because it mis-identified a tree as a pedestrian who was about to cross. How could we understand that the reason for this decision was a poorly-trained pedestrian detector?

One approach we could take to"explain" these errors would be to use Gradient Descent learn a perturbation to the misclassified image such that it is correctly classified. We could then observe the perturbation and see what needed to be modified in the input to produce the correct class. In our example this might correspond to perturbing the car's camera image at the time of the stop, to minimize the strength of the "stop" output. We could then observe what change to the image was needed to avoid the sudden stop. We might observe that the tree which was mis-identified as a person becomes less person-like and conclude that a faulty pedestrian-detector was to blame.

This "Gradient Descent on the input" approach taken by (Szegedy et al., 2013), in which they introduced the notion of adversarial examples. Adversarial examples are created by perturbing an image so that it is misclassified. The surprising finding of this paper was that it is almost always possible to create an imperceptibly small perturbation to an image that changes the output class to any target value. These perturbations tend to look like white noise to the naked eye, and tell us nothing about what caused the image to be classified as it was.

Ideally, for the user to understand why a certain image is misclassified, the perturbations should be constrained to only the parts of an image relevant to the class and must be interpretable to the user.

In this paper, we generate explanations that align with human perception and are meaningful using generative models that perturb the features of a misclassified image such that it is correctly classified. The paper is structured in the following manner. In section 2 we introduce our proposed method. In section 3 the experiments are discussed. Finally, in section 4 we discuss the related work and in section 5 we will conclude.

2 METHOD NEW

2.1 TERMINOLOGY

Our method (described visually in Figure 1), consists of a **classifier** $(c(\cdot))$ and a generative model, both trained separately on the same dataset. We use the cross entropy error for our classifier denoted as $CE(\cdot, y)$. The generative model consists of an **encoder** $(e(\cdot))$ and a **generator** $(g(\cdot))$. We refer to the **original image** as x and the correct class for the original image as y. Once the original image has been encoded to the latent space of the generative model $(e(x))$, we refer to it as z. The reconstruction of z we call the **reconstructed image** and refer to as $g(z)$. Furthermore, we call $z + \epsilon$ the perturbation and $g(z + \epsilon)$ the **perturbed reconstruction**. Lastly, we call the result of our method x' the perturbed image.

2.2 OUR METHOD

Formally, the problem we try to solve can be defined in the following manner. We have a misclassified image x (i.e.. $c(x) \neq y$). We wish to generate x', a perturbed version of x, such that $c(x') = y$. We define the perturbed reconstruction according to equation 1.

$$x' = g(z + \epsilon) + x - g(z) \tag{1}$$

We can see that if ϵ is 0, we are left with x. As such, so long as g is smooth, the condition $\lim_{\epsilon \to 0} x' = x$ holds. This equation is inspired by Difference Target Propagation, proposed by (Lee et al., 2015), where they used it to propagate a perturbation backwards through a network. The goal of our method is to firstly, minimize the Cross Entropy: $CE(c(x'), y)$ and secondly to keep the euclidean norm of ϵ as small as possible to limit the amount of features added to the original image. We accomplish the first goal by using gradient descent to learn the perturbation ϵ. As such epsilon is updated iteratively by formula 2. Where λ is a small constant learning rate.

$$\epsilon_{n+1} = \epsilon_n - \lambda \frac{\partial CE(c(x'), y)}{\partial \epsilon_n} \tag{2}$$

The second goal is accomplished by stopping the perturbation of ϵ once the condition $c(x') = y$ is met. A visual representation of our method is shown in figure 1. Because we are minimizing the $CE(x', y)$ using a generative model as opposed to maximizing it, we say that our method generates *Latent Sympathetic Examples*(LSE).

For this research we use a variational auto encoder (Kingma & Welling, 2013) as a generative model for MNIST and a combination of a variational auto encoder with a Generative Adversarial Network (Larsen et al., 2015) as a generative model for CelebA.

2.3 DEFINING WHAT IT MEANS TO EXPLAIN A CLASSIFICATION

Various definitions for explaining classifier decisions exist. We define an explanation for a classifier decision as; the perturbation that must be made to an image such that it is correctly classified. Subject to the conditions that:

1. The added parts are interpretable and visible by the naked eye.

2. The perturbation is close to the original encoded point in the latent space of the generative model. This is measured as the euclidean norm of ϵ.

As such our method tries to add only those parts of the reconstruction that are most relevant for the original image to be perturbed into the correct class.

Figure 1: Latent Sympathetic Examples (LSE). The original input image is encoded and reconstructed . x' is then perturbed, by iteratively calculating the gradients with respect to the correct class and updating ϵ. By keeping ϵ as small as possible, much of the reconstruction error should be canceled out by the reconstructed image.

3 EXPERIMENTS

3.1 MNIST

We trained two different Variational Auto Encoders on MNIST. The first had a 2 dimensional latent space, the second a 10 dimensional latent space. We used the former in order to create a latent space that was easy to display visually, alongside the $CE(c(x'), y)$ errors. We used the latter to determine the impact of the dimensionality of the latent space on the rate of success of our method to push images into another class . We attached a classifier to the variational auto encoders and trained it without updating the weights of the VAE's. In order to get an intuition of how our method works, we discuss the results created using the 2-D VAE and their respective conclusions. Firstly, the predictions made by the classifier from the $g(z)$ may differ from the predictions made using x'. In order to illustrate this we have plotted the predictions $c(g(z))$ and the predictions of $c(x')$ for various values of z and ϵ, respectively. $c(g(z))$ is shown in figure 2 and $c(x')$ is shown in figure 3. As can be seen the predicted values are quite different. Secondly, our method may not be able to always perturb to the target class. Figure 3 shows that our method may not work for all cases. The class '1' is missing for this image. If this is the target class, then our method will not be able to generate a LSE for it. Furthermore, our method sometimes gets stuck in a local minimum. In that case it may be possible to create an LSE, however the method is unable to reach it. An example of this happening is shown in appendix B.

In order to illustrate how our our method works part of the latent space of a successfully perturbed image has been plotted in figure 4. This figure also demonstrates how the perturbation is visible in the image space. As can be seen the image quality is quite coarse. The 10-D latent space yields qualitatively better results. These can be found in appendix A.

3.2 EFFECTS OF THE DIMENSIONALITY OF THE LATENT SPACE

Another goal of our research is to explore what the relation between the dimensionality of the latent space of the VAE is and effectiveness of our method to generate LSE's. We conduct 2 experiments in order to investigate this. Firstly, we perturb a set of misclassified examples and calculate the success rate. We define the success rate as what percentage of the time our method succeeds in finding a perturbation which pushes the perturbed image to the correct class. Secondly, we try to use our method to generate *latent adversarial examples* (LAE's), we take correctly classified images and try to perturb them to another class. We verify that our method should have more difficulty generating

Figure 2: This figure shows the predictions of $c(g(z))$ given a grid of values for z. As can be seen here every MNIST class is present. The star labels the point where z_1 and z_2 is zero and the triangle where the original image is encoded.

Figure 3: The predictions of $c(x')$ given a grid of values for ϵ. It can be seen that the classifier gives different results for the perturbed image x' as opposed to the image reconstruction $(g(z))$. Furthermore, not every class is available. Here it is impossible to perturb to a 1 for example. The star labels the point where z_1 and z_2 is zero and the triangle where the original image is encoded.

LAE's. However, it is only ineffective at generating LAE's using the 2D latent space, not the 10D latent space.

3.2.1 EFFECT OF DIMENSIONALITY VAE ON SUCCESS RATE LSE

In order to explore what the impact of the dimensionality of the latent space is on the success rate of LSE generation, 2 experiments are run. We attempt to perturb 87 misclassified examples for both experiments to their correct class. We used a λ of 0.1 . The method was successful in generating an LSE in 100% of the cases for the 10D VAE. The average euclidean distance from the original $e(x)$ points was 0.22. The 2D VAE successfully perturbed 78.16 % of the misclassified examples to their target class with an average euclidean distance of 0.10. This is evidence that the dimensionality of the latent space directly impacts the success rate positively.

3.2.2 EFFECT OF DIMENSIONALITY VAE ON SUCCESS RATE LAE

In this experiment we want to check whether this method has more success in creating an LSE then creating a LAE. Therefore, an experiment is run where the goal is to perturb 100 correctly classified examples to a class different from their target class. Before generating the LAE's the images which already had the label that was being targeted were removed. As such each of the 10 resulting experiments (each of the MNIST labels was targeted), had a different number of images. The weighted average success rate of the 2-D and 10-D VAE's are 22.34 % and 91.11% respectively, the weighted average L-2 distances are 0.52 and 1.53, respectively. It can be seen that the average success rates for generating latent adversarial examples for the 2-D and 10-D VAE differ by quite a large margin.

An explanation for this difference is that it is harder to get stuck in a 10-D latent space as compared to a 2-D latent space. Furthermore, it can be seen that the LSE generation is more effective compared to the LAE generation. This may be due to the distance being traveled in the latent space. Because the target class in the LAE case is farther away then it is for LSEs on average, the chances of getting stuck in a local minimum are higher.

3.3 CELEBA

In order to test whether this method can be applied to get meaningful results on a more complicated dataset we applied this method on CelebA. We trained a VAEGAN with a 1024-D latent space on the

Figure 4: The plot on the right shows the path of $z + \epsilon$. The different colored areas show the class predictions made for a given value of $z + \epsilon$. These areas are annotated with the corresponding class. Furthermore, the contours indicate the cross entropy error $c(x', y)$ gives for different areas in the latent space. The triangle is the starting point, where ϵ is a vector of zeros. The black dot is where the perturbed image was first classified as the correct class, the gold star is where we stopped the algorithm. Several points are annotated with the correct step number. These steps correspond to images on the left. Here the LSE and the perturbation $(x' - x)$ are shown. As can be seen these perturbations are quite coarse.

dataset. We trained several classifiers on the traits; "Receding Hairline", "Big Lips", "Wearing Earrings" and "Eyeglasses". Several examples of successfully explained examples are shown in figure 5. It can be seen that the method gives plausible explanations as to why an image is misclassified. We want to see whether the success depends on the trait. To this end we again calculated the success rates. These are shown in figure 1. As can be seen the success rate varies per trait, with the trait "Big Lips" performing significantly worse compared to the other traits. Furthermore, it is also interesting to see how the image changed as it was being perturbed to its correct class, this is shown in figure 6.

Table 1: Results of the search for LSEs using the method on 100 misclassified examples of the CelebA dataset. As can be seen, the success of the method is dependent on the trait. The search is performed over the 1024D latent space of a VAE-GAN trained on CelebA.

trait	Success Rate
Receding Hairline	95 %
Big Lips	30 %
Wearing Earrings	98 %
Eyeglasses	86 %

Figure 5: Examples of using LSE to perturb images to be correctly classified. The left image is the original image, the center image is the perturbation ($x' - x$) and the right image is the perturbed image. In the first row we see an image which is misclassified as not wearing earrings. By darkening the area around the earring and making the neck slightly lighter the image was correctly classified. The second image from the top is of an image where the person was misclassified as not having a receding hairline, after making the area below the hairline lighter the image was correctly classified. The third image from the top was misclassified as not wearing glasses. After adding blue to the area of the glasses, the image was correctly classified. The bottom image was misclassified as having a receding hairline, after perturbation and making the area below the hairline slightly darker, the image was correctly classified. The perturbations are normalized using min-max normalization, where the minimum is set to -1 and the maximum is set to 1.

4 RELATED WORK

The work done in our research is related to adversarial examples. Adversarial examples were introduced by (Szegedy et al., 2013). These examples take advantage of finding low probability pockets in the manifold on which the images are located, which fool the neural network into classifying the image in another class. As such an optimization problem can be formulated and solved to find adversarial examples. Such a problem can be optimized by means of various optimizers. For example, (Szegedy et al., 2013) used L-BFGS and (Goodfellow et al., 2014) took the sign of the gradients and used those to update the image until the prediction error was maximized. The prior two methods generate adversarial attacks in an untargeted fashion, meaning that they simply perturb to another unspecified class. Generating adversarial examples of a particular class is also possible. An example of this is the Deepfool algorithm (Moosavi-Dezfooli et al., 2016). More closely related to our work is the work done by (Kos et al., 2017). The authors devise several different adversarial attacks to change the encoding of an image in the latent space of a VAE or VAE-GAN such that the reconstructed image is different in a way that is advantageous to the attacker. Our work extends the prior work in the sense that it uses gradient descent to create an adversarial example and attempts to create an explanation of why a certain classification was made . However there are two key differences. Firstly, as was said before, our method attempts to help the trained classifier to minimize the prediction error, in contrast to adversarial examples. As such it can be said such examples are not adversarial at all but sympathetic to the classifier. Secondly, despite one of the goals of adversarial attacks being to better understand the input-output mapping of a neural network, classical adversar-

Figure 6: Plotting every fifth step through the latent space, alongside the perturbation $(x' - x)$. It can be seen that our method perturbs the original image to be correctly classified. The perturbations are normalized using min-max normalization, where the minimum is set to -1 and the maximum is set to 1.

ial examples are non-intuitive to any user. As such our method constrains the search for adversarial examples by means of a trained generative model. The intuition being that the search is constrained to features that should be interpretable to a user.

Our work was in part inspired by the Difference Target Propagation technique developed by (Lee et al., 2015). They propose an alternative to backpropagation for assigning credit in deep networks, called "target propagation". During training, target propagation sends targets, instead of gradients, backwards through the network, where the target is a small perturbation on the activation of the layer from the forward pass. The authors show that so long as layers are invertable, this will minimize the final loss. Because layers are in general not invertable, they apply a linear correction (which we borrow in Equation 1) to adjust shift the backpropagating target so that it remains close to the forward activation value. We use the same correction in our paper to ensure that as our latent perturbation becomes small, so does our perturbation in image space. i.e. $\lim_{\epsilon \to 0} x' = x$

5 DISCUSSION

In this paper we introduced a new method to construct an explanation for why a neural network has misclassified an image that is intuitive for a user to understand. We have demonstrated that the method gives meaningful results on both simple and more complicated datasets. Though the method looks promising, there is still a potential problem with applying it in the real world.

A problem may be that the method does not work well on all annotated traits that images may have. We already saw in the experiments on CelebA that the success rate depends on the trait. An explanation for this may be that the opinion of when an image has a certain trait may be ambiguous for annotators. For example, what constitutes somebody having big lips may vary among individuals to such an extent that only the extremes can be classified with certainty, making them hard to reach using gradient descent.

Another application for our method, besides providing explanations, is improving classifier performance. We can use our method to generate edge cases, by finding a class boundary and jumping in and out of it on various points. These edge cases can then be annotated by a human and used for training. A hurdle to widespread use of neural networks is that they can seem like black-boxes, when they feel it is difficult to understand why. We believe that this method will help overcome this problem by making the decisions explainable.

REFERENCES

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Jernej Kos, Ian Fischer, and Dawn Song. Adversarial examples for generative models. *arXiv preprint arXiv:1702.06832*, 2017.

Anders Boesen Lindbo Larsen, Søren Kaae Sønderby, Hugo Larochelle, and Ole Winther. Autoencoding beyond pixels using a learned similarity metric. *arXiv preprint arXiv:1512.09300*, 2015.

Dong-Hyun Lee, Saizheng Zhang, Asja Fischer, and Yoshua Bengio. Difference target propagation. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pp. 498–515. Springer, 2015.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, and Pascal Frossard. Deepfool: a simple and accurate method to fool deep neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2574–2582, 2016.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

A   10-D EXAMPLE

Figure 7: This plot shows the results of perturbing a misclassified image after different amounts of iterations. As can be seen the perturbation is qualitatively much more fine grained when compared to the perturbation in figure 4.

B   LOCAL MINIMUM

Figure 8: This plot shows our method getting stuck in a local minimum. The image was originally misclassified as a zero. The correct class, eight, exists, however a local minimum blocks the way. The white triangle is the starting point, the gold star is the end point of the search.