Attention-Based Guided Structured Sparsity of Deep Convolutional Neural Networks

Amirsina Torfi
Virginia Tech
atorfi@vt.edu

Rouzbeh A. Shirvani
Howard University
rouzbeh.asgharishir@bison.howard.edu

ABSTRACT

Network pruning is aimed at imposing sparsity in a neural network architecture by increasing the portion of zero-valued weights for reducing its size energy-efficiency consideration and increasing evaluation speed. In most of the conducted research efforts, the sparsity is enforced for network pruning without any attention to the internal network characteristics such as unbalanced outputs of the neurons or more specifically the distribution of the weights and outputs of the neurons. That may cause severe accuracy drop due to uncontrolled sparsity. In this work, we propose an attention mechanism that simultaneously controls the sparsity intensity and supervised network pruning by keeping important information bottlenecks of the network to be active. On CIFAR-10, the proposed method outperforms the best baseline method by 6% and reduced the accuracy drop by $2.6\times$ at the same level of sparsity.

1 INTRODUCTION

The main incentive behind model pruning is to impose sparsity by considerably reducing the number of effective parameters in a deep neural network while the accuracy drop is negligible (Han et al., 2015a; Denil et al., 2013). Different effective methods such as utilizing group lasso for learning sparse structure Yuan & Lin (2006), constrain the structure scale Liu et al. (2015), and regularizing multiple DNN structures known as Structured Sparsity Learning (SSL) (Wen et al., 2016) have been implemented for network pruning.

Unfortunately, there is a lack of addressing two issues for most of the conducted research efforts. First, pruning over-parameterized models with negligible accuracy drop, does not provide rigorous empirical proof for the effectiveness of the model since one can claim manually reducing the network size can generate relatively similar results (Zhu & Gupta, 2017). Second, imposing uncontrolled sparsity on under-parameterized baseline models may cause severe accuracy drop. Even if the network is over-parameterized, then imposing two much sparsity may cause the aforementioned issues.

In this work, we propose a controller mechanism for network pruning with the goal of (1) model compression for having few active parameters by enforcing group sparsity, (2) preventing the accuracy drop by controlling the sparsity of the network using an additional loss function by forcing a portion of the output neurons to stay alive in each layer of the network, and (3) capability of being incorporated for any layer type.

2 ATTENTION MECHANISM FOR GROUP SPARSE REGULARIZATION

The weights in a convolutional layer form a tensor as $W \in R^{C,[Width,Heigth],F}$ in which C is the number of input-channel, $[Width, Heigth]$ is the spatial size of the kernel, and F is the number of output filters (channels). In our proposed method, the objective is the minimization of the following loss function:

$$L(W) = L_{Softmax}(W) + \lambda_r.\ell_2(W) + \frac{1}{\sqrt{|G(W^l)|}}\{\lambda_{gs}.\sum_{l=1}^{N} L_{gs}(G(W^l)) + \lambda_{gv}.\sum_{l=1}^{N} L_{gv}^{-1}(G(W^l))\}$$

(1)

In the above equation, superscript l indicates the layer index[1], $L_{Softmax}(W)$ is the Softmax loss, $\ell_2(W)$ is the ℓ_2-regularization loss, and L_{gs} and L_{gv} are the group sparsity and group variance losses respectively. The value of $|G(W^l)|$ is essentially the number of channels for l_{th} layer and λ parameters are the hyper-parameter coefficients for the associated losses. The group sparsity regularization on a set of weights w which are split into M groups can be shown as follows:

$$L_{gs} = \sum_{j=1}^{M} \sqrt{\sum_{i=1}^{|w^{(j)}|} (w_i^{(j)})^2}$$

(2)

in which $w^{(j)}$ is the j_{th} group of partial weights in w and $|w^{(j)}|$ is the number of weights in the associated group. Group sparsity has been employed due to its ability for deactivating neurons[2] by forcing the weights in a group to become zero[3] (Yuan & Lin, 2006; Meier et al., 2008). The loss function objective leverages group variance loss in addition to group sparsity loss to *force the distribution of the grouped weights to be skewed*. In another word, this attention mechanism, *simply emphasize on a high variance with a concentration around zero*. This will supervise the sparsity mechanism to deliberately keep a portion of grouped weights to be much larger than the majority of the groups in order to simultaneously sparse the architecture and prevent the accuracy drop. Intuitively, this operation forces a portion of channels to be active for transferring sufficient information through the channels in the whole architecture (information bottlenecks). The visualization of this reasoning is demonstrated in Fig. 1. So basically, in a convolutional layer, each group is all set of weights which forms an output channel. Equivalently, in a fully-connected layer, a group is the set of outgoing (ingoing) weights from a neuron. The group-variance is defined as below:

$$L_{gv} = \frac{1}{M}\sum_{j=1}^{M}\left(\sqrt{\sum_{i=1}^{|w^{(j)}|} (w_i^{(j)})^2} - \frac{1}{M}\sum_{k=1}^{M}\sqrt{\sum_{i=1}^{|w^{(k)}|} (w_i^{(k)})^2}\right)^2$$

(3)

In case of enforcing sparsity of output channels of convolutional layers, $W_{F_j}^{(i)}$ is the j_{th} output channel of the i_{th} layer, then the $L_{gs} = \sum_{j=1}^{N_{filters}}\sqrt{\sum(W_{F_j}^{(i)})^2}$ and so the formulation of L_{gv} becomes straightforward. We call our method *Guided Structured Sparsity (GSS)* as it can be considered as an extension to SSL Wen et al. (2016) by having an attention mechanism using variational loss that is utilized for supervision of sparsity enforcement operation.

3 EXPERIMENTAL RESULTS

We evaluated our proposed method on two databases: MNIST LeCun et al. (2010), CIFAR-10 Krizhevsky & Hinton (2009).In all our experiments we enforce the sparsity on both fc-layers (Using group sparsity for neurons inputs) and convolutional layers (Using channel-wise structured sparsity for eliminating unimportant filters). In the experiment on MNIST dataset, LeNet architecture LeCun et al. (1998) has been utilized as a baseline for investigation of our proposed method with no data augmentation. For experiments on CIFAR-10 dataset, we use the *ConvNet* provided by TensorFlow Abadi et al. (2015). The utilized baseline model contains two convolutional layers with *Local Response Normalization (LRN)* Krizhevsky et al. (2012) followed by two fully connected layers[4].

---

[1] In the range of [1:N] in case of having N layers.

[2] Channels in convolutional layer

[3] This effectively deactivate the neuron by canceling its output

[4] Further details: `https://www.tensorflow.org/tutorials/deep_cnn`

Figure 1: Channel-wise grouping and enforcing sparsity in addition to variance loss for each channel.

Table 1: Error rate for Different Methods on MNIST and CIFAR-10 at the same level of sparsity (90%).

Method	Error(%)	
	MNIST	**CIFAR-10**
baseline [*no sparsity*]	0.93	15.51
$\ell_1 - regularization$	3.16	24.84
Network Pruning (Han et al., 2015b)	2.67	23.12
sparsely-connected networks (Ardakani et al., 2016)	1.91	18.71
SSL (Wen et al., 2016)	1.43	17.12
Variational-loss Guided Pruning [ours]	**1.21**	**16.13**

Table. 1 demonstrates the comparison results. It demonstrates that our method achieves less error rate compared to other methods.

Figure 2: The results for experiments on CIFAR-10 dataset at different sparsity levels.

Fig. 2 depicts a comparison at different level of sparsity. As it can be observed from the figure, our method demonstrates its superiority in higher levels of sparsity.

4 CONCLUSION

We have demonstrated that by utilization of the attention mechanism for sparsity supervision, a reduction of $2.6\times$ in accuracy drop has been obtained. Group sparse regularization has been performed on both convolutional and fully-connected layers for simultaneously imposing sparsity and demonstration of the adaptability of the proposed mechanism to both layer types. We anticipate greater superiority of our proposed method compared to the others by utilizing more complex models and evaluation on larger datasets. Besides, it is expected to show advancements in applications such as multi-modality fusion for which network pruning becomes of great importance due to the large number of weights and difficulties in learning a shared common feature space for all modalities (Ngiam et al., 2011; Zhao et al., 2015).

REFERENCES

Martín Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S. Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian Goodfellow, Andrew Harp, Geoffrey Irving, Michael Isard, Yangqing Jia, Rafal Jozefowicz, Lukasz Kaiser, Manjunath Kudlur, Josh Levenberg, Dan Mané, Rajat Monga, Sherry Moore, Derek Murray, Chris Olah, Mike Schuster, Jonathon Shlens, Benoit Steiner, Ilya Sutskever, Kunal Talwar, Paul Tucker, Vincent Vanhoucke, Vijay Vasudevan, Fernanda Viégas, Oriol Vinyals, Pete Warden, Martin Wattenberg, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. TensorFlow: Large-scale machine learning on heterogeneous systems, 2015. URL https://www.tensorflow.org/. Software available from tensorflow.org.

Arash Ardakani, Carlo Condo, and Warren J Gross. Sparsely-connected neural networks: Towards efficient vlsi implementation of deep neural networks. *arXiv preprint arXiv:1611.01427*, 2016.

Misha Denil, Babak Shakibi, Laurent Dinh, Nando de Freitas, et al. Predicting parameters in deep learning. In *Advances in Neural Information Processing Systems*, pp. 2148–2156, 2013.

Song Han, Huizi Mao, and William J Dally. Deep compression: Compressing deep neural networks with pruning, trained quantization and huffman coding. *arXiv preprint arXiv:1510.00149*, 2015a.

Song Han, Jeff Pool, John Tran, and William Dally. Learning both weights and connections for efficient neural network. In *Advances in Neural Information Processing Systems*, pp. 1135–1143, 2015b.

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. 2009.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pp. 1097–1105, 2012.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Yann LeCun, Corinna Cortes, and Christopher JC Burges. Mnist handwritten digit database. *AT&T Labs [Online]. Available: http://yann. lecun. com/exdb/mnist*, 2, 2010.

Baoyuan Liu, Min Wang, Hassan Foroosh, Marshall Tappen, and Marianna Pensky. Sparse convolutional neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 806–814, 2015.

Lukas Meier, Sara Van De Geer, and Peter Bühlmann. The group lasso for logistic regression. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 70(1):53–71, 2008.

Jiquan Ngiam, Aditya Khosla, Mingyu Kim, Juhan Nam, Honglak Lee, and Andrew Y Ng. Multimodal deep learning. In *Proceedings of the 28th international conference on machine learning (ICML-11)*, pp. 689–696, 2011.

Wei Wen, Chunpeng Wu, Yandan Wang, Yiran Chen, and Hai Li. Learning structured sparsity in deep neural networks. In *Advances in Neural Information Processing Systems*, pp. 2074–2082, 2016.

Ming Yuan and Yi Lin. Model selection and estimation in regression with grouped variables. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 68(1):49–67, 2006.

Lei Zhao, Qinghua Hu, and Wenwu Wang. Heterogeneous feature selection with multi-modal deep neural networks and sparse group lasso. *IEEE Transactions on Multimedia*, 17(11):1936–1948, 2015.

Michael Zhu and Suyog Gupta. To prune, or not to prune: exploring the efficacy of pruning for model compression. *arXiv preprint arXiv:1710.01878*, 2017.