# DEEP EVIDENTIAL REGRESSION

## ABSTRACT

Deterministic neural networks (NNs) are increasingly being deployed in safety critical domains, where calibrated, robust and efficient measures of uncertainty are crucial. While it is possible to train regression networks to output the parameters of a probability distribution by maximizing a Gaussian likelihood function, the resulting model remains oblivious to the underlying confidence of its predictions. In this paper, we propose a novel method for training deterministic NNs to not only estimate the desired target but also the associated evidence in support of that target. We accomplish this by placing evidential priors over our original Gaussian likelihood function and training our NN to infer the hyperparameters of our evidential distribution. We impose priors during training such that the model is penalized when its predicted evidence is not aligned with the correct output. Thus the model estimates not only the probabilistic mean and variance of our target but also the underlying uncertainty associated with each of those parameters. We observe that our evidential regression method learns well-calibrated measures of uncertainty on various benchmarks, scales to complex computer vision tasks, and is robust to adversarial input perturbations.

## 1 INTRODUCTION

Recent advances in deep supervised learning have yielded super human level performance and precision. While these models empirically generalize well when placed into new test enviornments, they are often easily fooled by adversarial perturbations (Goodfellow et al., 2014), and have difficulty understanding when their predictions should not be trusted. Today, regression based neural networks are being deployed in safety critical domains of computer vision (Godard et al., 2017) as well as in robotics and control (Bojarski et al., 2016) where the ability to infer model uncertainty is crucial for eventual wide-scale adoption. Furthermore, precise uncertainty estimates are useful both for human interpretation of confidence and anomaly detection, and also for propagating these estimates to other autonomous components of a larger, connected system.

Figure 1: **Evidential distributions.** Maximum likelihood optimization learns a likelihood distribution given data, while evidential distributions model higher-order probability distribution over the likelihood parameters.

Existing approaches to uncertainty estimation are roughly split into two categories: (1) learning aleatoric uncertainty (uncertainty in the data) and (2) epistemic uncertainty (uncertainty in the prediction). While representations for aleatoric uncertainty can be learned directly from data, approaches for estimating epistemic uncertainty focus on placing probabilistic priors over the weights and sampling to obtain a measure of variance. In practice, many challenges arise with this approach, such as the computational expense of sampling during inference, how to pick an appropriate weight prior, or even how to learn such a representation given your prior.

Instead, we formulate learning as an evidence acquisition process, where the model can acquire evidence during training (Sensoy et al., 2018; Malinin & Gales, 2018). Every training example adds support to a learned higher-order, *evidential* distribution. Sampling from this evidential distribution yields instances of lower-order, likelihood functions from which the data was drawn (cf. Fig. 1). We demonstrate that, by placing priors over our likelihood function, we can learn a grounded representation of epistemic and aleatoric uncertainty without sampling during inference.

In summary, this work makes the following contributions:

1. A novel and scalable method for learning representations of epistemic and aleatoric uncertainty, specifically on regression problems, by placing evidential priors over the likelihood;

2. Evaluation of learned epistemic uncertainty on benchmark regression tasks and comparison against other state-of-the-art uncertainty estimation techniques for neural networks;

3. Robustness evaluation against out of distribution and adversarially perturbed test data.

## 2 MODELLING UNCERTAINTIES FROM DATA

### 2.1 PRELIMINARIES

Consider the following supervised optimization problem: given a dataset, $\mathcal{D}$, of $N$ paired training examples, $(x_1, y_1), \ldots, (x_N, y_N)$, we aim to learn a function $f$, parameterized by a set of weights, $\boldsymbol{w}$, which approximately solves the following optimization problem:

$$\min_{\boldsymbol{w}} J(\boldsymbol{w}); \quad J(\boldsymbol{w}) = \frac{1}{N} \sum_{i=1}^{N} \mathcal{L}_i(\boldsymbol{w}), \tag{1}$$

where $\mathcal{L}_i(\cdot)$ describes a loss function. In this work, we consider deterministic regression problems, which commonly optimize the sum of squared errors, $\mathcal{L}_i(\boldsymbol{w}) = \frac{1}{2} \|y_i - f(x_i; \boldsymbol{w})\|^2$. In doing so, the model is encouraged to learn the average correct answer for a given input, but does not explicitly model any underlying noise or uncertainty in the data when making its estimation.

### 2.2 MAXIMUM LIKELIHOOD ESTIMATION

Alternatively, we can approach our optimization problem from a maximum likelihood perspective, where we learn model parameters that maximize the likelihood of observing the particular set of training datapoints. In the context of deterministic regression, if we assume our targets, $y_i$, were drawn i.i.d. from a Gaussian distribution with mean and variance parameters $\theta = (\mu, \sigma^2)$, then the likelihood of observing a single target, $y_i$, can be expressed as

$$p(y_i|\theta) = p(y_i|\mu, \sigma^2) = \frac{1}{\sigma\sqrt{2\pi}} \exp\left\{-\frac{1}{2\sigma^2}(y_i - \mu)^2\right\}. \tag{2}$$

In maximum likelihood estimation, we aim to learn a model to infer the $(\mu, \sigma^2)$ that maximize the likelihood of observing our targets, $y$. Equivalently, instead of maximizing the likelihood function, in practice it is common to instead minimize the negative log likelihood by setting

$$\mathcal{L}_i(\boldsymbol{w}) = -\log p(y_i|\mu, \sigma^2) = \frac{1}{2} \log(2\pi\sigma^2) + \frac{(y_i - \mu)^2}{2\sigma^2}. \tag{3}$$

In learning the parameters $\theta$, this likelihood function allows us to successfully model the uncertainty of our data, also known as the aleatoric uncertainty. However, our model remains oblivious to the predictive model uncertainty. This metric, known as epistemic uncertainty, corresponds to the model's uncertainty in its own output prediction (Kendall & Gal, 2017). In this paper, we present a novel approach for estimating the evidence in support of network predictions by directly learning both the inferred aleatoric uncertainty as well as the underlying epistemic uncertainty over its predictions. We achieve this by placing higher-order prior distributions over the learned parameters governing the distribution from which our observations are drawn.

## 3 EVIDENTIAL UNCERTAINTY FOR REGRESSION

### 3.1 PROBLEM SETUP

We consider the problem where our observed targets, $y_i$, are drawn i.i.d. from a Gaussian distribution with *unknown mean and variance* $(\mu, \sigma^2)$, which we seek to probabilistically estimate. We model this by placing a conjugate prior distribution on $(\mu, \sigma^2)$. If we assume our observations are drawn

Figure 2: **Normal Inverse-Gamma distribution.** Different realizations of our evidential distribution (A) correspond to different levels of confidences in the parameters (e.g. $\mu, \sigma^2$). Sampling from a single realization of a higher-order evidential distribution (B), yields lower-order distributions (C) over the data (e.g. $p(y|\mu, \sigma^2)$). Darker shading indicates higher probability mass.

from a Gaussian, this leads to placing a Gaussian prior on our unknown mean and an Inverse-Gamma prior on our unknown variance:

$$(y_1, \ldots, y_N) \sim \mathcal{N}(\mu, \sigma^2)$$
$$\mu \sim \mathcal{N}(\gamma, \sigma^2 \lambda^{-1}) \qquad \sigma^2 \sim \Gamma^{-1}(\alpha, \beta).$$

where $\Gamma(\cdot)$ is the gamma function, and $\gamma \in R, \lambda > 0, \alpha > 0, \beta > 0$.

From a variational Bayesian perspective, our aim is to estimate a posterior distribution $q(\mu, \sigma^2) = p(\mu, \sigma^2 | y_1, \ldots, y_N)$. To obtain an approximation for the true posterior, we assume that the estimated distribution can be factorized, (Parisi, 1988), such that $q(\mu, \sigma^2) = q(\mu) \, q(\sigma^2)$. In this case, the true distribution takes the form of a Normal Inverse-Gamma (N.I.G.) distribution:

$$p(\mu, \sigma^2 | \gamma, \lambda, \alpha, \beta) = \frac{\beta^\alpha \sqrt{\lambda}}{\Gamma(\alpha)\sqrt{2\pi\sigma^2}} \left( \frac{1}{\sigma^2} \right)^{\alpha+1} \exp \left\{ -\frac{2\beta + \lambda(\gamma - \mu)^2}{2\sigma^2} \right\}. \qquad (4)$$

A alternative, popular interpretation of the parameters of the conjugate prior distribution is in terms of "virtual-observations" (Jordan, 2009). For example, the mean of a N.I.G. distribution can be interpreted as being estimated from $\lambda$ virtual-observations with sample mean $\gamma$ while its variance was estimated from $2\alpha$ virtual-observations with sample mean $\gamma$ and sum of squared deviations $2\beta$. Following from this interpretation, we define the total evidence, $\Phi$, of our evidential distributions as the sum of all inferred virtual-observations counts ($\Phi = \lambda + 2\alpha$).

Thus, we can interpret the estimated posterior $q(\theta) = q(\mu, \sigma^2)$ as an *evidential, higher-order* probability distribution on top of the unknown *lower-order* likelihood distribution from which observations are drawn. Drawing a single sample $\theta_j$ from our evidential posterior yields $(\mu_j, \sigma_j^2)$ representing a single instance of our likelihood function, namely $\mathcal{N}(\mu_j, \sigma_j^2)$. Thus, the parameters of the posterior, specifically $(\gamma, \lambda, \alpha, \beta)$, determine not only the location but also the dispersion concentrations, or uncertainty, associated with our inferred likelihood function.

For example, in Fig. 2A we visualize the posterior of different evidential N.I.G. distributions with varying model parameters. We illustrate that by increasing the evidential parameters (i.e. $\lambda, \alpha$) of this distribution, the p.d.f. becomes more tightly concentrated about its inferred likelihood function. Considering a single parameter realization of this higher-order distribution, cf. Fig. 2B, we can subsequently sample many lower-order realizations of our likelihood function, as shown in Fig. 2C.

In this work, we use neural networks to learn a higher-order evidential distribution that directly captures prediction uncertainties and evaluate our method on various regression tasks. This approach presents several distinct advantages. First, this method enables simultaneous learning of the desired regression task, along with uncertainty estimation, built in, due to our evidential priors. Second, since the evidential prior is a higher-order N.I.G. distribution, the maximum likelihood Gaussian can be computed analytically from the expected values of the $(\mu, \sigma^2)$ parameters, without the need

for sampling. Third, by explicitly modeling the evidence, we effectively capture the epistemic or model uncertainty associated with the network's prediction. This can be done by simply evaluating the variance of our inferred evidential distribution.

## 3.2 LEARNING THE EVIDENTIAL DISTRIBUTION

Having formalized the problem of using an evidential distribution to capture model uncertainty, we next describe our approach for actually learning this distribution. Given a set of observations, variational inference methods aim to approximate a posterior distribution over unobserved variables or parameters by maximizing the evidence lower bound (ELBO) (Kingma & Welling, 2013). Similarly, here we seek to estimate the posterior distribution $q(\theta) = q(\mu, \sigma^2)$ governed by the higher-order distribution parameters $m = (\gamma, \lambda, \alpha, \beta)$ to maximize the likelihood of our observations. Applying the principle of variational inference, we have:

$$\text{ELBO} := \underbrace{\mathbb{E}_q[\log p_m(y|\theta)]}_{\text{log-likelihood}} - \underbrace{\text{KL}[\, q(\theta|y) \,\|\, p(\theta) \,]}_{\text{dissimilarity penalty}} \tag{5}$$

where $\theta = (\mu, \sigma^2)$. Similar to the principle of variational inference, in the remainder of this section we will discuss how we learn evidential distributions for regression by maximizing the log-likelihood of model evidence and minimizing the distance to an uncertainty prior. As we will see, maximizing the log-likelihood allows our model to fit the data, while the regularization provides an "uncertainty" penalty so the model can express when it does not know the answer.

The "model evidence", or marginal likelihood, is defined as the likelihood of an observation, $y_i$, given the evidential distribution parameters $m$ and is computed using Bayesian probability theory by marginalizing over the likelihood parameters $\theta$:

$$p(y_i|m) = \frac{p(y_i|\theta, m)p(\theta|m)}{p(\theta|y_i, m)} = \int_\theta p(y_i|\theta, m)p(\theta|m)\, d\theta. \tag{6}$$

The model evidence is not, in general, straightforward to evaluate since computing it involves integrating out the dependence on model parameters. However, by placing a N.I.G. prior on our Gaussian likelihood function an analytical solution does exist.

$$p(y_i|m) = \int_{\sigma^2=0}^{\infty} \int_{\mu=-\infty}^{\infty} \left[ \sqrt{\frac{1}{2\pi\sigma^2}} e^{-\frac{1}{2\sigma^2}(y_i-\mu)^2} \right] \left[ \frac{\beta^\alpha \sqrt{\lambda}}{\Gamma(\alpha)\sqrt{2\pi}} \left( \frac{1}{\sigma^2} \right)^{\alpha+\frac{3}{2}} e^{-\frac{\beta}{\sigma^2}} e^{-\frac{\lambda(\mu-\gamma)^2}{2\sigma^2}} \right] d\mu\, d\sigma^2 \tag{7}$$

For computational reasons it is common to instead minimize the negative log-likelihood of the model evidence ($\mathcal{L}_i^{\text{NLL}}(\boldsymbol{w})$). For a complete derivation please refer to Sec. 7.1.

$$\mathcal{L}_i^{\text{NLL}}(\boldsymbol{w}) = -\log p(y_i|m) = -\log \left( 2^{\frac{1}{2}+\alpha} \beta^\alpha \sqrt{\frac{\lambda}{2\pi(1+\lambda)}} \left( 2\beta + \frac{\lambda(\gamma-y_i)^2}{1+\lambda} \right)^{-\frac{1}{2}-\alpha} \right). \tag{8}$$

Instead of modeling the loss using empirical Bayes, where the objective is to *maximize* model evidence, we can alternatively *minimize* the sum-of-squared (SOS) errors, between the evidential prior and the data that would be sampled from the associated likelihood. Thus, we define $\mathcal{L}_i^{\text{SOS}}(\boldsymbol{w})$ as

$$\mathcal{L}_i^{\text{SOS}}(\boldsymbol{w}) = \int_{\sigma^2=0}^{\infty} \int_{\mu=-\infty}^{\infty} \mathbb{E}_{y\sim p(y|\mu,\sigma^2)} \left[ ||y - y_i||_2^2 \right] p(\mu, \sigma^2|\gamma, \lambda, \alpha, \beta)\, d\mu\, d\sigma^2 \tag{9}$$

$$= \left( \frac{\Gamma(\alpha - \frac{1}{2})}{4\,\Gamma(\alpha)\,\lambda\sqrt{\beta}} \right) \left( 2\beta(1+\lambda) + (2\alpha-1)\lambda(y_i - \gamma)^2 \right). \tag{10}$$

A step-by-step derivation is given in Sec. 7.1. In our experiments, using $\mathcal{L}_i^{\text{SOS}}(\boldsymbol{w})$ resulted in greater training stability and increased performance, over the $\mathcal{L}_i^{\text{NLL}}(\boldsymbol{w})$ loss. Therefore, $\mathcal{L}_i^{\text{SOS}}(\boldsymbol{w})$ is used in all presented results.

## 3.3 EXPRESSING LACK OF EVIDENCE

In the previous subsection, we outlined a loss function for training a NN to output parameters of a N.I.G. distribution which maximize the log-likelihood of our data. In this subsection we describe how

we regularize training against a prior where the model does not have any evidence (i.e. maximum uncertainty). In variational inference this is done by minimizing the KL-divergence between the inferred posterior, $q(\mu, \sigma^2) = q(\theta)$, and a prior, $p(\theta)$, cf. Eq. 5. In the evidential setting, our prior is also a Normal Inverse-Gamma distribution, but with zero evidence (or infinite uncertainty). Therefore, during training we aim to minimize our evidence (or maximize our uncertainty) everywhere except where we have training data, as enforced by the negative log-likelihood loss term.

Unfortunately, the KL-divergence between an arbitrary N.I.G. distribution and another with infinitely low evidence is not well defined (Soch & Allefeld, 2016). To address this, we formulate a custom evidence regularizer, $\mathcal{L}_i^R$, based on the error of the $i$-th prediction,

$$\mathcal{L}_i^R(\boldsymbol{w}) = \|y_i - \gamma\|_p \cdot \Phi = \|y_i - \gamma\|_p \cdot (2\alpha + \lambda),$$

where $\|x\|_p$ represents the L-p norm of $x$. The value of $p$ impacts the penalty imposed on the evidence when a wrong prediction is made. For example, $p = 2$, heavily over-penalizes the evidence on larger errors, whereas $p = 1$ and $p = 0.5$ saturate the evidence penalty for larger errors. We found that $p = 0.5$ provided the optimal stability during training and use this value in all presented results.

This regularization loss imposes a penalty whenever there is an error in the prediction that scales with the total evidence of our inferred posterior. Conversely, large amounts of predicted evidence will not be penalized as long as the prediction is close to the target observation.

The combined loss function employed during training consists of the two loss terms for maximizing model evidence and regularizing evidence,

$$\mathcal{L}_i(\boldsymbol{w}) = \mathcal{L}_i^{\text{SOS}}(\boldsymbol{w}) + \mathcal{L}_i^R(\boldsymbol{w}). \tag{11}$$

### 3.4 Evaluating aleatoric and epistemic uncertainty

The aleatoric uncertainty, also referred to as statistical or data uncertainty, is representative of unknowns that differ each time we run the same experiment. We evaluate the aleatoric uncertainty from $\mathbb{E}[\sigma^2] = \frac{\beta}{\alpha - 1}$. The epistemic, also known as the model uncertainty, describes the estimated uncertainty in the learned model and is defined as $\text{Var}[\mu] = \frac{\beta}{(\alpha - 1)\lambda}$. Note that $\text{Var}[\mu] = \mathbb{E}[\sigma^2]/\lambda$, which is expected as $\lambda$ is one of our two evidential virtual-observation counts.

## 4 Experiments

### 4.1 Predictive accuracy and uncertainty benchmarking

We first qualitatively compare the performance of our approach against a set of benchmarks on a one-dimensional toy regression dataset (Fig. 3). For training and dataset details please refer to Sec. 7.2.1. We compare deterministic regression, as well as techniques using empirical variance of the networks' predictions such as MC-dropout, model-ensembles, and Bayes-by-Backprop which underestimate the uncertainty outside the training distribution. In contrast, evidential regression estimates uncertainty appropriately and grows the uncertainty estimate with increasing distance from the training data.

Figure 3: **Epistemic uncertainty estimation.** Modeling the supportive evidence during learning enables precise prediction within the training regime and conservative uncertainty estimates where there was no training data. Comparisons to other epistemic uncertainty estimation methods are illustrated (bottom).

Additionally, we compare our approach to state-of-the-art methods for predictive uncertainty estimation using NNs on common real world datasets used in (Hernández-Lobato & Adams, 2015; Lakshminarayanan et al., 2017; Gal & Ghahramani, 2016). We evaluate our proposed evidential regression method against model-ensembles and BBB based on root mean squared error (RMSE), and negative log-likelihood (NLL). We do not provide results for MC-dropout since it consistently performed inferior to the other baselines. The

| Dataset | RMSE | | | NLL | | |
|---|---|---|---|---|---|---|
| | Ensembles | BBB | Evidential | Ensembles | BBB | Evidential |
| Boston | 0.09 ± 4.3e-4 | 0.09 ± 3.7e-4 | **0.09 ± 1.0e-6** | **-0.89 ± 6.5e-2** | -0.67 ± 1.5e-2 | **-0.87 ± 2.2e-2** |
| Concrete | **0.07 ± 4.4e-3** | **0.06 ± 3.3e-6** | **0.06 ± 7.0e-7** | **-1.29 ± 4.1e-2** | **-1.32 ± 4.3e-3** | **-1.31 ± 1.9e-2** |
| Energy | **0.10 ± 2.3e-4** | **0.10 ± 1.6e-5** | **0.10 ± 9.0e-7** | -0.61 ± 8.9e-2 | -0.60 ± 2.0e-2 | **-0.75 ± 1.4e-2** |
| Kin8nm | **0.07 ± 3.5e-4** | 0.17 ± 3.5e-4 | 0.08 ± 3.8e-3 | -0.78 ± 1.4e-2 | -0.32 ± 6.3e-3 | **-1.17 ± 2.6e-2** |
| Naval | **0.01 ± 1.0e-7** | 0.04 ± 1.2e-2 | **0.01 ± 3.4e-4** | -2.55 ± 3.3e-2 | -1.83 ± 2.4e-1 | **-3.17 ± 2.1e-3** |
| Power | **0.06 ± 4.0e-7** | **0.06 ± 2.3e-6** | **0.06 ± 5.3e-6** | -1.29 ± 6.9e-2 | -1.33 ± 2.5e-3 | **-1.40 ± 6.2e-3** |
| Protein | **0.17 ± 1.0e-6** | 0.17 ± 8.0e-4 | **0.17 ± 1.6e-6** | **-0.27 ± 6.7e-2** | 0.32 ± 5.9e-2 | **-0.29 ± 1.1e-2** |
| Wine | **0.10 ± 3.0e-4** | **0.10 ± 2.9e-4** | **0.10 ± 3.8e-5** | -0.46 ± 2.5e-1 | **-0.89 ± 2.4e-3** | -0.85 ± 6.9e-3 |
| Yacht | 0.07 ± 1.3e-3 | 0.07 ± 3.4e-3 | **0.06 ± 6.2e-5** | -1.16 ± 6.3e-2 | -0.74 ± 5.8e-2 | **-1.28 ± 9.4e-3** |

Table 1: **Benchmark regression tests.** We evaluate RMSE and negative log-likelihood (NLL) for model ensembling (Lakshminarayanan et al., 2017), Bayes-By-Backprop (BBB) (Blundell et al., 2015) and evidential regression. Evidential achieves top scores (bolded, within statistical significance) on 8 of the 9 datasets.

results in Table 1 indicate that although the loss function for evidential regression is more complex than competing approaches, it is the top performer in RMSE and NLL in 8 out of 9 datasets.

Furthermore, we demonstrate that, on a synthetic dataset with *a priori* known noise, evidential models can additionally estimate and recover the underlying aleatoric uncertainty. For more information please refer to Sec. 7.2.2 for results and experiment details.

## 4.2 DEPTH ESTIMATION

After establishing benchmark comparison results, in this subsection we demonstrate the scalability of our evidential learning by extending to the complex, high-dimensional task of depth estimation. Monocular end-to-end depth estimation is a central problem in computer vision which aims to learn a representation of depth directly from an RGB image of the scene. This is a challenging learning task since the output target $y$ is very high-dimensional. For every pixel in the image, we regress over the desired depth and simultaneously estimate the uncertainty associated to that individual pixel.

Our training data consists of over 27k RGB-to-depth pairs of indoor scenes (e.g. kitchen, bedroom, etc.) from the NYU Depth v2 dataset (Nathan Silberman & Fergus, 2012). We train a U-Net style NN (Ronneberger et al., 2015) for inference. The final layer of our model outputs a single $H \times W$ activation map in the case of deterministic regression, dropout, ensembling and BBB. Evidential models four final activation maps corresponding to $(\gamma, \lambda, \alpha, \beta)$.

Table 2 summarizes the size and speed of all models. Evidential models contain significantly fewer trainable parameters than ensembles (where the number of parameters scales linearly with the size of the ensemble). BBB maintains a trainable mean and variance for every weight in the network, so its size is roughly $2\times$ larger as well. Since evidential regression models do not require sampling in order to estimate their uncertainty, their forward-pass inference times are also significantly more efficient. Finally, we demonstrate comparable predictive accuracy (through RMSE and NLL) to the other models. For a more detailed breakdown of how the number of samples effects the baselines please refer to Tab. 3. Note that the output size of the depth estimation problem presented significant learning challenges for the BBB baseline, and it was unable to converge during training. As a result, for the remainder of this analysis we compare against only spatial dropout and ensembles.

We evaluate these models in terms of their accuracy and their predictive uncertainty on unseen test data. Fig. 4A-C visualizes the predicted depth, absolute error from ground truth, and predictive uncertainty across three randomly picked test images. Ideally, a strong predictive uncertainty would capture any errors in the prediction (i.e., roughly correspond to where the model is making errors).

| | # Parameters | | Inference Speed | | RMSE | NLL |
|---|---|---|---|---|---|---|
| | Absolute | Relative | Seconds | Relative | | |
| **Evidential (Ours)** | 7,846,776 | 1.00 | 0.003 | 1.00 | 0.024 ± 0.032 | -1.128 ± 0.290 |
| **Spatial Dropout** | 7,846,657 | 1.00 | 0.031 | 11.48 | 0.031 ± 0.033 | -1.227 ± 0.374 |
| **Ensembles** | 39,233,285 | 5.00 | 0.010 | 3.72 | 0.023 ± 0.027 | -1.077 ± 0.298 |
| **BBB** | 11,772,929 | 1.50 | 0.070 | 25.55 | - | - |

Table 2: **Benchmark performance comparison on depth prediction.** For fair performance comparison, sampling methods were all parallelized and sampled 5 times as RMSE and NLL did not significantly improve with greater samples. For an extended analysis with larger number of samples please refer to Table 3.

Figure 4: **Modeling uncertainty in depth estimation.** Three methods for estimating epistemic (model) uncertainty are evaluated in the context of monocular depth estimation. For each model, we visualize the prediction, error to ground-truth, and estimated uncertainty for three randomly chosen examples (A-C). Ideally, the model should predict high uncertainty whenever it does not know the answer (i.e., large error). We evaluate the sensitivity and specificity of the predictive uncertainty in identifying likely errors with ROC curves (D).

Compared to dropout and ensembling, evidential uncertainty modeling captures the depth errors while providing clear and localized predictions of confidence. In general, dropout drastically underestimates the amount of uncertainty present, while ensembling occasionally overestimates the uncertainty.

To evaluate predictive uncertainty calibration to the ground-truth errors, we fit receiver operating characteristic (ROC) curves to normalized estimates of error and uncertainty. Thus, we test the network's ability to detect how likely it is to make an error at a given pixel using its predictive uncertainty. ROC curves take into account sensitivity and specificity of the uncertainties towards error predictions and are stronger if they contain greater area under their curve (AUC). Fig. 4D demonstrates that our evidential model provides uncertainty estimates concentrate to where the model is making the errors.

Figure 5: **Aleatoric uncertainty in depth.** Visualizing predicted aleatoric uncertainty in challenging reflection and illumination scenes. Comparison between evidential and (Kendall & Gal, 2017) show strong semantic agreement.

In addition to epistemic uncertainty, we also evaluate the aleatoric uncertainty estimates that are learned from our evidential models as well. Fig. 5 compares the evidential aleatoric uncertainty to those obtained by Gaussian likelihood optimization in several domains with high data uncertainty (mirror reflections and poor illumination). The results between both methods are in strong agreement, identifying mirror reflections and dark regions without visible geometry as sources of high uncertainty.

### 4.3 OUT-OF DISTRIBUTION TESTING

A key use of uncertainty estimation is to understand when a model is faced with test samples that fall out-of-distribution (OOD) or when the model's output cannot be trusted. In the previous subsection, we showed that our evidential uncertainties were well calibrated with the model's errors. In this subsection, we investigate the performance on out-of-distribution samples. Fig. 6 illustrates predicted depth on various test input images (left) and outside (right) of the original distribution. All images

Figure 6: **Out-of-distribution (OOD) data samples.** Evidential models estimate and inflate epistemic uncertainty on OOD data, where the prediction should not be trusted. All samples were not seen during training.

Figure 7: **Evidential robustness under adversarial noise.** Increasing levels of adversarial noise (A) corrupt the predicted depth, and our model begins to incur greater amounts of error. As adversarial noise increases, inferred epistemic uncertainty increases (localized to where the most error occurs). Adversarially perturbed test accuracy (B), epistemic uncertainty (C), as well as the noise to evidential error estimation (D) is also provided.

have not been seen by the model during training. We qualitatively and quantitatively demonstrate that the epistemic uncertainty predicted by our evidential model consistently increases on the OOD samples.

### 4.3.1 ROBUSTNESS TO ADVERSARIAL SAMPLES

Next, we consider the extreme case of OOD detection where the inputs are adversarially perturbed to inflict maximum error on the model. We compute adversarial perturbations to our test set using the fast gradient sign method (Goodfellow et al., 2014), with increasing scales, $\epsilon$, of noise. Fig. 7A confirms that the absolute error of all methods increasing as adversarial noise is added. We also observe a positive effect noise on our predictive uncertainty estimates in Fig. 7B. An additional desirable property of evidential uncertainty modeling is that it presents a higher overall uncertainty when presented with adversarial inputs compared to dropout and ensembling methods. Furthermore, we observe this strong overall uncertainty estimation despite the model losing calibration accuracy from the adversarial examples (Fig. 7C).

The robustness of evidential uncertainty against adversarial perturbations is visualized in greater detail in Fig. 7D, which illustrates the predicted depth, error, and estimated pixel-wise uncertainty as we perturb the input image with greater amounts of noise (left-to-right). Note that the predictive uncertainty not only steadily increases as we increase the noise, but the spatial concentrations of uncertainty throughout the image maintain tight correspondence with the error.

## 5 DISCUSSION AND RELATED WORK

Uncertainty estimation has a long history in neural networks, from modeling probability distribution parameters over outputs (Bishop, 1994) to Bayesian deep learning (Kendall & Gal, 2017). Our work builds on this foundation and presents a scalable representation for inferring the parameters of an evidential uncertainty distribution while simultaneously learning regression tasks via MLE.

In Bayesian deep learning, priors are placed over network weights and estimated using variational inference (Kingma et al., 2015). Dropout (Gal & Ghahramani, 2016; Molchanov et al., 2017) and BBB (Blundell et al., 2015) rely on multiple samples to estimate predictive variance. Ensembles (Lakshminarayanan et al., 2017) provide a tangential approach where sampling occurs over multiple trained instances. In contrast, we place uncertainty priors over the likelihood function and thus only need a single forward pass to evaluate both prediction and uncertainty. Additionally, our approach of uncertainty estimation proved to be better calibrated and capable of predicting where the model fails.

A large topic of research in Bayesian inference focuses on placing prior distributions over hierarchical models to estimate uncertainty (Gelman et al., 2006; 2008). Our methodology falls under the class of evidential deep learning which leverages the *Theory of Evidence* to model prior distributions over neural network predictions and interpret uncertainty. Prior works in this field (Sensoy et al., 2018; Malinin & Gales, 2018) have focused exclusively on modeling uncertainty in the classification domain with Dirichlet prior distributions. Our work extends this field into the broad range of regression learning tasks (e.g. depth estimation, forecasting, robotic control learning, etc) and demonstrates generalizability to out-of-distribution test samples.

## 6 CONCLUSION

In this paper, we develop a novel method for training deterministic NNs that both estimates a desired target and evaluates the *evidence* in support of the target to generate robust metrics of model uncertainty. We formalize this in terms of learning evidential distributions, and achieve stable training by penalizing our model for prediction errors that scale with the available evidence. Our approach for evidential regression is validated on a benchmark regression task. We further demonstrate that this method robustly scales to a key task in computer vision, depth estimation, and that the predictive uncertainty increases with increasing out-of-distribution adversarial perturbation. This framework for evidential representation learning provides a means to achieve the precise uncertainty metrics required for robust neural network deployment in safety-critical domains.

## REFERENCES

Christopher M Bishop. Mixture density networks. In *Tech. Rep. NCRG/94/004, Neural Computing Research Group*. Aston University, 1994.

Charles Blundell, Julien Cornebise, Koray Kavukcuoglu, and Daan Wierstra. Weight uncertainty in neural networks. *arXiv preprint arXiv:1505.05424*, 2015.

Mariusz Bojarski, Davide Del Testa, Daniel Dworakowski, Bernhard Firner, Beat Flepp, Prasoon Goyal, Lawrence D Jackel, Mathew Monfort, Urs Muller, Jiakai Zhang, et al. End to end learning for self-driving cars. *arXiv preprint arXiv:1604.07316*, 2016.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *international conference on machine learning*, pp. 1050–1059, 2016.

Andrew Gelman, Aleks Jakulin, Maria Grazia Pittau, Yu-Sung Su, et al. A weakly informative default prior distribution for logistic and other regression models. *The Annals of Applied Statistics*, 2(4): 1360–1383, 2008.

Andrew Gelman et al. Prior distributions for variance parameters in hierarchical models (comment on article by browne and draper). *Bayesian analysis*, 1(3):515–534, 2006.

Clément Godard, Oisin Mac Aodha, and Gabriel J Brostow. Unsupervised monocular depth estimation with left-right consistency. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 270–279, 2017.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

José Miguel Hernández-Lobato and Ryan Adams. Probabilistic backpropagation for scalable learning of bayesian neural networks. In *International Conference on Machine Learning*, pp. 1861–1869, 2015.

Michael I Jordan. The exponential family: Conjugate priors, 2009.

Alex Kendall and Yarin Gal. What uncertainties do we need in bayesian deep learning for computer vision? In *Advances in neural information processing systems*, pp. 5574–5584, 2017.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Durk P Kingma, Tim Salimans, and Max Welling. Variational dropout and the local reparameterization trick. In *Advances in Neural Information Processing Systems*, pp. 2575–2583, 2015.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Advances in Neural Information Processing Systems*, pp. 6402–6413, 2017.

Andrey Malinin and Mark Gales. Predictive uncertainty estimation via prior networks. In *Advances in Neural Information Processing Systems*, pp. 7047–7058, 2018.

Dmitry Molchanov, Arsenii Ashukha, and Dmitry Vetrov. Variational dropout sparsifies deep neural networks. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 2498–2507. JMLR. org, 2017.

Pushmeet Kohli Nathan Silberman, Derek Hoiem and Rob Fergus. Indoor segmentation and support inference from rgbd images. In *ECCV*, 2012.

Giorgio Parisi. *Statistical field theory*. Addison-Wesley, 1988.

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pp. 234–241. Springer, 2015.

Murat Sensoy, Lance Kaplan, and Melih Kandemir. Evidential deep learning to quantify classification uncertainty. In *Advances in Neural Information Processing Systems*, pp. 3179–3189, 2018.

Joram Soch and Carsten Allefeld. Kullback-leibler divergence for the normal-gamma distribution. *arXiv preprint arXiv:1611.01437*, 2016.

## 7 APPENDIX

### 7.1 MODEL EVIDENCE DERIVATIONS

For convenience, define $\tau = 1/\sigma^2$ be the precision of a Gaussian distribution. The change of variables transforms the Normal Inverse-Gamma distribution $p(\mu, \sigma^2|\gamma, \lambda, \alpha, \beta)$ to the equivalent Normal Gamma distribution $p(\mu, \tau|\gamma, \lambda, \alpha, \beta)$, parameterized by precision $\tau \in (0, \infty)$ instead of variance $\sigma^2$,

$$p(\mu, \tau|\gamma, \lambda, \alpha, \beta) = \frac{\beta^\alpha \sqrt{\lambda}}{\Gamma(\alpha)\sqrt{2\pi}} \tau^{\alpha-\frac{1}{2}} e^{-\beta\tau} e^{-\frac{\lambda\tau(\mu-\gamma)^2}{2}}. \tag{12}$$

#### 7.1.1 TYPE II MAXIMUM LIKELIHOOD LOSS

Marginalizing out $\mu$ and $\tau$ gives the result of equation 7,

$$p(y_i|m) = \int_\tau \int_\mu p(y_i|\mu, \tau) \, p(\mu, \tau|\gamma, \lambda, \alpha, \beta) \, \mathrm{d}\mu \, \mathrm{d}\tau \tag{13}$$

$$= \int_{\tau=0}^\infty \int_{\mu=-\infty}^\infty \left[\sqrt{\frac{\tau}{2\pi}} e^{-\frac{\tau}{2}(y_i-\mu)^2}\right] \left[\frac{\beta^\alpha \sqrt{\lambda}}{\Gamma(\alpha)\sqrt{2\pi}} \tau^{\alpha-\frac{1}{2}} e^{-\beta\tau} e^{-\frac{\lambda\tau(\mu-\gamma)^2}{2}}\right] \mathrm{d}\mu \, \mathrm{d}\tau \tag{14}$$

$$= \int_{\tau=0}^\infty \frac{(\beta\tau)^\alpha}{\Gamma(\alpha)} \sqrt{\frac{\lambda}{2\pi\tau(1+\lambda)}} e^{-\beta\tau} e^{-\frac{\tau\lambda(\gamma-y_i)^2}{2(1-\lambda)}} \, \mathrm{d}\tau \tag{15}$$

$$= 2^{\frac{1}{2}+\alpha} \beta^\alpha \sqrt{\frac{\lambda}{2\pi(1+\lambda)}} \left(2\beta + \frac{\lambda(\gamma-y_i)^2}{1+\lambda}\right)^{-\frac{1}{2}-\alpha}. \tag{16}$$

For computational reasons it is common to instead minimize the negative logarithm of the model evidence.

$$\mathcal{L}_i^{\mathrm{NLL}}(\boldsymbol{w}) = -\log p(y_i|m) = -\log\left(2^{\frac{1}{2}+\alpha} \beta^\alpha \sqrt{\frac{\lambda}{2\pi(1+\lambda)}} \left(2\beta + \frac{\lambda(\gamma-y_i)^2}{1+\lambda}\right)^{-\frac{1}{2}-\alpha}\right) \tag{17}$$

### 7.1.2 Sum of Squares Loss

Similarly, we can marginalize out $\mu$ and $\tau$ to receive the result of equation 9,

$$\mathcal{L}_i^{\text{SOS}}(\boldsymbol{w}) = \int_\tau \int_\mu \mathbb{E}_{y \sim p(y|\mu,\tau)} \left[ ||y_i - y||_2^2 \right] p(\mu, \tau|\gamma, \lambda, \alpha, \beta) \, \mathrm{d}\mu \, \mathrm{d}\tau \tag{18}$$

$$= \int_\tau \int_\mu \int_y ||y_i - y||_2^2 \, p(y|\mu,\tau) \, p(\mu,\tau|\gamma,\lambda,\alpha,\beta) \, \mathrm{d}y \, \mathrm{d}\mu \, \mathrm{d}\tau \tag{19}$$

$$= \int_{\tau=0}^\infty \int_{\mu=-\infty}^\infty \int_{y=-\infty}^\infty ||y_i - y||_2^2 \left[ \sqrt{\frac{\tau}{2\pi}} e^{-\frac{\tau}{2}(y-\mu)^2} \right]$$
$$\left[ \frac{\beta^\alpha \sqrt{\lambda}}{\Gamma(\alpha)\sqrt{2\pi}} \tau^{\alpha-\frac{1}{2}} e^{-\beta\tau} e^{-\frac{\lambda\tau(\mu-\gamma)^2}{2}} \right] \mathrm{d}y \, \mathrm{d}\mu \, \mathrm{d}\tau \tag{20}$$

$$= \int_{\tau=0}^\infty \int_{\mu=-\infty}^\infty \left[ (y_i - \mu)^2 + \frac{1}{\tau} \right] \left[ \frac{\beta^\alpha \sqrt{\lambda}}{\Gamma(\alpha)\sqrt{2\pi}} \tau^{\alpha-\frac{1}{2}} e^{-\beta\tau} e^{-\frac{\lambda\tau(\mu-\gamma)^2}{2}} \right] \mathrm{d}\mu \, \mathrm{d}\tau \tag{21}$$

$$= \int_{\tau=0}^\infty \frac{\beta^\alpha}{\lambda\Gamma(\alpha)} \exp\left(-\beta/\tau\right) \tau^{(\alpha-1)} \left( \tau(1+\lambda) + \lambda(y_i - \gamma)^2 \right) \mathrm{d}\tau \tag{22}$$

$$= \left( \frac{\Gamma(\alpha - \frac{1}{2})}{4\,\Gamma(\alpha)\,\lambda\sqrt{\beta}} \right) \left( 2\beta(1+\lambda) + (2\alpha - 1)\lambda(y_i - \gamma)^2 \right) \tag{23}$$

### 7.2 Benchmark Regression Task Evaluations

#### 7.2.1 Epistemic Uncertainty Estimation

The training set consists of training examples drawn from $y = \sin(3x)/(3x) + \epsilon$, where $\epsilon \sim \mathcal{N}(0, 0.02)$ in the region $-3 \le x \le 3$, whereas the test data is unbounded. All models consisted of 100 neurons with 3 hidden layers and were trained to convergence. The data presented in Fig. 3 illustrates the estimated epistemic uncertainty and predicted mean accross the entire test set, $-3 \le x \le 3$.

#### 7.2.2 Aleatoric Uncertainty Estimation

The training set consists of training examples drawn from $y = \sin(3x)/(3x) + \epsilon(x)$, where $\epsilon(x) \sim \mathcal{N}(0, s(x))$, and $s(x) = \frac{1}{20}\cos(3.3x) + 0.1$. We evaluate against (Kendall & Gal, 2017) which presents an algorithm for heteroscedastic aleatoric uncertainty estimation by inferring the mean and variance of a Gaussian likelihood function. As presented in the paper, training is done by minimizing the negative log-likelihood of the data given the inferred likelihood parameters. Both our network and the baseline Gaussian NLL network consisted of 100 neurons with 3 hidden layers and were trained to convergence.

Figure 8: **Aleatoric uncertainty estimation.** Comparing the ability to learn the heteroscedastic aleatoric uncertainty in a synthetic dataset. Evidential modelling is able to match the performance of Gaussian likelihood optimization (Kendall & Gal, 2017).

### 7.3 Additional Depth Estimation Performance Results

| | N | # Parameters | | Inference Speed | | RMSE | NLL |
|---|---|---|---|---|---|---|---|
| | | Absolute | Relative | Seconds | Relative | | |
| **Evidential (Ours)** | - | 7,846,776 | 1.00 | 0.003 | 1.00 | $0.024 \pm 0.032$ | $-1.128 \pm 0.290$ |
| **Spatial Dropout** | 2 | 7,846,657 | 1.00 | 0.028 | 10.20 | $0.033 \pm 0.037$ | $-0.564 \pm 0.231$ |
| **Spatial Dropout** | 5 | 7,846,657 | 1.00 | 0.031 | 11.48 | $0.031 \pm 0.033$ | $-1.227 \pm 0.374$ |
| **Spatial Dropout** | 10 | 7,846,657 | 1.00 | 0.037 | 13.69 | $0.035 \pm 0.042$ | $-1.139 \pm 0.379$ |
| **Spatial Dropout** | 25 | 7,846,657 | 1.00 | 0.065 | 23.99 | $0.032 \pm 0.035$ | $-1.137 \pm 0.327$ |
| **Spatial Dropout** | 50 | 7,846,657 | 1.00 | 0.107 | 39.36 | $0.032 \pm 0.036$ | $-1.110 \pm 0.381$ |
| **Ensembles** | 2 | 15,693,314 | 2.00 | 0.005 | 1.94 | $0.026 \pm 0.032$ | $-1.080 \pm 3.334$ |
| **Ensembles** | 5 | 39,233,285 | 5.00 | 0.010 | 3.72 | $0.023 \pm 0.027$ | $-1.077 \pm 0.298$ |
| **Ensembles** | 10 | 78,466,570 | 10.00 | 0.019 | 6.82 | $0.025 \pm 0.038$ | $-0.980 \pm 0.298$ |
| **Ensembles** | 25 | 196,166,425 | 25.00 | 0.045 | 16.45 | $0.022 \pm 0.029$ | $-1.000 \pm 0.259$ |
| **Ensembles** | 50 | 392,332,850 | 50.00 | 0.112 | 41.26 | $0.022 \pm 0.031$ | $-0.996 \pm 0.275$ |
| **BBB** | 2 | 11,772,929 | 1.50 | 0.064 | 23.58 | - | - |
| **BBB** | 5 | 11,772,929 | 1.50 | 0.070 | 25.55 | - | - |
| **BBB** | 10 | 11,772,929 | 1.50 | 0.088 | 32.25 | - | - |
| **BBB** | 25 | 11,772,929 | 1.50 | 0.144 | 53.09 | - | - |
| **BBB** | 50 | 11,772,929 | 1.50 | 0.284 | 104.33 | - | - |

Table 3: **Depth estimation performance.** Comparison of different epistemic uncertainty estimation algorithms and predictive performance on an unseen test set. Dropout, ensembles, and Bayes-by-Backprop were sampled N times on parallel threads. The evidential method outperforms all other algorithms in terms of space (#Parameters) and inference speed while maintaining competetive RMSE and NLL.