FEATURE-WISE BIAS AMPLIFICATION

ABSTRACT

We study the phenomenon of *bias amplification* in classifiers, wherein a machine learning model learns to predict classes with a greater disparity than the underlying ground truth. We demonstrate that bias amplification can arise via inductive bias in gradient descent methods resulting in overestimation of importance of moderately-predictive "weak" features if insufficient training data is available. This overestimation gives rise to *feature-wise bias amplification* – a previously unreported form of bias that can be traced back to the features of a trained model. Through analysis and experiments, we show that the while some bias cannot be mitigated without sacrificing accuracy, feature-wise bias amplification can be mitigated through targeted feature selection. We present two new feature selection algorithms for mitigating bias amplification in linear models, and show how they can be adapted to convolutional neural networks efficiently. Our experiments on synthetic and real data demonstrate that these algorithms consistently lead to reduced bias without harming accuracy, in some cases eliminating predictive bias altogether while providing modest gains in accuracy.

1 INTRODUCTION

Bias amplification occurs when the distribution over prediction outputs is skewed in comparison to the prior distribution of the prediction target. Aside from being problematic for accuracy, this phenomenon is also potentially concerning as it relates to the *fairness* of a model's predictions (Zhao et al., 2017; Burns et al., 2018; Bolukbasi et al., 2016; Stock and Cissé, 2017) as models that learn to overpredict negative outcomes for certain groups may exacerbate stereotypes, prejudices, and disadvantages already reflected in the data (Hart, 2017).

Several factors can cause bias amplification in practice. The *class imbalance problem* is a well-studied scenario where some classes in the data are significantly less likely than others (Wallace et al., 2011a). Classifiers trained to minimize emprical risk are not penalized for ignoring minority classes. However, as we show through analysis and experiments, bias amplification can arise in cases where the class prior is not severely skewed, or even when it is unbiased. Thus, techniques for dealing with class imbalance alone cannot explain or address all cases of bias amplification.

We examine bias amplification in the context of binary classifiers, and show that it can be decomposed into a component that is intrinsic to the model, and one that arises from the inductive bias of gradient descent on certain feature configurations. The intrinsic case manifests when the class prior distribution is more informative for prediction than the features, causing the the model to predict the class mode. This type of bias is unavoidable, as we show that any mitigation of it will lead to less accurate predictions (Section 2.1).

Interestingly, linear classifiers trained with gradient descent tend to overestimate the importance of moderately-predictive "weak" features if insufficient training data is available (Section 2.2). This overestimation gives rise to *feature-wise bias amplification* – a previously unreported form of bias that can be traced back to the features of a trained model. It occurs when there are features that positively correlate more with one class than the other (see Section 5 for comparison to related work). If these features are given undue importance in the model, then their combined influence will lead to bias amplification in favor of the corresponding class. Indeed, we experimentally demonstrate that feature-wise bias amplification can happen even when the class prior is unbiased.

Our analysis sheds new light on real instances of the problem, and paves the way for practical mitigations of it. The existence of such moderately-predictive weak features is not uncommon in

models trained on real data. Viewing deep neural networks as the composition of a feature extractor and a linear classifier, we explain some instances of bias amplification in deep neural networks (Table 1 in Section 4).

Finally, this understanding of feature-wise bias amplification motivates a solution based on feature selection. We develop two new feature selection algorithms that are designed to mitigate bias amplification (Section 3). We demonstrate their effectiveness on both linear classifiers and deep neural networks (Section 4). For example, for a VGG16 network trained on CelebA (Liu et al., 2015) to predict the "attractive" label, our approach removed 95% of the bias in predictions. We observe that in addition to mitigating bias amplification, these feature selection methods reduce generalization error relative to an ℓ_1 regularization baseline for both linear models and deep networks (Table 1).

2   BIAS AMPLIFICATION IN BINARY CLASSIFIERS

In this section, we define bias amplification for binary classifiers, and show that in some cases it may be unavoidable. Namely, a Bayes-optimal classifier trained on poorly-separated data can end up predicting one label nearly always, even if the prior label bias is minimal. While our analysis makes strong generative assumptions, we show that its results hold qualitatively on real data that resemble these assumptions. We begin by formalizing the setting.

We consider the standard binary classification problem of predicting a label $y \in \{0, 1\}$ given features $\mathbf{x} = (x_1, \ldots, x_d) \in \mathcal{X}$. We assume that data are generated from some unknown distribution $\mathcal{D}$, and that the prior probability of $y = 1$ is p^*. Without loss of generality, we assume that $p^* \geq 1/2$. The learning algorithm recieves a training set S drawn i.i.d. from $\mathcal{D}^n$ and outputs a predictor $h_S : \mathcal{X} \to \{0, 1\}$ with the goal of minimizing 0-1 loss on unknown future i.i.d. samples from $\mathcal{D}$.

Definition 1 (Bias amplification, systematic bias) *Let h_S be a binary classifier trained on $S \sim \mathcal{D}$. The* bias amplification *of h_S on $\mathcal{D}$, written $B_{\mathcal{D}}(h_S)$, is given by Equation 1.*

$$B_{\mathcal{D}}(h_S) = \mathop{\mathbb{E}}_{(\mathbf{x},y)\sim\mathcal{D}}[h_S(\mathbf{x}) - y] \tag{1}$$

We say that a learning rule exhibits systematic bias *whenever it exhibits non-zero bias amplification on average over training samples, i.e. it satisfies Equation 2.*

$$\mathop{\mathbb{E}}_{S\sim\mathcal{D}^n}[B_{\mathcal{D}}(h_S)] \neq 0 \tag{2}$$

Definition 1 formalizes bias amplification and systematic bias in this setting. Intuitively, bias amplification corresponds to be the probability that h_S predicts class 1 on instances from class 0 in excess of the prior p^*. Systematic bias lifts the definition to learners, characterizing rules that are expected to amplify bias on training sets drawn from $\mathcal{D}$.

2.1   SYSTEMATIC BIAS IN BAYES-OPTIMAL PREDICTORS

Definition 1 makes it clear that systematic bias is a property of the learning rule producing h_S and the distribution, so any technique that aims to address it will need to change one or both. However, if the learner always produces Bayes-optimal predictors for $\mathcal{D}$, then any such change will result in suboptimal classifiers, making bias amplification unavoidable. In this section we characterize the systematic bias of a family of linear Bayes-optimal predictors.

Consider a special case of binary classification in which $\mathbf{x}$ are drawn from a multivariate Gaussian distribution with class means $\boldsymbol{\mu}_0^*, \boldsymbol{\mu}_1^* \in \mathbb{R}^d$ and diagonal covariance matrix $\boldsymbol{\Sigma}^*$, and y a Bernoulli with parameter p^*. Then $\mathcal{D}$ is given by Equation 3.

$$\mathcal{D} \triangleq \Pr[\mathbf{x}|y] = \mathcal{N}(\mathbf{x}|\boldsymbol{\mu}_y^*, \boldsymbol{\Sigma}^*), y \sim \text{Bernoulli}(p^*) \tag{3}$$

Because the features in $\mathbf{x}$ are independent given the class label, the Bayes-optimal learning rule for this data is Gaussian Naive Bayes, which is expressible as a linear classifier (Murphy, 2012).

Making the ideal assumption that we are always able to learn the Bayes-optimal classifier h^* for parameters $\boldsymbol{\mu}_y^*, \boldsymbol{\Sigma}^*, p^*$, we proceed with the question: does h^* have systematic bias? Our assumption of $h_S = h^*$ reduces this question to whether $B_{\mathcal{D}}(h^*)$ is zero. Theorem 1 shows that $B_{\mathcal{D}}(h^*)$ is

dataset	D	p^*	$B_{\mathcal{D}}(h_S)$	% acc
banknote	1.87	0.56	0.04	84.1
breast cancer wisc	1.81	0.63	0.02	94.2
drug consumption	0.86	0.78	0.12	75.6
pima diabetes	1.15	0.66	0.08	79.9

(a)

(b)

Figure 1: (a) Bias amplification on real datasets classified using Gaussian Naive Bayes; (b) bias amplification of Bayes-optimal classifier in terms of the Mahalanobis distance D between class means and prior class probability p^*.

strictly a function of the class prior p^* and the Mahalanobis distance D of the class means $\boldsymbol{\mu}_y^*$. Corollary 1 uses this relationship to show that when the prior is unbiased, the model's predictions will remain unbiased.

Theorem 1 *Let* $\mathbf{x}$ *be distributed according to Equation 3,* y *be Bernoulli with parameter* p^*, D *be the Mahalanobis distance between the class means* $\boldsymbol{\mu}_0^*, \boldsymbol{\mu}_1^*$, *and* $\beta = -D^{-1}\log(p^*/(1-p^*))$. *Then the bias amplification of the Bayes-optimal classifier* h^* *is:*

$$B_{\mathcal{D}}(h^*) = 1 - p^* - (1 - p^*)\Phi\left(\beta + \frac{D}{2}\right) - p^*\Phi\left(\beta - \frac{D}{2}\right)$$

Corollary 1 *When* $\mathbf{x}$ *is distributed according to Equation 3 and* $p^* = 1/2$, $B_{\mathcal{D}}(h^*) = 0$.

The proofs of both claims are given in the appendix. Corollary 1 is due to the fact that when $p^* = 1/2$, $\beta = 0$. Because of the symmetry $\Phi(-x) = 1 - \Phi(x)$, the Φ terms cancel out giving $\Pr[h^*(\mathbf{x}) = 1] = 1/2$, and thus the bias amplification $B_{\mathcal{D}}(h^*) = 0$.

Figure 1a shows the effect on real data available on the UCI repository classified using Gaussian Naive Bayes (GNB). These datasets were chosen because their distributions roughly correspond to the naive Bayes assumption of conditional feature independence, and GNB outperformed logistic regression. In each case, bias amplification occurs in approximate correspondence with Theorem 1, tracking the empirical class prior and class distance to Figure 1b.

Figure 1b shows $B_{\mathcal{D}}(h^*)$ as a function of p^* for several values of D. As the means grow closer together, there is less information available to make reliable predictions, and the label prior is used as the more informative signal. Note that $B_{\mathcal{D}}(h^*)$ takes its maximum value at 1/2, and the critical point corresponds to bias "saturation" where the model always predicts class 1. From this is becomes clear that the extent to which overprediction occurs grows rather quickly when the means are moderately close. For example when $p^* = 3/4$ and the class means are separated by distance $1/2$, the classifier will predict $Y = 1$ with probability close to 1.

Summary: Bias amplification may be unavoidable when the learning rule is a good fit for the data, but the features are less effective at distinguishing between classes than the prior on average. Our results show that in the particular case of conditionally-independent Gaussian data, the Bayes-optimal predictor suffers from bias as the Mahalanobis distance between class means decreases, leading to a noticeable increase even when the prior is only somewhat biased. The effect is strong enough to manifest in real settings where Bayes-optimality doesn't necessarily hold, but GNB outperforms other linear classifiers.

2.2 FEATURE ASYMMETRY AND GRADIENT DESCENT

When the learning rule does not produce a Bayes-optimal predictor, it may be the case that excess bias can safely be removed without harming accuracy. To support this claim, we turn our attention

to logistic regression classifiers trained using stochastic gradient descent. Logistic regression predictors for data generated according to Equation 3 converge in the limit to the same Bayes-optimal predictors studied in Theorem 1 and Corollary 1 (Murphy, 2012).

Logistic regression models make fewer assumptions about the data and are therefore more widely-applicable, but as we demonstrate in this section, this flexibility comes at the expense of an inductive bias that can lead to systematic bias in predictions. To show this, we continue under our assumption that $\mathbf{x}$ and y are generated according to Equation 3, and consider the case where $p^* = 1/2$. According to Corollary 1, any systematic bias that emerges must come from differences between the trained classifier h_S and the Bayes-optimal h^*, i.e., a consequence of gradient descent's inductive bias.

2.2.1 Feature Asymmetry

To define what is meant by "feature asymmetry", consider the orientation of each feature x_j as given by the sign of $\mu_{1j} - \mu_{0j}$. The sign of each coefficient in h^* will correspond to its feature orientation, so we can think of each feature as being "towards" either class 0 or class 1. Likewise, we can view the combined features as being *asymmetric towards* y when there more features oriented towards y than there are towards $1 - y$.

As shown in Table 1, high-dimensional data with biased class priors often exhibit feature asymmetry towards the majority class. This does not necessarily lead to excessive bias, and the analysis from the previous section indicates that if $p^* = 1/2$ then it may be possible to learn a predictor with no bias. However, if the learning rule overestimates the importance of some of the features oriented towards the majority class, then variance in those features present in minority instances will cause mispredictions that lead to excess bias beyond what is characterized in Theorem 1.

This problem is pronounced when many of the majority-oriented features are weak predictors, which in this setting means that they have high variance. The magnitude of the coefficients for weak features will be small relative to the others in h^*, but if the learner systematically overestimates them in h_S, the resulting classifier will be "out of balance" with the distribution generating the data.

Figure 2 explores this phenomenon through synthetic data exemplifying a strong/weak feature dichotomy, in which the *strong* features have low variance and high Bayes-optimal weight, and the *weak* features have relatively higher variance and low Bayes-optimal weight. In particular, Figure 2c shows that overestimation of weak features is precisely the form of inductive bias exhibited by gradient descent when learning logistic classifiers. As h_S converges to the Bayes-optimal, the magnitude of weak-feature coefficients gradually decreases to the appropriate quantity. As the variance increases, the extent of the overapproximation grows accordingly.

2.2.2 Prediction Bias from Inductive Bias

While the classifier remains far from convergence, the cumulative effect of their overapproximation with high-dimensional data leads to systematic bias. Figure 2a demonstrates that as the disparity in weak features towards class 1 increases, so does the expected bias towards class 1. This bias cannot be explained by Theorem 1, because this data is distributed with $p^* = 1/2$. Rather, it is clear that the effect diminishes as the training size increases and h_S converges towards h^*. This suggests gradient descent tends to "overuse" the weak features, leading to systematic bias that over-predicts the majority class in asymmetric regimes.

Figure 2b demonstrates that for a fixed disparity in weak features, the features must be sufficiently weak in order to cause bias. This suggests that a feature imbalance alone is not sufficient for causing systematic bias. Moreover, the weak features, rather than the strong features, are responsible for the bias. As the training size increases, the amount of variance required to cause bias increases. However, when the features have sufficiently high variance, the model will eventually decrease their contribution, relieving their impact on the bias and accuracy of the model.

Summary: When the data is distributed asymmetrically with respect to features' orientation towards a class, gradient descent may lead to systematic bias especially when many of the asymmetric features are weak predictors. This bias is a result of the learning rule, as it manifests in cases where a Bayes-optimal predictor would exhibit no bias, and therefore it may be possible to mitigate it without harming accuracy.

Figure 2: (a), (b): Expected bias (computed from 1000 samples) as a function of (a) number of weak features and (b) variance of the weak features, shown for models trained on $N = 100, 500, 1000$. Variance in (a) is fixed at 10, and in (b) the number of features is fixed at 256. (c): Extent of overestimation of weak-feature coefficients in logistic classifiers trained with stochastic gradient descent, in terms of the amount of training data. The vertical axis is the difference in magnitude between the trained coefficient (h_S) and that of the Bayes-optimal predictor (h^*). In (a)-(c), $p^* = 1/2$, there is one strong feature (variance 1), and results are averaged over 100 training runs.

3 MITIGATING FEATURE-WISE BIAS AMPLIFICATION

While Theorem 1 suggests that some bias is unavoidable, the empirical analysis in the previous section shows that some systematic bias may not be. Our analysis also suggests an approach for removing such bias, namely by identifying and removing the weak features that are systematically overestimated by gradient descent. In this section, we describe two approaches for accomplishing this that are based on measuring the influence (Leino et al., 2018) of features on trained models. In Section 4, we show that these methods are effective at mitigating bias without harming accuracy on both logistic predictors and deep networks.

3.1 INFLUENCE-DIRECTED FEATURE REMOVAL

Given a model $h : \mathcal{X}_0 \to \mathbb{R}$ and feature, x_j, the *influence* χ_j of x_j on h is a quantitative measure of feature j's contribution to the output of h. To extend this notion to internal layers of a deep network h, we consider the *slice abstraction* (Leino et al., 2018) comprised of a pair of functions $f : \mathcal{X}_0 \to \mathcal{X}$, and $g : \mathcal{X} \to \mathbb{R}$, such that $h = g \circ f$. We define f to be the network up to the penultimate layer, and g be the final layer. Intuitively, We can then think of the features as being precomputed by f, i.e., $\mathbf{x} = f(\mathbf{x}_0)$ for $\mathbf{x}_0 \in \mathcal{X}_0$, allowing us to treat the final layer as a linear model acting on features computed via a deep network. Note that the slice abstract encompasses linear models as well, by defining f to be the identity function.

A growing body of work on influence measures (Simonyan, Vedaldi, and Zisserman, 2013; Sundararajan, Taly, and Yan, 2017; Leino et al., 2018) provides numerous choices for χ_j, each with different tradeoffs. We use the *internal distributional influence* (Leino et al., 2018), as it incorporates the slice abstraction naturally. This measure is given by Equation 4 for a *distribution of interest* P, which characterizes the distribution of test instances.

$$\chi_j(g \circ h, P) = \int_{\mathbf{x} \in \mathcal{X}_0} \left. \frac{\partial g}{\partial h(\mathbf{x})_j} \right|_{h(\mathbf{x})} P(\mathbf{x}) d\mathbf{x} \qquad (4)$$

We now describe two techniques that use this measure to remove features causing bias.

Feature parity. Motivated by the fact that bias amplification may be caused by feature asymmetry, we can attempt to mitigate it by enforcing parity in features across the classes. To avoid removing features that are useful for correct predictions, we order the features by their influence on the model's output, and remove features from the majority class until parity is reached. If the model has a bias term, we adjust it by subtracting the product of each removed coefficient and the mean of its corresponding feature.

dataset	p^*	asymm. (%)	$B_{\mathcal{D}}(h_S)$	$B_{\mathcal{D}}(h_S)$ (post-fix)			acc. (%)	acc. (%) (post-fix)		
				par	exp	ℓ_1		par	exp	ℓ_1
CIFAR10	50.0	52.0	1.8	1.7	**0.4**	n/a	93.0	93.1	**94.0**	n/a
CelebA	50.4	50.2	7.7	7.7	**0.2**	n/a	79.6	79.6	**79.9**	n/a
arcene	56.0	57.7	2.7	**0.6**	1.2	1.7	68.9	69.0	**74.2**	69.4
colon	64.5	51.0	23.1	22.9	**22.6**	35.5	58.5	58.7	58.7	**64.5**
glioma	69.4	54.8	17.4	17.4	**12.2**	17.0	76.3	**76.3**	76.7	75.44
micromass	69.0	54.1	0.68	**0.66**	0.69	0.68	**98.4**	**98.4**	**98.4**	**98.4**
pc/mac	50.5	60.6	1.6	1.6	**1.4**	1.6	**89.0**	**89.0**	88.0	**89.0**
prostate	51.0	44.4	47.3	47.2	**10.0**	28.1	52.7	52.8	**90.2**	71.3
smokers	51.9	50.4	47.4	45.4	**8.0**	33.0	50.0	50.7	**59.0**	51.2
synthetic	50.0	99.9	24.1	17.2	23.6	**5.7**	74.9	**77.9**	74.8	71.4

Table 1: Bias measured on real datasets, and results of applying one of three mitigation strategies: feature parity (*par*), influence-directed experts (*exp*), and ℓ_1 regularization. The columns give: p^*, percent class prior for the majority class ($y = 1$); *asymm*, the percentages of features oriented towards $y = 1$; $B_{\mathcal{D}}(h_S)$ the bias of the learned model on test data, which we measure before and after each fix (*post-fix*); *acc*, the test accuracy before and after each fix. The first two rows are experiments on deep networks, and the remainder are on 20 training runs of logistic regression with stochastic gradient descent. ℓ_1 regularization was not applied to the deep network experiments due to the cost of hyperparameter tuning.

Experts   Section 2.2 identifies "weak" features as a likely source of systematic bias. This is a somewhat artificial construct, as real data often does not exhibit a clear separation between strong and weak features. Qualitatively, the weak features are less predictive than the strong features, and the learner accounts for this by giving less influence to the weak features. Thus, we can think of imposing a strong/weak feature dichotomy by defining the weak features to be those such that $|\chi_j| < \chi^*$ for some threshold χ^*. This reduces the feature selection problem to a search for an appropriate χ^* that mitigates bias to the greatest extent without harming accuracy.

We parameterize this search problem in terms of α, β, where the α features with the most positive influence and β features with the most negative influence are "strong", and the rest are considered weak. This amounts to selecting the *class-wise expert* (Leino et al., 2018) for the dominant class. Formally, let F_α be the set of α features with the α highest positive influences, and F_β the set of β features with the β most negative influences. For slice $h = g \circ f$, let g_β^α be defined as model g with its weights replaced by w_β^α as defined by Equation 5. Then we define *expert*, $g_{\beta^*}^{\alpha^*}$, to be the classifier given by setting α^* and β^* according to Equation 6. In other words, the α and β that minimize bias while maintaining at least the original model's accuracy.

$$\mathbf{w}_{\beta\ j}^\alpha = \begin{cases} \mathbf{w}_j & j \in F_\alpha \cup F_\beta \\ 0 & j \notin F_\alpha \cup F_\beta \end{cases}, \tag{5}$$

$$\alpha^*, \beta^* = \operatorname*{arg\,min}_{\alpha, \beta} \left| B_{\mathcal{D}}(g_\beta^\alpha) \right| \text{ subject to } L_S(g_\beta^\alpha) \le L_S(g) \tag{6}$$

We note that this is always feasible by selecting all the features. Furthermore, this is a discrete optimization problem, which can be solved efficiently with a grid search over the possible α and β. In practice, even when there are many features, we can exhaustively search this space. When there are ties we can break them by preferring the model with the greatest accuracy.

4   EXPERIMENTS

In this section we present empirical evidence to support our claim that feature-wise bias amplification can safely be removed without harming the accuracy of the classifier. We show this on both logistic predictors and deep networks by measuring the bias on several benchmark datasets, and running the parity and expert mitigation approaches described in Section 3. As a baseline, we compare against ℓ_1 regularization in the logistic classifier experiments.

The results are shown in Table 1. To summarize, on every dataset we consider, at least one of the methods in Section 3 proves effective at reducing the classifier's bias amplification. ℓ_1 regu-

larization removes bias less reliably, and never to the extent that our methods do. In all but two cases, the influence-directed experts show the best performance in terms of bias removal, and this method is able to reduce bias in all but one case. In terms of accuracy, our methods consistently improve classifier performance, and in some cases significantly. For example, on the *prostate* dataset, influence-directed experts removed 80% of the prediction bias while improving accuracy from 57.7% to 90.2%.

Data. We performed experiments over eight binary classification datasets from various domains (rows 3-11 in Table 1) and two image classification datasets (CIFAR10-binary, CelebA). Our criteria for selecting logistic regression datasets were: high feature dimensionality, binary labels, and row-structured instances (i.e., not time series data). Among the logistic regression datasets, *arcene*, *colon*, *glioma*, *pc/mac*, *prostate*, *smokers* were obtained from the scikit-feature repository (Li et al., 2016), and *micromass* was obtained from the UCI repository (Dheeru and Karra Taniskidou, 2017). The synthetic dataset was generated in the manner described in Section 2.2, containing one strongly-predictive feature ($\sigma^2 = 1$) for each class, 1,000 weak features ($\sigma^2 = 3$), and $p^* = 1/2$.

For the deep network experiments, we created a binary classification problem from CIFAR10 (Krizhevsky and Hinton, 2009) from the "bird" and "frog" classes. We selected these classes as they showed the greatest posterior disparity on VGG16 network trained on the original dataset. For CelebA, we trained a VGG16 network with one fully-connected layer of 4096 units to predict the *attractiveness* label given in the training data.

Methodology. For the logistic regression experiments, we used scikit-learn's SGDClassifier estimator to train each model using the logistic loss function. Logistic regression measurements were obtained by averaging over 20 pseudorandom training runs on a randomly-selected stratified train/test split. Experiments involving ℓ_1 regularization use a grid search to select the regularization paramter, optimizing forthe greatest reduction of $B_{\mathcal{D}}(h_S)$ on the training data. Similarly, experiments involving experts selected α, β using grid search over the possible values as described in Section 3. Experiments on deep networks use the training/test split provided by the respective dataset authors. Models were trained until convergence using Keras 2 with the Theano backend.

Logistic regression. Table 1 shows that on linear models, feature parity always improves or maintains the model in terms of both bias amplification and accuracy. Notably, in each case where feature parity removes bias, the accuracy is likewise improved, supporting our claim that bias resulting from asymmetric feature regimes is avoidable. In most cases, the benefit from applying feature parity is however rather small. *arcene* is the exception, which is likely due to the fact that it has large feature asymmetry and substantial bias in the original model, leaving ample opportunity for improvement by this approach.

The results suggest that influence-directed experts are the most effective mitigation technique, both in terms of bias removal and accuracy improvement. In most datasets, this approach reduced bias while improving accuracy, often substantially. Most notably on the *prostate* dataset, where the original model failed to achieve accuracy appreciably greater than chance and extreme bias. The mitigation achieves 90% accuracy while removing 80% of the bias, improving the model significantly. Similarly, for *arcene* and *smokers*, this approach removed over 50% of the prediction bias while improving accuracy 5-11%.

ℓ_1 regularization proved least reliable at removing bias. Except on the synthetic data, it did not as often succeed at removing significant bias without harming accuracy (exceptions on *arcene*, *prostate*, and *smokers*). In some cases, it made bias significantly worse (*colon*) for gains in accuracy, or gave moderate improvement in bias for slightly worse accuracy (*glioma*).

Deep networks. The results show that deep networks tend to have a less significant feature asymmetry than data used for logistic models, which we would expect to render the feature parity approach less effective. The results confirm this, although on CIFAR10 parity had some effect on bias and a proportional positive effect on accuracy. Influence-directed experts, on the other hand, continued to perform well for the deep models. While this approach generally had a greater effect on accuracy than bias for the linear models, this trend reversed for deep networks, where the decrease in bias was consistently greater than the increase in accuracy. For example, the 7.7% bias in the original CelebA model was reduced by approximately 98% to 0.2%, effectively eliminating it

from the model's predictions. The overall effect on accuracy remained modest (0.3% improvement), however.

These results on deep networks are somewhat surprising, considering that the techniques described in Section 3 were motivated by observations concerning simple linear classifiers. While the improvements in accuracy are not as significant as those seen on linear classifiers, they align with our expectations regarding bias reduction. This suggests that future work might improve on these results by adapting the approach described in this paper to better suit deep networks.

5 RELATED WORK

While the term bias is used in a number of different contexts in machine learning, we use *bias amplification* in the sense of (Zhao et al., 2017), where the distribution over prediction outputs is skewed in comparison to the prior distribution of the prediction target. For example, (Zhao et al., 2017) and (Burns et al., 2018) use the imSitu vSRL dataset to perform the MS-COCO task, i.e. to classify agents and actions (among other elements) in pictures. In the dataset, women are 33% more likely to be the agent in pictures where the action is cooking, but the model predicted 68% of people cooking to be women on the test set.

In a related example, a recent paper by Stock and Cissé identifies bias in models trained on the ImageNet dataset. Despite there being near-parity of white and black people in pictures in the basketball class, 78% of the images that the model classified as *basketball* had black people in them and only 44% had white people in them. Additionally, 90% of the misclassified *basketball* pictures had white people in them, whereas only 20% had black people in them. Note that this type of bias over classes is distinct from the learning bias in machine learning (Geman, Bienenstock, and Doursat, 1992) which has received renewed interest in the context of SGD and under-determined models (Gunasekar et al., 2018; Soudry et al., 2017).

Bias amplification is often thought to be result of class imbalance in the training data, which is well-studied in the learning community (see (He and Garcia, 2009) and (Buda, Maki, and Mazurowski, 2017) for comprehensive surveys). There are a myriad of empirical investigations of the effects of class imbalance in machine learning and different ways of mitigating these effects (Maloof, 2003; Chawla, 2005; Mazurowski et al., 2008; Oommen, Baise, and Vogel, 2011; Wallace et al., 2011b).

It has been shown that neural networks are affected by class imbalance as well (Murphey, Guo, and Feldkamp, 2004; Buda, Maki, and Mazurowski, 2017). Buda, Maki, and Mazurowski point out that the detrimental effect of class imbalance on neural networks increases with scale. They advocate for an oversampling technique mixed with thresholding to improve accuracy based on empirical tests. An interesting and less common technique from Havaei et. al. relies on a drastic change to neural network training procedure in order to better detect brain tumors: they first train the net on an even distribution, and then on a representative sample, but only on the output layer in the second half of training (Havaei et al., 2015).

In contrast to prior work, we demonstrate the bias amplification can occur without existing imbalances in the training set. Therefore, we identify a new source of bias that can be traced to particular features in the model. Since we remove bias feature-wise, our approach can also be viewed as method for feature selection. While feature selection is a well-studied problem, to the authors' knowledge, no one has looked at removing features to mitigate *bias* in a model, only to improve accuracy, and this is usually during training (Chandrashekar and Sahin, 2014). We select features to remove, post-hoc, that are likely to increase bias, and can be removed while maintaining accuracy.

REFERENCES

Bolukbasi, T.; Chang, K.; Zou, J. Y.; Saligrama, V.; and Kalai, A. 2016. Man is to computer programmer as woman is to homemaker? debiasing word embeddings. *CoRR* abs/1607.06520.

Buda, M.; Maki, A.; and Mazurowski, M. A. 2017. A systematic study of the class imbalance problem in convolutional neural networks. *CoRR* abs/1710.05381.

Burns, K.; Hendricks, L. A.; Darrell, T.; and Rohrbach, A. 2018. Women also snowboard: Overcoming bias in captioning models. *CoRR* abs/1803.09797.

Chandrashekar, G., and Sahin, F. 2014. A survey on feature selection methods. *Computers and Electrical Engineering* 40(1):16 – 28. 40th-year commemorative issue.

Chawla, N. 2005. Data mining for imbalanced datasets: An overview.

Dheeru, D., and Karra Taniskidou, E. 2017. UCI machine learning repository.

Geman, S.; Bienenstock, E.; and Doursat, R. 1992. Neural networks and the bias/variance dilemma. *Neural Comput.* 4(1):1–58.

Gunasekar, S.; Lee, J.; Soudry, D.; and Srebro, N. 2018. Implicit Bias of Gradient Descent on Linear Convolutional Networks. *ArXiv e-prints*.

Hart, R. D. 2017. If you're not a white male, artificial intelligence's use in healthcare could be dangerous. `https://goo.gl/Mtgf8B`, July 10 2017. Retrieved 9/25/18.

Havaei, M.; Davy, A.; Warde-Farley, D.; Biard, A.; Courville, A. C.; Bengio, Y.; Pal, C.; Jodoin, P.; and Larochelle, H. 2015. Brain tumor segmentation with deep neural networks. *CoRR* abs/1505.03540.

He, H., and Garcia, E. A. 2009. Learning from imbalanced data. *IEEE Transactions on Knowledge and Data Engineering* 21(9):1263–1284.

Krizhevsky, A., and Hinton, G. 2009. Learning multiple layers of features from tiny images. *Master's thesis, Department of Computer Science, University of Toronto.*

Leino, K.; Li, L.; Sen, S.; Datta, A.; and Fredrikson, M. 2018. Influence-directed explanations for deep convolutional networks. *CoRR* abs/1802.03788.

Li, J.; Cheng, K.; Wang, S.; Morstatter, F.; Trevino, R. P.; Tang, J.; and Liu, H. 2016. Feature selection: A data perspective. *arXiv preprint arXiv:1601.07996*.

Liu, Z.; Luo, P.; Wang, X.; and Tang, X. 2015. Deep learning face attributes in the wild. In *Proceedings of International Conference on Computer Vision (ICCV)*.

Maloof, M. A. 2003. Learning when data sets are imbalanced and when costs are unequeal and unknown.

Mazurowski, M. A.; Habas, P. A.; Zurada, J. M.; Lo, J. Y.; Baker, J. A.; and Tourassi, G. D. 2008. Training neural network classifiers for medical decision making: The effects of imbalanced datasets on classification performance. *Neural Networks* 21(2):427 – 436. Advances in Neural Networks Research: IJCNN '07.

Murphey, Y.; Guo, H.; and Feldkamp, L. 2004. Neural learning from unbalanced data: Special issue: Engineering intelligent systems (guest editor: László monostori). 21.

Murphy, K. P. 2012. *Machine Learning: A Probabilistic Perspective*. The MIT Press.

Oommen, T.; Baise, L.; and Vogel, R. 2011. Sampling bias and class imbalance in maximum-likelihood logistic regression. 43:99–120.

Simonyan, K.; Vedaldi, A.; and Zisserman, A. 2013. Deep inside convolutional networks: Visualising image classification models and saliency maps. *CoRR* abs/1312.6034.

Soudry, D.; Hoffer, E.; Shpigel Nacson, M.; Gunasekar, S.; and Srebro, N. 2017. The Implicit Bias of Gradient Descent on Separable Data. *ArXiv e-prints*.

Stock, P., and Cissé, M. 2017. Convnets and imagenet beyond accuracy: Explanations, bias detection, adversarial examples and model criticism. *CoRR* abs/1711.11443.

Sundararajan, M.; Taly, A.; and Yan, Q. 2017. Axiomatic attribution for deep networks. *CoRR* abs/1703.01365.

Wallace, B. C.; Small, K.; Brodley, C. E.; and Trikalinos, T. A. 2011a. Class imbalance, redux. In *2011 IEEE 11th International Conference on Data Mining*.

Wallace, B. C.; Small, K.; Brodley, C. E.; and Trikalinos, T. A. 2011b. Class imbalance, redux. In *2011 IEEE 11th International Conference on Data Mining*, 754–763.

Zhao, J.; Wang, T.; Yatskar, M.; Ordonez, V.; and Chang, K. 2017. Men also like shopping: Reducing gender bias amplification using corpus-level constraints. *CoRR* abs/1707.09457.

A PROOFS

Theorem 1 *Let* $\mathbf{x}$ *be distributed according to Equation 3,* y *be Bernoulli with parameter* p^*, D *be the Mahalanobis distance between the class means* $\boldsymbol{\mu}_0^*, \boldsymbol{\mu}_1^*$, *and* $\beta = -D^{-1}\log(p^*/(1-p^*))$. *Then the bias amplification of the Bayes-optimal classifier* h^* *is:*

$$B_{\mathcal{D}}(h^*) = 1 - p^* - (1 - p^*)\Phi\left(\beta + \frac{D}{2}\right) - p^*\Phi\left(\beta - \frac{D}{2}\right)$$

Proof. Note that the Bayes-optimal classifier can be expressed as a linear weighted sum (Murphy, 2012) in terms of parameters $\hat{\mathbf{w}}, \hat{b}$ as shown in Equation 7.

$$\Pr[Y = 1|X = \mathbf{x}] = (1 + \exp - (\hat{\mathbf{w}}^T\mathbf{x} + \hat{b}))^{-1} \tag{7}$$
$$\hat{\mathbf{w}} = \hat{\boldsymbol{\Sigma}}^{-1}(\hat{\boldsymbol{\mu}}_1 - \hat{\boldsymbol{\mu}}_0)$$
$$\hat{b} = -\frac{1}{2}(\hat{\boldsymbol{\mu}}_1 - \hat{\boldsymbol{\mu}}_0)^T\hat{\boldsymbol{\Sigma}}^{-1}(\hat{\boldsymbol{\mu}}_1 + \hat{\boldsymbol{\mu}}_0) + \log\frac{\hat{p^*}}{1 - \hat{p^*}}$$

The random variable $\mathbf{w}^T X$ is a univariate Gaussian with variance $\mathbf{w}^T\boldsymbol{\Sigma}\mathbf{w}$ and mean $\mathbf{w}^T\boldsymbol{\mu}_y$ when $Y = y$. Then the quantity we are interested in is shown in Equation 8, where Φ is the CDF of the standard normal distribution.

$$\Pr\left[\mathbf{w}^T X > -b \middle| Y = y\right] = 1 - \Phi\left(\frac{-b - \mathbf{w}^T\boldsymbol{\mu}_y}{\sqrt{\mathbf{w}^T\boldsymbol{\Sigma}\mathbf{w}}}\right) \tag{8}$$

Notice that the quantity

$$\mathbf{w}^T(\boldsymbol{\mu}_1 - \boldsymbol{\mu}_0) = (\boldsymbol{\mu}_1 - \boldsymbol{\mu}_0)^T\boldsymbol{\Sigma}^{-1}(\boldsymbol{\mu}_1 - \boldsymbol{\mu}_0)$$

is the square of the Mahalanobis distance between the class means.

$$-b - \mathbf{w}^T\boldsymbol{\mu}_0 = \frac{1}{2}\mathbf{w}^T(\boldsymbol{\mu}_1 - \boldsymbol{\mu}_0) - \log\frac{p^*}{1 - p^*}$$
$$= \frac{D^2}{2} - \log\frac{p^*}{1 - p^*}$$
$$-b - \mathbf{w}^T\boldsymbol{\mu}_1 = -\frac{1}{2}\mathbf{w}^T(\boldsymbol{\mu}_1 - \boldsymbol{\mu}_0) - \log\frac{p^*}{1 - p^*}$$
$$= -\frac{D^2}{2} - \log\frac{p^*}{1 - p^*}$$

Similarly, we can rewrite the standard deviation of $\mathbf{w}^T X$ exactly as D. Rewriting the numerator in the Φ term of (8),

$$(\mathbf{w}^T\boldsymbol{\Sigma}\mathbf{w})^{\frac{1}{2}} = \left((\boldsymbol{\mu}_1 - \boldsymbol{\mu}_0)^T\boldsymbol{\Sigma}^{-1}\boldsymbol{\Sigma}\boldsymbol{\Sigma}^{-1}(\boldsymbol{\mu}_1 - \boldsymbol{\mu}_0)\right)^{\frac{1}{2}}$$
$$= \left((\boldsymbol{\mu}_1 - \boldsymbol{\mu}_0)^T\boldsymbol{\Sigma}^{-1}(\boldsymbol{\mu}_1 - \boldsymbol{\mu}_0)\right)^{\frac{1}{2}}$$
$$= D$$

Then we can write $\Pr\left[\mathbf{w}^T X > -b\right]$ as:

$$(1 - p^*)\left(1 - \Phi\left(\beta + \frac{D}{2}\right)\right) + p^*\left(1 - \Phi\left(\beta - \frac{D}{2}\right)\right)$$
$$= 1 - (1 - p^*)\Phi\left(\beta + \frac{D}{2}\right) - p^*\Phi\left(\beta - \frac{D}{2}\right)$$

$\square$

Corollary 1 *When* $\mathbf{x}$ *is distributed according to Equation 3 and* $p^* = 1/2$, $B_{\mathcal{D}}(h^*) = 0$.

Proof. Note that because $p^* = 1/2$, the term $\beta = 0$ in Theorem 1. Using the main result of the theorem, we have:

$$
\begin{aligned}
\Pr\left[\mathbf{w}^T X > -b\right] &= 1 - \frac{1}{2}\left[\Phi\left(\frac{D}{2}\right) + \Phi\left(-\frac{D}{2}\right)\right] \\
&= 1 - \frac{1}{2}\left[\Phi\left(\frac{D}{2}\right) + \left(1 - \Phi\left(\frac{D}{2}\right)\right)\right] \\
&= \frac{1}{2}
\end{aligned}
$$

The third equality holds because Φ has rotational symmetry about $(0, 1/2)$, giving the identity $\Phi(-x) = 1 - \Phi(x)$.

□