Deformable Medical Image Registration Using a Randomly-Initialized CNN as Regularization Prior

Max-Heinrich Laves   LAVES@IMES.UNI-HANNOVER.DE
Sontje Ihler   IHLER@IMES.UNI-HANNOVER.DE
Tobias Ortmaier   ORTMAIER@IMES.UNI-HANNOVER.DE
Institute of Mechatronic Systems, Leibniz Universität Hannover, Germany

Abstract

We present deformable unsupervised medical image registration using a randomly-initialized deep convolutional neural network (CNN) as regularization prior. Conventional registration methods predict a transformation by minimizing dissimilarities between an image pair. The minimization is usually regularized with manually engineered priors, which limits the potential of the registration. By learning transformation priors from a large dataset, CNNs have achieved great success in deformable registration. However, learned methods are restricted to domain-specific data and the required amounts of medical data are difficult to obtain. Our approach uses the idea of deep image priors to combine convolutional networks with conventional registration methods based on manually engineered priors. The proposed method is applied to brain MRI scans. We show that our approach registers image pairs with state-of-the-art accuracy by providing dense, pixel-wise correspondence maps. It does not rely on prior training and is therefore not limited to a specific image domain.

Keywords: deformable registration, convolutional network, optical coherence tomography

1. Introduction

Deformable registration is a major challenge in medical image processing. The result is a dense mapping showing pixel-wise non-linear correspondences between a pair of images that best aligns the input image I onto the target image T by means of some similarity definition $\mathcal{L}$. Deformable registration is applied in the analysis of patient-specific temporal or anatomical changes, e.g. from pre-operative to post-operative state, or to show inter-patient variances (Sotiras et al., 2013). Deformable registration is also performed in atlas-based segmentation, where an input image is matched onto a target image with known segmentation (Cabezas et al., 2011).

Existing registration methods can be separated into two categories. The first category is based on non-learning methods which estimate a registration w by optimizing a cost function of the form

$$\arg \min_{w} \left\{ \mathcal{L}(T, w \circ I) + \lambda \mathcal{R}(w) \right\} , \tag{1}$$

where $w \circ I$ denotes I warped by w. A common assumption of w is a displacement vector field $\boldsymbol{u}$ mapping every pixel coordinate to other pixel coordinates. The first term is referred to as data term, which is typically chosen to be a pixel intensity error measure. Optimization

Figure 1: Overview of our method. The randomly-initialized generator network f_θ acts as parameterization of the registration field $\boldsymbol{u}$. The parameters θ are optimized for every image pair individually by gradient descent.

of the data term alone is considered ill-posed. The second term $\mathcal{R}$, weighted by trade-off factor λ, is a regularizer that shapes the registration by any chosen prior, which helps solving the ill-posed problem. Common regularization is done by enforcing smoothness onto the displacement vector field by penalizing first or higher order spatial derivatives of $\boldsymbol{u}$ (Werlberger et al., 2010). The result of the registration algorithm heavily depends on the cost function and therefore on the chosen prior of $\mathcal{R}$.

The second category implicitly learns the regularization prior by training a convolutional network on a large database of domain-specific images. Early approaches rely on ground truth registrations (Sokooti et al., 2017), which are hard to obtain especially in medical imaging. More recent methods (Balakrishnan et al., 2019) propose unsupervised registration using the spatial transformer function (Jaderberg et al., 2015). However, these methods either only support small displacements or require segmentation maps of the image pairs during training to assist the convergence (Hu et al., 2018). Additionally, the trained networks are limited to register images from the training domain (e.g. CT or MRI).

Inspired by the idea of deep image priors (Lempitsky et al., 2018), we subsequently propose our learning-free method for deformable medical image registration using the structure of an untrained convolutional network as regularization prior.

2. Methods

Lempitsky et al. have recently shown that the excellent performance of CNNs for inverse image problems, such as denoising, is not only based on their ability to learn image priors from data, but is also based on the structure of a convolutional image generator itself (Lempitsky et al., 2018). They gave evidence that the structure of a network alone is sufficient to capture enough image statistics to provide state-of-the-art performance in inverse image tasks.

Leveraged by this idea, we reformulate the task of deformable image registration by using the structure of a convolutional network as regularizer (see Fig. 1). An image generator network $\boldsymbol{u} = f_\theta(z)$ with randomly-initialized parameters θ is interpreted as parameterization of the dense correspondence mapping $\boldsymbol{u} \in \mathbb{R}^{2 \times H \times W}$ between an input image $I \in \mathbb{R}^{C \times H \times W}$

Figure 2: Results of our approach compared to a state-of-the-art method from the Insight ToolKit (ITK). Left: Two example MRI pairs from the data set. Right: Boxplots of the means of $\det(J_{\boldsymbol{u}})$ and SSIM between T and $\boldsymbol{u} \circ I$.

and a target image $T \in \mathbb{R}^{C \times H \times W}$. The input $z \in \mathbb{R}^{C' \times H \times W} \sim \mathcal{N}(0, 0.1)$ has the same spatial dimensions as $\boldsymbol{u}$ and is sampled from a random normal distribution in every iteration. This leads to the following optimization problem

$$\arg\min_{\theta} \left\{ \mathcal{L}\left(T, f_{\theta}(z) \circ I\right) \right\}, \tag{2}$$

where $f_{\theta}(z) \circ I$ denotes the differentiable spatial transformer function (Jaderberg et al., 2015). Eq. (2) is optimized for every image pair $\{I, T\}$ using the Adam gradient descent optimizer (Kingma and Ba, 2014). As data term, we chose pixel-wise mean absolute error $\mathcal{L}(T, f_{\theta} \circ I) = |(f_{\theta} \circ I) - T|$. The architecture of the image generator network f_{θ} is chosen according to (Lempitsky et al., 2018). It has an encoder-decoder structure with skip connections between the encoding and decoding part.

3. Results & Conclusion

We demonstrate our approach on the task of 2D brain magnetic resonance imaging (MRI) registration. The data used in this work contain 109 pairs of MRI scans from The Cancer Genome Atlas (NCI, 2019) showing lower-grade gliomas. We use the structural similarity index (SSIM) (Wang et al., 2004) between $\boldsymbol{u} \circ I$ and T and the mean of the determinants of Jacobians $\det(J_{\boldsymbol{u}})$ (Ashburner, 2007) of the warp as evaluation metrics. The latter metric shows regularity of $\boldsymbol{u}$. We compare our method to state-of-the-art methods from the Insight ToolKit (ITK) registration framework by combining an initial affine registration and a subsequent deformable displacement field registration (Avants et al., 2012). Results for exemplary image pairs and boxplots of results for all image pairs are shown in Fig. 2. Additional results including registration fields are shown in appendix A.

The results reveal that the structure of a convolutional network can act as regularization in deformable medical image registration with state-of-the-art performance. This connects traditional non-learning methods and learning-based methods by using randomly-initialized convolutional networks as prior.

Acknowledgments

This research has received funding from the European Union as being part of the EFRE OPhonLas project.

References

The Cancer Genome Atlas Program. https://www.cancer.gov/about-nci/organization/ccg/research/structural-genomics/tcga, 2019. Accessed: 2019-04-01.

John Ashburner. A fast diffeomorphic image registration algorithm. *NeuroImage*, 38(1): 95–113, 2007. doi: 10.1016/j.neuroimage.2007.07.007.

Brian B Avants, Nicholas J Tustison, Gang Song, Baohua Wu, Michael Stauffer, Matthew M McCormick, Hans J Johnson, and James C Gee. A unified image registration framework for ITK. In *International Workshop on Biomedical Image Registration*, pages 266–275. Springer, 2012.

Guha Balakrishnan, Amy Zhao, Mert R. Sabuncu, John Guttag, and Adrian V. Dalca. VoxelMorph: A Learning Framework for Deformable Medical Image Registration. *IEEE Transactions on Medical Imaging*, 2019. doi: 10.1109/TMI.2019.2897538.

Mariano Cabezas, Arnau Oliver, Xavier Lladó, Jordi Freixenet, and Meritxell Bach Cuadra. A review of atlas-based segmentation for magnetic resonance brain images. *Computer Methods and Programs in Biomedicine*, 104(3):e158–e177, 2011. doi: 10.1016/j.cmpb.2011.07.015.

Yipeng Hu, Marc Modat, Eli Gibson, Wenqi Li, Nooshin Ghavami, Ester Bonmati, Guotai Wang, Steven Bandula, Caroline M. Moore, Mark Emberton, Sébastien Ourselin, J. Alison Noble, Dean C. Barratt, and Tom Vercauteren. Weakly-supervised convolutional neural networks for multimodal image registration. *Medical Image Analysis*, 49:1–13, 2018. doi: https://doi.org/10.1016/j.media.2018.07.002.

Max Jaderberg, Karen Simonyan, Andrew Zisserman, and Koray Kavukcuoglu. Spatial Transformer Networks. In *Advances in Neural Information Processing Systems 28*, pages 2017–2025, 2015.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv e-prints*, 2014. URL https://arxiv.org/abs/1412.6980.

Victor Lempitsky, Andrea Vedaldi, and Dmitry Ulyanov. Deep Image Prior. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9446–9454, June 2018. doi: 10.1109/CVPR.2018.00984.

Hessam Sokooti, Bob de Vos, Floris Berendsen, Boudewijn P. F. Lelieveldt, Ivana Išgum, and Marius Staring. Nonrigid Image Registration Using Multi-scale 3D Convolutional Neural Networks. In *Medical Image Computing and Computer Assisted Intervention*, pages 232–239, 2017.

Aristeidis Sotiras, Christos Davatzikos, and Nikos Paragios. Deformable Medical Image Registration: A Survey. *IEEE Transactions on Medical Imaging*, 32(7):1153–1190, July 2013. doi: 10.1109/TMI.2013.2265603.

Zhou Wang, Alan C Bovik, Hamid R Sheikh, Eero P Simoncelli, et al. Image quality assessment: from error visibility to structural similarity. *IEEE Transactions on Image Processing*, 13(4):600–612, 2004.

Manuel Werlberger, Thomas Pock, and Horst Bischof. Motion estimation with non-local total variation regularization. In *IEEE Conference on Computer Vision and Pattern Recognition*, pages 2464–2471, June 2010. doi: 10.1109/CVPR.2010.5539945.

Appendix A. Results

	SSIM	$\det(J_{\boldsymbol{u}})$
ITK	0.827 ± 0.096	1.036 ± 0.254
ours	0.913 ± 0.051	1.007 ± 0.045

Table 1: Mean results of SSIM between T and $\boldsymbol{u} \circ I$, and determinants of Jacobian $\det(J_{\boldsymbol{u}})$ of warp $\boldsymbol{u}$ compared to a state-of-the-art method from ITK.

Figure 3: Additional results showing image pairs $\{I, T\}$, warped input $\boldsymbol{u} \circ I$, estimated displacement grid $\boldsymbol{u}$ and map of determinants of the Jacobian matrix $J_{\boldsymbol{u}} = \nabla \boldsymbol{u}$ for every entry of $\boldsymbol{u}$. $J_{\boldsymbol{u}}$ shows local regularity of the displacement field. The deformation is diffeomorphic, where $\det(J_{\boldsymbol{u}}) > 0$.