UNSUPERVISED CLASSIFICATION INTO UNKNOWN NUMBER OF CLASSES

ABSTRACT

We propose a novel graph Laplacian based framework for the unsupervised classification task. Unlike the widely used classification method, this architecture does not require the labels of data and the number of classes. Our key idea is to introduce a approximate linear map and a spectral decomposition method on the dimension reduced space into generative adversarial networks. Inspired by the human visual recognition system, the proposed framework can classify and also generate images as the human brains do. We build a approximate linear connection analogous to the cerebral cortex, between the discriminator D and the generator G. This connection allows us to estimate the unknown number of classes. Estimating the number of classes is one of the challenging research in the unsupervised learning, especially in spectral clustering.

1 INTRODUCTION

Image classification has been one of the most important research in machine learning and artificial intelligence. For the predefined number k of classes, the classification models based on deep learning have performed well that the test accuracy is better than humans (Geirhos et al., 2017; He et al., 2016; Russakovsky et al., 2015; Szegedy et al., 2015). This result is, however, true only when the number of classes, k is predefined and we use the supervised learning with entire ground truth labels. Humans learn visual information by memorizing the compressed information (features) in the brain, reconstruct the object, and recognize the difference between objects. This capability allows humans to classify data where the number of classes is unknown into the reasonable numbers of classes. In this paper, we propose a method to mimic such human capability.

The main contribution of the proposed framework consists of two parts. We first show that there exists a approximate linear map between two separated neural networks of Generative Adversarial Networks (GANs). Secondly, we prove that the number of classes in a latent space is the same as the number of classes in the original space in terms of the multiplicity (corresponding to eigenvalue 0) of a Laplacian matrix in spectral clustering theory. By combining the results, We derive a novel unsupervised classification framework, which estimates the number of classes k and then extract k vectors representing each class. With the framework, the approximate linear map between two networks can induce the information of the spectral decomposed components in a data graph.

The latent variable model is commonly used in the generative models. Variational auto-encoders (VAEs) (Kingma & Welling, 2013) and GANs (Goodfellow et al., 2014) are a few of the most famous cases that learn the data distribution successfully. GANs randomly samples the latent variables that are used to train the data distribution so we cannot figure out which latent variable generates a result that we are interested in. To avoid the drawback by random sampling, auxiliary conditions on latent variables were introduced (Chen et al., 2016; Mirza & Osindero, 2014). Introducing a label information into the condition of the estimated data probability is highly effective in classification where a data point x came from, however this method is not a unsupervised learning. In addition, there are some GANs frameworks that analyze the property of latent spaces (Kumar et al., 2017; Radford et al., 2015).

Spectral clustering is one of the most popular clustering algorithm that outperforms other well-known clustering algorithms (Ng et al., 2002; Shi & Malik, 2000). Despite high performance, spectral clustering is difficult to use because it requires the full dataset that have very large N data points. In this case, the dimension of the Laplacian matrix is $N \times N$ and it takes at least $O(N^3)$. Therefore,

we need a novel dimension reduction technique to use spectral clustering in practical applications (Elhamifar & Vidal, 2009; Ji et al., 2017; Law et al., 2017; Shaham et al., 2018). Especially, we apply the self-expressiveness property (Elhamifar & Vidal, 2009) to the proposed method.

The main concepts of spectral clustering, GANs and the self-expressiveness property will be introduced Section 2. We prove the preliminary propositions that allow us to classify data with unsupervised learning methods in Section 3. Finally, we propose a unsupervised classification algorithm and test our algorithm in Section 4.

Recent image classification methods are based on supervised learning, in which a learning model processes a dataset consisting of pairs of an image and its ground-truth label. This training dataset usually consists of more than 10 K data point, some part of which need to be used for cross-validation. It also takes a lot of costs to produce a reliable training dataset.

2 PRELIMINARIES

In this section, we review cycle-consistent adversarial networks and sparse subspace clustering that we will use when extracting indicator vectors. We also overview the basic probabilistic property between a classification model and a generative model, which can be used as tools to generate indicator vectors.

2.1 CYCLE-CONSISTENT ADVERSARIAL NETWORKS

Generative Adversarial Networks (GANs) is a generative model that a generator network learns a data distribution implicitly (Goodfellow et al., 2014). GANs is a two player minimax game with two neural networks: a discriminator D and a generator G. The discriminator $D(\mathbf{x})$ is a probability measure that an input x follows the data distribution $p_{data}(\mathbf{x})$ rather than the generator's distribution p_g. The generator G is a mapping from the latent space $\mathbf{z} \sim p_{\mathbf{z}}$ to the data space. This minimax game can be represented as a stochastic optimization problem with value function given by

$$\min_G \max_D V(D, G) = \mathbb{E}_{x \sim p_{data}(\mathbf{x})} \left[\log D(\mathbf{x}) \right] + \mathbb{E}_{z \sim p_z(z)} \left[\log \left(1 - D \left(G \left(\mathbf{z} \right) \right) \right) \right]. \quad (1)$$

The cycle-consistent adversarial networks (cycleGANs) is a variant of GANs, which learns how to translate an representation from a source domain S to a target domain T without a paired dataset (Zhu et al., 2017). The cycle-consistency states that two mappings $G : S \to T$ and $F : T \to S$ encode the right permutation of images in S and T, so that, for an arbitrary data point $s \in S$, the mapping from S to T and back again, $F(G(s))$, should be the same as s. This property encourages adversarial networks G and D to have a connection between generated images and input data. We adopt two cycle consistency loss for the forward map and the backward map to learn a connection between two high-level representation domain in G and D.

2.2 SPARSE SUBSPACE CLUSTERING

Sparse subspace clustering is a clustering algorithm that is based on spectral clustering. Spectral clustering has many variants depending on the simiiliarity measure, Gaussian kernel similarity function (Ng et al., 2002), k-nearest neighbor graphs, ϵ-neighborhood graph. A similarity measure defined on the similarity graph $G = (V, E)$ is a pairwise metric between two data points (nodes) in a dataset and the similarity w_{ij} of two data points x_i, x_j is equal to or greater than 0. The similarity w_{ij} is also same as w_{ji} because the above similarity graph is defined as an undirected graph. The similarity matrix W is composed of the elements which correspond to the similarity measure w_{ij} respectively and then W is symmetric. See more details about spectral clustering in (Von Luxburg, 2007).

Sparse subspace clustering (Elhamifar & Vidal, 2009) uses a novel similarity matrix that is based on the self-expressiveness property. When we assume that the data space is a union of linear subspaces $S = \cup_{l=1}^{k} S_l$, we can express an arbitrary data point in the dataset as a linear combination of other data points in the dataset, where the coefficients of the data points in the same subspace are non-zero and others should be 0 (Elhamifar & Vidal, 2009; Ji et al., 2017). Formally, each data point $\mathbf{y}_i \in S$ can be reconstructed as $\mathbf{y}_i = \sum_{j=1}^{N} c_{ij}\mathbf{y}_j = \mathbf{Y}\mathbf{c}_i$, where $c_{ii} = 0$, N is the size of the dataset, $\mathbf{c}_i := [c_{i1} \ c_{i2} \ \cdots \ c_{iN}]^T$ is the coefficient vector of $\mathbf{y}_i$ and $\mathbf{Y} = [\mathbf{y}_1 \ \mathbf{y}_2 \ \cdots \ \mathbf{y}_N]$ is the dictionary

Figure 1: (a) shows the mappings relation in our proposed method. (b) shows the architecutre of the our networks.

matrix. The sparse solution of c_i indicates that the node i is in the same subspace as the node j if the element c_{ij} is non-zero. In this paper, we expand the notion of the self-expressiveness property to reduce the dimensionality of L in Section 3.3.

3 GRAPH LAPLACIAN OF THE CONNECTOR NETWORK

We first introduce our proposed architecture of adversarial networks. As point of view as autoencoder, we can consider two adversarial networks as autoencoder. We build a connector network between two networks to improve the cycle consistency and extract the information of connected components. (As shown in Figure 1-b). By training with the cycle-consistency loss, we can make the tuples (Z, X, H) for each data point X in a given dataset. Then, we show the relation between the spectral clustering and unsupervised classification. In order to show the relation, we prove the dimension reduction of the mutual expressiveness property.

3.1 DISENTANGLING UNFOLDS AND EXPANDING THE VOLUME OF MANIFOLD

Deep neural networks learn the high-level abstract representation of the data manifold and the well trained abstraction can disentangle the underlying factors of variation (Bengio et al., 2007). These properties allow interpolating between the data samples more naturally and smoothly. (Bengio et al., 2013) studied the disentangling effect and proposed three hypotheses about the shape of manifolds in the different representation domains. These hypotheses are verified by several empirical implementations (Goodfellow et al., 2009; Glorot et al., 2011). We can summarize three hypotheses as follows.

- The deeper representations can better disentangle the underlying factors of variation.
- Disentangled representations unfold the manifolds near which raw data concentrates irregularly and expand the relative volume occupied by high-probability points near these manifolds. Then these representations are with greater convexity.
- The underlying class factors of variations will be better disentangled than other factors, so the deeper layer has the better discriminant ability of classes.

In our proposed architecture, there are two high-level (deeper) representation spaces H and Z which is called as feature spaces. These feature spaces fill more uniformly the space than the pixel space

(a)   (b)

Figure 2: (a) shows the density of h for 1 and 2 MNIST, (b) shows the mean footprint of entire MNIST classes

X. H and Z also have the smoother density. Therefore, H and Z have greater than convexity than X and it allows the linear combination on these two manifolds in the feature spaces H and Z are and be more convex than the manifold in the pixel space X. By manifold hypothesis, the different class manifolds are well-separated by regions of very low density (Cayton, 2005). The feature spaces are the high-level representation spaces so that the density are unfolded and the linear combinations of features generates more natural results in the pixel space Bengio (2014).

Now, we can define the effective basis of the subspace for each class. In the feature spaces, each class manifold has the enough convexity. The class manifolds are well-separated and show good discriminant ability. Using both properties, we can build the effective basis for each class subspaces and generate the original space by the direct sum of these subspaces, where the subspaces are orthogonal. We empirically tested the effective basis as shown in Figure 3. Randomly sampled features in a subspace of the data space can be an effective basis and be possible to generate all data point in the same subspace. The features in the different subspaces cannot generate the given data samples. We can estimate the effective dimension using the number of the effective basis. Then, we can generate orthogonal subspaces of the entire classes if the effective dimension is small enough than the dimension of feature spaces.

3.2 Connector network and cycle consistency

We will study the relation between 3 different spaces, Z, X and H in the proposed architecture. As shown in the figure 1-(b), we can consider two adversarial networks as a decoder and an encoder of an auto-encoder respectively (Berthelot et al., 2017; Zhao et al., 2016). The discriminator network D encodes the pixel space X to the feature space H and generator network G decodes the feature space Z to X. We define the connector network C which maps from H to X. The map C between two feature spaces will be trained by the cycle consistency loss to obtain the tuples (Z, X, H) with the correct permutation, where all of elements is in the same-class manifold and shares same learned features.

Cycle consistency loss tends to minimize the difference between an arbitrary point and the returned point after traveling other representation domains. This cycle-consistency objective can allow the inverse maps between all representation spaces. When we apply the forward cycle-consistency loss $\|z - C(D(G(z)))\|_1$ and backward cycle consistency loss $\|x - G(C(D(x)))\|_1$, the maps between all two spaces become unique. Therefore, we will induce the feature-invariant one-to-one maps G, C, D. All elements of an arbitrary tuple (Z, X, H) share same class features as shown In figure 1-(a). Therefore we now naturally build the following assumption.

Assumption 3.1. *All elements of the cycle consistent tuple (Z, X, H) shares the identical factors, such as class factor and other factors (e.g. rotation and brightness).*

As shown in fig 3-(c, d), we can conjecture that each class subset is closed and the linear combinations in the certain class subset are also in the class because each class manifold is unfolded and expanded in Z and H. In addition, we showed there exists the effective basis for each class. By

Figure 3: (a), (b) the generate images using the footprint mask for MNIST and CIFAR10, (c) describes the linear combination using class 2 to generate 1 but failed. (d) is the generated image by the linear combination of the right features h for 1

the hypotheses (Bengio et al., 2013), we know that each class manifold has the compactness and the convexity. Now we can assume the following assumption.

Assumption 3.2. *Each class subspace H_i, where $H_i \subset H$ are orthogonal, so as Z_i where $Z_i \subset Z$. We define Sets for each class S_{H_i} and S_{Z_i} in H_i, Z_i respectively to be the the class manifolds which lies on the corresponding class subspaces. The sets S_{H_i} and S_{Z_i} are compact and convex.*

This assumption is more tight than the union of linear subspaces in Elhamifar & Vidal (2009). We can also conjecture that the feature space H and Z are descried as the direct sum of H_i and Z_i respectively. Now, we can show the existence of an approximate linear map C from H to Z.

Lemma 3.1. *There exists a compact and convex linear map C_i from S_{H_i} to S_{Z_i}, If $\|C_i\|$ is bounded.*

Proof.

1. By the asumption 3.2, the class subset S_{H_i} and S_{Z_i} are convex. Let $h_1, h_2 \in S_{H_i}$ and $z_1 = C_i h_1, z_2 = C_i h_2$. We know that C_i is linear, then

$$tz_1 + (1-t)z_2 = tC_i h_1 + (1-t)C_i h_2 = C_i(th_1 + (1-t)h_2). \tag{2}$$

   $th_1 + (1-t)h_2$ is also in S_{H_i} for $t \in [0,1]$. Also, $tz_1 + (1-t)z_2$ is in S_{Z_i} because S_{Z_i} have convexity. Therefore C_i is a convex linear map.

2. If S_{H_i} is compact, then for $h \in S_{H_i}$, $\|h\|$ is closed. Then $z \in S_{Z_i}$ is closed, because

$$\|z\| = \|C_i h\| \le \|C_i\|\|h\|. \tag{3}$$

   We know that C_i and h have finite values. Therefore S_{Z_i} is also compact.

Theorem 3.1. *By the assumption that the data space are the direct sum of orthogonal class subspaces, the map from H to Z can be written as a block matrix, which block component is C_i. C can maps between all class subset approximately.*

Proof. C_i is a linear map from H_i to Z_i. H_i and Z_i are orthogonal. It is trivial.

3.3 MUTUAL EXPRESSIVENESS PROPERTY AND DIMENSION REDUCTION

As we discussed in Section 2, the self-expressiveness property shows that we can express an arbitrary data point as a linear combination of other N data points. Modifying this property slightly, we can write each data point x as a linear combination of N sampled data points $\alpha = \{\mathbf{x}_1, \mathbf{x}_2, \cdots, \mathbf{x}_N\}$ from the data space X. This fact allows us to generate a set of feature variables, which satisfies the self-expressiveness property. The self-expressiveness property implies that the generated data points are in the class manifolds. Now, we weaken the self-expressiveness property to generalize the situation of the problem. We divide the latent space H into $H_1, \cdots, H_l$ where the self-expressiveness only satisfies in each H_i not in $H - H_i$. We also know that it is possible to discard redundant coefficients in the self-expressiveness expression by optimizing the matrix of coefficients (Elhamifar &

Vidal, 2009), so there exists at least one sparse solution of x where most coefficients are zero. By observing this property, we can expect that the number of non zero coefficients goes to the dimension of latent space, m. That is because N is much higher than $\dim X$ and X is a m-dimensional manifold. Image clustering methods, for instance, treat the dataset in which the number of data points is much larger than the dimension of data points so we can optimize a solution to have sufficiently enough zero coefficients in the self-expressive linear combination.

Theorem 3.2. *From now on, $Z_i' = C_i' H_i'$ where $Z_i' = (z_1, \cdots, z_{m_i})^T$ and $H_i' = (h_1, \cdots, h_{m_i})^T$.*

Proof. By the observation on GANs, we have N_i feature variables $\beta_i = \{h_{ij}\}_{1 \leq j \leq N_i}$ for each $1 \leq i \leq l$ where $D(x_i) = h_i$ and $N = N_1 + \cdots + N_l$. By the self-expressiveness property in H_i, we can express each $h_i \in H_i$ by the linear combination of $\beta_i' = \{h_1, h_2 \cdots, h_{m_i}, h_{m_i+1}, \cdots h_{N_i}\}$ where β_i' is a reordered set of β_i and the coeffcents of the linear combination $\{c_{m_i+1}, c_{m_i+2}, \cdots, c_{Ni}\}$ are zero. In other words, the ordered set $\gamma_i = \{h_1, \cdots, h_{m_i}\}$ is enough to represent all points in the class manifold X_i and Z_i, which correspond to (Z_i, X_i, H_i), i.e. $span(\gamma_i) = H_i$. Hence, we can choose C_i' by an $m_i \times m_i$ real matrix. $\square$

This theorem is empirically shown by the our effective basis conjecture. By reducing dimensionality, calculating the eigenvalue of Lapalacian matrix of which similarity matrix is $|C| + |C^T|$ is tractable.

Theorem 3.3. *Suppose that G is an undirected graph with non-negative weights. Then, the number of connected components $A_1, \cdots, A_k$ in G is same as the multiplicity k of the eigenvalue 0 of L. The eigenspace corresponding to the eigenvalue 0 is spanned by the indicator vectors $1_{A_1}, \cdots, 1_{A_k}$ of those components.*

Proof. the proof in (Von Luxburg, 2007). $\square$

Therefore, we can conclude that the estimated numbers of classes are identical between the original spectral clustering and our method.

3.4 UNSUPERVISED CLASSIFICATION

Now, we consider the unsupervised classification problem that is not given even a single ground-truth label for the given dataset. For example, when the cross-entropy loss is applied in the supervised classification, we need pairs of input data and ground-truth probability mass $p = [0, , 1, \cdots, 0]$, which contains single 1 at the i-th element, i.e. the class index $c = i$, to estimate the difference between the prediction and the ground-truth. We can formally write the probabilistic interpretation as

$$P(c = i|\mathbf{x}) = \frac{P(c = i)P(\mathbf{x}|c = i)}{P(\mathbf{x})} \tag{4}$$

, where $\mathbf{x}$ is a data point. If we assume that the numbers of data points in the whole classes are same, then $P(c)$ is uniform. Then, for the given point $\mathbf{x}$, $P(\mathbf{x})$ is fixed so the we can measure $P(c|\mathbf{x})$ by the estimating the likelihood $P(\mathbf{x}|c)$. In Section 3.3, we showed that the indicator vectors of the connected components are the eigenvectors of the Laplacian matrix L, which are corresponding to the eigenvalue 0. The components of the indicator vectors span the eigenspaces of the matched connected components respectively. The orders of components for the Laplacian matrix L_C and the connector network C are identical by the definition in Section 3.3. Therefore, for all connected component A_i, the indicator vectors $\mathbf{1}_{A_i} = h \in H_i$ spans the class subspace H_i. The indicator vector itself, however, might not be in the class manifold because it can exist outside the boundary of the manifold. We find out that the changes of norms between H and Z are different by the class. The connector network can be considered as a singular value decomposition for each class. This implies that each class data points move differently by the class. We define the mean vector of a class in H as h' and the Gaussian noise n.

$$\|z\|^2 = \|Ch\|^2 = h^T C^T C h \tag{5}$$

$$= (h' + n)^T C^T C(h' + n) \tag{6}$$

The expectation of $\|z\|^2$ is,

$$E[\|z\|^2] = h'^T C^T C h' + E[n^T C^T C n] \tag{7}$$

$$= h'^T C^T C h' + E[n_Z^T n_Z] \tag{8}$$

, where n_Z is the variation in Z. We now assume that the distribution of $\|z\|^2$ is Gaussian. Then, we can calculate the probability that $\|z\|^2$ is in the certain class.

We also know that $B = C^T C$ is a normal operator, then B satisfies the following theorem.

Theorem 3.4. $|x^T B x| \leq \max\{|\lambda| : \lambda \text{ is an eigenvalue of } B\}\|x\|_2^2$

Proof. By ordering the eigenvalue of B, we can find out the interval that $\|z\|^2$ lies in. This eigenvalue works as the indicator of classifying class.

4 UNSUPERVISED CLASSIFICATION INTO UNKNOWN k CLASSES

In this section, we describe the loss function and the training algorithm of unsupervised classification into unknown k classes. Is is known that estimating the number of classes k is hard and heuristic (Von Luxburg, 2007). We find the empirical observation on the hint of k. Using the observation, we suggest a conjecture that helps to estimate the number of classes k in the certain case.

Algorithm 1 Unsupervised Classification into Unknown k Classes (UCUC)

1: **for** the number of iterations **do**
2:     Sample minibatch of m latent vectors $\mathbf{z}^{(0)}, \cdots, \mathbf{z}^{(m)}$ from prior $p_g(z)$
3:     Sample minibatch of m data points $\mathbf{x}^{(0)}, \cdots, \mathbf{x}^{(m)}$ from dataset
4:     Update the discriminator by ascending :

$$\nabla_{\theta_d} \frac{1}{m} \sum_{i=1}^{m} \left[\log D\left(\mathbf{x}^{(i)}\right) + \log\left(1 - D\left(G\left(\mathbf{z}^{(i)}\right)\right)\right) \right] + \lambda_D \left\| \mathbf{x}^{(i)} - G\left(C\left(D\left(\mathbf{x}^{(i)}\right)\right)\right) \right\|_1 \tag{9}$$

5:     Update the generator and connect by descending their stochastic gradients:

$$\nabla_{\theta_g} \frac{1}{m} \sum_{i=1}^{m} \left[\log\left(1 - D\left(G\left(\mathbf{z}^{(i)}\right)\right)\right) \right] + \lambda_G \left\| \mathbf{z}^{(i)} - C\left(D\left(G\left(\mathbf{z}^{(i)}\right)\right)\right) \right\|_1 \tag{10}$$

6:     Update the connector network C with two cycle-consistency loss

$$\nabla_C \left[\left\| \mathbf{z}^{(i)} - C\left(D\left(G\left(\mathbf{z}^{(i)}\right)\right)\right) \right\|_1 + \left\| \mathbf{x}^{(i)} - G\left(C\left(D\left(\mathbf{x}^{(i)}\right)\right)\right) \right\|_1 \right] \tag{11}$$

7:     Compute the moving average of each i-th eigenvalue of normalized symmetric Laplacian matrix $L_{sym} = D^{\frac{-1}{2}} L D^{\frac{-1}{2}}$ and find the estimated number $\hat{k}$ by find the second deep local minimum
8: **end for**

4.1 ESTIMATING THE NUMBER OF CLASSES k

We found an interesting observation about the number of classes k. The eigenvalue λ of the graph Laplacian matrix equals to Ncut of the given graph (Shi & Malik, 2000). In the ideal cases, we can assume that L is a block-diagonal matrix and each of blocks L_i is a proper sub-graph Laplacian. If there is no connection between subgraphs, then L is a perfect block-digonal matrix and the multiplicity of the eigenvalue 0 is same as the number of blocks. In the real world dataset, there exists quite large off-diagonal noise in the similarity matrix, as shown in the previous result. These non-zero off-diagonal elements make the eigenvalue zero only at the first eigenvalue and increase the Ncut of the graph gradually. We can consider the $i - th$ eigenvalue as the Ncut by the block diagonal matrix with i blocks, which is applied on the perturbed block diagonal matrix of which the underlying connected component is k. Now, we conjecture the pattern of the eigenvalue. We assume that the off-diagonal elements have the same value and the dimension of the all eigenspaces are same. Now, we estimate the number of classes k by starting from $m \ll k$. We can consider the difference of Ncut between k-block diagnoal matrix and m-block diagnoal matrix as the the area of $S_m - S_m \cap S_k$, where $S_m = \frac{n^2}{m}$ and $S_k = \frac{n^2}{k}$ when the matrix size is n. As m increases, the

difference of Ncut increases, but at $k = m$ the value have the very small local minimum becuase two matrices are perfectly overlapped. Using this property we can derive the function of the difference of the Ncut over m, as follows.

$$S_m \cap S_k = n^2(\frac{1}{k^2}(k - m + 1) + \sum_{i=1}^{m-1}[(\frac{i}{m} - \lfloor\frac{ik}{m}\rfloor\frac{1}{k})^2 + ((1 + \lfloor\frac{ik}{m}\rfloor)\frac{1}{k} - \frac{i}{m})^2] \quad (12)$$

where $m \leq k$. if $m > k$, swith m and k vice versa. This overlapped area is $\frac{n^2}{k}$ at $m = k$ trivially. The figure of the theoretical conjecture is in 4a. This result can predict the emprical result of the pattern of the eigenvalue. Therefore, we can conjecture that the underlying number of classes is at the second deep local minima.

5 EVALUATION

We introduce the setting of experiments and the architecture of our adversarial networks (Radford et al., 2015). For the smaller size of dataset, such as MNIST and CIFAR10 we reduce the size of kernels properly. We have the result the expectation of the estimated number of k is 10.2 for MNIST and 10.1 for CIFAR10. Now we use the unsupervised clustering accuracy (ACC) (Cai et al., 2011; Shaham et al., 2018).

$$ACC(l, c) = \frac{1}{n} \max_{\pi \in \Pi} \sum_{i=1}^{n} 1\{l_i = \pi(c_i)\}, \quad (13)$$

where l_i is true label, c_i is the ground-truth label, and π is the collection of permutations.

Algorithm	ACC (MNIST)
spectral clustering	.717
SpectralNet	.971
IMSAT	.984
UCUC(ours)	.735

Table 1: Other methods have the ground-truth number of classes. However, our method estimating the number of classes first. Other results are reported in (Shaham et al., 2018)

| (a) | (b) | (c) |

Figure 4: a shows theoretical result of the estimated eigengap using the overlapped area of block-diagonal matrices and Figure (b) and (c) shows the eigengap $|\lambda_k - \lambda_{k-1}|$ of the MNIST and CIFAR10.

6 CONCLUSION

We have proposed an unsupervised classification method that can automatically estimates the unknown number of classes k. Our method provides the learned class-feature and this implies that the label of the given data point is automatically generated.

ACKNOWLEDGMENTS

REFERENCES

Yoshua Bengio. How auto-encoders could provide credit assignment in deep networks via target propagation. *arXiv preprint arXiv:1407.7906*, 2014.

Yoshua Bengio, Yann LeCun, et al. Scaling learning algorithms towards ai. *Large-scale kernel machines*, 34(5):1–41, 2007.

Yoshua Bengio, Grégoire Mesnil, Yann Dauphin, and Salah Rifai. Better mixing via deep representations. In *International Conference on Machine Learning*, pp. 552–560, 2013.

David Berthelot, Thomas Schumm, and Luke Metz. Began: boundary equilibrium generative adversarial networks. *arXiv preprint arXiv:1703.10717*, 2017.

Deng Cai, Xiaofei He, and Jiawei Han. Locally consistent concept factorization for document clustering. *IEEE Transactions on Knowledge and Data Engineering*, 23(6):902–913, 2011.

Lawrence Cayton. Algorithms for manifold learning. *Univ. of California at San Diego Tech. Rep*, 12(1-17):1, 2005.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. In *Advances in Neural Information Processing Systems*, pp. 2172–2180, 2016.

Ehsan Elhamifar and René Vidal. Sparse subspace clustering. In *Computer Vision and Pattern Recognition, 2009. CVPR 2009. IEEE Conference on*, pp. 2790–2797. IEEE, 2009.

Robert Geirhos, David HJ Janssen, Heiko H Schütt, Jonas Rauber, Matthias Bethge, and Felix A Wichmann. Comparing deep neural networks against humans: object recognition when the signal gets weaker. *arXiv preprint arXiv:1706.06969*, 2017.

Xavier Glorot, Antoine Bordes, and Yoshua Bengio. Domain adaptation for large-scale sentiment classification: A deep learning approach. In *Proceedings of the 28th international conference on machine learning (ICML-11)*, pp. 513–520, 2011.

Ian Goodfellow, Honglak Lee, Quoc V Le, Andrew Saxe, and Andrew Y Ng. Measuring invariances in deep networks. In *Advances in neural information processing systems*, pp. 646–654, 2009.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pp. 2672–2680, 2014.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Pan Ji, Tong Zhang, Hongdong Li, Mathieu Salzmann, and Ian Reid. Deep subspace clustering networks. In *Advances in Neural Information Processing Systems*, pp. 23–32, 2017.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Abhishek Kumar, Prasanna Sattigeri, and Tom Fletcher. Semi-supervised learning with gans: Manifold invariance with improved inference. In *Advances in Neural Information Processing Systems*, pp. 5540–5550, 2017.

Marc T Law, Raquel Urtasun, and Richard S Zemel. Deep spectral clustering learning. In *International Conference on Machine Learning*, pp. 1985–1994, 2017.

Mehdi Mirza and Simon Osindero. Conditional generative adversarial nets. *arXiv preprint arXiv:1411.1784*, 2014.

Andrew Y Ng, Michael I Jordan, and Yair Weiss. On spectral clustering: Analysis and an algorithm. In *Advances in neural information processing systems*, pp. 849–856, 2002.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. *arXiv preprint arXiv:1511.06434*, 2015.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision (IJCV)*, 115(3):211–252, 2015. doi: 10.1007/s11263-015-0816-y.

Uri Shaham, Kelly Stanton, Henry Li, Boaz Nadler, Ronen Basri, and Yuval Kluger. Spectralnet: Spectral clustering using deep neural networks. *arXiv preprint arXiv:1801.01587*, 2018.

Jianbo Shi and Jitendra Malik. Normalized cuts and image segmentation. *IEEE Transactions on pattern analysis and machine intelligence*, 22(8):888–905, 2000.

Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, Andrew Rabinovich, et al. Going deeper with convolutions. Cvpr, 2015.

Ulrike Von Luxburg. A tutorial on spectral clustering. *Statistics and computing*, 17(4):395–416, 2007.

Junbo Zhao, Michael Mathieu, and Yann LeCun. Energy-based generative adversarial network. *arXiv preprint arXiv:1609.03126*, 2016.

Jun-Yan Zhu, Taesung Park, Phillip Isola, and Alexei A Efros. Unpaired image-to-image translation using cycle-consistent adversarial networks. In *Computer Vision (ICCV), 2017 IEEE International Conference on*, pp. 2242–2251. IEEE, 2017.