Robust training of recurrent neural networks to handle missing data for disease progression modeling

Mostafa Mehdipour Ghazi[1,2,3], **Mads Nielsen**[1,2], **Akshay Pai**[1,2], **M. Jorge Cardoso**[3],
Marc Modat[3], **Sebastien Ourselin**[3], **Lauge Sørensen**[1,2]

[1]Biomediq A/S, Copenhagen, DK
[2]Department of Computer Science, Univeristy of Copenhagen, DK
[3]Centre for Medical Image Computing, University College Londen, UK
mehdipour@biomediq.com

Abstract

Disease progression modeling (DPM) using longitudinal data is a challenging task in machine learning for healthcare that can provide clinicians with better tools for diagnosis and monitoring of disease. Existing DPM algorithms neglect temporal dependencies among measurements and make parametric assumptions about biomarker trajectories. In addition, they do not model multiple biomarkers jointly and need to align subjects' trajectories. In this paper, recurrent neural networks (RNNs) are utilized to address these issues. However, in many cases, longitudinal cohorts contain incomplete data, which hinders the application of standard RNNs and requires a pre-processing step such as imputation of the missing values. We, therefore, propose a generalized training rule for the most widely used RNN architecture, long short-term memory (LSTM) networks, that can handle missing values in both target and predictor variables. This algorithm is applied for modeling the progression of Alzheimer's disease (AD) using magnetic resonance imaging (MRI) biomarkers. The results show that the proposed LSTM algorithm achieves a lower mean absolute error for prediction of measurements across all considered MRI biomarkers compared to a prevalent parametric, regression-based DPM method and using standard LSTM networks with data imputation. Moreover, linear discriminant analysis based classification of the predicted biomarkers' values using the proposed algorithm results in a larger area under the receiver operating characteristic curve (AUC) for clinical diagnosis of AD compared to the same alternatives, and the AUC is comparable to state-of-the-art AUC's from a recent cross-sectional medical image classification challenge. Built-in handling of missing values in LSTM network training paves the way for application of RNNs in disease progression modeling.

1 Introduction

Alzheimer's disease (AD) is a chronic neurodegenerative disorder that begins with short-term memory loss and develops over time causing issues in conversation, orientation, and control of bodily functions [1]. Early diagnosis of the disease is challenging and is usually made once cognitive impairment has already compromised daily living. Hence, developing robust data-driven methods for disease progression modeling (DPM) utilizing longitudinal data is necessary to yield a complete perspective of the disease for better diagnosis, monitoring, and prognosis [2].

Existing DPM techniques attempt to describe biomarker measurements as a function of disease progression through continuous curve fitting. In the AD progression literature, a variety of regression-based methods have been applied to fit logistic or polynomial functions to the longitudinal dynamic

1st Conference on Medical Imaging with Deep Learning (MIDL 2018), Amsterdam, The Netherlands.

of each biomarker [3–8]. However, parametric assumptions on the biomarker trajectories limits the applicability of such methods; in addition, none of the existing approaches consider the temporal dependencies among measurements. They mostly rely on independent biomarker modeling and require alignment of subjects' trajectories – either as a pre-processing step or as part of the algorithm.

Recurrent neural networks (RNNs) are sequence learning based methods that can offer continuous, non-parametric, joint modeling of longitudinal data while taking temporal dependencies amongst measurements into account [9]. However, since longitudinal cohort data often contain missing values due to, for instance, dropped out patients, unsuccessful measurements, and/or varied trial design, standard RNNs require pre-processing steps for data imputation which mostly results in suboptimal analyses and predictions [10]. Therefore, the lack of methods to handle incomplete data using RNNs is evident [11].

Long short-term memory (LSTM) networks are widely used types of RNNs developed to effectively capture long-term temporal dependencies by dealing with the exploding and vanishing gradient problem during backpropagation through time [12–14]. They employ a memory cell with nonlinear reset units – so called constant error carousels (CECs), and learn to store history for either long or short time periods. Since their introduction, a variety of LSTM networks have been developed for different time-series applications [15]. The vanilla LSTM, among others, is the most commonly used architecture that utilizes three reset gates and applies full gate recurrence by passing current and recurrent inputs while backpropagating full gradients. Nevertheless, its complete topology can include biases and peephole or cell-to-gates connections.

In this paper, we generalize a method for training LSTM networks that can handle missing values in both target and predictor variables. This is achieved via applying the batch gradient descent algorithm together with normalizing the loss function and its gradients with respect to the number of missing points in target and input using the batch-sequence, to ensure a proportional contribution of each weight per epoch. Unlike previous methods that attempt to benefit from the inherent bias of missing values' patterns to improve prediction [10, 11], our goal is to make the training algorithm robust to missing values. The proposed LSTM algorithm is applied for modeling the progression of AD in the Alzheimer's Disease Neuroimaging Initiative (ADNI) cohort [16] based on imaging biomarkers, and the estimated biomarker trajectories are used to predict the clinical status of subjects per visits.

Our main contribution is three-fold. Firstly, we generalize formulation of backpropagation through time for LSTM networks to handle incomplete data and show that such built-in handling of missing values provides better modeling and prediction performances compared to using data imputation with standard LSTM networks. Secondly, we model temporal dependencies within the ADNI data using the proposed LSTM network via sequence-to-sequence learning. To the best of our knowledge, this is the first time such multi-dimensional sequence learning methods are applied for neurodegenerative DPM. Lastly, we introduce an end-to-end approach for modeling the longitudinal dynamics of imaging biomarkers – without need for trajectory alignment – and for clinical status prediction. This is a practical way to implement a robust DPM for both research and clinical applications.

2   Proposed LSTM algorithm

The main goal of this study is to minimize the influence of missing values on the learned LSTM network parameters. This is achieved by using the batch gradient descend scheme together with the backpropagation through time algorithm modified to contribute the effects of missing data in the input and target vectors. More specifically, the algorithm accumulates the subject-specific input weight gradients proportionally weighted according to the number of available time points per input node using the subject-biomarker specific normalization factor of β_n^j. In addition, it uses an L2-norm loss function with residuals weighted according to the number of available time points per output node using the subject-biomarker specific normalization factor of β_m^j, and normalized with respect to the total number of available input values for all visits-biomarkers – propagated through the forward pass – using the subject-specific normalization factor of β_x^j. Such modification of the loss function also ensures that all gradients of the network weights are indirectly normalized. Finally, the use of batch gradient descend can guarantee sufficiency of subjects-visits in the batch to be connected at least once to each input node to proportionally contribute in the weight updates.

Figure 1: An illustration of vanilla LSTM unit with peephole connections in red. The solid and dashed lines show weighted and unweighted connections, respectively.

2.1 The basic LSTM architecture

Figure 1 shows a typical schematic of a vanilla LSTM architecture. As can be seen, the topology includes a memory cell, an input modulation, a hidden activation, and three nonlinear reset gates, namely input gate, forget gate, and output gate, each of which accepting current and recurrent inputs. The memory cell learns to maintain its state over time while the multiplicative gates learn to open and close access to the constant error/information flow, to prevent exploding or vanishing gradients. In fact, the input gate protects the memory contents from perturbation by irrelevant inputs. This is while the output gate protects other units from perturbation by currently irrelevant memory contents. The forget gate, on the other hand, deals with continual or very long input sequences. Finally, peephole connections allow the gates to access the CEC of the same cell state.

2.2 Feedforward in LSTM networks

Assume $\boldsymbol{x}_j^t \in \mathbb{R}^{N \times 1}$ is the j-th observation of an N-dimensional input vector at current time t. If M is the number of output units, feedforward calculations of the LSTM network under study can be summarized as

$$\boldsymbol{f}_j^t = W_f \boldsymbol{x}_j^t + U_f \boldsymbol{h}_j^{t-1} + \boldsymbol{V}_f \odot \boldsymbol{c}_j^{t-1} + \boldsymbol{b}_f \longrightarrow \tilde{\boldsymbol{f}}_j^t = \sigma_g(\boldsymbol{f}_j^t)$$
$$\boldsymbol{i}_j^t = W_i \boldsymbol{x}_j^t + U_i \boldsymbol{h}_j^{t-1} + \boldsymbol{V}_i \odot \boldsymbol{c}_j^{t-1} + \boldsymbol{b}_i \longrightarrow \tilde{\boldsymbol{i}}_j^t = \sigma_g(\boldsymbol{i}_j^t)$$
$$\boldsymbol{z}_j^t = W_c \boldsymbol{x}_j^t + U_c \boldsymbol{h}_j^{t-1} + \boldsymbol{b}_c \longrightarrow \tilde{\boldsymbol{z}}_j^t = \sigma_c(\boldsymbol{z}_j^t)$$
$$\boldsymbol{c}_j^t = \tilde{\boldsymbol{f}}_j^t \odot \boldsymbol{c}_j^{t-1} + \tilde{\boldsymbol{i}}_j^t \odot \tilde{\boldsymbol{z}}_j^t \longrightarrow \tilde{\boldsymbol{c}}_j^t = \sigma_h(\boldsymbol{c}_j^t)$$
$$\boldsymbol{o}_j^t = W_o \boldsymbol{x}_j^t + U_o \boldsymbol{h}_j^{t-1} + \boldsymbol{V}_o \odot \boldsymbol{c}_j^t + \boldsymbol{b}_o \longrightarrow \tilde{\boldsymbol{o}}_j^t = \sigma_g(\boldsymbol{o}_j^t)$$
$$\boldsymbol{h}_j^t = \tilde{\boldsymbol{o}}_j^t \odot \tilde{\boldsymbol{c}}_j^t$$

where $\{\boldsymbol{f}_j^t, \boldsymbol{i}_j^t, \boldsymbol{z}_j^t, \boldsymbol{c}_j^t, \boldsymbol{o}_j^t, \boldsymbol{h}_j^t\} \in \mathbb{R}^{M \times 1}$ and $\{\tilde{\boldsymbol{f}}_j^t, \tilde{\boldsymbol{i}}_j^t, \tilde{\boldsymbol{z}}_j^t, \tilde{\boldsymbol{c}}_j^t, \tilde{\boldsymbol{o}}_j^t, \tilde{\boldsymbol{h}}_j^t\} \in \mathbb{R}^{M \times 1}$ are j-th observation of forget gate, input gate, modulation gate, candidate or cell state, output gate, and hidden output at time t before and after activation, respectively. Moreover, $\{W_f, W_i, W_o, W_c\} \in \mathbb{R}^{M \times N}$ and $\{U_f, U_i, U_o, U_c\} \in \mathbb{R}^{M \times M}$ are sets of connecting weights from input and recurrent, respectively, to

the gates and cell; $\{V_f, V_i, V_o\} \in \mathbb{R}^{M \times 1}$ is the set of peephole connections from the cell to the gates, $\{b_f, b_i, b_o, b_c\} \in \mathbb{R}^{M \times 1}$ represents corresponding biases of neurons, and the product $\odot$ denotes the element-wise multiplication. Finally, σ_g, σ_c, and σ_h imply nonlinear activation functions assigned for the gates, input modulation, and hidden output, respectively. Logistic sigmoid is always applied for the gates with range $[0, 1]$ while hyperbolic tangent is typically assigned for modulation of both cell input and hidden output with range $[-1, 1]$.

2.3 Robust backpropagation through time

Let $\mathcal{L} \in \mathbb{R}^{M \times 1}$ be the loss function defined based on the actual target s and network output y. Here, we simply assume that the network output is the same hidden output. The idea is to calculate the partial derivatives of the loss function (δ) with respect to the weights using the chain rule. Hence, the backpropagation calculations through time using full gradients can be obtained as

$$\mathcal{L}(m) = \frac{1}{2} \sum_{j,t} \frac{1}{\beta_x^j \beta_m^j} (\boldsymbol{y}_j^t(m) - \boldsymbol{s}_j^t(m))^2 \longrightarrow \delta \boldsymbol{y}_j^t(m) = \frac{\partial \mathcal{L}_j^t(m)}{\partial \boldsymbol{y}_j^t(m)} = \frac{1}{\beta_x^j \beta_m^j} (\boldsymbol{y}_j^t(m) - \boldsymbol{s}_j^t(m))$$

$$\delta \boldsymbol{h}_j^t = \delta \boldsymbol{y}_j^t + U_f^T \delta \boldsymbol{f}_j^{t+1} + U_i^T \delta \boldsymbol{i}_j^{t+1} + U_c^T \delta \boldsymbol{z}_j^{t+1} + U_o^T \delta \boldsymbol{o}_j^{t+1}$$

$$\delta \tilde{\boldsymbol{o}}_j^t = \delta \boldsymbol{h}_j^t \odot \tilde{\boldsymbol{c}}_j^t \longrightarrow \delta \boldsymbol{o}_j^t = \delta \tilde{\boldsymbol{o}}_j^t \odot \sigma_g'(\boldsymbol{o}_j^t)$$

$$\delta \tilde{\boldsymbol{c}}_j^t = \delta \boldsymbol{h}_j^t \odot \tilde{\boldsymbol{o}}_j^t \longrightarrow \delta \boldsymbol{c}_j^t = \delta \tilde{\boldsymbol{c}}_j^t \odot \sigma_h'(\boldsymbol{c}_j^t) + \delta \boldsymbol{c}_j^{t+1} \odot \tilde{\boldsymbol{f}}_j^{t+1} + \boldsymbol{V}_f \odot \delta \boldsymbol{f}_j^{t+1} + \boldsymbol{V}_i \odot \delta \boldsymbol{i}_j^{t+1} + \boldsymbol{V}_o \odot \delta \boldsymbol{o}_j^t$$

$$\delta \tilde{\boldsymbol{z}}_j^t = \delta \boldsymbol{c}_j^t \odot \tilde{\boldsymbol{i}}_j^t \longrightarrow \delta \boldsymbol{z}_j^t = \delta \tilde{\boldsymbol{z}}_j^t \odot \sigma_c'(\boldsymbol{z}_j^t)$$

$$\delta \tilde{\boldsymbol{i}}_j^t = \delta \boldsymbol{c}_j^t \odot \tilde{\boldsymbol{z}}_j^t \longrightarrow \delta \boldsymbol{i}_j^t = \delta \tilde{\boldsymbol{i}}_j^t \odot \sigma_g'(\boldsymbol{i}_j^t)$$

$$\delta \tilde{\boldsymbol{f}}_j^t = \delta \boldsymbol{c}_j^t \odot \boldsymbol{c}_j^{t-1} \longrightarrow \delta \boldsymbol{f}_j^t = \delta \tilde{\boldsymbol{f}}_j^t \odot \sigma_g'(\boldsymbol{f}_j^t)$$

$$\delta \boldsymbol{x}_j^t = W_f^T \delta \boldsymbol{f}_j^t + W_i^T \delta \boldsymbol{i}_j^t + W_c^T \delta \boldsymbol{z}_j^t + W_o^T \delta \boldsymbol{o}_j^t$$

where $\beta_x^j = J \frac{|\boldsymbol{x}_j|}{TN}$ and $\beta_m^j = |\boldsymbol{y}_j(m)|$ are normalization factors to handle missing values of the j-th observation with batch size J and sequence length T. Also, $|\boldsymbol{x}_j|$ and $|\boldsymbol{y}_j(m)|$ denote the total number of available input values and the number of available target time points in the m-th node, respectively. Finally, if $\theta \in \{f, i, z, o\}$ and $\phi \in \{f, i\}$, the gradients of the loss function with respect to the weights are calculated as

$$\delta W_\theta(n) = \sum_{j=1}^{J} \frac{1}{\beta_n^j} \delta \boldsymbol{\theta}_j^{\{0 \to T\}} \boldsymbol{x}_j^{\{0 \to T\}}(n)$$

$$\delta U_\theta = \sum_{j=1}^{J} \delta \boldsymbol{\theta}_j^{\{1 \to T\}} \boldsymbol{h}_j^{\{0 \to T-1\}}$$

$$\delta \boldsymbol{V}_\phi = \sum_{j=1}^{J} \sum_{t=0}^{T-1} \delta \boldsymbol{\phi}_j^{t+1} \odot \boldsymbol{c}_j^t$$

$$\delta \boldsymbol{V}_o = \sum_{j=1}^{J} \sum_{t=0}^{T} \delta \boldsymbol{o}_j^t \odot \boldsymbol{c}_j^t$$

$$\delta \boldsymbol{b}_\theta = \sum_{j=1}^{J} \sum_{t=0}^{T} \delta \boldsymbol{\theta}_j^t$$

where $\beta_n^j = \frac{|\boldsymbol{x}_j(n)|}{T}$ is the normalization factor handling input missing values and $|\boldsymbol{x}_j(n)|$ is the number of available input time points in the n-th node.

Table 1: Demographics statistics of the TADPOLE dataset

| | Number of visits | | Age, year (mean±SD) | | Education, year |
	male	female	male	female	(mean±SD)
CN	1,356	1,389	76.67±6.44	75.85±6.28	16.38±2.70
MCI	2,454	1,604	75.59±7.47	73.87±8.09	15.91±2.84
AD	1,208	900	77.22±7.11	75.45±7.92	15.18±2.99
All (labeled & unlabeled)	12,741		76.00±7.38		15.91±2.86

2.4 Momentum batch gradient descent

As an efficient iterative algorithm, momentum batch gradient descent method is applied to find the local minimum of the loss function calculated over a batch while speeding up the convergence. The update rule can be written as

$$\vartheta^{new} = \mu\vartheta^{old} - \alpha(\delta\omega + \gamma\omega^{old})$$
$$\omega^{new} = \omega^{old} + \vartheta^{new}$$

where ϑ is the weight update initialized at zero, ω is a typical to-be-updated weight array, $\delta\omega$ is the gradient of loss function with respect to the weight ω, and α, γ, and μ are the learning rate, weight decay or regularization factor, and momentum weight, respectively.

3 Experiments

3.1 Data preparation

We utilize the dataset of The Alzheimer's Disease Prediction Of Longitudinal Evolution [1] (TADPOLE) challenge for time-series analysis using the LSTM network. The dataset is composed of data from three ADNI phases of ADNI 1, ADNI GO, and ADNI 2. This includes biomarkers acquired from 1,737 subjects (957 males and 780 females) during 12,741 visits at 22 distinct time points between 2003 and 2017. The data is captured by measures of brain structural integrity using magnetic resonance imaging (MRI), positron emission tomography (PET), and diffusion tensor imaging (DTI), or obtained from blood tests of cerebrospinal fluid (CSF), neuropsychological (cognitive) tests, as well as demographics and genetics information. Table 1 summarizes statistics of the demographics in the TADPOLE dataset. Note that the subjects include missing measurements during their visits and not all of them are clinically labeled.

In this work, we have merged existing groups labeled as cognitively normal (CN), significant memory concern (SMC), and normal (NL) under cognitively normal, mild cognitive impairment (MCI), early MCI (EMCI), and late MCI (LMCI) under mild cognitive impairment, and Alzheimer's disease (AD) and Dementia under Alzheimer's disease. Moreover, groups with labels converting from one status to another, e.g. "MCI-to-AD", are assumed to belong the next status ("AD" in this example).

MRI biomarkers are used for AD progression modeling. This includes T1–weighted brain MRI volumes of ventricles, hippocampus, whole brain, fusiform, middle temporal gyrus, and entorhinal cortex. We normalize the MRI measurements with respect to the corresponding intracranial volume (ICV). Out of 22 visits, we select 11 visits – including baselines – with a fix interval of one year to span the majority of measurements and subjects. Next, we filter the data outliers based on the potential range of each biomarker and normalize the measurements to be in the range $[-1, 1]$. Finally, subjects with less than three distinct visits per biomarker are removed to better adapt with the LSTM network for sequence learning.

For the evaluation purpose, we partition the entire dataset to three non-overlapping subsets of training, validation, and test. To achieve this, we randomly select 10% of the within-class subjects for validation and the same for testing. To be more specific, based on the baseline labels of subjects, we randomly

---

[1]https://tadpole.grand-challenge.org

pick within-class samples ensuring to have enough subjects with few and large number of visits in each subset.

3.2 Evaluation metrics

Mean absolute error (MAE) and multi-class area under the receiver operating characteristic (ROC) curve (AUC) are used to assess the modeling and classification performances, respectively. MAE measures accuracy of continuous prediction per biomarker by computing the difference between actual and estimated variables as follows

$$\text{MAE} = \frac{1}{\mathcal{I}} \sum_{j,t} |\boldsymbol{y}_j^t - \boldsymbol{s}_j^t|$$

where $\boldsymbol{s}_j^t$ and $\boldsymbol{y}_j^t$ are the ground-truth and estimated values of the specific biomarker for the j-th subject at the t-th visiting point, respectively, and $\mathcal{I}$ is the number of existing points in the target array $\boldsymbol{s}$.

Multi-class AUC [17], on the other hand, is a measure to examine the diagnostic performance of a multi-class test using ROC analysis. AUC can be calculated using the posterior probabilities as follows

$$\text{AUC} = \frac{1}{(n_c(n_c-1))} \sum_{i=1}^{n_c-1} \sum_{k=i+1}^{n_c} \frac{1}{n_i n_k} \left[\text{SR}_i - \frac{n_i(n_i+1)}{2} + \text{SR}_k - \frac{n_k(n_k+1)}{2} \right]$$

where n_c stands for the number of distinct classes, n_i denotes the number of available points belonging to the i-th class, and SR_i is the sum of the ranks of posteriors $p(c_i|\boldsymbol{s}_i)$ after sorting all concatenated posteriors $\{p(c_i|\boldsymbol{s}_i), p(c_i|\boldsymbol{s}_k)\}$ in an increasing order, where $\boldsymbol{s}_i$ and $\boldsymbol{s}_k$ are vectors of scores belonging to the true classes c_i and c_k, respectively.

3.3 Experimental setup

All the proposed and utilized methods in this study are implemented by in-house development in MATLAB R2017b. We initialize the LSTM network weights by generating uniformly distributed random values in the range $[-0.05, 0.05]$ and set the weights' updates and weights' gradients to zero. We set the batch size to the number of available training subjects. Furthermore, for simplicity, we use the first ten visits to estimate the second to eleventh visits per subject and use the estimated values for evaluation. Finally, we train the network using feedforward and the proposed method of backpropagation through time where the network replace the input missing values and corresponding error of the output missing values with zero.

We utilize the validation set to tune the network parameters each time by adjusting one of the parameters while keeping the rest at fixed values to achieve the lowest average MAE. Based on this strategy, the optimal network parameters are obtained as $\alpha = 0.1$, $\mu = 0.9$, and $\gamma = 0.0001$ with 1,000 epochs. The corresponding MAE's for the validation set are also calculated as 2.9590×10^{-3}, 2.4603×10^{-4}, 1.4943×10^{-2}, 2.4161×10^{-4}, 7.5522×10^{-4}, 9.6592×10^{-4}, respectively for ventricles, hippocampus, whole brain, entorhinal cortex, fusiform, and middle temporal gyrus. It is worthwhile mentioning that all the estimated biomarker's measurements are transformed back to their actual ranges while calculating MAE's. Finally, we see that using LSTM networks with peephole connections improves the performance.

3.4 Results

After training our LSTM network with the best models, we examine it using the obtained test subset. Next, we train the network using mean imputation (LSTM-Mean) [11] and forward imputation (LSTM-Forward) [10]. Moreover, we use the parametric, regression-based method of [3] to model the AD progression. Table 2 compares the test modeling performance (MAE) of the MRI biomarkers using aforementioned approaches.

Table 2: Test modeling performance (MAE) of the MRI biomarkers using different DPM methods.

	Proposed	LSTM-Mean [11]	LSTM-Forward [10]	Jedynak et al. [3]
Ventricles	3.0674×10^{-3}	6.2010×10^{-3}	4.7204×10^{-3}	8.0718×10^{-3}
Hippocampus	2.3267×10^{-4}	5.0916×10^{-4}	3.3977×10^{-4}	5.1455×10^{-4}
Whole brain	1.3298×10^{-2}	2.3746×10^{-2}	1.6389×10^{-2}	5.5125×10^{-3}
Entorhinal cortex	2.1138×10^{-4}	3.0324×10^{-4}	2.5489×10^{-4}	3.4660×10^{-4}
Fusiform	6.7932×10^{-4}	1.2964×10^{-3}	1.0044×10^{-3}	9.0342×10^{-4}
Middle temporal gyrus	8.6750×10^{-4}	1.2606×10^{-3}	1.1759×10^{-3}	1.1092×10^{-3}

Table 3: Test diagnostic performance (AUC) of the MRI biomarkers using LDA with different DPM methods.

	Proposed	LSTM-Mean [11]	LSTM-Forward [10]	Jedynak et al. [3]
CN vs. MCI	0.5914	0.5838	0.5800	0.5468
CN vs. AD	0.9029	0.8404	0.8150	0.7826
MCI vs. AD	0.7844	0.6936	0.6890	0.7330
CN-MCI-AD	0.7596	0.7059	0.6947	0.6875

As it can be deduced from Table 2, our proposed method outperforms all other modeling techniques in all categories. It should be noticed that when we apply data imputation, the backpropagation formulas simply generalize to the standard LSTM network.

To assess the ability of the estimated biomarkers' measurements in predicting the clinical labels, we apply linear discriminant analysis (LDA) to the multi-dimensional training data estimations to compute the posterior probability scores in the test data. The obtained scores are then used to calculate the AUC's. The diagnostic prediction results for the test set are shown in Table 3 for the utilized methods.

As can be seen, the proposed method outperforms all other schemes in predicting clinical status of subjects per visits. This, in turn, reveals the effect of modeling on classification performance. One could of course use different classifiers to improve the results. But, our focus in this paper is on DPM or sequence-to-sequence learning. On the other hand, it is possible to train the LSTM network for a classification (sequence-to-label) problem. However, in practice, even less data is labeled to be used for training the network to improve the diagnostic prediction performance.

4 Summary and discussion

In this paper, a training algorithm was proposed for LSTM networks aiming to improve robustness against missing data, and applied for AD progression modeling using longitudinal measurements of imaging biomarkers. To the best of our knowledge this was the first time RNNs were studied on DPM problem within ADNI cohort. The proposed training method demonstrated better performance than using imputation prior to standard LSTM network and outperformed an established parametric, regression-based DPM method, in terms of both joint modeling for biomarker prediction and subsequent diagnostic classification.

Furthermore, the diagnostic classification results of the predicted MRI biomarkers' measurements using the proposed approach are comparable to state-of-the-art cross-sectional MRI-based classification results in the recent challenge on Computer-Aided Diagnosis of Dementia (CADDementia) [18]. To be more specific, LDA classification on predicted features using the proposed method achieves a multi-class AUC of 0.76 which is within the top-five multi-class AUCs in the challenge that ranged from 0.79 to 0.75. It should, however, be noted that there are important differences between this study and the CADDementia challenge. Firstly, this work has the advantage of training and testing features from the same cohort whereas CADDementia algorithms were applied to classify data from independent cohorts. Secondly, the top performing CADDementia algorithms incorporated different types of MRI features besides volumetry. Thirdly, in contrast to CADDementia that features were completely available, this work predicts features based on longitudinal data before classification.

The most common approaches to handling missing data with LSTM networks are data interpolation pre-processing steps, usually using mean or forward imputation. This two-step procedure decouples missing data handling and network training and is heavily influenced by the choice of data imputation scheme, resulting in a sub-optimal performance. Other approaches, however, update the architecture to utilize possible correlations between missing values' patterns and the target to improve prediction results [10, 11]. Our goal is different; we want to make the training of LSTM networks robust to missing values to more faithfully capture the true underlying signal, and to make the learned model generalizable across cohorts – not relying on a specific cohort or demographic-specific circumstances correlated with the target.

This study highlights the potential of RNNs for modeling the progression of AD using longitudinal measurements, provided that proper care is taken to handle issues with the data under study including missing values and time intervals. In general, standard LSTM networks are designed to handle sequences with a fixed temporal or spatial sampling rate within longitudinal data. We use the same approach in the AD progression modeling application by disregarding, for example, visiting months 3, 6 and 18, and confine the experiments to yearly follow-up in the ADNI data. However, one could utilize modified LSTM architectures such as time-aware LSTM [19] to address irregular time steps in longitudinal patient records.

Acknowledgments

This project has received funding from the European Union's Horizon 2020 research and innovation programme under the Marie Skłodowska-Curie grant agreement No 721820. This work uses the TADPOLE data sets https://tadpole.grand-challenge.org constructed by the EuroPOND consortium http://europond.eu funded by the European Union's Horizon 2020 research and innovation programme under grant agreement No 666992.

References

[1] Guy McKhann, David Drachman, Marshall Folstein, Robert Katzman, Donald Price, and Emanuel M. Stadlan. Clinical diagnosis of Alzheimer's disease. *Neurology*, 34(7):939–939, 1984.

[2] Neil P. Oxtoby and Daniel C. Alexander. Imaging plus X: multimodal models of neurodegenerative disease. *Current opinion in neurology*, 30(4):371, 2017.

[3] Bruno M. Jedynak, Andrew Lang, Bo Liu, Elyse Katz, Yanwei Zhang, Bradley T. Wyman, David Raunig, C. Pierre Jedynak, Brian Caffo, and Jerry L Prince. A computational neurodegenerative disease progression score: method and results with the Alzheimer's disease neuroimaging initiative cohort. *Neuroimage*, 63(3):1478–1486, 2012.

[4] Anders M. Fjell, Lars T. Westlye, Håkon Grydeland, Inge Amlien, Thomas Espeseth, Ivar Reinvang, Naftali Raz, Dominic Holland, Anders M. Dale, and Kristine B. Walhovd. Critical ages in the life course of the adult brain: nonlinear subcortical aging. *Neurobiology of aging*, 34 (10):2239–2247, 2013.

[5] Neil P. Oxtoby, Alexandra L. Young, Nick C. Fox, Pankaj Daga, David M. Cash, Sebastien Ourselin, Jonathan M. Schott, and Daniel C. Alexander. Learning imaging biomarker trajectories from noisy Alzheimer's disease data using a bayesian multilevel model. In *Bayesian and grAphical Models for Biomedical Imaging*, pages 85–94. 2014.

[6] Michael C. Donohue, Helene Jacqmin-Gadda, Mélanie Le Goff, Ronald G. Thomas, Rema Raman, Anthony C. Gamst, Laurel A. Beckett, Clifford R. Jack, Michael W. Weiner, Jean-Francois Dartigues, and Paul S. Aisen. Estimating long-term multivariate progression from short-term data. *Alzheimer's & dementia: the journal of the Alzheimer's Association*, 10(5): S400–S410, 2014.

[7] Wai-Ying Wendy Yau, Dana L. Tudorascu, Eric M. McDade, Snezana Ikonomovic, Jeffrey A. James, Davneet Minhas, Wenzhu Mowrey, Lei K. Sheu, Beth E. Snitz, Lisa Weissfeld, et al. Longitudinal assessment of neuroimaging and clinical markers in autosomal dominant Alzheimer's disease: a prospective cohort study. *The Lancet Neurology*, 14(8):804–813, 2015.

[8] Ricardo Guerrero, Alexander Schmidt-Richberg, Christian Ledig, Tong Tong, Robin Wolz, and Daniel Rueckert. Instantiated mixed effects modeling of Alzheimer's disease markers. *NeuroImage*, 142:113–125, 2016.

[9] Barak A. Pearlmutter. Learning state space trajectories in recurrent neural networks. *Neural Computation*, 1(2):263–269, 1989.

[10] Zachary C. Lipton, David C. Kale, and Randall Wetzel. Modeling missing data in clinical time series with RNNs. *Machine Learning for Healthcare*, 2016.

[11] Zhengping Che, Sanjay Purushotham, Kyunghyun Cho, David Sontag, and Yan Liu. Recurrent neural networks for multivariate time series with missing values. *arXiv:1606.01865*, 2016.

[12] Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

[13] Felix A. Gers, Jürgen Schmidhuber, and Fred Cummins. Learning to forget: Continual prediction with LSTM. 1999.

[14] Felix A. Gers and Jürgen Schmidhuber. LSTM recurrent networks learn simple context-free and context-sensitive languages. *IEEE Transactions on Neural Networks*, 12(6):1333–1340, 2001.

[15] Klaus Greff, Rupesh K. Srivastava, Jan Koutník, Bas R. Steunebrink, and Jürgen Schmidhuber. LSTM: A search space odyssey. *IEEE transactions on neural networks and learning systems*, 28(10):2222–2232, 2017.

[16] Ronald Carl Petersen, P.S. Aisen, L.A. Beckett, M.C. Donohue, A.C. Gamst, D.J. Harvey, C.R. Jack, W.J. Jagust, L.M. Shaw, A.W. Toga, J.Q. Trojanowski, and M.W. Weiner. Alzheimer's disease neuroimaging initiative (ADNI) clinical characterization. *Neurology*, 74(3):201–209, 2010.

[17] David J. Hand and Robert J. Till. A simple generalisation of the area under the ROC curve for multiple class classification problems. *Machine learning*, 45(2):171–186, 2001.

[18] Esther E. Bron, Marion Smits, Wiesje M. Van Der Flier, Hugo Vrenken, Frederik Barkhof, Philip Scheltens, Janne M. Papma, Rebecca M.E. Steketee, Carolina Méndez Orellana, Rozanna Meijboom, et al. Standardized evaluation of algorithms for computer-aided diagnosis of dementia based on structural MRI: the CADDementia challenge. *NeuroImage*, 111:562–579, 2015.

[19] Inci M. Baytas, Cao Xiao, Xi Zhang, Fei Wang, Anil K. Jain, and Jiayu Zhou. Patient subtyping via time-aware LSTM networks. In *Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 65–74, 2017.