GDPP: Learning Diverse Generations using Determinantal Point Processes

Abstract

Generative models have proven to be an outstanding tool for representing high-dimensional probability distributions and generating realistic looking images. A fundamental characteristic of generative models is their ability to produce multi-modal outputs. However, while training, they are often susceptible to mode collapse, which means that the model is limited in mapping the input noise to only a few modes of the true data distribution. In this paper, we draw inspiration from Determinantal Point Process (DPP) to devise a generative model that alleviates mode collapse problem while producing higher quality samples. DPP is an elegant probabilistic measure used to model negative correlations within a subset and hence quantify its diversity. We use DPP to model the diversity in real data as well as in synthetic data. Then, we propose a generation penalty term that encourages the generator to synthesize data with a similar diversity to real data. In contrast to previous state-of-the-art generative models that tend to use additional trainable parameters or complex training paradigms, our method does not change the original training scheme. Embedded in an adversarial training and variational autoencoder, our Generative DPP approach shows a consistent resistance to mode-collapse on a wide-variety of synthetic data and natural image datasets including MNIST, CIFAR10 and CelebA, while outperforming state-of-the-art methods for data-efficiency, convergence-time, and generation quality. Our code will be made publicly available.

1 Introduction

Deep generative models have gained enormous research interest in recent years as a powerful framework to learn high dimensional data in an unsupervised fashion. Generative Adversarial Networks (GANs) (Goodfellow et al., 2014) are among the most dominant generative approaches, and consist of training two networks: a generator and a discriminator. The generator attempts to map random noise to *fake* data points that simulate the probability distribution of *real* data. In adversary, the discriminator aims to distinguish real data from fake data. The constant competition between the networks results in improved performance of both of them. GANs are typically attributed with high quality and sharp images. Nevertheless, in the process of learning such multi-modal complex distribution, the system may converge to a trivial solution where the generator only learns to produce few modes exclusively, as referred as the mode collapse problem.

To address this, we propose utilizing Determinantal Point Processes (DPP) to model the diversity within data samples. DPP is a probabilistic model that has been mainly adopted to solve subset selection problems with diversity constraints (Kulesza & Taskar, 2011), such as video and document summarization. By repetitively modeling the diversity within real and fake data along the training process, we aim at matching the one of fake to the one of real by imposing a diversity constraint on the generation. We encourage the generator on producing samples of similar diversity distribution to the true-data. This way, the generator explicitly learns to cover significantly more modes of the real distributions alleviating the mode collapse problem.

Recent approaches tackled the mode-collapse problem in one of two different ways: (1) improving the learning of the system to reach a better convergence point(e.g. Metz et al. (2017); Arjovsky & Bottou (2017)); or (2) explicitly enforcing the models to capture diverse modes or map back to the true-data distribution (e.g. Srivastava et al. (2017); Che et al. (2017)). Here we focus on a relaxed

version of the former, where we use the same learning paradigm of the standard GANs and only change the objective function. The advantage of such an approach is to avoid adding any extra trainable parameters to the trained system while maintaining the same back-propagation steps as the standard GANs. Thus, our model converges faster to a fair equilibrium point where the generator captures the diversity of the true-data distribution while preserving the quality of the generations.

Contribution. We introduce a new loss function, that we denote Generative Determinantal Point Processes (*GDPP*) loss. Our loss only assumes an access to a generator, a feature extraction function $\phi(\cdot)$, and sampler from true data distribution p_d. The loss encourages the generator to diversify the generated samples similar to the diversity of real data. This criterion can be considered as a complement to the original adversarial loss which attempts to learn an indistinguishable distribution from the true-data distribution without being specific to diverse modes. We assess the performance of GDPP on three different synthetic data environments, while also verifying the superiority on two real-world images datasets. We compared our approach with state-of-the-art approaches of more complex architectures and learning paradigms and our experiments show that outperforms all the competing methods in terms of alleviating mode-collapse, and the generator quality.

2 RELATED WORK

Among the tremendous amount of work that tackles the training challenges of Generative Adversarial Networks (GANs), a few methods stood out as significant contributions towards addressing the problem of mode collapse.

Methods that map the data back to noise. (Donahue et al., 2017; Dumoulin et al., 2017) are one of the earliest methods that proposed learning a reconstruction network besides learning the deep generative network. Adding this extra network to the system aims at reversing the action of the generator by mapping from data to noise. Likelihood-free variational inference (LFVI) (Tran et al., 2017), merge this concept with learning implicit densities using hierarchical Bayesian modeling. Ultimately, VEEGAN (Srivastava et al., 2017) used the same concept, but the authors did not base their reconstruction loss on the discriminator. This has the advantage of isolating the generation process from the discriminator's sensitivity to any of the modes. Che et al. (2017) proposed several ways of regularizing the objective of adversarial learning including geometric metric regularizer, mode regularizer, and manifold-diffusion training. Mode regularization specifically has shown a potential into addressing the mode collapse problem and stabilizing the GANs training in general.

Methods that provide a surrogate objective function. Chen et al. (2016) on the other hand propose with InfoGAN an information-theoretic extension of GANs that obtains disentangled representation of data by latent-code reconstitution through a penalty term in its objective function. InfoGAN includes an autoencoder over the latent codes; however, it was shown to have stability problems similar to the standard GAN and requires stabilization tricks. Ghosh et al. (2018) base the ModeGAN method on the assumption of the availability of sufficient samples of every mode on the training data. In particular, if a sample from the true data distribution belongs to a particular mode, then the generated fake sample is likely to belong to the same mode. The Unrolled-GAN of Metz et al. (2017) propose a novel objective to update the generator with respect to the unrolled optimization of the discriminator. This allows training to be adjusted between using the optimal discriminator in the generator's objective. It has been shown to improve the generator training process which in turn helps to reduce the mode collapse problem. Generalized LS-GAN of Edraki & Qi (2018) define a pullback operator to map generated samples to the data manifold. BourGAN Xiao et al. (2018), with a similar philosophy, additionally draws samples from a mixture of Gaussians instead of a single Gaussian. There is, however, no specific enforcement to diversify samples. Spectral normalization strategies have been recently proposed in the works of Miyato et al. (2018) and SAGAN (Zhang et al., 2018) to further stabilize the training. We note that these strategies are orthogonal to our contribution and could be implemented in conjunction with ours to further improve the training stability of generator models. Finally, improving the Wasserstein GANs of Arjovsky et al. (2017), WGAN-GP (Gulrajani et al., 2017) introduce a gradient penalization employed in state-of-the-art systems (Karras et al., 2018).

Methods use multiple generators and discriminators. One of the popular methods to reduce mode collapse is using multiple generator networks to provide a better coverage of the true data

distribution. Liu & Tuzel (2016) propose using two generators with shared parameters to learn the joint distribution of the data. The two generators are trained independently on two domains to ensure a diverse generation. However, sharing the parameters guide both the generators to a similar subspace. Also, Durugkar et al. (2017) propose a similar idea of multiple discriminators that are being an ensemble, which was shown to produce better quality samples. Recently, Ghosh et al. (2018) proposed MAD-GAN which is a multi-agent GAN architecture incorporating multiple generators and one discriminator. Along with distinguishing real from fake samples, the discriminator also learns to identify the generator that generated the fake sample. The learning of such a system implies forcing different generators to learn unique modes, which helps in a better coverage of data modes. DualGAN of Nguyen et al. (2017) improves the diversity within GANs at the additional requirement of training two discriminators. In contrast to these approaches, our DPP-GAN does not require the training of extra networks which provides an easier and faster training as well as being less susceptible to overfitting.

Finally, we also refer to PacGAN Lin et al. (2018) as another approach addressing mode collapse. They do that by modifying the discriminator input with concatenated samples to better sample the diversity within real data. Nevertheless, such approach is subject to memory and computational constraints as a result of the significant increase in batch size.

3 DETERMINANTAL POINT PROCESS (DPP)

DPP is a probabilistic measure that was introduced in quantum physics (Macchi, 1975) and has been studied extensively in random matrix theory (Hough et al., 2006). It provides a tractable and efficient means to capture negative correlation with respect to a similarity measure, that in turn can be used to quantify the diversity within a subset. A key characteristic in DPP that the model is agnostic about the order of items as pointed out by Gong et al. (2014), and therefore can be used to model data that is randomly sampled from a certain distribution.

A point process $\mathcal{P}$ on a ground set $\mathcal{V}$ is a probability measure on the power set of $\mathcal{V}$ (i.e., 2^N), where $N = |\mathcal{V}|$ is the size of the ground set. A point process $\mathcal{P}$ is called determinantal if, given a random subset Y drawn according to $\mathcal{P}$, we have for every $S \subseteq Y$,

$$\mathcal{P}(S \subseteq Y) \propto \det(L_S) \tag{1}$$

for some symmetric similarity kernel $L \in \mathbb{R}^{N \times N}$, where L_S is the similarity kernel of subset S. L must be real, positive semidefinite matrix $L \preceq I$ (all the eigenvalues of L is between 0 and 1); since it represents a probabilistic measure and all of its principal minors must be non-negative.

L is often referred to as the marginal kernel because it contains all the information needed to compute the probability of any subset S being selected in $\mathcal{V}$. L_S denotes the sub-matrix of L indexed by S, specifically, $L_S \equiv [L_{ij}]; i, j \in S$. Hence, the marginal probability of including one element e_i is $p(e_i \in Y) = L_{ii}$, and two elements e_i and e_j is $L_{ii}L_{jj} - 2L_{ij}^2 = p(e_i \in Y)p(e_j \in Y) - L_{ij}^2$. A large value of L_{ij} reduces the likelihood of both elements to appear together. Kulesza & Taskar (2010) proposed decomposing the kernel L_S as a Gram matrix:

$$\mathcal{P}(S \subseteq Y) \propto \det(\phi(S)^\top \phi(S)) \prod_{e_i \in S} q^2(e_i), \tag{2}$$

Here $q(e_i) \geq 0$ may be seen as a quality score of an item e_i in the ground set $\mathcal{V}$, while $\phi_i \in \mathbb{R}^D; D \leq N$ and $||\phi_i||_2 = 1$ is used as an ℓ_2 normalized feature vector of an item. In this manner, $\phi_i^\top \phi_j \in [-1, 1]$ is evaluated as a "normalized similarity" between items e_i and e_j of $\mathcal{V}$, and the kernel L_S is guaranteed to be real positive semidefinite matrix.

Geometric interpretation: $\det(\phi(S)^\top \phi(S)) = \prod_i \lambda_i$, where λ_i is the i^{th} eigen value of the matrix $\phi(S)^\top \phi(S)$. Hence, we may visualize that DPP models diverse representations of data because the determinant of $\phi(S)^\top \phi(S)$ corresponds to the volume in n-D represented by the multiplication of the variances of the data (i.e., the eigen values).

DPP in literature: DPP has proven to be a tremendously valuable tool when addressing the problem of diversity enforcing such as document summarization (e.g., Kulesza & Taskar (2011); Hong & Nenkova (2014)), pose estimation (e.g., Gupta (2015)) and video summarization (e.g., Gong et al.

(a) Given a generator G, and feature extraction function ϕ, the diversity kernel is constructed as $L_S = \phi^\top \cdot \phi$. We use the last feature map of the discriminator in GAN or the encoder in VAE as the feature representation ϕ of a fake/real batch.

(b) Using ϕ obtained from generated samples, we model their diversity using L_{S_B}. We also model the diversity of a real batch by extracting its features and constructing its diversity kernel L_{D_B}. Adversarial loss aims at generating similar data points to the real, and diversity loss aims at matching fake data diversity kernel L_{S_B} to real data diversity kernel L_{D_B}.

Figure 1: We draw inspiration from DPP to model a subset diversity using a kernel. During training, we extract the feature representation of real and fake batches ϕ_{real} and ϕ_{fake}. Then, we construct their diversity kernels: L_{S_B}, L_{D_B}. Our loss encourages G to synthesize data of similar diversity L_{S_B} to the real data diversity L_{D_B}.

(2014); Mahasseni et al. (2017)). For instance, Zhang et al. (2016) proposed to learn the two parameters q, ϕ in eq. 2 to quantify the diversity of the kernel L_S using MLPs based on spatio-temporal features of the video to perform summarization. Recently, Hsiao & Grauman (2018) proposed to use DPP to automatically create capsule wardrobes, i.e. assemble a minimal set of items that provide maximal mix-and-match outfits given an inventory of candidate garments.

4 GENERATIVE DETERMINANTAL POINT PROCESSES

As illustrated in Fig. 1b, our GDPP loss encourages the generator to sample fake data of diversity similar to real data diversity. The key challenge is to model the diversity within real data and fake data. We discussed in Sec. 3 how DPP is used to model the negative correlation within a discrete data distribution, which is commonly employed as a measure of diversity. Thus, we construct a DPP kernel for both the real data and the generated samples at every iteration of the training process as shown in Fig. 1a. Then, we encourage the network to generate samples that have a similar diversity kernel to that of the training data. To simplify the optimization process, we choose to match the eigenvalues and eigenvectors of the fake data DPP kernel with their corresponding of the real data DPP kernel.

During training, a generative model G produces a batch of samples $S_B = \{e_1, e_2, \cdots e_B\}$, where B is the batch size. Our aim is to produce S_B that is probabilistically sampled following the DPP which satisfies:

$$\mathcal{P}(S_B \subseteq Y) \propto \det(L_{S_B}), \tag{3}$$

such that Y is a random variable representing a subset drawn with a generative point process $\mathcal{P}$, and L_{S_B} is the kernel matrix of the subset indexed by S, as detailed in Sec. 3. Connecting DPP to the data generation, we assume that G is the point process sampler that generates subset S_B according to $\mathcal{P}$. Let $\phi(S_B) \in \mathbb{R}^{d \times B}$ be a feature representation of the generated subset S_B, where $\phi(\cdot)$ is a feature extraction function. Therefore, the DPP kernel is constructed as follows:

$$L_{S_B} = \phi(S_B)^\top \phi(S_B); \quad S_B = G(z_B), \tag{4}$$

where $z_B \in R^{d_z \times B}$ is noise vector inputted to the generator G resulting in the generated subset S_B. Let us denote $\phi(S_B)$ a feature representation of a generated batch and $\phi(D_B)$ a feature representation of a true batch. Our aim is to match $\mathcal{P}(S_B \subseteq Y) \propto [\det(L_{S_B}) = \prod_i \lambda^i_{fake}]$ to $\mathcal{P}(D_B \sim p_d) \propto [\det(L_{D_B}) = \prod_i \lambda^i_{real}]$, where λ^i_{real} and λ^i_{fake} are the i^{th} eigenvalues of L_{D_B} and L_{S_B} respectively. Thus, our problem is reduced to learn a fake diversity kernel L_{S_B} close to

the real diversity kernel L_{D_B}. We choose to match those kernels using their major characteristics: eigenvalues and eigenvectors.

Our GDPP loss is composed of two components: diversity magnitude loss $\mathcal{L}_m$, and diversity structure loss $\mathcal{L}_s$ as follows:

$$\mathcal{L}_g^{DPP} = \mathcal{L}_m + \mathcal{L}_s = \sum_i \|\lambda_{real}^i - \lambda_{fake}^i\|_2 - \sum_i \hat{\lambda}_{real}^i \cos(v_{real}^i, v_{fake}^i) \qquad (5)$$

where v_{fake}^i and v_{real}^i are the i^{th} eigenvectors of L_{D_B} and L_{S_B} respectively. $\hat{\lambda}_{real}^i$ are the min-max normalized version of its corresponding eigenvalues λ_{real}^i. We note that $\lambda \geq 0$ for both fake and real data, since both L_{S_B} and L_{D_B} are guaranteed to be positive semidefinite matrices.

Scaling the structure loss aims to induce noise invariance within the eigenvectors similarity learning. This can be seen as alleviating the effect of outlier structures that intrinsically exist within the real data on learning the diversity kernel of fake data. We note that all the eigenvalues of L_{S_B} and L_{S_D} will be real non-negatives since both of the kernels are symmetric semi-positive definite. Therefore, the kernels represent a probability measure since none of the principal minors will be negative.

Integrating GDPP loss with GANs. For a primary benchmark, we integrate our GDPP loss with GANs. Since our aim is to avoid adding any extra trainable parameters, we utilize features extracted by the discriminator. We choose to use the hidden activations before the last layer as our feature extraction function $\phi(.)$. We apply ℓ_2 normalization on the obtained features that guarantees constructing a positive semi-definite matrix according to eq. 2. We finally integrate $\mathcal{L}_g^{DPP}$ into the GAN objective by only modifying the generator loss of the standard adversarial loss (Goodfellow et al., 2014) as follows:

$$\mathcal{L}_g = \mathbb{E}_{z \sim p_z}[\log(1 - D(G(z)))] + \mathcal{L}_g^{DPP}. \qquad (6)$$

Integrating GDPP loss with VAEs. A key property of our loss is its generality to any generative model. Beside incorporating our loss in GANs, we prove it can be also embedded within Variational Auto-Encoders (VAEs) proposed in Kingma & Welling (2013). We use the decoder network as our generator G and the final hidden activations within the encoder network as our feature extraction function $\phi(.)$. To compute $\mathcal{L}^{DPP}$ at the training time, we feed an input training batch D_B to the encoder constructing L_{D_B}. We also feed a random Gaussian noise to the decoder that generates a fake batch S_B, which we then feed to the encoder to construct L_{S_B}. Finally, we compute $\mathcal{L}^{DPP}$ as stated in eq. 2 using the ℓ_2 normalized features, then add it to the original VAE loss at the training time as follows:

$$\mathcal{L}_{VAE} = \mathbb{E}_{z \sim p(z|x)}[\log\{p(x|z)\}] + KL[p(z|x)||p(z)] + \mathcal{L}^{DPP}. \qquad (7)$$

5 EXPERIMENTS

In our experiments, we target evaluating the generation based on two criteria: mode collapse and generated samples quality. Due to the intractability of log-likelihood estimation, this problem tends to be non-trivial in real data. Therefore, we start by analyzing our method on synthetic data where we can accurately evaluate the performance. Then, we demonstrate the effectiveness of our method on real data using standard evaluation metrics. We note that the same architecture is used for all the methods on the same data; one for synthetic data and one for the real datasets (See appendix A for details).

5.1 SYNTHETIC DATA EXPERIMENTS

Mode collapse and the quality of generations can be explicitly evaluated on synthetic data since the true distribution is well-defined. In this section, we evaluate the performance of the methods on mixtures of Gaussian of known mode locations and distribution (See appendix B for details). We use the same architecture for all the models, which is the same one used by Metz et al. (2017) and Srivastava et al. (2017). We note that the first four rows in Table 1 are obtained from Srivastava et al. (2017), since we are using the same architecture and training paradigm. Fig. 2 displays the effect of each method on the 2D Ring and Grid data. As shown by the vanilla-GAN in the 2D Ring example (Fig. 2a), it can generate the highest quality samples however it only captures a single mode. On

	2D Ring		2D Grid		1200D Synthetic	
	Modes (Max 8)	% High Quality Samples	Modes (Max 25)	% High Quality Samples	Modes (Max 10)	% High Quality Samples
GAN (Goodfellow et al., 2014)	1	99.3	3.3	0.5	1.6	2.0
ALI (Dumoulin et al., 2017)	2.8	0.13	15.8	1.6	3	5.4
Unrolled GAN (Metz et al., 2017)	7.6	35.6	23.6	16.0	0	0.0
VEE-GAN (Srivastava et al., 2017)	**8.0**	52.9	24.6	40.0	5.5	28.3
WGAN-GP (Gulrajani et al., 2017)	6.8	59.6	24.2	28.7	6.4	29.5
GDPP-GAN	**8.0**	**71.7**	**24.8**	**68.5**	**7.4**	**48.3**

Table 1: Sample quality and degree of mode collapse on mixtures of Gaussians. GDPP-GAN consistently captures the highest number of modes and produces better samples.

the other extreme, the WGAN-GP on the 2D grid (Fig. 2k) captures almost all the modes in the true distribution, but this is simply because it generates highly scattered samples that do not precisely depict the true distribution. GDPP-GAN (Fig. 2f,l) creates a precise representation of the true data distribution reflecting that the method learned an accurate structure manifold.

Performance Evaluation: In every iteration of our experiments, we sample fake points from the generator and real points from the given distribution. The mode collapse is quantified by the number of real modes recovered in fake data, and the generation quality is quantified by the % of High-Quality Samples. A generated sample is counted as high-quality if it was sampled within three standard deviations in the case of the 2D Ring or 2D Grid, and ten standard deviations in the case of the 1200D data. We train all the models for 25K iterations, except for VEEGAN which is trained for 100K iterations. At inference time, we generate 2500 samples from each of the trained models and measure both metrics. We report the numbers averaged over five runs with different random initialization in Table 1. GDPP-GAN clearly outperforms all other methods, for instance on the most challenging 1200D dataset that was designed to mimic a natural data distribution, bringing a 63% relative improvement in high-quality samples and 15% in mode detection over its best competitor WGAN-GP.

Ablation Study: We run a study on the 2D Ring and Grid data to show the individual effects of each component in our loss. As shown in Table 2, optimizing the determinant $\det L_S$ directly increases the diversity generating the highest quality samples. This works best on the 2D Ring since the true data distribution can be represented by a repulsion model. However, for more complex data such as the 2D Grid, optimizing the determinant fails because it does not well-represent the structure of the diversity and aims at repelling the fake samples from each other. Nonetheless, learning the unnormalized structure is prone to outlier structures introduced by the noise in the data and in the learning process. However, when scaling the structure loss by the true-data eigenvalues seems to better disengage the model from the noise that exists within the true-data features and only focus on learning the dominant structure.

Data-Efficiency: We evaluate the amount of training data needed by each method to reach the same local optima as evaluated by our two metrics on both the 2D Ring and Grid data. Since we are sampling the true-data from a mixture of Gaussians, we can generate an infinite size of training data.

Figure 2: Scatter plots of the true data(green dots) and generated data(blue dots) from different GAN methods trained on mixtures of Gaussians arranged in a ring (top) or a grid (bottom).

(a) Examining the effect of training batch size B given the same number of training iterations.

(b) Monitoring convergence at different iterations given the same training data size.

Figure 3: Evaluating the models on the 2D Ring and Grid datasets in terms of (a) data-efficiency and (b) time-efficiency. GDPP-GAN tends to converge faster and require the least amount of training data.

Therefore, we can quantify the amount of the training data by using the batch-size while fixing the number of back-propagation steps. In this experiment (Fig. 3a), we run all the methods for the same number of iterations (25,000) and vary the batch size. However, WGAN-GP tends to capture higher quality samples with fewer data. In the case of the 2D Grid data, GDPP-GAN performs on par with other methods for small amounts of data, yet it tends to significantly outperform other methods on the quality of generated samples once trained on enough data.

Time-Efficiency: Another property of interest is which method converges faster given the same amount of training data. In this experiment, we fix the batch size at 512 and train the models for a variable number of iterations (Fig. 3b). For the 2D Ring, Only VEE-GAN captures a higher number of modes before GDPP-GAN, however, they are of much lower quality than the ones generated by GDPP-GAN. In the 2D Grid data, GDPP-GAN performs on par with unrolled-GAN for the first 5,000 iterations while the others are falling behind. After that our method significantly outperforms all the methods with respect to both the number of captured modes and the quality of generated samples.

5.2 Image generation experiments

We use the architecture described in (Gulrajani et al., 2017) for evaluating all the models on the Stacked MNIST (Metz et al., 2017), CIFAR10, CelebA datasets. In the evaluation, we mainly focus on comparing to methods that adopt a change in the original adversarial loss. Nevertheless, many of them can be deemed orthogonal to our contribution and can enhance the generation if embedded with our approach. Since our method is cost-free, we observe that the training of GDPP-GAN has an indistinguishable running time than the DCGAN, which are the fastest models to train. We show the average iteration time of each of the methods in Table 5 in Appendix C. We also show that our loss is generic to any generative model by comparing it with the Variational AutoEncoder (VAE) Kingma & Welling (2013).

Stacked-MNIST A variant of MNIST (LeCun, 1998) designed to increase the number of discrete modes in the data. The data is synthesized by stacking three randomly sampled MNIST digits along

	2D Ring		2D Grid	
	Modes (Max 8)	% High Quality Samples	Modes (Max 25)	% High Quality Samples
Exact determinant: $(\det[L_{S_B}])$	**8**	**82.9**	12.6	21.7
Only diversity magnitude: $(\mathcal{L}_m)$	**8**	67.0	20.4	15.9
Only diversity structure: $(\mathcal{L}_s)$	**8**	65.2	18.2	35.2
GDPP with unnormalized $\mathcal{L}_s$: $(\mathcal{L}_m + \mathcal{L}_s^u)$	7.2	81.2	20.6	**68.8**
Final GDPP-loss: $(\mathcal{L}_m + \mathcal{L}_s)$	**8**	71.7	**24.8**	68.5

Table 2: GDPP loss Ablation study. $\mathcal{L}_s^u$ is the same as $\mathcal{L}_s$ without min-max eigen value normalization

	Stacked-MNIST		CIFAR-10	
	#Modes (Max 1000)	KL div.	Inception score	IvO
DCGAN (Radford et al., 2016)	427	3.163	5.26 ± 0.13	0.0911
DeLiGAN (Gurumurthy et al., 2017)	767	1.249	5.68 ± 0.09	0.0896
Unrolled-GAN (Metz et al., 2017)	817	1.430	5.43 ± 0.21	0.0898
RegGAN (Che et al., 2017)	955	0.925	5.91 ± 0.08	0.0903
WGAN (Arjovsky et al., 2017)	961	0.140	5.44 ± 0.06	0.0891
WGAN-GP (Gulrajani et al. (2017))	995	0.148	6.27 ± 0.13	0.0891
GDPP-GAN (Ours)	**1000**	**0.135**	**6.58 ± 0.10**	**0.0883**
VAE (Kingma & Welling, 2013)	341	2.409	1.19 ± 0.02	0.543
GDPP-VAE (Ours)	**623**	**1.328**	**1.32 ± 0.03**	**0.203**

Table 3: Performance of various methods on real datasets. Stacked-MNIST is evaluated using the number of captured modes (Mode Collapse) and KL-divergence between the generated class distribution and true class distribution (Quality of generations). CIFAR-10 is evaluated by Inference-via-Optimization (Mode-Collapse) and Inception-Score (Quality of generations).

Figure 4: Real images and their nearest generations of CIFAR-10. Nearest generations are obtained by optimizing the input noise to minimize the reconstruction error of the generated image.

Figure 5: Adding GDPP loss to DCGAN stabilizes adversarial training and generates high quality samples earlier on CIFAR-10.

the color channel resulting in a 28x28x3 image. In this case, Stacked MNIST has 1000 discrete modes corresponding to the number of possible triplets of digits. Following (Gulrajani et al., 2017), we generate 50,000 images that are later used to train the networks. We train all the models for 15,000 iterations, except for DCGAN and unrolled-GAN that need 30,000 iterations to converge to a reasonable local-optima.

We follow (Srivastava et al., 2017) to evaluate the methods on the number of recovered modes and the divergence between the true and fake distributions. We sample 26000 fake images for all the models. We identify the mode of each generated image by using the classifier mentioned in (Che et al., 2017) that is trained on the standard MNIST dataset to classify each channel of the fake sample. The quality of samples is evaluated by computing the KL-divergence between the generated label distribution and the training labels distribution. GDPP-GAN captures all the modes and generates a fake distribution that has the lowest KL-Divergence with the true-data. Moreover, when applied on the VAE, it doubles the number of modes captured and cuts the KL-Divergence to half.

CIFAR-10 Finally, we evaluate the methods on CIFAR-10 after training all the models for 100K iterations. Unlike Stacked-MNIST, the modes are intractable in this dataset. To assess the performance on real-world images, we use two metrics: Inception Score for the generation quality and Inference-via-Optimization for diversity. As shown in the Quantitative results on CIFAR and Stacked MNIST (Table 3), GDPP-GAN consistently outperforms all other methods in both mode collapse and developing higher quality samples. When applying the GDPP on the VAE, it reduces the IvO by 63%, however, we note that both the inception-scores are considerably low which is also observed by Shmelkov et al. (2018) when applying the VAE on CIFAR-10.

Inference-via-optimization (Metz et al., 2017), has been used to assess the severity of mode collapse in any generator by providing a metric to compare real images with the nearest generated image. In the case of mode collapse, there are some real images for which this distance is large. We measure this metric by sampling a real image x from the test set of real data. Then we optimize the ℓ_2 loss between x and generated image $G(z)$ by modifying the noise vector z. If a method attains low MSE,

then it can be assumed that this method captures more modes than ones that attain a higher MSE. Fig. 4 presents some real images with their nearest optimized generations. Randomly generated sample images can be seen in Appendix C. As demonstrated by (Srivastava et al., 2017), this metric can be fooled by producing blurry images out of the optimization. That is why the inception score is necessary for this evaluation.

Inception score (Salimans et al., 2016) is widely used as a metric for assessing the quality of images. It bases its validity from the premise that every realistic image should be recognizable by a standard architecture(e.g., Inception Network). Ideally, meaning that the score distribution for it must be dominated by one class. We also assess the stability of the training, by calculating the inception score at different stages while training on CIFAR-10 (Fig. 5). Evidently, DCGAN has the least stable training with a high variation. However, by only adding GDPP penalty term to the generator loss, model generates high-quality images the earliest on training with a stable increase.

CelebA Finally, to evaluate the performance of our loss on large-scale Adversarial training, we train Progressive-Growing GANs (Karras et al., 2017). We show the effect of embedding our loss in adversarial training by adding it to the WGAN-GP this time instead of DCGAN loss, which is as well orthogonal to our loss. We train the model for 40K iterations corresponding to 4 scales up to 64×64 results on CelebA dataset (Liu et al., 2018). Unlike CIFAR-10, CelebA dataset does not simulate ImageNet because it only contains faces not natural scenes/objects. Therefore, using a model trained on ImageNet as a basis for evaluation (i.e., Inception Score), might not be the best strategy. We follow Karras et al. (2017) to evaluate the performance on CelebA using Sliced Wasserstein Distance (SWD) (Peyré et al., 2017). A small Wasserstein distance indicates that the distribution of the patches is similar, which entails that real and fake images appear similar in both appearance and variation at this spatial resolution. Accordingly, SWD metric can evaluate the quality of images as well as the severity of mode-collapse on large-scale datasets such as CelebA. Table 4 shows the average and minimum SWD metric across the last 10K training iterations. For qualitative examples, refer to Fig. 12 in Appendix C.

	Avg. SWD	Min. SWD
DCGAN	0.0906	0.0241
WGAN-GP	0.0186	0.0115
GDPP-GAN	**0.0163**	**0.0075**

Table 4: Average and Minimum Sliced Wasserstein Distance over the last 10K iterations.

6   CONCLUSION

In this work, we introduce a novel criterion to train generative networks on capturing a similar diversity to one of the true data by utilizing Determinantal Point Process(DPP). We apply our criterion to Generative Adversarial training and the Variational Autoencoder by learning a kernel via features extracted from the discriminator/encoder. We train the generator on optimizing a loss between the fake and real, eigenvalues and eigenvectors of this kernel to simulate the diversity of the real data. Our GDPP framework accumulates many desirable properties: it does not require any extra trainable parameters, it works in an unsupervised setting, and outperforms state-of-the-art on synthetic data and real image datasets for both generation quality and invariance to mode collapse. Furthermore, GDPP-GANs exhibit a stabilized adversarial training and has been shown to be time and data efficient as compared to state-of-the-art approaches. Moreover, the GDPP criterion is architecture and model invariant, allowing it to be embedded with any variants of generative models such as adversarial feature learning or conditional GANs.

REFERENCES

Martin Arjovsky and Léon Bottou. Towards principled methods for training generative adversarial networks. *stat*, 1050:17, 2017.

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein gan. *stat*, 1050:26, 2017.

Tong Che, Yanran Li, Athul Paul Jacob, Yoshua Bengio, and Wenjie Li. Mode regularized generative adversarial networks. *ICLR*, 2017.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. In *NIPS*, 2016.

Jeff Donahue, Philipp Krähenbühl, and Trevor Darrell. Adversarial feature learning. *ICLR*, 2017.

Vincent Dumoulin, Ishmael Belghazi, Ben Poole, Olivier Mastropietro, Alex Lamb, Martin Arjovsky, and Aaron Courville. Adversarially learned inference. *ICLR*, 2017.

Ishan Durugkar, Ian Gemp, and Sridhar Mahadevan. Generative multi-adversarial networks. *ICLR*, 2017.

Marzieh Edraki and Guo-Jun Qi. Generalized loss-sensitive adversarial learning with manifold margins. In *ECCV*, 2018.

Arnab Ghosh, Viveka Kulharia, Vinay Namboodiri, Philip HS Torr, and Puneet K Dokania. Multi-agent diverse generative adversarial networks. *CVPR*, 2018.

Boqing Gong, Wei-Lun Chao, Kristen Grauman, and Fei Sha. Diverse sequential subset selection for supervised video summarization. In *NIPS*, 2014.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *NIPS*, 2014.

Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron C Courville. Improved training of Wasserstein GANs. In *NIPS*. 2017.

Swati Gupta. Determinantal point processes. *Lecture notes*, 2015.

Swaminathan Gurumurthy, Ravi Kiran Sarvadevabhatla, and R Venkatesh Babu. Deligan: Generative adversarial networks for diverse and limited data. In *CVPR*, pp. 4941–4949, 2017.

Kai Hong and Ani Nenkova. Improving the estimation of word importance for news multi-document summarization. In *Proceedings of the 14th Conference of the European Chapter of the Association for Computational Linguistics*, pp. 712–721, 2014.

J Ben Hough, Manjunath Krishnapur, Yuval Peres, Bálint Virág, et al. Determinantal processes and independence. *Probability surveys*, 3:206–229, 2006.

Wei-Lin Hsiao and Kristen Grauman. Creating capsule wardrobes from fashion images. In *CVPR*, 2018.

Tero Karras, Timo Aila, Samuli Laine, and Jaakko Lehtinen. Progressive growing of gans for improved quality, stability, and variation. *arXiv preprint arXiv:1710.10196*, 2017.

Tero Karras, Timo Aila, Samuli Laine, and Jaakko Lehtinen. Progressive growing of GANs for improved quality, stability, and variation. *ICLR*, 2018.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Alex Kulesza and Ben Taskar. Structured determinantal point processes. In *NIPS*, 2010.

Alex Kulesza and Ben Taskar. Learning determinantal point processes. *arXiv:1202.3738*, 2011.

Yann LeCun. The MNIST database of handwritten digits. *http://yann. lecun. com/exdb/mnist/*, 1998.

Zinan Lin, Ashish Khetan, Giulia C. Fanti, and Sewoong Oh. Pacgan: The power of two samples in generative adversarial networks. *NIPS*, 2018.

Ming-Yu Liu and Oncel Tuzel. Coupled generative adversarial networks. In *NIPS*, 2016.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Large-scale celebfaces attributes (celeba) dataset. *Retrieved August*, 15:2018, 2018.

Odile Macchi. The coincidence approach to stochastic point processes. *Advances in Applied Probability*, 7(1):83–122, 1975.

Behrooz Mahasseni, Michael Lam, and Sinisa Todorovic. Unsupervised video summarization with adversarial lstm networks. In *CVPR*, 2017.

Luke Metz, Ben Poole, David Pfau, and Jascha Sohl-Dickstein. Unrolled generative adversarial networks. *ICLR*, 2017.

Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks. *ICLR*, 2018.

Tu Nguyen, Trung Le, Hung Vu, and Dinh Phung. Dual discriminator generative adversarial nets. In *Advances in Neural Information Processing Systems*, pp. 2670–2680, 2017.

Gabriel Peyré, Marco Cuturi, et al. Computational optimal transport. Technical report, 2017.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. *ICLR*, 2016.

Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. In *NIPS*, 2016.

Konstantin Shmelkov, Thomas Lucas, Karteek Alahari, Cordelia Schmid, and Jakob Verbeek. Coverage and quality driven training of generative image models. 2018.

Akash Srivastava, Lazar Valkoz, Chris Russell, Michael U Gutmann, and Charles Sutton. Veegan: Reducing mode collapse in GANs using implicit variational learning. In *NIPS*, 2017.

Dustin Tran, Rajesh Ranganath, and David M Blei. Deep and hierarchical implicit models. *CoRR, abs/1702.08896*, 2017.

Chang Xiao, Peilin Zhong, and Changxi Zheng. Bourgan: Generative networks with metric embeddings. *arXiv preprint arXiv:1805.07674*, 2018.

Han Zhang, Ian Goodfellow, Dimitris Metaxas, and Augustus Odena. Self-attention generative adversarial networks. *arxiv 1805.08318*, 2018.

Ke Zhang, Wei-Lun Chao, Fei Sha, and Kristen Grauman. Video summarization with long short-term memory. In *ECCV*, 2016.

SUPPLEMENTARY MATERIAL

A   NETWORK ARCHITECTURES

The architectures of the generator and discriminator networks employed in our experiments are given in Figure 6.

Figure 6: (a) Architectures employed in the synthetic experiments. (b) Architectures employed in our image generation experiments.

A.1 Hyperparameters

In all of our experiments, we use Adam Optimizer with $\beta_1 = 0.5$ and $\epsilon = 1 \times 10^{-8}$. For the synthetic data experiments, we follow the configurations used by (Srivastava et al., 2017) and (Metz et al., 2017). We use 1×10^{-4} for the discriminator learning rate, and 1×10^{-3} for the generator learning rate. For synthetic data we use a batch size of 512. For Stacked-MNIST and CIFAR-10 we use a batch size of 64. For CIFAR-10, we use a batch size of 16.

For the Stacked MNIST, CIFAR-10 and CelebA datasets, we use 2×10^{-4} as the learning rate for both of the generator and the discriminator. To relatively stabilize the training of DCGAN, we follow the protocol in (Gulrajani et al., 2017) to train it by applying a learning rate scheduler. The decay is to happen with a ratio of $1/(\#max - iters)$ at every iteration.

B Synthetic Data Collections

The first data collection is introduced in (Metz et al., 2017) as a mixture of eight 2D Gaussian distributions arranged in a ring. This distribution is the easiest to mimic since it only requires the generated data to have an equal repulsion from the center of the distribution, even if it is not targeted to the modes. The second and third collections were introduced by (Srivastava et al., 2017). In the second collection, there is a mixture of twenty-five 2D Gaussian distributions arranged in a grid. Unlike the first collection, this one requires a more structured knowledge of the true data modes' locations. The last collection is a mixture of ten 700 dimensional Gaussian distributions embedded in a 1200 dimensional space. This mixture arrangement mimics the higher dimensional manifolds of natural images, and demonstrates the effectiveness of each method on manipulating sparse patterns.

C Additional results

Figure 7: GDPP-GAN with different random initializations. GDPP-GAN respects the structure of the true data distribution even with poor initializations. On the other extreme, WGAN-GP tends to map the generated data to a disperse distribution covering all the modes with lower quality samples.

	DCGAN	Unrolled-GAN	Reg-GAN	WGAN	WGAN-GP	GDPP-GAN
Avg. Iter. Time (s)	0.0674	0.2467	0.1357	0.1747	0.4331	**0.0746**

Table 5: Average Iteration time for each of the baseline methods on CIFAR-10. GDPP-GAN obtains the closest time to the original GAN. The table shows the average of 1000 iterations over five runs for each method.

Figure 8: Random Samples generated by GDPP-GAN on Stacked-MNIST after 15K iterations.

Figure 9: Random Samples generated by GDPP-VAE on Stacked-MNIST after 45K iterations.

Figure 10: Random Samples generated by GDPP-GAN after 100K iterations.

Figure 11: Fixed noise qualitative samples progression for different models.

(b) random samples using WGAN-GP at 200000 iterations

(c) random samples using our GDPP-GAN at 200000 iterations

Figure 12: Comparing the performance of our loss when compared to DCGAN and WGAN-GP loss, using Progressive-Growing GANs (Karras et al., 2017).