Approximate Value Equivalence

Abstract

Model-based reinforcement learning agents must make compromises about which aspects of the environment their models should capture. The value equivalence (VE) principle posits that these compromises should be made considering the model's eventual use in value-based planning. Given sets of functions and policies, a model is said to be order-k VE to the environment if k applications of the Bellman operators induced by the policies produce the correct result when applied to the functions. Prior work investigated the classes of models induced by VE when we vary k and the sets of policies and functions. This gives rise to a rich collection of topological relationships and conditions under which VE models are optimal for planning. Despite this effort, relatively little is known about the planning performance of models that fail to satisfy these conditions. This is due to the rigidity of the VE formalism, as classes of VE models are defined with respect to *exact* constraints on their Bellman operators. This limitation gets amplified by the fact that such constraints themselves may depend on functions that can only be approximated in practice. To address these problems we propose approximate value equivalence (AVE), which extends the VE formalism by replacing equalities with error tolerances. This extension allows us to show that AVE models with respect to one set of functions are also AVE with respect to any other set of functions if we tolerate a high enough error. We can then derive bounds on the performance of VE models with respect to *arbitrary sets of functions* by relating them to a particular model class with known performance guarantees. We support these results by providing intuitions and discussions of their implications.

1 Introduction

Reinforcement learning (RL) is a general framework in which an agent learns to maximize the reward it receives from its environment by interacting with it [Sutton and Barto, 2018]. Though RL makes no prescriptions about their internal processes, agents are commonly endowed with the ability to learn simulators of their environment, called *models*, which enable predicting the effects of sequences of actions without executing them in the environment. The subfield of RL which studies such agents is referred to as model-based reinforcement learning (MBRL).

In classical MBRL, agents endeavor to learn models that accurately capture the dynamics of their environments and subsequently use these models in their estimation of the values of different policies. Though having an accurate model is sufficient for this task, they are frequently impractical to learn— as MBRL agents are deployed in more complex environments, the demands of learning models which accurately capture these complexities become more severe. Fortunately, such models are not necessary for learning performant MBRL agents, as demonstrated by several recent works [Oh et al., 2017, Silver et al., 2017, Farquhar et al., 2018, Schrittwieser et al., 2020]. The agents in these works learn models that are accurate at what they are eventually used for: the estimation of policy values.

In particular, these models are learnt to be able to accurately predict the values of policies in the environment rather than to be able to accurately predict the environment's dynamics.

Grimm et al. [2020, 2021] provide a theoretical underpinning for models learned in this way by establishing the *value equivalence* (VE) principle. VE partitions the space of models an agent can learn into different VE classes according to properties of their Bellman operators. For a given integer k, an order-k VE class consists of models whose k-step Bellman operators of certain policies match the environment's when applied to certain functions. The policies and functions used as VE constraints are the identifiers of the equivalent classes. Accordingly, much of the prior work on value equivalence has concerned the selection of these sets such that the corresponding VE models are of use to an agent. In particular, Grimm et al. [2021] proved that any model in the infinite-order VE—also known as *proper value equivalent* or PVE—class induced by all deterministic policies is sufficient for optimal planning. However, with the exception of this specific model class, the analyses by Grimm et al. [2020, 2021] offer no bounds on the performance of more general VE classes.

In this work we extend the VE framework by developing an approximate theory of value equivalence which augments VE classes with an error tolerance parameter that controls the degree to which models can violate their class' constraints (Definition 1). We call the resulting framework *approximate value equivalence* (AVE). We show that topological relationships exist between *arbitrary* pairs of AVE classes (Proposition 1). By leveraging these topological relationships, we extend the performance bound on the aforementioned PVE class to arbitrary AVE classes (Proposition 2). Initially, we present the bound in terms of generic topological relationship between an AVE class and the reference PVE class. We then conduct a quantitative analysis of how topological properties of an AVE class impact on the bound. To aid our analysis, we study these properties for different aspects of AVE classes in isolation: first we study the impact of the model class order (Section 4.1) and then we look at the impact of specific choices of function sets (Section 4.2). We then combine these results to obtain a general topological relationship between AVE classes as order and function sets vary (Section 4.3), which, due to the connection we showed between AVE topology and performance (Proposition 2), directly translates into a bound on the performance of models in AVE classes with arbitrary orders and function sets. This result extends the set of VE classes whose performance can be analyzed from the PVE class mentioned above to AVE classes with *arbitrary* orders and function sets.

2 Background

An agent's interaction with its environment is modeled using a Markov Decision Process (MDP) [Puterman, 1994] denoted by $\langle \mathcal{S}, \mathcal{A}, r, p, \gamma \rangle$, where $\mathcal{S}$ is a state-space, $\mathcal{A}$ is a set of actions that can be taken from each state, $r(s, a)$ is the expected reward of taking action a from state s, $p(s'|s, a)$ is the probability of transitioning to state s' when action a is taken from state s and $\gamma \in [0, 1]$ is a discount factor. The behavior of an agent is specified by a policy, $\pi : \mathcal{S} \mapsto \mathcal{P}(\mathcal{A})$, where $\mathcal{P}(\mathcal{A})$ is the set of probability distributions over $\mathcal{A}$. We denote the set of all policies as $\mathbb{\Pi}$ and the set of all functions of signature $\mathcal{S} \mapsto \mathbb{R}$ as $\mathbb{V}$. The performance of a policy in an MDP is measured by its value function:

$$v_\pi(s) \equiv \mathbb{E}_{\pi,p} \left[\sum_{t=0}^{\infty} \gamma^t r(S_t, A_t) | S_0 = s \right], \tag{1}$$

where $\mathbb{E}_{\pi,p}[\cdot]$ denotes expectation over trajectories generated by policy π in an MDP with transition dynamics given by p, and S_t and A_t are random variables for the state occupied and action taken by the agent at timestep t. We denote the set of all value functions in an environment as $\mathbb{V}_{\mathbb{\Pi}} = \{v_\pi : \pi \in \mathbb{\Pi}\}$.

An RL agent's goal is to find a policy with maximal value across all states [Sutton and Barto, 2018]. This process is typically carried out by alternating between computing the value of the agent's policy and improving it. Value functions can be computed iteratively using the policy's *Bellman operator*:

$$\mathcal{T}_\pi[v](s) \equiv \mathbb{E}_{A \sim \pi(\cdot|s), S' \sim p(\cdot|s,A)} \left[r(s, A) + \gamma v(S') \right], \tag{2}$$

which accepts a function $v \in \mathbb{V}$ and returns an updated function in also in $\mathbb{V}$. Repeated applications of a policy's Bellman operator are denoted by $\mathcal{T}_\pi^k$ and referred to as the policy's k-step Bellman operator. It is known that, in the limit, k-step Bellman operators converge to their corresponding value functions: $\lim_{k \to \infty} \mathcal{T}_\pi^k[v] = v_\pi \ \forall v \in \mathbb{V}$. In RL it is assumed that the agent does not have access to r and p, and thus $\mathcal{T}_\pi$ cannot be computed directly. MBRL addresses this problem by learning a model, $\tilde{m} \equiv (\tilde{r}, \tilde{p})$, that is used in place of the environment's reward and transition dynamics to construct model Bellman operators, denoted $\tilde{\mathcal{T}}_\pi$.

Traditional MBRL methods attempt to learn models such that $\tilde{r} \approx r$ and $\tilde{p} \approx p$ [Sutton, 1991]. In contrast, there are alternative paradigms in which a model is learned with its eventual use in mind such as value-aware model learning (VAML; [Farahmand et al., 2017]) and the value equivalence (VE) principle [Grimm et al., 2020]. This work concerns the VE principle, under which models are learned to support their eventual use in estimating value functions. Accordingly, VE delineates models according to *VE constraints*, each of which require, for a specific k, policy $\pi \in \mathbb{\Pi}$ and function $v \in \mathbb{V}$, that $\tilde{\mathcal{T}}_\pi^k v = \mathcal{T}_\pi^k v$. We denote the class of order-k VE models with respect to a set of policies $\Pi \subseteq \mathbb{\Pi}$ and a set of functions $\mathcal{V} \subseteq \mathbb{V}$ as

$$\mathcal{M}^k(\Pi, \mathcal{V}) \equiv \{\tilde{m} \in \mathcal{M} : \tilde{\mathcal{T}}_\pi^k v = \mathcal{T}_\pi^k v \ \forall \pi \in \Pi, v \in \mathcal{V}\}. \tag{3}$$

In the limit of $k \to \infty$, Grimm et al. [2021] showed that order-k VE classes converge to special model classes whose value functions $\tilde{v}_\pi = \lim_{k \to \infty} \tilde{\mathcal{T}}_\pi^k v$ match those of the environment:

$$\mathcal{M}^\infty(\Pi) \equiv \{\tilde{m} \in \mathcal{M} : \tilde{v}_\pi = v_\pi \ \forall \pi \in \Pi\}. \tag{4}$$

These limiting model classes are referred to as *proper value equivalent (PVE)* due to their dependence on model and environment *value functions*. The PVE class with respect to all deterministic policies, denoted $\mathcal{M}^\infty(\mathbb{\Pi}_{\mathrm{det}})$, contains only models which can plan optimally. Notably, this is the only model class within the VE framework with such a performance guarantee [Grimm et al., 2021].

3 Approximate value equivalence

We begin our treatment of the approximate theory of value equivalence by extending the definitions of order-k VE and PVE classes given in Eqs. 3 and 4 to the approximate setting. Recall that the exact versions of these model classes are characterized by sets of policies and functions which induce a set of VE constraints on the model's Bellman operators. In this work we will consider model classes whose models can violate these constraints up to some limited degree, $\epsilon \geq 0$. We say that these *approximate value equivalent (AVE)* classes *tolerate* ϵ error.

Definition 1. *(Approximate Value Equivalence) Given $\Pi \subseteq \mathbb{\Pi}$, $\mathcal{V} \in \mathbb{V}$ and $\epsilon \in \mathbb{R}$, we denote the set of order-k AVE models which tolerate ϵ error as:*

$$\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon) = \{\tilde{m} \in \mathcal{M} : \|\tilde{\mathcal{T}}_\pi^k v - \mathcal{T}_\pi^k v\| \leq \epsilon \ \forall \pi \in \Pi, \forall v \in \mathcal{V}\} \tag{5}$$

where $\|\cdot\|$ denotes the ℓ_∞-norm.

Moreover, we can analogously define approximate proper value equivalent (APVE) classes as follows:

$$\mathcal{M}^\infty(\Pi; \epsilon) = \{\tilde{m} \in \mathcal{M} : \|\tilde{v}_\pi - v_\pi\| \leq \epsilon \ \forall \pi \in \Pi\}. \tag{6}$$

3.1 Topological properties

In what follows we investigate the topological properties of AVE classes, ultimately showing that, by introducing approximation to VE, we can relate *arbitrary* model classes. An order-k VE class is specified in terms of four quantities: a model class $\mathcal{M}$, a set of policies Π, a set of functions $\mathcal{V}$, and an order k. Grimm et al. [2020] illustrated a variety of topological properties of order-1 VE classes by studying the effect of varying $\mathcal{M}$, Π and $\mathcal{V}$. These results were later extended by Grimm et al. [2021], who also investigated the effect of varying the order k. We now conduct a similar analysis of AVE classes, which are extensions of VE classes that depend on a fifth quantity: an error tolerance ϵ. We start by showing that AVE models are a strict generalization of VE models, which become a special case when $\epsilon = 0$:

Property 1. *For any $\Pi \subseteq \mathbb{\Pi}$, $\mathcal{V} \in \mathbb{V}$ and $\mathcal{M} \subseteq \mathbb{M}$, it follows that $\mathcal{M}^k(\Pi, \mathcal{V}; 0) = \mathcal{M}^k(\Pi, \mathcal{V})$ and $\mathcal{M}^\infty(\Pi; 0) = \mathcal{M}^\infty(\Pi)$.*

Proofs of these properties will be deferred to Appendix A.1. Since Property 1 tells us that AVE is a generalization of exact VE, it is natural to inspect which other topological properties carry over.

Property 2. *For any $\epsilon \geq 0$, $\mathcal{M} \subseteq \bar{\mathcal{M}} \subseteq \mathbb{M}$, $\Pi \subseteq \Pi' \subseteq \mathbb{\Pi}$ and $\mathcal{V} \subseteq \mathcal{V}' \subseteq \mathbb{V}$, it follows that*

$$\mathcal{M}^k(\Pi', \mathcal{V}'; \epsilon) \subseteq \mathcal{M}^k(\Pi, \mathcal{V}; \epsilon) \subseteq \bar{\mathcal{M}}^k(\Pi, \mathcal{V}; \epsilon). \tag{7}$$

129 Property 2 generalizes two of the topological properties described by Grimm et al. [2020] to AVE. In
130 particular, the first subset relation in Eq. 7 shows that, like with VE, as the sizes of the sets of policies
131 and functions increase, the corresponding AVE class shrinks. The second relation shows that as the
132 set of models $\mathcal{M}$ increases in size, so too do AVE classes.

133 We now investigate the effect of the new parameter, the error tolerance ϵ, on the topology of the
134 resulting AVE classes:

135 **Property 3.** *For any $\Pi \subseteq \mathbb{\Pi}$, $\mathcal{V} \subseteq \mathbb{V}$ and $\epsilon' \geq \epsilon \geq 0$, it follows that*

$$\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon) \subseteq \mathcal{M}^k(\Pi, \mathcal{V}; \epsilon'). \tag{8}$$

136 Property 3 shows that increasing the tolerated error of an AVE class causes it to include more models.
137 While this is intuitive from our parlance (e.g., "a model class that tolerates a higher error also tolerates
138 a lower error"), it may be less obvious that this property can be used to relate AVE classes with
139 respect to arbitrary orders and sets of functions and policies.

140 **Proposition 1.** *For any $\epsilon \geq 0$, $\Pi, \Pi' \subseteq \mathbb{\Pi}$, $\mathcal{V}, \mathcal{V}' \subseteq \mathbb{V}$ and $k, K \in \mathbb{Z}^+$ there exists some $\epsilon' \geq 0$ such*
141 *that*

$$\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon) \subseteq \mathcal{M}^K(\Pi', \mathcal{V}'; \epsilon'). \tag{9}$$

142 Proposition 1 shows that it is possible to relate *arbitrary*
143 AVE classes. This is significantly broader than previous
144 topological results in which VE classes could be related
145 only when their corresponding sets of policies and func-
146 tions were subsets of each other (when $\Pi \subseteq \Pi'$ or $\mathcal{V} \subseteq \mathcal{V}'$)
147 [Grimm et al., 2020], or when the orders being compared
148 were multiples of each other (when k divided K) [Grimm
149 et al., 2021]. The proposition follows directly from taking
150 the limit of $\epsilon' \to \infty$ in Property 3: by tolerating a high
151 enough error *any AVE class can be made to contain any*
152 *other* (as illustrated in Figure 1).

153 Why is it important to ensure that one AVE class is a sub-
154 class of another? We know that, if a property applies to a
155 model class, it must also apply to any sub-class. Grimm
156 et al. [2021] have shown that all models in $\mathcal{M}^\infty(\mathbb{\Pi}_{\det}; 0)$
157 have the same optimal policy as the environment. They
158 also showed that, without further assumptions, this is the
159 "largest" model class with this property. Thus, up until
160 now, the best performance guarantees one could provide
161 regarding a model class were: "if the model class is a

Figure 1: An illustration of the impli-
cation of Proposition 1: as ϵ' increases
$\mathcal{M}^K(\Pi', \mathcal{V}'; \epsilon')$ grows— eventually to
the point of containing $\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon)$.

162 sub-class of $\mathcal{M}^\infty(\mathbb{\Pi}_{\det}; 0)$, any model in it yields an optimal policy; otherwise, there is nothing one
163 can say without making further assumptions."

164 Proposition 1 allows us to go much further and provide performance guarantees for *any* AVE class.
165 This is possible because we know we can relate arbitrary AVE classes of the form $\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon)$ to
166 $\mathcal{M}^\infty(\mathbb{\Pi}_{\det}; 0)$ by tolerating a sufficiently large amount of error ϵ'. Obviously, the tolerated error ϵ'
167 will play a role in the resulting performance guarantees. In general, the larger this error the weaker
168 the guarantees. So, we are interested in finding the minimum ϵ' that makes Proposition 1 true.

169 The minimum ϵ' for which Proposition 1 holds between any two AVE classes can also be thought of
170 as a function, which we will refer to as the *minimum tolerated error*.

171 **Definition 2.** *(Minimum Tolerated Error) For any AVE classes $\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon)$ and $\mathcal{M}^K(\Pi', \mathcal{V}'; \epsilon')$*
172 *we denote the minimum $\epsilon' \geq 0$ such that $\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon) \subseteq \mathcal{M}^K(\Pi, \mathcal{V}; \epsilon')$ as $\mathcal{E}_\epsilon(\Pi, \mathcal{V}, k | \Pi', \mathcal{V}', K)$.*

173 Note that the minimum tolerated error is well defined for any two AVE classes. Equipped with this
174 concept, we can now present the following result:

175 **Proposition 2.** *For any $\tilde{m} \in \mathcal{M}^k(\Pi, \mathcal{V}; \epsilon)$ it follows that*

$$\|v_{\tilde{\pi}_*} - v_*\| \leq 2 \cdot \mathcal{E}_\epsilon(\Pi, \mathcal{V}, k \,|\, \mathbb{\Pi}, \mathbb{V}, \infty),$$

176 *where $\mathbb{V}_{\mathbb{\Pi}}$ is the set of all value functions of the environment m and $\tilde{\pi}_*$ is any optimal policy of $\tilde{m}$.*

Proposition 2 assures us that we can bound the performance of any AVE class $\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon)$ in terms of the minimum error tolerance $\mathcal{E}_\epsilon(\Pi, \mathcal{V}, k \mid \mathbb{\Pi}, \mathbb{V}, \infty)$. Accordingly, understanding how this function varies with respect to its inputs is *crucial* to determining the performance of models in $\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon)$. It is worth emphasizing that $\mathcal{E}_\epsilon(\cdot|\cdot)$ is fundamentally a function concerned with the topology of AVE classes and that Proposition 2 provides a link between such topological properties and the performance of the corresponding models. In what follows we will quantify $\mathcal{E}_\epsilon(\cdot|\cdot)$ by providing upper-bounds on it that shed light on how it behaves as its inputs are varied.

4 Bounding the minimum tolerated error

We are interested in studying how the function $\mathcal{E}_\epsilon(\Pi, \mathcal{V}, k | \Pi', \mathcal{V}', K)$ changes as we vary its parameters. To facilitate our analysis, we will begin by varying these inputs in pairs, focusing first on orders (k, K) and then on function sets $(\mathcal{V}, \mathcal{V}')$.[1] Later, we combine these results to obtain a general upper bound for $\mathcal{E}_\epsilon(\cdot|\cdot)$, which will in turn yield a generic performance bound for any AVE class.

4.1 Model class order and error tolerance

In this section we consider pairs of model classes that share a common set of policies Π and functions $\mathcal{V}$, but have different orders k and K. In particular, we explore this dependence in the special case in which k divides K and that $\mathcal{V}$ is closed under environment Bellman updates with respect to any of the policies in Π.

Proposition 3. *For any $\epsilon \in \mathbb{R}$, $\Pi \subseteq \mathbb{\Pi}$, $\mathcal{V} \subseteq \mathbb{V}$ such that $v \in \mathcal{V} \implies \mathcal{T}_\pi v \in \mathcal{V} \ \forall \pi \in \Pi$ and $k, K \in \mathbb{Z}^+$ such that k divides K, we have that*

$$\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon) \subseteq \mathcal{M}^K(\Pi, \mathcal{V}; \tfrac{\epsilon \cdot (1-\gamma^K)}{1-\gamma^k}). \tag{10}$$

Proposition 3 shows that, in our special case, our upper-bound on the minimum tolerated error increases according to a multiplicative factor that depends on the orders k and K. For a fixed k, as K grows our upper-bound will also grow, however the rate of growth is decreasing since the numerator of this factor, $(1 - \gamma^K)$, approaches 1 as $K \to \infty$. The fact that our upper-bound does not grow without bound suggests that there is a similar relationship between order-k AVE and APVE classes. Indeed, by sending $K \to \infty$ we obtain such a relationship.

Corollary 1. *For any set of policies $\Pi \subseteq \mathbb{\Pi}$, set of functions $\mathcal{V} \in \mathbb{V}$ such that $\{v_\pi : \pi \in \Pi\} \subseteq \mathcal{V}$ and $k \in \mathbb{Z}^+$, it follows that*

$$\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon) \subseteq \mathcal{M}^\infty(\Pi; \tfrac{\epsilon}{1-\gamma^k}). \tag{11}$$

Notice in Corollary 1 how the constraint on $\mathcal{V}$ has been relaxed, since now it is no longer required that $\mathcal{V}$ be closed under arbitrary compositions of the Bellman operators of the policies in Π. Instead, $\mathcal{V}$ must contain the value functions associated with Π. This looser constraint implies that $\mathcal{V}$ can be finite when Π is finite, which in turn reflects the fact that PVE and APVE classes do not depend on a set of functions $\mathcal{V}$.

4.2 Function sets and error tolerance

In this section we consider two AVE classes with the same order k and set of policies Π but different function sets, that is, we compare $\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon)$ and $\mathcal{M}^k(\Pi, \mathcal{V}'; \epsilon')$. Though we are able to provide an upper-bound on the minimum tolerated error for arbitrary function sets, it can be shown to scale differently when there is special relation between $\mathcal{V}$ and $\mathcal{V}'$. We begin by examining this special case.

4.2.1 Related function sets

We begin by examining the case in which $\mathcal{V}'$ consists of constrained linear combinations of the elements of $\mathcal{V}$. In particular, we consider a set $\mathcal{V}'$ of the following form:

$$c\text{-vspan}(\mathcal{V}) \equiv \left\{ \sum_i \alpha_i v_i(s) : \ \forall \alpha_i \quad \sum_i \alpha_i = 1, \sum_i |\alpha_i| \leq c \right\}, \tag{12}$$

---

[1] Since in many scenarios the effect of the set of policies Π on the resulting VE class is easier to control [Grimm et al., 2020], in this paper we assume that $\Pi' = \Pi$.

which we refer to as the *constrained vspan of $\mathcal{V}$ with parameter c*. The coefficients of the linear combinations in c-vspan($\mathcal{V}$) are constrained to sum to 1 and to have magnitudes which sum to less than c.

Grimm et al. [2020] studied a special case of Eq. 12 without the coefficient magnitude constraint (by taking $c \to \infty$) and showed that $\mathcal{M}^1(\Pi, \mathcal{V}; 0) = \mathcal{M}^1(\Pi, \mathcal{V}'; 0)$ (where $\mathcal{V}' = \infty$-vspan($\mathcal{V}$)). Notice how, in the language of Proposition 1, we have just related two VE classes with different sets of functions $\mathcal{V}$ and $\mathcal{V}'$ without tolerating any additional error. However, this result is relatively narrow, only applying to exact order-1 VE classes. In what follows we extend this relationship to order-k AVE classes:

Proposition 4. *For any set of policies $\Pi \subseteq \mathbb{\Pi}$, set of functions $\mathcal{V} \in \mathbb{V}$, $c > 1$ and error $\epsilon \in \mathbb{R}$, we have*

$$\mathcal{M}^k(\Pi, c\text{-vspan}(\mathcal{V}); \epsilon) \subseteq \mathcal{M}^k(\Pi, \mathcal{V}; \epsilon) \subseteq \mathcal{M}^k(\Pi, c\text{-vspan}(\mathcal{V}); c \cdot \epsilon). \tag{13}$$

Proposition 4 shows how $\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon)$ is "squeezed" between two other model classes whose function sets are replaced by c-vspan($\mathcal{V}$). In particular, by considering the rightmost subset relationship in Eq. 13, we see that the error term scales multiplicatively with c. It is interesting to note that, for particular choices of ϵ and c, the left- and right-most terms in Eq. 13 can be made identical, reducing the expression to an equality.

Corollary 2. *When either $c = 1$ or $\epsilon = 0$, for any $\Pi \in \mathbb{\Pi}$, $\mathcal{V} \in \mathbb{V}$ it follows that*

$$\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon) = \mathcal{M}^k(\Pi, c\text{-vspan}(\mathcal{V}); \epsilon). \tag{14}$$

Note that, when $\epsilon = 0$, Corollary 2 recovers Grimm et al. [2020]'s result by sending $c \to \infty$. On the other hand, when $c = 1$, c-vspan($\mathcal{V}$) reduces to the convex hull of $\mathcal{V}$. In the context of Proposition 1, this means that, regardless of ϵ and k, we do not need to tolerate any additional error for $\mathcal{M}^k(\Pi, 1\text{-vspan}(\mathcal{V}); \epsilon)$ to contain $\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon)$.

4.2.2 Unrelated function sets

In the previous section we studied the case in which the set $\mathcal{V}'$ coincided with c-vspan($\mathcal{V}$); we now consider a more general scenario where $\mathcal{V}$ and $\mathcal{V}'$ are not assumed to have any relationship to each other. In this setting, we will measure the similarity of sets of functions using a distance function $\beta : 2^{\mathbb{V}} \times 2^{\mathbb{V}} \mapsto \mathbb{R}$ defined as

$$\beta(\mathcal{V}||\mathcal{V}') \equiv \max_{v' \in \mathcal{V}'} \min_{v \in \mathcal{V}} \|v - v'\|. \tag{15}$$

In words, β measures the distance between the farthest function in $\mathcal{V}'$ from any function in $\mathcal{V}$. Before we continue, it is worth pointing out some interesting properties of β.

Proposition 5.

  1. **(Asymmetry)** *For any $\mathcal{V} \subseteq \mathcal{V}' \subseteq \mathcal{V}'' \subseteq \mathbb{V}$ it follows that*

$$0 = \beta(\mathcal{V}||\mathcal{V}) \leq \beta(\mathcal{V}||\mathcal{V}') \leq \beta(\mathcal{V}||\mathcal{V}'') \quad and \quad 0 = \beta(\mathcal{V}''||\mathcal{V}'') \leq \beta(\mathcal{V}'||\mathcal{V}'') \leq \beta(\mathcal{V}||\mathcal{V}'').$$

  2. **(Convex, Compact $\mathcal{V}$)** *When $\mathcal{V}$ is convex and compact it follows that*

$$\beta(\mathcal{V}||\mathcal{V}') = \beta(\mathcal{V}||1\text{-vspan}(\mathcal{V}')).$$

Proposition 5 illustrates several interesting features of β. Firstly, it measures the similarity between sets $\mathcal{V}$ and $\mathcal{V}'$ asymmetrically: if $\mathcal{V}'$ grows then β also increases, since there are more elements to maximize over; however, if $\mathcal{V}$ grows, β *decreases* instead, since there are more elements to minimize over. Secondly, when $\mathcal{V}$ is a convex compact set, $\mathcal{V}'$ can be replaced with its convex-hull (equivalently, 1-vspan($\cdot$)) without changing β.

Using the similarity measure β, we can then determine the amount of error an AVE class with respect to $\mathcal{V}'$ must tolerate to contain a counterpart defined with respect to $\mathcal{V}$.

Proposition 6. *For any $\Pi \in \mathbb{\Pi}$, $\mathcal{V}, \mathcal{V}' \in \mathbb{V}$ and $\epsilon \geq 0$, it follows that*

$$\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon) \subseteq \mathcal{M}^k(\Pi, \mathcal{V}'; \epsilon + 2\gamma^k \beta(\mathcal{V}||\mathcal{V}')).$$

Moreover, if $\mathcal{V}$ is convex and compact, we obtain:

$$\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon) \subseteq \mathcal{M}^k(\Pi, 1\text{-vspan}(\mathcal{V}'); \epsilon + 2\gamma^k \beta(\mathcal{V}||\mathcal{V}')).$$

Proposition 6 shows that, for any two sets of functions $\mathcal{V}$ and $\mathcal{V}'$, the our upper-bound on the minimum tolerated error is proportional to $\beta(\mathcal{V}||\mathcal{V}')$, which we analyzed in Proposition 5. In particular, we know that our upper-bound increases as $\mathcal{V}'$ grows and decreases as $\mathcal{V}$ grows. In addition, in the special case in which $\mathcal{V}$ is a convex compact set, $\mathcal{V}'$ can be replaced by its convex hull without any increase in our upper-bound.

4.3 Unifying results

In the previous sections we studied upper-bounds on the minimum tolerated error such that models in particular kinds of AVE classes would be contained in other kinds of AVE classes. Each section concerned a different type of upper-bound constructed by varying certain aspects of the AVE classes: Section 4.1 held function sets fixed and varied model-class orders whereas Section 4.2 held model-class orders fixed and varied function sets. Now, we combine these results to obtain a more general theorem.

Theorem 1. *For any $\Pi \subseteq \mathbb{\Pi}$, $\mathcal{V} \subseteq \mathbb{V}$, $k \in \mathbb{Z}^+$, and $\epsilon \geq 0$ it follows that*

$$\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon) \subseteq \mathcal{M}^\infty(\Pi; \tfrac{1}{1-\gamma^k} \cdot \min_{c \geq 1}(c \cdot \epsilon + 2\gamma^k \beta(c\text{-vspan}(\mathcal{V})||\mathbb{V}_\mathbb{\Pi}))).$$

Proof. The proof follows by a sequential application of our previous results.

$$
\begin{aligned}
\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon) &\subseteq \mathcal{M}^k(\Pi, c\text{-vspan}(\mathcal{V}); c \cdot \epsilon) && \text{(Proposition 4)} \\
&\subseteq \mathcal{M}^k(\Pi, \mathbb{V}_\mathbb{\Pi}; c \cdot \epsilon + 2\gamma^k \beta(c\text{-vspan}(\mathcal{V})||\mathbb{V}_\mathbb{\Pi})) && \text{(Proposition 6)} \\
&= \bigcap_{\pi \in \Pi} \bigcap_{v_{\pi'} \in \mathbb{V}_\mathbb{\Pi}} \mathcal{M}^k(\{\pi\}, \{v_{\pi'}\}; c \cdot \epsilon + 2\gamma^k \beta(c\text{-vspan}(\mathcal{V})||\mathbb{V}_\mathbb{\Pi})) \\
&\subseteq \bigcap_{\pi \in \Pi} \mathcal{M}^k(\{\pi\}, \{v_\pi\}; c \cdot \epsilon + 2\gamma^k \beta(c\text{-vspan}(\mathcal{V})||\mathbb{V}_\mathbb{\Pi})) && (16) \\
&\subseteq \bigcap_{\pi \in \Pi} \mathcal{M}^\infty(\{\pi\}; \tfrac{1}{1-\gamma^k}(c \cdot \epsilon + 2\gamma^k \beta(c\text{-vspan}(\mathcal{V})||\mathbb{V}_\mathbb{\Pi}))) && \text{(Corollary 1)} \\
&= \mathcal{M}^\infty(\Pi; \tfrac{1}{1-\gamma^k}(c \cdot \epsilon + 2\gamma^k \beta(c\text{-vspan}(\mathcal{V})||\mathbb{V}_\mathbb{\Pi}))).
\end{aligned}
$$

Since Eq. 16 holds for all $c \geq 1$, it follows that:

$$\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon) \subseteq \mathcal{M}^\infty(\Pi; \tfrac{1}{1-\gamma^k} \cdot \min_{c \geq 1}(c \cdot \epsilon + 2\gamma^k \beta(c\text{-vspan}(\mathcal{V})||\mathbb{V}_\mathbb{\Pi}))),$$

as needed. $\square$

Theorem 1 reveals an interesting tension. Notice how the quantity inside the minimum is determined by two terms, $c \cdot \epsilon$ and $2\gamma^k \beta(c\text{-vspan}(\mathcal{V})||\mathcal{V}')$. As c grows, the first term increases; however, due to the properties of β described in Proposition 5, the second term will shrink.

5 Bounds on model performance

Propositions 1 and 2 form a powerful connection between the topology of AVE classes and model performance, which, in principle, allows us to quantify the performance of models in *any* AVE class $\mathcal{M}^k(\Pi, \mathcal{V}; \epsilon)$ with respect to the minimum tolerated error $\mathcal{E}_\epsilon(\Pi, \mathcal{V}, k|\mathbb{\Pi}, \mathbb{V}, \infty)$ (Definition 2). Although we know that the aforementioned minimum tolerated error *exists*, Proposition 1 does not specify *how* to quantify it. Accordingly, in Section 4 we produced topological results about AVE models when policy sets Π and either order or function sets are held fixed. We ultimately combined these results into Theorem 1, which we can use to obtain a general bound on the minimum tolerated error: $\mathcal{E}_\epsilon(\Pi, \mathcal{V}, k|\mathbb{\Pi}, \mathbb{V}, \infty)$.

By combining Theorem 1 with Proposition 2 we can obtain a performance bound on AVE classes with respect to arbitrary orders and function sets:

Theorem 2. *For any $\tilde{m} \in \mathcal{M}^k(\Pi, \mathcal{V}; \epsilon)$ it follows that*

$$\|v_* - v_{\tilde{\pi}_*}\| \leq \frac{2}{1-\gamma^k} \cdot \min_{c \geq 1} \left(c \cdot \epsilon + 2\gamma^k \beta(c\text{-vspan}(\mathcal{V})\|\mathbb{V}_\Pi)\right), \tag{17}$$

where $\tilde{\pi}_*$ is an optimal policy of $\tilde{m}$.

Theorem 2 suggests that ideal AVE classes have low error ϵ and function sets such that $c\text{-vspan}(\mathcal{V}) \supseteq$ $\mathbb{V}_\Pi$. However, in practice an agent does not directly have control over the error ϵ with which it learns a model. Rather, this error is dependent on the choice of $\mathcal{V}$: some functions may be harder to learn VE models with respect to than others. Since finding a model that is VE with respect to a small number of functions is generally easier, this dependence between ϵ and $\mathcal{V}$ introduces a tension in the selection of the set $\mathcal{V}$. The smaller the number of functions in $\mathcal{V}$, the smaller the resulting ϵ tends to be, but on the other hand the distance $\beta(c\text{-vspan}(\mathcal{V})\|\mathbb{V}_\Pi)$ generally increases.

One option for choosing $\mathcal{V}$, which was explored in both Grimm et al. [2020] and Grimm et al. [2021], is to use some manageable set of value functions: $\{v_{\pi_i}\}_{i=1}^n$. This is sensible as it is known that value functions form a polytope $\mathbb{V}_\Pi$ which could be covered by $c\text{-vspan}(\cdot)$ [Dadashi et al., 2019]. However, value functions are quantities of the environment which are not assumed to be known by the agent. At best, an agent can produce *estimates* of such quantities.

Interestingly, our AVE formalism can address not only the error in the satisfaction of VE constraints but also in the estimation of functions that the constraints depend upon. If an agent can estimate each v_{π_i} by $\hat{v}_{\pi_i}$ with bounded approximation error $\|v_{\pi_i} - \hat{v}_{\pi_i}\| \leq \epsilon_{\text{approx}}$, we have:

$$\begin{aligned}
\mathcal{M}^k(\Pi, \{\hat{v}_{\pi_i}\}_{i=1}^n; \epsilon) &\subseteq \mathcal{M}^k(\Pi, \{v_{\pi_i}\}_{i=1}^n; \epsilon + 2\gamma^k \beta(\{\hat{v}_{\pi_i}\}_{i=1}^n\|\{\hat{v}_{\pi_i}\}_{i=1}^n)) \\
&\subseteq \mathcal{M}^k(\Pi, \{v_{\pi_i}\}_{i=1}^n; \epsilon + 2\gamma^k \epsilon_{\text{approx}}).
\end{aligned} \tag{18}$$

Eq. 18 shows that we can *exchange* the estimation error of functions in VE function sets for error in the satisfaction of VE constraints. This ultimately means that we can bound the performance of models which are approximately VE with respect to functions that deviate from $\mathbb{V}_\Pi$:

Corollary 3. *Let $\hat{\mathbb{V}}_\Pi = \{\hat{v}_\pi : \pi \in \Pi\}$ be a set of approximate value functions satisfying $\|v_\pi - \hat{v}_\pi\| \leq$ ϵ_{approx} for all $\pi \in \Pi$. Then for any $\tilde{m} \in \mathcal{M}^k(\Pi, \hat{\mathbb{V}}_\Pi; \epsilon)$ it follows that:*

$$\|v_* - v_{\tilde{\pi}_*}\| \leq \frac{2(\epsilon + 2\gamma^k \epsilon_{approx})}{1 - \gamma^k},$$

where $\tilde{\pi}_*$ is any optimal policy in $\tilde{m}$.

6 Related work

Our work directly extends previous theoretical results on VE to the approximate setting. This naturally situates us closest to the works that originally explicated value equivalence and its higher order analogues [Grimm et al., 2020, 2021]. Our focus on exploring models whose Bellman operators behave approximately like those of the environment is also similar to works which studied approximate forms of policy and value iteration [Bertsekas and Tsitsiklis, 1995, Munos, 2005].

A closely related line of work is value-aware model learning (VAML, IterVAML, VaGraM) [Farahmand et al., 2017, Farahmand, 2018, Voelcker et al., 2021]). In VAML models are learned in order to minimize the discrepancy between their Bellman optimality operators and those of the environment. In practice, a family of functions is constructed and a model is learned to minimize the maximum discrepancy across this family. In IterVAML, instead of minimizing the worst case discrepancy across a family of functions, the functions are generated by the model during a value iteration procedure. In VaGraM, the authors consider a similar discrepancy-based loss as in VAML, but use a Taylor series approximation to avoid having loss terms involving the values of predicted future states. This ultimately gives rise to a squared-error loss between predicted and actual next states weighted by the gradients of a value function. VE and VAML can be seen as complementary: both concern models that are learned with their eventual use in mind, but VAML focuses on the associated optimization problems of finding such models whereas VE focuses on characterizing these models into classes.

There have also been several recent empirical works which explored concepts adjacent to VE. Farquhar et al. [2021] explored adding auxilliary terms to different model learning procedures

which encouraged the learned models' Bellman operators and value estimates to satisfy the Bellman equations (i.e., to be self-consistent). They show that there are circumstances in which this leads to better data-efficiency in practice. Another example is Nikishin et al. [2021], who study the problem of learning models whose Bellman optimality operators induce optimal policies in the environment. In the service of this, they propose using implicit differentiation [Christianson, 1994] to compute gradients from the model's optimality operator all the way to its optimal policy.

7 Conclusion and future work

We provided an approximate theory of value equivalence that extends the existing VE formalism [Grimm et al., 2020, 2021]. The main concept introduced was a family of AVE classes whose models can violate VE constraints up to a limited degree. We showed that, as a product of introducing approximation to VE, arbitrary AVE classes can be related to each other topologically. Moreover, we showed that, by relating them to specific VE classes for which there are performance guarantees, we can derive bounds on the performance of arbitrary AVE classes in terms of their topological properties. Motivated by this link between topology and performance bounds, we proceed to derive isolated topological relationships between AVE classes whose function sets, orders and error tolerances vary, which we then can combine to produce bounds which hold over AVE classes with respect to arbitrary orders, functions sets and error tolerances. This addresses a fundamental open question in the VE theory: how to provide performance guarantees for models that do not satisfy the VE constraints exactly. While it may be possible to derive topological relationships jointly and, in so doing, provide tighter performance bounds, we leave this for future work. We also believe that the performance bounds we have introduced might give rise to new algorithms that attempt to minimize them, either directly or indirectly.

References

Dimitri P Bertsekas and John N Tsitsiklis. Neuro-dynamic programming: an overview. In *Proceedings of 1995 34th IEEE conference on decision and control*, volume 1, pages 560–564. IEEE, 1995.

Bruce Christianson. Reverse accumulation and attractive fixed points. *Optimization Methods and Software*, 3(4):311–326, 1994.

Robert Dadashi, Adrien Ali Taiga, Nicolas Le Roux, Dale Schuurmans, and Marc G. Bellemare. The value function polytope in reinforcement learning. In *Proceedings of the International Conference on Machine Learning (ICML)*, volume 97, pages 1486–1495, 2019.

Amir-massoud Farahmand. Iterative value-aware model learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 9090–9101, 2018.

Amir-Massoud Farahmand, André Barreto, and Daniel Nikovski. Value-Aware Loss Function for Model-based Reinforcement Learning. In *Proceedings of the International Conference on Artificial Intelligence and Statistics (AISTATS)*, volume 54, pages 1486–1494, 2017.

G Farquhar, T Rocktäschel, M Igl, and S Whiteson. Treeqn and atreec: Differentiable tree-structured models for deep reinforcement learning. In *6th International Conference on Learning Representations, ICLR 2018-Conference Track Proceedings*, volume 6. ICLR, 2018.

Gregory Farquhar, Kate Baumli, Zita Marinho, Angelos Filos, Matteo Hessel, Hado Philip van Hasselt, and David Silver. Self-consistent models and values. In *NeurIPS*, 2021.

Christopher Grimm, Andre Barreto, Satinder Singh, and David Silver. The value equivalence principle for model-based reinforcement learning. *Advances in Neural Information Processing Systems*, 33, 2020.

Christopher Grimm, André Barreto, Greg Farquhar, David Silver, and Satinder Singh. Proper value equivalence. *Advances in Neural Information Processing Systems*, 34, 2021.

Rémi Munos. Error bounds for approximate value iteration. In *Proceedings of the National Conference on Artificial Intelligence*, volume 20, page 1006. Menlo Park, CA; Cambridge, MA; London; AAAI Press; MIT Press; 1999, 2005.

Evgenii Nikishin, Romina Abachi, Rishabh Agarwal, and Pierre-Luc Bacon. Control-oriented model-based reinforcement learning with implicit differentiation. *ArXiv*, abs/2106.03273, 2021.

Junhyuk Oh, Satinder Singh, and Honglak Lee. Value prediction network. In *Advances in Neural Information Processing Systems*, pages 6118–6128, 2017.

Martin L. Puterman. *Markov Decision Processes—Discrete Stochastic Dynamic Programming*. John Wiley & Sons, Inc., 1994.

Julian Schrittwieser, Ioannis Antonoglou, Thomas Hubert, Karen Simonyan, Laurent Sifre, Simon Schmitt, Arthur Guez, Edward Lockhart, Demis Hassabis, Thore Graepel, et al. Mastering atari, go, chess and shogi by planning with a learned model. *Nature*, 588(7839):604–609, 2020.

David Silver, Hado van Hasselt, Matteo Hessel, Tom Schaul, Arthur Guez, Tim Harley, Gabriel Dulac-Arnold, David Reichert, Neil Rabinowitz, Andre Barreto, et al. The predictron: End-to-end learning and planning. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pages 3191–3199. JMLR. org, 2017.

Richard S Sutton. Dyna, an integrated architecture for learning, planning, and reacting. *ACM Sigart Bulletin*, 2(4):160–163, 1991.

Richard S. Sutton and Andrew G. Barto. *Reinforcement Learning: An Introduction*. MIT Press, 2018. URL `https://mitpress.mit.edu/books/reinforcement-learning-second-edition`. 2nd edition.

Claas A Voelcker, Victor Liao, Animesh Garg, and Amir-massoud Farahmand. Value gradient weighted model-based reinforcement learning. In *International Conference on Learning Representations*, 2021.