Distributed Saddle-Point Problems Under Similarity

Abstract

We study solution methods for (strongly-)convex-(strongly)-concave Saddle-Point Problems (SPPs) over networks of two type–master/workers (thus centralized) architectures and meshed (thus decentralized) networks. The local functions at each node are assumed to be *similar*, due to statistical data similarity or otherwise. We establish lower complexity bounds for a fairly general class of algorithms solving the SPP. We show that a given suboptimality $\epsilon > 0$ is achieved over master/workers networks in $\Omega\big(\Delta \cdot \delta/\mu \cdot \log(1/\varepsilon)\big)$ rounds of communications, where $\delta > 0$ measures the degree of similarity of the local functions, μ is their strong convexity constant, and Δ is the diameter of the network. The lower communication complexity bound over meshed networks reads $\Omega\big(1/\sqrt{\rho} \cdot \delta/\mu \cdot \log(1/\varepsilon)\big)$, where ρ is the (normalized) eigengap of the gossip matrix used for the communication between neighbouring nodes. We then propose algorithms matching the lower bounds over either types of networks (up to log-factors). We assess the effectiveness of the proposed algorithms on a robust logistic regression problem.

1 Introduction

We study smooth (strongly-)convex-(strongly-)concave SPPs over a network of M agents:

$$\min_{x \in X} \max_{y \in Y} f(x,y) := \frac{1}{M} \sum_{m=1}^{M} f_m(x,y), \tag{P}$$

where $X, Y \subseteq \mathbb{R}^d$ are convex and compact sets common to all the agents; and $f_m(x,y)$ is the loss function of agent m, known only to the agent. Problem (P) has found a wide range of applications, including, game theory [38, 8], image deconvolution problems [6], adversarial training [3, 10], and statistical learning [1]–see Sec. 2 for some motivating examples in the distributed setting. We are particularly interested in learning problems, where each f_m is the empirical risk that measures the mismatch between the model to be learned and the *local* dataset owned by agent m.

Since the functions f_m can be accessed only locally and routing local data to other agents is infeasible or highly inefficient, solving (P) calls for the design of distributed algorithms that alternate between a local computation procedure at each agent's side, and a round of communication among (suitably chosen) neighboring nodes. We address such a design considering explicitly two type of computational architectures, namely: **(i) master/workers** networks–these are centralized systems suitable for parallel computing; for instance, they are the typical computational architecture arising from federated learning applications (e.g., [15]), where data are split across multiple workers and computations are performed in parallel, coordinated by the master node(s); and **(ii) meshed networks**– these are distributed systems with no special topology (modeled just as undirected graphs), which capture scenarios wherein there is no hierarchical structure (e.g., master nodes) and each node can communicate only with its intermediate neighbors.

Function similarity: Motivated in particular by machine learning applications, our design and analysis pertain to distributed algorithms for SPPs (P) where the local functions f_m's are *related*–

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

quantities such as gradients and the second derivatives matrices of f_m's differ only by a finite quantity $\delta > 0$; we will term such SPPs as δ-related SPPs. For instance, this is the typical situation in the aforementioned distributed empirical risk minimization setting [2, 11, 43]: when data are i.i.d. among machines, the f_m's reflect statistical similarities in the data residing at different nodes, resulting in a $\delta = \tilde{O}(1/\sqrt{n})$, where n is the local sample size ($\tilde{O}$ hides log-factors and dependence on d).

While SPPs have been extensively studied in the centralized setting (e.g., [8, 27, 16, 28, 4]) and more recently over meshed networks [20, 24, 19, 23, 34], we are not aware of any analysis or (distributed) algorithm that explicitly exploit function similarity to boost communication efficiency–either lower complexity bounds or upper bounds. On the other hand, recent works for sum-utility minimization problems over networks (e.g., [2, 36, 33, 41, 39, 9, 43, 11, 37, 17]) show that employing some form of statistical preconditioning in the algorithm design provably reduces communication complexity. Whether these improvements are possible/achievable for δ-related SSPs in the form (P) remains unclear. This paper provides a positive answer to the above open problem.

Major contributions: Our major results are summarized next. **(a) Lower complexity bounds:** Under mild structural assumptions on the algorithmic oracle (satisfied by a variety of methods), we establish lower complexity bounds for the δ-related SPP (P) with μ-strongly-convex-strongly -concave, L-smooth (twice-differentiable) local functions: an ε precision on the optimality gap over master/workers system is achieved in $\Omega\big(\Delta \cdot \delta/\mu \cdot \log(1/\varepsilon)\big)$ communication steps, where Δ is the diameter of the network. The lower complexity bound over meshed networks reads $\Omega\big(1/\sqrt{\rho} \cdot \delta/\mu \cdot \log(1/\varepsilon)\big)$ rounds of communications, where ρ is the (normalized) eigengap of the gossip matrix used for the communication between neighbouring nodes. These new lower bounds show a more favorable dependence on the optimization parameters (via δ/μ) than that of distributed oracles for SPPs ignoring function similarity [4, 34], whose communication complexity, e.g., over meshed networks reads $\Omega\big(1/\sqrt{\rho} \cdot L/\mu \cdot \log(1/\varepsilon)\big)$. The latter provides a pessimistic prediction when $\delta/\mu \ll L/\mu$. This is the typical situation of ill-conditioned problems, such as many learning problems where the regularization parameter that is optimal for test predictive performance is so small that a scaling with L/μ is no longer practical while δ/μ is (see, e.g., [22, 11]). **(b) Near optimal algorithms:** We proposed algorithms for such SPPs over master/workers and meshed networks that match the lower bounds up to logarithmic factors. They are provably faster than existing solution methods for μ-strongly-convex-strongly-concave, L-smooth SPPs, which do not exploit function similarity. Preliminary numerical results on distributed robust logistic regression support our theoretical findings.

1.1 Related works

Methods for SPPs ignoring function similarity: (Strongly)-convex-(strongly)-concave SPPs have been extensively studied in the optimization literature and as special instances of (strongly) monotone Variational Inequalities (VI) [8, 14]. Several algorithms are available in the **centralized** setting, some directly imported from the VI literature; representative examples include: the mirror-proximal algorithm [27], the extra-gradient methods [16] and the scheme in [28]–they are readily implementable on master/workers architectures as well. For SPPs with μ-strongly-convex-strongly-concave, L-smooth loss, all these schemes achieve iteration complexity of $O\big(L/\mu \cdot \log(1/\varepsilon)\big)$, which has been shown to be optimal for first-order methods solving such a class of SPPs [42, 32]. Lower bounds and optimal algorithms in the **distributed** setting for SPPs without similarity have been studied in [4].

Note that none of the above lower (and upper) complexity bounds or (centralized or distributed) algorithmic designs capture function similarity. As a consequence, convergence rates certified in the aforementioned works, when applicable to δ-related SPPs in the form (P), provide quite pessimistic predictions, in the setting $1 + \delta/\mu \ll L/\mu$.

Methods for sum-utility minimization exploiting function similarity: Several works exploited the idea of statistical preconditioning to provably improve communication complexity of solution methods for the minimization of the sum of δ-related, μ-strongly convex and L-smooth functions over master/workers networks. Lower complexity bounds are established in [2], and read $\Omega\big(\sqrt{\delta/\mu} \log(1/\varepsilon)\big)$, which contrasts with $O\big(\sqrt{L/\mu} \log(1/\varepsilon)\big)$ achievable by first-order (Nesterov) accelerated methods [29], certifying thus faster rates whenever $\delta/\mu < L/\mu$. Solutions methods exploiting function similarity are mirror proximal-like schemes, and include [36, 33, 41] (for quadratic losses), [43] (for self-concordant losses), [39], and [9] (for composite optimization), with [11] employing acceleration. None of these methods are implementable over meshed networks, because they rely on a centralized (master) node. To our knowledge, Network-DANE [17] and SONATA [37] are the

only two methods that leverage statistical similarity to enhance convergence of distributed methods over meshed networks; [17] studies strongly convex quadratic losses while [37] considers general objectives, achieving a communication complexity of $\widetilde{O}((1/\sqrt{\rho}) \cdot \beta/\mu \cdot \log(1/\varepsilon))$, where $\widetilde{O}$ hides logarithmic factors. None of the methods above however are applicable to the δ-related SPP (P).

1.2 Notation

Given a positive integer M, we define $[M] = \{1, \ldots, M\}$. We use $\langle x, y \rangle := \sum_{i=1}^{n} x_i y_i$ to denote standard inner product of $x, y \in \mathbb{R}^d$. It induces ℓ_2-norm in $\mathbb{R}^d$ in the following way $\|x\| := \sqrt{\langle x, x \rangle}$. We also introduce $\mathrm{proj}_{\mathcal{Z}}(z) = \min_{u \in \mathcal{Z}} \|u - z\|$ – the Euclidean projection onto $\mathcal{Z}$. We order the eigenvalues of any symmetrix matrix $A \in \mathcal{R}^{m \times m}$ in nonincreasing fashion, i.e., $\lambda_{\max}(A) = \lambda_1(A) \geq \ldots \geq \lambda_m(A) = \lambda_{\min}(A)$, with $\lambda_{\max}(\cdot)$ [resp. $\lambda_{\min}(\cdot)$] denoting the largest (resp. smallest) eigenvalue.

2 Setup and Background

Problem setting: We begin introducing the main assumptions underlying Problem (P) and some useful notation.

Let us stack the x- and y-variables in the tuple $z = (x, y)$; accordingly, define $\mathcal{Z} = \mathcal{X} \times \mathcal{Y}$ and the operators $F_m, F : \mathcal{Z} \to \mathcal{R}^{2d}$:

$$F_m(z) := \begin{pmatrix} \nabla_x f_m(x, y) \\ -\nabla_y f_m(x, y) \end{pmatrix}, \quad \text{and} \quad F(z) := \frac{1}{M} \sum_{m=1}^{M} F_m(z). \tag{1}$$

The following conditions are standard for strongly convex-strongly concave SPPs.

Assumption 1 *Given* (P)*, the following hold:*

   (i) $\emptyset \neq \mathcal{Z}$ is a convex and compact set;

   (ii) Each $f_m : \mathcal{R}^{2d} \to \mathcal{R}$ is twice differentiable on (an open set containing) $\mathcal{Z}$, with L-smooth gradient: $\|F_m(z_1) - F_m(z_2)\| \leq L\|z_1 - z_2\|$, for all $z_1, z_2 \in \mathcal{Z}$;

   (iii) $f(z)$ is μ-strongly convex-strongly concave on $\mathcal{Z}$, i.e., $\langle F(z_1) - F(z_2), z_1 - z_2 \rangle \geq \mu\|z_1 - z_2\|^2$, for all $z_1, z_2 \in \mathcal{Z}$;

   (iii) Each $f_m(z)$ is convex-concave on $\mathcal{Z}$, i.e. 0-strongly convex-strongly concave.

We are interested in studying Problem (P) under function similarity.

Assumption 2 (δ-related f_m's) *The local functions are δ-related: for all $(x, y) \in \mathcal{Z}$,*

$$\|\nabla_{xx}^2 f_m(x, y) - \nabla_{xx}^2 f(x, y)\| \leq \delta,$$
$$\|\nabla_{xy}^2 f_m(x, y) - \nabla_{xy}^2 f(x, y)\| \leq \delta,$$
$$\|\nabla_{yy}^2 f_m(x, y) - \nabla_{yy}^2 f(x, y)\| \leq \delta.$$

The interesting case is when $1 + \delta/\mu \ll L/\mu$. When the f_m's are empirical loss functions over local data sets of size n, under standard assumptions on data distributions and learning model (e.g., [43, 11]), $\delta = \tilde{O}(1/\sqrt{n})$ with high probability ($\tilde{O}$ hides log-factors and dependence on d)–some motivating examples falling in this category are discussed in Sec. 2.1 below. While such examples represent important applications, we point out that our (lower and upper) complexity bounds are valid in all scenarios wherein Assumption 2 holds due, not necessarily due to statistical arguments.

Network setting: The communication network is modeled as a fixed, connected, undirected graph, $\mathcal{G} \triangleq (\mathcal{V}, \mathcal{E})$, where $\mathcal{V} \triangleq \{1, \ldots, M\}$ denotes the vertex set–the set of agents–while $\mathcal{E} \triangleq \{(i, j) \mid i, j \in \mathcal{V}\}$ represents the set of edges–the communication links; $(i, j) \in \mathcal{E}$ iff there exists a communication link between agent i and j. We denote by Δ the diameter of the graph. When it comes to distributed algorithms over meshed networks, we leverage neighbouring communications among adjoining nodes. Communications of d-dimensional vectors will be modeled as a matrix multiplication by a matrix W (a.k.a. gossip matrix). The following assumptions on W are standard to establish convergence of distributed algorithms over meshed networks.

Assumption 3 *The matrix $W \in \mathcal{R}^{M \times M}$ satisfies the following: **(a)** It is compliant with $\mathcal{G}$, that is, (i) $w_{ii} > 0, \forall i \in [M]$; (ii) $w_{ij} > 0$, if $\{j, i\} \in \mathcal{G}$; and (iii) $w_{ij} = 0$ otherwise; **b** It is symmetric and stochastic, that is, $W1 = 1$ (and thus also $1^\top W = 1^\top$).*

Notice that a direct consequence of Assumption 3 (along with the fact that $\mathcal{G}$ is connected) is that

$$\rho \triangleq 1 - \max\{\lambda_2(W), |\lambda_{\min}(W)|\} < 1, \tag{2}$$

where ρ is the eigengap between the first and second largest (magnitude) eigenvalue of W. Roughly speaking, ρ measures how fast the network mixes information (the larger, the faster).

2.1 Motivating examples

Several problems of interest can be cast in the SPP (P), for which function similarity arises naturally, some are briefly discussed next.

Robust Regression: A first example is the robust instance of the linear regression problem in its Lagrangian form

$$\min_w \max_\rho \frac{1}{N} \sum_{n=1}^{N} (w^T(x_n + \rho) - y_n)^2 + \frac{\lambda}{2}\|w\|^2 - \frac{\beta}{2}\|\rho\|, \tag{3}$$

where w are the weights of the model, $\{(x_n, y_n)\}_{n=1}^N$ are pairs of the training data, and ρ models the noise, and λ and β are the regularization parameters. Let n be the local sample size (thus $N = nm$). The typical regularization parameter that is optimal for test predictive performance is $\lambda = O(1/\sqrt{N})$. Assuming β of the same order of λ and invoking function similarity $\delta = O(1/\sqrt{n})$ [22, 11] yield a condition number of the problem $\kappa = \mathcal{O}(\sqrt{m \cdot n})$ while $\beta/\mu = \mathcal{O}(\sqrt{m})$. This implies that first order methods applied to (3) will slowdown as the local sample size n grows. Rate scaling with δ/μ would be instead be independent on the local sample size.

Adversarial robustness of neural networks [21, 30]: Recent work has demonstrated that deep neural networks are vulnerable to adversarial examples—inputs that are almost indistinguishable from natural data and yet classified incorrectly by the network. To improve resistance to a variety of adversarial inputs, a widely studied approach is leveraging robust optimization and formulate the training as saddle-point problem:

$$\min_w \max_\rho \frac{1}{N} \sum_{n=1}^{N} l(f(w, x_n + \rho, y_n)^2 + \frac{\lambda}{2}\|w\|^2 - \frac{\beta}{2}\|\rho\|,$$

where w are the weights of the model, $\{(x_n, y_n)\}_{n=1}^N$ are pairs of the training data, ρ is the so-called adversarial noise, which introduces a perturbation in the data, and λ and β are the regularizers.

Other optimization problems: More generally, saddle-points reformulation are useful to cast optimization problems with constraints in their Lagrangian form, which may lead to more more favorable solution properties and efficient optimization algorithms [12, 13].

3 Lower Complexity Bounds

In this section we establish lower complexity bounds for centralized (i.e., master/workers-based) and distributed (gossip-based) algorithms. We begin introducing the back-box procedure describing the class of algorithms these lower bounds pertain to.

3.1 Optimization/communication oracle

Our procedure models a fairly general class of (centralized and distributed) algorithms over graphs, whereby nodes perform local computation and communication tasks. Computations at each node are based on linear operations involving current or past iterates, gradients, and vector products with local Hessians and their inverses, as well as solving local optimization problems involving such quantities. During communications, the nodes can share (compatibly with the graph topology) any of the vectors they have computed up until that time. The black-box procedure can be formally describe as follows.

Definition 1 *Each agent m has its own local memories $\mathcal{M}_m^x$ and $\mathcal{M}_m^y$ for the x- and y-variables, respectively–with initialization $\mathcal{M}_m^x = \mathcal{M}_m^y = \{0\}$. $\mathcal{M}_m^x$ and $\mathcal{M}_m^x$ are updated as follows.*

• *Local computation: Between communication rounds, each agent m computes and adds to its $\mathcal{M}_m^x$ and $\mathcal{M}_m^y$ a finite number of points x, y, each satisfying*

$$
\begin{aligned}
\alpha x + \beta \nabla_x f_m(x,y) \in span\big\{ & x' , \ \nabla_x f_m(x',y'), \\
& (\nabla_{xx}^2 f_m(x'',y'') + D)x' , \ (\nabla_{xx}^2 f_m(x'',y'') + D)\nabla_x f_m(x',y') \\
& (\nabla_{xx}^2 f_m(x'',y'') + D)^{-1}x' , \ (\nabla_{xx}^2 f_m(x'',y'') + D)^{-1}\nabla_x f_m(x',y'), \\
& (\nabla_{xy}^2 f_m(x'',y''))y' , \ (\nabla_{xy}^2 f_m(x'',y''))\nabla_y f_m(x',y')\big\}, \\
\theta y - \varphi \nabla_y f_m(x,y) \in span\big\{ & y' , \ \nabla_y f_m(x',y'), \\
& (\nabla_{yy}^2 f_m(x'',y'') + D)y' , \ (\nabla_{yy}^2 f_m(x'',y'') + D)\nabla_y f_m(x',y') \\
& (\nabla_{yy}^2 f_m(x'',y'') + D)^{-1}y' , \ (\nabla_{yy}^2 f_m(x'',y'') + D)^{-1}\nabla_y f_m(x',y'), \\
& (\nabla_{xy}^2 f_m(x'',y''))^T x' , \ (\nabla_{xy}^2 f_m(x'',y''))^T \nabla_x f_m(x',y')\big\},
\end{aligned}
\tag{4}
$$

for given $x', x'' \in \mathcal{M}_m^x$ and $y', y'' \in \mathcal{M}_m^y$; some $\alpha, \beta, \theta, \varphi \geq 0$ such that $\alpha + \beta > 0$ and $\theta + \varphi > 0$; and D is some diagonal matrix (such that all the inverse matrices exist).

• *Communication: Based upon communication rounds among neighbouring nodes, $\mathcal{M}_m^x$ and $\mathcal{M}_m^y$ are updated according to*

$$
\mathcal{M}_m^x := span\left\{ \bigcup_{(i,m)\in\mathcal{E}} \mathcal{M}_i^x \right\}, \quad \mathcal{M}_m^y := span\left\{ \bigcup_{(i,m)\in\mathcal{E}} \mathcal{M}_i^y \right\}.
\tag{5}
$$

• *Output: The final global output is calculated as:*

$$
x^K \in span\left\{ \bigcup_{m=1}^M \mathcal{M}_m^x \right\}, \quad y^K \in span\left\{ \bigcup_{m=1}^M \mathcal{M}_m^y \right\}.
$$

The above oracle captures a gamut of existing centralized and distributed algorithms. For instance, local computations model either inexact local solutions–e.g., based on single/multiple steps of gradient or Newton-like updates, which corresponds to setting $\alpha = \theta = 1$ and $\beta = \phi = 0$–or exact solutions of agents' subproblems (via some subroutine algorithm), corresponding to $\alpha = \theta = 0$ and $\beta = \phi = 1$. Multiple rounds of computations (resp. communications) can be performed between communication rounds (resp. computation tasks). Notice that the proposed oracle builds on [35, 2] for minimization problems over networks–the former modeling only gradient updates and the latter considering only centralized optimization (master/workers systems).

3.2 Lower complexity bounds

We are in the position to state our main results on communication complexity–Theorem 1 pertains to algorithms over master/workers systems while Theorem 2 deals with meshed networks.

Theorem 1 *For any $\mu \in [0;1)$, $\delta \in (0;1)$ and connected graph $\mathcal{G}$ with diameter $\Delta > 0$, there exist a SPP in the form (P) (satisfying Assumption 1) with $\mathcal{Z} = \mathcal{R}^{2d}$ (where d is sufficiently large), and local functions f_m being 1-smooth, μ-strongly-convex-strongly-concave, δ-related (Assumption 2) such that any centralized algorithm satisfying Definition 1 produces the following estimate on the global output $z^K = (x^K, y^K)$ after K communication rounds:*

$$
\|z^K - z^*\|^2 = \Omega\left(\exp\left(-\frac{K}{\Delta} \cdot \frac{1}{8 + \sqrt{16\delta^2 \left(\frac{1}{\mu} - 1\right)^2 + 1}} \right) \|y^*\|^2 \right).
$$

Corollary 1 *In the setting of Theorem 1, the number of communication rounds required to obtain a ε-solution is lower bounded by*

$$\Omega\left(\Delta\left(1+\frac{\delta}{\mu}\right)\cdot\log\left(\frac{\|y^*\|^2}{\varepsilon}\right)\right).$$ (6)

Theorem 2 *For any $\mu\in[0;1)$, $\delta\in(0;1)$ and $\rho\in(0;1]$, there exist a SPP in the form (P) (satisfying Assumption 1) with $\mathcal{Z}=\mathcal{R}^{2d}$(where d is sufficiently large), and local functions f_m being 1-smooth, μ-strongly-convex-strongly-concave, δ-related (Assumption 2), and a gossip matrix W over the connected graph $\mathcal{G}$, satisfying Assumption 3 and with eigengap ρ, such that any decentralized algorithm satisfying Definition 1 and using the gossip matrix W in the communication steps (5) produces the following estimate on the global output $z^K=(x^K,y^K)$ after K communication rounds:*

$$\|z^K-z^*\|^2=\Omega\left(\exp\left(-K\sqrt{\rho}\cdot\frac{1}{1+\sqrt{\frac{\delta^2}{4}\left(\frac{1}{\mu}-1\right)^2+\frac{1}{64}}}\right)\|y^*\|^2\right).$$

Corollary 2 *In the setting of Theorem 2, number of communication rounds required to obtain a ε-solution is lower bounded by*

$$\Omega\left(\frac{1}{\sqrt{\rho}}\left(1+\frac{\delta}{\mu}\right)\cdot\log\left(\frac{\|y^*\|^2}{\varepsilon}\right)\right).$$ (7)

These lower complexity bounds show an expected dependence on the optimization parameters and network quantities. Specifically, the number of communications scale proportionally to δ/μ–this generalizes existing lower bounds [4] that do not account for such similarity, resulting instead in the more pessimistic dependence on L/μ–typically $\delta\leq L$. The network impact is captured by the diameter Δ of the network for master/workers architectures–Δ communications steps are required in the worst case to transmit a message between two nodes–and the eigengap ρ of the matrix W, when arbitrary graph typologies are consider; $1/\sqrt{\rho}$ can be bounded as $\mathcal{O}(T)$, where T is the largest hitting time of the Markov chain with probability transition matrix W [31]. For instance, for fully connected networks $\Delta=1/\sqrt{\rho}=1$ while for star networks $\Delta=1$ and $1/\sqrt{\rho}=\sqrt{M}$. For general graphs, $1/\sqrt{\rho}$ can be larger than Δ, see [25] for more details. To certify the tightness of the derived lower bounds, the next section designs algorithms that reach such bounds.

4 Optimal algorithms

4.1 Centralized case (master/workers systems)

Our first optimal algorithm is for SPPs over master/workers architectures or more generally networked systems where a spanning tree (with the root as master node) is preliminary set; it is formally described in Algorithm 1. We assumed w.l.o.g. that the master node owns function f_1.

It is not difficult to check that Algorithm 1 is an instance of the oracle introduced in Definition 1. It accommodates either exact solutions of the strongly convex subproblems (8) (corresponding to $e=0$) or inexact ones (up to tolerance $e>0$)–the latter can be computed, e.g., using the extragradient method [14], which is optimal in this case.

The communication complexity of the method is proved in the next theorem, which certifies that the proposed algorithm is optimal, i.e., achieves the lower bound (6) on the number of required communications–we refer to Appendix B.1 in the supplementary material for a detailed description of the algorithmic tuning as well as a study of the computational complexity when the extragradient method is employed to solve subproblems (8) (up to a suitably chosen tolerance).

Theorem 3 *Consider Problem (P) under Assumptions 1-2 over a connected graph $\mathcal{G}$ with a master node. Let $\{z^k\}$ be the sequence generated by Algorithm 1 with tuning as described in Appendix B.1 (cf. the supplementary material). Then, given $\varepsilon>0$, the number of communication rounds for $\|z^k-z^*\|^2\leq\varepsilon$ is $\mathcal{O}\left((1+\delta/\mu)\log(1/\varepsilon)\right)$.*

Algorithm 1 (Star Min-Max Data Similarity Algorithm)

    Parameters: stepsize γ, accuracy e;

    Initialization: Choose $(x^0, y^0) = z^0 \in \mathcal{Z}$, $z_m^0 = z^0$, for all $m \in [M]$;

1: **for** $k = 0, 1, 2, \ldots$ **do**

2:     Each worker m computes $F_m(z^k)$ and sends it to the master;

3:     The master node:

  (i) computes $v^k = z^k - \gamma \cdot \left(F(z^k) - F_1(z^k) \right)$;

  (ii) finds u^k, s.t. $\|u^k - \hat{u}^k\|^2 \leq e$, where $\hat{u}^k$ is the solution of:

$$\min_{u_x \in \mathcal{X}} \max_{u_y \in \mathcal{Y}} \left[\gamma f_1(u_x, u_y) + \frac{1}{2}\|u_x - v_x^k\|^2 - \frac{1}{2}\|u_y - v_y^k\|^2 \right]; \tag{8}$$

  (iii) updates $z^{k+1} = \operatorname{proj}_{\mathcal{Z}} \left[u^k + \gamma \cdot (F(z^k) - F_1(z^k) - F(u^k) + F_1(u^k)) \right]$ and broadcasts z^{k+1} to the workers

4: **end for**

4.2 Distributed case (meshed networks)

We consider now meshed networks. Because of the lack of a master node, each agent m now owns local estimates u_m and v_m of the common variables u and v, respectively, which are iteratively updated. At each iteration, a node is selected uniformly at random, which plays the role of the master node, performing thus the update of its own local variables, followed by some rounds of communications via accelerated (inexact) gossip protocols [18, 40]–the latter being instrumental to propagate the updates of the u, v-variables and gradients across the network. The algorithm is formally introduced in Algorithm 2, with the accelerated gossip procedure described in Algorithm 3.

Algorithm 2 (Distributed Min-Max Data Similarity Algorithm)

    Parameters: stepsize γ, accuracy e, e_0, e_1, communication rounds H_0, H_1;

    Initialization: Choose $(x^0, y^0) = z^0 \in \mathcal{Z}$, $z_m^0 = z^0$, for all $m \in [M]$;

1: **for** $k = 0, 1, 2, \ldots$ **do**

2:     `Communications:` $\bar{F}_1^k, \ldots \bar{F}_M^k = \text{AccGossip}(F_1(z_1^k), \ldots F_M(z_M^k); H_0)$;

3:     `Local computations:` Choose an index $m_k \in [M]$ uniformly at random; then node m_k

  (i) compute $v_{m_k}^k = z_{m_k}^k - \gamma \cdot (\bar{F}_{m_k}^k - F_{m_k}(z_{m_k}^k))$;

  (ii) finds $u_{m_k}^k$, s.t. $\|u_{m_k}^k - \hat{u}_{m_k}^k\|^2 \leq e$, where $\hat{u}_{m_k}^k$ is the solution of:

$$\min_{u_x \in \mathcal{X}} \max_{u_y \in \mathcal{Y}} \left[\gamma f_{m_k}(u_x, u_y) + \frac{1}{2}\|u_x - v_{x,m_k}^k\|^2 - \frac{1}{2}\|u_y - v_{y,m_k}^k\|^2 \right]; \tag{9}$$

4:     `Communications:` Run accelerated gossip to propagate $\tilde{u}_{m_k}^k$ and update gradient variables:

$$u_1^k, \ldots u_M^k = M \cdot \text{AccGossip}(0, \ldots, 0, \tilde{u}_{m_k}^k, 0 \ldots, 0; H_1),$$
$$\bar{F}_1^{k+1/2}, \ldots \bar{F}_M^{k+1/2} = \text{AccGossip}(F_1(u_1^k), \ldots F_M(u_M^k); H_0);$$

5:     `Update of` z_{m_k}`-variable:` node m_k performs

$$z_{m_k}^{k+1} = \tilde{u}_{m_k}^k + \gamma \cdot (\bar{F}_{m_k}^k - F_{m_k}(z_{m_k}^k) - \bar{F}_{m_k}^{k+1/2} + F_{m_k}(\tilde{u}_{m_k}^k));$$

6:     `Communications:` Run accelerated gossip to propagate $z_{m_k}^{k+1}$:

$$\hat{z}_1^{k+1}, \ldots \hat{z}_M^{k+1} = M \cdot \text{AccGossip}(0 \ldots, 0, \tilde{z}_{m_k}^{k+1}, 0 \ldots, 0; H_1)$$

7:     Each worker update $z_i^{k+1} = \operatorname{proj}_{\mathcal{Z}} \left[\hat{z}_i^{k+1} \right]$;

8: **end for**

Algorithm 3 (AccGossip)

Input: $z_1, ..., z_M \in \mathcal{R}^{2d}$, and $H > 0$ (communication rounds);
Initialization: Construct matrix Z with rows $z_1^T, \ldots, z_M^T$;

$$\text{Set } Z^{-1} = Z, Z^0 = Z, \text{ and } \eta = \frac{1 - \sqrt{1 - \lambda_2^2(W)}}{1 + \sqrt{1 - \lambda_2^2(W)}}.$$

1:
2: **for** $t = 0, 1, 2, \ldots, H$ **do**
3: $\quad Z^{t+1} = (1 + \eta)W Z^{t+1} - \eta Z^{t-1}$,
4: **end for**
  Output: Rows of Z^{H+1}

Convergence of the method is established in Theorem 4 below–we refer to Appendix B.2 in the supplementary material for a detailed description of the algorithmic tuning [choice of the stepsize γ, precision e, numbers of communications rounds H_0, H_1, and algorithm to solve (8)].

Theorem 4 *Consider Problem* (P) *under Assumptions 1-2 over a connected graph $\mathcal{G}$. Let $\{(z_m^k)_{m \in [M]}\}$ be the sequence generated by Algorithm 2 with tuning as described in Appendix B.2 (cf. the supplementary material) and gossip matrix W satisfying Assumption 3. Then, given $\varepsilon > 0$, the number of communication rounds for $\|\bar{z}^k - z^*\|^2 \le \varepsilon$ reads $\tilde{\mathcal{O}}\left(1/\sqrt{\rho} \cdot \left(1 + \delta/\mu\right) \log^2 \frac{1}{\varepsilon}\right)$.*

While the algorithm achieves the lower bound (7), up to log-factors (which now however depends on ε as well), there is room for improvements. In fact, by selecting only one agent at time performing the updates, it does not fully exploit the potential computational speedup offered by the networking setting. Also, the use of gossip protocols to propagate the updates of a single agent across the entire network seems to be not very efficient. Designing alternative distributed algorithms overcoming these limitation is a challenging open problem.

5   Numerical Results

We simulate the Robust Linear Regression problem which is defined as

$$\min_{w} \max_{\|\rho\| \le R_\rho} \frac{1}{N} \sum_{n=1}^{N} (w^T(x_n + \rho) - y_n)^2 + \frac{\lambda}{2}\|w\|^2 - \frac{\beta}{2}\|\rho\|^2. \tag{10}$$

where w are the model weights, $\{x_n, y_n\}_{n=1}^N$ is the training dataset, and ρ is the artificially added noise; we use L2-regularization on both w and ρ. We solve the problem over a master/workers topology; we consider networks with 10 and 15 workers. Experiments over meshed networks can be found in the supplementary material. We test Algorithm 1 wherein the subproblems (8) at the master node are solved with high accuracy using the extragradient method [29]. A description of the tuning of the algorithm parameters can be found in the supplementary material. Our first experiment uses

Figure 1: Simulated data, 10 workers, ambient dimension = 15

synthetic, which allows us to control the factor δ, measuring statistical similarity of functions over different nodes. Specifically, we assume all local datasets of size $n = 100$. The data set $\{\hat{x}_i, \hat{y}_i\}_{i=1}^n$ at the master node is generated randomly, with each entry of $\hat{x}_i$ and $\hat{y}_i$, $i = 1, \ldots, n$ drawn from

Figure 2: Simulated data, 20 workers, ambient dimension $= 40$

the Standard Gaussian distribution. The datasets at the workers' sides, $i = 2, \ldots, M$, are obtained
perturbing $\{\hat{x}_i, \hat{y}_i\}_{i=1}^n$ by random noise ξ_i with controlled variance.

(a) a9a dataset

(b) w8a dataset

Figure 3

Figures 1 and 2 compare the performance of Algorithm 1 and the Extragradient method applied
directly to Problem (10), under different level of noise added to local datasets (level of similarity), and
two different problem and network dimensions–we plot the distance of the iterates from the solution
versus the number of communications. It can be seen that Algorithm 1 consistently outperforms the
Extragradient method in terms of number of communications–the smaller the noise (the more similar
the local functions are), the larger the gap between the two algorithm (in favor of Algorithm 1). On
the other hand, at high noise (amplitude 10.0) the performance of Extragradient and Algorithm 1
become comparable.

Our second experiment is using real data, specifically LIBSVM datasets [7]. In this scenario, we do
not use additional noise, but still can control the data similarity by choosing the number of workers.
The larger the number of workers, the less similar the local functions (less data at each node). Figure 3
compares Algorithm 1 and the Extragradient method: we plot the distance of the iterates from the
solution vs. the number of communications. Quite interesting, Algorithm 1 compares favorably even
when the number of workers becomes large.

References

[1] S.S. Abadeh, P.M. Esfahani, and D. Kuhn. Distributionally robust logistic regression. In *Advances in Neural Information Processing Systems (NeurIPS))*, pages 1576–1584, 2015.

[2] Yossi Arjevani and Ohad Shamir. Communication complexity of distributed convex learning and optimization. In *Proc. of the 28th International Conference on Neural Information Processing Systems (NIPS)*, volume 1, pages 1756–1764, December 2015.

[3] M. Arjovsky, S. Chintala, and L. Bottou. Wasserstein generative adversarial networks. *Proceedings of the 34th International Conference on Machine Learning (ICML)*, 70(1):214–223, 2017.

[4] Aleksandr Beznosikov, Valentin Samokhin, and Alexander Gasnikov. Distributed saddle-point problems: Lower bounds, optimal algorithms and federated gans. *arXiv preprint arXiv:2010.13112*, 2021.

[5] Stephen Boyd, Arpita Ghosh, Balaji Prabhakar, and Devavrat Shah. Randomized gossip algorithms. *IEEE transactions on information theory*, 52(6):2508–2530, 2006.

[6] Antonin Chambolle and Thomas Pock. A first-order primal-dual algorithm for convex problems with applications to imaging. *Journal of mathematical imaging and vision*, 40(1):120–145, 2011.

[7] Chih-Chung Chang and Chih-Jen Lin. Libsvm: a library for support vector machines. *ACM transactions on intelligent systems and technology (TIST)*, 2(3):1–27, 2011.

[8] F. Facchinei and J.S. Pang. *Finite-Dimensional Variational Inequalities and Complementarity Problems*. Springer Series in Operations Research and Financial Engineering. Springer New York, 2007.

[9] Jianqing Fan, Yongyi Guo, and Kaizheng Wang. Communication-efficient accurate statistical estimation. *arXiv:1906.04870*, 2019.

[10] I. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio. Generative adversarial nets. In *Advances in Neural Information Processing Systems (NeurIPS))*, pages 2672–2680, 2014.

[11] Hadrien Hendrikx, Lin Xiao, Sebastien Bubeck, Francis Bach, and Laurent Massoulie. Statistically preconditioned accelerated gradient method for distributed optimization. In *Proc. of the 37th International Conference on Machine Learning*, volume 119, pages 4203–4227, 13–18 Jul 2020.

[12] Arun Jambulapati, Aaron Sidford, and Kevin Tian. A direct tilde {O}(1/epsilon) iteration parallel algorithm for optimal transport. *Advances in Neural Information Processing Systems*, 32:11359–11370, 2019.

[13] Yujia Jin and Aaron Sidford. Efficiently solving mdps with stochastic mirror descent. In *International Conference on Machine Learning*, pages 4890–4900. PMLR, 2020.

[14] Anatoli Juditsky, Arkadii S. Nemirovskii, and Claire Tauvel. Solving variational inequalities with stochastic mirror-prox algorithm, 2008.

[15] Peter Kairouz, H Brendan McMahan, Brendan Avent, Aurélien Bellet, Mehdi Bennis, Arjun Nitin Bhagoji, Keith Bonawitz, Zachary Charles, Graham Cormode, Rachel Cummings, et al. Advances and open problems in federated learning. *arXiv preprint arXiv:1912.04977*, 2019.

[16] G. M. Korpelevich. The extragradient method for finding saddle points and other problems, 1976.

[17] Boyue Li, Shicong Cen, Yuxin Chen, and Yuejie Chi. Communication-efficient distributed optimization in networks with gradient tracking and variance reduction. *Journal of Machine Learning Research*, 21(180):151, Sept. 2020.

[18] Ji Liu and A Stephen Morse. Accelerated linear iterations for distributed averaging. *Annual Reviews in Control*, 35(2):160–165, 2011.

[19] Mingrui Liu, Wei Zhang, Youssef Mroueh, Xiaodong Cui, Jerret Ross, Tianbao Yang, and Payel Das. A decentralized parallel algorithm for training generative adversarial nets. *arXiv preprint arXiv:1910.12999*, 2019.

[20] Weijie Liu, Aryan Mokhtari, Asuman Ozdaglar, Sarath Pattathil, Zebang Shen, and Nenggan Zheng. A decentralized proximal point-type method for saddle point problems. *arXiv preprint arXiv:1910.14380*, 2019.

[21] Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

[22] Ulysse Marteau-Ferey, Francis Bach, and Alessandro Rudi. Globally convergent newton methods for ill-conditioned generalized self-concordant losses. In *Advances in Neural Information Processing Systems*, pages 7636–7646, 2019.

[23] David Mateos-Núñez and Jorge Cortés. Distributed subgradient methods for saddle-point problems. In *2015 54th IEEE Conference on Decision and Control (CDC)*, pages 5462–5467, 2015.

[24] Soham Mukherjee and Mrityunjoy Chakraborty. A decentralized algorithm for large scale min-max problems. In *2020 59th IEEE Conference on Decision and Control (CDC)*, pages 2967–2972, 2020.

[25] A. Nedić, A. Olshevsky, and M. G. Rabbat. Network topology and communication-computation tradeoffs in decentralized optimization. *Proceedings of the IEEE*, 106:953–976, 2018.

[26] Angelia Nedic and Asuman Ozdaglar. Distributed subgradient methods for multi-agent optimization. *IEEE Transactions on Automatic Control*, 54(1):48–61, 2009.

[27] Arkadi Nemirovski. Prox-method with rate of convergence o(1/t) for variational inequalities with lipschitz continuous monotone operators and smooth convex-concave saddle point problems. *SIAM Journal on Optimization*, 15:229–251, 01 2004.

[28] Yuri Nesterov. Dual extrapolation and its applications to solving variational inequalities and related problems. *Mathematical Programming*, 109(1-2):319–344, 2007.

[29] Yurii Nesterov. *Lectures on convex optimization*, volume 137. Springer, 2018.

[30] Maher Nouiehed, Maziar Sanjabi, Tianjian Huang, Jason D Lee, and Meisam Razaviyayn. Solving a class of non-convex min-max games using iterative first order methods. *arXiv preprint arXiv:1902.08297*, 2019.

[31] A. Olshevsky. Linear time average consensus on fixed graphs. In *3rd IFAC Workshop Distrib. Estimation Control Netw. Syst.*, 2015.

[32] Yuyuan Ouyang and Yangyang Xu. Lower complexity bounds of first-order methods for convex-concave bilinear saddle-point problems. *Mathematical Programming*, pages 1–35, 2019.

[33] Sashank J Reddi, Jakub Konečnỳ, Peter Richtárik, Barnabás Póczós, and Alex Smola. Aide: Fast and communication efficient distributed optimization. *arXiv preprint arXiv:1608.06879*, 2016.

[34] Alexander Rogozin, Alexander Beznosikov, Darina Dvinskikh, Dmitry Kovalev, Pavel Dvurechensky, and Alexander Gasnikov. Decentralized distributed optimization for saddle point problems. *arXiv preprint arXiv:2102.07758*, 2021.

[35] Kevin Scaman, Francis Bach, Sébastien Bubeck, Yin Tat Lee, and Laurent Massoulié. Optimal algorithms for smooth and strongly convex distributed optimization in networks. *arXiv preprint arXiv:1702.08704*, 2017.

[36] Ohad Shamir, Nati Srebro, and Tong Zhang. Communication-efficient distributed optimization using an approximate newton-type method. In *Proc. of the 31st International Conference on Machine Learning (PMLR)*, volume 32, pages 1000–1008, 2014.

[37] Y Sun, A Daneshmand, and G Scutari. Distributed optimization based on gradient-tracking revisited: Enhancing convergence rate via surrogation. *arXiv preprint arXiv:1905.02637*, 2019.

[38] J. von Neumann, O. Morgenstern, and H.W. Kuhn. *Theory of Games and Economic Behavior (commemorative edition)*. Princeton University Press, 2007.

[39] Shusen Wang, Farbod Roosta-Khorasani, Peng Xu, and Michael W. Mahoney. Giant: Globally improved approximate newton method for distributed optimization. In *Proc. of the 32nd 32nd International Conference on Neural Information Processing Systems*, volume 37, pages 2338–2348, 2018.

[40] Haishan Ye, Luo Luo, Ziang Zhou, and Tong Zhang. Multi-consensus decentralized accelerated gradient descent. *arXiv preprint arXiv:2005.00797*, 2020.

[41] Xiao-Tong Yuan and Ping Li. On convergence of distributed approximate newton methods: Globalization, sharper bounds and beyond. *arXiv preprint arXiv:1908.02246*, 2019.

[42] Junyu Zhang, Mingyi Hong, and Shuzhong Zhang. On lower iteration complexity bounds for the saddle point problems. *arXiv preprint arXiv:1912.07481*, 2019.

[43] Yuchen Zhang and Lin Xiao. Disco: Distributed optimization for self-concordant empirical loss. In *Proc. of the 32nd International Conference on Machine Learning (PMLR)*, volume 37, pages 362–370, 2015.