EvoCurr: Self-evolving Curriculum with Behavior Code Generation for Complex Decision-making

Abstract

Complex decision-making often requires agents to progress through intermediate tasks rather than solve the final target directly. Existing LLM self-refinement methods typically iterate on a fixed target, while curriculum-learning methods often rely on hand-designed schedules, training-time optimization, or domain-specific difficulty metrics. To smooth out the learning curve with adaptive curriculum desgin, we introduce EVOCURR, a general inference-time framework that co-evolves curricula and executable policies. A Designer proposes verifiable intermediate tasks from the latest accepted progress and recent failures, while a Solver generates or trains policies for these tasks. A task-policy pair is accepted only when it passes hard feasibility checks and reaches a specified performance threshold meanwhile an accepted-floor constraint preserves the latest verified checkpoint and prevents failed harder attempts from overwriting mastered behavior. We evaluate EVOCURR across code-as-policy and closed-loop MARL settings on StarCraft II super-late-game micromanagement, hardest stress test, where EVOCURR achieves 96.7–99.2% macro-average win rates across three LLM backbones without LLM parameter training. The performance improvments on other experiments, Flatland, POGEMA, Overcooked, and LiveCodeBench Hard, reflect the generality of our EvoCurr.

1 Introduction

Complex decision-making tasks are rarely solved by attempting the final objective in one step. Agents often need to master simpler subproblems, preserve the successful behaviors, and gradually extend them toward harder goals. Curriculum learning formalizes this intuition, but practical curricula are still difficult to deploy broadly, as many methods require hand-designed task sequences, training-time schedules, or domain-specific difficulty metrics (Bengio et al., 2009; Wang et al., 2021; Soviany et al., 2022). These assumptions are restrictive for LLM-based agents, which are increasingly expected to solve new tasks at inference time by code generation, interpreting feedback, and interacting with external environments.

Most LLM self-improvement methods also do not explicitly construct curricula. They usually keep the target fixed: the model generates a solution, observes feedback, and then revises another solution for the same final task (Shinn et al., 2023). Such fixed-target refinement can repair local errors, but it is often insufficient when the final hard task combines executable validity, long-horizon control, multi-agent coordination, and environment-specific constraints. In these settings, progress may require changing the task itself. The system should identify intermediate tasks that are solvable, verify the corresponding policies, and use them as stepping stones toward the final objective.

We propose EVOCURR, an inference-time framework for curriculum-policy co-evolution. Given a final task and an acceptance criterion, a Designer proposes the next curriculum task using the final target, the latest accepted progress, and the history of recent successes and failures. A Solver then generates or trains a policy for the proposed task. The candidate is accepted only if it is feasible and reaches the required score. During the evolution process, the easibility is enforced through hard checks such as task-schema validation, code compilation when applicable, and runtime execution. Meanwhile, the accepted-floor constraint enables EVOCURR advance only when a candidate task-policy pair is verified. The latest accepted checkpoint is preserved when the Solver fails a harder task. This separates productive exploration from policy regression and allows the system to search over task difficulty at inference time.

We use StarCraft II super-late-game micromanagement as the hardest stress test for this idea. As shown in Figure 2, this setting sits between SMAC-

Figure 1: EvoCurr overview. A curriculum designer proposes the next curriculum C_{t+1}; a solver produces an executable policy π_{t+1} and evaluates it; the outcome feeds back to the designer. The loop starts from a simplified version of the final target T_f and proceeds until T_f is solved.

style fixed skirmishes (Samvelyan et al., 2019a) and AlphaStar-scale full-game training (Vinyals et al., 2019): economy, scouting, and production are removed, but the remaining battle still requires coordinated control over large heterogeneous armies under simulator feedback. Recent LLM-based StarCraft agents show that language models can reason about strategies and write game-playing code, while also exposing weaknesses in late-game control, long-horizon planning, and policy interpretability (Ma et al., 2024). This makes the domain a compact test of whether an LLM can turn local tactical knowledge into one coherent executable controller.

Across 12 StarCraft II late-game micro tasks, EVOCURR evolves interpretable behavior-tree policies with no parameter training for the LLM Solver and achieves high final-task win rates, while direct generation, fixed-target self-reflection, and autonomous coding-agent baselines are much less reliable. We further evaluate the same Designer–Solver mechanism beyond games: Flatland railway scheduling (Mohanty et al., 2020), POGEMA cooperative pathfinding (Skrynnik et al., 2025) , Overcooked MARL (Carroll et al., 2020), and Live-CodeBench (Jain et al., 2025) Hard show positive transfer across code-as-policy and closed-loop training settings, while pandapipes (Lohmeier et al., 2020) and JSSP (Lee et al., 2024) clarify cases where curriculum adds little because a simpler feed-back loop or heuristic already saturates the task. These results support the method-level claim that self-evolving curricula help when direct final-task generation fails but meaningful, verifiable intermediate tasks exist.

Our contributions are fourfold: 1) We introduce EVOCURR, a general inference-time framework for co-evolving curricula and executable policies. 2) We propose an accepted-floor constraint that preserves verified progress while allowing failed harder tasks to guide future curriculum proposals. 3) We introduce a new StarCraft II super-late-game micromanagement benchmark that extends beyond SMAC-style skirmishes toward professional-level late-game control with large heterogeneous armies, diverse abilities, and terrain-dependent tactics. 4) We demonstrate the framework across code-as-policy and closed-loop MARL domains, using Star-Craft II as the hardest stress test and additional benchmarks to establish method-level generality.

2 Related Work

Curriculum Learning. (Bengio et al., 2009) formalized curriculum learning, demonstrating that training on examples organized from easy to hard improves generalization and convergence compared to random data shuffling. This paradigm has achieved success across computer vision, NLP, and reinforcement learning (Soviany et al., 2022; Wang et al., 2021). Various adaptive paradigms have been

explored to eliminate predefined schedules. Self-paced learning (SPL) automatically determines the learning pace based on sample difficulty (Kumar et al., 2010), which was further extended with diversity constraints (Jiang et al., 2015). In reinforcement learning (RL), adaptive curriculum generation has been framed via comprehensive task frameworks (Narvekar et al., 2020), inference-based optimizations (Klink et al., 2020), teacher-student networks (Matiisen et al., 2019), and prioritized level replays (Jiang et al., 2021). However, these approaches primarily focus on training phase optimization and require either manual curriculum design or domain-specific difficulty metrics, leaving a gap for inference-time adaptive curriculum generation.

Environment Generation. Procedural content generation has evolved toward learning-based approaches, such as POET's co-evolution (Wang et al., 2019) and PAIRED's adversarial training (Dennis et al., 2020) for generating challenging, solvable environments. Recent LLM-driven methods like EnvGen (Zala et al., 2024) and Rainbow Teaming (Samvelyan et al., 2024) adaptively create training scenarios based on world knowledge. Other works explore evolution strategies and transferable curricul (Parker-Holder et al., 2022). However, these approaches primarily generate static training data prior to agent learning, rather than dynamically adapting during inference based on the solver's immediate capabilities.

LLM Self-Refinement and Executable Reasoning. A growing line of work improves LLM outputs through iterative feedback, self-reflection, or execution traces. Reflexion-style methods (Shinn et al., 2023) revise a solution after observing errors, while code-generation benchmarks such as LiveCodeBench (Jain et al., 2025) emphasize contamination-controlled evaluation of executable programs. These approaches are complementary to EvoCurr but operate on a fixed target: each iteration still asks the model to solve the same full problem. EvoCurr instead changes the task distribution during inference, using accepted intermediate tasks as checkpoints so that feedback controls both policy repair and difficulty progression.

Executable Policy Generation. Games such as StarCraft II have become standard benchmarks for complex decision-making, established by PySC2 (Li et al., 2026) and AlphaStar (Vinyals et al., 2019). Recent LLM integration includes TextStarCraft II (Ma et al., 2024, 2025a,b; Li et al.,

2026) and behavior tree approaches (Deng et al., 2025, 2024). For code generation, Code as Policies (Liang et al., 2023) targets robot control, while behavior tree synthesis (Colledanchise and Ögren, 2018; Lykov and Tsetserukou, 2023) demonstrates that LLMs can produce structurally correct trees. These methods successfully generate executable policies but operate on fixed tasks without adaptive difficulty progression.

3 Method

EvoCurr frames inference-time policy generation as an iterative curriculum loop (Figure 1). Rather than asking the Solver to attempt the final target directly, a Designer proposes a sequence of progressively harder tasks; an *accepted floor* anchors progress to the most recently mastered task, preventing regression when a harder candidate fails.

3.1 Two-Agent Cooperative Framework

Let T_f be the final task and $\mathcal{H}_t$ the history of previous attempts. The *accepted floor* C_t^+ is the latest curriculum on which the Solver met the acceptance threshold τ. At round t, the Designer proposes a candidate task, the Solver generates a policy, and the environment returns a score:

$$
\begin{aligned}
\widehat{C}_{t+1} &= D(\mathcal{H}_t, C_t^+, T_f), \\
\pi_{t+1} &= S(\widehat{C}_{t+1}, \mathcal{H}_t), \\
s_{t+1} &= \mathcal{P}(\pi_{t+1}, \widehat{C}_{t+1}).
\end{aligned} \tag{1}
$$

Here D (the Designer) and S (the Solver) may be implemented by LLM prompting, code generation, or RL training depending on the domain; $\mathcal{P}$ is the task-specific score, such as SC2 win rate or Overcooked order completion.

Let $a_{t+1} \in \{0, 1\}$ be the accept flag for round $t + 1$. The candidate is accepted only if both the task and policy are executable and the score reaches the threshold:

$$
a_{t+1} = \mathbb{1}\Big[F_{\text{feas}}(\widehat{C}_{t+1}, \pi_{t+1}) = 1 \ \wedge \ s_{t+1} \geq \tau\Big]. \tag{2}
$$

Here F_{feas} is a hard validity check covering task-schema validation, code compilation, and at least one runtime execution. The accepted-floor update is then:

$$
C_{t+1}^+ = \begin{cases} \widehat{C}_{t+1}, & a_{t+1} = 1, \\ C_t^+, & a_{t+1} = 0. \end{cases} \tag{3}
$$

This is the main anti-regression mechanism. A failed harder task may inform the next Designer

prompt, but it never replaces the most recently mastered task. The Solver is restored to the accepted floor before the next proposal, so later attempts build from a known working checkpoint.

3.2 Curriculum Generation and Feasibility Constraints

A curriculum is a task configuration. In StarCraft II, for example, $C = (M, A, G)$ encodes the map, army specification , and goal; the Designer changes unit counts, unit types, abilities, and spawn regions to move from a simple fight toward T_f. In other domains, the same slot C denotes the corresponding problem instance: a railway layout in Flatland, a partially observable grid in POGEMA, an Overcooked layout and order schedule, or a code-generation subgoal.

The Designer is guided by a simple pacing rule rather than by a universal closed-form difficulty metric. After success, it proposes a task closer to T_f. After failure, it proposes an intermediate task that is harder than the accepted floor but easier than the failed candidate. This keeps progress monotone with respect to solved tasks while still allowing the curriculum to back off when the Solver is over-challenged.

Algorithm 1 EvoCurr Loop with Accepted-Floor Constraint

Require: Final task T_f, starting task C_0, threshold τ
1: **Objects:** D is the Designer, S is the Solver, $\mathcal{P}$ is the evaluator, and F_{feas} checks compile/runtime validity.
2: **State:** $\mathcal{H}_t$ stores tried candidates, policies, scores, and accept flags; C_t^+ is the accepted floor, i.e., the latest solved task.
3: **Variables:** $\widehat{C}_{t+1}$ is a candidate task, π_{t+1} is its policy, s_{t+1} is its score, and a_{t+1} is the accept flag.
4: Initialize history $\mathcal{H}_0 \leftarrow \emptyset$ and accepted floor $C_0^+ \leftarrow C_0$
5: **for** $t = 0, 1, 2, \ldots$ **do**
6:     *Designer proposes a candidate task*
7:     $\widehat{C}_{t+1} \leftarrow D(\mathcal{H}_t, C_t^+, T_f)$
8:     *Solver generates a policy for the candidate*
9:     $\pi_{t+1} \leftarrow S(\widehat{C}_{t+1}, \mathcal{H}_t)$
10:    *Evaluate and decide whether to accept*
11:    $s_{t+1} \leftarrow \mathcal{P}(\pi_{t+1}, \widehat{C}_{t+1})$
12:    $a_{t+1} \leftarrow \mathbb{1}[F_{\text{feas}}(\widehat{C}_{t+1}, \pi_{t+1}) = 1 \wedge s_{t+1} \geq \tau]$
13:    **if** $a_{t+1} = 1$ **then**
14:       $C_{t+1}^+ \leftarrow \widehat{C}_{t+1}$
15:    **else**
16:       $C_{t+1}^+ \leftarrow C_t^+$
17:       Restore Solver to checkpoint C_t^+
18:    **end if**
19:    $\mathcal{H}_{t+1} \leftarrow \mathcal{H}_t \cup \{(\widehat{C}_{t+1}, \pi_{t+1}, s_{t+1}, a_{t+1})\}$
20:    **if** $C_{t+1}^+ = T_f$ **then**
21:       **return** π_{t+1}
22:    **end if**
23: **end for**

The feasibility gate F_{feas} is a hard validity check, not a soft reward. It includes task-schema validation, constraint checking, code compilation when the Solver emits code, and at least one runtime execution. Invalid tasks and non-executable policies receive $a_{t+1} = 0$ even if their textual plan appears plausible.

3.3 Solver Implementation Across Domains

The Solver can instantiate $S(\cdot)$ in two ways. For open-loop code-as-policy tasks such as StarCraft II, Flatland, POGEMA, and LiveCodeBench, it generates executable programs. In StarCraft II these programs are behavior trees: the Solver first writes structured control code, then repairs syntax/runtime errors, and finally refines strategic failures using rollout feedback. For closed-loop domains such as Overcooked, $S(\cdot)$ is an RL trainer; π_{t+1} denotes the trained policy parameters after a fixed environment-step budget on $\widehat{C}_{t+1}$.

Thus the policy representation changes across domains, but the outer loop does not: propose a task, solve it, evaluate it, and update the accepted floor only after executable success.

4 Experiments

We evaluate EVOCURR across multiple domains, with StarCraft II micro-management as the flagship stress test. The Solver generates complete behavior-tree scripts for fixed-army late-game engagements, turning a traditionally closed-loop control problem into open-loop code-as-policy synthesis. Further details on the proposed StarCraft II super-late-game micromanagement benchmark, including its distinction from SMAC-style skirmishes and its scope relative to AlphaStar-scale full-game play, are provided in Appendix A. Overcooked (Carroll et al., 2020) then tests the same Designer–Solver loop in a closed-loop MARL setting, where the Solver trains neural policies that continuously adapt to observations.

After these two primary experiments, Section 5 broadens the evaluation to Flatland railway scheduling, POGEMA cooperative pathfinding, Live-CodeBench Hard code generation, and two boundary controls (pandapipes and JSSP). Across these settings, the policy representation changes, but F_{feas}, the accepted-floor constraint, and progressive task generation remain the same. Implementation details are in Appendices F and D.1.

Figure 2: Positioning EvoCurr against existing StarCraft II paradigms. (a) SMAC targets small-scale skirmishes with limited flexibility. (b) AlphaStar handles large-scale, full-game complexity but requires prohibitive training compute. (c) EvoCurr tackles complex, super-late-game micromanagement (50+ units) at inference time, achieving high-level coordination with zero parameter training cost.

4.1 StarCraft II Micro-Management

Experiment Setup The Solver generates `python-sc2` behavior trees that act at the unit-action level and is evaluated in an open-loop manner. To validate the framework's effectiveness across different architectures, we instantiate EvoCurr using three distinct LLM backbones: DeepSeek-V3.1, GPT-5, and Claude-4. We test on six newly designed micro maps against two opponent races (Terran vs Protoss and Terran vs Zerg). Each curriculum specifies unit sets, technologies, and spawn regions on a selected map; *compile-and-run* serves as a hard feasibility check in line with F_{feas}. The final target T_f for the canonical Terran vs Protoss and Terran vs Zerg settings is given in Tables 10 and 11 in Appendix D.3. For acceptance, we require $\mathcal{P}(\pi|C) \geq \tau = 0.9$, evaluated as win rate over 10 rollouts. The primary baseline, *Direct Code*, attempts to solve T_f in one shot under the same rollout and validation budgets as EvoCurr. Per-curriculum compositions and complete evolution traces are summarized in the appendix.

Statistical protocol. Statistical protocol. For direct baselines, we evaluate 10 independent target-task attempts per backbone to capture variability, executable rates, and peak performance. Conversely, an EvoCurr run spans a full curriculum-search trajectory with feasibility filtering and accepted-floor updates. We evaluate robustness via three views: final policy success over 10 game rollouts (Table 1), combat-score stability across backbones and attempts (Table 2), and direct-attempt distributions (Appendix B). Non-executable attempts score 0. The damage-cost-aware combat score $\mathcal{S}_{combat}$ is defined as:

$$\mathcal{S}_{combat} = 0.5 \cdot \frac{R_{\text{agent\_final}}}{R_{\text{agent\_init}}} + 0.5 \cdot \left(1 - \frac{R_{\text{enemy\_final}}}{R_{\text{enemy\_init}}}\right),$$
(4)

where $R_{\text{agent\_final}}$, $R_{\text{agent\_init}}$, $R_{\text{enemy\_final}}$, and $R_{\text{enemy\_init}}$ are instantiated from the following side-level combat-power function:

$$R_{\text{side}} = \sum_i (m_i + \alpha v_i + \beta b_i) \frac{h_i + s_i}{h_i^{\max} + s_i^{\max}}. \quad (5)$$

where m_i, v_i, and b_i denote the mineral cost, vespene gas cost, and supply cost of unit i, respectively, and α, β are balancing coefficients for resource normalization. The health ratio $\frac{h_i + s_i}{h_i^{\max} + s_i^{\max}}$ measures the remaining combat effectiveness of each unit based on current and maximum health/shield values.

This metric aggregates resource cost and remaining health/shields; scores range from 0 to 1. A combat score $\mathcal{S}_{combat} > 0.5$ indicates successful annihilation of the majority of enemy forces while

Table 1: Final-policy win rate (%) on StarCraft II micro tasks. Each selected policy is evaluated over 10 SC2 rollouts. This table provides the task-level success view; Table 2 reports the compact combat-score robustness summary.

Task	EvoCurr (DeepSeek)	EvoCurr (Claude)	EvoCurr (GPT)	DeepSeek-V3.1	GPT-5	Claude-4	Gemini-2.5	Claude_code	Codex	Cursor
bush (TVP)	**100**	**100**	**100**	0	0	10	0	0	0	0
corridor (TVP)	**100**	70	90	80	80	**100**	0	0	0	0
corner (TVP)	90	**100**	**100**	**100**	90	**100**	30	0	0	0
flat (TVP)	**100**	**100**	**100**	0	**100**	40	0	0	0	0
main (TVP)	**100**	**100**	**100**	100	100	**100**	100	0	0	0
ramp (TVP)	**100**	**100**	**100**	10	0	**100**	100	0	0	0
bush (TVZ)	**100**	90	**100**	100	0	**100**	0	40	0	0
corridor (TVZ)	**100**	**100**	90	90	0	**100**	100	0	0	0
corner (TVZ)	**100**	**100**	**100**	30	100	**100**	100	100	100	0
flat (TVZ)	**100**	**100**	90	0	0	0	0	0	0	0
main (TVZ)	**100**	**100**	**100**	100	0	0	100	10	20	0
ramp (TVZ)	**100**	**100**	**100**	50	60	**100**	0	20	0	0

preserving our own, providing a finer-grained assessment than binary win/loss especially for failed code executions where the first term becomes 0.

Experimental Results We evaluate 12 complex micro-management tasks (2 matchups × 6 maps) in Table 1. The selected EvoCurr policies reach high final-task win rates across the benchmark: 99.2% macro-average win rate for DeepSeek, 97.5% for GPT-5, and 96.7% for Claude-4. The combat-score statistics in Table 2 give the corresponding graded view: EvoCurr's curriculum-selected policies remain consistently strong across backbones, while direct generation is much less stable across its 10 one-shot attempts, even when its selected-best policy is competitive on some maps.

In contrast, Baseline performance varies by specialization. General LLMs (DeepSeek, GPT-5, Claude-4, Gemini-2.5) succeed on simpler layouts—often matching EvoCurr's 100% win rate on Main and Corner—but collapse to 0% on complex terrains like Bush and Flat (e.g., DeepSeek and GPT-5 on Bush (TvP)). Code-specialized agents (Claude Code, Codex, Cursor) also struggle despite code-synthesis optimizations. Except for Codex's 100% win rate on Corner (TvZ), they fail at strategic behavior-tree generation: Cursor scores 0% across all 12 tasks, and Claude Code fails most scenarios. Thus, while coding agents excel syntactically, they lack the strategic reasoning for open-loop policy design, a gap EvoCurr bridges through curriculum-driven evolution.

Scope and compute. EvoCurr targets a deliberately scoped fixed-army micro mini-game, not full StarCraft II: there is no economy, scouting, production, or build-order search. This scope makes the result complementary to AlphaStar-scale full-game training and substantially harder per engagement than SMAC-style small skirmishes. EvoCurr costs roughly $0.2–$1.5 in LLM API calls and 1–3 wall-clock hours per final SC2 task. Detailed scope comparison, compute accounting, and compute-matched iterative-baseline evidence are reported in Appendix A.

4.2 Overcooked

Experiment Setup We instantiate EvoCurr in a closed-loop Overcooked setting, with curricula parameterized by layouts, ingredient placements, and timing constraints. Unlike SC2, the Solver is a MARL trainer optimizing decentralized policies under a fixed $B = 10^7$ timestep budget per curriculum. Acceptance requires completing all mandatory orders ($\mathcal{P}(\pi|C) = 1$). The framework also yields greater rewards for fulfilling subsequent bonus orders (contributing to total deliveries in Table 3), isolating the impact of curriculum evolution from standard policy optimization. Detailed curriculum specifications and complete performance metrics for both map configurations are provided in Appendix G.

Experimental Results As shown in Table 3, EvoCurr outperforms direct E3T training under matched total environment-step budgets. On Coord. Ring with Multi-Recipe, EvoCurr achieves 29.10 effective deliveries on average versus 24.11 for direct training; on Counter Circuit with Multi-Recipe, EvoCurr reaches 18.64 versus 16.36 (Wang et al., 2024). The higher delivery counts include both required and bonus orders, showing that the progressive curriculum not only reaches the prescribed objectives but also enables more efficient exploration of bonus rewards. Performance drops at curriculum transitions reflect distribution shift: policies specialized to one curriculum must re-explore when

Table 2: Compact SC2 combat-score robustness summary. EVOCURR selected reports across-backbone mean ± std over three full curriculum-search outputs, one per backbone. Direct selected reports mean ± std over the best executable policy found by each of four direct backbones after 10 one-shot attempts. Direct all attempts pools all 40 one-shot attempts; non-executable attempts are counted as score 0. Full selected-score and direct-attempt tables are in the appendix.

Task	EVOCURR selected	Direct selected	Direct all attempts	Direct exec.
Bush (TvP)	0.677 ± 0.036	0.471 ± 0.100	0.167 ± 0.191	19/40
Corridor (TvP)	0.648 ± 0.058	0.557 ± 0.145	0.209 ± 0.220	22/40
Corner (TvP)	0.616 ± 0.057	0.636 ± 0.061	0.220 ± 0.252	20/40
Flat (TvP)	0.645 ± 0.048	0.434 ± 0.154	0.103 ± 0.188	10/40
Main (TvP)	0.684 ± 0.038	0.745 ± 0.076	0.239 ± 0.312	16/40
Ramp (TvP)	0.679 ± 0.044	0.651 ± 0.089	0.218 ± 0.273	17/40
Bush (TvZ)	0.683 ± 0.044	0.524 ± 0.153	0.163 ± 0.225	15/40
Corridor (TvZ)	0.641 ± 0.062	0.640 ± 0.066	0.173 ± 0.235	16/40
Corner (TvZ)	0.734 ± 0.110	0.698 ± 0.136	0.257 ± 0.318	17/40
Flat (TvZ)	0.590 ± 0.051	0.395 ± 0.104	0.113 ± 0.161	14/40
Main (TvZ)	0.738 ± 0.032	0.660 ± 0.103	0.283 ± 0.291	21/40
Ramp (TvZ)	0.702 ± 0.047	0.462 ± 0.152	0.173 ± 0.196	19/40

Table 3: Curriculum progression and performance metrics for Overcooked maps.

Map	Task	Orders	Agent0 Delivery	Agent1 Delivery	Total Delivery	Total Reward
Map 1	EvoCurr	5	14.74	14.36	29.10	290.9
Map 1	Direct Training	5	11.93	12.18	24.11	240.5
Map 2	EvoCurr	5	7.82	10.82	18.64	186.2
Map 2	Direct Training	5	7.40	8.96	16.36	163.4

difficulty increases, yet prior experience accelerates re-convergence, consistent with the monotone advancement prescribed by EvoCurr.

5 Cross-Domain Generality

Beyond StarCraft II, we evaluate EvoCurr across multi-agent pathfinding, operations research, closed-loop MARL, and code generation. We posit that autonomous curricula provide maximal leverage when a domain exposes a meaningful difficulty axis, executable feedback, and reusable intermediate solutions. Flatland and POGEMA illustrate this directly: despite distinct failure modes—direction-aware rail transitions in Flatland versus partially observable coordination in POGEMA—both benefit from evolutionary progression.

Flatland and POGEMA illustrate this most directly. Both are pathfinding domains with different failure modes: Flatland requires direction-aware rail transitions and train reservations, while POGEMA requires coordination under partial observations. In both cases, direct generation and fixed-target Reflexion remain at zero, whereas EVOCURR reaches non-trivial final-task performance across three seeds. The gain therefore comes not from additional iterations on the same prompt, but from changing the task distribution so that executable intermediate policies can be reused.

The other positive domains show that the mechanism is not tied to SC2 code-as-policy. In Overcooked, the accepted-floor curriculum improves total deliveries for a closed-loop MARL trainer under matched budgets. In LiveCodeBench Hard, securing runnable scaffolds before full hidden-test evaluation raises Pass@1 from 8/20 to 11/20.

However, boundary cases clarify EvoCurr's scope: it requires room for an acceptance ladder. In pandapipes, direct diagnostic feedback suffices, and in JSSP, a simple SPT-like heuristic already saturates the metric. Thus, EvoCurr excels when direct generation fails on the final task but verifiable intermediate steps exist.

6 Analysis

Why the Designer matters. The central ablation asks whether Solver-side self-correction alone can replace the Designer. It cannot. Reflection-enabled variants of the same LLM backbones still collapse on many final SC2 tasks, while EvoCurr raises those backbones to 90–100% win rates across al-

Table 4: Cross-domain final-target results. Higher is better. Direct denotes one-shot generation for code-as-policy tasks and direct E3T training for Overcooked. Fixed-target iteration denotes Reflexion-style self-correction on the final task when available. SC2 entries are macro-average win-rate ranges across backbones; Overcooked entries are Map 1 / Map 2 total deliveries.

Domain	Final-task structure	Metric	Direct	Fixed-target iteration	EVOCURR
StarCraft II	Heterogeneous fixed-army micro with terrain effects and 10+ active abilities	win rate	44.2–70.8%	10.0–41.7%	**96.7–99.2%**
Flatland	Direction-conditioned rail routing with multi-train reservations	completion	0.000	0.000 (20 gen.)	**0.710 ± 0.195**
POGEMA	Partially observable multi-agent pathfinding with time-indexed reservations	ISR	0.000	0.000 (20 gen.)	**0.693 ± 0.108**
Overcooked	Closed-loop coordination across staged layouts and order schedules	deliveries	24.11 / 16.36	–	**29.10 / 18.64**
LiveCodeBench Hard	Executable program synthesis under contest test constraints	Pass@1	8/20	8/20 (3 iter.)	**11/20**
pandapipes	Low-dimensional gas-network control with direct diagnostic feedback	feasibility	0.00	**1.00** (6 iter.)	0.33
JSSP	Dispatching benchmark where SPT already reaches the comparison ceiling	vs. SPT	1.00	$1.00 \rightarrow 0.91$	1.00

most all scenarios. This shows that the key gain is not merely code repair or extra attempts, but the accepted-floor curriculum that lets the Solver accumulate tactical skills without regressing. Full ablation tables are provided in Appendix B.

How policies evolve. Qualitatively, EvoCurr grows behavior-tree policies by preserving solved micro-skills and adding new unit-specific control functions as the curriculum becomes harder. Early scripts learn basic focus fire; later scripts add Ghost, Viking, Siege Tank, Raven, Medivac, and terrain-specific control, while refining existing functions for area-of-effect avoidance and target prioritization. Detailed generated code examples, curriculum trajectories, and layered-critic analysis are deferred to Appendix B and Appendix E.

7 Discussion, Future Work, and Conclusion

EvoCurr demonstrates that self-evolving curricula can extend frozen LLMs from local task knowledge to reliable executable policies without a handwritten curriculum sequence. The strongest narrative evidence comes from fixed-army StarCraft II super-late-game micro-management: EvoCurr solves a difficult middle ground between SMAC-scale skirmishes and AlphaStar-scale full-game training, while direct generation and autonomous coding agents fail. The additional experiments show that this is not merely a StarCraft II artifact. The same accepted-floor curriculum mechanism improves Flatland, POGEMA, Overcooked, and LiveCodeBench Hard, while pandapipes and JSSP mark cases where curriculum is unnecessary or the domain ceiling is already saturated.

Future Work Future directions include hierarchical Designer–Solver architectures for finer task decomposition, adaptive difficulty scaling based on acceptance patterns and solver feedback, and hybrid methods that distill interpretable behavior-tree policies into more reactive neural policies when closed-loop robustness is required.

Conclusion Overall, EvoCurr offers a general inference-time curriculum mechanism for structured executable reasoning. StarCraft II provides the central story and hardest stress test; the added OR, MARL, and NLP-code experiments show that the same mechanism transfers beyond games while exposing its limits.

Limitations Primary constraints include sensitivity to difficulty pacing, which may stall progress if the Designer proposes steps that are too small or too large, LLM context-window limits that restrict behavior-tree complexity in long-horizon scenarios,

and cumulative overhead from maintaining historical trajectories $\mathcal{H}_t$. The boundary controls also clarify scope: EvoCurr is most useful when direct LLM generation cannot self-bootstrap and the solution requires structured multi-step reasoning; it is less useful when Reflexion already solves the task or when a simple heuristic saturates the benchmark.

References

Yoshua Bengio, Jérôme Louradour, Ronan Collobert, and Jason Weston. 2009. Curriculum learning. In *International Conference on Machine Learning (ICML)*, pages 41–48.

Micah Carroll, Rohin Shah, Mark K. Ho, Thomas L. Griffiths, Sanjit A. Seshia, Pieter Abbeel, and Anca Dragan. 2020. On the utility of learning about humans for human-ai coordination. *Preprint*, arXiv:1910.05789.

Michele Colledanchise and Petter Ögren. 2018. *Behavior trees in robotics and AI: An introduction*. CRC Press.

Yue Deng, Weiyu Ma, Yuxin Fan, Ruyi Song, Yin Zhang, Haifeng Zhang, and Jian Zhao. 2025. Smac-r1: The emergence of intelligence in decision-making tasks. *Preprint*, arXiv:2410.16024.

Yue Deng, Yan Yu, Weiyu Ma, Zirui Wang, Wenhui Zhu, Jian Zhao, and Yin Zhang. 2024. Smac-hard: Enabling mixed opponent strategy script and self-play on smac. *Preprint*, arXiv:2412.17707.

Michael Dennis, Natasha Jaques, Eugene Vinitsky, Alexandre Bayen, Stuart Russell, Andrew Critch, and Sergey Levine. 2020. Emergent complexity and zero-shot transfer via unsupervised environment design. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 33, pages 13049–13061.

Naman Jain, Alex Gu, Wen-Ding Li, Fanjia Yan, Tianjun Zhang, Sida Wang, Armando Solar-Lezama, Koushik Sen, and Ion Stoica. 2025. Livecodebench: Holistic and contamination free evaluation of large language models for code. In *International Conference on Learning Representations*, volume 2025, pages 58791–58831.

Lu Jiang, Deyu Meng, Qian Zhao, Shiguang Shan, and Alexander G Hauptmann. 2015. Self-paced curriculum learning. In *AAAI conference on artificial intelligence (AAAI)*, volume 29.

Minqi Jiang, Edward Grefenstette, and Tim Rocktäschel. 2021. Prioritized level replay. In *International Conference on Machine Learning (ICML)*, pages 4940–4950.

Pascal Klink, Carlo D'Eramo, Jan Peters, and Joni Pajarinen. 2020. Self-paced deep reinforcement learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 33, pages 16185–16195.

M Pawan Kumar, Benjamin Packer, and Daphne Koller. 2010. Self-paced learning for latent variable models. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 1189–1197.

Jaejin Lee, Seho Kee, Mani Janakiram, and George Runger. 2024. Attention-based reinforcement learning for combinatorial optimization: Application to job shop scheduling problem. *arXiv preprint arXiv:2401.16580*.

Zongyuan Li, Yanan Ni, Runnan Qi, Chang Lu, Lumin Jiang, Xu Xiaojie, Xiangbei Liu, Pengfei Li, Yunzheng Guo, Zhe Ma, and 1 others. 2026. Llm-pysc2: Starcraft ii learning environment for large language models. *Advances in Neural Information Processing Systems*, 38:127595–127657.

Jacky Liang, Wenlong Huang, Fei Xia, Peng Xu, Karol Hausman, Brian Ichter, Pete Florence, and Andy Zeng. 2023. Code as policies: Language model programs for embodied control. In *IEEE International Conference on Robotics and Automation (ICRA)*, pages 9493–9500.

Daniel Lohmeier, Dennis Cronbach, Simon Ruben Drauz, Martin Braun, and Tanja Manuela Kneiske. 2020. Pandapipes: An open-source piping grid calculation package for multi-energy grid simulations. *Sustainability*, 12(23):9899.

Artem Lykov and Dzmitry Tsetserukou. 2023. Llm-brain: Ai-driven fast generation of robot behaviour tree based on large language model. *arXiv preprint arXiv:2305.19352*.

Weiyu Ma, Yuqian Fu, Zecheng Zhang, Bernard Ghanem, and Guohao Li. 2025a. Ava: Attentive vlm agent for mastering starcraft ii. *Preprint*, arXiv:2503.05383.

Weiyu Ma, Jiwen Jiang, Haobo Fu, and Haifeng Zhang. 2025b. Tacticcraft: Natural language-driven tactical adaptation for starcraft ii. *Preprint*, arXiv:2507.15618.

Weiyu Ma, Qirui Mi, Yongcheng Zeng, Xue Yan, Yuqiao Wu, Runji Lin, Haifeng Zhang, and Jun Wang. 2024. Large language models play starcraft ii: Benchmarks and a chain of summarization approach. *Preprint*, arXiv:2312.11865.

Tambet Matiisen, Avital Oliver, Taco Cohen, and John Schulman. 2019. Teacher–student curriculum learning. *IEEE transactions on neural networks and learning systems*, 31(9):3732–3740.

Sharada Mohanty, Erik Nygren, Florian Laurent, Manuel Schneider, Christian Scheller, Nilabha Bhattacharya, Jeremy Watson, Adrian Egli, Christian Eichenberger, Christian Baumberger, and 1 others. 2020. Flatland-rl: Multi-agent reinforcement learning on trains. *arXiv preprint arXiv:2012.05893*.

Sanmit Narvekar, Bei Peng, Matteo Leonetti, Jivko Sinapov, Matthew E Taylor, and Peter Stone. 2020. Curriculum learning for reinforcement learning domains: A framework and survey. *Journal of Machine Learning Research (JMLR)*, 21(1):7382–7431.

Jack Parker-Holder, Minqi Jiang, Michael Dennis, Mikayel Samvelyan, Jakob Foerster, Edward Grefenstette, and Tim Rocktäschel. 2022. Evolving curricula with regret-based environment design. In *International Conference on Machine Learning (ICML)*, pages 17473–17498.

Mikayel Samvelyan, Sharath C Raparthy, Andrei Lupu, Eric Hambro, Aram H Markosyan, Manish Bhatt, Yuning Mao, Minqi Jiang, Jack Parker-Holder, Jakob Foerster, and 1 others. 2024. Rainbow teaming: Open-ended generation of diverse adversarial prompts. *Advances in Neural Information Processing Systems*, 37:69747–69786.

Mikayel Samvelyan, Tabish Rashid, Christian Schroeder De Witt, Gregory Farquhar, Nantas Nardelli, Tim GJ Rudner, Chia-Man Hung, Philip HS Torr, Jakob Foerster, and Shimon Whiteson. 2019a. The starcraft multi-agent challenge. *arXiv preprint arXiv:1902.04043*.

Mikayel Samvelyan, Tabish Rashid, Christian Schroeder De Witt, Gregory Farquhar, Nantas Nardelli, Tim GJ Rudner, Chia-Man Hung, Philip HS Torr, Jakob Foerster, and Shimon Whiteson. 2019b. The starcraft multi-agent challenge. *arXiv preprint arXiv:1902.04043*.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. 2023. Reflexion: Language agents with verbal reinforcement learning. *Advances in neural information processing systems*, 36:8634–8652.

Alexey Skrynnik, Anton Andreychuk, Anatolii Borzilov, Alexander Chernyavskiy, Konstantin Yakovlev, and Aleksandr Panov. 2025. Pogema: A benchmark platform for cooperative multi-agent pathfinding. In *International Conference on Learning Representations*, volume 2025, pages 5576–5606.

Petru Soviany, Radu Tudor Ionescu, Paolo Rota, and Nicu Sebe. 2022. Curriculum learning: A survey. *International Journal of Computer Vision (IJCV)*, 130(6):1526–1565.

Oriol Vinyals, Igor Babuschkin, Wojciech M Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H Choi, Richard Powell, Timo Ewalds, Petko Georgiev, and 1 others. 2019. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, 575(7782):350–354.

Rui Wang, Joel Lehman, Jeff Clune, and Kenneth O Stanley. 2019. Paired open-ended trailblazer (poet): Endlessly generating increasingly complex and diverse learning environments and their solutions. In *arXiv preprint arXiv:1901.01753*.

Xihuai Wang, Shao Zhang, Wenhao Zhang, Wentao Dong, Jingxiao Chen, Ying Wen, and Weinan Zhang. 2024. Zsc-eval: An evaluation toolkit and benchmark for multi-agent zero-shot coordination. *Preprint*, arXiv:2310.05208.

Xin Wang, Yudong Chen, and Wenwu Zhu. 2021. A survey on curriculum learning. *IEEE Transactions on Pattern Analysis and Machine Intelligence (TPAMI)*, 44(9):4555–4576.

Xue Yan, Jiaxian Guo, Xingzhou Lou, Jun Wang, Haifeng Zhang, and Yali Du. 2023. An efficient end-to-end training approach for zero-shot human-ai coordination. *Advances in neural information processing systems*, 36:2636–2658.

Abhay Zala, Jaemin Cho, Han Lin, Jaehong Yoon, and Mohit Bansal. 2024. Envgen: Generating and adapting environments via llms for training embodied agents. *arXiv preprint arXiv:2403.12014*.

A   Additional StarCraft II Analyses

This appendix provides robustness checks, scope comparisons, and compute accounting for the Star-Craft II experiments.

Scope and positioning: a super-late-game micro mini-game. We emphasise upfront that EVOCURR solves a deliberately scoped *mini-game*: a fixed-army, super-late-game micro-management engagement with no economy, no build order, and no scouting. Both sides spawn with a full late-game tech tree: our agent commands 80+ Terran units across 10+ unit types (Marine, Marauder, Medivac, Ghost, Siege Tank, Viking, Cyclone, Widow Mine, Raven, Liberator) with all 10+ active abilities researched, and faces an equally late-game Protoss or Zerg opposition (Colossus, High Templar, Disruptor, Carrier, or Brood Lord, Lurker, Viper, Infestor, etc.) on a single tactical map. The single decision the agent must make is *how to fight*, not *what to build*.

This narrow scope is what makes the comparison in Table 5 both fair and informative. SMAC-style benchmarks (Samvelyan et al., 2019b) target a similar regime—fixed armies, no economy—but only at very small scale (3–30 homogeneous units, 0–2 active abilities). AlphaStar (Vinyals et al., 2019) solves the full game including economy and macro, at the cost of approximately 200,000 TPU-hours of training. EVOCURR sits between them: it tackles the late-game micro complexity that SMAC scenarios omit, but does so without leaving the mini-game frame and without any parameter training. With roughly 1–3 hours of inference-time LLM calls and $1.5 in API cost, the system produces behavior-tree code that coordinates Stimpack, Siege Mode, Personal Cloaking, EMP, Snipe, AoE avoidance and Medivac healing in a single engagement, while exploiting map terrain (Bush concealment, Ramp choke-points, Corridor funnels) explicitly via readable Python.

We make two explicit non-claims. First, EVOCURR does *not* play full StarCraft II: there is no build order, no scouting, no production decision in our scenario. Second, we do *not* claim parity with AlphaStar on full-game generality; AlphaStar operates on raw camera and spatial actions while we use python-sc2's unit-level command API, so our result speaks to micro proficiency on this mini-game alone. What the comparison does establish is that, on the super-late-game micro mini-game that classical RL micro-benchmarks have under-

represented, an inference-time curriculum over a frozen LLM can produce readable policies with substantial multi-ability tactical coordination.

Compute budget analysis. A natural concern is whether EVOCURR's gains stem simply from spending more compute than the baselines. Table 6 disaggregates this. Per final task, EVOCURR-DeepSeek consumes roughly $0.2 of LLM API calls and 1–3 hours of wall-clock; the GPT-5 / Claude-4 backbones cost about $1.5 each. This is, in absolute terms, an order of magnitude more than direct one-shot ×10 sampling ($0.02–$0.30 depending on backbone), but is comparable to or cheaper than the autonomous-agent baselines we contrast against: Claude Code consumes a similar 90-minute wall-clock budget and still achieves 0% on the final task (Appendix H), while Codex / Cursor at single-shot pricing also fail.

The decisive evidence that EVOCURR's advantage is mechanism rather than budget comes from our cross-domain ablations (Appendix H and the Flatland / POGEMA equal-budget experiments in Section 5): extending Reflexion to 20 iterations—roughly 4× the per-attempt budget of Self-reflection and within an order of magnitude of EvoCurr's total spend—still yields 0% across 40 / 40 generations on the multi-agent pathfinding domains where direct LLM code generation fundamentally fails. The gap is therefore not closed by additional inference-time compute in the absence of a curriculum: EVOCURR's accepted-floor mechanism enables incremental progress through cheap simple stages, whereas budget-matched baselines repeatedly burn compute on the hardest task and never converge.

On compute-matched iterative baselines. A natural concern is whether EvoCurr's gain over direct generation reflects the curriculum mechanism itself or simply additional inference-time compute. We address this with three complementary lines of evidence.

(i) Reflection-enabled backbones at the same SC2 scale. Table 7 reports reflection-enabled variants of all four LLM backbones evaluated in Section 4.1. Reflection yields only marginal gains over the one-shot baseline and remains far below EVOCURR on the same final tasks; the curriculum gap is robust to this iteration scaling.

(ii) An autonomous Reflexion-style agent at ∼3× the budget on the same SC2 task. Appendix H reports **Claude Code**, a state-of-the-art

Table 5: Positioning EVOCURR against SMAC-style closed-loop RL micro benchmarks and AlphaStar (Vinyals et al., 2019) full-game RL+imitation. **Scope:** EVOCURR targets a single super-late-game micro *mini-game*—fixed armies, full tech tree, no economy, no build order, no scouting—i.e., it is *not* a full-game agent. SMAC sits in the same mini-game frame but at very small scale (3–30 homogeneous units, 0–2 abilities); AlphaStar solves the full game at industrial training cost. Numbers for AlphaStar are from (Vinyals et al., 2019); SMAC characteristics aggregate canonical scenarios (3m, 8m_vs_9m, MMM2, 27m_vs_30m). * *Action-space caveat:* EVOCURR uses python-sc2 unit-level commands while AlphaStar uses raw camera + spatial actions; we therefore claim only that EVOCURR addresses only this fixed-army micro mini-game, not AlphaStar's full-game setting or action space.

Dimension	SMAC (RL micro benchmarks)	AlphaStar	EVOCURR (ours)
Scenario scale	3–30 units; 1–3 unit types	Full game (200+ units, all races)	**81 units, 10+ types, 10+ abilities**
Game phase	Isolated micro skirmish	Full game (build + macro + micro)	**Super-late-game micro mini-game**
Control paradigm	Closed-loop RL (per-step)	Closed-loop RL+imitation	**Open-loop code-as-policy**
Action space	Per-unit discrete (move/attack/...)	Raw camera + spatial actions	python-sc2 unit-action API*
Training compute	∼1–10 GPU-days	∼200,000 TPU-hours	**0 (no parameters trained)**
Inference cost	GPU forward pass	GPU forward pass	**≈1–3 hr LLM calls, ≈\$1.5**
Solution interpretability	Low (neural policy)	Low (neural policy)	**High (readable Python behavior tree)**
Terrain utilisation	Minimal (open maps)	Strong (full map awareness)	**Strong (Bush concealment, Ramp choke, Corridor funnel explicit in code)**
Multi-ability coordination	0–2 abilities	50+ abilities	**Stimpack, SiegeMode, Cloak, EMP, Snipe, AoE-avoid, Heal, ... all in one engagement**
Reproducibility cost	Re-train each scenario	Train once at industrial scale	**Re-run inference, hours not months**

autonomous coding agent that implements an aggressive Reflexion-style execute-feedback-revise loop with full tool use, running for **90 minutes / 100+ simulated matches** against our final task. This budget exceeds EvoCurr's end-to-end LLM-call cost on every task in Section 4.1, yet Claude Code achieves a 0% win rate on the final task. The same agent's performance on its self-designed intermediate tasks is substantially higher (cf. Appendix H for the trajectory), confirming that the bottleneck is *curriculum structure* rather than per-iteration compute.

(iii) Direct 20-*iteration Reflexion ablations in two mechanism-orthogonal cross-domain settings.* On both Flatland (Section C.1) and POGEMA (Section C.2) we explicitly run Reflexion at a budget of **20 generations** (approximately 3× and 1.6× EvoCurr's training-time budget, respectively); both yield **0/20 generations with non-zero performance**. The POGEMA failure mode is particularly diagnostic: 17/20 generations cannot even execute (e.g. `NameError: heapq` appears on 6 consecutive generations 12–19, indicating that Summarizer feedback fails to teach the model to add a single `import` statement over 20 rounds). On LiveCodeBench Hard (Section C.3) we further isolate

Table 6: Compute budget per single final SC2 task (e.g., Bush TvP). All EvoCurr and Claude Code numbers are as reported in Appendix I and Appendix H. Direct one-shot and Self-reflection rows are estimated from API pricing (DeepSeek-V3.1 input \$0.27/M, output \$1.10/M; GPT-5 input \$1.25/M, output \$10/M; Claude-4 Sonnet input \$3/M, output \$15/M; as of 2026-04) multiplied by the attempt counts already committed to in the paper (10 target-task attempts for direct, 10 attempts × one refinement round for self-reflection). **Win rate** is the average over the 12 final tasks of Table 1. AlphaStar (Vinyals et al., 2019) is included for reference only; it solves a different scope (full game vs. mini-game).

Method	LLM calls	Wall-clock	Cost (USD)	Outcome
Direct one-shot ×10 (DeepSeek)	10	∼10 min	≈\$0.02 (est.)	55.0% macro
Direct one-shot ×10 (GPT-5)	10	∼10 min	≈\$0.15 (est.)	44.2% macro
Direct one-shot ×10 (Claude-4)	10	∼10 min	≈\$0.30 (est.)	70.8% macro
Self-reflection (1 round ×10, DeepSeek)	20	∼20 min	≈\$0.04 (est.)	below EvoCurr
Self-reflection (1 round ×10, GPT-5)	20	∼20 min	≈\$0.30 (est.)	below EvoCurr
Self-reflection (1 round ×10, Claude-4)	20	∼20 min	≈\$0.60 (est.)	below EvoCurr
Claude Code (autonomous coding agent)	100+ matches	∼90 min	comparable to EvoCurr	**0%**
Codex / Cursor (single-attempt agents)	1–10	<30 min	\$0.5–\$2 (est.)	0–40%
EVOCURR-DeepSeek (ours)	4–6 stages	1–3 hr	**≈\$0.2**	**99.2% macro**
EVOCURR-Claude-4 (ours)	4–6 stages	1–3 hr	**≈\$1.5**	**96.7% macro**
EVOCURR-GPT-5 (ours)	4–6 stages	1–3 hr	**≈\$1.5**	**97.5% macro**
AlphaStar (full game, reference)	—	≈200,000 TPU-hours	not applicable	full game (different scope)

this effect at the algorithmic-code-generation level: Reflexion-3 finishes at exactly the same Pass@1 as Direct one-shot (40%) while spending $2.5\times$ the cost, and on one problem (abc388_e) the Summarizer's feedback *regresses* a 100%-correct solution to 0%, the exact failure mode (Summarizer drift) that the accepted-floor mechanism is designed to prevent.

Taken together, these three lines establish that scaling iterative inference compute on the SC2 final task, whether via plain reflection (Table 7), via a state-of-the-art autonomous agent (Appendix H), or via 20-iteration Reflexion in two structurally distinct domains and one NLP code-generation

domain (Section 5), does not close the gap. The curriculum mechanism, specifically Designer-driven progressive difficulty, accepted-floor anti-regression, and feasibility checking, contributes the gain, not the inference budget.

B Designer Ablation and Code-Evolution Details

Designer ablation. To validate the effectiveness of the Designer module, we extend the direct approach by enabling different LLMs to generate behavior trees in a way that emulates the Solver module, permitting the models to self-correct and refine their outputs. The results are presented in Table 7.

The data reveal a significant performance disparity. Standalone LLMs with self-correction still struggle with complex scenarios and often yield 0% win rates on challenging tasks such as Bush and Flat. In contrast, EvoCurr consistently raises the same base models to near-perfect performance, maintaining win rates between 90% and 100% across diverse tasks. For instance, Claude-4 achieves only a 40% win rate on Bush (TvP) and Corridor (TvP) through direct generation, but reaches 100% and 70% respectively when guided by EvoCurr. This confirms that Solver-side self-correction is insufficient in isolation: the Designer's progressive curriculum is necessary to break the final task into solvable steps.

Behavior code generation. When facing a new curriculum with more units or new unit types, the behavior coder generates a new script by extending the script that solved the previous curriculum. The first refinement phase adds new unit-specific control functions, such as `control_vikings` and `control_ghosts`; the second phase refines existing control functions to improve coordination among units. For example, Marines initially learn focus fire, and later learn to split against area-of-effect damage before resuming focus fire.

For further insights into the specific curriculum trajectories, see Appendix E. Table 18 presents the step-by-step sub-task generation across all 12 scenarios, while Table 19 gives a representative full path showing how the framework advances through successful nodes and backs off from failed proposals.

Layered critic refinement. Although LLMs learn extensive coding resources during pre-training, their ability to generate scripts for the python-sc2 package depends on the amount and quality of community-written examples they have seen. We therefore use a two-layer critic. The first layer is a sanity-check module that corrects grammar bugs, API misuse, and runtime exceptions. The second layer refines strategy-level logic in the behavior-tree script. This two-layer critic improves the rate of successful behavior-tree generation.

C Cross-Domain Experiment Details

This appendix gives the experimental details behind Table 4. The main text uses these results only to support the method-level generality claim; the implementation settings, failure modes, and auxiliary figures are kept here to avoid interrupting the SC2-led narrative.

C.1 Flatland

Flatland (Mohanty et al., 2020) is a 2D-grid multi-train pathfinding benchmark. Our final task is a 35×35 grid with 3 cities and 4 trains under `single_speed` and `no_malfunctions`; a run is counted as successful when mean completion is at least 0.90. Direct LLM generation fails because the API requires direction-conditioned transitions through `env.rail.get_transitions(r,c,d)`, and valid routing must search over (cell, direction) rather than cells alone. Multi-train collision avoidance further requires priority-aware reservations.

Across three random seeds, EvoCurr reaches 0.710 ± 0.195 mean completion, while Direct and Reflexion-5 remain at 0.000 on all seeds. A more adversarial Reflexion-20 ablation on seed 42 also produces 0/20 generations with non-zero completion despite spending roughly $3 \times$ EvoCurr's training budget.

C.2 POGEMA

POGEMA (Skrynnik et al., 2025) is a partially observable multi-agent pathfinding benchmark. Our final task is a 20×20 grid with 8 agents, obstacle density 0.25, and observation radius 3. The metric is ISR (Individual Success Rate), with a success threshold of 0.90. Unlike Flatland, POGEMA requires time-indexed reservations and global belief accumulation from local 7×7 observations.

EvoCurr reaches 0.693 ± 0.108 mean ISR across three seeds, while Direct and Reflexion-6 remain at 0.000. In the Reflexion-20 ablation, 17/20 generations crash and the remaining 3/20 execute but

Table 7: Winning rate (%). Validation of the Designer module by enabling LLMs to emulate Solver-style self-correction and refinement. Self-correction alone remains far below EvoCurr on most final tasks.

Task	EvoCurr (DeepSeek-V3.1)	EvoCurr (Claude-4)	EvoCurr (GPT-5)	DeepSeek-V3.1	GPT-5	Claude-4	Gemini-2.5
TvP+bush	**100**	**100**	**100**	10	0	40	0
TvP+corridor	**100**	70	90	0	0	40	0
TvP+corner	90	**100**	**100**	**100**	0	**100**	0
TvP+flat	**100**	**100**	**100**	40	30	**100**	0
TvP+main	**100**	**100**	**100**	**100**	0	**100**	0
TvP+ramp	**100**	**100**	**100**	30	20	10	90
TvZ+bush	**100**	90	**100**	0	0	20	0
TvZ+corridor	**100**	**100**	90	60	10	10	0
TvZ+corner	**100**	**100**	**100**	**100**	100	20	0
TvZ+flat	**100**	**100**	90	20	0	0	0
TvZ+main	**100**	**100**	**100**	0	0	60	30
TvZ+ramp	**100**	**100**	**100**	0	0	0	0

deadlock at ISR= 0. The most diagnostic failure is repeated `NameError: heapq`, which appears on six later generations even after feedback, showing that generic reflection does not reliably repair basic executable-structure errors.

Table 8: Multi-seed verification on the two main supplementary domains. Direct one-shot and short-horizon Reflexion are both 0.000 across all 3 seeds; EVOCURR is the only non-zero method. Reflexion-20 numbers are seed-42 only.

Method	seed 42	seed 43	seed 44	mean $\pm$ s.d.
Flatland – completion				
hand_rule	0.17	0.17	0.00	0.113 ± 0.098
direct_oneshot	0.000	0.000	0.000	0.000
Reflexion-5	0.000	0.000	0.000	0.000
Reflexion-20	0.000	–	–	0.000
EVOCURR	**0.880**	**0.750**	**0.500**	$\mathbf{0.710 \pm 0.195}$
POGEMA – ISR				
hand_rule	0.04	–	0.08	0.060
direct_oneshot	0.000	–	–	0.000
Reflexion-6	0.000	0.000	0.000	0.000
Reflexion-20	0.000	–	–	0.000 (17/20 crash)
EVOCURR	**0.710**	**0.580**	**0.790**	$\mathbf{0.693 \pm 0.108}$

C.3 LiveCodeBench Hard

We evaluate 20 *Hard*-tier problems from Live-CodeBench version v6 (Jain et al., 2025), restricted to contest dates after 2024-08 to mitigate contamination relative to the DeepSeek-V4-Pro training cutoff. Direct one-shot makes one Coder call. Reflexion-3 uses up to three Coder + Summarizer rounds against the full test suite. EvoCurr uses the same backbone and three-round budget, but decomposes each problem into a three-stage constraint-relaxation curriculum: produce runnable code, pass at least one test case, then pass all test cases. The accepted-floor mechanism prevents later feedback from destroying an already-working stage.

Table 9: LiveCodeBench Hard (post-2024-08, contamination-controlled): per-method Pass@1 over 20 problems. All methods use the same DeepSeek-V4-Pro backbone.

Method	Solved (Pass@1)	Avg pass rate	LLM calls	Cost (USD)
Direct one-shot	8/20 (40%)	40.0%	20	$0.30
Reflexion-3	8/20 (40%)	40.0%	44	$0.74
EVOCURR	**11/20 (55%)**	**58.3%**	69	$1.03

EvoCurr solves 11/20 problems versus 8/20 for Direct and Reflexion-3. Iteration alone does not close the gap: Reflexion-3 spends $2.5\times$ the cost of Direct yet obtains the same Pass@1, gaining one problem while regressing on another (`abc388_e`: $100\% \rightarrow 0\%$). EvoCurr's gains concentrate on problems where the runnable-code warm-up stage creates a scaffold that direct generation never reaches.

C.4 Boundary Controls

pandapipes. On an 18-junction gas-network control benchmark, 6-iteration Reflexion already reaches 1.00 feasibility and 0.009 MW power consumption, outperforming EvoCurr's 0.33 feasibility. This is a deliberate negative control: the control space is low-dimensional, the feedback is direct, and PI-style code templates are within the LLM's one-shot reach.

JSSP. On Taillard 10×5 Job-Shop Scheduling, all three methods tie SPT (Shortest Processing

Time) at score 1.00. The LLM's first attempt is already SPT-like, so the curriculum cannot exceed an already-saturated ceiling. Reflexion can even degrade the working solution, consistent with the Summarizer-drift failure mode observed in Live-CodeBench.

D StarCraft II Micro-Management Details

D.1 Introduction to StarCraft II

StarCraft II is a real-time strategy game developed by Blizzard Entertainment. It has three asymmetric factions, Terran, Protoss, and Zerg, each with distinct units, technologies, and tactical interactions. Players must simultaneously manage economy, production, technology, army composition, and real-time combat control. This makes the game a long-standing benchmark for studying decision-making under partial observability, large action spaces, and severe time pressure.

For AI research, StarCraft II is valuable because it combines long-horizon strategic planning with millisecond-level tactical execution. AlphaStar demonstrated that large-scale learning systems can reach Grandmaster-level full-game play, while PySC2 and SMAC-style benchmarks made controlled micro-management evaluation more accessible. Our work focuses on a narrower but difficult slice of this space: fixed-army late-game engagements where the economy and production systems are removed, leaving the agent to solve the tactical question of how to fight with a large heterogeneous army.

D.2 StarCraft II API and Python Interfaces

The technical foundation enabling AI research in StarCraft II rests on Blizzard Entertainment's official StarCraft II Machine Learning API, which provides programmatic access to the game's complete state information and action execution capabilities. This API exposes the game engine through a protocol buffer-based interface that delivers real-time observations including unit positions, resource states, map geometry, and tactical information while accepting high-level commands for unit control, building construction, and technology research. The official **s2client-proto** defines the core communication protocol between external programs and the StarCraft II executable, establishing standardized data structures for observations, actions, and game configuration. This low-level interface handles the complex details of game state serialization, network communication, and command validation, but requires substantial boilerplate code and deep understanding of the underlying protocol specifications to implement effective AI agents.

Building upon this foundation, the research community has developed higher-level abstractions that significantly simplify AI development while preserving the full functionality of the underlying API. **PySC2**, developed by DeepMind, transforms the raw API into a structured reinforcement learning environment that follows standard RL conventions with observation spaces, action spaces, and reward functions. This environment emphasizes feature-layer representations and provides built-in mini-games for curriculum learning, making it particularly suitable for deep reinforcement learning approaches.

Complementing PySC2, the **python-sc2** library offers a more direct and intuitive interface focused on scripted bot development, where complex strategic behaviors can be implemented using straightforward Python code with minimal boilerplate. The python-sc2 library abstracts away protocol buffer complexities while exposing high-level game objects such as units, abilities, and map structures through clean Python APIs, enabling researchers to focus on strategic logic rather than low-level implementation details. Our EvoCurr framework leverages python-sc2's accessibility and expressiveness to generate behavior tree scripts that can be easily interpreted, debugged, and modified, making it an ideal choice for our curriculum-based approach to complex tactical reasoning.

D.3 Final Task Setting

To rigorously evaluate the framework's capacity for handling high-dimensional state spaces and heterogeneous multi-agent coordination, we construct two terminal scenarios (T_f) representing late-game full-technology engagements. As delineated in Tables 10 and 11, these tasks simulate asymmetric warfare against Protoss and Zerg factions, respectively. The agent is tasked with controlling a complex Terran composition that integrates biological infantry (e.g., Marines, Ghosts) with mechanical support (e.g., Siege Tanks, Liberators). This configuration necessitates the execution of precise micro-management actions, including the timely activation of abilities such as *Stimpack*, *Personal Cloaking*, and *Siege Mode*. Conversely, the adversary configurations are initialized with

Table 10: Final Terran vs Protoss Task Specification

Unit Type	Quantity	Technology
AGENTS (Terran)		
Marine	20	Stimpack
Marauder	12	Stimpack
Medivac	4	Heal
Ghost	8	PersonalCloaking
SiegeTank	6	SiegeTech
VikingFighter	8	AssaultMode
Cyclone	7	LockOn
WidowMine	7	Burrow
Raven	3	HunterSeeker
Liberator	2	DefenderMode
ENEMIES (Protoss)		
Zealot	15	Charge
Stalker	14	BlinkTech
Sentry	10	ForceField
HighTemplar	8	PsiStormTech
Colossus	4	ExtendedThermalLance
Tempest	5	GroundAttack
Disruptor	4	PurificationNova
Carrier	4	InterceptorLaunch

Table 11: Final Terran vs Zerg Task Specification

Unit Type	Quantity	Technology
AGENTS (Terran)		
Marine	20	Stimpack
Marauder	12	Stimpack
Medivac	4	Heal
Ghost	8	PersonalCloaking
SiegeTank	6	SiegeTech
VikingFighter	8	AssaultMode
Cyclone	7	LockOn
WidowMine	7	Burrow
Raven	3	HunterSeeker
Liberator	2	DefenderMode
ENEMIES (Zerg)		
Zergling	60	ZerglingMovementSpeed
Baneling	24	CentrificalHooks
Roach	15	GlialReconstitution
Hydralisk	10	HydraliskSpeed
Lurker	6	Burrow
Corruptor	10	FlyerWeaponsLevel1
Infestor	3	EnergyUpgrade
Viper	4	FlyerArmorsLevel1
Overseer	3	FlyerArmorsLevel1
Queen	4	MissileWeaponsLevel1
Broodlord	4	FlyerWeaponsLevel1

high-threat counter-units possessing lethal Area-of-Effect (AoE) capabilities, specifically High Templars and Colossi in the Protoss matchup, and Banelings and Broodlords in the Zerg matchup. Consequently, successful task completion demands that the agent exhibit emergent tactical behaviors, such as formation dispersion to mitigate AoE damage and priority targeting to neutralize key enemy assets.

D.4 StarCraft II Score Tables

Win rate captures final success but not the quality of partial or already-winning policies. We therefore also report a damage-cost-aware combat score $\mathcal{S}_{combat}$ for more nuanced evaluation. This metric compares EvoCurr with direct target-task implementations generated by closed-source LLMs (DeepSeek-V3.1, GPT-5, Claude-4, and Gemini-2.5), given by:

$$\mathcal{S}_{combat} = 0.5 \cdot \frac{R_{\text{agent\_final}}}{R_{\text{agent\_init}}} + 0.5 \cdot \left(1 - \frac{R_{\text{enemy\_final}}}{R_{\text{enemy\_init}}}\right), \tag{6}$$

where the total combat power for one side is

$$R_{\text{side}} = \sum_i (m_i + \alpha v_i + \beta b_i) \frac{h_i + s_i}{h_i^{\text{max}} + s_i^{\text{max}}}. \tag{7}$$

This metric aggregates resource cost and remaining health/shields; scores range from 0 to 1. A combat score $\mathcal{S}_{combat} > 0.5$ indicates successful annihilation of the majority of enemy forces while preserving our own, providing a finer-grained assessment than binary win/loss especially for failed code executions where the first term becomes 0.

Following the protocol in Section 4.1, we keep selected-policy comparison and cheap-sampling variability separate. EvoCurr cells below are the final policies selected by complete curriculum searches. Direct selected cells are the best executable policies found by repeated one-shot target-task sampling under the same per-policy rollout evaluation. We then report the direct-attempt distributions separately, since those 10 attempts estimate one-shot generation variability rather than full curriculum-search variability.

To demonstrate the effectiveness of EvoCurr, we compared it against direct behavior tree generation using LLMs and an approach that enables models to refine behavior trees through self-reflection. The

Table 12: **Winning Score (Part 1: Ours).** Comparison of EvoCurr variants.

Task	Evo-DeepSeek	Evo-Claude	Evo-GPT
bush (TVP)	**0.6998**	0.6359	0.6963
corridor (TVP)	**0.7146**	0.6095	0.6200
corner (TVP)	0.5515	0.6367	0.6586
flat (TVP)	**0.6996**	0.6070	0.6295
main (TVP)	0.7277	0.6565	0.6669
ramp (TVP)	0.7226	0.6345	0.6811
bush (TVZ)	**0.7322**	0.6701	0.6467
corridor (TVZ)	**0.6980**	0.6497	0.5751
corner (TVZ)	**0.8405**	0.7420	0.6206
flat (TVZ)	**0.6263**	0.6125	0.5314
main (TVZ)	0.7017	**0.7603**	0.7531
ramp (TVZ)	**0.7466**	0.6519	0.7064

Part 2: Baselines Comparison.

Task	DeepSeek	GPT	Claude	Gemini	Claude code	Codex	Cursor
bush (P)	0.33	0.43	0.35	0.49	0.19	0.27	0
corr (P)	0.56	0.51	0.63	0.26	0.19	0.21	0
corn (P)	**0.66**	0.52	0.62	0.55	0.28	0.27	0
flat (P)	0.41	0.56	0.39	0.30	0.21	0.22	0
main (P)	0.69	0.63	0.67	**0.77**	0.34	0.40	0
ramp (P)	0.45	0.48	**0.74**	0.66	0.21	0.23	0
bush (Z)	0.61	0.34	0.64	0.36	0.46	0.31	0
corr (Z)	0.58	0.56	0.65	0.59	0.34	0.31	0
corn (Z)	0.41	0.69	0.77	0.80	0.74	0.62	0
flat (Z)	0.36	0.29	0.49	0.37	0.31	0.27	0
main (Z)	0.68	0.43	0.43	0.66	0.45	0.45	0
ramp (Z)	0.45	0.45	0.68	0.29	0.45	0.29	0

results are presented in Tables 12 and 13.

Table 13: **Reflect Score (Part 1: Ours).** Comparison of EvoCurr variants with self-reflection.

Task	Evo-DeepSeek	Evo-Claude	Evo-GPT
pvt+bush	**0.6998**	0.6359	0.6963
pvt+corridor	**0.7146**	0.6095	0.6200
pvt+corner	0.5515	0.6367	0.6586
pvt+flat	**0.6996**	0.6070	0.6295
pvt+main	0.7277	0.6565	0.6669
pvt+ramp	**0.7226**	0.6345	0.6811
zvt+bush	**0.7322**	0.6701	0.6467
zvt+corridor	**0.6980**	0.6497	0.5751
zvt+corner	**0.8405**	0.7420	0.6206
zvt+flat	**0.6263**	0.6125	0.5314
zvt+main	0.7017	**0.7603**	0.7531
zvt+ramp	**0.7466**	0.6519	0.7064

Part 2: Baselines Comparison.

Task	DeepSeek	GPT-5	Claude-4	Gemini
pvt+bush	0.4605	0.1667	0.5208	0
pvt+corridor	0.3328	0.2649	0.4651	0
pvt+corner	**0.7332**	0.0899	0.6823	0
pvt+flat	0.5467	0.4502	0.6110	0
pvt+main	0.6518	0.4196	**0.7381**	0
pvt+ramp	0.4679	0.4142	0.5935	0.6649
zvt+bush	0.3189	0.2134	0.4271	0
zvt+corridor	0.5696	0.4746	0.2913	0.4614
zvt+corner	0.7043	0.7620	0.5773	0
zvt+flat	0.4520	0.2765	0.3424	0
zvt+main	0.3068	0.2982	0.5518	0.4567
zvt+ramp	0.2691	0.5488	0.3305	0

Table 14: Selected SC2 combat scores for Terran-vs-Protoss tasks. EvoCurr columns report the curriculum-selected final policy for each backbone. Direct columns report the best executable policy found by each direct-generation backbone within 10 target-task attempts.

	EVOCURR selected			Direct selected best			
Task	DS	Claude	GPT	DS	GPT	Claude	Gemini
Bush	0.700	0.636	0.696	0.373	0.406	0.590	0.514
Corridor	0.715	0.610	0.620	0.627	0.617	0.644	0.340
Corner	0.551	0.637	0.659	0.640	0.638	0.708	0.559
Flat	0.700	0.607	0.629	0.433	0.652	0.331	0.319
Main	0.728	0.657	0.667	0.666	0.706	0.766	0.841
Ramp	0.723	0.635	0.681	0.658	0.550	0.766	0.631

Table 15: Direct-generation combat-score distributions for Terran-vs-Protoss tasks. Cells report mean ± std over 10 independent target-task attempts; brackets give executable attempts out of 10.

Task	DeepSeek-V3.1	GPT-5	Claude-4	Gemini-2.5
Bush	0.098±0.159 [3]	0.261±0.147 [8]	0.097±0.210 [2]	0.212±0.210 [6]
Corridor	0.320±0.242 [7]	0.259±0.205 [7]	0.174±0.241 [4]	0.081±0.118 [4]
Corner	0.200±0.278 [4]	0.413±0.177 [9]	0.071±0.224 [1]	0.197±0.222 [6]
Flat	0.108±0.177 [3]	0.238±0.265 [5]	0.033±0.105 [1]	0.032±0.101 [1]
Main	0.247±0.279 [5]	0.476±0.276 [8]	0.150±0.316 [2]	0.084±0.266 [1]
Ramp	0.302±0.279 [6]	0.197±0.218 [5]	0.310±0.335 [5]	0.063±0.199 [1]

Table 16: Selected SC2 combat scores for Terran-vs-Zerg tasks. The reporting convention matches Table 14.

Task	EVOCURR selected			Direct selected best			
	DS	Claude	GPT	DS	GPT	Claude	Gemini
Bush	0.732	0.670	0.647	0.646	0.430	0.661	0.357
Corridor	0.698	0.650	0.575	0.668	0.541	0.676	0.675
Corner	0.840	0.742	0.621	0.495	0.745	0.764	0.789
Flat	0.626	0.612	0.531	0.362	0.318	0.548	0.353
Main	0.702	0.760	0.753	0.786	0.535	0.661	0.657
Ramp	0.747	0.652	0.706	0.428	0.411	0.681	0.329

Table 17: Direct-generation combat-score distributions for Terran-vs-Zerg tasks. The reporting convention matches Table 15.

Task	DeepSeek-V3.1	GPT-5	Claude-4	Gemini-2.5
Bush	0.255±0.283 [5]	0.226±0.196 [6]	0.100±0.224 [2]	0.071±0.149 [2]
Corridor	0.325±0.168 [9]	0.171±0.225 [4]	0.068±0.214 [1]	0.130±0.273 [2]
Corner	0.121±0.201 [3]	0.356±0.324 [6]	0.288±0.373 [4]	0.265±0.347 [4]
Flat	0.123±0.161 [4]	0.149±0.158 [5]	0.144±0.200 [4]	0.035±0.112 [1]
Main	0.534±0.240 [9]	0.297±0.213 [7]	0.066±0.209 [1]	0.234±0.309 [4]
Ramp	0.276±0.192 [7]	0.227±0.166 [7]	0.124±0.228 [3]	0.065±0.137 [2]

D.5 Generated Behavior Tree Code Examples

This section presents complete examples of behavior tree implementations generated by the EvoCurr framework at different curriculum stages, demonstrating the evolution of tactical complexity.

D.5.1 Early Stage: Basic Marine Micro-management

```python
from sc2 import maps
from sc2.bot_ai import BotAI
from sc2.data import Race, Difficulty
from sc2.ids.ability_id import AbilityId
from sc2.ids.unit_typeid import UnitTypeId
from sc2.main import run_game
from sc2.player import Bot, Computer

class BattleBot(BotAI):
    def __init__(self):
        super().__init__()
        self.stim_used = set()

    async def on_step(self, iteration: int):
        if iteration == 0:
            print("Marine Micro Bot - 5v2 Marines vs
              Zealots!")
        if self.units.exists:
            await self.marine_micro()

    async def marine_micro(self):
        marines = self.units(UnitTypeId.MARINE)
        zealots = self.enemy_units(UnitTypeId.ZEALOT)

        if not marines.exists or not zealots.exists:
            return

        close_zealots = zealots.filter(lambda z:
            marines.closest_to(z.position).distance_to(z)
          < 6)

        if close_zealots.exists:
            for marine in marines:
                if (marine.tag not in self.stim_used and
                    AbilityId.EFFECT_STIM_MARINE in
                    await
              self.get_available_abilities(marine)):
                    marine(AbilityId.EFFECT_STIM_MARINE)
                    self.stim_used.add(marine.tag)

        target = min(zealots, key=lambda z: z.health +
          z.shield)

        for marine in marines:
            dist = marine.distance_to(target)
            if dist < 1:
                retreat_pos =
          marine.position.towards(target.position, -3)
                marine.move(retreat_pos)
            elif dist <= 5:
                marine.attack(target)
            else:
                marine.move(target.position)
```

D.5.2 Intermediate Stage: Multi-unit Coordination

```python
class BattleBot(BotAI):
    async def on_step(self, iteration: int):
        if iteration == 0:
            print("Terran Battle Bot Activated!")

        if self.units.exists:
            await self.control_ghosts()
            await self.control_marines()
            await self.control_marauders()
            await self.control_medivacs()

    async def control_ghosts(self):
        ghosts = self.units(UnitTypeId.GHOST)
        if not ghosts.exists:
            return

        high_templars =
          self.enemy_units(UnitTypeId.HIGHTEMPLAR)
        stalkers = self.enemy_units(UnitTypeId.STALKER)

        for ghost in ghosts:
            if high_templars.exists:
                templar =
          high_templars.closest_to(ghost.position)
                if ghost.distance_to(templar) < 12:
                    if AbilityId.SNIPE_SNIPE in
                        await
          self.get_available_abilities(ghost):
                        ghost(AbilityId.SNIPE_SNIPE,
          templar)
                    elif AbilityId.EMP_EMP in
                          await
          self.get_available_abilities(ghost):
                        ghost(AbilityId.EMP_EMP,
          templar.position)
                        ghost.move(templar.position)
                    if AbilityId.BEHAVIOR_CLOAKON_GHOST in
                        await
          self.get_available_abilities(ghost):

          ghost(AbilityId.BEHAVIOR_CLOAKON_GHOST)
            elif stalkers.exists:
                target =
          stalkers.closest_to(ghost.position)
                ghost.attack(target)

    async def control_medivacs(self):
        medivacs = self.units(UnitTypeId.MEDIVAC)
        if not medivacs.exists:
            return

        bio_units = self.units.filter(lambda unit:
                    unit.type_id in {UnitTypeId.MARINE,
                    UnitTypeId.MARAUDER})
        for medivac in medivacs:
            injured = bio_units.filter(lambda unit:
                    unit.health_percentage < 0.75)
            if injured.exists:
                target =
          injured.closest_to(medivac.position)
                medivac.move(target.position)
                if medivac.distance_to(target) < 5:
                    medivac(AbilityId.MEDIVACHEAL_HEAL,
          target)
            elif bio_units.exists:
                medivac.move(bio_units.center)
```

D.5.3 Advanced Stage: Complex Multi-unit Tactical Framework

```python
class BattleBot(BotAI):
    async def on_step(self, iteration: int):
        if iteration == 0:
            self.setup_complete = False
            await self.initial_positioning()
            self.setup_complete = True

        bio_units =
            self.units.of_type({UnitTypeId.MARINE,
            UnitTypeId.MARAUDER})
        medivacs = self.units(UnitTypeId.MEDIVAC)

        await self.avoid_aoe(bio_units + medivacs)
        await self.control_siege_tanks()
        await self.control_vikings()
        await self.control_liberators()
        await self.control_ghosts()
        await self.control_bio(UnitTypeId.MARINE)
        await self.control_bio(UnitTypeId.MARAUDER)
        await self.control_medivacs()

    async def avoid_aoe(self, units: Units):
        storms = [e for e in self.state.effects
                    if e.id == EffectId.PSISTORMPERSISTENT]
        disruptor_balls =
            self.enemy_units(UnitTypeId.DISRUPTORPHASED)

        threats = []
        for storm in storms:
            threats.append((storm.position, 2.5))
        for ball in disruptor_balls:
            threats.append((ball.position, 2.5))

        for unit in units:
            for pos, radius in threats:
                if unit.distance_to(pos) < radius:
                    away = unit.position.towards(pos, -3)
                    unit.move(away)
                    break

    async def control_siege_tanks(self):
        siege_tanks =
            self.units(UnitTypeId.SIEGETANKSIEGED)
        sieged_tanks =
            self.units(UnitTypeId.SIEGETANKSIEGED)

        for tank in siege_tanks:
            if tank.distance_to(Point2((15, 15))) > 2:
                continue
            abilities = await
                self.safe_get_abilities(tank)
            if AbilityId.SIEGEMODE_SIEGEMODE in abilities:
                tank(AbilityId.SIEGEMODE_SIEGEMODE)

        if sieged_tanks.exists:
            enemies = self.enemy_units
            if not enemies.exists:
                return
            priority_targets =
                enemies.of_type([UnitTypeId.COLOSSUS,
                                 UnitTypeId.STALKER,
                UnitTypeId.HIGHTEMPLAR,
                                 UnitTypeId.ZEALOT])

            for tank in sieged_tanks:
                targets_in_range =
                    priority_targets.in_attack_range_of(tank)
                if targets_in_range:
                    target = min(targets_in_range,
                        key=lambda t: (t.type_id not in
                            {UnitTypeId.COLOSSUS,
                UnitTypeId.HIGHTEMPLAR},
                                    t.distance_to(tank)))
                    tank.attack(target)
```

E Complete Curriculum Evolution Paths (StarCraft II)

E.1 Curriculum Design

We illustrate the curriculum-design process by listing the sub-tasks generated for the final task in Table 18. Each sub-task is generated based on the outcome of the previous curriculum. For StarCraft II tasks, we set the acceptance threshold to $\tau = 0.9$: the Designer increases difficulty when the win rate is above 90% and decreases difficulty otherwise. Among the 12 tasks, the Terran vs Protoss setting on the Bush map requires the longest curriculum trajectory because bush concealment makes enemy visibility and target selection harder; the Designer therefore lowers difficulty twice before the Solver finally masters the target task.

We omit the older evolution schematic here because it is visually noisy in the two-column appendix. The main paper keeps the clearer trajectory view in Figure 3; this appendix focuses on the exact curriculum tables needed for auditability.

E.2 Example EvoCurr Evolution Path

To provide a granular view of the curriculum evolution process, Table 19 traces a representative curriculum path in the Terran vs. Protoss scenario. The progression demonstrates the adaptive Designer–Solver dynamics: beginning with a simple engagement of 5 Marines against 2 Zealots, the curriculum escalates through increasingly complex multi-unit compositions incorporating specialized roles such as Ghosts for detection and Siege Tanks for area control. When the Solver fails to achieve the acceptance threshold at Stage 3 with an ambitious 5-unit-type composition, the framework retreats to a simplified 4-unit configuration in Stage 4, re-establishing a 90% win rate before advancing again. This adaptive adjustment enables the system to reach the final task at Stage 6, where the agent commands a diverse 10-unit-type army against an 8-unit-type enemy force.

E.3 StarCraft II Mini-Game Maps

Figure 3: Conceptual illustration of the self-evolving curriculum tree in EvoCurr. The framework progressively grows task difficulty from simple starter seeds to the final high-quality complex tasks. By enforcing an accepted-floor constraint, the model efficiently prunes failed sub-paths and backs off to mastered checkpoints, preventing policy regression. Representative intermediate states from StarCraft II and Overcooked domains are illustrated on both sides.

Table 18: Winning rates (%) of curricula designed for the 12 complex decision-making scenarios.

Task	Task1	Task2	Task3	Task4	Task5	Task6	Task7
Flat (TvP)	100	100	70	90	100	-	-
Flat (TvZ)	100	100	100	100	100	-	-
Bush (TvP)	100	100	40	90	50	100	100
Bush (TvZ)	100	90	60	100	100	-	-
Corridor (TvP)	100	90	100	100	90	-	-
Corridor (TvZ)	100	90	90	100	100	-	-
Corner (TvP)	90	90	90	100	-	-	-
Corner (TvZ)	100	100	90	90	100	-	-
Main (TvP)	100	100	100	100	-	-	-
Main (TvZ)	100	100	100	100	-	-	-
Ramp (TvP)	100	100	90	100	100	-	-
Ramp (TvZ)	100	100	100	90	100	-	-

Table 19: **Curriculum Evolution Trace (Path 1).** Detailed breakdown of unit compositions from the initial task to the final complex scenario.

Stage	Composition (Agent vs Enemy)	Win Rate
1	**Agent:** Marine (5)
Enemy: Zealot (2, Charge)	90%
2	**Agent:** Marine (10), Marauder (5), Medivac (1)
Enemy: Zealot (5, Charge), Stalker (5, Blink), HighTemplar (1, PsiStorm)	90%
3	**Agent:** Marine (15), Marauder (8), Ghost (2), Medivac (2), SiegeTank (1)
Enemy: Zealot (10, Charge), Stalker (8, Blink), HighTemplar (2, PsiStorm), Colossus (1, ExtendedThermalLance)	Failed
4	**Agent:** Marine (12), Marauder (6), Ghost (1), Medivac (1)
Enemy: Zealot (8, Charge), Stalker (6, Blink), HighTemplar (1, PsiStorm)	90%
5	**Agent:** Marine (18), Marauder (10), Ghost (2), Medivac (2), SiegeTank (1), Viking (2)
Enemy: Zealot (12, Charge), Stalker (10, Blink), HighTemplar (2, PsiStorm), Colossus (1, ExtendedThermalLance)	90%
6	**Agent:** Marine (20), Marauder (12), Medivac (4), Ghost (8), SiegeTank (6), VikingFighter (8), Cyclone (7), WidowMine (7), Raven (3), Liberator (2)
Enemy: Zealot (15, Charge), Stalker (14, BlinkTech), Sentry (10, ForceField), HighTemplar (8, PsiStormTech), Colossus (4, ExtendedThermalLance), Tempest (5, GroundAttack), Disruptor (4, PurificationNova), Carrier (4, InterceptorLaunch)	100%

Figure 4: Flat map layout

Figure 5: Bush map layout

Figure 6: Terran vs Protoss on Flat

Figure 7: Terran vs Protoss on Bush

Figure 8: Terran vs Zerg on Flat

Figure 9: Terran vs Zerg on Bush

Figure 10: Corner map layout

Figure 11: Main map layout

Figure 12: Terran vs Protoss on Corner

Figure 13: Terran vs Protoss on Main

Figure 14: Terran vs Zerg on Corner

Figure 15: Terran vs Zerg on Main

Figure 16: Ramp map layout

Figure 17: Terran vs Protoss on Ramp

Figure 18: Terran vs Zerg on Ramp

F Overcooked Details

F.1 MARL Training Configuration

For the Overcooked experiments, we employ the E3T (Efficient End-to-End Training) algorithm (Yan et al., 2023) as our MARL training framework. The training configuration is detailed in Table 20.

F.2 Curriculum Design for Overcooked

The curriculum progression in Overcooked is structured around three key dimensions:

1. **Layout Complexity**: Starting from simple layouts (e.g., small_corridor) with direct paths between stations, progressing to complex layouts with obstacles and longer navigation requirements.

2. **Order Complexity**: Beginning with single-ingredient dishes, advancing to multi-ingredient recipes requiring precise coordination between agents.

3. **Temporal Constraints**: Initially allowing unlimited time for order completion, then introducing time pressure and simultaneous order requirements.

The acceptance criterion $\mathcal{P}(\pi|C) = 1$ is achieved when all required orders are completed

Table 20: Overcooked MARL training hyperparameters

Parameter	Value
Algorithm	E3T
Number of agents	2
Episode length	400
Number of environment steps per curriculum	10^7
PPO epochs	15
Number of mini-batches	1
Rollout threads	100
Evaluation threads	10
Evaluation interval	20 episodes
Entropy Regularization	
Entropy coefficients	[0.2, 0.05, 0.01]
Entropy coefficient horizons	$[0, 6 \times 10^6, 10^7]$
Network Architecture	
CNN layers	[(32, 3×3, stride=1), (64, 3×3, stride=1), (32, 3×3, stride=1)]
Recurrent policy	LSTM
Shared policy	True
E3T Specific	
Epsilon (diversity bonus)	0.25
Weights copy factor	0.1
Random index	Enabled
Curriculum-specific	
Reward shaping horizon	10^8
Budget per curriculum	10^7 timesteps

Figure 19: Overcooked Map 1.

Table 21: Map 1: Curriculum progression and performance metrics (A0 Del: Agent0 Delivery; A1 Del: Agent1 Delivery; Total: Total Delivery)

Task	Orders	A0 Del.	A1 Del.	Total	Reward
Task 0	3	11.75	12.33	24.08	239.2
Task 1	4	14.56	14.33	28.89	288.1
Task 2 (Final)	5	14.74	14.36	29.10	290.9
Direct Training	5	11.93	12.18	24.11	240.5

Table 22: Map 1: Key performance indicators for final task (A0: Agent0; A1: Agent1)

Metric	EvoCurr A0	EvoCurr A1	Direct A0	Direct A1
Onion in Pot	15.77	15.94	13.38	13.57
Tomato in Pot	0.31	0.32	0.21	0.26
Dish Pickup	7.81	7.63	6.15	6.34
Soup Pickup	7.68	7.55	6.31	6.33
Cook Actions	7.44	8.67	6.34	7.30
Delivery	7.37	7.19	5.99	6.11
Idle Move	9.40	8.68	14.90	15.10

1216 within the episode. After meeting this criterion, **1217** agents can pursue bonus orders to maximize total **1218** deliveries. The entropy regularization schedule en- **1219** sures exploration early in training (high entropy) **1220** while converging to more deterministic policies as **1221** training progresses.

1222 For layouts with particular navigation challenges **1223** (e.g., small_corridor), we adjust the entropy co- **1224** efficient horizons to $[0, 8 \times 10^6, 10^7]$ to allow **1225** for extended exploration before convergence. The **1226** shared policy architecture enables agents to learn **1227** cooperative behaviors more efficiently by sharing **1228** representations while maintaining individual action **1229** distributions.

G Overcooked Experimental Results **1230** **1231** Details

1232 This appendix provides detailed experimental re- **1233** sults for the Overcooked environment, showing the **1234** complete curriculum evolution and performance **1235** metrics for two different map configurations.

G.1 Map Configuration 1 **1236**

G.1.1 Final Layout Specification **1237**

```
{                                              1238
  "grid": "XXXPX                               1239
          X 2 P                                1240
          D1X X                                1241
          O   X                                1242
          XTSXX",                              1243
  "start_all_orders": [                        1244
   {"ingredients": ["onion", "tomato"]},       1245
    {"ingredients": ["onion", "onion"]},       1246
   {"ingredients": ["onion", "tomato", "tomato"]}, 1247
   {"ingredients": ["onion", "onion", "tomato"]}, 1248
   {"ingredients": ["onion", "onion", "onion"]} 1249
  ],                                           1250
  "recipe_value": [10, 10, 20, 20, 20],        1251
  "recipe_time": [10, 10, 20, 20, 20]          1252
}                                              1253
```

1254 Grid Legend: X=Wall, P=Pot, D=Dish, **1255** O=Onion, T=Tomato, S=Service

G.1.2 Curriculum Evolution Results **1256**

The Overcooked Map 1 evolution path and result **1257** details are shown in Table 21. **1258**

G.1.3 Detailed Performance Metrics **1259** Comparison **1260**

The Overcooked Map 1 result details and metrics **1261** are shown in Table 22. **1262**

Figure 20: Overcooked Map 2.

Table 23: Map 2: Curriculum progression and performance metrics (A0 Del: Agent0 Delivery; A1 Del: Agent1 Delivery; Total: Total Delivery)

Task	Ord.	A0 Del.	A1 Del.	Total	Reward
Task 0	3	7.28	7.25	14.53	290.3
Task 1	5*	7.32	7.28	14.60	291.6
Task 2 (Final)	5	7.82	10.82	18.64	186.2
Direct Training	5	7.40	8.96	16.36	163.4

G.2 Map Configuration 2

G.2.1 Final Layout Specification

```
{
  "grid": "XXXPDPXXX
          X    2    X
          X XXXXX X
          X    1    X
          XXXOSTXXX",
  "start_all_orders": [
    {"ingredients": ["onion", "tomato"]},
    {"ingredients": ["onion", "onion"]},
    {"ingredients": ["onion", "tomato", "tomato"]},
    {"ingredients": ["onion", "onion", "tomato"]},
    {"ingredients": ["onion", "onion", "onion"]}
  ],
  "recipe_value": [10, 10, 20, 20, 20],
  "recipe_time": [10, 10, 20, 20, 20]
}
```

Grid Legend: X=Wall, P=Pot, D=Dish, O=Onion, T=Tomato, S=Service

G.2.2 Curriculum Evolution Results

The Overcooked Map 2 evolution path and result details are shown in Table 23. Task 1 includes two single-ingredient recipes alongside complex recipes for an easier transition.

G.2.3 Detailed Performance Metrics Comparison

The Overcooked Map 2 result details and metrics are shown in Table 24.

Table 24: Map 2: Key performance indicators for final task (A0: Agent0; A1: Agent1)

Metric	EvoCurr		Direct	
	A0	A1	A0	A1
Onion in Pot	7.91	5.95	9.85	9.29
Tomato in Pot	3.17	3.87	0.08	0.07
Dish Pickup	5.45	4.20	4.32	4.81
Soup Pickup	4.12	5.62	4.24	4.79
Cook Actions	5.45	4.85	5.16	4.38
Delivery	3.92	5.42	3.71	4.49
Size-2 Del.	3.84	5.27	3.65	4.40
Size-3 Del.	0.07	0.14	0.05	0.08
Idle Move	14.42	14.21	10.49	11.28

H Claude Code Behavior-Tree Generation Details

H.1 Execution Results

Claude Code is evaluated as an autonomous coding-agent baseline. It generates its own intermediate curricula and iteratively edits the behavior-tree implementation using execution feedback.

Table 25: Claude Code execution outcomes on self-designed curricula and the held-out final task.

Task	Attempts	Outcome	Win rate
Curriculum 1	1	5W/0D/0L	**100%**
Curriculum 2	1	5W/0D/0L	**100%**
Curriculum 3	1	5W/0D/0L	**100%**
Curriculum 4	1	5W/0D/0L	**100%**
Curriculum 5	1	5W/0D/0L	**100%**
Final task	2	0W/1D/9L	**0%**

Final winning rate: 0%
Total time: ∼90 min
Evaluation budget: 100+ simulated matches

Despite passing all self-designed intermediate curricula, Claude Code does not solve the final target task within this budget. Its final evaluation produces 0 wins, 1 draw, and 9 losses.

H.2 Curriculum Generation Process

The following trajectory illustrates the intermediate curricula generated by Claude Code, ordered from easier to harder settings.

Table 26: Claude Code self-generated curriculum trajectory. Unit entries are written as *unit count (upgrade)*.

Step	Scenario Configuration
C1	**Friendly:** Marine 20 (Stimpack), Marauder 12 (Stimpack), Medivac 4 (Heal)
Enemy: Zealot 6 (Charge), Stalker 4 (BlinkTech)
C2	**Friendly:** Marine 20 (Stimpack), Marauder 12 (Stimpack), Medivac 4 (Heal)
Enemy: Zealot 10 (Charge), Stalker 8 (BlinkTech)
C3	**Friendly:** Marine 20 (Stimpack), Marauder 12 (Stimpack), Medivac 4 (Heal)
Enemy: Zealot 12 (Charge), Stalker 10 (BlinkTech), Sentry 4 (ForceField)
C4	**Friendly:** Marine 20 (Stimpack), Marauder 12 (Stimpack), Medivac 4 (Heal), Ghost 4 (PersonalCloaking)
Enemy: Zealot 12 (Charge), Stalker 10 (BlinkTech), HighTemplar 4 (PsiStormTech)
C5	**Friendly:** Marine 20 (Stimpack), Marauder 12 (Stimpack), Medivac 4 (Heal), Ghost 6 (PersonalCloaking), SiegeTank 4 (SiegeTech)
Enemy: Zealot 15 (Charge), Stalker 12 (Blink), HighTemplar 6 (PsiStorm), Colossus 2 (ExtThermalLance)

Prompt Template

```
You have a sc2 control task as
following:
AGENTS:
Marine: 20, (5,25), Stimpack
Marauder: 12, (5,25), Stimpack
Medivac: 4, (5,25), Heal
Ghost: 8, (5,25), PersonalCloaking
SiegeTank: 6, (5,25), SiegeTech
VikingFighter: 8, (5,25), AssaultMode
Cyclone: 8, (5,25), LockOn
WidowMine: 8, (5,25), Burrow
Raven: 3, (5,25), HunterSeeker
Liberator: 4, (5,25), DefenderMode

ENEMIES:
Zealot: 15, (25,5), Charge
Stalker: 15, (25,5), BlinkTech
Sentry: 10, (25,5), ForceField
HighTemplar: 9, (25,5), PsiStormTech
Colossus: 4,             (25,5),
   ExtendedThermalLance
Tempest: 5, (25,5), GroundAttack
Disruptor: 4, (25,5), PurificationNova
Carrier: 4, (25,5), InterceptorLaunch

You should design the curricula from
easy to hard to make sure the final
control code can win the final task.
You  can  change  environments  by
assigning  the  scenario_type  and
map_name in rollout_config.py.
Generate the control code and test
it in res-temp.py. Prefer changing
only the BattleBot class. Use the
evaluation feedback to revise the
policy.
When you pass the current curriculum
with a high winning rate, you can
design the next curriculum.
```

1311

H.4 Generated Code Sample 1312

```python
1  class BattleBot(BotAI):
2      """
3      Terran Auto-Micro Bot - Optimized Version
4      Strategy: Immediate Stimpack + Focus Fire Nearest
   ↪  Enemy + Simple Kiting + Medivac Healing
5      """
6
7      def __init__(self):
8          super().__init__()
9          self.stim_used = set()
10         self.started = False
11
12     async def on_step(self, iteration: int):
13         # Get units
14         marines = self.units(UnitTypeId.MARINE)
15         marauders = self.units(UnitTypeId.MARAUDER)
16         medivacs = self.units(UnitTypeId.MEDIVAC)
17         ghosts = self.units(UnitTypeId.GHOST)
18         tanks = self.units(UnitTypeId.SIEGETANK) |
   ↪  self.units(UnitTypeId.SIEGETANKSIEGED)
19
20         bio_units = marines | marauders
21         all_combat = bio_units | ghosts | tanks
22         enemies = self.enemy_units
23         enemy_pos = Point2((27, 27))
24
25         if not all_combat.exists:
26             return
27
28         # No enemies - quick attack
29         if not enemies.exists:
30             for unit in all_combat:
31                 unit.attack(enemy_pos)
32             for medivac in medivacs:
33                 medivac.move(enemy_pos)
34             return
35
36         # === Optimization 1: Stimpack immediately upon
   ↪  first enemy sight ===
37         if not self.started:
38             self.started = True
39             for unit in bio_units:
40                 if unit.health > 20:
41                     if unit.type_id == UnitTypeId.MARINE:
42                         unit(AbilityId.EFFECT_STIM_MARINE)
43                     elif unit.type_id ==
   ↪  UnitTypeId.MARAUDER:
44
   ↪  unit(AbilityId.EFFECT_STIM_MARAUDER)
45                     self.stim_used.add(unit.tag)
46
47         # === Optimization 2: Simplified target selection
   ↪  ===
48         low_health = enemies.filter(lambda u:
   ↪  u.health_percentage < 0.4)
49         if low_health.exists:
50             target =
   ↪  low_health.closest_to(bio_units.center)
51         else:
52             target = enemies.closest_to(bio_units.center)
53
54         # === Optimization 3: Kiting tactics ===
55         for unit in bio_units:
56             closest = enemies.closest_to(unit.position)
57             dist = unit.distance_to(closest)
58             # Maintain distance from melee units
59             if closest.type_id in [UnitTypeId.ZEALOT,
   ↪  UnitTypeId.ZERGLING]:
60                 if dist < 3:
61                     retreat_pos =
   ↪  unit.position.towards(closest.position, -4)
62                     unit.move(retreat_pos)
63                     continue
64             unit.attack(target)
65
66         # === Ghost EMP ===
67         for ghost in ghosts:
68             shielded = enemies.filter(lambda u: u.shield
   ↪  > 20)
69             if shielded.exists and ghost.energy >= 75:
70                 emp_target = max(shielded, key=lambda u:
   ↪  enemies.closer_than(3, u).amount)
71                 ghost(AbilityId.EMP_EMP,
   ↪  emp_target.position)
72             else:
73                 ghost.attack(target)
74
75         # === Tank Control ===
76         for tank in tanks:
77             if tank.type_id == UnitTypeId.SIEGETANK:
78                 closest =
   ↪  enemies.closest_to(tank.position)
79                 dist = tank.distance_to(closest)
80                 if 3 < dist < 13:
81                     tank(AbilityId.SIEGEMODE_SIEGEMODE)
82                 else:
83                     tank.attack(target)
84             else:  # SIEGETANKSIEGED
85                 if
   ↪  tank.distance_to(enemies.closest_to(tank)) < 3:
86                     tank(AbilityId.UNSIEGE_UNSIEGE)
87                 else:
88                     tank.attack(target)
89
90         # === Medivac Healing ===
91         for medivac in medivacs:
92             if bio_units.exists:
93                 injured = bio_units.filter(lambda u:
   ↪  u.health_percentage < 0.8)
94                 if injured.exists:
95                     heal_target = min(injured, key=lambda
   ↪  u: u.health)
96                     medivac(AbilityId.MEDIVACHEAL_HEAL,
   ↪  heal_target)
97                 else:
98                     medivac.move(bio_units.center)
```

I Computational Experiments

We measure the approximate API cost and wall-clock time required to solve a final SC2 task such as Bush (TvP). These measurements use closed-source model APIs and include all curriculum stages needed to reach the final task.

For DeepSeek-V3.1, completing one final task costs approximately \$0.2. For GPT-5 and Claude-4, the cost is approximately \$1.5.

Each individual curriculum stage requires approximately 5–30 minutes. A final task typically requires 4–6 sequential stages, for a total wall-clock time of approximately 1–3 hours.