CAB: Comprehensive Attention Benchmarking on Long Sequence Modeling

Abstract

Transformer has achieved remarkable success in language, image, and speech processing. Recently, various efficient attention architectures have been proposed to improve transformer's efficiency while largely preserving its efficacy, especially in modeling long sequences. A widely-used benchmark to test these efficient methods' capability on long-range modeling is Long Range Arena (LRA). However, LRA only focuses on bidirectional (or noncausal) self attention, and completely ignores cross attention and unidirectional (or causal) attentions, which are equally critical to downstream applications. Although designing cross and causal variants of an attention method is straightforward for vanilla attention, it is often challenging for efficient attentive models with subquadratic time and memory complexity. In this paper, we first present an attention taxonomy with four distinguishable attention patterns, namely, noncausal self, causal self, noncausal cross, and causal cross attentions. We then set up Comprehensive Attention Benchmark (CAB) with seven real-world tasks from different research areas to evaluate efficient attentive models under the four attention patterns. Among these tasks, CAB validates efficient attentive models in eight backbone networks with different inductive biases to show their generalization across neural architectures. We conduct exhaustive experiments to benchmark the performance of nine widely-used efficient attention architectures designed with different philosophies on CAB. Extensive experimental results also shed light on the fundamental problems of efficient attentive models, such as efficiency length against vanilla attention, performance consistency across attention patterns, the importance of noncausal self attention in information processing, and interpolation and extrapolation on long-context language modeling.

1 Introduction

Transformer has achieved great breakthroughs in natural language processing (Devlin et al., 2019; Radford et al., 2019; Brown et al., 2020), computer vision (Dosovitskiy et al., 2020; Liu et al., 2021b), speech processing (Schneider et al., 2019; Ren et al., 2021), and biology (Jumper et al., 2021; Brandes et al., 2022). Despite the great success, its main drawback is the quadratic computational complexity in both time and memory, which prevents Transformer from scaling to long sequence modeling.

Recently, a surge of efficient attentive models make significant progress to improve attention efficiency while preserving efficacy. (Wang et al., 2020; Kitaev et al., 2019; Zaheer et al., 2020; Choromanski et al., 2020; Zheng et al., 2022). These efficient attentive models mostly compete with each other on Long Range Arena (LRA) benchmark (Tay et al., 2020a). However, LRA only focuses on standard bidirectonal (or noncausal) self attention, and completely ignores the cross attention and unidirectional (or causal) attention, which are equally important and even more challenging. The cross attention is beneficial for conditionality modeling such as sequence-to-sequence (Bahdanau et al., 2014), data-to-text (Dušek et al., 2020) and knowledge-enhanced models (Liu et al., 2021a); the causal attention is critical for causality modeling in sequence generation such as text generation (Vaswani et al., 2017; Zhang et al., 2020), language modeling (Radford et al., 2019; Brown et al., 2020) and speech synthesis (Li et al., 2019).

To address these problems, we introduce an attention taxonomy, considering their functionality on conditionality and causality modeling. Under the taxonomy, we present four patterns of attentive models, namely, noncausal self, causal self, noncausal cross, and causal cross, representing distin-

guishable attentive functionality to sequence modeling. We then propose a comprehensive attention benchmark named CAB on long sequence modeling. CAB collects seven real-world tasks from diverse fields of computer vision, natural language processing, speech processing, and time series prediction. Among these tasks, CAB includes rich backbone models with different inductive biases to evaluate attentive models, which reflect their generalization across neural models. Given four attention patterns defined by the attention taxonomy, CAB advocates a pattern-wise comparison for attentive models, evaluating their attentive functionality independently.

We conduct exhaustive experiments on CAB, assessing attentive functionality of nine widely-used efficient attentive models designed with different philosophies. The experimental results show that existing efficient attentive models perform comparable or even superior to vanilla attention, but is less competitive in modeling conditionality and causality, especially for the causal cross scenario. It indicates that efficient attentive models' capability cannot generalize across attention patterns with different attentive functionality. Then we quantify the efficiency of attentive models by computing its efficiency length, which is the minimum length for a sub-quadratic efficient model to surpass vanilla attention in efficiency. The efficiency length reveals the underlying training inefficiency problem of existing efficient attention methods in causality modeling. We also perform attention ablation on backbone neural models and surprisingly observe that on several models, removing noncausal self attention modules does not harm model performance. Besides, we investigate interpolation and extrapolation on a long-context language model, and find that it is promising for efficient attention, such as LongShort Transformer, to scale to long-context language modeling. All the experimental code of CAB will be released at https://github.com/Anonymous.

2   ATTENTION TAXONOMY

Attention methods are designed to capture token-to-token dependency within and across sequences. Let $Y = \{y_1, y_2, \ldots, y_n\}$ and $\mathbf{Y} \in \mathbb{R}^{n \times d}$ be a target sequence and its feature matrix, and $X = \{x_1, x_2, \ldots, x_m\}$ and $\mathbf{X} \in \mathbb{R}^{m \times d}$ be a source sequence and its feature matrix, where n and m are target and source sequence lengths respectively, and d denotes dimensionality. Note that $\mathbf{X}$ could be the same as $\mathbf{Y}$ in the case of self attention. The target and source feature matrices are transformed to **Q**uery-**K**ey-**V**alue feature matrices as $\mathbf{Q} = \mathbf{Y}W_{\mathbf{Q}}, \mathbf{K} = \mathbf{X}W_{\mathbf{K}}, \mathbf{V} = \mathbf{X}W_{\mathbf{V}}$ with learnt parametric matrices $W_{\mathbf{Q}}, W_{\mathbf{K}}, W_{\mathbf{V}}$. Vanilla transformer (Vaswani et al., 2017) learns to integrate key-value feature matrices $\mathbf{K} \in \mathbb{R}^{m \times d}, \mathbf{V} \in \mathbb{R}^{m \times d}$ into a query one $\mathbf{Q} = \{\mathbf{q}_1, \mathbf{q}_2, \ldots, \mathbf{q}_n\} \in \mathbb{R}^{n \times d}$ with multihead token-to-token attention:

$$\mathrm{Attn}(\mathbf{Q}, \mathbf{K}, \mathbf{V}) = \mathrm{softmax}\left(\mathbf{Q}\mathbf{K}^{\top}/\sqrt{d}\right)\mathbf{V} \tag{1}$$

in which we omit the multihead notation without loss of generality. Vanilla attentive model in Eq. 1 advocates a token-to-token alignment matrix $\mathbf{Q}\mathbf{K}^{\top}$, which results in quadratic complexity $O(nm)$ of computational time and memory usage. It is observed that $\mathrm{Attn}(\cdot)$ in Eq. 1 acts as an integration model, projecting query features $\mathbf{Q}$ by integrating key-value features without changing $\mathbf{Q}$'s shape. Beyond the vanilla token-to-token attention mechanism, we extend Eq. 1 to a more general form of attentive model family as:

$$\begin{aligned} \mathrm{Attn}(\mathbf{Q}, \mathbf{K}, \mathbf{V}) &= f(\mathbf{Q}; \mathbf{K}, \mathbf{V}) : \mathbb{R}^{n \times d} \rightarrow \mathbb{R}^{n \times d} \\ \text{where } \mathrm{Attn}_i(\mathbf{Q}, \mathbf{K}, \mathbf{V}) &= f_i(\mathbf{q}_i; \mathbf{Q}, \mathbf{K}, \mathbf{V}), i = 1 \ldots n \end{aligned} \tag{2}$$

where $\mathbf{Q}$ is treated as the main variable and $\mathbf{K}, \mathbf{V}$ are conditional ones. Comparing with Eq. 1, Eq. 2 covers efficient attention methods without explicitly modeling the token-to-token alignment. In usage, attentive models are modified to fit generative models with underlying structures, such as conditional models and causal models, to achieve specific attentive functionality.

In this section, we put forward an attention taxonomy, considering the conditionality and causality of attentive models. We show their challenges and potential impact on real-world applications in modeling conditionality and causality. Under the taxonomy, we present four attention patterns with different attentive functionality as shown in Figure 1.

Self Attention & Cross Attention   Self attention (Lin et al., 2017; Vaswani et al., 2017; Dosovitskiy et al., 2020) learns contextual features within a sequence whereas cross attention (Bahdanau et al., 2014) learns to integrate features across sequences. Both self attention and cross attention are highly

Figure 1: Computation diagrams for (a) noncausal self, (b) causal self, (c) noncausal cross, (d) causal cross attentions. Shaded blocks represent future tokens that are invisible to the current state. Blocks with red rims represent the current state token.

effective in sequence learning, but designing cross-attention is more challenging for efficient attentive models without explicit token-to-token alignment. On the aspect of computation, $\mathbf{Q} \in \mathbb{R}^{n \times d}$ and $\mathbf{K}, \mathbf{V} \in \mathbb{R}^{m \times d}$ are of different shapes, and are impossible to perform elementwise operations along length dimension, such as cross-covariance as XCiT (Ali et al., 2021). Besides, different from self attention, cross attention lacks implicit alignment between $\mathbf{Q}$ and $\mathbf{K}, \mathbf{V}$, such as neighboring information. Cross-attention learns to integrate conditional features $\mathbf{K}, \mathbf{V}$ into the main features $\mathbf{Q}$, and impacts on real-world applications, such as machine translation (Bahdanau et al., 2014; Vaswani et al., 2017), data-to-text generation (Dušek et al., 2020; Shen et al., 2020) and knowledge enhanced model (Jin et al., 2020; Liu et al., 2021a).

Noncausal Attention & Causal Attention   While modeling a sequence, noncausal models have a holistic view of the whole sequence whereas causal ones only access to previous tokens up to now [1]. This restriction forbids efficient attention like Nyströmformer (Xiong et al., 2021b), which must condition on the whole target sequence to achieve linearity, to be applied in causal models. Furthermore, when training a causal model, efficient attention such as RFA (Peng et al., 2021) and ABC (Peng et al., 2022) have to provide different sets of features from $\mathbf{X}$ for each query token. This mechanism in these attentive models, therefore, leads to multiplied memory consumption compared to their noncausal counterparts. We provide a detailed analysis of the increasing computation costs in Appendix B. In real-world applications, causal attentive models brings up strong generation capability and is widely adopted in text generation (Bahdanau et al., 2014; Vaswani et al., 2017; Zhang et al., 2020), text-to-speech synthesis (Li et al., 2019) and language modeling (Radford et al., 2019; Brown et al., 2020; Raffel et al., 2020; Chen et al., 2021).

Attention Patterns   As discussed above, conditionality and causality are two orthogonal aspects of modeling sequences. Thus we obtain four attention patterns via Cartesian product as $\{\text{noncausal}, \text{causal}\} \times \{\text{self}, \text{cross}\}$: noncausal self (NS), causal self (CS), noncausal cross (NC), and causal cross (CC) ones. Following the general form of attentive models in Eq. 2, we formulate the four attention patterns as below:

$$\text{NS}_i(\mathbf{Q}, \mathbf{K}, \mathbf{V}) \triangleq f_i(\boldsymbol{q}_i; \mathbf{Q}, \mathbf{K}, \mathbf{V}), s.t. \ \mathbf{Y} = \mathbf{X} \tag{3}$$

$$\text{CS}_i(\mathbf{Q}, \mathbf{K}, \mathbf{V}) \triangleq f_i(\boldsymbol{q}_i; \mathbf{Q}_{\leq i}, \mathbf{K}_{\leq i}, \mathbf{V}_{\leq i}), s.t. \ \mathbf{Y} = \mathbf{X} \tag{4}$$

$$\text{NC}_i(\mathbf{Q}, \mathbf{K}, \mathbf{V}) \triangleq f_i(\boldsymbol{q}_i; \mathbf{Q}, \mathbf{K}, \mathbf{V}) \tag{5}$$

$$\text{CC}_i(\mathbf{Q}, \mathbf{K}, \mathbf{V}) \triangleq f_i(\boldsymbol{q}_i; \mathbf{Q}_{\leq i}, \mathbf{K}, \mathbf{V}) \tag{6}$$

Fig. 1 illustrates the computation diagrams of these four patterns. These attention patterns construct typical sequence models with attention mechanisms. For instance, Transformer (Vaswani et al., 2017) adopt NS attention in encoder, and CS/CC ones in decoder; recently prevailing Non-Autoregressive Transformer (Gu et al., 2018) models adopt NS attention in the encoder, and NS/NC attention in the decoder. Previous efficient attention benchmark LRA only tests attentive models with the NS pattern but without the others, leading to an insufficient evaluation of attentive functionality. In the subsequent sections, we will introduce a comprehensive attention benchmark CAB that evaluates attentive models comprehensively on the four patterns.

---

[1]When generating a sequence $Y = \{y_1, y_2, \ldots, y_n\}$ autoregressively, neural models (Vaswani et al., 2017; Li et al., 2019; Brown et al., 2020) usually adopt a causal graph $\mathcal{G}(V, E)$ with vertices $V = \{y_i \in Y\}$ and edges $E = \{y_i \rightarrow y_j | i \in [1, \ldots, n], j \in [1, \ldots, n], i \leq j\}$.

Table 1: Task statistics of evaluation metrics, backbone neural networks and their supported attention patterns. For the encoder-decoder framework, there are two values of source and target lengths, otherwise, there is only one value.

Task	Dataset	Length	Model	Metric	Noncausal Self	Causal Self	Noncausal Cross	Causal Cross
TTS	LJSpeech	559	FastSpeech2	MCD MSD	✔	✗	✗	✗
		500/559	Transformer-TTS		✔	✔	✗	✔
Sum	Multi-News	4,096/400	Transformer	ROUGE	✔	✔	✗	✔
LSTF	ETT	336/720	Informer	MSE MAE	✔	✗	✔	✗
	ECL	336/960						
	Weather	720/720						
PCC	PCN	1,536/3,584	PoinTr	CD F-Score	✔	✗	✔	✗
LM	PG-19	8,192	GPT2	PPL	✗	✔	✗	✗
MLM		2,048	RoBERTa-base		✔	✗	✗	✗
SR	FFHQ CelebA-HQ	16,384	SR3	PSNR SSMI	✔	✗	✗	✗

3 COMPREHENSIVE ATTENTION BENCHMARK

In this section, we propose Comprehensive Attention Benchmark (CAB) that collects seven tasks covering four research fields, including computer vision, natural language processing, speech processing, and time series prediction. We introduce these tasks with their datasets, input/output sizes, backbone neural networks as well as evaluation metrics. Then we present *ranking*-based and *score*-based indexes to combine individual task performance into a compositional one for direct performance comparison across tasks and models.

3.1 LONG SEQUENCE MODELING TASKS

We collect seven real-world long-sequence modeling tasks in CAB with data sizes from 300 to 16,000 and include eight widely-used models as backbones in CAB to assess typical efficient attention mechanisms against different inductive biases. Table 1 epitomizes the tasks' statistics, evaluation metrics, backbone neural networks and the required attention patterns in §2 are also checkedf.

Text-to-Speech Synthesis (TTS) This task requires models to convert input text sequences, descriptions, or narrations produced by a single speaker, to synthesized audio clips sharing the same timbre as the provided speaker. The CAB incorporates the LJSpeech dataset (Ito, 2017) whose audio clips are sampled with 22,050 Hz. Under this set of relatively high sample rates, the average sequence length of processed audio clips is 559. We use non-autoregressive FastSpeech2 (Ren et al., 2021) and autoregressive Transformer-TTS (Li et al., 2019) as backbone networks. We adopt Mean Cepstral Distortion (MCD) and Mel Spectral Distortion (MSD) for objective evaluation.

Summarization (Sum) This task is one that makes a comprehensive summary of multiple input documents without losing important information. We consider multi-document summarization task and use Multi-News datasets (Fabbri et al., 2019) for long sequence modeling. To make the task more challenging, we set the maximum source text and target summary lengths to be 4,096 and 400, respectively. Transformer (Vaswani et al., 2017) serves the evaluating backbone and ROUGE (R-N) (Lin, 2004) is used to evaluate each attentive model.

Long Time-Series Forecasting (LTSF) Long time-series forecasting is to predict long-term future behavior based on past states. This task evaluates models on three datasets, including Electricity Transformer Temperature (ETT), Electricity Consuming Load (ECL), and Weather (Zhou et al., 2021). Following (Zhou et al., 2021), we also conduct univariate and multivariate evaluations and average their Mean Square Error (MSE) and Mean Absolute Error (MAE) to obtain the final scores.

Table 2: Overview of 9 efficient attentions. The complexity is discussed under the self-noncausal setting and we omit the independent factor *w.r.t.* the target length n. ($*$) denotes these attention architectures perform differently with their released paper, which is illustrated in Appendix A.

Method	Attention Name	Complexity	Noncausal Self	Causal Self	Noncausal Cross	Causal Cross
Sparsity	local attention	$O(n)$	✔	✔	✗	✗
Kernel	LARA	$O(n)$	✔	✗	✗	✗
	cosFormer $*$	$O(n)$	✔	✗	✔	✗
	Performer $*$	$O(n)$	✔	✗	✔	✔
Low-rank factorization	Nyströmformer	$O(n)$	✔	✗	✗	✗
Prototype	ABC	$O(n)$	✔	✔	✔	✔
	ProbSparse	$O(n \log n)$	✔	✗	✗	✗
Hybrid	LongShort	$O(n)$	✔	✔	✗	✗
State space	S4D	$O(n)$	✔	✗	✗	✗

Point Cloud Completion (PCC)   This task is to complete a frame of point cloud data when providing partial points. CAB adopts PCN dataset (Griffiths & Boehm, 2019) which inputs 2,048 3D point coordinates and requires models to output the complete point cloud data comprising 14,336 points. PoinTr (Yu et al., 2021) is adopted here serving as evaluating backbone. Chamfer Distance (CD) (Yuan et al., 2018; Tchapmi et al., 2019; Xie et al., 2020; Huang et al., 2020) and F-Score (Tatarchenko et al., 2019) are selected to evaluate each attentive model. For clearer comparison, CD metrics are enlarged by 1,000 times.

Language Modeling (LM)   The language modeling task requires the language model to predict the next text based on the previous information. In this task, we consider a long-context language modeling where the context length is prolonged to 8,192. We use PG-19 dataset (Rae et al., 2019) for evaluating language models. Perplexity (PPL) is used to serve as the evaluation metric.

Masked Language Modeling (MLM)   Different from the language modeling task, masked language modeling (Devlin et al., 2019) uses full context to predict masked tokens. Roberta-base (Liu et al., 2019) is adopted as the evaluation backbone. We use the same dataset and evaluation metric as LM task while the context length is set to 2,048.

Super-Resolution (SR)   In this task, we aims to convert low-resolution (16×16) face images into high-resolution (128×128) images. Following Saharia et al. (2021), we train super-resolution models on Flickr-Faces-HQ (FFHQ) dataset (Karras et al., 2019) and evaluate them on CelebA-HQ dataset (Karras et al., 2018). Peak Signal-to-Noise Ratio (PSNR) and Structural SIMilarity (SSIM) (Wang et al., 2004) are selected to evaluate models from different aspects.

3.2 COMPOSITIONAL INDEXES

We compute a compositional index (*CI*) from seven tasks for performance comparison. *CI* is a normalized score to balance the influence among evaluation metrics, and is computed as follows: a) we transform all evaluation metrics beforehand, so that a higher score indicates better performance; b) we then normalize each transformed metric with Z-score normalization $\widetilde{s}_{ij}^k = (s_{ij}^k - \mu_j^k)/\sigma_j^k$ where i, j and k denote attentive model, task and corresponding evaluation metric respectively; c) after normalization, the normalized score of each evaluation metric is averaged within each task, and is further averaged across tasks. We includes details of CI in Appendix C.

4 EXPERIMENTS

We conduct exhaustive experiments on CAB by applying various efficient attentive models to the backbone models and measure their performance under noncausal self, causal self, noncausal cross, and causal cross patterns. We extensively study the fundamental problems of efficient attentive

Table 3: Experimental results on CAB with (a) noncausal self, (b) causal self, (c) noncausal cross, and (d) causal cross attention pattern. ($-$) denotes that the method fails on the task. (†) denotes that the attention is trained with fp32.

Method	TTS				Sum			SR		MLM	CI
	FastSpeech2		Transformer-TTS		Transformer			SR3		RoBERTa	
	MCD↓	MSD↓	MCD↓	MSD↓	R-1↑	R-2↑	R-L↑	PSNR↑	SSMI↑	PPL↓	
vanilla	3.475	1.974	4.095	2.199	34.61	6.35	31.66	23.18	0.675	3.42	-0.024
local	3.419	1.970	4.015	2.164	**38.50**	**10.54**	**35.39**	23.33	0.682	4.18	**0.978**
ABC	3.393	1.966	4.085	2.204	33.80	6.07	30.98	22.54	0.635	10.5	-0.686
LARA	3.463	2.012	4.116	2.209	34.03	6.23	31.23	23.35	0.685	6.45	-0.032
cosFormer†	3.400	1.956	4.030	2.160	34.77	6.34	31.74	**23.53**	**0.690**	5.25	0.466
ProbSparse	3.363	1.946	4.034	2.161	34.62	6.36	31.64	22.98	0.667	186.35	-0.661
Performer	3.437	1.983	4.115	2.198	34.85	6.54	31.88	23.34	0.682	111.73	-0.285
LongShort	3.436	1.996	**3.913**	**2.136**	34.35	6.41	31.55	23.28	0.681	**3.38**	0.269
Nyströmformer	3.557	2.036	4.274	2.276	34.45	6.30	31.56	23.20	0.679	6.32	-0.440
S4D†	**3.303**	**1.905**	4.017	2.195		-		23.35	0.682	25.34	-0.147

(a)

Method	TTS		Sum			LM	CI
	Transformer-TTS		Transformer			GPT-2	
	MCD↓	MSD↓	R-1↑	R-2↑	R-L↑	PPL↓	
vanilla	4.095	2.198	**34.61**	**6.35**	**31.66**	-	-0.814
local	4.141	2.220	33.50	6.27	30.74	19.73	-0.239
LongShort	**4.039**	2.195	33.55	6.27	30.71	**15.52**	**0.617**
ABC	4.058	**2.189**	30.17	5.48	27.92	29.13	-0.623

(b)

Method	PCC			LTSF						CI
	PoinTr			Informer						
	CD-ℓ_1↓	CD-ℓ_2↓	F-Score↑	ETT		Weather		ECL		
				MSE↓	MAE↓	MSE↓	MAE↓	MSE↓	MAE↓	
vanilla	7.425	0.231	0.779	**1.138**	**0.775**	0.478	0.508	**0.449**	**0.486**	**0.596**
ABC	**7.344**	**0.227**	**0.784**	1.147	0.809	0.489	0.52	0.519	0.527	0.204
Performer	7.368	0.235	0.783	1.254	0.819	**0.463**	**0.508**	0.881	0.722	0.014
cosFormer	8.673	0.298	0.704	1.219	0.823	0.474	0.509	0.632	0.590	-0.815

(c)

Method	TTS		Sum			CI
	Transformer-TTS		Transformer			
	MCD↓	MSD↓	R-1↑	R-2↑	R-L↑	
vanilla	**4.095**	**2.198**	**34.61**	**6.35**	**31.66**	**0.956**
ABC	5.780	2.631	32.22	5.55	29.53	0.057
Performer	6.635	3.053	27.22	3.88	25.21	-1.014

(d)

models, in terms of performance consistency across attention patterns, efficiency quantification, interpolation and extrapolation on long-context language model, and attention ablation. The details of experimental settings for tasks are shown in Appendix D.

4.1 EFFICIENT ATTENTION MODULES

We benchmark 9 typical efficient attentive models designed with different philosophies, including sparse attention (**local attention** (Luong et al., 2015)), kernel-based linearized attention (**Performer** (Choromanski et al., 2020), **cosFormer** (Qin et al., 2021), **LARA** (Zheng et al., 2022)), low-rank factorization (**Nyströmformer** (Xiong et al., 2021b)), prototype (**ABC** (Peng

Figure 2: Empirical running time (a) and memory cost (b) with sequence length, and efficiency lengths (c) of attention architectures compared to vanilla attention. Relative measurements to vanilla attention are reported. Performer and ABC have efficiency lengths of 1 on memory usage and running time, respectively.

et al., 2022) [2], **ProbSparse** (Zhou et al., 2021)), hybrid attention (**LongShort Transformer** (Zhu et al., 2021)), and state space (**S4D** (Gu et al., 2022)) and evaluate these attention architectures in terms of different attention patterns described in §2. We provide a brief overview of these attention architectures in Table 2 and leave a detailed description in Appendix. F.

4.2 MAIN RESULTS

The main results are shown in Table 3. It is observed that efficient attention achieves comparable performance with vanilla attention under noncausal self attention patterns, and some of them even surpass vanilla attention. It suggests that the current efficient attention indeed improves the ability to learn contextual features in long sequences of various modalities. Although the performance of efficient attention is remarkable in the noncausal self pattern, it is less competitive in the other three patterns. As shown in Table 3d, causal cross attentive models are extremely hard to design and are inferior to vanilla attention by a significant margin. Due to the challenge of causality modeling, it is notable that compared with autoregressive models (i.e. Transformer and Transformer-TTS), non-autoregressive or parallel generation models (i.e. FastSpeech2, SR3, and RoBERTa) are more promising to have their efficient variants without significant performance drops.

On the dimension of efficient attention, we find that local attention is a strongly competitive efficient model on most real-world tasks although it is utterly defeated in LRA. It achieves the highest score of 0.978 under the noncausal self pattern and ranks the second under the causal self pattern. In contrast, S4D, which achieves impressive results on LRA, is scored -0.147 under the noncausal self pattern which is less inspiring than expected on the real-world tasks.

4.3 EFFICIENCY ANALYSIS

We conduct a simulation efficiency experiment on noncausal and causal self attention. The experiment is performed on a single A100 GPU, where attention mechanisms are fed a set of dummy sequences with a batch size of 12 and lengths of $\{256, 512, 1024, 2048, 4096, 8192\}$. Table 2 shows the time and memory consumption against sequence length by each attentive models. We can find that the advantage of efficient attention gradually expands as the sequence length increases. Moreover, the kernel-based and low-rank attentions are more effcient on time and space.

Further, we report *efficiency length* to measure the utility of efficient attentive models. The efficiency length is defined as the intersection point of computational time and memory curves by efficient models and vanilla attention. The efficiency length represents the minimum length that a sub-quadratic efficient model surpasses the vanilla attention in efficiency. Specifically, we perform regression on vanilla and efficient attentions by their theoretical complexity. Then we calculate the intersection of the regression line and the quadratic regression curve to get an efficiency length.

---

[2]We implement and experiment ABC with its fast version as suggested by Peng et al. (2022).

Figure 3: (a) Pairwise attention pattern correlation where NS, CS, NC, and CC signify noncausal self, causal self, noncausal cross, and causal cross attention respectively; (b) Ablation study of removing attention. The gray part is the score achieved by the existing efficient attention family, where we select the most well-performed efficient attention for each task; (c) the performance of efficient attentions based on different context lengths in the LM task during the test phase.

Fig 2c shows that efficient attentions gain their superiority over vanilla attention once the sequence contains thousands of tokens. For noncausal self attention, ABC and Performer have the shortest efficiency lengths on running time and memory usage, respectively. consistently, and Performer consumes lower memory than vanilla attention at any length. For causal self attention, LongShort has lower memory usage than vanilla attention at any length. Although local has a shorter efficiency length than other attentions to run faster than vanilla attention, it still requires sequences longer than 4000. The details of efficiency lengths and experiment setting can be found in Appendix G.

4.4 PERFORMANCE INCONSISTENCY ACROSS ATTENTION PATTERNS

We investigate whether attentive models perform consistently across different tasks and backbone neural models. To achieve this, compute Pearson correlation (Benesty et al., 2009) over CI between each pair of attention patterns against the same arrangement of efficient attentions[3] for intra-benchmark comparison. Note that we also include CI computed from LRA for inter-benchmark comparison between CAB's NS attention pattern and LRA.

In Figure 3a, CAB's NS attention pattern is highly correlated with LRA, reflecting that efficient NS attentive models developed on LRA do contribute to real-world applications. In contrast, cross attention patterns share non-positive correlations with self attention patterns, indicating their inconsistent performance on self and cross attention[4]. On the causality dimension, the performances of causal and noncausal models are highly related but not strictly consistent. We also include task-to-task correlation analysis in Appendix I.

4.5 ATTENTION ABLATION

Self attention is designed to capture context features while cross attention integrates non-homologous information. But how much do these features benefit the model? We conduct an ablation study without the attention mechanism. In a preliminary experiment, we find that causal and cross patterns are indispensable to the backbone models as expected, while noncausal self attention only has a limited contribution. Therefore, we focus on discussing the attentive functionality of noncausal self attention Figure 3b depicts the CI of backbone models with and without attention on tasks. Detailed *CI* can be found in Appendix H. Embarrassingly, after removing the attention mechanism, the PoinTr and Informer achieve improvement on PCC and LTSF tasks, respectively. A possible reason is that there are alternative contextualizing structures such as the convolutional neural network in the backbone models and the contribution of the attention mechanism is weakened. Besides, we also notice that the current efficient attention family has already surpassed vanilla attention in modeling noncausal self relationships on most tasks.

---

[3]The order is [vanilla, local, ABC, LARA, cosFormer, ProbSparse, Performer, LongShort, Nyströmformer, S4D]

[4]The negative correlation here is biased due to limited exploration on causal and cross efficient attentions.

4.6 INTERPOLATION AND EXTRAPOLATION ON LONG-CONTEXT LANGUAGE MODELING

Language models with efficient attentions are more likely to face unexpected long context that exceeds predefined lengths, resulting in an extrapolation problem. It is critical for efficient attentions to scale to longer sequences while preserving the performance on short ones. Therefore, we conduct an experiment on the language modeling task, where we train the model with the input of 8,192 tokens and calculate perplexity of contexts with 256-16, 384 tokens in test. Figure 3c shows the results on both of interpolation and extrapolation. On the one hands, as the size of context grows until 8,192, language models achieves decreasing perplexity. It means that longer context indeed improves language modeling, and efficient attentions do well in interpolation as expected. On the other hands, for sequence with more than 8,192 tokens, the perplexity of all these efficient attention-equipped language model becomes higher. Notably, local attention and LongShort with local features have only a slight drop in performance in extrapolation, while ABC with only global features fails to extrapolate to longer sequence.

5 RELATED WORK

Long sequence modeling Most efficient attention architectures are designed for long sequence modeling. Previous works evaluate their proposed attention modules separately on Language Model (Qin et al., 2021; Choromanski et al., 2020; Peng et al., 2022), Masked Language Model (Qin et al., 2021; Peng et al., 2022), Image Classification (Choromanski et al., 2020; Zheng et al., 2022), and Machine Translation (Peng et al., 2022; 2021). Without unified criteria for evaluating attention modules, researchers find it hard to distinguish between them and select an appropriate attention module for their research. Later, Tay et al. (2020a) proposed Long Range Arena (LRA), a benchmark that contains 5 different classification tasks across language and image domains, to evaluate the capability of attention. However, their benchmark contains most synthetic tasks and the performance on these tasks is quite different from that on real-world tasks. Besides, different attention modules perform nearly equally on LRA (Xiong et al., 2021a), which causes LRA a limited benchmark.

Efficient attention The emergence and prevalence of Transformer models (Vaswani et al., 2017) as well as its strong capability for encoding and generation have imposed impressiveness on various applications. Previous work also explored other attention modules that can replace the softmax attention in Transformer models, including sparse attention (Ainslie et al., 2020; Beltagy et al., 2020; Guo et al., 2019a), low-rank attention (Chen et al., 2020; Guo et al., 2019b; Xiong et al., 2021b), kernel-based linearized attention (Choromanski et al., 2020; Katharopoulos et al., 2020), prototype attention (Zhou et al., 2021; Vyas et al., 2020), prior attention (Ying et al., 2021; Tay et al., 2021; Zhang et al., 2018), and memory compress (Wang et al., 2020; Lee et al., 2019; Liu* et al., 2018). For interested readers, we refer them to Lin et al. (2021); Tay et al. (2020b) for a more detailed description of efficient attention.

6 CONCLUSION

In this paper, we create a taxonomy for attentive models with four distinguishable attention patterns, each of which reflects different attentive functionality. Under the taxonomy, we present Comprehensive Attention Benchmark (CAB), consisting seven real-world tasks and eight backbone networks with different inductive biases. We conduct exhaustive experiments to benchmark nine typical efficient attentive models on CAB. The empirical results show that existing efficient attentions make significant progress in noncausal self attention, but are still struggling to catch up with vanilla attention in conditional and causality modeling. The efficiency analysis shows that although existing efficient attentions enjoy lower computational complexity, most of them cannot achieve significant efficiency gain when applying to sequences with less than one thousand tokens, especially in the causal attention scenario. Moreover, we find that attention mechanisms, in the noncausal self case, are sometimes not helpful or even harmful to neural models that already contain feature integration modules as convolutional blocks. An extensive experiment sheds light on long-context language modeling and shows that efficient attention such as LongShort Transformer is promising for extrapolation problems in language modeling.

REFERENCES

Joshua Ainslie, Santiago Ontanon, Chris Alberti, Vaclav Cvicek, Zachary Fisher, Philip Pham, Anirudh Ravula, Sumit Sanghai, Qifan Wang, and Li Yang. ETC: Encoding long and structured inputs in transformers. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 268–284, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.19. URL https://aclanthology.org/2020.emnlp-main.19.

Alaaeldin Ali, Hugo Touvron, Mathilde Caron, Piotr Bojanowski, Matthijs Douze, Armand Joulin, Ivan Laptev, Natalia Neverova, Gabriel Synnaeve, Jakob Verbeek, et al. Xcit: Cross-covariance image transformers. *Advances in neural information processing systems*, 34:20014–20027, 2021.

Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate. *arXiv preprint arXiv:1409.0473*, 2014.

Iz Beltagy, Matthew E Peters, and Arman Cohan. Longformer: The long-document transformer. *arXiv preprint arXiv:2004.05150*, 2020.

Jacob Benesty, Jingdong Chen, Yiteng Huang, and Israel Cohen. Pearson correlation coefficient. In *Noise reduction in speech processing*, pp. 1–4. Springer, 2009.

Nadav Brandes, Dan Ofer, Yam Peleg, Nadav Rappoport, and Michal Linial. Proteinbert: A universal deep-learning model of protein sequence and function. *Bioinformatics*, 38(8):2102–2110, 2022.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 1877–1901. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/1457c0d6bfcb4967418bfb8ac142f64a-Paper.pdf.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, et al. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*, 2021.

Ziye Chen, Mingming Gong, Lingjuan Ge, and Bo Du. Compressed self-attention for deep metric learning with low-rank approximation. In Christian Bessiere (ed.), *Proceedings of the Twenty-Ninth International Joint Conference on Artificial Intelligence, IJCAI-20*, pp. 2058–2064. International Joint Conferences on Artificial Intelligence Organization, 7 2020. doi: 10.24963/ijcai.2020/285. URL https://doi.org/10.24963/ijcai.2020/285. Main track.

Krzysztof Marcin Choromanski, Valerii Likhosherstov, David Dohan, Xingyou Song, Andreea Gane, Tamas Sarlos, Peter Hawkins, Jared Quincy Davis, Afroz Mohiuddin, Lukasz Kaiser, et al. Rethinking attention with performers. In *International Conference on Learning Representations*, 2020.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL https://aclanthology.org/N19-1423.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2020.

Ondřej Dušek, Jekaterina Novikova, and Verena Rieser. Evaluating the state-of-the-art of end-to-end natural language generation: The e2e nlg challenge. *Computer Speech & Language*, 59:123–156, 2020.

Alexander Fabbri, Irene Li, Tianwei She, Suyi Li, and Dragomir Radev. Multi-news: A large-scale multi-document summarization dataset and abstractive hierarchical model. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 1074–1084, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1102. URL https://aclanthology.org/P19-1102.

David Griffiths and Jan Boehm. A review on deep learning techniques for 3d sensed data classification. *Remote Sensing*, 11(12):1499, 2019.

Albert Gu, Tri Dao, Stefano Ermon, Atri Rudra, and Christopher Ré. Hippo: Recurrent memory with optimal polynomial projections. *Advances in Neural Information Processing Systems*, 33: 1474–1487, 2020.

Albert Gu, Ankit Gupta, Karan Goel, and Christopher Ré. On the parameterization and initialization of diagonal state space models. *arXiv preprint arXiv:2206.11893*, 2022.

Jiatao Gu, James Bradbury, Caiming Xiong, Victor O.K. Li, and Richard Socher. Non-autoregressive neural machine translation. In *International Conference on Learning Representations*, 2018.

Qipeng Guo, Xipeng Qiu, Pengfei Liu, Yunfan Shao, Xiangyang Xue, and Zheng Zhang. Star-transformer. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 1315–1325, Minneapolis, Minnesota, June 2019a. Association for Computational Linguistics. doi: 10.18653/v1/N19-1133. URL https://aclanthology.org/N19-1133.

Qipeng Guo, Xipeng Qiu, Xiangyang Xue, and Zheng Zhang. Low-rank and locality constrained self-attention for sequence modeling. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 27(12):2213–2222, 2019b. doi: 10.1109/TASLP.2019.2944078.

Zitian Huang, Yikuan Yu, Jiawen Xu, Feng Ni, and Xinyi Le. Pf-net: Point fractal network for 3d point cloud completion. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 7662–7670, 2020.

Keith Ito. The lj speech dataset. https://keithito.com/LJ-Speech-Dataset/, 2017.

Hanqi Jin, Tianming Wang, and Xiaojun Wan. Semsum: Semantic dependency guided neural abstractive summarization. *Proceedings of the AAAI Conference on Artificial Intelligence*, 34 (05):8026–8033, Apr. 2020. doi: 10.1609/aaai.v34i05.6312. URL https://ojs.aaai.org/index.php/AAAI/article/view/6312.

John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with alphafold. *Nature*, 596(7873):583–589, 2021.

Tero Karras, Timo Aila, Samuli Laine, and Jaakko Lehtinen. Progressive growing of gans for improved quality, stability, and variation. In *International Conference on Learning Representations*, 2018.

Tero Karras, Samuli Laine, and Timo Aila. A style-based generator architecture for generative adversarial networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

Angelos Katharopoulos, Apoorv Vyas, Nikolaos Pappas, and François Fleuret. Transformers are RNNs: Fast autoregressive transformers with linear attention. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 5156–5165. PMLR, 13–18 Jul 2020.

Nikita Kitaev, Lukasz Kaiser, and Anselm Levskaya. Reformer: The efficient transformer. In *International Conference on Learning Representations*, 2019.

Juho Lee, Yoonho Lee, Jungtaek Kim, Adam Kosiorek, Seungjin Choi, and Yee Whye Teh. Set transformer: A framework for attention-based permutation-invariant neural networks. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 3744–3753. PMLR, 09–15 Jun 2019. URL https://proceedings.mlr.press/v97/lee19d.html.

Naihan Li, Shujie Liu, Yanqing Liu, Sheng Zhao, and Ming Liu. Neural speech synthesis with transformer network. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 6706–6713, 2019.

Chin-Yew Lin. Rouge: A package for automatic evaluation of summaries. In *Text summarization branches out*, pp. 74–81, 2004.

Tianyang Lin, Yuxin Wang, Xiangyang Liu, and Xipeng Qiu. A survey of transformers. *arXiv preprint arXiv:2106.04554*, 2021.

Zhouhan Lin, Minwei Feng, Cicero Nogueira dos Santos, Mo Yu, Bing Xiang, Bowen Zhou, and Yoshua Bengio. A structured self-attentive sentence embedding. 2017.

Peter J. Liu*, Mohammad Saleh*, Etienne Pot, Ben Goodrich, Ryan Sepassi, Lukasz Kaiser, and Noam Shazeer. Generating wikipedia by summarizing long sequences. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=Hyg0vbWC-.

Ye Liu, Yao Wan, Lifang He, Hao Peng, and Philip S. Yu. Kg-bart: Knowledge graph-augmented bart for generative commonsense reasoning. *Proceedings of the AAAI Conference on Artificial Intelligence*, 35(7):6418–6425, May 2021a. doi: 10.1609/aaai.v35i7.16796. URL https://ojs.aaai.org/index.php/AAAI/article/view/16796.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 10012–10022, 2021b.

Thang Luong, Hieu Pham, and Christopher D. Manning. Effective approaches to attention-based neural machine translation. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pp. 1412–1421, Lisbon, Portugal, September 2015. Association for Computational Linguistics. doi: 10.18653/v1/D15-1166. URL https://aclanthology.org/D15-1166.

Hao Peng, Nikolaos Pappas, Dani Yogatama, Roy Schwartz, Noah A Smith, and Lingpeng Kong. Random feature attention. *arXiv preprint arXiv:2103.02143*, 2021.

Hao Peng, Jungo Kasai, Nikolaos Pappas, Dani Yogatama, Zhaofeng Wu, Lingpeng Kong, Roy Schwartz, and Noah A. Smith. ABC: Attention with bounded-memory control. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 7469–7483, Dublin, Ireland, May 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.acl-long.515. URL https://aclanthology.org/2022.acl-long.515.

Zhen Qin, Weixuan Sun, Hui Deng, Dongxu Li, Yunshen Wei, Baohong Lv, Junjie Yan, Lingpeng Kong, and Yiran Zhong. cosformer: Rethinking softmax in attention. In *International Conference on Learning Representations*, 2021.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

Jack W Rae, Anna Potapenko, Siddhant M Jayakumar, Chloe Hillier, and Timothy P Lillicrap. Compressive transformers for long-range sequence modelling. In *International Conference on Learning Representations*, 2019.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, Peter J Liu, et al. Exploring the limits of transfer learning with a unified text-to-text transformer. *J. Mach. Learn. Res.*, 21(140):1–67, 2020.

M Kafaei Razavi, Asghar Kerayechian, Mortaza Gachpazan, and Stanford Shateyi. A new iterative method for finding approximate inverses of complex matrices. In *Abstract and Applied Analysis*, volume 2014. Hindawi, 2014.

Yi Ren, Chenxu Hu, Xu Tan, Tao Qin, Sheng Zhao, Zhou Zhao, and Tie-Yan Liu. Fastspeech 2: Fast and high-quality end-to-end text to speech. In *International Conference on Learning Representations*, 2021.

Chitwan Saharia, Jonathan Ho, William Chan, Tim Salimans, David J Fleet, and Mohammad Norouzi. Image super-resolution via iterative refinement. *arXiv preprint arXiv:2104.07636*, 2021.

Steffen Schneider, Alexei Baevski, Ronan Collobert, and Michael Auli. wav2vec: Unsupervised pre-training for speech recognition. In *INTERSPEECH*, 2019.

Dinghan Shen, Guoyin Wang, Wenlin Wang, Martin Renqiang Min, Qinliang Su, Yizhe Zhang, Chunyuan Li, Ricardo Henao, and Lawrence Carin. Baseline needs more love: On simple word-embedding-based models and associated pooling mechanisms. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 440–450, Melbourne, Australia, July 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-1041. URL https://aclanthology.org/P18-1041.

Xiaoyu Shen, Ernie Chang, Hui Su, Jie Zhou, and Dietrich Klakow. Neural data-to-text generation via jointly learning the segmentation and correspondence. *arXiv preprint arXiv:2005.01096*, 2020.

Maxim Tatarchenko, Stephan R Richter, René Ranftl, Zhuwen Li, Vladlen Koltun, and Thomas Brox. What do single-view 3d reconstruction networks learn? In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 3405–3414, 2019.

Yi Tay, Mostafa Dehghani, Samira Abnar, Yikang Shen, Dara Bahri, Philip Pham, Jinfeng Rao, Liu Yang, Sebastian Ruder, and Donald Metzler. Long range arena: A benchmark for efficient transformers. In *International Conference on Learning Representations*, 2020a.

Yi Tay, Mostafa Dehghani, Dara Bahri, and Donald Metzler. Efficient transformers: A survey. *ACM Computing Surveys (CSUR)*, 2020b.

Yi Tay, Dara Bahri, Donald Metzler, Da-Cheng Juan, Zhe Zhao, and Che Zheng. Synthesizer: Rethinking self-attention for transformer models. In *International conference on machine learning*, pp. 10183–10192. PMLR, 2021.

Lyne P Tchapmi, Vineet Kosaraju, Hamid Rezatofighi, Ian Reid, and Silvio Savarese. Topnet: Structural point cloud decoder. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 383–392, 2019.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Apoorv Vyas, Angelos Katharopoulos, and François Fleuret. Fast transformers with clustered attention. *Advances in Neural Information Processing Systems*, 33:21665–21674, 2020.

Sinong Wang, Belinda Z Li, Madian Khabsa, Han Fang, and Hao Ma. Linformer: Self-attention with linear complexity. *arXiv preprint arXiv:2006.04768*, 2020.

Zhou Wang, Alan C Bovik, Hamid R Sheikh, and Eero P Simoncelli. Image quality assessment: from error visibility to structural similarity. *IEEE transactions on image processing*, 13(4):600–612, 2004.

Haozhe Xie, Hongxun Yao, Shangchen Zhou, Jiageng Mao, Shengping Zhang, and Wenxiu Sun. Grnet: Gridding residual network for dense point cloud completion. In *European Conference on Computer Vision*, pp. 365–381. Springer, 2020.

Wenhan Xiong, Barlas Oğuz, Anchit Gupta, Xilun Chen, Diana Liskovich, Omer Levy, Wen-tau Yih, and Yashar Mehdad. Simple local attentions remain competitive for long-context tasks. *arXiv preprint arXiv:2112.07210*, 2021a.

Yunyang Xiong, Zhanpeng Zeng, Rudrasis Chakraborty, Mingxing Tan, Glenn Fung, Yin Li, and Vikas Singh. Nyströmformer: A nyström-based algorithm for approximating self-attention. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pp. 14138–14148, 2021b.

Chengxuan Ying, Guolin Ke, Di He, and Tie-Yan Liu. Lazyformer: Self attention with lazy update. *arXiv preprint arXiv:2102.12702*, 2021.

Xumin Yu, Yongming Rao, Ziyi Wang, Zuyan Liu, Jiwen Lu, and Jie Zhou. Pointr: Diverse point cloud completion with geometry-aware transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 12498–12507, October 2021.

Wentao Yuan, Tejas Khot, David Held, Christoph Mertz, and Martial Hebert. Pcn: Point completion network. In *2018 International Conference on 3D Vision (3DV)*, pp. 728–737. IEEE, 2018.

Manzil Zaheer, Guru Guruganesh, Kumar Avinava Dubey, Joshua Ainslie, Chris Alberti, Santiago Ontanon, Philip Pham, Anirudh Ravula, Qifan Wang, Li Yang, et al. Big bird: Transformers for longer sequences. *Advances in Neural Information Processing Systems*, 33:17283–17297, 2020.

Biao Zhang, Deyi Xiong, and Jinsong Su. Accelerating neural transformer via an average attention network. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1789–1798, Melbourne, Australia, July 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-1166. URL https://aclanthology.org/P18-1166.

Jingqing Zhang, Yao Zhao, Mohammad Saleh, and Peter Liu. Pegasus: Pre-training with extracted gap-sentences for abstractive summarization. In *International Conference on Machine Learning*, pp. 11328–11339. PMLR, 2020.

Lin Zheng, Chong Wang, and Lingpeng Kong. Linear complexity randomized self-attention mechanism. *arXiv preprint arXiv:2204.04667*, 2022.

Haoyi Zhou, Shanghang Zhang, Jieqi Peng, Shuai Zhang, Jianxin Li, Hui Xiong, and Wancai Zhang. Informer: Beyond efficient transformer for long sequence time-series forecasting. *Proceedings of the AAAI Conference on Artificial Intelligence*, 35(12):11106–11115, May 2021. URL https://ojs.aaai.org/index.php/AAAI/article/view/17325.

Chen Zhu, Wei Ping, Chaowei Xiao, Mohammad Shoeybi, Tom Goldstein, Anima Anandkumar, and Bryan Catanzaro. Long-short transformer: Efficient transformers for language and vision. *Advances in Neural Information Processing Systems*, 34:17723–17736, 2021.

A   WHY COSFORMER AND PERFORMER CANNOT DO CAUSAL TASKS WITH LINEARITY?

cosFormer   requires a cos-reweighting mechanism to behave like vanilla softmax attention. However, their reweighting mechanism needs the maximum length of the source and target sequences in Eq. 16. This operation requires different L values for each token of $\mathbf{Q}$ and $\mathbf{K}$, which is ignored in their released repository [5]. If we change the implementation to enable each token to have a different value L, the time and space complexity during training will increase to $O(n^2)$.

Performer   uses random feature matrices to project $\mathbf{Q}$ and $\mathbf{K}$ to latent space. However, during the transformation of $\mathbf{K}$ with the softmax kernel, their repository [6] uses the golden target sequence length to project each key token, instead of using the token index of the key sequence as the actual target sequence length. This operation brings inconsistency between training and inference because during inference, the golden target sequence length is unavailable. And similar to cosFormer, if we use different random feature matrices for different key tokens, the complexity during training also increases to $O(n^2)$.

B   INCREASE OF COMPUTATIONAL COSTS FOR CAUSAL EFFICIENT MODELS

In this section, we use an efficient attention example RFA (Peng et al., 2021) to illustrate causality brings an increase in computation for efficient attention. In RFA, the noncausal version models the query $\boldsymbol{q}_t$ as:

$$\text{RFA}(\boldsymbol{q}_t, \{\boldsymbol{k}_i\}, \{\boldsymbol{v}_i\}) = \frac{\phi(\boldsymbol{q}_t)^\top \sum_i \phi(\boldsymbol{k}_i) \otimes \boldsymbol{v}_i}{\phi(\boldsymbol{q}_t) \sum_j \phi(\boldsymbol{k}_j)} \tag{7}$$

$$= \frac{\phi(\boldsymbol{q}_t)^\top \mathbf{S}_t}{\phi(\boldsymbol{q}_t) \cdot \mathbf{z}_t} \tag{8}$$

where $\mathbf{S}_t \in \mathbb{R}^{2D \times d}$ and $\mathbf{z}_t \in \mathbb{R}^d$ and $2D$ is the dimensionality of kernel ϕ. In its causal version, the hidden state $\mathbf{S}_t$ and $\mathbf{z}_t$ are recurrently modified to maintain the causality:

$$\mathbf{S}_t = \mathbf{S}_{t-1} + \phi(\boldsymbol{k}_t) \otimes \boldsymbol{v}_t \quad \mathbf{z}_t = \mathbf{z}_{t-1} + \phi(\boldsymbol{k}_t) \tag{9}$$

These recurrent operations add additional $O(ndD)$ time and memory consumption than noncausal models.

C   COMPOSITIONAL INDEX

Denote an attentive model as i-th model, and a task as j-th task, the k-th metric to evaluate the task is denoted as s_{ij}^k, where $k = 1, \ldots, K$. Compositional index (*CI*) first normalizes each metric s_{ij}^k to its normalized score $\overline{s}_{ij}^k$ following $\overline{s}_{ij}^k = \frac{s_{ij}^k - \mu_j^k}{\sigma_j^k}$ if s_{ij}^k signifies excellence when its value is lower. Those metrics that denotes high performance when their values are higher are converted as such: $\overline{s}_{ij}^k = \frac{\mu_j^k - s_{ij}^k}{\sigma_j^k}$. After this normalization, we again average the normalized score of each metric within each task to obtain $\tilde{x}_{ij} = \frac{\sum_{k=1}^K s_{ij}^k}{K}$, which is further converted to final score $\overline{x}_i = \frac{\sum_{j=1}^M \tilde{x}_{ij}}{M}$. This score is finally ranked to obtain rankings for each attentive model.

D   HYPERPARAMETERS

Hyperparameters for all tasks are shown in Table 4.

---

[5]https://github.com/OpenNLPLab/cosFormer/blob/main/cosformer.py#L106
[6]https://github.com/google-research/google-research/blob/master/performer/fast_attention/tensorflow/fast_attention.py#L190

Table 4: Hyperparameters for the tasks in CAB.

Task	TTS Synthesis	LSTF			Point Cloud Completion	Summarization	LM	MLM	Super Resolution
Data	LJSpeech	ETT	ECL	Weather	PCN	Multi-News	PG-19		FFHQ CelebA-HQ
Batch Size	48	32			48	64	16	256	4
Number of Steps	20K	6 (epochs)			300 (epochs)	50K	125K	125K	1M
Warmup Steps	4K	-			4K	1K	10K	5K	-
Peak Learning Rate	5e-4	1e-4			5e-4	5e-4	5e-4	3e-4	1e-4
Scheduler	Inverse Sqrt	Exponential Decay			LamdaLR	Inverse Sqrt	Inverse Sqrt	Polynomial Decay	Linear
Optimizer	AdamW	AdamW			AdamW	AdamW	AdamW	AdamW	AdamW
Adam	(0.9, 0.98)	(0.9, 0.999)			(0.9, 0.98)	(0.9, 0.98)	(0.9, 0.999)	(0.9, 0.98)	(0.9, 0.999)
Clip Norm	5.0	0.0			0.0	0.0	0.0	0.0	0.0
Attention Dropout	0.1	0.05			0.0	0.1	0.1	0.1	0.2
Weight Decay	0.01	0.0			5e-4	0.01	0.01	0.01	0.0
Tokens per Batch	-	-			-	-	2^{17}	2^{19}	-
Iteration	-	5	3	3	-	-	-	-	-

Table 5: Hyperparameters for various efficient attentions under noncausal self attention pattern (a), causal self attention pattern (b), noncausal cross attention pattern (c), and causal cross attention pattern (d). (*) We find that the performance of LongShort with num_landmarks = 64 is significantly lower than its performance with num_landmarks = 16 on Sum task under the noncausal self attention pattern. So we finally use LongShort with num_landmarks = 16.

Method	Hyperparameters	TTS	Sum	SR	MLM
local	wsize	31	31	31	31
ABC	num_landmarks	64	64	16	16
LARA	num_landmarks	64	64	16	16
ProbSparse	factor	5	5	5	5
Performer	approx_attn_dim	64	64	16	16
LongShort	wsize	16	16	16	16
	num_landmarks	64	16*	16	16
	conv_kernel_size	5		-	
Nyströmformer	num_landmarks	64	64	16	16
	conv_kernel_size	5		-	
S4D	d_state	64	64	16	16
cosFormer	-			-	

(a)

Method	Hyperparameters	TTS	Sum	LM
local	wsize		16	
LongShort	num_landmarks		64	
ABC	num_landmarks		64	

(b)

Method	Hyperparameters	PCC	LSTF
ABC	num_landmarks	64	16
Performer	approx_attn_dim	64	16
cosFormer	-		-

(c)

Method	Hyperparameters	TTS	Sum
ABC	num_landmarks	64	64
Performer	approx_attn_dim	64	64

(d)

E   TASK SCORE FOR COMPARISON

We show the compositional index of each task in Table 6. The means and standard deviations of metrics are shown in the Table 7, Table 8, Table 9, and Table 10.

F   DETAILED DESCRIPTION OF 9 EFFICIENT ARCHITECTURES

We here only present the self-noncausal forms of these efficient architectures.

Local Attention   Local attention (Luong et al., 2015) intuitively forces each query token to attend its neighborhood tokens within a fixed window size w to reduce the computation cost. In the full attention map, the neighborhood tokens contribute a large proportion of the attention score for the querying token (Qin et al., 2021). Therefore, local attention intuitively selects $w + 1$ ($2w + 1$ for noncausal self) tokens around a querying token to serve as $\mathbf{K}_w$ and $\mathbf{V}_w$. Its formulation is as follows:

$$\text{Local}(\boldsymbol{q}_i, \mathbf{K}_w, \mathbf{V}_w) = \text{softmax}(\boldsymbol{q}_i \mathbf{K}_w^\top) \mathbf{V}_w \tag{10}$$

Table 6: Compositional index. We use the mean and variance of the metric to take the 95% confidence lower bound as the score for the attention mechanism that fails on the task, as shown by the red score.

Method	NS				CS			NC		CC	
	TTS	Sum	SR	MLM	TTS	Sum	LM	PCC	LTSF	TTS	Sum
vanilla	-0.301	-0.246	-0.077	0.527	-0.047	0.784	-3.178	0.449	0.744	1.047	0.867
local	0.362	2.617	0.421	0.515	-1.361	0.337	0.305				
ABC	0.043	-0.678	-2.525	0.414	0.707	-1.461	-1.117	0.573	-0.164	-0.112	0.228
LARA	-0.639	-0.522	0.554	0.479							
cosFormer	0.516	-0.190	1.042	-0.498				-1.496	-0.135		
ProbSparse	0.705	-0.246	-0.697	-2.408							
Performer	-0.282	-0.088	0.439	-1.211				0.473	-0.445	-0.935	-1.094
LongShort	0.572	-0.322	0.298	0.528	0.701	0.340	0.812				
Nyströmformer	-2.011	-0.321	0.088	0.481							
S4D	1.035	-2.250	0.457	0.176							

where $\mathbf{K}_w, \mathbf{V}_w \in \mathbb{R}^{w \times d}$ denotes the neighborhood tokens within w size around the querying token in $\mathbf{K}$ and $\mathbf{V}$. The complexity is $O(nwd)$ and when w is predefined and independent of n, local attention is of linear complexity. Due to the locality setting, local attention is competent only at self-causal and self-noncausal when no locality is found at cross attention.

Nyströmformer Nyströmformer (Xiong et al., 2021b) adopts the Nyström method to approximate the softmax attention matrix. To perform this method, it selects r landmarks for $\mathbf{Q}$ and $\mathbf{K}$ with Segment-means (Shen et al., 2018) and produces $\widetilde{\mathbf{Q}}$ and $\widetilde{\mathbf{K}}$. Using iterative Moore-Penrose pseudoinverse (Razavi et al., 2014), Nyströformer decomposes the softmax attention matrix into three sub-softmax matrices as follows:

$$\text{Nyströmformer}(\mathbf{Q}, \mathbf{K}, \mathbf{V}) = \text{softmax}(\mathbf{Q}\widetilde{\mathbf{K}}^\top)(\text{softmax}(\widetilde{\mathbf{Q}}\widetilde{\mathbf{K}}^\top))^+ \text{softmax}(\widetilde{\mathbf{Q}}\mathbf{K}^\top)\mathbf{V} \quad (11)$$

where $(\text{softmax}(\widetilde{\mathbf{Q}}\widetilde{\mathbf{K}}^\top))^+$ is the Moore-Penrose pseudoinverse of $\text{softmax}(\widetilde{\mathbf{Q}}\widetilde{\mathbf{K}}^\top)$. The overall computation costs $O(nrd + rrd + nrd) = O(nrd)$ when r is predefined. Moore-Penrose pseudoinverse is also linear with respect to n when iteration time is a constant. Because it needs to select the same number of landmarks for $\mathbf{Q}$ and $\mathbf{K}$ and requires the full $\mathbf{Q}$ matrix, it is only adaptable in non-causal self-attention.

Performer Performer (Choromanski et al., 2020) is another linear transformer that uses *random feature map* $\phi(\cdot) : \mathbb{R}^d \to \mathbb{R}^r_+$ (for some $r > 0$) as a kernel function to reduce computational complexity. Formally, the random feature map is defined to approximate the exponential kernel as

$$\exp(\boldsymbol{q}_i^\top \boldsymbol{k}_j) = \mathbb{E}_q[\phi(\boldsymbol{q}_i)^\top \phi(\boldsymbol{k}_j)], \quad (12)$$

where $\phi(\boldsymbol{x}) = \exp(W_r \boldsymbol{x} - \frac{1}{2}\|\boldsymbol{x}\|^2 \mathbf{1}_r) \in \mathbb{R}^r$ and all elements of W_r are independently drawn from a standard Gaussian $q(w) = \mathcal{N}(w; 0, 1)$. Given the defined random feature map, the whole softmax attention for each query can then be approximated as

$$\sum_{j=1}^m \frac{\exp(\boldsymbol{q}_i^\top \boldsymbol{k}_j)\boldsymbol{v}_j}{\sum_{j'=1}^m \exp(\boldsymbol{q}_i^\top \boldsymbol{k}'_j)} \approx \frac{\phi(\boldsymbol{q}_i)^\top \sum_{j=1}^m \phi(\boldsymbol{k}_j)\boldsymbol{v}_j^\top}{\phi(\boldsymbol{q}_i)^\top \sum_{j'=1}^m \phi(\boldsymbol{k}'_j)} = \text{Performer}(\boldsymbol{q}_i, \mathbf{K}, \mathbf{V}) \quad (13)$$

Thanks to the kernel approximation, Performer can achieve $O(nrd)$ complexity in both self-noncausal and cross-noncausal attention; however, for causal self-attention and causal cross-attention, Performer has to store the cumulative summation for both $\sum_{j=1}^m \phi(\boldsymbol{k}_j)\boldsymbol{v}_j$ and $\sum_{j=1}^m \phi(\boldsymbol{k}_j)$, which requires a dedicated CUDA operator to accelerate the computation.

LARA LARA (Zheng et al., 2022) further extends the random feature approximation from estimating individual exponential kernels to directly estimating the whole softmax function. In particular, Zheng et al. (2022) proved that there exists a distribution p that instantiates the random feature such that

$$\sum_{j=1}^m \frac{\exp(\boldsymbol{q}_i^\top \boldsymbol{k}_j)\boldsymbol{v}_j^\top}{\sum_{j'=1}^m \exp(\boldsymbol{q}_i^\top \boldsymbol{k}'_j)} = \mathbb{E}_p \left[\sum_{j=1}^m \frac{\phi(\boldsymbol{q}_i)^\top \phi(\boldsymbol{k}_j)\boldsymbol{v}_j^\top}{\sum_{j'=1}^m \phi(\boldsymbol{q}_i)^\top \phi(\boldsymbol{k}'_j)} \right]. \quad (14)$$

Table 7: The means and standard deviations for noncausal self pattern evaluation.

Method	TTS				Sum			SR		MLM
	FastSpeech2		Transformer-TTS		Transformer			SR3		RoBERTa
	MCD	MSD	MCD	MSD	R-1	R-2	R-L	PSNR	SSMI	PPL
μ	3.425	1.974	4.069	2.190	34.89	6.79	31.96	23.21	0.676	36.292
σ	0.068	0.036	0.094	0.038	1.396	1.410	1.314	0.274	0.015	62.308

Table 8: The means and standard deviations for causal self pattern evaluation.

Method	TTS		Sum			LM
	Transformer-TTS		Transformer			GPT-2
	MCD	MSD	R-1	R-2	R-L	PPL
μ	4.083	2.200	32.96	6.09	30.26	22.26
σ	0.045	0.013	1.927	0.410	1.619	8.299

By viewing softmax attention as an expectation over a potentially complicated distribution p, Zheng et al. (2022) noted that Performer can be understood as performing self-normalized importance sampling to approximate this expectation, with standard Gaussian as the proposal distribution. LARA generalizes this view by adopting multiple adaptive proposal distributions to further improve the approximation fidelity. It is shown that LARA takes the following form

$$\text{LARA}\,(\boldsymbol{q}_n, \mathbf{K}, \mathbf{V}) = \frac{\phi(\boldsymbol{q}_n)^\top A_n \sum_{j=1}^m \phi(\boldsymbol{k}_j) \boldsymbol{v}_j^\top}{\phi(\boldsymbol{q}_n)^\top A_n \sum_{j'=1}^m \phi(\boldsymbol{k}_{j'})}, \tag{15}$$

where A_n is a query-specific diagonal matrix that ensures the computation overall still yields a valid self-normalized importance sampling estimation; and the elements of sampled W_r in $\phi(\boldsymbol{x}) = \exp(W_r \boldsymbol{x} - \frac{1}{2}\|\boldsymbol{x}\|^2 \mathbf{1}_r)$ are allowed to be drawn from different distributions beyond standard Gaussian.

cosFormer Following the same method defined in Eq. 13, cosFormer (Qin et al., 2021) adopts another kernel function $\text{ReLU}(\cdot)$ instead of random feature map. Due to the importance of the softmax operator that can ensure the non-negativeness of value weights and stabilize the training process, cosFormer designed a new *cos*-based reweighting mechanism similar to softmax. Denote $\boldsymbol{q}_i' = \text{ReLU}(\boldsymbol{q}_i)$ and $\boldsymbol{k}_j' = \text{ReLU}(\boldsymbol{k}_j)$, the re-weight formula is expressed as follows:

$$s(\boldsymbol{q}_i, \boldsymbol{k}_j) = \boldsymbol{q}_i^\top \boldsymbol{k}_j \cos(\frac{\pi}{2} \times \frac{i-j}{L}) \tag{16}$$

where $L = \max(n, m)$. Using this formula and Ptolemy's theorem, the final expression of cosFormer is as follows:

$$\text{cosFormer}(\boldsymbol{q}_i, \mathbf{K}, \mathbf{V}) = \frac{\sum_{j=1}^m \boldsymbol{q}_i^{\cos}((\boldsymbol{k}_j^{\cos})^\top \boldsymbol{v}_j) + \sum_{j=1}^m \boldsymbol{q}_i^{\sin}((\boldsymbol{k}_j^{\sin})^\top \boldsymbol{v}_j)}{\sum_{j=1}^m (\boldsymbol{q}_i^{\cos})^\top \boldsymbol{k}_j^{\cos} + \sum_{j=1}^m (\boldsymbol{q}_i^{\sin})^\top \boldsymbol{k}_j^{\sin}} \tag{17}$$

where $\boldsymbol{q}_i^{\cos} = \boldsymbol{q}_i \cos(\frac{\pi i}{2L})$, $\boldsymbol{q}_i^{\sin} = \boldsymbol{q}_i \sin(\frac{\pi i}{2L})$, $\boldsymbol{k}_j^{\cos} = \boldsymbol{k}_j \cos(\frac{\pi j}{2L})$, $\boldsymbol{k}_j^{\sin} = \boldsymbol{k}_j \sin(\frac{\pi j}{2L})$. Similar to Performer, it can efficiently fulfill self-noncausal and cross-noncausal attention with linear complexity $O(nd^2)$, but its causal attention relies on a specialized CUDA operator to achieve high efficiency. **[the notational inconsistency needs to be fixed: the vectors in cosFormer are of shape $1 \times d$ but in Performer vectors are of shape $d \times 1$. –lin]**

LongShort Transformer LongShort Transformer (Zhu et al., 2021) models the long-range and short-term dependency of a sequence with two different methods discussed above. For long-range modeling, it utilizes the low-rank property of the softmax function to convert key and value to a more compact representation using a learnable matrix $W^P \in \mathbb{R}^{d \times r}$: $\overline{\mathbf{K}} = P^\top \mathbf{K} \in \mathbb{R}^{r \times d}$ and $\overline{\mathbf{V}} = P^\top \mathbf{V} \in \mathbb{R}^{r \times d}$ where $P = \text{softmax}(\mathbf{K} W^P)$ and r is the compressed dimension. For short-term modeling, it borrows local attention to output a token representation fused with neighborhood

Table 9: The means and standard deviations for noncausal cross pattern evaluation.

Method	PCC			LSTF					
	PoinTr			Informer					
				ETT		Weather		ECL	
	CD-ℓ_1	CD-ℓ_2	F-score	MSE	MAE	MSE	MAE	MSE	MAE
μ	7.702	0.247	0.762	1.189	0.806	0.476	0.511	0.620	0.581
σ	0.647	0.033	0.039	0.056	0.021	0.010	0.006	0.189	0.103

Table 10: The means and standard deviations for causal cross pattern evaluation.

Method	TTS		Sum		
	Transformer-TTS		Transformer		
	MCD	MSD	R-1	R-2	R-L
μ	5.503	2.627	31.35	5.26	28.80
σ	1.292	0.427	3.771	1.260	3.286

features via segment-wise local attention. Let l be the segment length and $s_i = \lfloor \frac{i}{l} \rfloor$ be the segment id for i-th token, segment-wise local attention produces $\mathbf{K}_w = \mathbf{K}_{(s_i-1)l+\frac{l}{2}:(s_i+1)l+\frac{l}{2}}$ and $\mathbf{V}_w = \mathbf{V}_{(s_i-1)l+\frac{l}{2}:(s_i+1)l+\frac{l}{2}}$. Combined with these two methods, the output of LongShort Transformer is formalized as below:

$$\text{LongShort}(\boldsymbol{q}_i, \mathbf{K}, \mathbf{V}) = \text{softmax}(\boldsymbol{q}_i[\mathbf{K}_w; \overline{\mathbf{K}}]^\top)[\mathbf{V}_w; \overline{\mathbf{V}}] \tag{18}$$

where $[\cdot; \cdot]$ is a concatenation operator at the first dimension. The complexity $O(nrd + nwd)$ is also linear *w.r.t.* the sequence length. Due to its introduction of local attention, LongShort Transformer can only complete self-causal and self-noncausal tasks.

ProbSparse Attention ProbSparse (Zhou et al., 2021) calculates attention scores for few $(\mathbf{Q}, \mathbf{K})$ dot-product pairs based on sparsity of self-attention scores. Specifically, ProbSparse selects some "important" queries whose attention distributions on keys are non-uniform. Then we only need to calculate the attention scores between the "important" queries and all keys and output the weighted sum of $\mathbf{V}$. For other trivial queries, ProbSparse takes the mean of $\mathbf{V}$ as the output.

To distinguish the "important" queries, ProbSparse first samples some keys $\overline{\mathbf{K}}$, and then measures the sparsity of query q_i by $\bar{M}\left(\mathbf{q}_i, \overline{\mathbf{K}}\right)$ as follows:

$$\bar{M}\left(\mathbf{q}_i, \overline{\mathbf{K}}\right) = \max_j \left\{ \frac{\mathbf{q}_i \bar{\mathbf{k}}_j^\top}{\sqrt{d}} \right\} - \frac{1}{L_K} \sum_{j=1}^{L_K} \frac{\mathbf{q}_i \bar{\mathbf{k}}_j^\top}{\sqrt{d}} \tag{19}$$

where L_K denotes the number of keys. Finally, the Top-u queries with large $\bar{M}\left(\mathbf{q}_i, \overline{\mathbf{K}}\right)$ are the "important" queries.

ABC (MLP) ABC (MLP) (Peng et al., 2022) adopts another way to approximate softmax attention. It bounds the amount of memory slot for $\mathbf{K}$ and $\mathbf{V}$ to be $r < n$, independent of m. ABC uses a learnable matrix to fill each memory slot with reweighted key and value representations:

$$\widetilde{\mathbf{K}} = \text{softmax}(W_\phi^K \mathbf{K}^\top)\mathbf{K}, \quad \widetilde{\mathbf{V}} = \text{softmax}(W_\phi^V \mathbf{V}^\top)\mathbf{V}$$

where $W_\phi^K, W_\phi^V \in \mathbb{R}^{r \times d}$ is a learnable matrix representing the bounded memory with limit $r < m$.
Leveraging the bounded representation $\widetilde{\mathbf{K}}$ and $\widetilde{\mathbf{V}}$, ABC (MLP) executes following softmax attention:

$$\text{ABC}_{\text{MLP}}(\boldsymbol{q}_i, \mathbf{K}, \mathbf{V}) = \text{softmax}(\boldsymbol{q}_i \widetilde{\mathbf{K}}^\top)\widetilde{\mathbf{V}} \tag{20}$$

ABC (MLP) is again of linear complexity $O(nrd)$. Due to the element-wise computation of W_ϕ, ABC (MLP) maintains high efficiency in recurrent computation and shows competence in all four types of attention.

S4D S4D (Gu et al., 2022) is different from the above attention-based methods, as it relies on State Space Matrix called "HiPPO matrix" (Gu et al., 2020) which enables the whole model to be viewed as a convolutional model. It does not require the introduction of $\mathbf{Q}, \mathbf{K}, \mathbf{V}$ as it takes the whole modeling process as a linear time-invariant (LTI) system $u(t) \mapsto y(t)$ where $u(t)$ is the input sequence. To parameterize the system, S4D designs a Convolution Kernel $K(t) \in \mathbb{R}^{n \times d}$ and introduces a inner state dimension r during parameterization of $K(t)$:

$$K(t) = \boldsymbol{C}e^{t\boldsymbol{A}}\boldsymbol{B}, \quad y(t) = (K * u)(t)$$

where $\boldsymbol{A}, \boldsymbol{B}, \boldsymbol{C}$ are all initialized with certain values and trained with the whole model. During implementation, to avoid low-efficiency of convolution operation in modern DL-frameworks, S4D processes u and K in the frequency domain and transforms back the output to the time domain:

$$K(\omega) = \texttt{fft}(K(t)) \tag{21}$$
$$U(\omega) = \texttt{fft}(u(t)) \tag{22}$$
$$S4D(u) = \texttt{ifft}(K(\omega)U(\omega)) \tag{23}$$

Such computation results in a linear complexity $O(nd)$ Although the S4D method shows strong performance in self-noncausal attention with high efficiency $O(nrd)$, it is incapable of the other three attention types.

G EFFICIENCY LENGTH

We show efficiency lengths under noncausal self attention pattern in Table 11, where we set hyperparameters as emb_dim = 512, head = 8, batch_size = 4, wsize = 16, num_landmarks = 16, approx_attn_dim = 16, d_state = 16, factor = 5, conv_kernel_size = 5.

Table 11: The efficiency lengths of attention architectures compared to vanilla attention under noncausal self attention pattern.

Method	Running Time		Memory Usage	
	Efficiency Length	R^2	Efficiency Length	R^2
Performer	2,361	0.977	37	0.999
LARA	2,541	0.975	68	0.999
Nyströmformer	3,045	0.987	94	0.999
ABC	1,877	0.964	70	0.999
ProbSparse	3,450	0.989	281	0.994
LongShort	5,652	0.998	342	0.999
S4D	6,011	0.996	949	0.999
cosFormer	2,539	0.990	164	0.999
local	4,195	0.996	1,169	0.999

H ATTENTION IMPORTANCE

Table 12: The scores of attention ablation study. '-' denotes that the method fails on the task.

Method	TTS	Sum	PCC	SR	LSTF	MLM
efficient attention	1.034	0.715	0.720	1.041	0.591	0.528
vanilla attention	-0.300	-0.246	0.908	-0.076	-0.102	0.527
w/o attention	-2.155	-1.817	0.940	-0.058	0.027	-

I INTER-TASK CORRELATION

Figure 4 shows the task-to-task correlation. Except for the cross-causal pattern, tasks within the other three patterns scarcely correlate positively with each other. This suggests that there does hardly exist a single task that can comprehensively test the capability of some attention module under an attention pattern.

Figure 4: Task-correlation between each task.