Radiology Reports Improve Visual Representations Learned from Radiographs

Address withheld   EMAIL(S) WITHHELD

Abstract

Although human's ability to visually understand the structure of the World plays a crucial role in perceiving the World and making appropriate decisions, human perception does not solely rely on vision but amalgamates the information from acoustic, verbal, and visual stimuli. An active area of research has been revolving around designing an efficient framework that adapts to multiple modalities and ideally improves the performance of existing tasks. While numerous frameworks have proved effective on natural datasets like ImageNet, a limited number of studies have been carried out in the biomedical domain. In this work, we extend the available frameworks for natural data to biomedical data by leveraging the abundant, unstructured multi-modal data available as radiology images and reports. We attempt to answer the question, "For multi-modal learning, self-supervised learning and joint learning using both learning strategies, which one improves the visual representation for downstream chest radiographs classification tasks the most?". Our experiments indicated that in limited labeled data settings with 1% and 10% labeled data, the joint learning with multi-modal and self-supervised models outperforms self-supervised learning and is at par with multi-modal learning. Additionally, we found that multi-modal learning is generally more robust on out-of-distribution datasets. The code is publicly available online [1].

Keywords: Multi-Modal Learning, Self-Supervised Learning, Out-of-Distribution, Radiology

1. Introduction

Multi-modal learning has become an extremely popular area of research in deep learning. While a good amount of multi-modal learning research has been conducted on datasets like ImageNet (Deng et al., 2009) which consists of natural images (Radford et al., 2021; Kim et al., 2021; Bardes et al., 2022b; He et al., 2020; Chen et al., 2020a; Grill et al., 2020; Zbontar et al., 2021; Bao et al., 2022; Li et al., 2021; Bardes et al., 2022a; Mu et al., 2022; Caron et al., 2020), a limited number of research have been conducted in the biomedical domain (Boecking et al., 2022; Tiu et al., 2022; Zhang et al., 2020; Chaitanya et al., 2020; Haghighi et al., 2022; Azizi et al., 2021; Seibold et al., 2022). In biomedical domain, the choice between multi-modal and self-supervised learning is still unclear for learning better visual representations. Although few studies similar to ConVIRT (Zhang et al., 2020) have looked into the quality of visual representation for biomedical images on multi-modal vs. self-supervised learning, their evaluations are conducted only on a small fraction of dataset for self-supervised learning, which is not guaranteed to see which methods generally perform

---

1. Code will be available in the camera-ready version or upon request.

better. Hence, we believe it is important to compare the performances of multi-modal, self-supervised learning and their joint training in a more comprehensive way.

Biomedical data can effortlessly take advantage of multi-modal learning. For example, there is a paired report for a given radiograph, and MRI scans generally contain multiple contrasts and reports. While many multi-modal models can be used off-the-shelf (Jaegle et al., 2021; Mu et al., 2022; Radford et al., 2021), they are usually trained on natural image datasets which are ten orders of magnitude larger than the available biomedical datasets. While several groups have conducted experiments on biomedical multi-modal learning (Tiu et al., 2022; Boecking et al., 2022; Seibold et al., 2022), their main focus was limited on evaluating the model performance with multi-modal input. To our knowledge, comparative research has yet to be conducted among multi-modal, self-supervised, and joint training on the out-of-distribution (OOD) chest radiograph classification tasks. The aim is to identify the optimal approaches for large scale unlabelled multi-modal radiograph datasets. Our contributions are summarized as follows:

- For OOD chest radiographs, we observe that multi-modal learning generally provides higher quality visual representation.

- Under limited supervised training data, we empirically identify multi-modal and joint training have better performance than self-supervised for chest radiographs. Under large scale supervised training data, the performance of self-supervised learning is at par with multi-modal learning and joint training.

- Provided a benchmark for contrastive learning-based self-supervised, multi-modal learning and their joint training for chest radiographs with code available for further investigation.

2. Related Works

Multi-modal learning learn representations for both image and text data concurrently. One of the most popular approaches of multi-modal learning is learning from image and text data contrastively, where the representation for paired image and text are aligned closer and unpaired image and text are dispelled further. Approaches like CLIP (Radford et al., 2021) and ConVIRT (Zhang et al., 2020) are considered be the representative work of contrastive multi-modal learning for natural and medical images, respectively.

Self-supervised learning is a recent popular topic in representation learning, where the model learns the patterns by training on unlabeled data. Three different self-supervised learning approaches, SimCLR (Chen et al., 2020a), MoCoV2 (Chen et al., 2020b), and VICReg (Bardes et al., 2022b) were evaluated in our paper. The general idea of the self-supervised learning methods we evaluated is that they train the model to learn the invariant representation of the same image by applying different augmentations.

Application in biomedical domain: CheXzero (Tiu et al., 2022) explored the performance of CLIP on radiology chest scan diagnosis by taking in language and vision input together with zero-shot prompting. BioVLP (Boecking et al., 2022) explored the performance of contrastive self-supervised learning with masked language modeling on radiology

chest scan diagnosis. ConVIRT (Zhang et al., 2020) explored if multi-modal learning on radiology image-text pair can learn strong image representation. GLoRIA (Huang et al., 2021) shows adding local representation during multi-modal learning on radiology image-text pair can improve performance upon ConVIRT. (Azizi et al., 2021) shows image representations learned from the medical images by SimCLR can improve downstream performance. REMEDIS (Azizi et al., 2022) performed a large-scale evaluation on both in-distribution (ID) and OOD medical images with SimCLR.

Out-of-Distribution problem: The medical domain also faces the problem of OOD, in which even though the input data from two different datasets is chest radiographs, however, the origin, extraction methods and target population affect the distribution. In our case, both CheXPert (Irvin et al., 2019) and NIH-ChestXray 14 (Wang et al., 2017) are OOD with MIMIC-CXR (Johnson et al., 2019), which we used for pre-training, because they are collected from very different regions.

3. Methods

The diagram of the experimental process is shown in Figure 1. For pre-training, we train the model with multi-modal learning, self-supervised learning or joint training by optimizing over both multi-modal learning and self-supervised learning as proposed by (Mu et al., 2022). For evaluating the pre-trained model quality, we finetune the pre-trained model with additional classification heads. Specifically, we performed linear probing (LP), fine-tuning (FT) or fine-tuning after linear probing (LPFT) (Kumar et al., 2022).

3.1. Self-Supervised and Multi-Modal Pretraining

We used the following models for the comparative study: we chose CLIP (Radford et al., 2021) and ConVIRT (Zhang et al., 2020) as they are two earliest representative works on contrastive multi-modal learning. We chose three most representative categories for self-supervised learning as SimCLR (Chen et al., 2020a) (traditional contrastive learning), VICReg (Bardes et al., 2022b) (redundancy reduction) and MoCoV2 (Chen et al., 2020b) (dictionary for caching negative representations for contrastive learning).

CLIP (Radford et al., 2021): Given image representation u and text representation v, CLIP loss is formulated as

$$\mathcal{L} = \mathcal{L}_{i2t} + \mathcal{L}_{t2i} \tag{1}$$

where

$$\mathcal{L}_{i2t} = -\sum_{i \in \mathcal{B}} \log \frac{\exp(\tau u_i v_i)}{\sum_{j \in \mathcal{B}} \exp(\tau u_i v_j)} \tag{2}$$

and

$$\mathcal{L}_{t2i} = -\sum_{j \in \mathcal{B}} \log \frac{\exp(\tau u_i v_i)}{\sum_{i \in \mathcal{B}} \exp(\tau u_i v_j)} \tag{3}$$

where $\mathcal{B}$ is batch size and τ is temperature hyperparameter .

ConVIRT (Zhang et al., 2020): ConVIRT followed the same loss as CLIP, but it is more fine-grained toward medical imaging with more specific augmentations (we adopted

a. Contrastive Multi-Modal Learning

b. General Self-Supervised Framework

c. Downstream Linear Probing

d. Downstream Fine-tuning

Figure 1: Experimental Process: a) Contrastive multi-modal learning training. b) Contrastive self-supervised learning training. c) Downstream linear probing **(LP)**. d) Downstream fine-tuning **(FT)**.

these augmentations as our general multi-modal learning augmentation mentioned in Appendix B.2) and an architecture design choice that freezes top six layers of text encoder.

SimCLR (Chen et al., 2020a): Given two input representations z_i and z_j in a given batch. The NT-Xent loss by SimCLR is formulate as

$$l_{i,j} = -\log \frac{\exp(sim(z_i, z_j)/\tau)}{\sum_{k=1}^{2N} \mathbb{1}_{k \neq i} \exp(sim(z_i, z_k)/\tau)} \tag{4}$$

where τ is temperature hyperparameter, N is number of in batch samples, sim is the similarity metric set to be a dot product following the original implementation.

MoCoV2 (Chen et al., 2020b): We followed the original proposal of MoCo that creates a very large memory bank to cache image representations with InfoNCE (van den Oord et al., 2018) in order to introduce more negative samples within a single batch. The InfoNCE loss is formulated as

$$\mathcal{L} = -\log \frac{\exp(q \cdot k_+/\tau)}{\sum_{i=0}^{K} \exp(q \cdot k_i/\tau)} \tag{5}$$

where q is the representation for anchor input, k_+ is the representation for positive input, k_i is the representation for all cached input in memory bank and τ is a temperature parameter. The sample representations in the memory bank is gradually updated by a separate encoder that is update by trained encoder with Exponential Moving Average (EMA).

VICReg ([Bardes et al., 2022b](#)): Given two input representations Z and Z' obtained by passing two transformed views of same image, VICReg loss is computed as

$$\ell(Z, Z') = \lambda s(Z, Z') + \mu[v(Z) + v(Z')] + \nu[c(Z) + c(Z')] \tag{6}$$

where $s(Z, Z') = \frac{1}{n} \sum_i \|z_i - z'_i\|_2^2$ is the invariance term for calculating the feature-wised mean-squared euclidean distance with given feature size n. $v(Z) = \frac{1}{d} \sum_{j=-1}^{d} \max(0, \gamma - S(z^j, \epsilon))$ is the variance term for given number of samples d, $S(x, \epsilon) = \sqrt{\text{Var}(x) + \epsilon}$ is the regularized standard deviation with γ as a constant target standard deviation value, ϵ as a scalar to enforce numerical stability. $C(Z) = \frac{1}{n-1} \sum_{i=1}^{n} (z_i - \bar{z})(z_i - \bar{z})^T$ is the covariance term where $\bar{z} = \frac{1}{n} z_i$. λ, μ, ν are hyperparameters to control the contribution of each loss term.

Joint Training: The joint training of multi-modal and self-supervised learning was proposed by SLIP ([Mu et al., 2022](#)) for natural image training. Given image and text representations u and v from CLIP projector, and two projected augmented image representations from some self-supervised learning projector z_i and z_j, SLIP is trained by minimizing

$$\ell_{slip} = c \cdot \ell_{ssl}(z_i, z_j) + \ell_{clip}(u, v) \tag{7}$$

where ℓ_{ssl} is the loss for some self-supervised method and c is a hyperparameter to control the contribution of self-supervised loss. In our experiments, we chose multi-modal learning methods to be CLIP and ConVIRT, self-supervised learning methods to be SimCLR, MoCoV2 and VICReg. While SimCLR and MoCoV2 with CLIP was experimented in the original SLIP paper, VICReg and ConVIRT were not experimented in the original work.

4. Experimental Setup

4.1. Dataset

Our multi-modal frameworks were trained on MIMIC-CXR ([Johnson et al., 2019](#)) dataset, which consists of 377,110 pairs of chest X-ray image-report pairs collected from Beth Israel Deaconess Medical Center in Boston, MA, USA. Radiology reports, although an excellent source of information, carry redundant information. Findings and impressions are richer in content. Findings present the diagnosis from the given radiology image, and impressions presents the complete narrative description from doctors according to multiple radiology images of the same patient. In our experiment, we only chose impressions as our text input because impressions have more concise description of the patients diagnosis, where we found it introduced less noise than findings.

Our trained models were evaluated on CheXPert ([Irvin et al., 2019](#)) and NIH-ChestX-ray14 ([Wang et al., 2017](#)) dataset with LP on 100% data, LPFT on 100% data and FT on 1%, 10% and 100% data ([Kumar et al., 2022](#)). CheXPert dataset consists of 224,316 chest radiographs of 65,240 patients from Stanford Hospital in Palo Alto, CA, USA. There are 14 observed pathologies labeled by the radiologist as positive, negative, or uncertain. NIH-ChestX-ray14 ([Wang et al., 2017](#)) dataset consisting of 112,120 frontal-view X-ray images of 30,805 collected at the National Institutes of Health Clinical Center, MD, USA, with unique patients and the text-mined fourteen common disease labels.

4.2. Backbone Encoders

For all frameworks, we fixed the image encoder to be ResNet-50 (He et al., 2016). For the text encoder, we used BERT-base (Devlin et al., 2019). The image encoder was initialized with ImageNet pre-trained weights, and the text encoder was initialized with CXR-BERT-general pre-trained weights (Boecking et al., 2022).

4.3. Data Preprocessing

We loaded MIMIC-CXR images from corresponding DICOM files, and the images were resized to 224×224. Only impressions were used as text input. Samples with missing impressions were removed from training. For data augmentation, we used random resized crop, random horizontal flip, color jittering, gaussian blur, and solarization for self-supervised learning methods. In addition to the augmentations for self-supervised methods, for multi-modal approaches we used random affine transform. ImageNet normalization was used in all experiments.

4.4. Hyperparameters

For pre-training, we trained all methods with a learning rate $1e$-4, batch size 256 with ResNet-50 backbone across four Tesla V100 GPUs with 32GB RAM. We used AdamW optimizer (Loshchilov and Hutter, 2019) with cosine scheduling as optimizer scheduler (Loshchilov and Hutter, 2016) without warmup steps, beta2 of AdamW was set to be 0.98 for more stable training. The total number of epochs was set to 50 for training with early stopping was decided based on the loss of validation set. For fairness of comparisons, all self-supervised learning and multi-modal learning used the same augmentations as mentioned in Section 4.3. We did not perform any augmentation on text data. See Appendix B for more details on hyperparameters for both pre-training and downstream training.

5. Results

We show our benchmarking result in Table 1. All results were evaluated with the mean AUROC from all pathology. We further explain them in section 5.1. We picked one method from multi-modal learning (CLIP), self-supervised learning (SimCLR) and joint training (SimCLR-CLIP) to analyze per pathology performance shown in Appendix C. Generally, we observed that using multi-modal learning or joint training improved the performance of pathologies that have low prevalence and the trend is more prominent with limited data.

5.1. Downstream Evaluation

For both OOD datasets we evaluated on, we observed that either FT with 100% data or LPFT has a comparable performance on self-supervised, multi-modal, and joint training. For FT with 1% and 10% data, self-supervised methods decay on performance fast, but multi-modal and joint training have much slower decay. For LP, we observed the same trend as fine-tuning on limited data: multi-modal and joint training perform much better than self-supervised learning. Empirically, we observed that results from NIH-ChestX-Ray with LP was very close to 100% FT and LPFT, which signifies that the two datasets

have a very similar distribution compared to CheXPert dataset. Another trend that we observed was introducing the additional information from radiology report helped the model to learn better visual representation than directly performing self-supervised learning. This phenomenon can be attributed to radiology reports becoming very precise, clear and created by radiologists thus they contain highly semantic and dense information which complements the visual representation from images.

	Methods	CheXPert (AUROC)				
		LPFT	LP	1%	10%	100%
(a)	Random Init.	77.35 ± 0.61	62.91 ± 0.62	62.88 ± 1.13	70.36 ± 0.98	**78.28** ± 1.10
	ImageNet Init.	**83.67** ± 0.88	67.12 ± 0.24	69.33 ± 0.15	77.98 ± 0.28	82.29 ± 2.79
	CLIP	**85.06** ± 0.85	78.17 ± 0.23	78.19 ± 1.80	82.90 ± 1.46	84.36 ± 3.07
	ConVIRT	84.34 ± 0.99	79.92 ± 0.11	76.96 ± 2.34	82.89 ± 2.40	**85.20** ± 1.44
	MoCoV2	81.95 ± 1.78	71.37 ± 0.17	74.33 ± 1.53	79.58 ± 1.30	**84.12** ± 1.08
	SimCLR	84.24 ± 0.95	68.70 ± 0.39	72.83 ± 0.91	78.33 ± 0.88	**84.74** ± 0.96
	VICReg	82.81 ± 0.67	71.05 ± 0.48	72.16 ± 1.83	78.51 ± 1.18	**85.40** ± 1.63
	MoCoV2-CLIP	**83.43** ± 2.21	76.89 ± 0.16	77.61 ± 1.57	80.29 ± 0.71	82.92 ± 1.24
	MoCoV2-ConVIRT	**84.81** ± 1.82	77.02 ± 0.14	77.93 ± 1.43	83.45 ± 1.79	83.51 ± 1.37
	SimCLR-CLIP	**85.10** ± 0.72	78.02 ± 0.13	77.84 ± 0.99	81.67 ± 2.76	84.33 ± 0.79
	SimCLR-ConVIRT	83.95 ± 1.66	75.97 ± 0.10	76.68 ± 1.61	82.57 ± 1.55	**84.39** ± 1.09
	VICReg-CLIP	**82.72** ± 1.71	69.01 ± 0.27	75.06 ± 1.64	81.17 ± 1.61	82.11 ± 1.34
	VICReg-ConVIRT	**83.05** ± 1.25	71.72 ± 0.36	74.93 ± 2.27	81.17 ± 2.34	**83.05** ± 1.76
	Methods	NIH-ChestX-Ray14 (AUROC)				
		LPFT	LP	1%	10%	100%
(b)	Random Init.	**78.97** ± 0.13	62.54 ± 0.34	58.30 ± 2.06	70.06 ± 1.02	78.52 ± 0.17
	ImageNet Init.	**82.96** ± 0.12	75.46 ± 0.78	67.18 ± 0.07	76.44 ± 0.63	82.70 ± 0.23
	CLIP	**83.84** ± 0.19	83.80 ± 0.16	72.95 ± 1.31	79.80 ± 0.67	83.74 ± 0.22
	ConVIRT	83.80 ± 0.05	83.48 ± 0.04	71.20 ± 0.98	79.24 ± 0.89	**83.92** ± 0.13
	MoCoV2	**83.20** ± 0.18	77.90 ± 0.31	68.50 ± 0.99	77.22 ± 0.67	83.10 ± 0.37
	SimCLR	**82.82** ± 0.19	77.00 ± 0.10	69.01 ± 0.41	76.52 ± 0.56	82.76 ± 0.32
	VICReg	**82.80** ± 0.26	75.14 ± 0.65	69.06 ± 0.47	75.98 ± 0.87	82.74 ± 0.24
	MoCoV2-CLIP	**83.68** ± 0.12	81.42 ± 0.04	71.28 ± 0.57	79.02 ± 0.52	83.32 ± 0.46
	MoCoV2-ConVIRT	**83.62** ± 0.40	81.00 ± 0.02	71.10 ± 0.81	78.58 ± 0.70	83.62 ± 0.13
	SimCLR-CLIP	**83.80** ± 0.12	80.98 ± 0.09	71.33 ± 0.99	79.30 ± 0.69	83.66 ± 0.18
	SimCLR-ConVIRT	83.38 ± 0.10	80.40 ± 0.09	70.90 ± 0.67	78.52 ± 0.67	**83.45** ± 0.08
	VICReg-CLIP	83.30 ± 0.18	78.02 ± 0.11	70.76 ± 0.94	78.22 ± 0.60	**83.32** ± 0.34
	VICReg-ConVIRT	**83.24** ± 0.20	76.92 ± 0.04	70.80 ± 0.76	78.38 ± 0.90	83.20 ± 0.25

Table 1: We report the 95% confidence interval (CI) obtained from 5 different seeds in the form of (Mean ± CI range) for the AUROC score of the chosen datasets with fine-tuning after linear probing (**LPFT**), linear probing (**LP**) (LPFT and LP are both on **100%** data), **1%**, **10%** and **100%** of labeled data fine-tuning

5.2. t-SNE visualization

We visualized the embedding of the backbone after downstream training by t-SNE (van der Maaten and Hinton, 2008) for monitoring the behaviors of different training methods shown in Figure 2. We randomly picked 10,000 samples for the visualization for each dataset and get visual representation by inferencing through different models after LPFT with corresponding dataset. As the figure shows, visual representation after t-SNE dimensional reduction was generally less separable across different datasets for self-supervised learning

(SimCLR), but it can be much better separated for models trained with multi-modal (CLIP) or joint training (SimCLR-CLIP). This finding re-identified our previous conclusion that multi-modal learning and joint training are generally getting better quality visual representations under limited supervised training data. We additionall showed visualization for ConVIRT, MoCoV2 and MoCoV2-ConVIRT in Appendix D, where we see similar trend.

(a) CLIP-NIH   (b) SimCLR-NIH   (c) SimCLR-CLIP-NIH

(d) CLIP-CHEXPERT   (e) SimCLR-CHEXPERT   (f) SimCLR-CLIP-CHEXPERT

Figure 2: Figures for t-SNE embedding with LPFT downstream training strategies with CLIP, SimCLR, SimCLR-CLIP pretrained backbone

6. Conclusion

In this work, we observed that multi-modal learning and joint training performs better than self-supervised learning with limited supervised data, but the performance difference between all methods is largely decreased when data size scales up. For NIH-ChestX-ray 14 datasets, we found that initial representation learned by multi-modal learning and joint training is very strong with LP to be getting very close performance as 100% FT which implies that the two datasets have more similar distribution compared to CheXPert dataset. We expect our work would provide a good reference for future research on both multi-modal and self-supervised learning for medical imaging.

Acknowledgments

Acknowledgments withheld.

References

Shekoofeh Azizi, Basil Mustafa, Fiona Ryan, Zachary Beaver, Jan Freyberg, Jonathan Deaton, Aaron Loh, Alan Karthikesalingam, Simon Kornblith, Ting Chen, Vivek Natarajan, and Mohammad Norouzi. Big self-supervised models advance medical image classification. In *2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 3458–3468, 2021. doi: 10.1109/ICCV48922.2021.00346.

Shekoofeh Azizi, Laura Culp, Jan Freyberg, Basil Mustafa, Sebastien Baur, Simon Kornblith, Ting Chen, Patricia MacWilliams, S. Sara Mahdavi, Ellery Wulczyn, Boris Babenko, Megan Wilson, Aaron Loh, Po-Hsuan Cameron Chen, Yuan Liu, Pinal Bavishi, Scott Mayer McKinney, Jim Winkens, Abhijit Guha Roy, Zach Beaver, Fiona Ryan, Justin Krogue, Mozziyar Etemadi, Umesh Telang, Yun Liu, Lily Peng, Greg S. Corrado, Dale R. Webster, David Fleet, Geoffrey Hinton, Neil Houlsby, Alan Karthikesalingam, Mohammad Norouzi, and Vivek Natarajan. Robust and efficient medical imaging with self-supervision, 2022. URL https://arxiv.org/abs/2205.09723.

Hangbo Bao, Wenhui Wang, Li Dong, Qiang Liu, Owais Khan Mohammed, Kriti Aggarwal, Subhojit Som, Songhao Piao, and Furu Wei. VLMo: Unified vision-language pre-training with mixture-of-modality-experts. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho, editors, *Advances in Neural Information Processing Systems*, 2022. URL https://openreview.net/forum?id=bydKs84JEyw.

Adrien Bardes, Jean Ponce, and Yann LeCun. Vicreg: Variance-invariance-covariance regularization for self-supervised learning. In *NIPS*. OpenReview.net, 2022a.

Adrien Bardes, Jean Ponce, and Yann LeCun. VICReg: Variance-invariance-covariance regularization for self-supervised learning. In *International Conference on Learning Representations*, 2022b. URL https://openreview.net/forum?id=xm6YD62D1Ub.

Benedikt Boecking, Naoto Usuyama, Shruthi Bannur, Daniel C. Castro, Anton Schwaighofer, Stephanie Hyland, Maria Wetscherek, Tristan Naumann, Aditya Nori, Javier Alvarez-Valle, Hoifung Poon, and Ozan Oktay. Making the most of text semantics to improve biomedical vision–language processing, 2022. URL https://arxiv.org/abs/2204.09817.

Mathilde Caron, Ishan Misra, Julien Mairal, Priya Goyal, Piotr Bojanowski, and Armand Joulin. Unsupervised learning of visual features by contrasting cluster assignments. In *Proceedings of the 34th International Conference on Neural Information Processing Systems*, NIPS'20, Red Hook, NY, USA, 2020. Curran Associates Inc. ISBN 9781713829546.

Krishna Chaitanya, Ertunc Erdil, Neerav Karani, and Ender Konukoglu. Contrastive learning of global and local features for medical image segmentation with limited annotations. *Advances in Neural Information Processing Systems*, 33, 2020.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In Hal Daumé III and Aarti Singh, editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 1597–1607. PMLR, 13–18 Jul 2020a. URL https://proceedings.mlr.press/v119/chen20j.html.

Xinlei Chen, Haoqi Fan, Ross Girshick, and Kaiming He. Improved baselines with momentum contrastive learning, 2020b. URL https://arxiv.org/abs/2003.04297.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pages 248–255. Ieee, 2009.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL https://aclanthology.org/N19-1423.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Guo, Mohammad Gheshlaghi Azar, Bilal Piot, koray kavukcuoglu, Remi Munos, and Michal Valko. Bootstrap your own latent - a new approach to self-supervised learning. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 21271–21284. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/f3ada80d5c4ee70142b17b8192b2958e-Paper.pdf.

Fatemeh Haghighi, Mohammad Reza Hosseinzadeh Taher, Michael B. Gotway, and Jianming Liang. Dira: Discriminative, restorative, and adversarial learning for self-supervised medical image analysis. In *2022 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 20792–20802, 2022. doi: 10.1109/CVPR52688.2022.02016.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 770–778, 2016. doi: 10.1109/CVPR.2016.90.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 9726–9735, 2020. doi: 10.1109/CVPR42600.2020.00975.

Shih-Cheng Huang, Liyue Shen, Matthew P. Lungren, and Serena Yeung. Gloria: A multimodal global-local representation learning framework for label-efficient medical image recognition. In *2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 3922–3931, 2021. doi: 10.1109/ICCV48922.2021.00391.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In Francis Bach and David Blei, editors, *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pages 448–456, Lille, France, 07–09 Jul 2015. PMLR. URL https://proceedings.mlr.press/v37/ioffe15.html.

Jeremy Irvin, Pranav Rajpurkar, Michael Ko, Yifan Yu, Silviana Ciurea-Ilcus, Chris Chute, Henrik Marklund, Behzad Haghgoo, Robyn Ball, Katie Shpanskaya, Jayne Seekins, David A. Mong, Safwan S. Halabi, Jesse K. Sandberg, Ricky Jones, David B. Larson, Curtis P. Langlotz, Bhavik N. Patel, Matthew P. Lungren, and Andrew Y. Ng. Chexpert: A large chest radiograph dataset with uncertainty labels and expert comparison. AAAI'19/IAAI'19/EAAI'19. AAAI Press, 2019. ISBN 978-1-57735-809-1. doi: 10.1609/aaai.v33i01.3301590. URL https://doi.org/10.1609/aaai.v33i01.3301590.

Andrew Jaegle, Felix Gimeno, Andrew Brock, Andrew Zisserman, Oriol Vinyals, and João Carreira. Perceiver: General perception with iterative attention. *CoRR*, abs/2103.03206, 2021. URL https://arxiv.org/abs/2103.03206.

Alistair E. W. Johnson, Tom J. Pollard, Seth J. Berkowitz, Nathaniel R. Greenbaum, Matthew P. Lungren, Chih-ying Deng, Roger G. Mark, and Steven Horng. Mimic-cxr, a de-identified publicly available database of chest radiographs with free-text reports. *Scientific Data*, 6(1):317, Dec 2019. ISSN 2052-4463. doi: 10.1038/s41597-019-0322-0. URL https://doi.org/10.1038/s41597-019-0322-0.

Wonjae Kim, Bokyung Son, and Ildoo Kim. Vilt: Vision-and-language transformer without convolution or region supervision. In Marina Meila and Tong Zhang, editors, *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 5583–5594. PMLR, 18–24 Jul 2021. URL https://proceedings.mlr.press/v139/kim21k.html.

Ananya Kumar, Aditi Raghunathan, Robbie Jones, Tengyu Ma, and Percy Liang. Fine-tuning can distort pretrained features and underperform out-of-distribution. *arXiv preprint arXiv:2202.10054*, 2022.

Junnan Li, Ramprasaath R. Selvaraju, Akhilesh Deepak Gotmare, Shafiq Joty, Caiming Xiong, and Steven Hoi. Align before fuse: Vision and language representation learning with momentum distillation. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021. URL https://openreview.net/forum?id=OJLaKwiXSbx.

Ilya Loshchilov and Frank Hutter. SGDR: stochastic gradient descent with restarts. *CoRR*, abs/1608.03983, 2016. URL http://arxiv.org/abs/1608.03983.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=Bkg6RiCqY7.

Norman Mu, Alexander Kirillov, David A. Wagner, and Saining Xie. SLIP: self-supervision meets language-image pre-training. In Shai Avidan, Gabriel J. Brostow, Moustapha

Cissé, Giovanni Maria Farinella, and Tal Hassner, editors, *Computer Vision - ECCV 2022 - 17th European Conference, Tel Aviv, Israel, October 23-27, 2022, Proceedings, Part XXVI*, volume 13686 of *Lecture Notes in Computer Science*, pages 529–544. Springer, 2022. doi: 10.1007/978-3-031-19809-0_30. URL https://doi.org/10.1007/978-3-031-19809-0_30.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. In Marina Meila and Tong Zhang, editors, *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 8748–8763. PMLR, 18–24 Jul 2021. URL https://proceedings.mlr.press/v139/radford21a.html.

Constantin Seibold, Simon Reiß, M. Saquib Sarfraz, Rainer Stiefelhagen, and Jens Kleesiek. Breaking with fixed set pathology recognition through report-guided contrastive training. In *Lecture Notes in Computer Science*, pages 690–700. Springer Nature Switzerland, 2022. doi: 10.1007/978-3-031-16443-9_66. URL https://doi.org/10.1007%2F978-3-031-16443-9_66.

Ekin Tiu, Ellie Talius, Pujan Patel, Curtis P. Langlotz, Andrew Y. Ng, and Pranav Rajpurkar. Expert-level detection of pathologies from unannotated chest x-ray images via self-supervised learning. *Nature Biomedical Engineering*, Sep 2022. ISSN 2157-846X. doi: 10.1038/s41551-022-00936-9. URL https://doi.org/10.1038/s41551-022-00936-9.

Aäron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *CoRR*, abs/1807.03748, 2018. URL http://arxiv.org/abs/1807.03748.

Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-SNE. *Journal of Machine Learning Research*, 9:2579–2605, 2008. URL http://www.jmlr.org/papers/v9/vandermaaten08a.html.

Xiaosong Wang, Yifan Peng, Le Lu, Zhiyong Lu, Mohammadhadi Bagheri, and Ronald M Summers. Chestx-ray8: Hospital-scale chest x-ray database and benchmarks on weakly-supervised classification and localization of common thorax diseases. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2097–2106, 2017.

Jure Zbontar, Li Jing, Ishan Misra, Yann LeCun, and Stephane Deny. Barlow twins: Self-supervised learning via redundancy reduction. In Marina Meila and Tong Zhang, editors, *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 12310–12320. PMLR, 18–24 Jul 2021. URL https://proceedings.mlr.press/v139/zbontar21a.html.

Yuhao Zhang, Hang Jiang, Yasuhide Miura, Christopher D. Manning, and Curtis P. Langlotz. Contrastive learning of medical visual representations from paired images and text. *CoRR*, abs/2010.00747, 2020. URL https://arxiv.org/abs/2010.00747.

Appendix A. Computational Cost

We trained all models on four NVIDIA Tesla V100 GPUs with 32GB RAM for MIMIC-CXR pre-training. For all downstream experiments on CheXPert and NIH-ChestXRay-14 dataset, we used one NVIDIA Tesla V100 GPUs with 16GB RAM. The pre-training took roughly 1.5 to 2 days and fine-tuning took roughly 0.5 days.

Appendix B. Hyperparameters Details

B.1. Model Hyperparameters Details

For downstream training, we used $1e$-4 learning rate and Adam optimizer for both datasets. We set the batch size to 64 for CheXPert and 16 for NIH-Chest-Xray14. Random Horizontal Flip and Center Crop were performed on CheXPert and no augmentation was applied to NIH-Chest-Xray14. We trained CheXPert for 5 epochs and picked the epoch with highest AUROC. We trained NIH-Chest-Xray14 for 30 epochs and picked the epoch based on validation loss. For LPFT, we trained upon best epoch on LP with additional 5 or 30 epochs and picked the best epoch after FT based on corresponding dataset. We set temperature for loss function as 0.07 for CLIP and MoCoV2, 0.1 for ConVIRT and SimCLR. We set the self-supervised loss contribution weight hyperparameter c in joint training to be 1.0.

B.2. Data Augmentation Details

For multi-modal learning, we performed Random Resized Crop with size 224 and scale from 0.6 to 1.0, Random Horizontal Flip with probability 0.5, Random Affine with degree -20 to 20, translation 0.09 to 0.10 and scale 0.95 to 1.05, Color Jitter with brightness 0.6 to 1.4 and contrast 0.6 to 1.4 with probability 0.5, Gaussian Blur with min 0.1, max 3.0 and probability 0.5.

For self-supervised learning, we performed Random Resized Crop with size 224 and scale from 0.75 to 1.0, Random Horizontal Flip with probability 0.5, Color Jitter with brightness 0.4 contrast 0.4 and probability 0.8, Gaussian Blur with probability either 1.0 or 0.1 with min 0.1 and max 2.0. Solarization with probability either 0.2 or 0.

B.3. Feature Projection Details

The image embeddings were originally projected to 2048 dimension and then further projected to 512 dimension for calculating CLIP loss. The text embeddings were originally extracted from last layer of $[CLS]$ token and then projected to 512 dimension as well. For SimCLR and MoCoV2, the image representations were re-projected to 512 dimension and then projected to 128 dimensions. For VICReg, the image representations were re-projected to 8192 dimensions with three linear layers that all have 8192 dimensions. We used batch normalization (Ioffe and Szegedy, 2015) for all projectors as in-between layers.

Appendix C. Performance on Different Pathology

This section shows per pathology performance on the two datasets with different methods. The AUROC score here is picked by taking mean around each pathology across seeds.

C.1. 100% **label fraction**

Pathologies	CheXPert (AUROC)				
100% fine-tuning	ImageNet	CLIP	SimCLR	SimCLR-CLIP	Prevalence (%)
No Finding	**90.07**	87.52	86.64	88.13	7.41
Enlarged Cardiomediastinum	**64.72**	52.21	55.14	50.72	8.55
Cardiomegaly	**86.10**	81.80	82.90	82.16	13.20
Lung Lesion	32.80	66.66	86.06	**96.01**	3.53
Lung Opacity	89.01	89.49	91.65	**91.66**	43.25
Edema	93.91	91.99	93.16	**94.97**	26.96
Consolidation	88.53	87.59	**89.44**	88.75	16.36
Pneumonia	**88.59**	82.53	72.93	74.42	9.02
Atelectasis	81.07	79.16	83.61	**85.07**	26.17
Pneumothorax	**91.64**	85.05	86.73	78.38	8.91
Pleural Effusion	93.23	92.73	**93.80**	93.08	37.94
Pleural Other	95.02	92.03	80.09	**97.01**	1.88
Fracture	93.51	92.76	94.90	**96.46**	3.46

Table 2: Per Pathology Performance for different pre-training methods after 100% fine-tuning

Pathologies	NIH-ChestX-Ray14 (AUROC)				
100% fine-tuning	ImageNet	CLIP	SimCLR	SimCLR-CLIP	Prevalence (%)
Atelectasis	80.92	82.10	80.05	**82.19**	10.79
Cardiomegaly	89.89	90.71	90.05	**90.75**	2.59
Effusion	87.25	87.36	87.35	**87.45**	12.28
Infiltration	69.90	70.50	70.11	**70.58**	17.56
Mass	82.97	83.39	82.53	**84.32**	5.05
Nodule	76.88	77.17	77.19	**77.33**	5.95
Pneumonia	74.35	76.14	74.81	**76.33**	1.08
Pneumothorax	85.05	86.86	86.16	**87.44**	4.85
Consolidation	79.74	80.63	79.61	**80.80**	4.27
Edema	88.99	89.47	88.06	**89.56**	1.84
Emphysema	91.91	92.57	91.63	**92.69**	2.27
Fibrosis	82.70	81.64	81.09	**83.07**	1.61
Pleural Thickening	77.12	78.62	76.50	**77.71**	3.27
Hernia	93.20	93.81	91.54	**95.08**	0.19

Table 3: Per Pathology Performance for different pre-training methods after 100% fine-tuning

C.2. 10% **label fraction**

Pathologies	CheXPert (AUROC)				
10% fine-tuning	ImageNet	CLIP	SimCLR	SimCLR-CLIP	Prevalence
No Finding	85.51	90.01	89.44	**90.10**	7.41
Enlarged Cardiomediastinum	57.46	**67.77**	57.66	67.72	8.55
Cardiomegaly	73.67	85.20	77.76	**86.16**	13.20
Lung Opacity	86.23	90.79	87.99	**91.50**	3.53
Lung Lesion	48.76	**56.21**	46.26	55.72	43.25
Edema	90.65	93.13	89.76	**93.49**	26.96
Consolidation	82.57	87.83	75.45	**89.39**	16.36
Pneumonia	71.65	**82.73**	81.82	78.67	9.02
Atelectasis	76.03	85.56	77.72	**85.92**	26.17
Pneumothorax	70.55	**89.96**	74.65	89.45	8.91
Pleural Effusion	84.23	92.50	90.37	**92.75**	37.94
Pleural Other	86.57	96.01	**99.50**	97.01	1.88
Fracture	81.91	**91.65**	82.63	90.64	3.46

Table 4: Per Pathology Performance for different pre-training methods after 10% fine-tuning

Pathologies	NIH-ChestX-Ray14 (AUROC)				
10% fine-tuning	ImageNet	CLIP	SimCLR	SimCLR-CLIP	Prevalence
Atelectasis	76.68	78.46	75.68	**78.69**	10.79
Cardiomegaly	83.07	**89.36**	85.40	88.14	2.59
Effusion	85.33	**87.18**	85.75	86.42	12.28
Infiltration	66.70	**68.16**	65.13	67.79	17.56
Mass	76.13	**81.93**	75.62	80.47	5.05
Nodule	68.35	**73.12**	65.65	72.57	5.95
Pneumonia	70.35	**73.13**	68.73	70.96	1.08
Pneumothorax	81.37	**84.77**	80.61	81.90	4.85
Consolidation	78.09	**78.58**	76.44	78.56	4.27
Edema	86.19	**86.85**	86.28	86.76	1.84
Emphysema	**87.20**	86.30	78.08	87.18	2.27
Fibrosis	75.39	**77.55**	73.69	75.56	1.61
Pleural Thickening	72.89	73.09	73.69	**75.34**	3.27
Hernia	81.85	**81.90**	78.89	77.94	0.19

Table 5: Per Pathology Performance for different pre-training methods after 10% fine-tuning

C.3. 1% **label fraction**

Pathologies	CheXPert (AUROC)				
1% fine-tuning	ImageNet	CLIP	SimCLR	SimCLR-CLIP	Prevalence
No Finding	82.65	**93.39**	93.00	91.63	7.41
Enlarged Cardiomediastinum	48.95	51.00	**69.63**	46.29	8.55
Cardiomegaly	70.35	74.45	77.94	**79.28**	13.20
Lung Opacity	72.70	**90.57**	83.64	86.05	3.53
Lung Lesion	40.30	28.35	32.83	**49.25**	43.25
Edema	82.54	**89.68**	81.26	89.47	26.96
Consolidation	82.76	84.70	85.47	**86.63**	16.36
Pneumonia	59.99	79.12	73.00	**83.24**	9.02
Atelectasis	75.43	**83.47**	80.30	78.47	26.17
Pneumothorax	80.88	**83.07**	67.17	67.54	8.91
Pleural Effusion	78.53	87.74	82.30	**91.50**	37.94
Pleural Other	78.11	95.52	68.65	**95.52**	1.88
Fracture	75.20	**89.77**	65.76	88.66	3.46

Table 6: Per Pathology Performance for different pre-training methods after 1% fine-tuning

Pathologies	NIH-ChestX-Ray14 (AUROC)				
1% fine-tuning	ImageNet	CLIP	SimCLR	SimCLR-CLIP	Prevalence
Atelectasis	65.17	76.14	74.18	**76.25**	10.79
Cardiomegaly	53.90	68.52	**68.87**	65.49	2.59
Effusion	80.12	**84.87**	81.45	84.37	12.28
Infiltration	63.23	**66.95**	64.65	65.66	17.56
Mass	67.69	**79.79**	63.77	74.39	5.05
Nodule	56.40	69.54	59.79	**64.61**	5.95
Pneumonia	62.14	**65.86**	62.39	61.75	1.08
Pneumothorax	77.00	**82.91**	76.47	78.86	4.85
Consolidation	75.38	**78.33**	75.09	75.93	4.27
Edema	80.58	79.52	**84.38**	82.29	1.84
Emphysema	73.18	**85.38**	72.01	68.55	2.27
Fibrosis	69.56	**72.83**	64.23	68.22	1.61
Pleural Thickening	67.80	**71.60**	64.37	70.94	3.27
Hernia	52.92	68.31	60.08	**79.13**	0.19

Table 7: Per Pathology Performance for different pre-training methods after 1% fine-tuning

Appendix D. Additional Visualization for t-SNE

(a) ConVIRT-NIH ChestX-ray14   (b) MoCoV2-NIH ChestX-ray14   (c) MoCoV2-ConVIRT-NIH ChestX-ray14

(d) ConVIRT-CheXpert   (e) MoCoV2-CheXpert   (f) MoCoV2-ConVIRT-CheXpert

Figure 3: Figures for t-SNE embedding with LPFT downstream training strategies for ConVIRT, MoCoV2, MoCoV2-ConVIRT pretrained backbone