Proportional Allocation of Indivisible Resources under Ordinal and Uncertain Preferences

Abstract

We study a fair resource allocation problem with indivisible items. The agents' preferences over items are assumed to be ordinal and have uncertainties. We adopt stochastic dominance proportionality as our fairness notion and study a sequence of problems related to finding allocations that are fair with a high probability. We provide complexity analysis for each problem and efficient algorithms for some problems. Finally, we propose several heuristic algorithms to find an allocation that is fair with the highest probability. We thoroughly evaluate the performance of the algorithms on both synthetic and real datasets.

1 INTRODUCTION

The problem of fairly allocating a set of scarce resources among multiple agents has been a central research topic in multi-agent systems and AI. One of the most prominent fairness notions in fair division is *proportionality*, which states that each agent should receive enough resources which are at least $1/n$ of the utility when she receives all the resources, where n is the total number of the agents. Proportionality is one of the first studied fairness concepts in the literature. The existence of a proportional allocation can always be guaranteed when the resources are divisible. However, with indivisible items, proportional allocations may fail to exist in some cases; a simple example is when there are only two agents and one item which both agents valued positively.

A classic notion of proportionality is defined under the setting that each agent has a *cardinal* and *deterministic* valuation function over the items. In contrast, this paper studies *ordinal* and *uncertain* preferences over items. Considering only ordinal preferences is a natural and appealing assumption due to several reasons. To name a few, first, it is often much easier to elicit ordinal preferences from the agents

since it requires significantly less information. Second, some weaker fairness notions defined for ordinal preferences may permit more positive computational results for many problems. Finally, in certain applications, it's not available to get the cardinal preferences due to agents' limited knowledge on their valuations. In fact, the ordinal preferences have been widely studied in the resource allocation problems [Kuhn, 1955, Gardenfors, 1973, Demko and Hill, 1988, Bogomolnaia and Moulin, 2001, Burkard et al., 2009, David, 2013, Aziz et al., 2019b].

The assumption of uncertain preferences is also practical. In some settings the ordinal preferences may not be completely known due to a lack of information or a high cost to elicit a full preference list. Specifically, it may require a large number of pairwise comparisons among possible options to get the full preference order. It can also be difficult to even rank two close options without additional costly information [Drummond and Boutilier, 2014]. In addition, according to the study of uncertain preferences in [Aziz et al., 2019a], an agent's preference may be a composition of several preference lists from other agents she represents, or a combination of preferences from different criteria, where their weights are not determined.

In summary, the problem studied in this paper is to find a fair allocation for agents that have ordinal and uncertain preferences over items. In particular, the notion to define fairness under ordinal preferences is based on *stochastic dominance (SD)*, a standard way of comparing fractional allocations. We model the uncertain preferences following a similar way in Aziz et al. [2019a] and Aziz et al. [2016]. Specifically, we use tied sets to represent the items that the agents are not sure of their preferences towards and assume equal probabilities over each linear order extension of the preference order in the tied sets. This model of uncertainty is common for ordinal preferences. It has also been widely used in the matching literature [Rastegari et al., 2013, 2014, Drummond and Boutilier, 2014]. To the best of our knowledge, this paper is the first one to consider fair allocations under such preference settings and provide algorithmic and

Submitted to the 38ᵗʰ Conference on Uncertainty in Artificial Intelligence (UAI 2022). **To be used for reviewing only**.

complexity analysis for it.

1.1 OUR RESULTS

In this work, we study how to find proportionally fair allocations when the agents have ordinal and uncertain preferences. Inspired by Aziz et al. [2017b] which studies Pareto optimal allocations under similar preference models, we study the computational complexity of the following four problems:

- FAIRPROB: What is the probability that a given allocation is fair under the specific fairness definition?

- EXISTSPOSSIBLYFAIR: Does there exist an allocation that is fair with non-zero probability?

- EXISTSCERTAINLYFAIR: Does there exist an allocation that is fair with probability one?

- HIGHESTPROB: How to find an allocation with the highest probability of being fair under the specific fairness definition?

We focus on two fairness notions introduced in Aziz et al. [2015]: weak SD proportionality and SD proportionality. For each fairness notion, we present hardness results and efficient algorithms for the above four questions. Specifically, we show that for both fairness notions, FAIRPROB and EXISTSPOSSIBLYFAIR can be solved in polynomial time via dynamic programming and matching. EXISTSCERTAINLYFAIR and HIGHESTPROB are NP-hard. But we can provide polynomial-time algorithms for some special cases. For instance, if the number of agents is constant or the agents are all identical, we can efficiently find an allocation satisfying the corresponding condition. We summarize all the theoretical findings in Table 1.

Finally, noted the importance of HIGHESTPROB in many real-world scenarios, we propose several heuristic algorithms to find an allocation that is fair with a high probability. Experiments in both synthetic and real datasets are conducted to evaluate their performance and computation efficiency.

1.2 RELATED WORKS

In most existing literature, agents are assumed to have *cardinal* and *deterministic* valuations over items [Lipton et al., 2004, Brams et al., 2012, Bouveret and Lang, 2008, Bezáková and Dani, 2005].

Several works have considered ordinal preferences and weaker fairness notions [Kuhn, 1955, Gardenfors, 1973, Demko and Hill, 1988, Bogomolnaia and Moulin, 2001, Burkard et al., 2009, David, 2013, Aziz et al., 2015, Segal-Halevi et al., 2020, Bouveret et al., 2010]. Aziz et al. [2015] is the most related one. They used the stochastic dominance relation between fractional allocations to define various generalized notions of proportionality and envy-freeness and investigated the computational complexity of finding a fair assignment. They assume preferences are completely known and consider possibly indifferent preferences over items. In contrast, we assume that agents have strictly different preferences for different items but their preferences may not be completely known. We name the set of items with unknown preferences a tie. We model the preferences for items in a tie using uniformly distributed linear order extensions. It is worthwhile to note that assuming indifference for items with unknown preference can be regarded as an alternative way to model the uncertain preference. But we show that the fair allocation from such a modeling perspective can only be mapped to the certainly and possibly fair allocation in weak SD proportionality and SD proportionality, respectively in our work, after some small modifications.

Another stream of related literature considers uncertainties in agents' knowledge about their valuations [Lumet et al., 2012, Aziz et al., 2016, 2017b,a, 2019a, Menon and Larson, 2018]. The most related ones are Aziz et al. [2019a] and Aziz et al. [2017b], in which they study a Pareto optimal assignment problem. In their problem, agents also express ordinal and uncertain preferences. We adopt the way how they model the uncertain preferences but study a proportionally fair allocation problem. Lumet et al. [2012] considered a different fair division uncertainty model in which each item could be in either good or bad state with certain probabilities. They developed algorithms to find ex-post fair allocations assuming independent states over items and correlated valuations over agents. Different from their paper, we assume the states of the items are correlated but the agent valuations are independent.

2 PRELIMINARIES

Consider an allocation problem instance with a set of n agents $N = \{1, \ldots, n\}$ and a set of m indivisible items $O = \{o_1, \ldots, o_m\}$. Each agent i has a complete and transitive strict preference order $\succ_i$ over O. The *ranking* of an item for an agent is defined as the sequence of the item in the agent's preference list. Specifically, an item's ranking in an agent's preference equals the number of items preferred by the agent plus one. An *allocation* is a partition of items into n bundles $A = (A_1, \ldots, A_n)$, such that each agent i is allocated a bundle A_i. We also denote $[p]$ as the set $\{1, \ldots, p\}$ for any positive integer p.

Uncertainty in Preferences. In this work, we allow agents to express uncertainty in their preferences in terms of "ties". Specifically, we adopt an uncertainty model considered in Aziz et al. [2016] and Aziz et al. [2019a] (termed as a *compact indifference model* in their paper). In this model, each agent i is allowed to report a weak preference list. For instance, consider such a preference list $(S_{i,1}) \succ_i \ldots \succ_i$

Table 1: Theorectical results

	Weak SD Proportionality	SD Proportionality
FAIRPROB	in P (Thm 3.1)	in P (Thm 4.1)
EXISTSPOSSIBLYFAIR	in P (Thm 3.2)	in P (Thm 4.2)
EXISTSCERTAINLYFAIR	NP-Hard (Thm 3.3)
in P for constant n (Thm 3.5)
in P for identical agents (Thm 3.4)	NP-Hard (Thm 4.3)
in P when the number of equivalent classes
is at most 4 in all preferences. (Thm 4.4)
HIGHESTPROB	NP-hard (Thm 3.3)
in P for constant n (Thm 3.5)	NP-hard (Thm 4.3)

(S_{i,k_i}). Each $S_{i,j}$ is a tied set in the weak preference list that we call the jth *equivalent class* of agent i. The actual strict preference $\succ_i$ of agent i is then chosen uniformly at random from all linear order extensions of this weak order. The choices of the linear order extensions of different agents are independent. We denote k_i as the number of equivalent classes of agent i.

Example 1. Consider the following allocation problem with 2 agents and 4 items: agent 1 has preference $(a, b) \succ_1 (c, d)$, agent 2 has preference $(a) \succ_2 (b, c, d)$. In this instance, the strict preference of agent 1 may be $a \succ_1 b \succ_1 c \succ_1 d$ or $a \succ_1 b \succ_1 d \succ_1 c$ or $b \succ_1 a \succ_1 c \succ_1 d$ or $b \succ_1 a \succ_1 d \succ_1 c$, each with probability $1/4$, while the strict preference of agent 2 may be $a \succ_2 b \succ_2 c \succ_2 d$ or $a \succ_2 b \succ_2 d \succ_2 c$, or the rest 4 preferences generated by the permutation of b, c, d, each with probability $1/6$.

Proportional Fairness. When only ordinal preferences are available, Aziz et al. [2015] defined several fairness notions that generalize proportionality to the ordinal setting. In this work we consider the following two definitions based on *stochastic dominance(SD)*.

- *Weak Stochastic Dominance (SD) proportionality*: an allocation satisfies *weak SD proportionality* if for each agent i, there exists $1 \le k \le m$ such that agent i is allocated at least $\lfloor \frac{k}{n} + 1 \rfloor$ of her top k items.

- *Stochastic Dominance (SD) proportionality*: an allocation satisfies *SD proportionality* if for each agent i and $1 \le k \le m$, agent i is allocated at least $\lceil \frac{k}{n} \rceil$ of her top k items.

The above definitions of weak SD proportionality and SD proportionality are the simplifications of that in Aziz et al. [2015] when only considering strict preferences. This is when comparing a uniform allocation with another allocation of an agent using the original SD preference definition in Aziz et al. [2015], it reduces to the comparison between $\frac{k}{n}$ and the number of items allocated to this agent in her top k favorites for every $1 \le k \le m$ under strict preferences.

Example 1 (continued). For our example above, when considering weak SD proportionality, one certainly fair allocation is to assign items b, c, d to agent 1 and item a to agent 2. However, when considering SD proportionality, this allocation has probability 0 to be fair for agent 2. The allocation that has the highest probability to be SD proportional is to assign b, c to agent 1 and a, d to agent 2, with fair probability $\frac{1}{4} \cdot \frac{2}{3} = \frac{1}{6}$.

3 WEAK SD PROPORTIONALITY

In this section, we consider the weak SD proportionality. First we show that given an allocation, one can efficiently compute the probability that this allocation is weak SD proportional.

Theorem 3.1. FAIRPROB *with regard to weak SD proportionality can be solved in polynomial time.*

Proof. Because the uncertainty in each agent's preference is independent, it suffices to show that the probability that the fairness condition is met for each agent $i \in N$ can be computed in polynomial time. In the following, we use dynamic programming to calculate this probability.

For one specific agent $i \in N$, there are $K := k_i$ equivalent classes and the j-th equivalent class has $s_j := |S_{i,j}|$ items. Firstly, we calculate the number of items owned by i in the j-th equivalent class of i and we denote it by $r_j \le s_j$.

The key to this dynamic programming algorithm is to identify the subproblem structure. We use $P_{\mathsf{num,tot,dis}}$ to represent the probability that there are tot items owned by agent i arranged in the top num items with a fair verification parameter dis defined as follows:

$$\mathsf{dis} = \begin{cases} 0, & \text{if it's tranferred from the state with } \mathsf{dis}' = 0 \\ \max \left\{ 0, \left\lfloor \frac{\mathsf{num}}{n} + 1 \right\rfloor - \mathsf{tot} \right\}, & \text{otherwise} \end{cases}$$

Intuitively, dis shows the distance to weak SD proportionality and once it reaches 0, it will keep at 0.

The complete algorithm is shown in Algorithm 1. The key steps in this algorithm are the state transfers in Steps 3-21. We let sta represent the equivalent class that the $(\mathsf{num} + 1)$-ranked item belongs to, and let p represent the probability of the item with ranking $(\mathsf{num} + 1)$ owned by i under the present state in Steps 7-9.

Algorithm 1 FAIRPROB Algorithm

Require:
  m: number of items
  n: number of agents
  K: number of equivalent classes of agent i
  $s_{1,\dots,K}$: number of items in each equivalent classes
  $r_{1,\dots,K}$: number of items owned by agent i in each equivalent classes
1: $P_{\mathsf{num,tot,dis}} \leftarrow 0 \quad \forall 0 \leq \mathsf{num}, \mathsf{tot} \leq m, 0 \leq \mathsf{dis} \leq \lfloor \frac{m}{n} + 1 \rfloor$
2: $P_{0,0,1} \leftarrow 1$
3: **for** num $\leftarrow 0$ to $m - 1$ **do**
4:   **for** tot $\leftarrow 0$ to num **do**
5:     **for** dis $\leftarrow 0$ to $\lfloor \frac{m}{n} + 1 \rfloor$ **do**
6:       **if** $P_{\mathsf{num,tot,dis}} \neq 0$ **then**
7:         Let sta be the minimum integer such that $\sum_{j \in [\mathsf{sta}]} s_j \geq \mathsf{num} + 1$.
8:         PrevP $\leftarrow P_{\mathsf{num,tot,dis}}$
9:         $p \leftarrow \frac{\sum_{j \in [\mathsf{sta}]} r_j - \mathsf{tot}}{\sum_{j \in [\mathsf{sta}]} s_j - \mathsf{num}}$
10:        **if** dis $= 0$ **then**
11:          $P_{\mathsf{num}+1,\mathsf{tot}+1,\mathsf{dis}} \mathrel{+}= \text{PrevP} \cdot p$
12:          $P_{\mathsf{num}+1,\mathsf{tot},\mathsf{dis}} \mathrel{+}= \text{PrevP} \cdot (1 - p)$
13:        **else**
14:          Let id be 1 if num $+ 1$ is a multiple of n and 0 otherwise.
15:          $P_{\mathsf{num}+1,\mathsf{tot}+1,\max\{0,\mathsf{dis}+\mathsf{id}-1\}} \mathrel{+}= \text{PrevP} \cdot p$
16:          $P_{\mathsf{num}+1,\mathsf{tot},\mathsf{dis}+\mathsf{id}} \mathrel{+}= \text{PrevP} \cdot (1 - p)$
17:        **end if**
18:      **end if**
19:    **end for**
20: **end for**
21: **end for**
22: **return** $P_{m,\sum_{j \in [K]} r_j, 0}$

We consider the specific transfers in two cases. Steps 11-12 solve the first case with dis $= 0$ where we have already reached fairness and the remaining is to arrange the order of the rest items. Steps 14-16 solve the second case with dis > 0 where dis has never met 0 before and we need to update it based on the definition. In both these two cases, we need to update the state based on the situation of whether the next item is owned by agent i. Specifically, when dis $= 0$, if the next item is owned by agent i, there are tot $+ 1$ items owned by i arranged in the top num $+1$ items, so we transfer the state to $P_{\mathsf{num}+1,\mathsf{tot}+1,\mathsf{dis}}$ in Step 11, otherwise only tot items in i's bundle are arranged in the top num $+ 1$ items, which corresponds to the state $P_{\mathsf{num}+1,\mathsf{tot},\mathsf{dis}}$ in Step 12. For the case of dis > 0, on top of the change of tot, we also use id to record the change of the term $\lfloor \frac{\mathsf{num}}{n} + 1 \rfloor$ in the above definition of dis in Step 14. Then, we transfer the state to $P_{\mathsf{num}+1,\mathsf{tot}+1,\max\{0,\mathsf{dis}+\mathsf{id}-1\}}$ in Step 15 if the next item is

owned by i, or $P_{\mathsf{num}+1,\mathsf{tot},\mathsf{dis}+\mathsf{id}}$ in Step 16 otherwise.

Finally, Step 22 returns the probability that the fairness condition is met for agent i with her all owned items. □

We further show that EXISTSPOSSIBLYFAIR can also be solved in polynomial time based on Theorem 7 in Aziz et al. [2015]. We defer the detailed proof to the online supplement.

Theorem 3.2. EXISTSPOSSIBLYFAIR *with regard to weak SD proportionality can be solved in polynomial time.*

Next we turn to EXISTSCERTAINLYFAIR problem. Unlike EXISTSPOSSIBLYFAIR, we show that it is NP-hard to determine whether there exists an allocation that is weak SD proportional with probability one. To prove this hardness result, we reduce from a known NP-hard problem denote as (2,2)-E3-SAT [Berman et al., 2004].

(2,2)-E3-SAT: Given a boolean formula in conjunctive normal form in which each clause has three literals and each variable occurs exactly twice positive and twice negative, decide whether this boolean formula is satisfiable.

Theorem 3.3. EXISTSCERTAINLYFAIR *and* HIGHEST-PROB *with regard to weak SD proportionality are NP-hard.*

Proof. We reduce from (2,2)-E3-SAT to EXISTSCERTAINLYFAIR, which can also imply NP-hardness for HIGHESTPROB. Considering a (2,2)-E3-SAT instance F with s variables $X = \{x_1, \dots, x_s\}$ and t clauses which satisfies $4s = 3t$. Based on F we construct a problem instance of EXISTSCERTAINLYFAIR with $6s$ agents and $12s$ items.

The agents are divided into two sets. The first is a set of $2s$ agents $A = \{A_1, \dots, A_{2s}\}$ where A_{2k-1} corresponds to the true valuation of x_k and A_{2k} corresponds to the false valuation of x_k for each $k \in [s]$. The second set is the set of the remaining $4s$ dummy agents $A' = \{A'_1, \dots, A'_{4s}\}$.

The $12s$ items are divided into five sets as follows:

- A set of t items $C = \{C_1, \dots, C_t\}$, where C_i corresponds to the i-th clause in (2,2)-E3-SAT;

- A set of $t/2$ items $T = \{T_1, \dots, T_{t/2}\}$, given to the agents corresponding to the correct value of variables together with the items in C;

- A set of s items $S = \{S_1, \dots, S_s\}$, compensated for the agents corresponding to the wrong value of variables;

- A set of $6s$ dummy items $B = \{B_1, \dots, B_{6s}\}$, where each 2 items are bound to $3s$ agents in A';

- A set of $3s$ dummy items $Q = \{Q_1, \dots, Q_{3s}\}$, where each 3 items are bound to the remaining s agents in A'.

Next, we construct the preference lists for agents. For each agent $A_i \in A$, we denote R_i as a set of items such that: for each $k \in [s]$, R_{2k-1} and R_{2k} consist of the two items in C corresponding to the clauses containing the positive x_k and the negative x_k respectively. The preference of each agent A_i in A is: $S_{\lceil i/2 \rceil} \succ (R_i, T, B) \succ$ (others). The preference of each dummy agent A_i' in A' is: $(B) \succ$ (others).

An example of this construction is shown below.

Example 2. Consider a simple (2,2)-E3-SAT problem instance with $s = 3$ variables and $t = 4$ clauses:

1. $x_1 \vee x_2 \vee \neg x_3$ 2. $x_1 \vee \neg x_2 \vee x_3$

3. $\neg x_1 \vee x_2 \vee x_3$ 4. $\neg x_1 \vee \neg x_2 \vee \neg x_3$

The corresponding instance of EXISTSCERTAINLYFAIR has 18 agents and 36 items. The preference lists are as follows:

- Agent 1: $S_1 \succ (C_1, C_2, T_1, T_2, B_1, \ldots, B_{18}) \succ (S_2, S_3, C_3, C_4, Q_1, \ldots, Q_9)$
- Agent 2: $S_1 \succ (C_3, C_4, T_1, T_2, B_1, \ldots, B_{18}) \succ (S_2, S_3, C_1, C_2, Q_1, \ldots, Q_9)$
- Agent 3: $S_2 \succ (C_1, C_3, T_1, T_2, B_1, \ldots, B_{18}) \succ (S_1, S_3, C_2, C_4, Q_1, \ldots, Q_9)$
- Agent 4: $S_2 \succ (C_2, C_4, T_1, T_2, B_1, \ldots, B_{18}) \succ (S_1, S_3, C_1, C_3, Q_1, \ldots, Q_9)$
- Agent 5: $S_3 \succ (C_2, C_3, T_1, T_2, B_1, \ldots, B_{18}) \succ (S_1, S_2, C_1, C_4, Q_1, \ldots, Q_9)$
- Agent 6: $S_3 \succ (C_1, C_4, T_1, T_2, B_1, \ldots, B_{18}) \succ (S_1, S_2, C_2, C_3, Q_1, \ldots, Q_9)$
- Agent 7-18: $(B_1, \ldots, B_{18}) \succ (S_1, S_2, S_3, C_1, \ldots, C_4, T_1, T_2, Q_1, \ldots, Q_9)$

If the (2,2)-E3-SAT instance has a satisfying assignment, we can construct an allocation as follows:

- If variable x_i is TRUE, we assign S_i to A_{2i}, otherwise we assign S_i to A_{2i-1};
- For the j-th clause, suppose the first true term in it is about x_i. Then, if this term is positive x_i, we assign C_j to A_{2i-1}, otherwise we assign C_j to A_{2i}.
- For agents in A who do not receive any S_i, we assign items in T to them so that these agents can each receive exactly two items. We know this can be satisfied because $2s = t + t/2$.
- Finally, we assign two items in B to each of the first $3s$ agents in A' and assign three items in Q to each of the remaining s agents in A' arbitrarily.

For the agents in A who get an item in S, their fairness conditions are met because they get their unique most preferred

item respectively. Each of the remaining agents in A gets exactly two items that are not least preferred by them, so their fair conditions are also met. Finally, agents in A' also meet the fair conditions because either they receive two items that they do not prefer the least, or they receive three items. Thus, this allocation must satisfy weak SD proportionality.

On the other hand, assume there is an allocation that is weak SD proportional with probability one, we can construct a satisfying assignment for the (2,2)-E3-SAT instance. First, the agents in A who do not receive their most preferred item must get at least two items to meet the fair condition. Because there are at most s agents that can receive items in S, at least s agents in A need at least two items. Next, for the agents in A', they can meet the fairness condition if and only if they receive either two items in B or three items. Because of the limit of the number of items in B, at most $3s$ agents in B can meet the fair condition with only two items.

We can consider the most optimistic situation: s agents in A each get their most preferred item in S and the remaining s agents in A get exactly two items in their respective second equivalent class but not in B; $3s$ agents in A' each get exactly two items in B while the remaining s agents in A' each get three items. The number of items needed in total is $12s$, which means that this situation is necessary.

Therefore, for any $k \in [s]$, exactly one agent between A_{2k-1} and A_{2k} gets the corresponding S_k while the other one needs to get two items from $C \cup T$, whose size is $t/2 + t = 2s$. This means each item in C must be chosen by the agents in A, and this will lead to a satisfying assignment for (2,2)-E3-SAT with such value scheme: for each pair A_{2k-1} and A_{2k} with $k \in [s]$, we set $x_k =$ FALSE if A_{2k-1} gets S_k otherwise we set $x_k =$ TRUE.

Example 2 (continued). The above mentioned (2,2)-E3-SAT instance is satisfiable by setting $x_1 =$ TRUE, $x_2 =$ TRUE, $x_3 =$ FALSE. We can get the corresponding allocation for the EXISTSCERTAINLYFAIR instance:

- The agent representing the wrong valuation of each variable takes the corresponding item in S: agent 2, 4 and 5 takes their respective S_1, S_2, S_3.
- Each item representing the clause is taken by the agent representing the first true term: agent 1 takes C_1, C_2, agent 3 takes C_3, and agent 6 takes C_4, and T_1, T_2 are given to agent 3 and 6 as a compensation.
- Each two of $B_{1,\ldots,18}$ are assigned to agent $7 - 15$, and each three of $Q_{1,\ldots,9}$ are assigned to agent $16 - 18$.

One can check that this is a certainly fair allocation in our EXISTSCERTAINLYFAIR instance.

$\square$

Next we present several positive results on solving EX-ISTSCERTAINLYFAIR and HIGHESTPROB for special cases.

Theorem 3.4. EXISTSCERTAINLYFAIR *with regard to weak SD proportionality can be solved in polynomial time when all agents have identical preferences.*

Theorem 3.5. EXISTSCERTAINLYFAIR *and* HIGHESTPROB *with regard to weak SD proportionality can be solved in polynomial time when the number of agents is constant.*

4 SD PROPORTIONALITY

In this section, we turn our focus to SD proportionality. This is a stronger fairness requirement than weak SD proportionality. Similar to the weak SD proportionality case, we show that with regard to SD proportionality, FAIRPROB and EXISTSPOSSIBLYFAIR can be solved in polynomial time, while EXISTSCERTAINLYFAIR and HIGHESTPROB are both NP-hard. The techniques we use to prove these results are similar in spirit to those for weak SD proportionality. However, due to the difference between these two fairness concepts, adjustments need to be made to the proofs to make them work in the SD proportionality setting. For example, to prove the NP-hardness for EXISTSCERTAINLY-FAIR and HIGHESTPROB with regard to SD proportionality, we need to reduce from another NP-hard problem known as X3C from Johnson and Garey [1979].

Below we list all the results in this section. The details of all proofs, except the proof of Theorem 4.4, are deferred to the supplementary material due to page limits.

Theorem 4.1. FAIRPROB *with regard to SD proportionality can be solved in polynomial time.*

Theorem 4.2. EXISTSPOSSIBLYFAIR *with regard to SD proportionality can be solved in polynomial time.*

Theorem 4.3. EXISTSCERTAINLYFAIR *and* HIGHEST-PROB *with regard to SD proportionality are NP-hard.*

In the proof of Theorem 4.3, we can see even the number of equivalent classes of each agent is 6, EXISTSCERTAINLY-FAIR is still NP-hard.

Theorem 4.4. EXISTSCERTAINLYFAIR *with regard to SD proportionality can be solved in polynomial time if the number of equivalent classes of each agent is at most* 4.

Proof. SD proportionality with probability one is a very demanding condition. We first list some properties that such an allocation must satisfy. First, a direct corollary from Aziz et al. [2015] shows that such an allocation may exist only when $m = qn$ for some integer q and each agent gets exactly q items.

Second, each agent must get all items in her first equivalent class to meet the fair condition with $k = 1$. Each agent also cannot get any items in her last equivalent class. This is because, suppose agent i gets at least one item in her last equivalent class, we can make this item her least favorite item, so we need to use the other $q - 1$ items to satisfy all fair conditions with $k \leq qn - 1$, which is impossible when $n > 1$. These two conditions also imply that the number of equivalent classes for each agent must be greater than 1 and the number of items in the first equivalent class must be no more than q for a certainly fair allocation to exist.

We will utilize the above characterizations to determine the existence of a certainly SD proportional allocation. More specifically, we will reduce the EXISTSCERTAINLYFAIR problem to a max-flow problem in a flow network G. The construction is as follows. Let the flow network $G = (V, E)$ with a capacity function $c : E \mapsto \mathbb{R}^+$. V consists of a source vertex s, a target vertex t, a vertex set A defined later and a vertex set B of m vertices representing the m items. For each vertex j in B, we create an edge (j, t) with capacity $c = 1$. Next, for each agent i, we construct its vertices in A depending on the number k_i of its equivalent classes.

- $k_i = 2$: Because we cannot give agent i any items in her last equivalent class and each agent must get all items in her first equivalent class, we must have $|S_{i,1}| = q$, otherwise there is no certainly fair allocation. Thus, we create a vertex i in A representing agent i, and construct edges (i, j) with capacity $c = 1$ for each vertex $j \in S_{i,1}$ in B. We also construct an edge pointing from the source s to i with capacity $c = q$.

- $k_i = 3$: Similar to the case $k_i = 2$, agent i must get all items in $S_{i,1}$ and the remaining $q - |S_{i,1}|$ items from $S_{i,2}$. We can use the algorithm for FAIRPROB to check whether such an allocation can meet agent i's fairness condition with probability one. If not, it means there does not exist a certainly fair allocation. Otherwise, we create two vertices i_1, i_2 in A for agent i.
  - The first vertex i_1 has an edge (s, i_1) with $c = |S_{i,1}|$, and edges (i_1, j) with $c = 1$ for each vertex $j \in S_{i,1}$ in B;
  - The second vertex i_2 has an edge (s, i_2) with $c = q - |S_{i,1}|$, and edges (i_2, j) with $c = 1$ for each vertex $j \in S_{i,2}$ in B.

- $k_i = 4$: This is the most complicated case. We assume that the numbers of items owned by agent i in the first three equivalence classes are x, y, z. It must satisfies $x = |S_{i,1}|$ and $x + y + z = q$. Once the value of x is fixed, we observe that the probability that agent i meets the fair condition increases with y. So we can find the minimum $y' \leq \min\{q - x, |S_{i,2}|\}$ such that i can meet her fair condition with probability one. If there exists no such y', there is no certainly fair allocation for this instance. Otherwise, we know for all eligible $y \geq y'$, agent i can always meet the fair condition with probability 1. Following this idea, we create three

vertices i_1, i_2, i_3 in A for i:

- the first vertex i_1 has an edge (s, i_1) with $c = x$, and edges (i_1, j) with $c = 1$ for each vertex $j \in S_{i,1}$ in B;
- the second vertex i_2 has an edge (s, i_2) with $c = y'$, and edges (i_2, j) with $c = 1$ for each vertex $j \in S_{i,2}$ in B;
- the third vertex i_3 has an edge (s, i_3) with $c = q - x - y'$, and edges (i_3, j) with $c = 1$ for each vertex $j \in S_{i,2} \cup S_{i,3}$ in B. The intuition for this step is to allow the allocation to give more items to agent i in $S_{i,2}$.

With this construction, one can check that if there exists a maximum flow with value $m = qn$, the corresponding allocation must be SD proportional with probability one, because it meets all fair conditions for each agent according to our analysis. $\qquad\square$

Remark: The algorithm can not be directly generalized to the case when some agent i has more than 4 equivalent classes. To see it, note that if we continue to use this approach and assume that the number of items owned by agent i in her top four equivalent classes are x, y, z, w, we still have $x = |S_{i,1}|$ and $x + y + z + w = q$. But it is no longer true that the fair probability is monotone increasing with both y and z. This is because the fair probability may decrease if z decreases even when y increases.

5 EXPERIMENTS

In this section, we focus on HIGHESTPROB with respect to weak SD proportionality given the importance of finding allocations with a high fair probability. Since we have shown this problem is NP-hard, we will only present several heuristic algorithms for it. The performance and computational efficiency are evaluated on both synthetic and real datasets.

5.1 ALGORITHMS

We design and evaluate four algorithms for HIGHESTPROB. The details and parameters used in each algorithm can be found in the supplementary material.

1. **BASELINE (B)**: This is a baseline algorithm that assigns each item to a random agent to get a random allocation.

2. **LOCALSEARCH (LS)**: This is a local search algorithm that repeatedly move one item from one agent to another until the allocation reaches a local optima.

3. **MATCHING (M)**: This is a multi-round matching algorithm that matches each agent to an item in each round. In particular, the weight of each arc linking an agent

to an item is based on a function of the item's possible rankings in the agent's preference list. We apply multi-round maximum weight matching algorithms to assign the items to each agent.

4. **GREEDY (G)**: This algorithm first converts HIGHESTPROB to a submodular welfare maximization problem and then uses a greedy algorithm from Lehmann et al. [2006] to output a 2-approximation solution.

5.2 DATASETS

We test the above four algorithms on both synthetic and real datasets.

1. **Synthetic dataset**: We enumerate n from 2 to 20 and m from n to $5n$. For each $p \in \{0.02, 0.03, 0.04, 0.05, 0.06\}$, we create 30 datasets in the following way: For each agent we create a random permutation of all items. For each pair of adjacent items in the permutation, we separate them into two equivalent classes with probability p. We choose p to be in this range because when p becomes larger, all the four algorithms can easily find an almost certainly fair assignment and there is no significant difference in their performance.

2. **Real dataset**: We use the Preflib database from Mattei and Walsh [2013], which is an online database of real-world preference profiles to test our algorithms. We select 11 datasets from two categories in this database:

   (a) *Matching Data (MD-00002)*: This category contains bidding preferences of reviewers over a subset of papers at Computer Science conferences. Each preference is an incomplete list with ties. We convert each preference into a complete list with ties by adding the remaining items as the last equivalent class. This category has 3 datasets corresponding to 3 different conferences.

   (b) *Matching Data (MD-00003)*: This category contains bids of students over a set of projects for student/project allocations at a university. It has 8 datasets in total, all with complete preferences with ties, with 31-51 students and 56-155 projects.

5.3 RESULTS AND DISCUSSIONS

5.3.1 Synthetic dataset

We measure the performance of each algorithm by the average fair probability across various tested datasets. Figure 1 shows the average fair probability generated by each algorithm for each n from 2 to 20. Each average fair probability is taken over multiple datasets with different m and p. Figure 2 presents the average running time of each algorithm.

Figure 1: Algorithm performance over synthetic data

Figure 2: Algorithm running time over synthetic data

From the figures, one can see that LOCALSEARCH, MATCH-ING and GREEDY generate allocations with a much higher average fair probability than BASELINE when the number of agents is at least 5. Besides, when the number of agents n increases, the running time of LOCALSEARCH increases significantly, while BASELINE, MATCHING, and GREEDY keep low running time. In summary, GREEDY and MATCH-ING require the least running time and perform the best consistently for different values of n.

5.3.2 Real dataset

Table 2 presents the fair probabilities of the suggested allocations by each algorithm on 11 real datasets. Table 3 further provides their running times. In the real datasets, BASELINE still performs the worst. The other three algorithms can generate allocations that are fair with probability 1 for most cases, with two exceptions for LOCALSEARCH and one exception for GREEDY. MATCHING is the only algorithm that performs consistently well. In terms of the running time, LOCALSEARCH takes much longer than the other three. The BASELINE and MATCHING take a little more time than GREEDY. But it is still acceptable.

Table 2: Fair probability of all algorithms over real data (sorted by the number of agents n)

no.	n	m	B	LS	M	G
1	24	52	0.03	1.00	1.00	1.00
2	31	54	0.11	1.00	1.00	1.00
3	31	103	0.02	1.00	1.00	1.00
4	32	102	0.06	1.00	1.00	1.00
5	34	63	0.23	1.00	1.00	1.00
6	35	61	0.01	1.00	1.00	1.00
7	37	56	0.00	0.01	1.00	1.00
8	38	133	0.03	1.00	1.00	1.00
9	51	147	0.28	1.00	1.00	1.00
10	51	155	0.00	1.00	1.00	1.00
11	146	176	0.00	0.00	1.00	0.37

Table 3: Running time(s) of all algorithms over real data (sorted by the number of agents n)

no.	n	m	B	LS	M	G
1	24	52	0.074	0.908	0.058	0.003
2	31	54	0.078	1.017	0.075	0.005
3	31	103	1.008	29.54	0.212	0.024
4	32	102	1.127	40.02	0.264	0.025
5	34	63	0.143	0.738	0.120	0.006
6	35	61	0.172	1.798	0.140	0.006
7	37	56	0.126	2.531	0.131	0.006
8	38	133	2.148	63.73	0.388	0.039
9	51	147	2.410	9.612	0.618	0.039
10	51	155	3.250	480.7	0.687	0.055
11	146	176	3.559	9255	5.533	0.064

In conclusion, according to the results from both synthetic and real data, LOCALSEARCH has a good performance at a high computation cost. GREEDY has decent performance with the best computation efficiency. MATCHING is a balanced algorithm with consistently good performance and high computation efficiency.

6 CONCLUSIONS

In this paper, we present algorithmic and complexity results in computing fair allocations assuming agents' preferences over items are ordinal and have uncertainties. Under the proposed fair notions, we provide polynomial-time solvable algorithms to find the probability that a given allocation is fair and determine whether there exists an allocation with non-zero fair probability. We show that it is NP-hard to see whether there exists an allocation that is fair with probability one. Finally, we show that to find an allocation with the highest fair probability is NP-hard. We further provide several heuristics for this problem. The performance of the heuristics is examined thoroughly on both synthetic and real datasets. One possible direction for future work is to consider other fairness concepts in the context of ordinal and uncertain preferences and study approximation algorithms to find fair allocations. It is also interesting to combine the fairness notions with other properties such as stability in the uncertain ordinal preference setting.

References

Haris Aziz, Serge Gaspers, Simon Mackenzie, and Toby Walsh. Fair assignment of indivisible objects under ordinal preferences. *Artificial Intelligence*, 227:71–92, 2015.

Haris Aziz, Péter Biró, Serge Gaspers, Ronald De Haan, Nicholas Mattei, and Baharak Rastegari. Stable matching with uncertain linear preferences. In *International Symposium on Algorithmic Game Theory*, pages 195–206. Springer, 2016.

Haris Aziz, Péter Biró, Tamás Fleiner, Serge Gaspers, and Ronald de Haan. Stable matching with uncertain pairwise preferences. 2017a.

Haris Aziz, Ronald De Haan, and Baharak Rastegari. Pareto optimal allocation under uncertain preferences. In *Proceedings of the 16th Conference on Autonomous Agents and MultiAgent Systems*, pages 1472–1474. International Foundation for Autonomous Agents and Multiagent Systems, 2017b.

Haris Aziz, Peter Biro, Ronald de Haan, and Baharak Rastegari. Pareto optimal allocation under compact uncertain preferences. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 1740–1747, 2019a.

Haris Aziz, Peter Biro, Jérôme Lang, Julien Lesca, and Jérôme Monnot. Efficient reallocation under additive and responsive preferences. *Theoretical Computer Science*, 790:1–15, 2019b.

Piotr Berman, Marek Karpinski, and A Scott. Approximation hardness of short symmetric instances of max-3sat. Technical report, 2004.

Ivona Bezáková and Varsha Dani. Allocating indivisible goods. *ACM SIGecom Exchanges*, 5(3):11–18, 2005.

Anna Bogomolnaia and Hervé Moulin. A new solution to the random assignment problem. *Journal of Economic theory*, 100(2):295–328, 2001.

Sylvain Bouveret and Jérôme Lang. Efficiency and envy-freeness in fair division of indivisible goods: Logical representation and complexity. *Journal of Artificial Intelligence Research*, 32:525–564, 2008.

Sylvain Bouveret, Ulle Endriss, Jérôme Lang, et al. Fair division under ordinal preferences: Computing envy-free allocations of indivisible goods. In *ECAI*, pages 387–392, 2010.

Steven J Brams, Michal Feldman, John K Lai, Jamie Morgenstern, and Ariel D Procaccia. On maxsum fair cake divisions. In *Twenty-sixth AAAI Conference on Artificial Intelligence*, 2012.

Rainer E Burkard, Mauro Dell'Amico, and Silvano Martello. *Assignment problems*. Springer, 2009.

Manlove David. *Algorithmics of matching under preferences*, volume 2. World Scientific, 2013.

Stephen Demko and Theodore P Hill. Equitable distribution of indivisible objects. *Mathematical Social Sciences*, 16 (2):145–158, 1988.

Joanna Drummond and Craig Boutilier. Preference elicitation and interview minimization in stable matchings. In Carla E. Brodley and Peter Stone, editors, *Proceedings of the Twenty-Eighth AAAI Conference on Artificial Intelligence, July 27 -31, 2014, Québec City, Québec, Canada*, pages 645–653. AAAI Press, 2014. URL http://www.aaai.org/ocs/index.php/AAAI/AAAI14/paper/view/8585.

Peter Gardenfors. Assignment problem based on ordinal preferences. *Management Science*, 20(3):331–340, 1973.

David S Johnson and Michael R Garey. *Computers and intractability: A guide to the theory of NP-completeness*, volume 1. WH Freeman San Francisco, 1979.

Harold W Kuhn. The hungarian method for the assignment problem. *Naval research logistics quarterly*, 2(1-2):83–97, 1955.

Benny Lehmann, Daniel Lehmann, and Noam Nisan. Combinatorial auctions with decreasing marginal utilities. *Games and Economic Behavior*, 55(2):270–296, 2006.

Richard J Lipton, Evangelos Markakis, Elchanan Mossel, and Amin Saberi. On approximately fair allocations of indivisible goods. In *Proceedings of the 5th ACM conference on Electronic commerce*, pages 125–131. ACM, 2004.

Charles Lumet, Sylvain Bouveret, and Michel Lemaître. Fair division of indivisible goods under risk. In *Proceedings of the 20th European Conference on Artificial Intelligence (ECAI'12)*, volume 242, pages 564–569. IOS Press, 2012.

Nicholas Mattei and Toby Walsh. Preflib: A library for preferences http://www. preflib. org. In *International Conference on Algorithmic DecisionTheory*, pages 259–270. Springer, 2013.

Vijay Menon and Kate Larson. Robust and approximately stable marriages under partial information. In *International Conference on Web and Internet Economics*, pages 341–355. Springer, 2018.

Baharak Rastegari, Anne Condon, Nicole Immorlica, and Kevin Leyton-Brown. Two-sided matching with partial information. In Michael J. Kearns, R. Preston McAfee, and Éva Tardos, editors, *Proceedings of the fourteenth ACM*

Conference on Electronic Commerce, EC 2013, Philadelphia, PA, USA, June 16-20, 2013, pages 733–750. ACM, 2013. doi: 10.1145/2492002.2482607. URL `https://doi.org/10.1145/2492002.2482607`.

Baharak Rastegari, Anne Condon, Nicole Immorlica, Robert W. Irving, and Kevin Leyton-Brown. Reasoning about optimal stable matchings under partial information. In Moshe Babaioff, Vincent Conitzer, and David A. Easley, editors, *ACM Conference on Economics and Computation, EC '14, Stanford , CA, USA, June 8-12, 2014*, pages 431–448. ACM, 2014. doi: 10.1145/2600057.2602884. URL `https://doi.org/10.1145/2600057.2602884`.

Erel Segal-Halevi, Avinatan Hassidim, and Haris Aziz. Fair allocation with diminishing differences. *Journal of Artificial Intelligence Research*, 67:471–507, 2020.

Proportional Allocation of Indivisible Resources under Ordinal and Uncertain Preferences
(Supplementary Material)

A MISSING PROOFS IN SECTION 3

Theorem 3.2. EXISTSPOSSIBLYFAIR with regard to weak SD proportionality can be solved in polynomial time.

Proof. Theorem 7 in Aziz et al. [2015] showed that when agents have strict and deterministic preferences, a weak SD proportional allocation exists if and only if (1) $m = n$ and no item is least preferred by all agents, or (2) $m > n$. Furthermore, when such allocation exists, it can also be found in polynomial time.

This result allows us to derive a simple algorithm for EXISTSPOSSIBLYFAIR. First, when $m > n$, we can simply find an arbitrary set of linear extensions and compute a corresponding weak SD proportional allocation. When $m = n$, we need to find a set of linear extensions in which no item is least preferred by all agents, then compute a weak SD proportional allocation with regard to this preference profile. To find such a preference profile, we can construct a bipartite graph between the agents and the items, such that an edge exists if and only if the item is not least preferred by the agent in some preference profiles. If there exists a perfect matching in this bipartite graph, this perfect matching corresponds to an allocation that is weak SD proportional with non-zero probability. If the graph does not have a perfect matching, because each agent has at least $n - 1$ edges, by Hall's marriage theorem [Hall, 2009], there must exist one item which is least preferred by all agents in all preference profiles. Thus, there is no allocation with non-zero fair probability. $\square$

Theorem 3.4. EXISTSCERTAINLYFAIR with regard to weak SD proportionality can be solved in polynomial time when all agents have identical preferences.

Proof. Firstly, we simplify some notions when agents have identical preferences: we use K to represent the number of equivalent classes and use S_j to represent the j-th equivalent class. Then we re-number all items with indices 1 to n such that $S_1 = \{1, \ldots, |S_1|\}$ and $S_j = \{\sum_{k=1}^{j-1} |S_k| + 1, \ldots, \sum_{k=1}^{j} |S_k|\}$ for each $1 < j \leq K$. This means for all agents, smaller-indexed items are always more preferred.

We consider the following greedy algorithm. For each agent from 1 to n, we consider the remaining items in increasing order of indices, and allocate them to this agent one by one, until the current allocation met the fairness condition for this agent with probability 1. We repeat this process until all items are fully allocated or all agents have received their desired bundles of items.

In the following, we show that if a certainly fair allocation M exists in a problem instance, the above greedy algorithm can always return such a certainly fair allocation.

Next, we perform a three-step transformation on the given certainly fair allocation M:

- For each agent i, if removing the item with largest index in her bundle can still keep her fairness condition met, we will remove that item from i's bundle. Repeat this process until no items can be removed anymore. After this step, we denote sta_i as the equivalent class the worst item in i's bundle belongs to. Then, for any agent i, she could not have her fairness condition met after throwing the present worst item and all owned items are always least preferred in their respective equivalent classes in the worst case, so there must exist $\sum_{j=1}^{\mathsf{sta}_i - 1} |S_j| < k_i \leq \sum_{j=1}^{\mathsf{sta}_i} |S_j|$ such that agent i is allocated at least $\lfloor \frac{k_i}{n} + 1 \rfloor$ of her top k_i items in the worst case mentioned above.

- Next, we find any agent who has item o that has a larger index than some thrown away item o', and we replace o with o'. Again repeat this process until no such changes can be made. We know M is still certainly fair. After this step, the present allocation must contain exactly all the items in $[m']$ for some $m' \leq m$.

- Finally, if there exists agent i and j such that the worst item in i's bundle has a larger index than the worst items in j's bundle, and agent i also has an item o_i

Submitted to the 38th Conference on Uncertainty in Artificial Intelligence (UAI 2022). **To be used for reviewing only.**

with a smaller index than some item o_j belonging to agent j, we will be able to swap o_i and o_j while still keeping the fairness conditions for both agents. This obviously holds for agent j. For agent i, this claim is true because o_j is still not worse than the worst item in i's bundle and it still holds that agent i is allocated at least $\lfloor \frac{k_i}{n} + 1 \rfloor$ of her top k_i items in the worst case for that k_i. Repeat this until no more exchanges can be made. After this step, we know the allocation must still be certainly fair and it is a consecutive partition of $[m']$ for some $m' \leq m$.

Finally, it is easy to see if there exists a consecutive partition that is certainly fair, the allocation computed by our greedy algorithm must be also certainly fair. $\qquad\square$

Theorem 3.5. EXISTSCERTAINLYFAIR and HIGHESTPROB with regard to weak SD proportionality can be solved in polynomial time when the number of agents is constant.

Proof. Let $m = qn + r$, where q, r are integers and $0 \leq r < n$.

First, we observe that any agent who gets $q + 1$ items is always weak SD proportional with probability one. Thus we can assume that no agent gets more than $q + 1$ items in the allocation with the highest fair probability. This also implies that every agent gets at least $q_m = q - (n - 1 - r)$ items, because otherwise the total number of allocated items will be less than $q - (n - 1 - r) + (n - 1)(q + 1) = qn + r = m$.

If there exists some agent i such that $|S_{i,1}| < n \cdot q_m$, we can choose $\min\{|S_{i,1}|, q_m\}$ items from $S_{i,1}$ to be allocated to agent i, which guarantees the fair condition for agent i to be met with probability one. Next, we assign all other agents $q + 1$ arbitrary items each and give the remaining items back to i. It is easy to check that this allocation is weak SD proportional with probability one.

Now we consider the case where $|S_{i,1}| \geq n \cdot q_m$ holds for every agent $i \in N$. This means that the total number of items not in the first equivalent class for any agent is no more than $n(n - 1 - r) + r$.

For each agent i, if there exists an integer $1 \leq j < |k_i|$, such that $1 + \sum_{t=1}^{j-1} |S_{i,t}| \geq (q' - 1)n$ and $\sum_{t=1}^{j+1} |S_{i,t}| < q'n$ for some $q' \leq q + 1$, then the items in the j-th and $(j + 1)$-th equivalent classes can be merged into one equivalent class without affecting the fair probability of any allocation, because all items in these two equivalent classes will always have the ranking in the range between $(q' - 1)n$ and $q'n - 1$. We don't really care about the specific ranking in this range because we can simplify the definition of weak SD proportionality to only consider whether there exists $k \in \{n - 1, 2n - 1, \ldots, qn - 1, m\}$ such that agent i is allocated at least $\lfloor \frac{k}{n} + 1 \rfloor$ of her top k items. We repeatedly merge such adjacent equivalent classes until none can be found.

By the end of this procedure, the total number of equivalent classes in each agent's preference list is no more than $1 + 2 \cdot (n - 1 - r + 1) = 2(n - r) + 1$.

Next, we enumerate the number of items assigned to each agent i from each equivalent class. More specifically, for each agent i, we first enumerate the total number of items in her bundle and then the number $C_{i,j}$ of items in each $S_{i,j}$ assigned to agent i. For each set of numbers $\{C_{i,j}\}$, we use the following perfect matching algorithm to find candidate allocations.

- We construct the bipartite graph $G = (A \cup B, E)$ where A has $C_{i,j}$ duplicate vertices representing the positions for items in $S_{i,j}$ for each agent $i \in [n]$ and each equivalent class $j \in [k_i]$, and B contains m vertices each representing an item. For each duplicate vertex for $S_{i,j}$ in A and each vertex in B corresponding to the item in $S_{i,j}$, there is an edge between them in E;

- If there exists a perfect matching between A and B (which also implies $|A| = |B|$), we pick the allocation where each item whose corresponding vertex is matched with one duplicate vertex for one $S_{i,j}$ is assigned to agent i and it meets our requirements.

If such allocation exists, its fair probability can be computed using the algorithm designed for FAIRPROB. Finally, we return the allocation with the highest fair probability.

Finally we analyze the time complexity of the above algorithm. The first step takes $O(nm)$ to enumerate each agent and each item. Merging equivalent classes also takes $O(nm)$ time. Next, for the enumeration step, because each number $C_{i,j} \leq n(n - 1 - r) + r$ when $j > 1$ and the total number of items in any bundle is between $q - (n - 1 - r)$ and $q + 1$, the total number of possibilities is $O((n(n - 1 - r) + r + 1)^{2(n-r)\cdot n} \cdot (n - 1 - r + 1 + 1)^n) = O(n^{4n^2+n+1})$. Finally, deciding the existence of an allocation and calculating its fair probability takes $O(m^3)$ time. Thus, the overall time complexity of this algorithm is $O(n^{4n^2+n+1} \cdot m^3)$. $\qquad\square$

B MISSING PROOFS IN SECTION 4

Theorem 4.1. FAIRPROB with regard to SD proportionality can be solved in polynomial time.

Proof. Similar to the case of FAIRPROB with regard to weak SD proportionality, we can compute the fair probability of an allocation by calculating the probability that each agent meets the fair condition independently. We again use dynamic programming to calculate the probability of each $i \in N$ satisfying the fair condition.

Fix one specific agent $i \in N$, we know there are $K := k_i$ equivalent classes and the j-th equivalent class has $s_j := |S_{i,j}|$ items. We first calculate the number of items owned

by i in the j-th equivalent class of i and we denote it by $r_j \leq s_j$.

When calculating the fair probability of one agent, we care only about the number of items owned by this agent i among her top s items for each integer $s \in [m]$, but not the specific ranking of any single item. Thus, we use $P_{\mathsf{num,tot,dis}}$ to represent the probability that there are tot items owned by agent i arranged in the top num items with a fair verification parameter dis defined as $(\mathsf{tot} - \lceil \frac{\mathsf{num}}{n} \rceil)$. The purpose of defining dis as such is to evaluate how much agent i is ahead of her fair condition. Note that dis should never be negative because otherwise fair condition won't be met.

Algorithm 1 FAIRPROB Algorithm

Require:
  m: number of items
  n: number of agents
  K: number of equivalent classes of agent i
  $s_{1,\ldots,K}$: number of items in each equivalent classes
  $r_{1,\ldots,K}$: number of items owned by agent i in each equivalent classes
 1: $P_{\mathsf{num,tot,dis}} \leftarrow 0 \quad \forall 0 \leq \mathsf{num, tot, dis} \leq m$
 2: $P_{0,0,0} \leftarrow 1$
 3: **for** num $\leftarrow 0$ to $m-1$ **do**
 4:   **for** tot $\leftarrow 0$ to num **do**
 5:     **for** dis $\leftarrow 0$ to tot **do**
 6:       **if** $P_{\mathsf{num,tot,dis}} \neq 0$ **then**
 7:         Let sta be the minimum integer such that $\sum_{j \in [\mathsf{sta}]} s_j \geq \mathsf{num} + 1$.
 8:         PrevP $\leftarrow P_{\mathsf{num,tot,dis}}$
 9:         $p \leftarrow \frac{\sum_{j \in [\mathsf{sta}]} r_j - \mathsf{tot}}{\sum_{j \in [\mathsf{sta}]} s_j - \mathsf{num}}$
10:         Let id be 1 if num is a multiple of n and 0 otherwise.
11:         $P_{\mathsf{num}+1,\mathsf{tot}+1,\mathsf{dis}+1-\mathsf{id}}$ += PrevP $\cdot p$
12:         **if** dis $-$ id ≥ 0 **then**
13:           $P_{\mathsf{num}+1,\mathsf{tot},\mathsf{dis}-\mathsf{id}}$ += PrevP $\cdot (1-p)$
14:         **end if**
15:       **end if**
16:     **end for**
17:   **end for**
18: **end for**
19: **return** $\sum_{\mathsf{dis}=0}^{\sum_{j \in [K]} r_j} P_{m, \sum_{j \in [K]} r_j, \mathsf{dis}}$

The complete algorithm is shown in Algorithm 1. The key steps are the state transfers in Steps 3-18. We define sta as the equivalent class that the item with ranking $(\mathsf{num} + 1)$ belongs to and p corresponding to the probability of the item with ranking $(\mathsf{num} + 1)$ owned by i under the present state in Steps 7-9. We also use id to record the change of the term $\lceil \frac{\mathsf{num}}{n} \rceil$ in the above definition of dis when considering the next item in Step 10.

We consider our transfer based on the situation of whether the next item is owned by agent i. Specifically, if the next

item is owned by agent i (corresponding to Step 11), there are tot $+ 1$ items owned by i arranged in the top num $+ 1$ items and the dis$'$ is equal to dis $+ 1 -$ id. On the other hand, if the next item is not owned by i (corresponding to Steps 12-14), only tot items in i's bundle are arranged in the top num $+ 1$ items, and we need to keep dis nonnegative, so we only transfer the state to $P_{\mathsf{num}+1,\mathsf{tot},\mathsf{dis}-\mathsf{id}}$ when dis $-$ id ≥ 0.

Finally, considering all possible amounts ahead of the fair condition, Step 19 returns the probability that agent i meets her fairness condition with all of her owned items. $\qquad\square$

Theorem 4.2. EXISTSPOSSIBLYFAIR with regard to SD proportionality can be solved in polynomial time.

Proof. Aziz et al. [2015] showed how to find a fair allocation when agents have strict and deterministic preferences with ties. We can solve this problem using a similar method. In particular, we can use the result in Aziz et al. [2015] to show that if $m \bmod n \neq 0$, there does not exist a possibly fair allocation in our setting. Therefore, we assume $m = qn$ for some integer q in the following. We will reduce EXIST-SPOSSIBLYFAIR to a max-flow problem in a flow network G. The construction is as follows.

Assume a flow network $G = (V, E)$ with a capacity function $c : E \mapsto \mathbb{R}^+$. V consists of a source vertex s, a sink vertex t, a vertex set A of $\sum_{i \in [n]} k_i$ vertices representing each equivalent class of each agent denoted by $A_{i \in [n], j \in [k_i]}$, and a vertex set B of m vertices representing each item denoted by $B_{i \in [m]}$. For each $A_{i,j} \in A$, we create an edge $(s, A_{i,j})$ with capacity $c = \left\lceil \frac{\sum_{k=1}^{j} |S_{i,j}|}{n} \right\rceil - \left\lceil \frac{\sum_{k=1}^{j-1} |S_{i,j}|}{n} \right\rceil$, which represents the quantity required to satisfy the fair condition that: if for agent i and $\sum_{k=1}^{j-1} |S_{i,j}| < k \leq \sum_{k=1}^{j} |S_{i,j}|$, agent i is allocated at least $\lceil \frac{k}{n} \rceil$ of her top k items. For each vertex $B_j \in B$, we create an edge (B_j, t) with capacity $c = 1$. Next, for each $A_{i,j} \in A$ and each $B_k \in B$, we construct an edge $(A_{i,j}, B_k)$ with capacity $c = 1$ if and only if the item corresponding to B_k is in the first j-th equivalent class of agent i.

If there exists a maximum flow with strength m in this flow network G, we can construct an allocation by assigning each item k to the agent i such that there exists one blocking edge $(A_{i,j}, B_k)$ for one $j \in [k_i]$. In this allocation, by placing the items owned by each agent as more preferred as possible, we can show that it must satisfy SD proportionality.

On the other hand, if there exists a possibly fair allocation, it must meet all capacity conditions in the flow newtork G by successively blocking the edges pointing from $S_{i,j}$ to the items in i's bundle in the increasing order of j for each agent i. $\qquad\square$

Theorem 4.2. EXISTSCERTAINLYFAIR and HIGHESTPROB with regard to SD proportionality are NP-hard.

Proof. We only prove the NP-hardness for EXISTSCER-
TAINLYFAIR and it directly implies NP-hardness for HIGH-
ESTPROB.

In order to prove the NP-hardness of EXISTSCERTAINLY-
FAIR, we reduce from the NP-hard problem denoted as
X3C[Johnson and Garey, 1979].

X3C: Given a collection T of subsets of a set of $3s$
elements S, where each subset in T has exactly 3 elements
in S, decide whether exists s subsets in T such that each
elements in S appears exactly once.

We reduce from X3C to this problem. Considering a X3C
problem instance F with $3s$ elements $S = \{S_1, \ldots, S_{3s}\}$
and t 3-sized sets $T = \{T_1, \ldots, T_t\}$ where each T_i contains
exactly three elements $T_{i,1}, T_{i,2}, T_{i,3}$ in S. Without loss of
generality, we suppose $t \geq 3s$ and $s > 3$. Based on F we
construct a problem instance of EXISTSCERTAINLYFAIR
with t agents and $4t$ items. Each agent $i \in [t]$ corresponds
to the 3-sized set $T_i \in T$.

The $4t$ items are divided into the following five sets:

- A set of $3s$ items corresponding to each element in S,
  where we still denote this set as $S = \{S_1, \ldots, S_{3s}\}$
  for simplifying the notations;

- A set of t items $A = \{A_1, \ldots, A_t\}$, which is denoted
  to meet the fair condition when considering only the
  most preferred item of each agent;

- Three sets of size $(t - s)$: $B = \{B_1, \ldots, B_{t-s}\}$, $C =
  \{C_1, \ldots, C_{t-s}\}$ and $D = \{D_1, \ldots, D_{t-s}\}$, which are
  used to compensate the agents whose corresponding
  3-sized sets are not selected.

To simplify the descriptions of the preference lists, for set
A and each agent $i \in [t]$, we partition the set $A - \{A_i\}$
into 4 disjoint subsets $A'_{i,1}, A'_{i,2}, A'_{i,3}, A'_{i,4}$ where $|A'_{i,1}| =
s - 1, |A'_{i,2}| = s - 3, |A'_{i,3}| = s, |A'_{i,4}| = t - 3s + 3$. The
intuition for this partition is to properly fill the items in the
end of every t items.

Next, we can construct the preference lists for agents. The
preference list of agent $i \in [t]$ is:

$$A_i \succ (A'_{i,1}, B) \succ (T_i) \succ (C, A'_{i,2}) \succ (D, A'_{i,3}) \succ (\text{others}).$$

Here, the items in the previous term (others) contain the
items in $A'_{i,4}$ and the items in $S - T_i$.

We can observe that $A_i, (A'_{i,1}, B)$ form the first t items, and
$(T_i), (C, A'_{i,2})$ form the second t items, while $(D, A'_{i,3})$ and
(others) form the third and the fourth t items respectively.

If the X3C instance has a satisfying assignment, we con-
struct an allocation as following:

- For each chosen set T_i, the corresponding agent i picks
  the items $A_i, T_{i,1}, T_{i,2}, T_{i,3}$.

- For each of the remaining unselected sets T_i, items
  $A_i, B_{\sigma(i)}$,
  $C_{\sigma(i)}, D_{\sigma(i)}$ are assigned to agent i. Here, σ is a bijec-
  tion from the remaining unselected sets to $\{1, ..., t-s\}$.

We can easily check the above allocation is always SD
proportional.

On the other hand, assume there is an allocation that is SD
proportional with probability one, we can also construct a
satisfying assignment for the X3C instance. First, to meet
the fair conditions, each item A_i must be assigned to agent i.
Then, among the first t items, only $t - s$ items in B have not
been assigned now, which means that at least $t - (t - s) = s$
agents cannot pick any item other than her corresponding
item in set A among the first t items. Thus, every agent i of
these s agents should pick all 3 items in their corresponding
T_i to meet the fair condition certainly where agent i is
allocated at least $\lceil \frac{k}{t} \rceil$ of her top k items when $k = t + 1$.
Further, because $|S| = 3s$, these s agents exactly cover all
elements in S. To summarize, the satisfying assignment for
the corresponding X3C instance is to choose the 3-sized sets
whose corresponding agents didn't pick any $B_i \in B$. $\square$

C   BASELINE ALGORITHMS

We explain in details about the four algorithms we test in
the experiment section.

1. **BASELINE (B)**: We assign each item to a random agent
   to get a random allocation. We repeat this process B
   times to get B random allocations and choose the one
   with the largest fair probability. We set $B = 4m$ in
   the experiment. We also tested our algorithm with B
   increased to $8m$, and did not observe any noticeable
   improvement on the algorithm's performance.

2. **LOCALSEARCH (LS)**: Two allocations are called
   neighbors if one allocation can be derived from the
   other by moving one item from some agent to another
   agent. In this Local Search algorithm, we start from
   a random allocation and iteratively move to a neigh-
   bor allocation that has a higher fair probability, until
   a locally optimal allocation is reached. We repeat the
   above process L times, each time with a new random
   initial allocation, and choose the final allocation with
   the highest fair probability. We set $L = n$ in the experi-
   ment. We also tested our algorithm with L increased to
   $2n$, and did not observe any noticeable improvement
   on the performance.

3. **MATCHING (M)**: Since in a weak SD proportional
   allocation, every agent needs to receive $\lfloor \frac{r}{n} \rfloor + 1$ items
   with ranking not worse than r for some r. We set the
   value of an agent getting an item with ranking r as

$\frac{1}{\lfloor \frac{r}{n} \rfloor + 1}$. For each agent i and item o, let $\mathsf{avg}(i, o)$ be the average value of i getting o.

This algorithm runs for $\frac{m}{n} + 1$ rounds and assigns at most one item to each agent each round. In round k, let R_i be the total value that agent i has received in previous rounds, then for each item o, we set the value of agent i getting item o in this round as $(1 - R_i) \cdot \mathsf{avg}(i, o)$. In addition, we remove all edges whose values are less than a certain threshold L. Then we find a maximum weight matching between agents and items and assign the item to the matched agent. Finally, we update R_i for each agent and remove all agents who receive a total value larger than another threshold U from consideration in future rounds. After finishing $\frac{m}{n} + 1$ rounds, we allocate the remaining items to the agents with less than $\frac{m}{n} + 1$ items arbitrarily.

In our experiment, we enumerate 5 different lower bound L from $\frac{1}{\lfloor \frac{m}{n} \rfloor + 1}$ to $\frac{1}{\lfloor \frac{m}{n} \rfloor + 1} + 0.1$ equidistant and 11 different upper bound U from 1 down to 0.7 equidistant. We run the algorithm for each pair of L and U, and choose the allocation with the largest fair probability among all solutions. We also test the algorithm with L higher than $\frac{1}{\lfloor \frac{m}{n} \rfloor + 1} + 0.1$ or with U lower than 0.7 and do not observe significant performance improvement.

4. **GREEDY (G)**: For each agent i and item o, we adopt notion $\mathsf{avg}(i, o)$ from the previous MATCHING algorithm to be the average value of i getting o. Then for each agent i and a set S of items, when calculating the R_i in the above MATCHING algorithm, we can find that it's always equal to $1 - \prod_{o \in S}(1 - \mathsf{avg}(i, o))$ no matter in what order the items in S are adding to agent i's bundle. Thus, we let $f_i(S) = \min(U, 1 - \prod_{o \in S}(1 - \mathsf{avg}(i, o)))$ denote the value of this agent receiving S, where U is a threshold parameter. One can check that f_i is a submodular function, and our question becomes a general submodular welfare maximization problem. We then use a greedy algorithm from Lehmann et al. [2006] which always outputs a 2-approximation solution for the submodular welfare maximization problem.

In the experiment, we run this algorithm with 11 different values of U from 1 down to 0.7, and choose the allocation with the largest fair probability. We also tested our algorithm with the value of U less than 0.7, and found it did not improve the algorithm's performance.

References

Haris Aziz, Serge Gaspers, Simon Mackenzie, and Toby Walsh. Fair assignment of indivisible objects under ordinal preferences. *Artificial Intelligence*, 227:71–92, 2015.

Philip Hall. On representatives of subsets. In *Classic Papers in Combinatorics*, pages 58–62. Springer, 2009.

David S Johnson and Michael R Garey. *Computers and intractability: A guide to the theory of NP-completeness*, volume 1. WH Freeman San Francisco, 1979.

Benny Lehmann, Daniel Lehmann, and Noam Nisan. Combinatorial auctions with decreasing marginal utilities. *Games and Economic Behavior*, 55(2):270–296, 2006.