TraCER: Offline Reinforcement Learning through Trajectory Clustering and Exclusive Regularisation

Abstract

In this paper, we propose Offline Reinforcement Learning through Trajectory Clustering and Exclusive Regularisation (TraCER), a value regularisation framework that accounts for out-of-distribution (OOD) actions. Unlike most existing methods, which avoid direct reasoning about OOD regions due to their inherent difficulty, TraCER traces and delineates OOD regions in the action space, potentially non-convex, using a trajectory clustering-based behaviour cloning algorithm. This approach assumes that each trajectory in the offline dataset was rolled out by a single behaviour policy, an assumption commonly satisfied in practice when datasets are collected from distinct sources or agents. Conditioned on this delineation, we introduce a Bellman-type operator that constrains value estimates for OOD actions to a tight lower bound while leaving in-distribution action-value estimates unchanged. The resulting value function supports standard policy extraction procedures. Experiments on multiple offline RL benchmarks demonstrate that TraCER consistently outperforms existing approaches.

1 Introduction

Offline reinforcement learning (RL) has attracted significant attention from the research community due to its sample efficiency and safety. Unlike conventional RL in which an agent learns an optimal policy through interactions with the environment, offline RL forgoes environmental interactions. Instead, the agent is provided with a fixed dataset $\mathcal{D}$ of trajectories and should derive a competent policy solely from the samples in the dataset. Offline RL relies on off-policy data collected by an unknown behaviour policy or multiple behaviour policies, and standard off-policy RL algorithms often fail in this setting. The primary cause of this failure is the lack of correction of the extrapolation error of the critic as the agent is unable to re-evaluate overestimated out-of-distribution (OOD) actions caused by function approximation errors through environmental interactions (Fujimoto et al., 2019). These extrapolation errors not only persist but also accumulate through bootstrapping, and thus careful handling of OOD actions is crucial in offline RL for stable training.

One of the main strategies for addressing the aforementioned extrapolation issue is *value regularisation*. By penalising the critic values of OOD actions, this method encourages the agent to prefer in-distribution (ID) actions over OOD ones. A variety of algorithms have been proposed within this paradigm (Kumar et al., 2020; Lyu et al., 2022; Mao et al., 2023), differing mainly in their choice of regularisation term. However, most of these algorithms rely on indirect proxies to determine the OOD-ness of actions. For example, Mao et al. (2023) approximates the behaviour policy with a Gaussian model and computes importance-sampling ratios to determine the OOD-ness. When the dataset contains multiple disparate behaviour policies, however, such unimodal approximation misrepresent the underlying multimodal structure. They assign spuriously high densities to the inter-modal region, distorting the OOD-ness estimates, eventually degrading the regularisation's effectiveness.

To address the limitations of previous critic penalisation methods, we propose a new value-regularisation algorithm that explicitly identifies the OOD region and penalises the critic's estimates with these identified OOD regions. Our explicit OOD identification can capture multimodal behaviour in the dataset and provide

more accurate OOD discrimination compared to previous indirect methods. Furthermore, we derive a new lower bound on the critic value that is tighter than those employed in previous works and use this for tight penalisation. Empirical evaluations on the D4RL benchmark (Fu et al., 2020) demonstrate that our approach yields high-performing policies across a wide range of offline RL datasets.

Our main contributions are summarised as follows:

- **Likelihood-based OOD detection.**
  We introduce a principled likelihood-based criterion for identifying the OOD region.

- **Behaviour modelling via trajectory clustering.**
  By linking trajectory clustering in offline RL to task identification in meta RL, we propose an algorithm that learns a Gaussian mixture model of the dataset, under the assumption that each trajectory originates from a single policy, enabling accurate density estimation in multimodal datasets.

- **A tight lower-bound-based value regulariser.**
  We derive a tight lower bound on the optimal action-value function and incorporate it into a value regulariser, and theoretically prove the optimality of the proposed penalisation method.

2 Background

Notation For the full list of notations used in this paper and their meanings, refer to Appendix Sec. A.

Markov Decision Process An RL problem is formulated as a Markov Decision Process (MDP), which is defined as a 6-tuple $\mathcal{M} = \langle \mathcal{S}, \mathcal{A}, P, R, \gamma, \rho_0 \rangle$, where $\mathcal{S} \subseteq \mathbb{R}^{d_s}$ is the state space, $\mathcal{A} \subseteq \mathbb{R}^{d_a}$ is the action space, $P \colon \mathcal{S} \times \mathcal{A} \to \mathcal{P}(\mathcal{S})$ is the transition dynamics, $R \colon \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to \mathcal{P}(\mathbb{R})$ is the reward function, $\gamma \in [0, 1]$ is the discount factor, and $\rho_0 \in \mathcal{P}(\mathcal{S})$ is the initial state distribution. We will assume that the reward function $R(s, a, s')$ is bounded above by $r_{\max}$ and bounded below by $r_{\min}$ for all $s, s' \in \mathcal{S}$ and $a \in \mathcal{A}$.

Value Functions Given a policy π, the Bellman operator $\mathcal{T}^\pi$ on $L^\infty(\mathcal{S} \times \mathcal{A})$ is defined by the following equation:

$$(\mathcal{T}^\pi Q)(s, a) = \mathbb{E}_{s' \sim P(s,a)} \left[\mathbb{E}_{r \sim R(s,a,s')}[r] \right] + \mathbb{E}_{s' \sim P(s,a)} \left[\mathbb{E}_{a' \sim \pi(s')} \left[Q(s', a') \right] \right].$$

Then, the action-value function (or Q-function) $Q^\pi \colon \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ is defined as the unique fixed point of $\mathcal{T}^\pi$, and the state-value function $V^\pi \colon \mathcal{S} \to \mathbb{R}$ is given by $V^\pi(s) = \mathbb{E}_{a \sim \pi(s)} [Q^\pi(s, a)]$. The objective of RL is to find an optimal policy π^* such that $V^{\pi^*} \succeq V^\pi$ for any policy π.

Offline Reinforcement Learning For offline RL, interactions with the environment is prohibited, and the agent has to learn a policy from a given dataset $\mathcal{D}$ of trajectories. Throughout this paper, we will assume that each trajectory $\tau \in \mathcal{D}$ is sampled with a uni-modal behaviour policy $\beta \in \{\beta_0, \beta_1, \beta_2, \ldots, \beta_{K-1}\}$, where the candidate mixture set $\mathcal{B} = \{\beta_0, \beta_1, \beta_2, \ldots, \beta_{K-1}\}$ is fixed but unknown to the agent.

3 TraCER: Method Overview

In this section, we propose *Trajectory Clustering and Exclusive Regularisation* (TraCER), our offline algorithm employing two central components: clustering trajectories to explicitly infer behaviour policies, and enforcing regularisation exclusively on OOD actions identified by our clustering. This section is structured as follows. In Section 3.1, we first discuss how to compute the OOD action set $\text{OOD}(s)$. We then propose a new lower bound of Q^{π^*} and show its effectiveness as a penalisation target in Section 3.2. Finally, we provide a practical offline RL algorithm in Section 3.3.

3.1 Identifying the Out-of-Distribution Action Set

Likelihood is a natural measure of how OOD a sample is, but selecting an appropriate threshold is non-trivial: blunt distributions require lower thresholds, whereas sharper distributions allow higher ones. The difficulty is further exacerbated for multi-modal distributions, where blunt and sharp modes may coexist,

Figure 1: Overview of our architecture. We also provided a diagram of the variBAD architecture in Figure 6 for comparison.

making heuristically chosen likelihood thresholds unreliable. We address this issue by proposing a systematic method of setting the threshold based on the concept of *highest density region* (HDR; Hyndman 1996), a generalisation of a confidence interval to multivariate random variables.[1]

Definition 3.1 (Hyndman 1996). *Let $p(X)$ be the pdf of a random variable X. Then, the $100(1-\alpha)\%$ highest density region (HDR) is the subset $\mathcal{R}(p_\alpha)$ of the sample space of X such that $\mathcal{R}(p_\alpha) = \{\, x : p(x) \geq p_\alpha \,\}$, where $p_\alpha = \sup\{\, y : P(X \in \mathcal{R}(y)) \geq 1 - \alpha \,\}$.*

Note that the HDR of a pdf is the minimum measure subset with given probability mass $1 - \alpha$ in the sample space, and HDR summarises the data more precisely than conventional quantile-based regions, particularly in cases involving skewed or multimodal distributions.

In the following subsections, we discuss how to compute the HDR under different assumptions.

3.1.1 Homogeneous Datasets

We first consider the case when the offline dataset $\mathcal{D}$ is homogeneous, that is, it was generated from a single unimodal behaviour policy β. Then, we may obtain a fairly accurate Gaussian approximation $\hat{\beta}$ of β through behaviour cloning. Let $\boldsymbol{\mu}\colon \mathcal{S} \to \mathbb{R}^{d_a}$ and $\boldsymbol{\Sigma}\colon \mathcal{S} \to \mathbb{R}^{d_a \times d_a}$ be the mean and covariance matrix functions of $\hat{\beta}$, respectively. Assuming $\boldsymbol{\Sigma}(s)$ is positive definite for all $s \in \mathcal{S}$, the $100(1 - \alpha)\%$ HDR has the following closed-form representation (see Proposition C.1 in the appendix):

$$\mathcal{R}_{\hat{\beta}}(p_\alpha; s) = \left\{ \mathbf{x} \in \mathbb{R}^{d_a} : A_{\hat{\beta}}(\mathbf{x}; s) \leq F^{-1}_{\chi^2_{d_a}}(1 - \alpha) \right\},$$

where $F^{-1}_{\chi^2_{d_a}}$ is the inverse cumulative distribution function of a chi-squared random variable with d_a degrees of freedom and

$$A_{\hat{\beta}}(\mathbf{x}; s) = (\mathbf{x} - \boldsymbol{\mu}(s))^\top \boldsymbol{\Sigma}(s)^{-1}(\mathbf{x} - \boldsymbol{\mu}(s)).$$

Choosing an appropriate value of $0 < \alpha < 1$, we can define $\mathrm{OOD}(s)$ as

$$\mathrm{OOD}(s) = \mathcal{A} \setminus \mathcal{R}_{\hat{\beta}}(p_\alpha; s). \tag{1}$$

3.1.2 Heterogeneous Datasets

The definition of $\mathrm{OOD}(s)$ for a homogeneous dataset given in Equation 1 can be generalised to the heterogeneous case, where dataset consists of trajectories generated by multiple different behaviour policies, as

$$\mathrm{OOD}(s) = \mathcal{A} \setminus \left(\bigcup_{\beta \in \mathcal{B}} \mathcal{R}_\beta(p_\alpha; s) \right) \tag{2}$$

---

[1]We provide a diagram (Figure 5 in Appendix) showing the $100(1 - \alpha)\%$ HDR of a normal distribution on page 34 to aid the understanding of the concept of a HDR.

for $\mathcal{B} = \{\beta_0, \beta_1, \beta_2, \ldots, \beta_{K-1}\}$, where $\mathcal{B}$ is the behaviour policy candidate set and $\mathcal{R}_\beta(p_\alpha, s)$ is the $(1-\alpha)$ HDR of distribution β. If we could identify which behaviour policy $\beta \in \mathcal{B}$ each and every trajectory in the dataset is sampled from, and isolate all trajectories according to their generation behaviour policies, then obtaining an estimation $\hat{\mathcal{B}}$ of $\mathcal{B}$ is straightforward. We can simply apply a behaviour cloning algorithm on each isolated trajectory cluster. Then, with the estimated $\hat{\mathcal{B}} = \{\hat{\beta}_0, \hat{\beta}_1, \ldots, \hat{\beta}_{K-1}\}$, we could compute $\mathrm{OOD}(s)$ for each state s with Equation 2. Therefore, in the remainder of this section, we will propose how to cluster the trajectories. Note that the proposed clustering algorithm is useful not only for value regularisation in this paper but also for other offline real-world data analysis. Hence, trajectory clustering itself is of an importance.

Trajectory clustering is a nontrivial problem for offline datasets because a data sample here is not a homongeneous sample like an image or a measurement but is a sequence of heterogeneous states, actions and rewards. Furthermore, only the sampling of action from state depends on the policy but general transitions from state and action to next state and reward share the same transition dynamics for the same task. Our key approach to this difficult problem is to convert the trajectory clustering problem closely to a task inference problem in meta RL, described below.

For each policy π, there is a corresponding Markov reward process (MRP) $\mathcal{M}^\pi = \langle \mathcal{S}, P^\pi, R^\pi, \gamma \rangle$, where for all $s, s' \in \mathcal{S}$ and $r \in \mathbb{R}$, the transition probability function $P^\pi \colon \mathcal{S} \to \mathcal{P}(\mathcal{S})$ and the reward probability function $R^\pi \colon \mathcal{S} \times \mathcal{S} \to \mathcal{P}(\mathbb{R})$ are defined by the equations

$$P^\pi(s' \mid s) = \mathbb{E}_{a \sim \pi(\cdot|s)}\left[P(s' \mid s, a)\right], \tag{3}$$

$$R^\pi(r \mid s, s') = \mathbb{E}_{a \sim \pi(\cdot|s)}\left[R(r \mid s, a, s')\right], \tag{4}$$

respectively. Since the dataset $\mathcal{D}$ can then be viewed as a collection of trajectories, where each trajectory is sampled from one of the MRPs $\mathcal{M}^{\beta_0}, \mathcal{M}^{\beta_1}, \mathcal{M}^{\beta_2}, \ldots, \mathcal{M}^{\beta_{K-1}}$, trajectory clustering task can be viewed as an MRP inference problem. We can infer the MRP by applying a technique similar to variational Bayes-adaptive deep RL (variBAD; Zintgraf et al. 2021). An overview of our clustering algorithm is given in Figure 1.

Our goal is to infer the behaviour policy index given a trajectory. To achieve this objective, we represent the index as a discrete latent variable m supported on $[K] = \{0, 1, \cdots, K-1\}$ and write $P^{\beta_m}(s) \approx P(s; m)$, $R^{\beta_m}(s, s') \approx R(s, s'; m)$, $\beta_m(s) \approx \beta(s; m)$, for all $s, s' \in \mathcal{S}$, sharing P, R, and β across trajectories. The marginal pdf of a trajectory $\tau_{:T} = (s_0, a_0, r_0, s_1, a_1, r_1, s_2, a_2, r_2, \ldots, s_{T-1}, a_{T-1}, r_{T-1}, s_T)$ is

$$p(\tau_{:T}) = \rho_0(s_0) \sum_{m=0}^{K-1} p(m) \prod_{t=0}^{T-1} B(s_t, a_t, r_t, s_{t+1}; m), \tag{5}$$

where $p(m)$ is the prior distribution on m. Modelling P, R, and β with neural networks parametrised by θ results in a loss that depends on θ. However, the multi-modality of Equation 5 causes gradient-based optimisation algorithms to produce sub-optimal solutions. We circumvent this issue by introducing amortised inference network q_ϕ that takes a variable-length action-less trajectory $\tilde{\tau}_{:t} = (s_0, r_0, s_1, r_1, s_2, r_2, \ldots, s_{t-1}, r_{t-1}, s_t)$ as an input and outputs a distribution in $\mathcal{P}_d([K])$. Instead of maximising Equation 5, we maximise the evidence lower bound (ELBO), which can be written by the following equation (see Proposition C.2 in the appendix):

$$\begin{aligned}
\mathrm{ELBO}_{\theta,\phi}(\tau; t) = &- D_{\mathrm{KL}}(q_\phi(\tilde{\tau}_{:t}) \,\|\, p) + \sum_{i=0}^{T-1} \mathbb{E}_{m \sim q_\phi(\tilde{\tau}_{:t})}\left[\log P_\theta(s_{t+1} \mid s_t; m)\right] \\
&+ \sum_{i=0}^{T-1} \mathbb{E}_{m \sim q_\phi(\tilde{\tau}_{:t})}\left[\log \beta_\theta(a_t \mid s_t; m)\right] + \sum_{i=0}^{T-1} \mathbb{E}_{m \sim q_\phi(\tilde{\tau}_{:t})}\left[\log R_\theta(r_t \mid s_t, s_{t+1}; m)\right].
\end{aligned} \tag{6}$$

The first term $\log \rho_0(s_0)$ in Equation 13 can be omitted because it is constant with respect to θ and ϕ. The final objective for trajectory clustering is to maximise

$$\mathbb{E}_{\tau \sim \mathcal{D}}\left[\frac{1}{T_\tau} \sum_{t=0}^{T_\tau - 1} \mathrm{ELBO}_{\theta,\phi}(\tau; t)\right], \tag{7}$$

where T_τ is the length of the trajectory τ sampled from the dataset.

After we finish trajectory clustering, we perform the behaviour policy estimation and cluster assignment according to the equations $\hat{\beta}_i = \beta_\theta(\cdot; i)$ and $\mathbb{A}(s) = \arg\max_m q_\phi(m \mid \tilde{\tau}(s))$, respectively, for each $i \in [K]$ and $s \in \mathcal{D}$, where $\tilde{\tau}(s)$ is the action-less trajectory containing the state s. This procedure yields an empirical set of behaviour policy estimates $\hat{\mathcal{B}} = \{\hat{\beta}_0, \hat{\beta}_1, \ldots, \hat{\beta}_{K-1}\}$ that approximates the policies used to generate the dataset.

3.2 Exclusive Regularisation via Lower Bounds

In this section, we derive a new lower bound on the optimal value function. As we did in the previous section, we start with the case where the offline dataset $\mathcal{D}$ is generated from a single behaviour policy β. The ideal penalisation method would be to use $Q^{\pi^*}(s, a)$ as a target, where π^* is the optimal policy, but the value of Q^{π^*} is inaccessible. We therefore aim to use a lower bound instead. To derive such a bound, we first need to make the following regularity assumptions on P and V^β.

Assumption 3.2. There is $K_P > 0$ such that for all $s \in \mathcal{S}$ and $a, a' \in \mathcal{A}$, $W_1(P(s, a), P(s, a')) < K_P \|a - a'\|$, where $W_1(P, Q)$ is the Wasserstein distance of order 1 between two probability distributions $P, Q \in \mathcal{P}(\mathcal{S})$.

Assumption 3.3. The value function of the behaviour policy β is K_V-Lipschitz, that is, for all $s, s' \in \mathcal{S}$, $\left|V^\beta(s) - V^\beta(s')\right| < K_V \|s - s'\|$.

Then, we can obtain a lower bound of Q^{π^*} with the above assumptions.

Proposition 3.4. *Define $Q_\beta^{\mathrm{LB}} \colon \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ by the equation*

$$Q_\beta^{\mathrm{LB}}(s, a) = \max\left\{V^\beta(s) - \Delta r - \gamma K_V K_P \mathbb{E}_{a' \sim \beta(s)}[\|a - a'\|], \frac{r_{\min}}{1 - \gamma}\right\}. \tag{8}$$

where β is the behaviour policy, $V^\beta(s)$ is the state value function of β, and $\Delta r = r_{\max} - r_{\min}$. For any policy π such that $V^\pi \succeq V^\beta$, we have $Q^\pi \succeq Q_\beta^{\mathrm{LB}}$.

Proof. See page 23. $\square$

The expectation term in Equation 8 admits a closed-form expression (see Proposition C.14 in the appendix) when we adopt a 1-norm $\|\cdot\|_1$. For a Gaussian policy with mean function $\boldsymbol{\mu} \colon \mathcal{S} \to \mathbb{R}^{d_a}$ and a diagonal covariance matrix function $\boldsymbol{\Sigma} \colon \mathcal{S} \to \mathbb{R}^{d_a \times d_a}$, the expectation term becomes

$$\sum_{i=1}^{d_a}(a_i - \mu_i(s))\operatorname{erf}\left(\frac{a_i - \mu_i(s)}{\sigma_i(s)\sqrt{2}}\right) + \sum_{i=1}^{d_a}\sqrt{\frac{2}{\pi}}\sigma_i(s)\exp\left(-\frac{(a_i - \mu_i(s))^2}{2\sigma_i^2(s)}\right),$$

where $a = (a_1, a_2, \ldots, a_{d_a})$, $\boldsymbol{\mu} = (\mu_1, \mu_2, \ldots, \mu_{d_a})$, $\boldsymbol{\Sigma} = \operatorname{diag}(\sigma_1, \sigma_2, \ldots, \sigma_{d_a})$, and erf is the Gauss error function. This closed-form expression eliminates the need for Monte–Carlo or surrogate bounds. Given an in-sample state s and an unseen action a, accurate estimation of $Q^\beta(s, a)$ would require trajectories that are not present in the dataset. In contrast, estimating $Q_\beta^{\mathrm{LB}}(s, a)$ only requires in-sample data through $V^\beta(s)$. The derived lower bound is tighter than the previous bound $r_{\min}/(1 - \gamma)$ (Mao et al., 2023).

Using this lower bound, we define the penalised Bellman optimality operator $\mathcal{T}_\beta^*$ for policy π by the equation

$$(\mathcal{T}_\beta^* Q)(s, a) = \begin{cases} Q_\beta^{\mathrm{LB}}(s, a) & \text{if } a \in \mathrm{OOD}(s), \\ (\mathcal{T}^* Q)(s, a) & \text{otherwise}, \end{cases} \tag{9}$$

where $\mathcal{T}^*$ is the Bellman optimality operator defined as

$$(\mathcal{T}^* Q)(s, a) = \mathbb{E}_{s' \sim P(s,a), r \sim R(s,a,s')}\left[r + \gamma \sup_{a' \in \mathcal{A}} Q(s', a')\right].$$

Unlike existing approaches that penalise based on indirect measures of OOD-ness, such as Kumar et al. (2020) and Mao et al. (2023), the penalty term in Equation 9 is applied directly using the identified OOD

region $\mathrm{OOD}(s)$. When the behaviour identification is accurate, this can yield more targeted suppression of OOD actions.

We can show that through repeated application of $\mathcal{T}_\beta^*$, it is possible to obtain a deterministic policy $\pi_\beta^* \colon \mathcal{S} \to \mathcal{A}$ that is optimal among the policies whose action for each state $s \in \mathcal{S}$ does not lie in $\mathrm{OOD}(s)$.

Theorem 3.5. *Any initial bounded real-valued function on $\mathcal{S} \times \mathcal{A}$ can converge to a unique fixed point Q_β^* by repeatedly applying $\mathcal{T}_\beta^*$. If for each $s \in \mathcal{S}$, there is $a_s \in \mathcal{A} \setminus \mathrm{OOD}(s)$ such that*

$$Q^\beta(s, a_s) \geq \mathbb{E}_{a \sim \beta(s)} \left[Q^\beta(s, a) \right]$$

and there exists a deterministic policy $\pi_\beta^* \colon \mathcal{S} \to \mathcal{A}$ that is optimal under the constraint $\pi(s) \notin \mathrm{OOD}(s)$ for all $s \in \mathcal{S}$, then for all $s \in \mathcal{S}$,

$$\pi_\beta^*(s) = \arg\max_{a \in \mathcal{A}} Q_\beta^*(s, a).$$

Proof. See page 27. $\qquad\square$

Thus, the greedy policy with respect to $Q_\beta^*(s, a)$ is optimal among in-distribution policies under the constraint $a \notin \mathrm{OOD}(s)$ for all $s \in \mathcal{S}$.

Finally, we extend the operator to heterogeneous datasets with a candidate behaviour set $\mathcal{B}$. Define

$$(\mathcal{T}_\mathcal{B}^* Q)(s, a) = \begin{cases} Q_\mathcal{B}^{\mathrm{LB}}(s, a) & \text{if } a \in \mathrm{OOD}(s), \\ (\mathcal{T}^* Q)(s, a) & \text{otherwise,} \end{cases} \tag{10}$$

where $Q_\mathcal{B}^{\mathrm{LB}} \colon \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ is defined as

$$Q_\mathcal{B}^{\mathrm{LB}}(s, a) = \max_{\beta \in \mathcal{B}} Q_\beta^{\mathrm{LB}}(s, a)$$

for each $(s, a) \in \mathcal{S} \times \mathcal{A}$. We can prove an analogous performance guarantee for repeated application of $\mathcal{T}_\mathcal{B}^*$.

Theorem 3.6. *Any initial bounded real-valued function on $\mathcal{S} \times \mathcal{A}$ can converge to a unique fixed point $Q_\mathcal{B}^*$ by repeatedly applying $\mathcal{T}_\mathcal{B}^*$. If there exists $a_s^\beta \in \mathcal{A} \setminus \mathrm{OOD}(s)$ such that*

$$Q^\beta(s, a_s^\beta) \geq \mathbb{E}_{a \sim \beta(s)} \left[Q^\beta(s, a) \right]$$

for each $\beta \in \mathcal{B}$ and $s \in \mathcal{S}$, and there exists a deterministic policy $\pi_\mathcal{B}^* \colon \mathcal{S} \to \mathcal{A}$ that is optimal under the constraint $\pi(s) \notin \mathrm{OOD}(s)$ for all $s \in \mathcal{S}$, then for all $s \in \mathcal{S}$,

$$\pi_\mathcal{B}^*(s) = \arg\max_{a \in \mathcal{A}} Q_\mathcal{B}^*(s, a).$$

Proof. See page 28. $\qquad\square$

3.3 Practical Algorithm

We summarise the three high-level stages of TraCER:

I. **Behaviour policy learning.** Run our trajectory clustering algorithm introduced in Section 3.1.2 together with behaviour cloning to obtain a set $\hat{\mathcal{B}}$ of behaviour policy estimates.

II. **Behaviour value learning.** Learn a value function $\hat{V}^{\hat\beta}$ for each $\hat\beta \in \hat{\mathcal{B}}$ through temporal difference learning.

III. **Policy learning.** Repeatedly apply the penalised Bellman optimality operator $\mathcal{T}_\mathcal{B}^*$ in Equation 10 to a randomly initialised Q-function until convergence and extract a policy that maximises the learned Q-functions, as justified in Theorems 3.5 and 3.6.

We next describe a practical implementation of these stages. While the conceptual structure of TraCER follows the three stages above, their efficient realisation involves several non-trivial design choices, particularly for policy learning. We address these challenges and present a practical offline RL algorithm with explicit identification of OOD action regions. Additional implementation details for all stages are provided in Appendix B.

3.3.1 Stage I: Behaviour Policy Learning

In Stage I, we learn a set of behaviour policies by clustering trajectories under a latent-variable model. The architecture follows the encoder-decoder structure of variBAD (Zintgraf et al., 2021), with several adaptations. The encoder maps an action-less trajectory to an amortised posterior over latent variables. To handle long and variable-length trajectories, we replace the GRU (Cho et al., 2014) encoder used in variBAD with a state-space model; in particular, we adopt the S5 (Smith et al., 2023) layer, which is computationally efficient and well-suited for modelling long-range temporal dependencies.

To obtain a discrete set of behaviour policies, we employ a vector quantised-variational autoencoder (VQ-VAE; van den Oord et al. 2017) formulation, which assigns each trajectory segment to a codebook entry and enables efficient approximation of the evidence lower bound. To reduce sensitivity to the choice of codebook size, we further adopt a simple two-phase training procedure that adaptively prunes rarely used codebook entries after an initial training phase. This allows the number of behaviour clusters to be inferred from data rather than selected via exhaustive hyperparameter tuning, and improves the accuracy of behaviour policy estimation by concentrating training samples on well-supported clusters. Additional architectural details and implementation choices are deferred to Appendix B.1.

3.3.2 Stage II: Behaviour Value Learning

Stage II learns a value function $\hat{V}^{\hat{\beta}}$ for each behaviour policy $\hat{\beta}$ using temporal difference learning. While this step does involve several design choices, the overall procedure is not central to the contributions of TraCER, as it largely follows standard practice. We therefore defer a detailed discussion to Appendix B.2.

3.3.3 Stage III: Policy Learning

In Stage III, we perform policy learning by repeatedly applying the penalised Bellman optimality operator $\mathcal{T}_{\mathcal{B}}^*$. In practice, directly computing the supremum over actions in this operator is infeasible. Moreover, the resulting critic landscape is highly non-convex due to the penalisation of actions that lie between the means of different behaviour policies. Consequently, naive gradient-based optimisation over the action space often converges to suboptimal solutions.

To address this challenge, we instead work with a vector-valued extension $\vec{\mathcal{T}}_{\mathcal{B}}^*$, which decomposes the optimisation into K subproblems, one per behaviour policy. Each subproblem is restricted to a convex ellipsoidal region $\mathcal{R}_{\beta_i}(p_\alpha; s)$ around the mean of the corresponding behaviour policy β_i, making the resulting component functions significantly easier to learn.

We adopt an actor-critic formulation with an ensemble of K actor-critic pairs, one per behaviour policy. Each actor predicts a residual action relative to the mean of its corresponding behaviour policy, thereby restricting the search for improved actions to the local neighbourhood of each behaviour. For a given state, only the actors whose corresponding behaviour policies are estimated to be active are considered, and the action with the highest critic value among these candidates is selected.

The critic is trained using a weighted combination of two loss terms: a temporal difference loss on dataset transitions, and a regularisation term that penalises OOD action values towards the lower bound $Q_{\hat{\beta}}^{\mathrm{LB}}$, for which we derive a closed-form expression under a diagonal Gaussian behaviour policy estimate. Full details of the loss functions, regularisation terms, and auxiliary computations are provided in Appendix B.3.

(a) halfcheetah   (b) hopper   (c) walker2d

Figure 2: Visualisation of the clustering results on three different random-medium-expert datasets. Each row corresponds to a trajectory and each column to a timestep. Colours indicate the inferred behaviour cluster assignment, illustrating how trajectories from different data regimes (random, medium, and expert) are consistently grouped over time.

Table 1: The impact of hyperparameters λ_T and λ_R on the performance of our trajectory clustering algorithm evaluated on custom D4RL datasets. The performance is measured in terms of adjusted rand index (ARI) and normalized mutual information score (NMI).

		$\lambda_T = 1$		$\lambda_T = 0$	
		$\lambda_R = 1$	$\lambda_R = 0$	$\lambda_R = 1$	$\lambda_R = 0$
halfcheetah-random-medium-expert					
	ARI	0.97 ± 0.04	0.99 ± 0.00	0.91 ± 0.19	0.91 ± 0.17
	NMI	0.97 ± 0.03	0.97 ± 0.01	0.93 ± 0.12	0.92 ± 0.12
hopper-random-medium-expert					
	ARI	0.49 ± 0.29	0.98 ± 0.02	0.59 ± 0.33	0.97 ± 0.06
	NMI	0.57 ± 0.26	0.97 ± 0.02	0.66 ± 0.29	0.98 ± 0.04
walker2d-random-medium-expert					
	ARI	0.88 ± 0.16	0.98 ± 0.05	0.98 ± 0.03	1.00 ± 0.00
	NMI	0.90 ± 0.11	0.98 ± 0.03	0.97 ± 0.04	1.00 ± 0.00
Average	ARI	0.78 ± 0.28	0.98 ± 0.03	0.83 ± 0.27	0.96 ± 0.10
	NMI	0.81 ± 0.24	0.97 ± 0.02	0.85 ± 0.22	0.96 ± 0.08

4 Experiments

Our experiments consist of four parts: i) evaluating our trajectory clustering algorithm, ii) tightness analysis of the proposed lower bound $Q_{\hat{\mathcal{B}}}^{\text{LB}}$, iii)offline RL performance on various D4RL tasks, iv) additional experiments on a heterogeneous dataset, and v) ablation studies.

4.1 Performance of Trajectory Clustering

We first evaluated our trajectory clustering algorithm, which constitutes one of the main contributions of this paper. Details of the clustering method are provided in Appendix B.1. In meta RL settings for MDP inference, each MDP has independent transition and reward dynamics, so they must be modelled to infer the underlying task from trajectories. Under our MRP formulation, on the other hand, the transition and reward

dynamics of each MRP are coupled through the behaviour policy as we can see from Equations 3 and 4. While this suggests that modelling the behaviour alone may suffice for MRP identification, we hypothesise that explicitly modelling transition and reward dynamics can provide meaningful auxiliary signals that improve clustering performance.

To test this hypothesis, we include transition and reward dynamics losses in the overall meta-learning objective and evaluate the four different configurations $(\lambda_T, \lambda_R) \in \{(1,1), (1,0), (0,1), (0,0)\}$, where λ_T and λ_R are the weights for the transition and reward loss terms in Equation 11 of Appendix B.1. Clustering accuracy is evaluated on heterogeneous D4RL (Fu et al., 2020) datasets constructed by concatenating random, medium, and expert datasets.

Quantitative results are reported in Table 1, which shows the mean and standard deviation of Adjusted Rand Indices (ARI; Hubert & Arabie 1985) and Normalised Mutual Information (NMI) scores, which are two of the most popular clustering evaluation metrics, over five random seeds. In addition, Figure 2 visualises the inferred cluster assignments for the halfcheetah-random-medium-expert-v2 dataset, where trajectories from different behaviour regimes are consistently grouped across timesteps, This result supports the effectiveness of the proposed trajectory-level clustering formulation.

Across metrics and datasets, the configuration $(\lambda_T, \lambda_R) = (1,0)$ performs the best on average. We ascribe the poor performance of $\lambda_R > 0$ to the fact that, unlike state transitions, reward distributions can very vary drastically across behaviour policies, making them difficult to model jointly with a single network. Additional results on other D4RL datasets are reported in Appendix D.1, where the proposed clustering method consistently achieves ARI and NMI scores close to one, the perfect score.

4.2 Tightness of the Proposed Lower Bound Target

To evaluate the tightness of the proposed lower bound $Q_{\hat{\mathcal{B}}}^{\mathrm{LB}}$, we report the *normalised tightness*, evaluated on the OOD state-action pairs used for critic regularisation, defined as

$$\frac{Q_{\beta}^{\mathrm{LB}}(s, a) - r_{\min}/(1-\gamma)}{(r_{\max} - r_{\min})/(1-\gamma)}.$$

A value of zero corresponds to the trivial lower bound $r_{\min}/(1-\gamma)$, while larger value indicate a tighter regularisation target.

Figure 3 shows the evolution of the normalised tightness during training on the Hopper-medium-v2 dataset. The positive tightness observed in the figure indicates that the bound provides a non-trivial and informative target for exclusive regularisation throughout training.

Figure 3: Normalised tightness of $Q_{\hat{\mathcal{B}}}^{\mathrm{LB}}$ during training on the Hopper-medium-v2 dataset. We plot the mini-batch mean of the normalised tightness over training steps with shading indicating one standard deviation.

4.3 Offline RL performance on the D4RL benchmark

We then evaluated our algorithm perform on various offline RL tasks, using the D4RL (Fu et al., 2020) benchmark. We compared it with existing offline RL methods such as BC (Pomerleau, 1988), TD3+BC (Fujimoto & Gu, 2021), BCQ (Fujimoto et al., 2019), CQL (Kumar et al., 2020), BEAR (Kumar et al., 2019), IQL (Kostrikov et al., 2022), MCQ (Lyu et al., 2022), and SVR (Mao et al., 2023). We trained our method with five different seeds to obtain five different policies and sampled ten trajectories with each of them. The result is reported in Table 2, which shows the average and standard deviation of the fifty normalised scores. It is seen that our algorithm can successfully learn high-performing policies from most datasets, while attaining state-of-the-art scores on some tasks.

Table 2: Average normalised scores on the D4RL benchmark. Note that "ha" means halfcheetah, "ho" means hopper, "wa" means walker2d, "m" means medium, "r" means replay, "ra" means random, and "e" means expert.

Dataset	BC	TD3BC	BCQ	BEAR	CQL	IQL	MCQ	SVR	TraCER (Ours)
ha-ra	2.6	11.0	2.2	2.3	17.5	13.1	28.5	27.2	27.0 ± 1.1
ho-ra	4.1	8.5	7.8	3.9	7.9	7.9	31.8	31.0	31.5 ± 0.2
wa-ra	1.2	1.6	4.9	12.8	5.1	5.4	17.0	2.2	16.6 ± 7.9
ha-m	42.0	48.3	46.6	43.0	47.0	47.4	64.3	60.5	63.5 ± 1.2
ho-m	56.2	59.3	59.4	51.8	53.0	66.2	78.4	103.5	103.4 ± 0.9
wa-m	71.0	83.7	71.8	−0.2	73.3	78.3	91.0	92.4	96.5 ± 13.9
ha-m-r	36.4	44.6	42.2	36.3	45.5	44.2	56.8	52.5	52.2 ± 0.8
ho-m-r	21.8	60.9	60.9	52.2	88.7	94.7	101.6	103.7	102.2 ± 1.1
wa-m-r	24.9	81.8	57.0	7.0	81.8	73.8	91.3	95.6	95.4 ± 19.2
ha-m-e	59.6	90.7	95.4	46.0	75.6	86.7	87.5	94.2	90.9 ± 4.2
ho-m-e	51.7	98.0	106.9	50.6	105.6	91.5	111.2	111.2	112.4 ± 1.1
wa-m-e	101.2	110.1	107.7	22.1	107.9	109.6	114.2	109.3	108.3 ± 0.7
ha-e	88.2	81.7	92.7	92.9	96.3	95.0	96.2	96.1	96.6 ± 0.9
ho-e	110.9	107.8	109.0	54.6	96.5	109.4	111.4	111.1	112.7 ± 0.9
wa-e	107.7	110.2	106.3	106.6	108.5	109.9	107.2	110.0	113.4 ± 0.5
Average	52.3	67.5	64.5	38.8	67.3	68.9	79.2	80.0	81.5

(a) halfcheetah-medium-expert-v2   (b) hopper-medium-expert-v2

Figure 4: The UMAP of the states in the halfcheetah-medium-expert-v2 and hopper-medium-expert-v2 dataset.

4.4 Experiments on a Heterogeneous Dataset

Although D4RL datasets such as hopper-medium-expert-v2 were sampled with more than one behaviour policies, the action distributions seem actually unimodal on most states due to the state distribution being so different between the trajectories of the two behaviour policies. Figure 4 presents a visualisation of the entire and initial state distributions of the halfcheetah-medium-expert-v2 and hopper-medium-expert-v2 datasets where we have used the uniform manifold approximation and projection (UMAP; McInnes & Healy

Table 3: The performance of SVR and our method on the heterogeneous dataset.

Algorithm	Length	Return
SVR	8.00 ± 0.00	4.05 ± 0.01
Ours	436.3 ± 32.1	4062.0 ± 24.5

2018) technique for dimension reduction. We can see that the majority of expert and medium states of both datasets are clearly separated.

To demonstrate the effectiveness of our trajectory clustering algorithm more clearly, we created a custom dataset with drastically different initial state behaviours using the Hopper-v5 environment provided by the Gymnasium library (Towers et al., 2024). Half of the samples in the dataset were sampled from an expert policy, and the other half was sampled from a policy that tripped over within eight timesteps. Table 3 demonstrates that our method can effectively classify the two datasets and learn an optimal policy from a truly heterogeneous dataset.

4.5 Ablation Studies

We investigate the impact of the choice of hyperparameters α and $\kappa = K_V K_P$ on the performance of our method on three different datasets: halfcheetah-medium-v2, hopper-medium-v2, and walker2d-medium-v2. As shown in Table 4, the performance is robust to a wide range of α values. Similarly, we can see from Table 5 that the performance remains stable for moderate choices of κ, while large values ($\kappa \geq 50$) lead to degradation, particularly for hopper-medium-v2. Overall, the result indicate that our method does not require precise tuning on α and κ to achieve strong performance.

Table 4: The impact of the hyperparamter α on the average normalised score on three different datasets in the D4RL benchmark.

Dataset	$\alpha = 0.1$	$\alpha = 0.3$	$\alpha = 0.5$	$\alpha = 0.7$	$\alpha = 0.9$
halfcheetah-medium-v2	63.2 ± 1.1	62.4 ± 1.4	63.5 ± 1.2	63.3 ± 1.0	62.5 ± 1.2
hopper-medium-v2	102.2 ± 0.5	103.3 ± 0.9	103.4 ± 0.9	102.4 ± 0.7	103.1 ± 0.5
walker2d-medium-v2	93.0 ± 22.9	91.3 ± 22.4	96.1 ± 13.9	94.2 ± 20.4	97.0 ± 15.2

Table 5: The impact of the hyperparamter κ on the average normalised score on three different datasets in the D4RL benchmark.

Dataset	$\kappa = 0.1$	$\kappa = 0.2$	$\kappa = 0.5$	$\kappa = 1.0$	$\kappa = 2.0$
halfcheetah-medium-v2	62.5 ± 0.7	63.1 ± 1.4	63.5 ± 1.2	63.4 ± 0.9	63.1 ± 1.1
hopper-medium-v2	102.1 ± 2.8	102.6 ± 0.7	102.2 ± 0.8	102.0 ± 5.7	103.4 ± 0.9
walker2d-medium-v2	86.9 ± 27.6	90.6 ± 25.0	93.1 ± 26.7	96.1 ± 13.9	93.9 ± 15.6

Dataset	$\kappa = 5.0$	$\kappa = 10.0$	$\kappa = 20.0$	$\kappa = 50.0$	$\kappa = 100.0$
halfcheetah-medium-v2	63.3 ± 1.3	62.8 ± 0.8	63.2 ± 1.2	62.6 ± 1.0	62.1 ± 1.2
hopper-medium-v2	102.3 ± 3.9	102.5 ± 1.5	100.0 ± 6.8	84.1 ± 20.7	92.5 ± 21.1
walker2d-medium-v2	92.3 ± 1.6	89.5 ± 1.5	88.0 ± 1.6	81.7 ± 9.1	78.4 ± 13.7

5 Related Work

Value regularisation Value regularisation aims to discourage the actor from choosing OOD actions by penalising their critic values. Conservative Q learning (CQL; Kumar et al. 2020) was one of the first works in this line of research, where they minimise the standard TD error together with the Q-values of OOD actions. Lyu et al. (2022) pointed out that the CQL excessively regularsies the OOD Q-values to the extent that hampers the learning process. They suggested a milder regularisation term based on the critic values of ID actions. Supported value regularisation (SVR; Mao et al. 2023) proposed a penalisation scheme that maintains standard Bellman updates for ID actions while selectively penalising OOD actions' critic values. Most existing value regularisation algorithm, including the three works introduced in this section, sample the OOD actions from the current policy. However, as training progresses, the current policy will start to produce ID samples, so it is crucial to prevent unnecessary penalisation for those actions. CQL circumvents this issue through maximising the critic values for actions in the dataset. SVR does it by soft thresholding the regulariser based on the importance sampling ratio. In contrary, our method adopts a hard thresholding mechanism where ID actions are not penalised at all. This is possible due to our capability of explicitly identifying the OOD action set.

Heterogeneous datasets There are multiple prior work concerned with offline RL datasets with heterogeneous behaviours. Wang et al. (2023) utilises a diffusion model (Sohl-Dickstein et al., 2015; Ho et al., 2020) to capture the multi-modality of the true behaviour policy. Li et al. (2023) trains a mixture of Gaussian policy on the dataset via likelihood maximisation and then obtains a closed-form estimate of the best possible action near the behaviour policy. These two works ignores the trajectory information and handles each transition individually. Mao et al. (2024) incorporates an expectation–maximisation algorithm to learn diverse policies from a given offline RL dataset. Wang et al. (2024) proposes a learning-based trajectory clustering algorithm that can also automatically determine the cluster size. Although these two works leverage the trajectory information, they obtain the trajectory representation by simply averaging the samples, causing a substantial loss of information. We incorporate a sequence modelling technique instead to learn an effective representation of each trajectory.

VQ-VAE State-conditioned action quantisation (SAQ; Luo et al. 2023) is closely related to our work in the sense that they also leverage a VQ-VAE in the offline RL setting. However, their main focus is to discretise the actions because most of the challenges in offline RL originates from the ambiguity of continuous distributions. On the other hand, our algorithm uses VQ-VAE to cluster the trajectories and recover the behaviour policies. Also, SAQ discretises the actions individually, ignoring the trajectory information.

6 Conclusion

In this paper, we proposed a value regularisation algorithm for offline reinforcement learning that penalises critic values for out-of-distribution (OOD) actions, based on an explicitly identified OOD action set. We quantify the OOD-ness of an action using likelihood under the behaviour policy, with an adaptive threshold that accounts for the shape of the policy distribution. To enable reliable likelihood estimation in heterogeneous datasets where standard behaviour cloning fails, we introduced a trajectory clustering method based on a meta-learning formulation of the clustering problem. By regressing critic values of OOD actions towards a lower bound on the optimal Q-function, our approach yields a conservative yet informative regularisation scheme, which we show to be effective both theoretically and empirically.

Our approach assumes that each trajectory in the dataset is generated by a single behaviour policy. While this assumption may be violated when behaviour policies change within a trajectory, such changes are often gradual, allowing our method to perform reasonably well in practice. Nevertheless, this limitation may become more pronounced in real-world settings. An important direction for future work is to develop mechanisms for detecting behaviour policy changes within trajectories and segmenting them at the corresponding transition points. This would enable the application of explicit OOD identification to more complex scenarios involving trajectories composed of multiple distinct behavioural segments.

Broader Impact Statement

This paper presents work whose goal is to advance the field of Machine Learning. There are many potential societal consequences of our work, none which we feel must be specifically highlighted here.

References

Yoshua Bengio, Patrice Y. Simard, and Paolo Frasconi. Learning long-term dependencies with gradient descent is difficult. *IEEE Trans. Neural Networks*, 5(2):157–166, 1994.

James Bradbury, Roy Frostig, Peter Hawkins, Matthew James Johnson, Chris Leary, Dougal Maclaurin, George Necula, Adam Paszke, Jake VanderPlas, Skye Wanderman-Milne, and Qiao Zhang. JAX: composable transformations of Python+NumPy programs, 2018.

Kyunghyun Cho, Bart van Merrienboer, Çaglar Gülçehre, Dzmitry Bahdanau, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. Learning phrase representations using RNN encoder-decoder for statistical machine translation. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing, EMNLP 2014, October 25-29, 2014, Doha, Qatar, A meeting of SIGDAT, a Special Interest Group of the ACL*, pp. 1724–1734. ACL, 2014.

Tri Dao and Albert Gu. Transformers are ssms: Generalized models and efficient algorithms through structured state space duality. In *Forty-first International Conference on Machine Learning, ICML 2024, Vienna, Austria, July 21-27, 2024*. OpenReview.net, 2024.

Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4RL: datasets for deep data-driven reinforcement learning. *CoRR*, abs/2004.07219, 2020.

Scott Fujimoto and Shixiang Shane Gu. A minimalist approach to offline reinforcement learning. In *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 20132–20145, 2021.

Scott Fujimoto, David Meger, and Doina Precup. Off-policy deep reinforcement learning without exploration. In *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 2052–2062. PMLR, 2019.

Albert Gu and Tri Dao. Mamba: Linear-time sequence modeling with selective state spaces. *CoRR*, abs/2312.00752, 2023.

Albert Gu, Tri Dao, Stefano Ermon, Atri Rudra, and Christopher Ré. Hippo: Recurrent memory with optimal polynomial projections. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.

Albert Gu, Isys Johnson, Karan Goel, Khaled Saab, Tri Dao, Atri Rudra, and Christopher Ré. Combining recurrent, convolutional, and continuous-time models with linear state space layers. In *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 572–585, 2021.

Albert Gu, Karan Goel, and Christopher Ré. Efficiently modeling long sequences with structured state spaces. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net, 2022.

Jonathan Heek, Anselm Levskaya, Avital Oliver, Marvin Ritter, Bertrand Rondepierre, Andreas Steiner, and Marc van Zee. Flax: A neural network library and ecosystem for JAX, 2024.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.

Lawrence Hubert and Phipps Arabie. Comparing partitions. *Journal of Classification*, 2(1):193–218, Dec 1985. ISSN 1432-1343.

Rob J. Hyndman. Computing and graphing highest density regions. *The American Statistician*, 50(2): 120–126, 1996.

Diederik P. Kingma and Max Welling. Auto-encoding variational bayes. In *2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings*, 2014.

Ilya Kostrikov, Ashvin Nair, and Sergey Levine. Offline reinforcement learning with implicit q-learning. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net, 2022.

Aviral Kumar, Justin Fu, Matthew Soh, George Tucker, and Sergey Levine. Stabilizing off-policy q-learning via bootstrapping error reduction. In *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pp. 11761–11771, 2019.

Aviral Kumar, Aurick Zhou, George Tucker, and Sergey Levine. Conservative q-learning for offline reinforcement learning. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.

Jiachen Li, Edwin Zhang, Ming Yin, Qinxun Bai, Yu-Xiang Wang, and William Yang Wang. Offline reinforcement learning with closed-form policy improvement operators. In *International Conference on Machine Learning, ICML 2023, 23-29 July 2023, Honolulu, Hawaii, USA*, volume 202 of *Proceedings of Machine Learning Research*, pp. 20485–20528. PMLR, 2023.

Timothy P. Lillicrap, Jonathan J. Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. In *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings*, 2016.

Jianlan Luo, Perry Dong, Jeffrey Wu, Aviral Kumar, Xinyang Geng, and Sergey Levine. Action-quantized offline reinforcement learning for robotic skill learning. In *Conference on Robot Learning, CoRL 2023, 6-9 November 2023, Atlanta, GA, USA*, volume 229 of *Proceedings of Machine Learning Research*, pp. 1348–1361. PMLR, 2023.

Jiafei Lyu, Xiaoteng Ma, Xiu Li, and Zongqing Lu. Mildly conservative q-learning for offline reinforcement learning. In *Advances in Neural Information Processing Systems 35: Annual Conference on Neural Information Processing Systems 2022, NeurIPS 2022, New Orleans, LA, USA, November 28 - December 9, 2022*, 2022.

Yihuan Mao, Chengjie Wu, Xi Chen, Hao Hu, Ji Jiang, Tianze Zhou, Tangjie Lv, Changjie Fan, Zhipeng Hu, Yi Wu, Yujing Hu, and Chongjie Zhang. Stylized offline reinforcement learning: Extracting diverse high-quality behaviors from heterogeneous datasets. In *The Twelfth International Conference on Learning Representations, ICLR 2024, Vienna, Austria, May 7-11, 2024*. OpenReview.net, 2024.

Yixiu Mao, Hongchang Zhang, Chen Chen, Yi Xu, and Xiangyang Ji. Supported value regularization for offline reinforcement learning. In *Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023*, 2023.

Leland McInnes and John Healy. UMAP: uniform manifold approximation and projection for dimension reduction. *CoRR*, abs/1802.03426, 2018.

F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

Dean Pomerleau. ALVINN: an autonomous land vehicle in a neural network. In *Advances in Neural Information Processing Systems 1, [NIPS Conference, Denver, Colorado, USA, 1988]*, pp. 305–313. Morgan Kaufmann, 1988.

Jimmy T. H. Smith, Andrew Warrington, and Scott W. Linderman. Simplified state space layers for sequence modeling. In *The Eleventh International Conference on Learning Representations, ICLR 2023, Kigali, Rwanda, May 1-5, 2023*. OpenReview.net, 2023.

Jascha Sohl-Dickstein, Eric A. Weiss, Niru Maheswaranathan, and Surya Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. In *Proceedings of the 32nd International Conference on Machine Learning, ICML 2015, Lille, France, 6-11 July 2015*, volume 37 of *JMLR Workshop and Conference Proceedings*, pp. 2256–2265. JMLR.org, 2015.

Mark Towers, Ariel Kwiatkowski, Jordan K. Terry, John U. Balis, Gianluca De Cola, Tristan Deleu, Manuel Goulão, Andreas Kallinteris, Markus Krimmel, Arjun KG, Rodrigo Perez-Vicente, Andrea Pierré, Sander Schulhoff, Jun Jet Tai, Hannah Tan, and Omar G. Younis. Gymnasium: A standard interface for reinforcement learning environments. *CoRR*, abs/2407.17032, 2024.

Aäron van den Oord, Oriol Vinyals, and Koray Kavukcuoglu. Neural discrete representation learning. In *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pp. 6306–6315, 2017.

Cédric Villani. *Cyclical monotonicity and Kantorovich duality*, pp. 51–92. Springer Berlin Heidelberg, Berlin, Heidelberg, 2009. ISBN 978-3-540-71050-9.

Qiang Wang, Yixin Deng, Francisco Roldan Sanchez, Keru Wang, Kevin McGuinness, Noel E. O'Connor, and Stephen J. Redmond. Dataset clustering for improved offline policy learning. *CoRR*, abs/2402.09550, 2024.

Zhendong Wang, Jonathan J. Hunt, and Mingyuan Zhou. Diffusion policies as an expressive policy class for offline reinforcement learning. In *The Eleventh International Conference on Learning Representations, ICLR 2023, Kigali, Rwanda, May 1-5, 2023*. OpenReview.net, 2023.

Ronald J. Williams and Jing Peng. An efficient gradient-based algorithm for on-line training of recurrent network trajectories. *Neural Comput.*, 2(4):490–501, 1990.

Luisa M. Zintgraf, Sebastian Schulze, Cong Lu, Leo Feng, Maximilian Igl, Kyriacos Shiarlis, Yarin Gal, Katja Hofmann, and Shimon Whiteson. Varibad: Variational bayes-adaptive deep RL via meta-learning. *J. Mach. Learn. Res.*, 22:289:1–289:39, 2021.

A Notations

- **0**: a zero vector with dimensionality implied by context

- $f(y \mid x)$: the value of the pdf (or pmf) of the distribution $f(x)$ at y, where Y is a set and $f \colon X \to \mathcal{P}(Y)$

- $f \succeq g$: $f(x) \geq g(x)$ for all $x \in X$, where f and g are real-valued functions defined on a set X

- $f \equiv g$: $f(x) = g(x)$ for all $x \in X$, where f and g are real-valued functions defined on a set X

- I_d: an identity matrix with d rows and d columns

- $L^\infty(X)$: the space of bounded real value functions on a set X endowed with the supremum norm

- $[N]$: the set $\{0, 1, \ldots, N-1\}$, where N is an integer

- $\mathcal{P}(X)$: family of absolutely continuous probability distributions with finite first moments supported on a subset of X, where $X \subseteq \mathbb{R}^d$

- $\mathcal{P}_d(X)$: the family of discrete distributions supported on a subset of X, where $X \subseteq \mathbb{R}^d$

- $\operatorname{supp} \mu$: the support of a probability distribution μ

- $W_1(P_1, P_2)$: the Wasserstein distance of order 1 between two probability distributions $P_1, P_2 \in \mathcal{P}(X)$

B Practical Algorithm

B.1 Stage I: Behaviour Policy Learning

The network architecture used for trajectory clustering consists of three parts: the encoder, the latent sampler, and the decoder. The architecture is generally similar to that of variBAD except for a few adaptations. In this section, we will first go over how and why we modified each part. Then, we will propose a simple mechanism to adaptively set the number of clusters. Finally, we discuss the practical issue of certain cluster not being assigned to certain states, which leads to incorrect policy estimation.

The encoder needs to take an action-less trajectory $\tilde{\tau}$ as an input and output the amortised posterior. Since the length of the trajectory may vary from one to another, the network should be capable of taking variable-length sequence as its input. For that purpose, variBAD utilises gated recurrent units (GRU; Cho et al. 2014). GRUs and other recurrent neural network variants suffer from the vanishing gradient problem (Bengio et al., 1994), which hampers their ability to process long sequences. Truncated backpropagation through time (Williams & Peng, 1990) can mitigate the phenomena to a certain extent, but we instead adopt the state space model architecture that is recently gaining interest in the area of sequence modelling (Gu et al., 2020; 2021; 2022; Gu & Dao, 2023; Dao & Gu, 2024). In particular, we use the S5 layer (Smith et al., 2023), which is simple and computationally efficient.

The second modification was made on the way latents are sampled and ELBOs are computed. As the latent variable in the variBAD architecture is continuous, it is impossible to analytically compute the expectation, and hence, the reparametrisation trick (Kingma & Welling, 2014) must be used. Although the latent variable is discrete in our case, exact computation is still inefficient because it requires multiple forward and backward passes through the decoder. We instead utilise the vector quantised-variational autoencoder (VQ-VAE; van den Oord et al. 2017) to approximate the ELBO. Under the VQ-VAE formulation, the amortised posterior q_ϕ is modelled as

$$q_\phi(m = k \mid \tilde{\tau}_{:t}) = \begin{cases} 1 & \text{if } k = k_\phi(\tilde{\tau}_{:t}) \\ 0 & \text{otherwise,} \end{cases}$$

where $e_0, e_1, \ldots, e_{K-1}$ are latent embedding vectors and

$$k_\phi(\tilde{\tau}_{:t}) = \operatorname*{arg\,min}_{j \in [K]} \|q_\phi(\tilde{\tau}_{:t}) - e_k\|_2.$$

Note that for simplicity, we have abused the notation q_ϕ to denote both the posterior and the encoder. The gradient flows into the encoder q_ϕ via the loss function

$$\ell_{\mathrm{VQ}}(\phi; \tilde{\tau}_{:t}) = \left\| q_\phi(\tilde{\tau}_{:t}) - e_{k_\phi(\tilde{\tau}_{:t})} \right\|_2^2$$

and the latent embedding vectors are updated with exponential moving averages (EMA).

For the decoder, we use Gaussian distributions with diagonal covariance matrix to represent P_θ, β_θ, and R_θ. Most RL environments have a bounded action space, whereas a Gaussian distribution has unbounded support. To estimate the behaviour policy more accurately, we first normalise the actions between -1 and 1 and apply the inverse hyperbolic tangent function on each dimension of the actions to map them onto $\mathbb{R}^{d_a}$. Note that we use the mapped actions when learning the critic, that is, the critic function takes $\tanh^{-1}(a)$ instead of a as input. Finally, instead of taking the summation over the entire trajectory in Equations 6 and 7, we adopt the implementation trick of variBAD and randomly subsample N_d transition steps in Equation 6 and N_e ELBO terms in Equation 7. To conclude, the loss function for the trajectory clustering algorithm is

$$\ell_{\mathrm{TC}}(\theta, \phi; \tau) = \frac{1}{N_e N_d} \sum_{t \in \mathcal{I}_e} \sum_{i \in \mathcal{I}_d} \left(\log \beta_\theta(a \mid s; m) + \lambda_T \log P_\theta(s' \mid s; m) + \lambda_R \log R_\theta(r \mid s, s'; m) \right) \\ + \lambda_{\mathrm{VQ}} \ell_{\mathrm{VQ}}(\phi; \tilde{\tau}_{:t}), \tag{11}$$

where $\mathcal{I}_e$ and $\mathcal{I}_d$ are sets of indices sampled uniformly at random with replacement from $[T_\tau]$ with sizes N_e and N_d, respectively, and $\lambda_{\mathrm{VQ}}, \lambda_T, \lambda_R$ are tunable hyperparameters.

Choosing the right number of clusters is crucial for high performance in most clustering algorithms. To alleviate the burden of hyperparameter tuning, we adopt a two-phase training paradigm. During the first phase of the paradigm, we set the codebook size to be sufficiently large. After completing the first phase, we compute the cluster assignments for each state in the dataset. If the number of states assigned to a particular cluster does not exceed a certain threshold, we remove the corresponding code from the VQ-VAE codebook. The training is resumed with the remaining codebook. This way, we could adaptively determine the number of clusters without needing to perform an exhaustive hyperparameter search.

In theory, each behaviour policy is well-defined on every state $s \in \mathcal{S}$. However, in practice, we can trust our estimations only in the vicinity of the states they were trained on. The problem is, we train each $\hat{\beta}$ only on the states they are assigned to. Therefore, we need a mechanism to determine which behaviour policy estimates we can trust given a state $s \in \mathcal{S}$. For this purpose, we additionally train a classifier $f_\psi \colon \mathcal{S} \to \mathcal{P}_d([K])$ using the computed assignments and determine the credible set by the equation

$$\hat{\mathcal{V}}(s) = \left\{ \hat{\beta}_i \in \hat{\mathcal{B}} : f_\psi(i \mid s) \geq \frac{1}{b} \max_{j \in [K]} f_\psi(j \mid s) \right\},$$

where $b > 0$ is a hyperparameter. We accordingly modify the definition of $Q_{\hat{\mathcal{B}}}^{\mathrm{LB}}$ to

$$Q_{\hat{\mathcal{B}}}^{\mathrm{LB}}(s, a) = \max_{\hat{\beta} \in \hat{\mathcal{V}}(s)} Q_{\hat{\beta}}^{\mathrm{LB}}(s, a),$$

for all $s \in \mathcal{S}$ and $a \in \mathcal{A}$.

B.2 Stage II: Behaviour Value Learning

To learn the value functions of all K behaviour policies in parallel, we leverage a network $V_\zeta \colon \mathcal{S} \to \mathbb{R}^K$ with K outputs. The per sample temporal difference (TD) loss function can be written by the equation

$$\ell_V(\zeta; s, r, s') = \left(V_\zeta(s)[\mathbb{A}(s)] - r - \gamma V_{\zeta'}(s')[\mathbb{A}(s')] \right)^2,$$

where s, r, and s' are the state, reward, and next state sampled from the dataset, respectively, ζ' is the target network parameter that is updated by polyak averaging as in Lillicrap et al. (2016), and $V_\zeta(s)[i]$ is the i-th coordinate of $V_\zeta(s)$. Note that $\mathbb{A}(s)$, the cluster assignment of s, is equal to $\mathbb{A}(s')$, because we assign each trajectory to the same cluster.

B.3 Stage III: Policy Learning

In practice, it is infeasible to compute the supremum term in the penalised Bellman optimality operator $\mathcal{T}_{\mathcal{B}}^*$. We instead adopt the actor-critic formulation that alternates between the policy improvement step and the critic learning step. However, the highly non-convex geometry of $Q_{\mathcal{B}}^*$ imposes a burden both on the critic and the actor step: it is difficult for a neural network to accurately capture the sophisticated structure of $Q_{\mathcal{B}}^*$ and gradient methods will yield suboptimal solutions during the actor step. To alleviate this challenge and facilitate both actor and critic learning, we adopt a vector-valued critic function and a vector version of the penalised Bellman optimality operator $\mathcal{T}_{\mathcal{B}}^*$, defined by the following equation:

$$(\boldsymbol{\mathcal{T}}_{\mathcal{B}}^* \mathbf{Q})_i(s,a) = \begin{cases} (\mathcal{T}^* \max_{j \in \{1,2,\dots,K\}} Q_j)(s,a) & \text{if } a \in \mathcal{R}_{\beta_i}(p_\alpha; s) \\ Q_{\beta_i}^{\mathrm{LB}}(s,a) & \text{otherwise.} \end{cases}$$

By Proposition C.15, repeated application of $\boldsymbol{\mathcal{T}}_{\mathcal{B}}^*$ results in a unique fixed point $\mathbf{Q}_{\mathcal{B}}^* = (Q_1^*, Q_2^*, \dots, Q_K^*)$ where

$$\pi_{\mathcal{B}}^*(s) = \arg\max_{a \in \mathcal{A}} \max_{i \in \{1,2,\dots,K\}} Q_i^*(s,a).$$

As $\mathcal{R}_\beta(p_\alpha; s)$ is a convex ellipsoid for all $\beta \in \mathcal{B}$ and $s \in \mathcal{S}$, a neural network can more accurately learn to estimate Q_i^* and gradient methods can yield near-optimal solutions.

To practically implement $\boldsymbol{\mathcal{T}}_{\mathcal{B}}^*$, we utilise an ensemble of K actors $(\pi_0, \pi_1, \dots, \pi_{K-1})$, and K critics $(Q_0, Q_1, \dots, Q_{K-1})$ parametrised by ψ_π and ψ_Q, respectively. We can compute K action candidates $a_0, a_1, \dots, a_{K-1}$, from the outputs of the K actors by the following equation:

$$a_i = \boldsymbol{\mu}_{\hat{\beta}_i}(s) + \pi_i(s; \psi_\pi),$$

where $\boldsymbol{\mu}_{\hat{\beta}}$ is the mean vector of the behaviour policy estimate $\hat{\beta}$. Then we choose the best action $a_{i_s^*}$ with respect to the current critic function, that is,

$$i_s^* = \arg\max_{i \in \hat{\mathcal{I}}(s)} Q_i(s, \pi_i(s; \psi_\pi); \psi_Q),$$

where

$$\hat{\mathcal{I}}(s) = \left\{ i \in [K] : \hat{\beta}_i \in \hat{\mathcal{V}}(s) \right\}.$$

Note that we feed $\pi_i(s; \psi_\pi)$ instead of a_i to Q_i. Since we have already obtained $\hat{\mathcal{B}}$ in Stage I, $\boldsymbol{\mu}_{\hat{\beta}_i}(s)$ is fixed throughout the entire training process, so we may just translate the actions by $\boldsymbol{\mu}_{\hat{\beta}_i}(s)$ without losing generality nor introducing a new source of instability. The loss function for the policy improvement step can be written by the following equation:

$$\ell_\pi(\psi_\pi; s) = -\frac{1}{K} \sum_{i=0}^{K-1} \mathbf{1}_{\hat{\beta}_i \in \hat{\mathcal{V}}(s)} Q_i(s, \pi_i(s; \psi_\pi); \psi_Q).$$

The critic learning step has two objectives: minimising the TD error and penalising the OOD actions. For the first objective, we adopt a TD loss adapted to our vector-valued critic, which is represented by the equation

$$\ell_Q^{\mathrm{TD}}(\psi_Q; s, a, r, s') = \frac{1}{K} \sum_{i=0}^{K-1} \mathbf{1}_{\hat{\beta}_i \in \hat{\mathcal{V}}(s)} \left(Q_i(s, a - \boldsymbol{\mu}_{\hat{\beta}_i}(s); \psi_Q) - T(r, s') \right)^2,$$

where s, a, r, and s' are the state, action, reward, and next state sampled from the dataset, respectively, and the TD target $T(r, s')$ is defined as

$$T(r, s') = r + \gamma \max_{i \in \hat{\mathcal{I}}(s)} Q_i\left(s', \pi_i(s'; \psi_\pi'); \psi_Q'\right).$$

ψ_Q' and ψ_π' in the preceding equation are the target critic network parameters and target actor network parameters, respectively, which are updated by polyak averaging to gradually follow ψ_Q and ψ_π. Following

TD3 (Fujimoto & Gu, 2021), both targets are updated only on actor update steps, that is, every T_{actor} critic updates.

The second objective of the critic learning step is to penalise the critic values of OOD actions towards the corresponding $Q_{\hat{\beta}}^{\text{LB}}(s, a)$. However, computing $Q_{\hat{\beta}}^{\text{LB}}$ is not straightforward, due to the term $\mathbb{E}_{a' \sim \hat{\beta}(s)}[\|a - a'\|]$ in Equation 8. We discovered that if we use a 1-norm and assume that $\hat{\beta}$ has a diagonal covariance matrix, the expectation has the following closed-form expression (Proposition C.14):

$$\mathbb{E}_{a' \sim \hat{\beta}(s)}[\|a - a'\|_1] = \sum_{i=1}^{d_a}(a_i - \mu_i(s))\operatorname{erf}\left(\frac{a_i - \mu_i(s)}{\sigma_i(s)\sqrt{2}}\right) + \sqrt{\frac{2}{\pi}}\sum_{i=1}^{d_a}\sigma_i\exp\left(-\frac{(a_i - \mu_i(s))^2}{2\sigma_i^2(s)}\right),$$

where $\hat{\beta}(s)$ is a Gaussian distribution with a state-dependent mean vector $\boldsymbol{\mu}(s) = (\mu_1(s), \mu_2(s), \ldots, \mu_{d_a}(s))$ and a state-dependent covariance matrix whose main diagonal is $\boldsymbol{\sigma}(s) = (\sigma_1(s), \sigma_2(s), \ldots, \sigma_{d_a}(s))$ and $a = (a_1, a_2, \ldots, a_{d_a})$. To sum up, the loss function for regularisation is

$$\ell_Q^{\text{reg}}(\psi_Q; \tilde{s}, \delta_0, \delta_1, \ldots, \delta_{K-1}) = \frac{1}{K}\sum_{i=0}^{K-1}\mathbf{1}_{\hat{\beta}_i \in \hat{\mathcal{V}}(\tilde{s})}\mathbf{1}_{\delta_i \notin \mathcal{R}_{\hat{\beta}_i}(p_\alpha; \tilde{s})}\left(Q_i(\tilde{s}, \delta_i) - Q_{\hat{\beta}_i}^{\text{LB}}(\tilde{s}, \delta_i)\right)^2,$$

where $\tilde{s}$ is a state sampled from the dataset and δ_i's are residual actions sampled from π_{alg}^i. The resulting total loss can be written by the following equation

$$\ell_Q(\psi_Q) = \mathbb{E}_{(s,a,r,s') \sim \mathcal{D}}\left[\ell_Q^{\text{TD}}(\psi_Q; s, a, r, s')\right] + w_Q\mathbb{E}_{\tilde{s} \sim \mathcal{D}, \delta_i \sim \pi_{\text{alg}}^i(\cdot|\tilde{s})}\left[\ell_Q^{\text{reg}}(\psi_Q; \tilde{s}, \delta_0, \delta_1, \ldots, \delta_{K-1})\right], \qquad (12)$$

where w_Q is a tunable hyperparameter. For π_{alg}^i we adopted

$$\pi_{\text{alg}}^i(\delta \mid s) = \frac{1}{2}\tilde{\beta}(\delta \mid s) + \frac{1}{2}\pi_i(\delta \mid s; \psi_\pi),$$

where π_i is the current actor and $\tilde{\beta}$ is defined as

$$\tilde{\beta}(\cdot \mid s) = \mathcal{N}(\mathbf{0}, \kappa^2\boldsymbol{\Sigma}_{\hat{\beta}_i}(s)).$$

Here, κ is a tunable hyperparameter that we set to 2. The first term regularises the critic values over a broad range of residual actions, which keeps Q_i low far from the behaviour mode, and consequently guides π_i towards producing near-zero residuals. The second term regularises the critic values in the vicinity of the current policy allowing delicate control near the boundary of OOD(s). For $r_{\min}$ and $r_{\max}$, following Mao et al. (2023), we estimate them by the minimum and maximum rewards in all of the datasets of a given task, that is, for example $r_{\min}$ and $r_{\max}$ for a hopper-v2 dataset is computed by the minimum and maximum of the rewards in hopper-expert-v2, hopper-medium-v2, and hopper-random-v2. A pseudocode for the entire policy learning step is given in Algorithm 2.

Algorithm 1 OOD test for residual action δ under mode i

Require: $\boldsymbol{\sigma}_{\hat{\beta}_i}(s)$ for all $i \in [K]$ and $s \in \mathcal{D}$

1: **function** IsOOD(s, δ, i)

2:     **if** $\displaystyle\sum_{k=1}^{d_a}\frac{\delta_k^2}{(\boldsymbol{\sigma}_{\hat{\beta}_i}(s))_k^2} > F_{\chi_{d_a}^2}^{-1}(1 - \alpha)$ **then**

3:         **Return** 1

4:     **else**

5:         **Return** 0

6:     **end if**

7: **end function**

Algorithm 2 Policy learning

Require: $r_{\min}$, $r_{\max}$, $\boldsymbol{\mu}_{\hat{\beta}_i}(s)$, $\boldsymbol{\sigma}_{\hat{\beta}_i}(s)$, $\hat{V}^{\hat{\beta}_i}(s)$, and $\hat{\mathcal{I}}(s)$ for all $i \in [K]$ and states $s \in \mathcal{D}$
1: **for** $t \leftarrow 0, 1, \ldots, N-1$ **do**
2:      Sample B transitions $\{(s_j, a_j, r_j, s'_j)\}_{j=0}^{B-1}$ from $\mathcal{D}$
3:      Sample BK residual actions $\delta_{ij} \sim \pi_i(s'_j; \psi'_\pi)$
4:      Compute TD targets
$$\tau_j \leftarrow r_j + \gamma \max_{k \in \hat{\mathcal{I}}(s'_j)} Q_k(s'_j, \delta_{kj}; \psi'_Q)$$

5:      Compute sample TD loss

$$\ell_Q^{\mathrm{TD}} \leftarrow \frac{1}{BK} \sum_{j=0}^{B-1} \sum_{i=0}^{K-1} \mathbf{1}_{i \in \hat{\mathcal{I}}(s_j)} \left(Q_i(s_j, a_j - \boldsymbol{\mu}_{\hat{\beta}_i}(s_j); \psi_Q) - \tau_j \right)^2$$

6:      Sample B' states $\{\tilde{s}_j\}_{j=0}^{B'-1}$ from $\mathcal{D}$
7:      Sample $B'K$ residual actions $\{\tilde{\delta}_{ij}\}_{i=0,j=0}^{i=K-1,j=B'-1}$, where

$$\tilde{\delta}_{ij} \sim \begin{cases} \mathcal{N}(\mathbf{0}, \mathrm{diag}(\boldsymbol{\sigma}_{\hat{\beta}_i}(\tilde{s}_j))) & \text{if } j < B'/2 \\ \pi_i(\tilde{s}_j; \psi_\pi) & \text{otherwise} \end{cases}$$

8:      Compute the OOD mask $m_{ij} \leftarrow \mathrm{IsOOD}(\tilde{\delta}_{ij}, \tilde{s}_j, i)$
9:      Compute the expected deviation

$$\Delta_{ij} \leftarrow \sum_{k=1}^{d_a} (\tilde{\delta}_{ij})_k \, \mathrm{erf}\left(\frac{(\tilde{\delta}_{ij})_k}{(\boldsymbol{\sigma}_{\hat{\beta}_i}(\tilde{s}_j))_k \sqrt{2}} \right) + \sum_{k=1}^{d_a} \sqrt{\frac{2}{\pi}} (\boldsymbol{\sigma}_{\hat{\beta}_i}(\tilde{s}_j))_k \exp\left(-\frac{(\tilde{\delta}_{ij})_k^2}{2(\boldsymbol{\sigma}_{\hat{\beta}_i}(\tilde{s}_j))_k^2} \right)$$

10:      Compute the lower bounds

$$\tilde{q}_{ij} \leftarrow \max\left\{ \hat{V}^{\hat{\beta}_i}(\tilde{s}) - r_{\max} + r_{\min} - \gamma K_T \Delta_{ij}, \frac{r_{\min}}{1-\gamma} \right\}$$

11:      Compute regularisation loss

$$\ell_Q^{\mathrm{reg}} \leftarrow \frac{1}{B'K} \sum_{j=0}^{B'-1} \sum_{i=0}^{K-1} \mathbf{1}_{i \in \hat{\mathcal{I}}(\tilde{s}_j)} m_{ij} \left(Q_i(\tilde{s}_j, \tilde{\delta}_{ij}; \psi_Q) - \tilde{q}_{ij} \right)^2$$

12:      Apply a gradient descent algorithm with respect to the following loss

$$\ell(\psi_Q) \leftarrow \ell_Q^{\mathrm{TD}} + w_Q \ell_Q^{\mathrm{reg}}$$

13:      **if** $t \equiv -1 \pmod{T_{\mathrm{actor}}}$ **then**
14:          Sample B states $\{\check{s}_j\}_{j=0}^{B-1}$ from $\mathcal{D}$
15:          Sample BK residual actions $\check{\delta}_{ij} \sim \pi_i(\check{s}_j; \psi_\pi)$
16:          Apply a gradient descent algorithm with respect to the following loss

$$\ell_\pi(\psi_\pi) \leftarrow -\frac{1}{BK} \sum_{j=0}^{B-1} \sum_{i=0}^{K-1} \mathbf{1}_{i \in \hat{\mathcal{I}}(\check{s}_j)} Q_i(\check{s}_j, \check{\delta}_{ij}; \psi_Q),$$

17:          $\psi'_Q \leftarrow \tau \psi'_Q + (1-\tau)\psi_Q$
18:          $\psi'_\pi \leftarrow \tau \psi'_\pi + (1-\tau)\psi_\pi$
19:      **end if**
20: **end for**

B.4 Implementation Details

We standardised the observations following Fujimoto & Gu (2021) and normalised the rewards so that the average empirical discounted return becomes $\hat{V}$, which we set to 100 for most of our experiments. The algorithm was implemented upon the JAX (Bradbury et al., 2018) framework using the Flax (Heek et al., 2024) library. The scikit-learn (Pedregosa et al., 2011) library was used to compute ARIs and NMIs for Sections 4.1 and D.1.

C Proofs

Proposition C.1. *Let $\mathbf{X}$ be a multivariate Gaussian random variable with mean vector $\boldsymbol{\mu} \in \mathbb{R}^d$ and positive definite covariance matrix $\boldsymbol{\Sigma} \in \mathbb{R}^{d \times d}$. The $100(1 - \alpha)\,\%$ HDR is*

$$\mathcal{R}(f_\alpha) = \left\{ \mathbf{x} \in \mathbb{R}^d : (\mathbf{x} - \boldsymbol{\mu})^\top \boldsymbol{\Sigma}^{-1} (\mathbf{x} - \boldsymbol{\mu}) \leq F_{\chi_d^2}^{-1}(1 - \alpha) \right\},$$

where $F_{\chi_d^2}$ is the cumulative distribution function of a chi-squared random variable with d degrees of freedom.

Proof. Let $\mathbf{Z} = (Z_1, Z_2, \ldots, Z_d) = \sqrt{\boldsymbol{\Sigma}^{-1}}(\mathbf{X} - \boldsymbol{\mu})$. By the change of variables formula,

$$\begin{aligned}
p_{\mathbf{Z}}(\mathbf{z}) &= \left| \det(\sqrt{\boldsymbol{\Sigma}}) \right| p_{\mathbf{X}}\left(\boldsymbol{\mu} + \sqrt{\boldsymbol{\Sigma}} \mathbf{z} \right) \\
&= \det(\boldsymbol{\Sigma})^{1/2} (2\pi)^{-d/2} \det(\boldsymbol{\Sigma})^{-1/2} \exp\left(-\frac{1}{2} \mathbf{z}^\top \mathbf{z} \right) \\
&= (2\pi)^{-d/2} \exp\left(-\frac{1}{2} \mathbf{z}^\top \mathbf{z} \right),
\end{aligned}$$

where $p_{\mathbf{X}}$ and $p_{\mathbf{Z}}$ are the pdfs of random vectors $\mathbf{X}$ and $\mathbf{Z}$, respectively. We can see that $\mathbf{Z}$ is a standard normal random vector. Since

$$\begin{aligned}
\mathcal{R}(y) &= \left\{ \mathbf{x} \in \mathbb{R}^d : (2\pi)^{-d/2} \det(\boldsymbol{\Sigma})^{-1/2} \exp\left(-\frac{1}{2}(\mathbf{x} - \boldsymbol{\mu})^\top \boldsymbol{\Sigma}^{-1}(\mathbf{x} - \boldsymbol{\mu}) \right) \geq y \right\} \\
&= \left\{ \mathbf{x} \in \mathbb{R}^d : (\mathbf{x} - \boldsymbol{\mu})^\top \boldsymbol{\Sigma}^{-1}(\mathbf{x} - \boldsymbol{\mu}) \leq -2 \log y + d \log(2\pi) + \log \det(\Sigma) \right\},
\end{aligned}$$

we have

$$\begin{aligned}
P(\mathbf{X} \in \mathcal{R}(y)) &= P\left(\mathbf{Z}^\top \mathbf{Z} \leq -2 \log y + d \log(2\pi) + \log \det(\Sigma) \right) \\
&= P\left(\sum_{i=1}^d Z_i^2 \leq -2 \log y + d \log(2\pi) + \log \det(\Sigma) \right).
\end{aligned}$$

$Z_1, Z_2, \ldots, Z_d$ are independent, so $\sum_{i=1}^d Z_i^2$ is a chi-squared random variable. This implies

$$P(\mathbf{X} \in \mathcal{R}(y)) = F_{\chi_d^2}(-2 \log y + d \log(2\pi) + \log \det(\boldsymbol{\Sigma})).$$

$P(\mathbf{X} \in \mathcal{R}(y)) \geq 1 - \alpha$ if and only if

$$-2 \log y + d \log(2\pi) + \log \det(\boldsymbol{\Sigma}) \geq F_{\chi_d^2}^{-1}(1 - \alpha).$$

Therefore,

$$f_\alpha = (2\pi)^{d/2} \det(\boldsymbol{\Sigma})^{1/2} \exp\left(-\frac{1}{2} F_{\chi_d^2}(1 - \alpha) \right),$$

which means

$$\mathcal{R}(f_\alpha) = \left\{ \mathbf{x} \in \mathbb{R}^d : (\mathbf{x} - \boldsymbol{\mu})^\top \boldsymbol{\Sigma}^{-1}(\mathbf{x} - \boldsymbol{\mu}) \leq F_{\chi_d^2}^{-1}(1 - \alpha) \right\}.$$

$\square$

Proposition C.2. *Let m be a discrete latent variable supported on $[K]$ and*

$$\tau_{:T} = (s_0, a_0, r_0, s_1, a_1, r_1, s_2, a_2, r_2, \ldots, s_{T-1}, a_{T-1}, r_{T-1}, s_T)$$

be a trajectory rolled-out according to the following sampling process: $s_0 \sim \rho_0$, $m \sim p$, and for each $t \in [T]$, $s_{t+1} \sim P(s_t; m)$, $a_t \sim \beta(s_t; m)$, and $r_t \sim R(s_t, s_{t+1}; m)$. The marginal pdf can be written as

$$p(\tau_{:T}) = \rho_0(s_0) \sum_{m=0}^{K-1} p(m) \prod_{t=0}^{T-1} P(s_{t+1} \mid s_t; m)\beta(a_t \mid s_t; m)R(r_t \mid s_t, s_{t+1}; m)$$

and for any distribution q on $[K]$,

$$
\begin{aligned}
\log p(\tau_{:T}) \geq{}& \log \rho_0(s_0) - D_{\mathrm{KL}}(q \parallel p) \\
&+ \sum_{t=0}^{T-1} \mathbb{E}_{m \sim q}\left[\log P(s_{t+1} \mid s_t; m) + \log \beta(a_t \mid s_t; m) + \log R(r_t \mid s_t, s_{t+1}; m)\right].
\end{aligned}
\tag{13}
$$

Proof. Let us denote the action-less trajectory by $\tilde{\tau}_{:T}$, that is,

$$\tilde{\tau}_{:T} = (s_0, r_0, s_1, r_1, s_2, r_2, \ldots, s_{T-1}, r_{T-1}, s_T).$$

By Jensen's inequality,

$$
\begin{aligned}
\log p(\tau_{:T}) &= \log \rho_0(s_0) + \log \sum_{m=0}^{K-1} p(m) \prod_{t=0}^{T-1} \left[P(s_{t+1} \mid s_t; m)\beta(a_t \mid s_t; m)R(r_t \mid s_t, s_{t+1}; m)\right] \\
&= \log \rho_0(s_0) + \log \sum_{m=0}^{K-1} q(m) \cdot \frac{p(m)}{q(m)} \prod_{t=0}^{T-1} \left[P(s_{t+1} \mid s_t; m)\beta(a_t \mid s_t; m)R(r_t \mid s_t, s_{t+1}; m)\right] \\
&\geq \log \rho_0(s_0) + \mathbb{E}_{m \sim q}\left[\log \frac{p(m)}{q(m)} + \sum_{t=0}^{T-1} A(s_t, a_t, r_t, s_{t+1}; m)\right] \\
&= \log \rho_0(s_0) - D_{\mathrm{KL}}(q \parallel p) + \sum_{t=0}^{T-1} \mathbb{E}_{m \sim q}\left[A(s_t, a_t, r_t, s_{t+1}; m)\right],
\end{aligned}
$$

where

$$A(s_t, a_t, r_t, s_{t+1}; m) = \log P(s_{t+1} \mid s_t; m) + \log \beta(a_t \mid s_t; m) + \log R(r_t \mid s_t, s_{t+1}; m).$$

$\square$

We restate the two assumptions we made in Section 3.2 for the reader's convenience.

Assumption C.3. There is $K_P > 0$ such that for all $s \in \mathcal{S}$ and $a_1, a_2 \in \mathcal{A}$, $W_1(P(s, a_1), P(s, a_2)) < K_P \|a_1 - a_2\|$.

Assumption C.4. The value function of the behaviour policy β is K_V-Lipschitz.

Lemma C.5. *For any policy π and $s \in \mathcal{S}$,*

$$\frac{r_{\min}}{1-\gamma} \leq V^\beta(s) \leq \frac{r_{\max}}{1-\gamma}.$$

Proof. By the definition of V^π, for all $s \in \mathcal{S}$,

$$V^\pi(s) = \mathbb{E}_{\tau \sim \pi|s}\left[\sum_{t=0}^{\infty} \gamma^t r_t\right] \geq \mathbb{E}_{\tau \sim \pi|s}\left[\sum_{t=0}^{\infty} \gamma^t r_{\min}\right] = \frac{r_{\min}}{1-\gamma},$$

and

$$V^\pi(s) = \mathbb{E}_{\tau \sim \pi|s}\left[\sum_{t=0}^{\infty} \gamma^t r_t\right] \leq \mathbb{E}_{\tau \sim \pi|s}\left[\sum_{t=0}^{\infty} \gamma^t r_{\max}\right] = \frac{r_{\max}}{1-\gamma}.$$

$\square$

Proposition C.6. *Define $Q_\beta^{\mathrm{LB}}\colon \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ by the equation*

$$Q_\beta^{\mathrm{LB}}(s,a) = \max\left\{V^\beta(s) - r_{\max} + r_{\min} - \gamma K_V K_P \mathbb{E}_{a'\sim\beta(s)}\left[\|a - a'\|\right], \frac{r_{\min}}{1-\gamma}\right\}.$$

For any policy $\pi\colon \mathcal{S} \to \mathcal{P}(\mathcal{A})$ such that $V^\pi \succeq V^\beta$, $Q^\pi \succeq Q_\beta^{\mathrm{LB}}$.

Proof. By Lemma C.5 and the definition of Q^π, for all $s \in \mathcal{S}$ and $a \in \mathcal{A}$,

$$Q^\pi(s,a) = \mathbb{E}_{s'\sim P(s,a,s'),r\sim R(s,a,s')}\left[r + \gamma V^\pi(s')\right] \geq \mathbb{E}_{s'\sim P(s,a,s'),r\sim R(s,a,s')}\left[r_{\min} + \gamma\frac{r_{\min}}{1-\gamma}\right] = \frac{r_{\min}}{1-\gamma}.$$

So we only need to show that for all $s \in \mathcal{S}$ and $a \in \mathcal{A}$,

$$Q^\pi(s,a) \geq V^\beta(s) - r_{\max} + r_{\min} - \gamma K_V K_P \mathbb{E}_{a'\sim\beta(s)}\left[\|a - a'\|\right].$$

Let $a_1, a_2 \in \mathcal{A}$. By the Kantorovich–Rubinstein formula (Villani, 2009),

$$\left|\mathbb{E}_{s'\sim P(\cdot|s,a_1)}[V^\beta(s')] - \mathbb{E}_{s'\sim P(\cdot|s,a_2)}[V^\beta(s')]\right| \leq K_V W_1(P(\cdot \mid s,a_1), P(\cdot \mid s,a_2)) \leq K_V K_P\|a_1 - a_2\|.$$

Therefore,

$$\begin{aligned}
Q^\pi(s,a) &= \mathbb{E}_{s'\sim P(s,a),r\sim R(s,a,s')}\left[r + \gamma V^\pi(s')\right]\\
&\geq \mathbb{E}_{s'\sim P(s,a),r\sim R(s,a,s')}\left[r + \gamma V^\beta(s')\right]\\
&= V^\beta(s) - \mathbb{E}_{a'\sim\beta(\cdot|s)}\left[\mathbb{E}_{s'\sim P(s,a'),r\sim R(s,a',s')}\left[r + \gamma V^\beta(s')\right]\right]\\
&\quad + \mathbb{E}_{s'\sim P(s,a),r\sim R(s,a,s')}\left[r + \gamma V^\beta(s')\right]\\
&\geq V^\beta(s) - r_{\max} + r_{\min} + \gamma\mathbb{E}_{a'\sim\beta(s)}\left[\mathbb{E}_{s'\sim P(s,a)}\left[V^\beta(s')\right] - \mathbb{E}_{s'\sim P(s,a')}\left[V^\beta(s')\right]\right]\\
&\geq V^\beta(s) - r_{\max} + r_{\min} - \gamma K_V K_P \mathbb{E}_{a'\sim\beta(\cdot|s)}\left[\|a - a'\|\right].
\end{aligned}$$

Note that we have used the fact that

$$V^\beta(s) = \mathbb{E}_{a'\sim\beta(s),s'\sim P(s,a'),r\sim R(s,a',s')}\left[r + \gamma V^\beta(s')\right].$$

$\square$

Theorem C.7. *Let $\{A_s\}_{s\in\mathcal{S}}$ be a family of subsets of $\mathcal{A}$, $\tilde{Q} \in L^\infty(\mathcal{S} \times \mathcal{A})$, and $\mathcal{T}_A$ be an operator on the space of real-valued functions on $\mathcal{S} \times \mathcal{A}$ defined by the equation*

$$(\mathcal{T}_A Q)(s,a) = \begin{cases} (\mathcal{T}^* Q)(s,a) & \text{if } a \in A_s,\\ \tilde{Q}(s,a) & \text{otherwise,} \end{cases}$$

for each $Q \in L^\infty(\mathcal{S} \times \mathcal{A})$. Then any bounded real-valued function on $\mathcal{S} \times \mathcal{A}$ converges to a unique fixed point Q_A by repeatedly applying $\mathcal{T}_A$.

Proof. Fix $s \in \mathcal{S}$, $a \in \mathcal{A}$, and $Q \in L^\infty(\mathcal{S} \times \mathcal{A})$. If $a \in A_s$,

$$\begin{aligned}
|(\mathcal{T}_A Q)(s,a)| &= |(\mathcal{T}^* Q)(s,a)|\\
&= \left|\mathbb{E}_{s'\sim P(s,a),r\sim R(s,a,s')}\left[r + \gamma \sup_{a'\in\mathcal{A}} Q(s',a')\right]\right|\\
&\leq \mathbb{E}_{s'\sim P(s,a),r\sim R(s,a,s')}\left[\left|r + \gamma \sup_{a'\in\mathcal{A}} Q(s',a')\right|\right]\\
&\leq \mathbb{E}_{s'\sim P(s,a),r\sim R(s,a,s')}\left[|r| + \gamma \left|\sup_{a'\in\mathcal{A}} Q(s',a')\right|\right]\\
&\leq \mathbb{E}_{s'\sim P(s,a),r\sim R(s,a,s')}\left[\max\left\{|r_{\max}|, |r_{\min}|\right\} + \gamma\|Q\|_\infty\right],\\
&= \max\left\{|r_{\max}|, |r_{\min}|\right\} + \gamma\|Q\|_\infty.
\end{aligned} \tag{14}$$

Otherwise,
$$|(\mathcal{T}_A Q)(s,a)| = |\tilde{Q}(s,a)| \leq \|\tilde{Q}\|_\infty.$$

So
$$\|\mathcal{T}_A Q\|_\infty \leq \max \left\{ \|\tilde{Q}\|_\infty, \max\{|r_{\max}|, |r_{\min}|\} + \gamma \|Q\|_\infty \right\} < \infty,$$

that is, $\mathcal{T}_A Q \in L^\infty(\mathcal{S} \times \mathcal{A})$. So the restriction of $\mathcal{T}_A$ onto $L^\infty(\mathcal{S} \times \mathcal{A})$ is an operator on $L^\infty(\mathcal{S} \times \mathcal{A})$. With a slight abuse of notation, we will just denote the restriction by $\mathcal{T}_A$ from now on.

Now we go on and prove that $\mathcal{T}_A$ is a contraction operator. Fix $s \in \mathcal{S}$, $a \in \mathcal{A}$ and $Q_1, Q_2 \in L^\infty(\mathcal{S} \times \mathcal{A})$. If $a \in A_s$,

$$
\begin{aligned}
|(\mathcal{T}_A Q_1)(s,a) - (\mathcal{T}_A Q_2)(s,a)| &= |(\mathcal{T}^* Q_1)(s,a) - (\mathcal{T}^* Q_2)(s,a)| \\
&= \gamma \left| \mathbb{E}_{s' \sim P(s,a)} \left[\sup_{a' \in \mathcal{A}} Q_1(s',a') - \sup_{a'' \in \mathcal{A}} Q_2(s',a'') \right] \right| \\
&\leq \gamma \mathbb{E}_{s' \sim P(s,a)} \left[\left| \sup_{a' \in \mathcal{A}} Q_1(s',a') - \sup_{a'' \in \mathcal{A}} Q_2(s',a'') \right| \right] \\
&\leq \gamma \mathbb{E}_{s' \sim P(s,a)} \left[\sup_{a' \in \mathcal{A}} |Q_1(s',a') - Q_2(s',a')| \right] \\
&\leq \gamma \|Q_1 - Q_2\|_\infty.
\end{aligned}
$$

Otherwise,
$$|(\mathcal{T}_A Q_1)(s,a) - (\mathcal{T}_A Q_2)(s,a)| = |\tilde{Q}(s,a) - \tilde{Q}(s,a)| = 0 \leq \gamma \|Q_1 - Q_2\|_\infty.$$

Therefore, and $\mathcal{T}_A$ is a contraction mapping on $L^\infty(\mathcal{S} \times \mathcal{A})$. By the contraction mapping theorem, any initial-bounded Q-function would converge to a unique fixed point Q_A. $\qquad\square$

Lemma C.8. *Let π_1 and π_2 be two policies. If $\mathbb{E}_{a \sim \pi_1(s)}[Q^{\pi_2}(s,a)] \geq V^{\pi_2}(s)$ for all $s \in \mathcal{S}$, then $V^{\pi_1} \succeq V^{\pi_2}$.*

Proof. We define a sequence (Q_n) of bounded real-valued functions on $\mathcal{S} \times \mathcal{A}$ by the recurrence relation

$$
Q_n = \begin{cases} Q^{\pi_2} & \text{if } n = 0, \\ \mathcal{T}^{\pi_1} Q_{n-1} & \text{otherwise.} \end{cases}
$$

We first show that $Q_n \succeq Q^{\pi_2}$ by mathematical induction. The base case is trivial because $Q_0 \equiv Q^{\pi_2}$. Suppose $Q_{n-1} \succeq Q^{\pi_2}$. Then for each $s \in \mathcal{S}$ and $a \in \mathcal{A}$,

$$
\begin{aligned}
Q_n(s,a) &= (\mathcal{T}^{\pi_1} Q_{n-1})(s,a) \\
&= \mathbb{E}_{s' \sim P(s,a), r \sim R(s,a,s')} \left[r + \gamma \mathbb{E}_{a' \sim \pi_1(s')} [Q_{n-1}(s',a')] \right] \\
&\geq \mathbb{E}_{s' \sim P(s,a), r \sim R(s,a,s')} \left[r + \gamma \mathbb{E}_{a' \sim \pi_1(s')} [Q^{\pi_2}(s',a')] \right] \\
&\geq \mathbb{E}_{s' \sim P(s,a), r \sim R(s,a,s')} \left[r + \gamma \mathbb{E}_{a' \sim \pi_2(s')} [Q^{\pi_2}(s',a')] \right] \\
&= (\mathcal{T}^{\pi_2} Q^{\pi_2})(s,a) \\
&= Q^{\pi_2}(s,a).
\end{aligned}
$$

So $Q_n \succeq Q^{\pi_2}$. By mathematical induction, $Q_n \succeq Q^{\pi_2}$ for all n. For all $s \in \mathcal{S}$ and $a \in \mathcal{A}$,

$$Q^{\pi_1}(s,a) = \lim_{n \to \infty} Q_n(s,a) \geq Q^{\pi_2}(s,a).$$

Therefore, for all $s \in \mathcal{S}$,

$$V^{\pi_1}(s) = \mathbb{E}_{a \sim \pi_1(s)} [Q^{\pi_1}(s,a)] \geq \mathbb{E}_{a \sim \pi_1(s)} [Q^{\pi_2}(s,a)] \geq V^{\pi_2}(s),$$

that is, $V^{\pi_1} \succeq V^{\pi_2}$. $\qquad\square$

Theorem C.9. *Let $\{A_s\}_{s \in \mathcal{S}}$ be a family of subsets of $\mathcal{A}$, $\tilde{Q} \in L^\infty(\mathcal{S} \times \mathcal{A})$, and Q_A be a bounded real-valued function that satisfies the relation*

$$Q_A(s,a) = \begin{cases} (\mathcal{T}^* Q_A)(s,a) & \text{if } a \in A_s, \\ \tilde{Q}(s,a) & \text{otherwise,} \end{cases} \tag{15}$$

for all $s \in \mathcal{S}$ and $a \in \mathcal{A}$. Suppose there is a policy π such that for all $s \in \mathcal{S}$,

$$V^\pi(s) \geq \sup_{a \in \mathcal{A}} \tilde{Q}(s,a)$$

and

$$Q^\pi(s,a_s) \geq V^\pi(s)$$

for some $a_s \in A_s$. If there exists a deterministic policy $\pi_A^*\colon \mathcal{S} \to \mathcal{A}$ that is optimal under the constraint $\pi_A(s) \in A_s$ for all $s \in \mathcal{S}$, then

$$\pi_A^*(s) = \arg\max_{a \in \mathcal{A}} Q_A(s,a),$$

and

$$Q_A(s, \pi_A^*(s)) = V^{\pi_A^*}(s).$$

Proof. Define $\mathcal{T}_A$ as in Theorem C.7. We can see that there is a unique bounded real-valued function Q_A that satisfies Equation 15, because by Theorem C.7, $\mathcal{T}_A$ has unique fixed point Q_A.

We proceed to prove that for each $s \in \mathcal{S}$, $Q_A(s, \pi_A^*(s)) \geq V^{\pi_A^*}(s)$. Define a sequence (Q_n) of bounded real-valued functions on $\mathcal{S} \times \mathcal{A}$ by the recurrence relation

$$Q_n = \begin{cases} Q_0 & \text{if } n = 0, \\ \mathcal{T}_A Q_{n-1} & \text{otherwise,} \end{cases} \tag{16}$$

where $Q_0\colon \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ is defined as

$$Q_0(s,a) = \begin{cases} Q^{\pi_A^*}(s,a) & \text{if } a \in A_s, \\ \tilde{Q}(s,a) & \text{otherwise.} \end{cases}$$

When $n = 0$, for all $s \in \mathcal{S}$

$$Q_0(s, \pi_A^*(s)) = Q^{\pi_A^*}(s, \pi_A^*(s)) = V^{\pi_A^*}(s),$$

because $\pi_A^*(s) \in A_s$. Assume $Q_{n-1}(s, \pi_A^*(s)) \geq V^{\pi_A^*}(s)$ for all $s \in \mathcal{S}$. Then for all $s \in \mathcal{S}$,

$$\begin{aligned}
Q_n(s, \pi_A^*(s)) &= \mathbb{E}_{s' \sim P(s,\pi_A^*(s)), r \sim R(s,\pi_A^*(s),s')} \left[r + \gamma \sup_{a' \in \mathcal{A}} Q_{n-1}(s', a') \right] \\
&\geq \mathbb{E}_{s' \sim P(s,\pi_A^*(s)), r \sim R(s,\pi_A^*(s),s')} \left[r + \gamma Q_{n-1}(s', \pi_A^*(s')) \right] \\
&\geq \mathbb{E}_{s' \sim P(s,\pi_A^*(s)), r \sim R(s,\pi_A^*(s),s')} \left[r + \gamma V^{\pi_A^*}(s') \right] \\
&= \mathbb{E}_{s' \sim P(s,\pi_A^*(s)), r \sim R(s,\pi_A^*(s),s')} \left[r + \gamma \mathbb{E}_{a' \sim \pi_A^*(s')} \left[Q^{\pi_A^*}(s', a') \right] \right] \\
&= (\mathcal{T}^{\pi_A^*} Q^{\pi_A^*})(s, \pi_A^*(s)) \\
&= Q^{\pi_A^*}(s, \pi_A^*(s)) \\
&= V^{\pi_A^*}(s).
\end{aligned}$$

So by mathematical induction, $Q_n(s, \pi_A^*(s)) \geq V^{\pi_A^*}(s)$ for all $s \in \mathcal{S}$ and $n \geq 0$. Therefore,

$$Q_A(s, \pi_A^*(s)) = \lim_{n \to \infty} Q_n(s, \pi_A^*(s)) \geq V^{\pi_A^*}(s).$$

Since for all $s \in \mathcal{S}$ and $a \in A_s$,

$$Q_A(s, a) = (\mathcal{T}_A Q_A)(s, a) = \tilde{Q}(s, a) \leq V^\pi(s).$$

We can define a deterministic policy $\pi_A \colon \mathcal{S} \to \mathcal{A}$ that maps $s \in \mathcal{S}$ to a_s. Since $\pi_A(s) = a_s \in A_s$ for all $s \in \mathcal{S}$ and π_A^* is the optimal policy among the policies that satisfy this constraint, we have $V^{\pi_A^*} \succeq V^{\pi_A}$. So we may conclude that for all $s \in \mathcal{S}$,

$$\sup_{a \in \mathcal{A} \setminus A_s} Q_A(s, a) \leq V^\pi(s) \leq V^{\pi_A}(s) \leq V^{\pi_A^*}(s) = Q_A(s, \pi_A^*(s)). \tag{17}$$

We finish the proof by showing that for all $s \in \mathcal{S}$,

$$Q_A(s, \pi_A^*(s)) = \max_{a \in \mathcal{A}} Q_A(s, a).$$

Recall the sequence (Q_n) we previously defined by the recurrence relation (Equation 16). We will prove that for every n, $s \in \mathcal{S}$, and $a \in \mathcal{A}$,

$$Q_n(s, a) \leq V^{\pi_A^*}(s) = Q_n(s, \pi_A^*(s)).$$

Assume $n = 0$. Fix $s^\dagger \in \mathcal{S}$ and $a^\dagger \in \mathcal{A}$. If $a^\dagger \notin A_{s^\dagger}$, then by the observation we made in Equation 17,

$$Q_0(s^\dagger, a^\dagger) = \tilde{Q}(s^\dagger, a^\dagger) \leq V^{\pi_A^*}(s^\dagger).$$

If $a^\dagger \in A_{s^\dagger}$, consider a policy $\pi^\dagger \colon \mathcal{S} \to \mathcal{A}$ defined as

$$\pi^\dagger(s) = \begin{cases} a^\dagger & \text{if } s = s^\dagger, \\ \pi_A^*(s) & \text{otherwise.} \end{cases}$$

For all $s \in \mathcal{S}$, $\pi^\dagger(s) \in A_s$, so $V^{\pi_A^*} \succeq V^{\pi^\dagger}$. If $Q_0(s^\dagger, a^\dagger) < V^{\pi_A^*}(s^\dagger)$, it satisfies our hypothesis. Otherwise,

$$Q^{\pi_A^*}(s^\dagger, \pi^\dagger(s^\dagger)) = Q_0(s^\dagger, a^\dagger) \geq V^{\pi_A^*}(s^\dagger) = Q^{\pi_A^*}(s^\dagger, \pi_A^*(s^\dagger))$$

and for $s \neq s^\dagger$,

$$Q^{\pi_A^*}(s, \pi^\dagger(s)) = Q^{\pi_A^*}(s, \pi_A^*(s)),$$

so by Lemma C.8, $V^{\pi^\dagger} \succeq V^{\pi_A^*}$, which means $V^{\pi^\dagger} \equiv V^{\pi_A^*}$. Then

$$
\begin{aligned}
Q^{\pi_A^*}(s^\dagger, a^\dagger) &= (\mathcal{T}^{\pi_A^*} Q^{\pi_\beta^*})(s^\dagger, a^\dagger) \\
&= \mathbb{E}_{s' \sim P(s^\dagger, a^\dagger), r \sim R(s^\dagger, a^\dagger, s')} \left[r + \gamma Q^{\pi_A^*}(s', \pi_A^*(s')) \right] \\
&= \mathbb{E}_{s' \sim P(s^\dagger, a^\dagger), r \sim R(s^\dagger, a^\dagger, s')} \left[r + \gamma V^{\pi_A^*}(s') \right] \\
&= \mathbb{E}_{s' \sim P(s^\dagger, a^\dagger), r \sim R(s^\dagger, a^\dagger, s')} \left[r + \gamma V^{\pi^\dagger}(s') \right] \\
&= \mathbb{E}_{s' \sim P(s^\dagger, a^\dagger), r \sim R(s^\dagger, a^\dagger, s')} \left[r + \gamma Q^{\pi^\dagger}(s', \pi^\dagger(s')) \right] \\
&= (\mathcal{T}^{\pi^\dagger} Q^{\pi^\dagger})(s^\dagger, a^\dagger) \\
&= Q^{\pi^\dagger}(s^\dagger, \pi^\dagger(s^\dagger)) \\
&= V^{\pi^\dagger}(s^\dagger) \\
&= V^{\pi_A^*}(s^\dagger).
\end{aligned}
$$

So $Q_0(s^\dagger, a^\dagger) \leq V^{\pi_A^*}(s^\dagger)$ in both cases. Since it is obvious that

$$Q_0(s^\dagger, \pi_A^*(s^\dagger)) = Q^{\pi_A^*}(s^\dagger, \pi_A^*(s^\dagger)) = V^{\pi_A^*}(s^\dagger),$$

our hypothesis holds for $n = 0$.

Assume the hypothesis holds for $n - 1$. Fix $s^\dagger \in \mathcal{S}$ and $a^\dagger \in \mathcal{A}$. If $a^\dagger \notin A_{s^\dagger}$,

$$Q_n(s^\dagger, a^\dagger) = (\mathcal{T}_\beta^* Q_{n-1})(s^\dagger, a^\dagger) = Q_\beta^{\mathrm{LB}}(s^\dagger, a^\dagger) \leq V^{\pi_\beta^*}(s^\dagger)$$

by Equation 17. Otherwise,

$$
\begin{aligned}
Q_n(s^\dagger, a^\dagger) &= (\mathcal{T}_A Q_{n-1})(s^\dagger, a^\dagger) \\
&= (\mathcal{T}^* Q_{n-1})(s^\dagger, a^\dagger) \\
&= \mathbb{E}_{s' \sim P(s^\dagger, a^\dagger), r \sim R(s^\dagger, a^\dagger, s')} \left[r + \gamma \sup_{a' \in \mathcal{A}} Q_{n-1}(s', a') \right] \\
&= \mathbb{E}_{s' \sim P(s^\dagger, a^\dagger), r \sim R(s^\dagger, s^\dagger, s')} \left[r + \gamma \max_{a' \in \mathcal{A}} Q_{n-1}(s', a') \right] \\
&= \mathbb{E}_{s' \sim P(s^\dagger, a^\dagger), r \sim R(s^\dagger, s^\dagger, s')} \left[r + \gamma V^{\pi_A^*}(s') \right] \\
&= \mathbb{E}_{s' \sim P(s^\dagger, a^\dagger), r \sim R(s^\dagger, s^\dagger, s')} \left[r + \gamma \mathbb{E}_{a' \sim \pi_A^*(s')} \left[Q^{\pi_A^*}(s', a') \right] \right] \\
&= (\mathcal{T}^{\pi_A^*} Q^{\pi_A^*})(s^\dagger, a^\dagger) \\
&= Q^{\pi_A^*}(s^\dagger, a^\dagger) \\
&= Q_0(s^\dagger, a^\dagger) \\
&\leq V^{\pi_A^*}(s^\dagger).
\end{aligned}
$$

When $a^\dagger = \pi_A^*(s^\dagger)$, the inequality becomes equality. So by mathematical induction, for every n, $s \in \mathcal{S}$, and $a \in \mathcal{A}$,

$$Q_n(s, a) \leq V^{\pi_A^*}(s) = Q_n(s, \pi_A^*(s)).$$

Sending n to infinity, we can see that for all $s \in \mathcal{S}$ and $a \in \mathcal{A}$,

$$Q_A(s, a) = \lim_{n \to \infty} Q_n(s, a) \leq V^{\pi_A^*}(s) = \lim_{n \to \infty} Q_n(s, \pi_A^*(s)) = Q_A(s, \pi_A^*(s)).$$

Therefore,

$$Q_A(s, \pi_A^*(s)) = \max_{a \in \mathcal{A}} Q_A(s, a).$$

$\square$

Theorem C.10. *Any initial bounded real-valued function on $\mathcal{S} \times \mathcal{A}$ can converge to a unique fixed point Q_β^* by repeatedly applying $\mathcal{T}_\beta^*$. Suppose for each $s \in \mathcal{S}$,*

$$Q^\beta(s, a_s) \geq \mathbb{E}_{a \sim \beta(s)} \left[Q^\beta(s, a) \right]$$

for some $a_s \in \mathcal{A} \setminus \mathrm{OOD}(s)$. If there exists a deterministic policy $\pi_\beta^* \colon \mathcal{S} \to \mathcal{A}$ that is optimal under the constraint $\pi(s) \notin \mathrm{OOD}(s)$ for all $s \in \mathcal{S}$, then for all $s \in \mathcal{S}$,

$$\pi_\beta^*(s) = \arg\max_{a \in \mathcal{A}} Q_\beta^*(s, a).$$

Proof. First observe that for all $s \in \mathcal{S}$ and $a \in \mathcal{A}$,

$$Q_\beta^{\mathrm{LB}}(s, a) \geq \frac{r_{\min}}{1 - \gamma},$$

and

$$Q_\beta^{\mathrm{LB}}(s, a) \leq V^\beta(s) - r_{\max} + r_{\min} \leq \frac{r_{\max}}{1 - \gamma} - r_{\max} + r_{\min},$$

by Lemma C.5. This implies $Q_\beta^{\mathrm{LB}} \in L^\infty(\mathcal{S} \times \mathcal{A})$. Since $\tilde{Q} = Q_\beta^{\mathrm{LB}}$ and $A_s = \mathcal{A} \setminus \mathrm{OOD}(s)$ satisfies the conditions of Theorem C.7, any initially bounded real-valued function on $\mathcal{S} \times \mathcal{A}$ converges to a unique fixed point, which we denote by Q_β^*, through repeated application of $\mathcal{T}_A$, which is in fact, $\mathcal{T}_\beta^*$.

For all $s \in \mathcal{S}$,

$$Q_\beta^{\mathrm{LB}}(s,a) \leq V^\beta(s) - r_{\max} + r_{\min} \leq V^\beta(s),$$

which means

$$\sup_{a \in \mathcal{A}} Q_\beta^{\mathrm{LB}}(s,a) \leq V^\beta(s) = \mathbb{E}_{a \sim \beta(s)}\left[Q^\beta(s,a)\right] < \sup_{a \in \mathcal{A} \backslash \mathrm{OOD}(s)} Q^\beta(s,a).$$

Now we can see that the second part of the theorem is a special case of Theorem C.9, where $A_s = \mathcal{A}\backslash\mathrm{OOD}(s)$, $\tilde{Q} = Q_\beta^{\mathrm{LB}}$, $Q_A = Q_\beta^*$, $\pi = \beta$, and $\pi_A^* = \pi_\beta^*$. $\qquad\square$

Lemma C.11. *Let* $\Pi = \{\pi_0, \pi_1, \pi_2, \ldots, \pi_{N-1}\}$ *be a finite set of policies. If* π^* *is a policy such that for each* $s \in \mathcal{S}$, *there is* $i \in [N]$ *such that* $\pi^*(s) = \pi_i(s)$ *and* $V^{\pi_i}(s) = \max_{\pi \in \Pi} V^\pi(s)$, *then* $V^{\pi^*} \succeq V^\pi$ *for every* $\pi \in \Pi$.

Proof. Define a sequence (Q_n) of bounded real-valued functions by the recurrence relation

$$Q_n = \begin{cases} \max_{\pi \in \Pi} Q^\pi & \text{if } n = 0, \\ \mathcal{T}^{\pi^*} Q_{n-1}, & \text{otherwise.} \end{cases}$$

We want to show that $Q_n \succeq \max_{\pi \in \Pi} Q^\pi$ for all $n \geq 0$. The base case is trivial. Assume $Q_{n-1} \succeq \max_{\pi \in \Pi} Q^\pi$. For each $s \in \mathcal{S}$, there is $i \in [N]$ such that $\pi^*(s) = \pi_i(s)$ and $V^{\pi_i}(s) = \max_{\pi \in \Pi} V^\pi(s)$, which implies

$$\mathbb{E}_{a \sim \pi^*(s)}\left[Q_{n-1}(s,a)\right] \geq \mathbb{E}_{a \sim \pi_i(s)}\left[Q^{\pi_i}(s)\right] = V^{\pi_i}(s) = \max_{\pi \in \Pi} V^\pi(s).$$

Now for all $s \in \mathcal{S}$ and $a \in \mathcal{A}$,

$$\begin{aligned}
Q_n(s,a) &= (\mathcal{T}^{\pi^*} Q_{n-1})(s,a) \\
&= \mathbb{E}_{s' \sim P(s,a), r \sim R(s,a,s')}\left[r + \gamma \mathbb{E}_{a' \sim \pi^*(s')}\left[Q_{n-1}(s',a')\right]\right] \\
&\geq \mathbb{E}_{s' \sim P(s,a), r \sim R(s,a,s')}\left[r + \gamma \max_{\pi \in \Pi} V^\pi(s')\right] \\
&= \max_{\pi \in \Pi} \mathbb{E}_{s' \sim P(s,a), r \sim R(s,a,s')}\left[r + \gamma \mathbb{E}_{a' \sim \pi(s')}\left[Q^\pi(s',a')\right]\right] \\
&= \max_{\pi \in \Pi}(\mathcal{T}^\pi Q^\pi)(s,a) \\
&= \max_{\pi \in \Pi} Q^\pi(s,a).
\end{aligned}$$

By mathematical induction, $Q_n \succeq \max_{\pi \in \Pi} Q^\pi$ for all $n \geq 0$. Therefore,

$$Q^{\pi^*}(s,a) = \lim_{n \to \infty} Q_n(s,a) \geq \max_{\pi \in \Pi} Q^\pi(s,a)$$

for all $s \in \mathcal{S}$ and $a \in \mathcal{A}$.

Fix $s \in \mathcal{S}$. There is $i \in [N]$ such that $\pi^*(s) = \pi_i(s)$ and $V^{\pi_i}(s) = \max_{\pi \in \Pi} V^\pi(s)$. Then

$$V^{\pi^*}(s) = \mathbb{E}_{a \sim \pi^*(s)}\left[Q^{\pi^*}(s,a)\right] \geq \mathbb{E}_{a \sim \pi_i(s)}\left[Q^{\pi_i}(s,a)\right] = V^{\pi_i}(s) = \max_{\pi \in \Pi} V^\pi(s).$$

Our choice of s was arbitrary, so $V^{\pi^*} \succeq \max_{\pi \in \Pi} V^\pi$. $\qquad\square$

Theorem C.12. *Any initial bounded real-valued function on* $\mathcal{S} \times \mathcal{A}$ *can converge to a unique fixed point* $Q_\mathcal{B}^*$ *by repeatedly applying* $\mathcal{T}_\mathcal{B}^*$. *Suppose for each* $\beta \in \mathcal{B}$ *and* $s \in \mathcal{S}$,

$$Q^\beta(s, a_s^\beta) \geq \mathbb{E}_{a \sim \beta(s)}\left[Q^\beta(s,a)\right]$$

for some $a_s^\beta \in \mathcal{A} \setminus \mathrm{OOD}(s)$. *If there exists a deterministic policy* $\pi_\mathcal{B}^*\colon \mathcal{S} \to \mathcal{A}$ *that is optimal under the constraint* $\pi(s) \notin \mathrm{OOD}(s)$ *for all* $s \in \mathcal{S}$, *then for all* $s \in \mathcal{S}$,

$$\pi_\mathcal{B}^*(s) = \arg\max_{a \in \mathcal{A}} Q_\mathcal{B}^*(s,a).$$

Proof. First observe that for all $s \in \mathcal{S}$, $a \in \mathcal{A}$, and $\beta \in \mathcal{B}$,

$$Q_\beta^{\mathrm{LB}}(s, a) \geq \frac{r_{\min}}{1 - \gamma},$$

and

$$Q_\beta^{\mathrm{LB}}(s, a) \leq V^\beta(s) - r_{\max} + r_{\min} \leq \frac{r_{\max}}{1 - \gamma} - r_{\max} + r_{\min},$$

by Lemma C.5. So obviously,

$$Q_\mathcal{B}^{\mathrm{LB}}(s, a) = \max_{\beta \in \mathcal{B}} Q_\beta^{\mathrm{LB}}(s, a) \geq \frac{r_{\min}}{1 - \gamma},$$

and

$$Q_\mathcal{B}^{\mathrm{LB}}(s, a) = \max_{\beta \in \mathcal{B}} Q_\beta^{\mathrm{LB}}(s, a) \leq \frac{r_{\max}}{1 - \gamma} - r_{\max} + r_{\min},$$

for all $s \in \mathcal{S}$ and $\mathcal{A}$. This implies $Q_\mathcal{B}^{\mathrm{LB}} \in L^\infty(\mathcal{S} \times \mathcal{A})$. Since $\tilde{Q} = Q_\mathcal{B}^{\mathrm{LB}}$ and $A_s = \mathcal{A} \setminus \mathrm{OOD}(s)$ satisfies the conditions of Lemma C.7, any initially bounded real-valued function on $\mathcal{S} \times \mathcal{A}$ converges to a unique fixed point, which we denote by $Q_\mathcal{B}^*$, through repeated application of $\mathcal{T}_A$, which is in fact, $\mathcal{T}_\mathcal{B}^*$.

For each $\beta \in \mathcal{B}$ define a deterministic policy $\beta' \colon \mathcal{S} \to \mathcal{A}$ so that $\beta'(s) = a_s^\beta$ for each $s \in \mathcal{S}$. Then

$$Q^\beta(s, \beta'(s)) = Q^\beta(s, a_s^\beta) \geq \mathbb{E}_{a \sim \beta(s)} \left[Q^\beta(s, a) \right]$$

for all $s \in \mathcal{S}$, so $V^{\beta'} \succeq V^\beta$ by Lemma C.8. We will denote the set $\{ \beta' : \beta \in \mathcal{B} \}$ by $\mathcal{B}'$. Consider a policy $\beta^* \colon \mathcal{S} \to \mathcal{A}$ defined as

$$\beta^*(s) = \left(\arg\max_{\beta' \in \mathcal{B}'} V^{\beta'}(s) \right)(s),$$

that is, for each state, we follow the β' with the highest value. Obviously, $\beta^*(s) \in \mathcal{A} \setminus \mathrm{OOD}(s)$ for all $s \in \mathcal{S}$, and by Lemma C.11, for all $s \in \mathcal{S}$, $a \in \mathcal{A}$, and $\beta \in \mathcal{B}$,

$$Q_\beta^{\mathrm{LB}}(s, a) \leq V^\beta(s) - r_{\max} + r_{\min} \leq V^\beta(s) \leq V^{\beta'}(s) \leq V^{\beta^*}(s),$$

which means

$$V^{\beta^*}(s) \geq \sup_{a \in \mathcal{A}} \max_{\beta \in \mathcal{B}} Q_\beta^{\mathrm{LB}}(s, a) = \sup_{a \in \mathcal{A}} Q_\mathcal{B}^{\mathrm{LB}}(s, a).$$

Now we can see that the second part of the theorem is a special case of Theorem C.9, where $A_s = \mathcal{A} \setminus \mathrm{OOD}(s)$, $\tilde{Q} = Q_\mathcal{B}^{\mathrm{LB}}$, $Q_A = Q_\mathcal{B}^*$, $\pi = \beta^*$, and $\pi_A^* = \pi_\mathcal{B}^*$. $\qquad\square$

Remark C.13. By Theorem C.9, $Q_\mathcal{B}^*(s, \pi_\mathcal{B}^*(s)) = V^{\pi_\mathcal{B}^*}(s)$.

Proposition C.14. *Let* $\mathbf{X}$ *be a non-degenerate multivariate Gaussian random vector with mean* $\boldsymbol{\mu} \in \mathbb{R}^d$ *and a diagonal covariance matrix* $\mathrm{diag}(\boldsymbol{\sigma})^2 \in \mathbb{R}^{d \times d}$. *For* $\mathbf{y} \in \mathbb{R}^d$,

$$\mathbb{E}\left[\|\mathbf{X} - \mathbf{y}\|_1\right] = \sum_{i=1}^d \left[(y_i - \mu_i) \operatorname{erf}\left(\frac{y_i - \mu_i}{\sigma_i \sqrt{2}} \right) + \sqrt{\frac{2}{\pi}} \sigma_i \exp\left(-\frac{(y_i - \mu_i)^2}{2\sigma_i^2} \right). \right]$$

Proof. Let $\mathbf{X} = (X_1, X_2, \ldots, X_d)$, $\mathbf{y} = (y_1, y_2, \ldots, y_d)$, $\boldsymbol{\mu} = (\mu_1, \mu_2, \ldots, \mu_d)$, and $\boldsymbol{\sigma} = (\sigma_1, \sigma_2, \ldots, \sigma_d)$. We may assume that $\sigma_1, \sigma_2, \ldots, \sigma_d > 0$. Then

$$\mathbb{E}\left[\|\mathbf{X} - \mathbf{y}\|_1\right] = \mathbb{E}\left[\sum_{i=1}^d |X_i - y_i| \right] = \sum_{i=1}^d \mathbb{E}\left[|X_i - y_i| \right].$$

Define $g_i(y) = \mathbb{E}\left[|X_i - y| \right]$.

$$g_i'(y) = \mathbb{E}\left[\frac{\mathrm{d}}{\mathrm{d}y} |X_i - y| \right] = \mathbb{E}[\mathbf{1}_{X_i < y} - \mathbf{1}_{X_i > y}] = F_{X_i}(y) - (1 - F_{X_i}(y)) = 2F_{X_i}(y) - 1,$$

where F_{X_i} is the cumulative distribution function of X_i. So

$$g_i'(y) = \mathrm{erf}\left(\frac{y - \mu_i}{\sigma_i \sqrt{2}}\right).$$

Observe that

$$g_i(\mu_i) = \mathbb{E}\left[|X_i - \mu_i|\right]$$
$$= \frac{1}{\sqrt{2\pi}\sigma_i} \int_{\mu_i}^{\infty} (x_i - \mu_i) \exp\left(-\frac{(x_i - \mu_i)^2}{2\sigma_i^2}\right) \mathrm{d}x_i - \frac{1}{\sqrt{2\pi}\sigma_i} \int_{-\infty}^{\mu_i} (x_i - \mu_i) \exp\left(-\frac{(x_i - \mu_i)^2}{2\sigma_i^2}\right) \mathrm{d}x_i.$$

Substituting $u_i = (x_i - \mu_i)/\sigma_i$,

$$g_i(\mu_i) = \frac{1}{\sqrt{2\pi}\sigma_i} \left[\int_0^{\infty} \sigma_i u_i e^{-\frac{1}{2}u_i^2} \sigma_i \ \mathrm{d}u_i - \int_{-\infty}^0 \sigma_i u_i e^{-\frac{1}{2}u_i^2} \sigma_i \ \mathrm{d}u_i\right]$$
$$= \frac{\sigma_i}{\sqrt{2\pi}} \left[\int_0^{\infty} u_i e^{-\frac{1}{2}u_i^2} \ \mathrm{d}u_i - \int_{-\infty}^0 u_i e^{-\frac{1}{2}u_i^2} \ \mathrm{d}u_i\right]$$
$$= \sqrt{\frac{2}{\pi}}\sigma_i.$$

By the fundamental theorem of calculus,

$$g_i(y) = g_i(\mu_i) + \int_{\mu_i}^y g_i'(v) \ \mathrm{d}v = \sqrt{\frac{2}{\pi}}\sigma_i + \int_{\mu_i}^y \mathrm{erf}\left(\frac{v - \mu_i}{\sigma_i \sqrt{2}}\right) \mathrm{d}v.$$

Substituting $z = (v - \mu_i)/(\sigma_i \sqrt{2})$,

$$\int_{\mu_i}^y \mathrm{erf}\left(\frac{v - \mu_i}{\sigma_i \sqrt{2}}\right) \mathrm{d}v = \int_0^{(y - \mu_i)/(\sigma_i \sqrt{2})} \mathrm{erf}(z)\sigma_i \sqrt{2} \ \mathrm{d}z$$
$$= \sqrt{2}\sigma_i \left[\left(\frac{y - \mu_i}{\sigma_i \sqrt{2}}\right) \mathrm{erf}\left(\frac{y - \mu_i}{\sigma_i \sqrt{2}}\right) + \frac{1}{\sqrt{\pi}} \exp\left(-\frac{(y - \mu_i)^2}{2\sigma_i^2}\right) - \frac{1}{\sqrt{\pi}}\right].$$

Therefore,

$$g_i(y) = (y - \mu_i) \mathrm{erf}\left(\frac{y - \mu_i}{\sigma_i \sqrt{2}}\right) + \sqrt{\frac{2}{\pi}}\sigma_i \exp\left(-\frac{(y - \mu_i)^2}{2\sigma_i^2}\right),$$

which implies

$$\mathbb{E}\left[\|\mathbf{X} - \mathbf{y}\|_1\right] = \sum_{i=1}^d g_i(y_i) = \sum_{i=1}^d \left[(y_i - \mu_i) \mathrm{erf}\left(\frac{y_i - \mu_i}{\sigma_i \sqrt{2}}\right) + \sqrt{\frac{2}{\pi}}\sigma_i \exp\left(-\frac{(y_i - \mu_i)^2}{2\sigma_i^2}\right).\right]$$

$\square$

Proposition C.15. *Let* $\mathbf{Q}\colon \mathcal{S} \times \mathcal{A} \to \mathbb{R}^K$ *be a function and* $\mathcal{T}_{\mathcal{B}}^*$ *be an operator on the space of* $\mathbb{R}^K$*-valued functions on* $\mathcal{S} \times \mathcal{A}$ *defined by the equation*

$$(\mathcal{T}_{\mathcal{B}}^* \mathbf{Q})_i(s, a) = \begin{cases} (\mathcal{T}^* \max_{j \in \{1,2,\ldots,K\}} Q_j)(s, a) & \text{if } a \in \mathcal{R}_{\beta_i}(p_\alpha; s) \\ Q_{\beta_i}^{\mathrm{LB}}(s, a) & \text{otherwise.} \end{cases}$$

Then for any initial bounded $\mathbb{R}^K$*-valued function on* $\mathcal{S} \times \mathcal{A}$ *converges to a unique fixed point* $\mathbf{Q}_{\mathcal{B}}^*$ *by repeatedly applying* $\mathcal{T}_{\mathcal{B}}^*$. *Suppose for each* $\beta \in \mathcal{B}$ *and* $s \in \mathcal{S}$,

$$Q^\beta(s, a_s^\beta) \geq \mathbb{E}_{a \sim \beta(s)}\left[Q^\beta(s, a)\right]$$

for some $a_s^\beta \in \mathcal{R}_\beta(p_\alpha; s)$. *If there exists a deterministic policy* $\pi_{\mathcal{B}}^*\colon \mathcal{S} \to \mathcal{A}$ *that is optimal under the constraint* $\pi(s) \notin \mathrm{OOD}(s)$ *for all* $s \in \mathcal{S}$, *then for all* $s \in \mathcal{S}$,

$$\pi_{\mathcal{B}}^*(s) = \arg\max_{a \in \mathcal{A}} \max_{i \in \{1,2,\ldots,K\}} (\mathbf{Q}_{\mathcal{B}}^*)_i(s, a).$$

Proof. Let X be a class of bounded $\mathbb{R}^K$-valued functions on $\mathcal{S} \times \mathcal{A}$. We may endow X with a norm $\|\cdot\|_\infty$ defined as

$$\|\mathbf{Q}\|_\infty = \max_{j \in \{1,2,\ldots,K\}} \sup_{(s,a) \in \mathcal{S} \times \mathcal{A}} |Q_j(s,a)|.$$

Now we will prove that the restriction of $\mathcal{T}_\mathcal{B}^*$ onto X is an operator on X. Fix $s \in \mathcal{S}$, $a \in \mathcal{A}$, $i \in \{1,2,\ldots,K\}$, and $\mathbf{Q} \in X$. If $a \in \mathcal{R}_{\beta_i}(p_\alpha; s)$, by Inequality 14 from the proof of Theorem C.7,

$$|(\mathcal{T}_\mathcal{B}^* \mathbf{Q})_i(s,a)| = \left| (\mathcal{T}^* \max_{j \in \{1,2,\ldots,K\}} Q_j)(s,a) \right|$$

$$\leq \max\{|r_{\max}|, |r_{\min}|\} + \gamma \sup_{(s',a') \in \mathcal{S} \times \mathcal{A}} \left| \max_{j \in \{1,2,\ldots,K\}} Q_j(s',a') \right|$$

$$\leq \max\{|r_{\max}|, |r_{\min}|\} + \gamma \sup_{(s',a') \in \mathcal{S} \times \mathcal{A}} \max_{j \in \{1,2,\ldots,K\}} |Q_j(s',a')|$$

$$= \max\{|r_{\max}|, |r_{\min}|\} + \gamma \|\mathbf{Q}\|_\infty.$$

Otherwise,

$$|(\mathcal{T}_\mathcal{B}^* \mathbf{Q})_i(s,a)| = |Q_{\beta_i}^{\mathrm{LB}}(s,a)|$$

In the proof of Theorem C.10, we have already showed that Q_β^{LB} is bounded, which implies

$$|(\mathcal{T}_\mathcal{B}^* \mathbf{Q})_i(s,a)| = |Q_{\beta_i}^{\mathrm{LB}}(s,a)| \leq \max_{j \in \{1,2,\ldots,K\}} \|Q_{\beta_j}^{\mathrm{LB}}(s,a)\|_\infty.$$

Therefore, $\mathcal{T}_\mathcal{B}^* \mathbf{Q}$ is bounded.

Next, we will show that $\mathbf{T}_\mathcal{B}^*$ is a contraction mapping on X. Let $\mathbf{Q}_1, \mathbf{Q}_2 \in X$, $i \in \{1,2,\ldots,K\}$, and $(s,a) \in \mathcal{S} \times \mathcal{A}$. If $a \in \mathcal{R}_{\beta_i}(p_\alpha; s)$,

$$|(\mathcal{T}_\mathcal{B}^* \mathbf{Q}_1)_i(s,a) - (\mathcal{T}_\mathcal{B}^* \mathbf{Q}_2)_i(s,a)| = \left| \mathcal{T}^* \max_{j \in \{1,2,\ldots,K\}} (\mathbf{Q}_1(s,a))_j - \mathcal{T}^* \max_{j \in \{1,2,\ldots,K\}} (\mathbf{Q}_2(s,a))_j \right|$$

$$\leq \gamma \left| \max_{j \in \{1,2,\ldots,K\}} (\mathbf{Q}_1(s,a))_j - \max_{j \in \{1,2,\ldots,K\}} (\mathbf{Q}_2(s,a))_j \right|$$

$$\leq \gamma \max_{j \in \{1,2,\ldots,K\}} |(\mathbf{Q}_1(s,a))_j - (\mathbf{Q}_2(s,a))_j|$$

$$\leq \gamma \|\mathbf{Q}_1 - \mathbf{Q}_2\|_\infty.$$

Otherwise,

$$(\mathcal{T}_\mathcal{B}^* \mathbf{Q}_1)(s,a) - (\mathcal{T}_\mathcal{B}^* \mathbf{Q}_2)(s,a) = Q_{\beta_i}^{\mathrm{LB}}(s,a) - Q_{\beta_i}^{\mathrm{LB}}(s,a) = 0 \leq \gamma \|\mathbf{Q}_1 - \mathbf{Q}_2\|_\infty.$$

Therefore,

$$\|\mathcal{T}_\mathcal{B}^* \mathbf{Q}_1 - \mathcal{T}_\mathcal{B}^* \mathbf{Q}_2\|_\infty = \max_{j \in \{1,2,\ldots,K\}} |(\mathcal{T}_\mathcal{B}^* \mathbf{Q}_1)_i(s,a) - (\mathcal{T}_\mathcal{B}^* \mathbf{Q}_2)_i(s,a)| \leq \gamma \|\mathbf{Q}_1 - \mathbf{Q}_2\|_\infty,$$

that is, $\mathcal{T}_\mathcal{B}^*$ is a contraction on X.

Define $\mathbf{Q} = (Q_1, Q_2, \ldots, Q_K) \in X$ by the equation

$$Q_i(s,a) = \begin{cases} Q_\mathcal{B}^*(s,a) & \text{if } a \in \mathcal{R}_{\beta_i}(p_\alpha; s) \\ Q_{\beta_i}^{\mathrm{LB}}(s,a) & \text{otherwise.} \end{cases}$$

Fix $i \in \{1,2,\ldots,K\}$, $s \in \mathcal{S}$, and $a \in \mathcal{A}$. If $a \in \mathcal{R}_{\beta_i}(p_\alpha; s)$,

$$(\mathcal{T}_\mathcal{B}^* \mathbf{Q})_i(s,a) = (\mathcal{T}^* \max_{j \in \{1,2,\ldots,K\}} Q_j)(s,a)$$

$$= \mathbb{E}_{s' \sim P(s,a), r \sim R(s,a,s')} \left[r + \gamma \sup_{a' \in \mathcal{A}} \max_{j \in \{1,2,\ldots,K\}} Q_j(s',a') \right]$$

$$= \mathbb{E}_{s' \sim P(s,a), r \sim R(s,a,s')} \left[r + \gamma \max_{j \in \{1,2,\ldots,K\}} \sup_{a' \in \mathcal{A}} Q_j(s',a') \right].$$

By Theorem C.12,

$$\pi_{\mathcal{B}}^*(s') = \arg\max_{a'\in\mathcal{A}} Q_{\mathcal{B}}^*(s',a'),$$

so

$$\sup_{a'\in\mathcal{A}} Q_j(s',a') = \max\left\{Q_{\mathcal{B}}^*(s',\pi_{\mathcal{B}}^*(s')), \sup_{a''\in\mathcal{A}\setminus\mathcal{R}_{\beta_j}(p_\alpha;s)} Q_{\beta_j}^{\mathrm{LB}}(s',a'')\right\}.$$

By Lemma C.8, Remark C.13, and the definition of $Q_{\beta_j}^{\mathrm{LB}}$,

$$Q_{\beta_j}^{\mathrm{LB}}(s',a'') \leq V^{\beta_j}(s') \leq V^{\beta_j^\dagger}(s') \leq V^{\pi_{\mathcal{B}}^*}(s') = Q_{\mathcal{B}}^*(s',\pi_{\mathcal{B}}^*(s')),$$

for all $a'' \in \mathcal{A} \setminus \mathcal{R}_{\beta_j}(p_\alpha;s')$, where $\beta_j^\dagger\colon \mathcal{S}\to\mathcal{A}$ is the deterministic policy $s^\dagger \mapsto a_{s^\dagger}^{\beta_j}$. So

$$\sup_{a'\in\mathcal{A}} Q_j(s',a') = Q_{\mathcal{B}}^*(s',\pi_{\mathcal{B}}^*(s')).$$

Since $a \in \mathcal{R}_{\beta_i}(p_\alpha;s) \subseteq \mathcal{A}\setminus\mathrm{OOD}(s)$, this implies

$$
\begin{aligned}
(\mathcal{T}_{\mathcal{B}}^*\mathbf{Q})_i(s,a) &= \mathbb{E}_{s'\sim P(s,a),r\sim R(s,a,s')}\left[r + \gamma \max_{j\in\{1,2,\dots,K\}} Q_{\mathcal{B}}^*(s',\pi_{\mathcal{B}}^*(s'))\right]\\
&= \mathbb{E}_{s'\sim P(s,a),r\sim R(s,a,s')}\left[r + \gamma Q_{\mathcal{B}}^*(s',\pi_{\mathcal{B}}^*(s'))\right]\\
&= \mathbb{E}_{s'\sim P(s,a),r\sim R(s,a,s')}\left[r + \gamma \sup_{a'\in\mathcal{A}} Q_{\mathcal{B}}^*(s',a')\right]\\
&= (\mathcal{T}^* Q_{\mathcal{B}}^*)(s,a)\\
&= (\mathcal{T}_{\mathcal{B}}^* Q_{\mathcal{B}}^*)(s,a)\\
&= Q_{\mathcal{B}}^*(s,a)\\
&= Q_i(s,a).
\end{aligned}
$$

Otherwise,

$$(\mathcal{T}_{\mathcal{B}}^*\mathbf{Q})_i(s,a) = Q_{\beta_i}^{\mathrm{LB}}(s,a) = Q_i(s,a).$$

Therefore, $\mathbf{Q} \equiv \mathbf{Q}_{\mathcal{B}}^*$.

We have already showed that for all $i \in \{1,2,\dots,K\}$,

$$\sup_{a\in\mathcal{A}} Q_i(s,a) = Q_{\mathcal{B}}^*(s,\pi_{\mathcal{B}}^*(s)).$$

Therefore,

$$\sup_{a\in\mathcal{A}} \max_{i\in\{1,2,\dots,K\}} (\mathbf{Q}_{\mathcal{B}}^*)_i(s,a) = \max_{i\in\{1,2,\dots,K\}} \sup_{a\in\mathcal{A}} Q_i(s,a) = Q_{\mathcal{B}}^*(s,\pi_{\mathcal{B}}^*(s)) = (\mathbf{Q}_{\mathcal{B}}^*)_1(s,\pi_{\mathcal{B}}^*(s)),$$

that is,

$$\pi_{\mathcal{B}}^*(s) = \arg\max_{a\in\mathcal{A}} \max_{i\in\{1,2,\dots,K\}} (\mathbf{Q}_{\mathcal{B}}^*)_i(s,a).$$

$\square$

D   Experiment Details

D.1   Additional Analysis on the Trajectory Clustering Algorithm

Aside from the three random-medium-expert datasets mentioned in Section 4.1, we also created custom D4RL datasets by concatenating medium and expert datasets of halfcheetah, hopper, and walker2d tasks. The mean and standard deviation of ARIs and NMIs for each configuration over 5 different seeds are reported in Table 6. The configuration $(\lambda_T, \lambda_R) = (1, 0)$ performs the best on average even after we include the three medium-expert datasets.

Table 6: The impact of hyperparameters λ_T and λ_R on the performance of our trajectory clustering algorithm evaluated on custom D4RL datasets. The performance is measured in terms of adjusted rand index (ARI) and normalised mutual information score (NMI).

		$\lambda_T = 1$		$\lambda_T = 0$	
		$\lambda_R = 1$	$\lambda_R = 0$	$\lambda_R = 1$	$\lambda_R = 0$
halfcheetah-medium-expert					
	ARI	1.00 ± 0.00	1.00 ± 0.00	1.00 ± 0.00	1.00 ± 0.00
	NMI	1.00 ± 0.00	0.99 ± 0.01	1.00 ± 0.00	1.00 ± 0.00
halfcheetah-random-medium-expert					
	ARI	0.97 ± 0.04	0.99 ± 0.00	0.91 ± 0.19	0.91 ± 0.17
	NMI	0.97 ± 0.03	0.97 ± 0.01	0.93 ± 0.12	0.92 ± 0.12
hopper-medium-expert					
	ARI	0.80 ± 0.44	1.00 ± 0.00	0.99 ± 0.01	1.00 ± 0.00
	NMI	0.80 ± 0.42	1.00 ± 0.00	0.97 ± 0.03	1.00 ± 0.00
hopper-random-medium-expert					
	ARI	0.49 ± 0.29	0.98 ± 0.02	0.59 ± 0.33	0.97 ± 0.06
	NMI	0.57 ± 0.26	0.97 ± 0.02	0.66 ± 0.29	0.98 ± 0.04
walker2d-medium-expert					
	ARI	0.99 ± 0.01	1.00 ± 0.00	0.99 ± 0.02	1.00 ± 0.00
	NMI	0.99 ± 0.02	1.00 ± 0.01	0.98 ± 0.04	1.00 ± 0.00
walker2d-random-medium-expert					
	ARI	0.88 ± 0.16	0.98 ± 0.05	0.98 ± 0.03	1.00 ± 0.00
	NMI	0.90 ± 0.11	0.98 ± 0.03	0.97 ± 0.04	1.00 ± 0.00
Average	ARI	0.86 ± 0.27	0.99 ± 0.02	0.91 ± 0.21	0.98 ± 0.07
	NMI	0.87 ± 0.24	0.98 ± 0.02	0.92 ± 0.17	0.98 ± 0.06

E   Additional Figures

Figure 5: A diagram showing the probability density function and the $100(1 - \alpha)\%$ highest density region of a normal distribution. The probability of the corresponding normal random variable to lie inside $\mathcal{R}(f_\alpha)$, which corresponds to the area of the coloured region, is $1 - \alpha$.

Figure 6: VariBAD architecture. This figure is a redrawn version of Figure 2 in Zintgraf et al. (2021).