Towards Achieving Adversarial Robustness Beyond Perceptual Limits

Abstract

The vulnerability of Deep Neural Networks to Adversarial Attacks has fuelled research towards building robust models. While most existing Adversarial Training algorithms aim towards defending against imperceptible attacks, real-world adversaries are not limited by such constraints. In this work, we aim to achieve adversarial robustness at larger epsilon bounds. We first discuss the ideal goals of an adversarial defense algorithm beyond perceptual limits, and further highlight the shortcomings of naively extending existing training algorithms to higher perturbation bounds. In order to overcome these shortcomings, we propose a novel defense, Oracle-Aligned Adversarial Training (OA-AT), that attempts to align the predictions of the network with that of an Oracle during adversarial training. The proposed approach achieves significantly improved results at large epsilon bounds (ℓ_∞ bound of $16/255$) while beating the state-of-the-art adversarial training algorithms such AWP, TRADES and PGD-AT at standard perturbation bounds (ℓ_∞ bound of $8/255$) as well.

1. Introduction

Deep Neural Networks are known to be vulnerable to Adversarial Attacks, which are perturbations crafted with an intention to fool the network [24]. In a classification setting, adversarially perturbed images cause the network's prediction to flip to unrelated classes, while causing no change in a human's prediction (Oracle label). The definition of adversarial attacks involves the presence of an Oracle, and this makes it challenging to formalize threat models for the training and verification of adversarial defenses. The widely accepted convention that circumvents this challenge is the ℓ_p norm based threat model [4] with low-magnitude bounds

[1]Anonymous Institution, Anonymous City, Anonymous Region, Anonymous Country. Correspondence to: Anonymous Author <anon.email@domain.com>.

Preliminary work. Under review by the ICML 2021 workshop on A Blessing in Disguise: The Prospects and Perils of Adversarial Machine Learning. Do not distribute.

Figure 1. Adversarially attacked images (b-e, g) and perturbations (f, h) for various ℓ_∞ bounds. Attacks are generated from a PGD [17, 18] Adversarially Trained model (AT) or normally trained model (NT). Original unperturbed image is shown in (a).

to ensure imperceptibility [10] . For example, attacks constrained within an ℓ_∞ norm of $8/255$ on the CIFAR-10 dataset are imperceptible to the human eye as shown in Fig.1(a), ensuring that the Oracle label is unchanged.

While low-magnitude ℓ_p norm based threat models form a crucial subset of the widely accepted definition of adversarial attacks [9], they are not sufficient, as there exist valid attacks at higher ε-bounds as well [26], as shown in Fig.1(g). However, the challenge at large perturbation bounds is the existence of attacks that can flip Oracle labels as well, as shown in Fig.1(c-e). This makes it difficult to naively scale existing Adversarial Training algorithms to large ε bounds. In this work, we aim to improve robustness at larger epsilon bounds, such as an ℓ_∞ norm bound of $16/255$. We define this as a moderate-magnitude bound, and discuss the ideal goals related to achieving robustness under this threat model in Sec.3. We further propose a novel defense Oracle-Aligned Adversarial Training (OA-AT), which attempts to align the predictions of the network with that of an Oracle, rather than enforcing all samples within the constraint set to have the same label as the unperturbed image.

Our contributions have been summarized below:

- We define the ideal goals for a moderate-ε threat model (ℓ_∞ radius of $16/255$) and construct our goals as a feasible subset of the same.
- We propose methods for generating Oracle-Aligned adversaries, which can be used for adversarial training under such a threat model.

- We propose Oracle-Aligned Adversarial Training (OA-AT) to improve robustness at larger epsilon bounds.
- We demonstrate state-of-the-art results on benchmark datasets. The proposed methods shows superior performance compared to state-of-the-art methods such as AWP, TRADES and PGD-AT at $\varepsilon = 16/255$ while also having better performance at $\varepsilon = 8/255$.
- We show improvement in results as the model capacity increases from ResNet-18 to WideResNet-34-10.

2. Related Works

Robustness against imperceptible attacks: Adversarial Training has emerged as the most successful defense strategies against ℓ_p norm bound imperceptible attacks. PGD Adversarial Training (PGD-AT) [17] constructs multi-step adversarial attacks by maximizing Cross-Entropy loss within the considered threat model and subsequently minimizes the same for training. This was followed by several adversarial training methods [29, 30, 19, 28, 22, 18] that improved accuracy against such imperceptible threat models further. Zhang et al. [29] proposed the TRADES defense, which maximizes the Kullback-Leibler (KL) divergence between softmax vectors of adversarial and clean samples for attack generation, and minimizes the same in addition to the cross entropy loss on clean samples for training.

Improving Robustness of base defenses: Wu et al. [28] proposed an additional step of *Adversarial Weight Perturbation* (AWP) to perturb the weights of the model in order to maximize the training loss, and further train the perturbed model to minimize the same. This generates a flatter loss surface [23], thereby improving robust generalization. While this can be integrated with any defense, AWP-TRADES is the state-of-the-art adversarial defense today. On similar lines, the use of stochastic weight averaging of model weights [13] is also seen to improve the flatness of loss surface, resulting in a boost in robustness [11, 5]. Recent works [18, 19, 11] attempt to find the best training techniques such as early stopping, use of optimal weight decay and weight averaging to achieve enhanced robust performance on base defenses such as PGD-AT [17] and TRADES [29].

Robustness against large perturbation attacks: Shaeiri et al. [20] demonstrate that the standard formulation of adversarial training is not well-suited for achieving robustness at large perturbations, as the loss saturates very early. The authors propose Extended Adversarial Training (ExAT), where a model trained on low-magnitude perturbations ($\varepsilon = 8/255$) is fine-tuned with large magnitude perturbations ($\varepsilon = 16/255$) for merely 5 training epochs, to achieve improved robustness at large perturbations. The authors also discuss the use of a varying epsilon schedule to improve training convergence. Friendly Adversarial Training (FAT) [30] performs early-stopping of an adversarial attack

by thresholding the number of times the model misclassifies the image during attack generation. The threshold is increased over training epochs to increase the strength of the attack over training. On similar lines, Sitawarin et al. [21] propose Adversarial Training with Early Stopping (ATES), which performs early stopping of a PGD attack based on the margin of the perturbed image being greater than a threshold that is increased over epochs. We improve upon these methods significantly using our proposed approach (Sec.4).

3. Preliminaries and Threat Model

3.1. Notation

We consider an N-class image classification problem with access to a labelled training dataset $\mathcal{D}$. The input images are denoted by $x \in \mathcal{X}$ and their corresponding labels are denoted as $y \in \{1, ..., N\}$. The function represented by the Deep Neural Network is denoted by f_θ where $\theta \in \Theta$ denotes the set of trained network parameters. The N-dimensional softmax output of the input image x is denoted as $f_\theta(x)$. Adversarial examples are defined to be images that are crafted specifically to fool a model into making an incorrect prediction [9]. An adversarial image corresponding to a clean image x would be denoted as $\widetilde{x}$. The set of all images within an ℓ_p norm ball of radius ε, $\mathcal{S}(x)$ is defined as, $\mathcal{S}(x) = \{\hat{x} : ||\hat{x} - x||_p < \varepsilon\}$. The set of all ℓ_p norm bound adversarial examples, $\mathcal{A}(x)$ is defined as, $\mathcal{A}(x) = \{\widetilde{x} : f_\theta(\widetilde{x}) \neq y, \widetilde{x} \in \mathcal{S}(x)\}$. In this work, we specifically consider robustness to ℓ_∞ norm bound adversarial examples. We define the Oracle prediction of a sample x as the label which a human is likely to assign to the image, and denote it as $O(x)$. For a clean image, $O(x)$ would correspond to the true label, y, while for a perturbed image it could differ from the original label.

3.2. Nomenclature of Adversarial Attacks

Tramèr et al. [26] discuss the existence of two types of adversaries: Sensitivity-based examples, where the model prediction changes, but the Oracle prediction remains the same as the unperturbed image, and Invariance-based examples, where the Oracle prediction changes, while the model prediction remains unchanged. Models trained using standard empirical risk minimization are susceptible to sensitivity-based adversarial examples, while models which are overly robust to large perturbation bounds could be susceptible to invariance-based examples. Since these definitions are dependent on the model being considered, we define a different nomenclature which only depends on the input image and the threat model considered, as below:

- Oracle-Invariant set $OI(x)$, is defined as the set of all images within the threat model which preserve the Oracle label. The Oracle is invariant to such perturbations: $OI(x) := \{\hat{x} : O(\hat{x}) = O(x), \hat{x} \in \mathcal{S}(x)\}$

- Oracle-Sensitive set $OS(x)$, is defined as the set of all images within the threat model which flip the label of the Oracle. The Oracle is sensitive to such perturbations: $OS(x) := \{\hat{x} : O(\hat{x}) \neq O(x), \hat{x} \in \mathcal{S}(x)\}$

3.3. Objectives of the Proposed Defense

Defenses based on the conventional ℓ_p norm based threat model defined in Sec.3.1 attempt to train models which are invariant to all samples within $\mathcal{S}(x)$. This is an ideal requirement for low ε-bound perturbations, where the added noise is imperceptible, and hence all samples within the threat model are Oracle-Invariant. An example of a low-ε threat model is the constraint set defined by $\varepsilon = 8/255$ for CIFAR-10 dataset, which produces adversarial examples that are perceptually similar to the corresponding clean images, as shown in Fig.1(b).

As we move to higher ε bounds, the Oracle-labels begin to change, as shown in Fig.1(c, d, e). For a very high perturbation bound such as $32/255$, the changes produced by the attack are clearly perceptible and flip the Oracle label for many images. Since the perturbations under such a high ε-bound threat model are clearly perceptible (even if the Oracle does not change prediction), this may not be of much practical relevance. The focus of this paper is to achieve robustness against moderate-magnitude ε-norm bound threat models, where some perturbations look partially modified, while others look unchanged, as is the case with $\varepsilon = 16/255$ in Fig.1(c) and (g). The existence of attacks which do not significantly change the perception of the image necessitates the requirement of robustness against such attacks, while the existence of partially Oracle-Sensitive samples makes it difficult to use standard adversarial methods on the same. We translate this to the following ideal goals for training defenses under this threat model:

- Robustness against samples which belong to $OI(x)$
- Sensitivity towards samples which belong to $OS(x)$, with model's prediction matching the Oracle label
- No specification on Out-of-Distribution (OOD) images

We incorporate these goals as the training objective in our proposed defense, which is discussed in Sec.4. Given the practical difficulty in assigning Oracle labels, we consider the following criteria for our defense evaluations:

- Robustness-Accuracy trade-off
- Robustness against all attacks within $\varepsilon = 8/255$
- Robustness to Oracle-Invariant samples within $\varepsilon = 16/255$, which is measured using accuracy against the Square attack [1] and other attacks discussed in Sec.4

4. Proposed Method

In order to achieve the goals discussed in Sec.3.3, we require to generate Oracle-Sensitive and Oracle-Invariant samples

and impose specific training losses on each of them individually. Since labeling of adversarial samples as Oracle-Invariant or Oracle-Sensitive is expensive and cannot be done while training networks, we propose to use attacks which ensure a given type of perturbation (OI or OS) by construction, and hence do not require explicit annotation.

Generation of Oracle-Sensitive examples: Tsipras et al. [27] show that robust models have perceptually aligned gradients. Adversarial examples generated using a robust model tend to start looking like the target (other) class images, as seen in Fig.1(c, d, e). Based on this, we use white-box adversarial examples generated from the model being trained as partially Oracle-Sensitive samples, and use the model's prediction as a proxy to the prediction of the Oracle.

Generation of Oracle-Invariant examples: While the strongest Oracle-Invariant examples are generated using the gradient-free Square attack [1], it uses 5000 queries which is computationally expensive for use in adversarial training, and reducing this weakens the attack significantly. The most efficient attack widely used for training is the PGD 10-step attack. However, it cannot be used for the generation of Oracle-Invariant samples as gradient-based attacks generated from adversarially trained models produce Oracle-Sensitive samples. We propose to use the Learned Perceptual Image Patch Similarity (LPIPS) measure for the generation of Oracle-Invariant attacks, as it is known to match well with perceptual similarity [31, 16]. As shown in Fig.A1, while the standard AlexNet model that is used in prior work [16] fails to distinguish between Oracle-Invariant and Oracle-Sensitive samples, an adversarially trained model is able to distinguish between the two types of attacks effectively. We therefore propose to minimize the LPIPS distance between the natural and perturbed images, in addition to the maximization of Cross-Entropy loss for attack generation: $\mathcal{L}_{CE}(x, y) - \lambda \cdot \text{LPIPS}(x, \hat{x})$. We choose λ as the minimum value that transforms the PGD attack from Oracle-Sensitive to Oracle-Invariant (OI), to generate strong OI attacks. This is further fine-tuned during training to achieve the optimal robustness-accuracy trade-off.

Oracle-Aligned Adversarial Training (OA-AT): The training algorithm for the proposed defense, Oracle-Aligned Adversarial Training (OA-AT) is presented in Algorithm-1 of the Appendix. We use the Trades-AWP formulation [29, 28] as the base implementation in the proposed training algorithm. We use the Cross-Entropy loss instead of KL-divergence loss for attack generation, as it generates stronger attacks [11]. Different from Wu et al. [28], we maximize loss on $x_i + 2 \cdot \widetilde{\delta}_i$ (where $\widetilde{\delta}_i$ is the attack) in the additional weight perturbation step, as it results in improved robust generalization. We use cosine learning rate schedule.

We start with an initial ε value of $4/255$ upto one-fourth the training epochs, and ramp up this value linearly to a

Table 1. **CIFAR-10, CIFAR-100**: Performance (%) of the proposed defense OA-AT compared to baselines, against attacks with different ε bounds. Sorted by AutoAttack accuracy [7] (AA 8/255)

Method	Clean	GAMA (8/255)	AA (8/255)	GAMA (12/255)	Square (12/255)	GAMA (16/255)	Square (16/255)
			CIFAR-10 (ResNet-18)				
FAT [30] (8)	**84.36**	48.41	48.14	29.39	39.48	15.18	25.07
PGD-AT [17] (10)	79.38	49.28	48.68	32.40	41.46	18.18	28.29
AWP [28] (10)	80.32	49.06	48.89	32.88	40.27	19.17	27.56
ATES [21] (10)	80.95	49.57	49.12	32.44	42.21	18.36	29.07
TRADES [29] (8)	80.53	49.63	49.42	33.32	40.94	19.27	27.82
ExAT-PGD [20] (11)	80.68	50.06	49.52	32.47	41.10	17.81	27.23
ExAT + AWP (10)	80.18	49.87	49.69	33.51	41.04	20.04	28.40
AWP [28] (8)	80.47	50.06	49.87	33.47	41.05	19.66	28.51
OA-AT (Ours)	80.24	**51.40**	**50.88**	**36.01**	**43.20**	**22.73**	**31.16**
Gain w.r.t. AWP	−0.23	+1.34	+1.01	+2.54	+2.15	+3.07	+2.65
			CIFAR-100 (ResNet-18)				
AWP [28]	59.88	25.81	25.52	14.80	20.24	8.72	12.80
OA-AT (Ours)	**60.27**	**26.41**	**26.00**	**16.28**	**21.47**	**10.47**	**14.60**
Gain w.r.t. AWP	+0.39	+0.60	+0.48	+1.48	+1.23	+1.75	+1.80

Table 2. **CIFAR-10**: Performance (%) of the proposed defense OA-AT (Ours) compared to the strongest baseline, AWP-TRADES (AWP) [28] against various attacks with different ε bounds

Method	Model	Clean	AA (8/255)	Square (12/255)	AA (12/255)	Square (16/255)	AA (16/255)
AWP	RN-18	80.47	49.87	41.05	33.19	28.51	19.23
Ours	RN-18	80.24	50.88	43.20	35.39	31.16	22.00
AWP	RN-34	83.89	52.44	42.84	34.61	29.22	19.69
Ours	RN-34	84.07	53.22	45.03	36.31	32.47	22.00
AWP	WRN-34	85.19	55.69	46.48	38.05	32.68	23.46
Ours	WRN-34	85.54	55.67	48.15	38.13	35.20	22.92
AWP + WA	WRN-34	85.10	55.87	46.52	37.97	32.50	23.27
Ours + WA	WRN-34	**85.67**	**55.93**	**48.79**	**39.06**	**35.76**	**24.05**

values and report the best baselines in Table-1. We observe that baseline defenses do not perform well when trained using large ε bounds such as $16/255$ (ref. Table-A1 for detailed results). We report adversarial robustness against the strongest known attacks, AutoAttack (AA) [7] and GAMA PGD-100 (GAMA) [22] for $\varepsilon = 8/255$ in order to obtain the worst-case robust accuracy. For larger bounds such as $12/255$ and $16/255$, we primarily aim for robustness against the Square attack [1], as it is the strongest known Oracle-Invariant attack. We compare the proposed approach against the strongest baseline AWP-TRADES [28] on CIFAR-100 dataset in Table-1 (ref. Table-A2 for detailed results), and on CIFAR-10 dataset on larger capacity models in Table-2. We observe significant gains in performance with the use of AutoAugment [8, 23] on CIFAR-100, and additionally with Model Weight Averaging (WA) [13, 11, 5] at larger model capacities. To ensure a fair comparison, we perform the same on the baselines as well.

Results: The proposed defense achieves consistent gains across all metrics considered in Sec.3.3 (AutoAttack [7] at $\varepsilon = 8/255$ and Square attack [1] at larger ε bounds). Although we train the model for achieving robustness at larger ε bounds, we achieve an improvement in the robustness at $\varepsilon = 8/255$ as well, which is not observed in any of the existing methods (Table-A1). We evaluate the proposed defense against diverse attacks (Table-A4) and sanity checks (Sec.A5) to ensure the absence of gradient masking.

6. Conclusions

In this work, we propose Oracle-Aligned Adversarial Training (OA-AT) for achieving robustness beyond perceptual limits. We first discuss the ideal goals of an adversarial defense at larger perturbation bounds, and further explore methods of effectively generating Oracle-Aligned adversaries during training. The key aspects of the defense include the use of LPIPS metric for generating Oracle-Invariant attacks during training, and the use of convex combination of clean and adversarial image predictions as targets for Oracle-Sensitive samples. A combination of these two losses help in achieving significant gains in robustness, and better robustness-accuracy trade-off as well.

value of $16/255$ at the last epoch. We use 5 attack steps when $\varepsilon = 4/255$ and 10 attack steps later. We perform standard adversarial training upto $\varepsilon = 12/255$ as the attacks in this range are imperceptible. Beyond this, we start incorporating separate training losses for Oracle-Invariant and Oracle-Sensitive samples in alternate training iterations. Oracle-Sensitive samples are generated by maximizing Cross-Entropy loss in a PGD attack formulation. Rather than enforcing the predictions of such attacks to be similar to the original image, we allow the network to be partially sensitive to such attacks by training them to be similar to a convex combinations of predictions on the clean image and perturbed samples at larger ($1.5 \cdot \varepsilon_{max}$) bounds as shown:
$$L_{adv} = KL\big(f_\theta(x_i + \widetilde{\delta}_i) \,||\, \alpha \, f_\theta(x_i) + (1-\alpha) \, f_\theta(x_i + \widehat{\delta}_i)\big)$$
Here $\widetilde{\delta}_i$ is the perturbation at the varying epsilon value $\widetilde{\varepsilon}$, and $\widehat{\delta}_i$ is the perturbation at $24/255$. This results in better robustness-accuracy trade-off as shown in Table-A3. In the other alternate iteration, we use the LPIPS metric to generate strong and efficient Oracle-Invariant attacks during training. We perform exponential weight-averaging of the network being trained and use this for computing the LPIPS metric for improved and stable results (Table-A3). We increase the values of α and λ over training, as the nature of attacks changes with varying ε. The use of both Oracle-Invariant and Oracle-Sensitive samples ensures that the proposed algorithm is robust to Oracle-Invariant samples and also agrees with the Oracle on the partially Oracle-Sensitive samples.

5. Experiments and Results

We compare performance of the proposed approach with the existing defenses discussed in Sec.2 on the CIFAR-10 [15] dataset in Table-1. We train all models on ResNet-18 architecture for 110 epochs. For each baseline, we find the best set of hyperparameters to achieve clean accuracy of around 80% to ensure a fair comparison across all methods. We also perform baseline training across various ε

References

[1] Andriushchenko, M., Croce, F., Flammarion, N., and Hein, M. Square attack: a query-efficient black-box adversarial attack via random search. In *The European Conference on Computer Vision (ECCV)*, 2020. 3, 4, 7, 10, 11

[2] Athalye, A., Carlini, N., and Wagner, D. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *International Conference on Machine Learning (ICML)*, 2018. 11

[3] Carlini, N. and Wagner, D. Defensive distillation is not robust to adversarial examples. *arXiv preprint arXiv:1607.04311*, 2016. 11

[4] Carlini, N., Athalye, A., Papernot, N., Brendel, W., Rauber, J., Tsipras, D., Goodfellow, I., and Madry, A. On evaluating adversarial robustness. *arXiv preprint arXiv:1902.06705*, 2019. 1

[5] Chen, T., Zhang, Z., Liu, S., Chang, S., and Wang, Z. Robust overfitting may be mitigated by properly learned smoothening. 2, 4

[6] Croce, F. and Hein, M. Minimally distorted adversarial examples with a fast adaptive boundary attack. In *International Conference on Machine Learning (ICML)*, 2020. 11

[7] Croce, F. and Hein, M. Reliable evaluation of adversarial robustness with an ensemble of diverse parameter-free attacks. In *International Conference on Machine Learning (ICML)*, 2020. 4, 9, 10, 11

[8] Cubuk, E. D., Zoph, B., Mane, D., Vasudevan, V., and Le, Q. V. Autoaugment: Learning augmentation policies from data. *arXiv preprint arXiv:1805.09501*, 2018. 4, 9, 10

[9] Goodfellow, I. and Papernot, N. Is attacking machine learning easier than defending it? Blog post on Feb 15, 2017. 1, 2

[10] Goodfellow, I. J., Shlens, J., and Szegedy, C. Explaining and harnessing adversarial examples. In *International Conference on Learning Representations (ICLR)*, 2015. 1, 11

[11] Gowal, S., Qin, C., Uesato, J., Mann, T., and Kohli, P. Uncovering the limits of adversarial training against norm-bounded adversarial examples. *arXiv preprint arXiv:2010.03593*, 2020. 2, 3, 4

[12] Hitaj, D., Pagnotta, G., Masi, I., and Mancini, L. V. Evaluating the robustness of geometry-aware instance-reweighted adversarial training. *arXiv preprint arXiv:2103.01914*, 2021. 11

[13] Izmailov, P., Podoprikhin, D., Garipov, T., Vetrov, D., and Wilson, A. G. Averaging weights leads to wider optima and better generalization. *arXiv preprint arXiv:1803.05407*, 2018. 2, 4

[14] Jiang, L., Ma, X., Weng, Z., Bailey, J., and Jiang, Y.-G. Imbalanced gradients: A new cause of over-estimated adversarial robustness. *arXiv preprint arXiv:2006.13726*, 2020. 11

[15] Krizhevsky, A. et al. Learning multiple layers of features from tiny images. 2009. 4, 8

[16] Laidlaw, C., Singla, S., and Feizi, S. Perceptual adversarial robustness: Defense against unseen threat models. *arXiv preprint arXiv:2006.12655*, 2020. 3, 7

[17] Madry, A., Makelov, A., Schmidt, L., Dimitris, T., and Vladu, A. Towards deep learning models resistant to adversarial attacks. In *International Conference on Learning Representations (ICLR)*, 2018. 1, 2, 4, 7, 9, 10, 11

[18] Pang, T., Yang, X., Dong, Y., Su, H., and Zhu, J. Bag of tricks for adversarial training. *arXiv preprint arXiv:2010.00467*, 2020. 1, 2, 7

[19] Rice, L., Wong, E., and Kolter, J. Z. Overfitting in adversarially robust deep learning. In *International Conference on Machine Learning (ICML)*, 2020. 2

[20] Shaeiri, A., Nobahari, R., and Rohban, M. H. Towards deep learning models resistant to large perturbations. *arXiv preprint arXiv:2003.13370*, 2020. 2, 4, 9, 10

[21] Sitawarin, C., Chakraborty, S., and Wagner, D. Improving adversarial robustness through progressive hardening. *arXiv preprint arXiv:2003.09347*, 2020. 2, 4, 9, 10

[22] Sriramanan, G., Addepalli, S., Baburaj, A., and Venkatesh Babu, R. Guided Adversarial Attack for Evaluating and Enhancing Adversarial Defenses. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020. 2, 4, 10, 11

[23] Stutz, D., Hein, M., and Schiele, B. Relating adversarially robust generalization to flat minima. *arXiv preprint arXiv:2104.04448*, 2021. 2, 4, 10

[24] Szegedy, C., Zaremba, W., Sutskever, I., Bruna, J., Erhan, D., Goodfellow, I. J., and Fergus, R. Intriguing properties of neural networks. In *International Conference on Learning Representations (ICLR)*, 2013. 1

[25] Tashiro, Y., Song, Y., and Ermon, S. Diversity can be transferred: Output diversification for white-and

black-box attacks. *Advances in Neural Information Processing Systems*, 33, 2020. 11

[26] Tramèr, F., Behrmann, J., Carlini, N., Papernot, N., and Jacobsen, J.-H. Fundamental tradeoffs between invariance and sensitivity to adversarial perturbations. In *International Conference on Machine Learning*, pp. 9561–9571. PMLR, 2020. 1, 2

[27] Tsipras, D., Santurkar, S., Engstrom, L., Turner, A., and Madry, A. Robustness may be at odds with accuracy. In *International Conference on Learning Representations (ICLR)*, 2019. 3

[28] Wu, D., Xia, S.-T., and Wang, Y. Adversarial weight perturbation helps robust generalization. *Advances in Neural Information Processing Systems*, 33, 2020. 2, 3, 4, 8, 9, 10

[29] Zhang, H., Yu, Y., Jiao, J., Xing, E., El Ghaoui, L., and Jordan, M. I. Theoretically principled trade-off between robustness and accuracy. In *International Conference on Machine Learning (ICML)*, 2019. 2, 3, 4, 8, 9, 10

[30] Zhang, J., Xu, X., Han, B., Niu, G., Cui, L., Sugiyama, M., and Kankanhalli, M. Attacks which do not kill training make adversarial learning stronger. In *ICML*, 2020. 2, 4, 9, 10

[31] Zhang, R., Isola, P., Efros, A. A., Shechtman, E., and Wang, O. The unreasonable effectiveness of deep features as a perceptual metric. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 586–595, 2018. 3, 7

Appendix

A1. Oracle-Invariant Attacks

Square Attack: The strongest Oracle-Invariant examples are generated using the Square attack [1]. These images are Oracle-Invariant by construction, since this is a query-based attack and does not use gradients from any model for attack generation. However this attack uses 5000 queries, and is a computationally expensive attack. Hence this attack cannot be used for adversarial training, although it is one of the best attacks which can be used for evaluations. We note that reducing the number of queries makes it computationally efficient, however it also reduces the effectiveness of the attack significantly.

PGD based Attacks: While the most efficient attack widely used for training is the PGD 10-step attack, it cannot be used for the generation of Oracle-Invariant samples as gradient-based attacks have perceptually aligned gradients and tend to produce Oracle-Sensitive samples. Therefore, we explore some variants of the PGD attack to make the generated perturbations Oracle-Invariant. We denote the Cross-Entropy loss on a data sample x with ground truth label y using $\mathcal{L}_{CE}(x, y)$. We explore the addition of regularizers to the Cross-Entropy loss weighted by a factor of λ_X in each case. The value of λ_X is chosen as the minimum value which transforms the PGD attacks from Oracle-Sensitive to Oracle-Invariant. This results in the strongest possible Oracle-Invariant attacks.

Discriminator based PGD Attack: In this attack, we train a discriminator to distinguish between Oracle-Invariant and Oracle-Sensitive attacks, and further use the following objective for generation of Oracle-Invariant attacks:

$$\mathcal{L}_{CE}(x, y) - \lambda_{Disc} \cdot \mathcal{L}_{BCE}(x, \text{OI}) \qquad \text{(A1)}$$

Here $\mathcal{L}_{BCE}(x, \text{OI})$ is the Binary Cross-Entropy loss of the discriminator with label corresponding to Oracle-Invariant (OI) attack. We train the discriminator to distinguish between images concatenated channel-wise with the corresponding Oracle-Sensitive perturbations, and a second distribution where perturbations are shuffled across images in the batch. This ensures that the discriminator relies on the spatial correlation between the image and its corresponding perturbation, rather than on the perturbation alone. Also, this captures the most salient property of Oracle-Sensitive attacks, which is spatial correlation.

LPIPS based PGD Attack: We propose to use the Learned Perceptual Image Patch Similarity (LPIPS) measure for the generation of Oracle-Sensitive attacks, as it is

Figure A1. LPIPS distance between clean and adversarially perturbed images. Attacks generated from PGD-AT [17, 18] model (Oracle-Sensitive) and Normally Trained model (Oracle-Invariant) are considered. (a) PGD-AT ResNet-18 model is used for computation of LPIPS distance (b) Normally Trained AlexNet model is used for computation of LPIPS distance. PGD-AT model based LPIPS distance is useful to distinguish between Oracle-Sensitive and Oracle-Invariant attacks.

known to match well with perceptual similarity [31, 16]. As shown in Fig.A1, while the standard AlexNet model that is used in prior work [16] fails to distinguish between Oracle-Invariant and Oracle-Sensitive samples, an adversarially trained model is able to distinguish between the two types of attacks effectively. In this plot, we consider attacks generated from a PGD-AT [17, 18] model (Fig.1(c-e)) as Oracle-Sensitive attacks, and attacks generated from a Normally Trained model (Fig.1(h)) as Oracle-Invariant attacks. We therefore propose to minimize the LPIPS distance between the natural and perturbed images, in addition to the maximization of Cross-Entropy loss for attack generation as shown below:

$$\mathcal{L}_{CE}(x, y) - \lambda_{\text{LPIPS}} \cdot \text{LPIPS}(x, \hat{x}) \qquad \text{(A2)}$$

We choose λ as the minimum value that transforms the PGD attack from Oracle-Sensitive to Oracle-Invariant (OI), to generate strong OI attacks. This is further fine-tuned during training to achieve the optimal robustness-accuracy trade-off.

As shown in Table A3, while we obtain the best results using the LPIPS based PGD attack for training (E1), the use of discriminator based PGD attack (E9) also results in a significantly better robustness-accuracy trade-off when compared to E2, where there is no explicit regularizer to ensure the generation of Oracle-Invariant attacks. This shows that both, LPIPS and Discriminator can be used for the generation of Oracle-Invariant attacks.

Evaluation of the proposed defense against Oracle-Invariant Attacks: We compare the performance of the

Figure A2. Comparison of the proposed model with the best baseline, AWP [28] against attacks of varying strength and Oracle sensitivity constrained within perturbation bound of $\varepsilon = 16/255$. (a) LPIPS based regularizer, and (b) Discriminator based regularizer are used for generating Oracle-Invariant attacks respectively. As the coefficient of the regularizer increases, the attack transforms from Oracle-Sensitive to Oracle-Invariant. The proposed method (OA-AT) achieves improved accuracy against the attacks throughout.

proposed defense OA-AT with the strongest baseline AWP [28] against the two proposed Oracle-Invariant attacks, LPIPS based attack and Discriminator based attack in Fig.A2 (a) and (b) respectively. We vary the coefficient of the regularizers used in the generation of attacks, λ_{Disc} (Eq.A1) and λ_{LPIPS} (Eq.A2) in each of the plots. As we increase the coefficient, the attack transforms from Oracle-Sensitive to Oracle-Invariant. We achieve better performance across all values of the coefficients when compared to the baseline.

A2. Details on the Datasets used

We evaluate the proposed approach on the CIFAR-10 and CIFAR-100 [15] datasets. The two datasets consist of RGB images of spatial dimension 32×32, and contain 10 and 100 distinct classes respectively. We first present results on CIFAR-10 since it has become the benchmark dataset to perform comparative analysis on different adversarial defense and attack methods. CIFAR-100 is a challenging dataset to achieve adversarial robustness given the large number of diverse classes that are interrelated. Each of these datasets consist of 50,000 training images and 10,000 test images. We split the original training set to create a validation set of 1,000 images in CIFAR-10 and 2,500 images in CIFAR-100. We ensure that the validation split is balanced equally across all classes, and use the remaining images for training. To enable fair comparison, we use this split for training the proposed defense as well as other baseline approaches. For both datasets, we consider the ℓ_∞ threat model of radius 8/255 to be representative of imperceptible perturbations, that is, the Oracle label does not change within this set. Further, we consider the ℓ_∞ threat model of radius 16/255 to investigate robustness on moderate-level perturbations.

Algorithm 1 Oracle-Aligned Adversarial Training
1: **Input:** Deep Neural Network f_θ with parameters θ, Training Data $\{x_i, y_i\}_{i=1}^M$, Epochs T, Learning Rate η, Perturbation budget ε_{max}, Adversarial Perturbation function $A(x, y, \ell, \varepsilon)$ which maximises loss ℓ
2: **for** epoch $= 1$ **to** T **do**
3: $\quad \widetilde{\varepsilon} = \max\{\varepsilon_{max}/4, \varepsilon_{max} \cdot \text{epoch}/T\}$
4: $\quad$ **for** $i = 1$ **to** M **do**
5: $\quad\quad \delta_i \sim U(-\min(\widetilde{\varepsilon}, \varepsilon_{max}/4), \min(\widetilde{\varepsilon}, \varepsilon_{max}/4))$
6: $\quad\quad$ **if** $\widetilde{\varepsilon} < 3/4 \cdot \varepsilon_{max}$ **then**
7: $\quad\quad\quad \ell = \ell_{CE}(f_\theta(x_i + \delta_i), y_i)$
8: $\quad\quad\quad \widetilde{\delta}_i = A(x_i, y_i, \ell, \widetilde{\varepsilon})$
9: $\quad\quad\quad L_{adv} = \mathrm{KL}\left(f_\theta(x_i + \widetilde{\delta}_i) \| f_\theta(x_i)\right)$
10: $\quad\quad$ **else if** $i \% 2 = 0$ **then**
11: $\quad\quad\quad \ell = \ell_{CE}(f_\theta(x_i + \delta_i), y_i)$
12: $\quad\quad\quad \widehat{\delta}_i = A(x_i, y_i, \ell, 1.5 \cdot \varepsilon_{max})$
13: $\quad\quad\quad \widetilde{\delta}_i = \Pi(\widehat{\delta}_i, \widetilde{\varepsilon})$
14: $\quad\quad\quad L_{adv} = \mathrm{KL}\left(f_\theta(x_i + \widetilde{\delta}_i) \quad \|\right.$
$\quad\quad\quad\quad\quad\quad\quad \left. \alpha \cdot f_\theta(x_i) + (1-\alpha) \cdot f_\theta(x_i + \widehat{\delta}_i)\right)$
15: $\quad\quad$ **else**
16: $\quad\quad\quad \delta_i \sim U(-\widetilde{\varepsilon}, \widetilde{\varepsilon})$
17: $\quad\quad\quad \ell = \ell_{CE}(f_\theta(x_i + \delta_i), y_i) - \mathrm{LPIPS}(x_i, x_i + \delta_i)$
18: $\quad\quad\quad \widetilde{\delta}_i = A(x_i, y_i, \ell, \widetilde{\varepsilon})$
19: $\quad\quad\quad L_{adv} = \mathrm{KL}\left(f_\theta(x_i + \widetilde{\delta}_i) \| f_\theta(x_i)\right)$
20: $\quad\quad$ **end if**
21: $\quad\quad L = \ell_{CE}(f_\theta(x_i), y_i) + L_{adv}$
22: $\quad\quad \theta = \theta - \eta \cdot \nabla_\theta L$
23: $\quad$ **end for**
24: **end for**

A3. Details on Training

The algorithm for the proposed method as explained in Sec.4 is presented in Algorithm-1. We use a varying ε schedule and start training on perturbations of strength $\varepsilon = 4/255$ since this results in better performance when compared to ramping up the value of ε from 0 (E7 of Table-A3). For CIFAR-10, we set the weight of the adversarial loss L_{adv} in L21 (β parameter of TRADES [29]) to 1.5 for the first three-quarters of training, and then linearly increase it from 1.5 to 3 in the moderate perturbation regime, where ε is linearly increased from 12/255 to 16/255. In this moderate perturbation regime, we also linearly increase the coefficient of the LPIPS distance (Alg.1, L17) from 0 to 1, and linearly decrease the α parameter used in the convex combination of softmax prediction (Alg.1, L14) from 1 to 0.8. This allows a smooth transition from adversarial training on imperceptible attacks to attacks with larger perturbation bounds. We use weight decay of 5e-4 along with the SGD optimizer and momentum of 0.9 for our experiments. Further, we use the cosine learning rate schedule for training over 110 epochs, with 0.2 set as the maximum learning rate. We use expo-

Table A1. **CIFAR-10**: Performance (%) of the proposed defense OA-AT against attacks with different ε bounds, when compared to the following baselines: AWP [28], ExAT [20], TRADES [29], ATES [21], PGD-AT [17] and FAT [30]. AWP [28] is the strongest baseline. The first partition shows defenses trained on $\varepsilon = 16/255$. Training on large perturbation bounds results in very poor Clean Accuracy. The second partition consists of baselines tuned to achieve clean accuracy close to 80%. These are sorted by AutoAttack accuracy [7] (AA 8/255). The proposed defense achieves significant gains in accuracy across all attacks.

Method	Attack ε (Training)	Clean	FGSM (BB) (8/255)	R-FGSM (8/255)	GAMA (8/255)	AA (8/255)	FGSM (BB) (12/255)	R-FGSM (12/255)	GAMA (12/255)	Square (12/255)	FGSM (BB) (16/255)	R-FGSM (16/255)	GAMA (16/255)	Square (16/255)
TRADES	16/255	75.30	73.26	53.10	35.64	35.12	72.13	44.27	20.24	30.11	70.76	36.99	10.10	18.87
AWP	16/255	71.63	69.71	54.53	40.85	40.55	68.65	47.13	27.06	34.42	67.42	40.89	15.92	24.16
PGD-AT	16/255	64.93	63.65	55.47	46.66	46.21	62.81	51.05	36.95	40.53	61.70	46.40	26.73	32.25
FAT	16/255	75.27	73.44	60.25	47.68	47.34	72.22	53.17	34.31	39.79	70.73	46.88	22.93	29.47
ExAT+AWP	16/255	75.28	73.27	60.02	47.63	47.46	71.81	52.38	34.42	39.62	70.47	45.39	22.61	28.79
ATES	16/255	66.78	65.60	56.79	47.89	47.52	64.64	51.71	37.47	42.07	63.75	47.28	26.50	32.55
ExAT + PGD	16/255	72.04	70.68	59.99	49.24	48.80	69.66	53.96	36.68	41.93	68.04	48.37	23.01	30.21
FAT	12/255	80.27	77.87	61.46	45.42	45.13	76.69	52.33	29.08	36.71	74.79	44.56	16.18	24.59
FAT	8/255	**84.36**	82.20	64.06	48.41	48.14	80.32	55.41	29.39	39.48	78.13	47.50	15.18	25.07
ATES	8/255	84.29	**82.39**	**65.66**	49.14	48.56	**80.81**	55.59	29.36	40.68	**78.48**	47.03	14.70	25.88
PGD-AT	8/255	81.12	78.94	63.48	49.03	48.58	77.19	54.42	30.84	40.82	74.37	46.28	15.77	26.47
PGD-AT	10/255	79.38	77.89	62.78	49.28	48.68	76.60	54.76	32.40	41.46	74.75	47.46	18.18	28.29
AWP	10/255	80.32	77.87	62.33	49.06	48.89	76.33	53.83	32.88	40.27	74.13	45.51	19.17	27.56
ATES	10/255	80.95	79.22	63.95	49.57	49.12	77.77	55.37	32.44	42.21	75.51	48.12	18.36	29.07
TRADES	8/255	80.53	78.58	63.69	49.63	49.42	77.20	55.48	33.32	40.94	75.05	47.92	19.27	27.82
ExAT + PGD	11/255	80.68	79.07	63.58	50.06	49.52	77.98	55.92	32.47	41.10	76.12	48.37	17.81	27.23
ExAT + AWP	10/255	80.18	78.04	63.15	49.87	49.69	76.34	54.64	33.51	41.04	74.37	46.54	20.04	28.40
AWP	8/255	80.47	78.22	63.32	50.06	49.87	76.88	54.61	33.47	41.05	74.42	46.16	19.66	28.51
OA-AT (Ours)	16/255	80.24	78.54	65.00	**51.40**	**50.88**	77.34	**57.68**	**36.01**	**43.20**	75.72	**51.13**	**22.73**	**31.16**
Gain w.r.t. AWP		−0.23	+0.32	+1.68	+1.34	+1.01	+0.46	+3.07	+2.54	+2.15	+1.30	+4.97	+3.07	+2.65

nential weight averaging with $\tau = 0.995$ for generating the model to compute LPIPS distance. We note from Table-A3 that this results in better performance when compared to using the current model being trained for the same (E10). This also leads to more stable results across reruns.

We also utilise AutoAugment [8] for training on CIFAR-100, and for large model capacities. We apply AutoAugment with a probability of 0.5 for CIFAR-100, and for the CIFAR-10 model trained on ResNet-34. Since the extent of overfitting is higher for large model capacities, we use AutoAugment with $p = 1$ on WideResNet-34-10. While the use of AutoAugment helps in overcoming overfitting, it could also negatively impact robust accuracy due to the drift between the training and test distributions. We observe a drop in robust accuracy on the CIFAR-10 dataset with the use of AutoAugment (E5 in Table-A3), while there is a boost in the clean accuracy. On similar lines, we observe a drop in robust accuracy on the CIFAR-100 dataset as well, when we increase the probability of applying AutoAugment from 0.5 (E11 in Table-A3) to 1 (E12 in Table-A3).

To investigate the stability of the proposed approach, we train a ResNet-18 network multiple times by using different random initialization of network parameters. We observe that the proposed approach is indeed stable, with a standard deviation of 0.167 for Clean accuracy, 0.115 and 0.180 for GAMA PGD-100 accuracies with $\varepsilon = 8/255$ and 16/255 respectively, and 0.143 for the Square attack with $\varepsilon = 16/255$ over three independent training runs on CIFAR-10. We also observe that the last epoch is consistently the best performing model for the ResNet-18 architecture. Nonetheless,

we still utilise early stopping on the validation set using PGD 7-step accuracy for all models including other baseline approaches to enable fair comparison overall.

A3.1. Ablation Study

In order to study the impact of different components of the proposed defense, we present a detailed ablative study using ResNet-18 models in Table-A3. In the first partition of the table, we present results on the CIFAR-10 dataset, with E1 representing the proposed approach. First, we study the efficacy of the LPIPS metric in generating Oracle-Invariant attacks. In experiment E2, we train a model without LPIPS by setting its coefficient to zero. While the resulting model achieves a slight boost in robust accuracy at $\varepsilon = 16/255$ due to the use of stronger attacks for training, there is a considerable drop in clean accuracy, and a corresponding drop in robust accuracy at $\varepsilon = 8/255$ as well. We observe a similar trend by setting the value of α to 1 as shown in E3, and by combining E2 and E3 as shown in E4. We note that E4 is similar to standard adversarial training, where the model attempts to learn consistent predictions in the ε ball around every data sample. While this works well for imperceptible attacks ($\varepsilon = 8/255$), it leads to poor clean accuracy as shown in the first partition of Table-A1.

As discussed in Sec.4, we maximize loss on $x_i + 2 \cdot \widetilde{\delta_i}$ (where $\widetilde{\delta_i}$ is the attack) in the additional weight perturbation step. We present results by using the standard ε limit for the weight perturbation step as well, in E6. This leads to a drop across all metrics, indicating the importance of using large magnitude perturbations in the weight perturbation

Table A2. **CIFAR-100**: Performance (%) of the proposed defense OA-AT against attacks with different ε bounds, when compared to the following baselines: AWP [28], ExAT [20], TRADES [29], ATES [21], PGD-AT [17] and FAT [30]. AWP [28] is the strongest baseline. The baselines are sorted by AutoAttack accuracy [7] (AA 8/255). The proposed defense achieves significant gains in accuracy against the strongest attacks across all ε bounds. Since the proposed defense uses AutoAugment [8] as the augmentation strategy, we present result on the strongest baseline AWP [28] with AutoAugment as well.

Method	Attack ε (Training)	Clean	FGSM (BB) (8/255)	R-FGSM (8/255)	GAMA (8/255)	AA (8/255)	FGSM (BB) (12/255)	R-FGSM (12/255)	GAMA (12/255)	Square (12/255)	FGSM (BB) (16/255)	R-FGSM (16/255)	GAMA (16/255)	Square (16/255)
FAT	8/255	56.61	52.10	34.76	23.36	23.20	49.54	27.77	13.96	18.21	46.01	22.52	8.30	11.56
TRADES	8/255	58.27	54.33	36.20	23.67	23.47	51.64	28.55	13.88	18.46	48.46	22.78	8.31	11.89
PGD-AT	8/255	57.43	53.71	37.66	24.81	24.33	50.90	30.07	13.51	19.62	47.43	23.18	7.40	11.64
ATES	8/255	57.54	53.62	37.05	25.08	24.72	50.84	29.18	13.75	19.42	47.35	22.89	7.59	11.40
ExAT-PGD	9/255	57.46	53.56	38.48	25.25	24.93	51.43	30.60	15.12	20.40	48.15	24.21	8.37	12.47
ExAT-AWP	10/255	57.76	53.46	37.84	25.55	25.27	50.42	30.39	14.98	19.72	46.99	24.48	9.07	12.68
AWP	8/255	58.81	54.13	37.92	25.51	25.30	50.72	30.40	14.71	19.82	46.66	23.96	8.68	12.44
AWP (with AutoAug.)	8/255	59.88	55.62	39.10	25.81	25.52	52.75	31.11	14.80	20.24	49.44	24.99	8.72	12.80
OA-AT (Ours) (with AutoAug.)	16/255	**60.27**	**56.27**	**40.24**	**26.41**	**26.00**	**53.86**	**33.78**	**16.28**	**21.47**	**51.11**	**28.02**	**10.47**	**14.60**
Gain w.r.t. AWP (with AutoAug.)		+0.39	+0.65	+1.14	+0.60	+0.48	+1.11	+2.67	+1.48	+1.23	+1.67	+3.03	+1.75	+1.80

Table A3. **CIFAR-10, CIFAR-100**: Ablation experiments on ResNet-18 architecture to highlight the importance of various aspects in the proposed defense OA-AT. Performance (%) against attacks with different ε bounds is reported.

Method	Clean	GAMA (8/255)	GAMA (16/255)	Square (16/255)
CIFAR-10				
E1: OA-AT (Ours)	80.24	51.40	22.73	31.16
E2: LPIPS weight = 0	78.47	50.60	24.05	31.37
E3: Alpha = 1	79.29	50.60	23.65	31.23
E4: Alpha = 1, LPIPS weight = 0	77.16	50.49	24.93	32.01
E5: With AutoAugment (p=0.5)	81.59	50.40	21.59	30.84
E6: Without 2ε perturbations for AWP	79.96	50.50	22.61	30.60
E7: Increasing epsilon from the beginning	80.34	50.77	22.57	30.80
E8: Maximizing KL div for attack generation	81.19	49.77	21.17	29.39
E9: Discriminator for OI Attack	80.56	50.75	22.13	31.17
E10: Current model (without WA) for LPIPS	80.50	50.75	22.90	30.76
CIFAR-100				
E11: OA-AT (Ours)	60.27	26.41	10.47	14.60
E12: With AutoAugment (p=1)	60.19	25.32	9.24	13.78
E13: Without AutoAugment	58.08	25.81	10.40	14.31

step for producing a flatter loss surface that leads to better generalization to the test set. Different from the standard TRADES formulation, we maximize Cross-Entropy loss for attack generation in the proposed method. From E8 we note that use of KL divergence leads to higher clean accuracy and a drop in robust accuracy since the KL divergence based attack is weaker.

A4. Detailed Results

A4.1. Comparison with State-of-the-Art

In Tables-A1 and A2, we present results of different defense methods such as AWP-TRADES [28], TRADES [29], PGD-AT [17], ExAT [20], ATES [21] and FAT [30], evaluated on a broad range of adversaries. We present evaluations on the Black-Box FGSM attack and a suite of White-Box attacks, on ℓ_∞ constraint sets of different radii: 8/255, 12/255 and 16/255. The white-box evaluations consist of the single-step Randomised-FGSM (R-FGSM) attack, the GAMA PGD-100 attack [22] and AutoAttack [7], with the latter two being amongst the strongest of attacks known to date.

Lastly, we also present evaluations on the Square attack [1] for ε=12/255, 16/255 in order to evaluate performance on Oracle-Invariant samples.

CIFAR-10: To enable fair comparison on adversaries that extend beyond the standard ℓ_∞ constraint of 8/255, we present a comprehensive comparison of various defenses trained with different attack strengths in Table-A1. In the first partition of the table, we present other approaches specifically trained with an ℓ_∞ constraint of 16/255. We first observe that while these models do achieve competitive robustness on adversaries of attack strength $\varepsilon = 8/255$, 12/255 and 16/255, they achieve significantly lower accuracy on clean samples which limits their use in practical scenarios. Thus, for better comparative analysis that accounts for the robustness-accuracy trade-off, we present other baseline approaches with hyperparameters and attack strengths tuned to achieve the best robust performance, while maintaining clean accuracy close to 80% as commonly observed on the CIFAR-10 dataset in the second partition of Table-A1. We thus observe that the proposed method OA-AT consistently out-performs other approaches on all three metrics described in Sec.3.3, by achieving enhanced performance on both Oracle-Sensitive and Oracle-Invariant attacks, while striking a favourable robustness-accuracy trade-off. Furthermore, the proposed defense is seen to have better robust performance even on the standard ℓ_∞ constraint set of 8/255 as compared to other approaches, despite training on larger perturbations sets.

CIFAR-100: In Table-A2, we present results on models trained on the highly-challenging CIFAR-100 dataset. Since this dataset contains relatively fewer training images per distinct class, we seek to enhance performance further by incorporating RL-based augmentation techniques such as AutoAugment [8, 23]. To enable fair comparison, we incorporate AutoAugment for the strongest baseline, AWP [28]. We thus observe that the proposed method consistently performs better than existing approaches by significant margins, both in terms of clean accuracy, as well as robustness against adversarial attacks conforming to the three distinct

(a) CIFAR-10 (Accuracy)	(b) CIFAR-10 (Loss)	(c) CIFAR-100 (Accuracy)	(d) CIFAR-100 (Loss)

Figure A3. (a, c) Plots showing the trend of Accuracy (%) against PGD-7 step attacks across variation in attack perturbation bound (ε) on CIFAR-10 and CIFAR-100 datasets. As the perturbation bound increases, accuracy against white-box attacks goes to 0, indicating the absence of gradient masking [2] (b, d) Plots showing the variation of Cross-Entropy Loss on FGSM attack [10] against variation in the attack perturbation bound (ε) on CIFAR-10 and CIFAR-100 datasets. As the perturbation bound increases, loss increases linearly, indicating the absence of gradient masking [2]

Table A4. **Evaluation against various attacks with a perturbation bound of** $\varepsilon = 8/255$ **on CIFAR-10**: Performance (%) of the proposed defense OA-AT against various attacks (sorted by Robust Accuracy) to ensure the absence of gradient masking. [†]Includes 5000-queries of Square attack.

Attack	No. of Steps	No. of restarts	Robust Accuracy (%)
AutoAttack[†] [7]	100	20	**50.88**
GAMA-MT [22]	100	5	50.90
ODS (98 +2 steps) [25]	100	100	50.94
MDMT attack [14]	100	10	51.19
Logit-Scaling attack [3, 12]	100	20	51.26
GAMA-PGD [22]	100	1	51.40
MD attack [14]	100	1	51.47
PGD-50 (1000 RR) [17]	50	1000	55.37
PGD-1000 [17]	1000	1	56.15

constraint sets. Further, this also confirms that the proposed method scales well to large, complex datasets, while maintaining a consistent advantage in performance compared to other approaches.

A5. Gradient Masking Checks

As discussed by Athalye et al. [2], we present various checks to ensure the absence of Gradient Masking in the proposed defense. In Fig.A3(a,c), we observe that the accuracy of the proposed defense on the CIFAR-10 and CIFAR-100 datasets monotonically decreases to zero against 7-step PGD white-box attacks as the perturbation budget is increased. This shows that gradient based attacks indeed serve as a good indicator of robust performance, as strong adversaries of large perturbation sizes achieve zero accuracy, indicating the absence of gradient masking. In Fig.A3(b,d), we plot the Cross-Entropy loss against FGSM attacks with varying perturbation budget. We observe that the loss increases linearly, thereby suggesting that the first-order Taylor approximation to the loss surface indeed remains effective in the local neighbourhood of sample images, again indicating the absence of gradient masking.

We also verify that the model achieves higher robust accuracy against weaker Black-box attacks, as compared to

strong gradient based attacks such as GAMA or AutoAttack in Tables-A1,A2. We also observe that adversaries that conform to larger constraint sets are stronger than their counterparts that are restricted to smaller epsilon bounds, as is expected.

In Table-A4, we perform exhaustive evaluations using various attack techniques to further verify the absence of gradient masking. In addition to AutoAttack [7] which in itself consists of an ensemble of four attacks- AutoPGD with Cross-Entropy and Difference-of-Logits loss, the FAB attack [6] and Square Attack [1], we present evaluations against strong multi-targeted attacks such as GAMA-MT [22] and the MDMT attack [14] which specifically target other classes during optimization. We also consider the untargeted versions of the latter two attacks, the GAMA-PGD and MD attack respectively. We also present the ODS attack [25] with 100 restarts, which diversifies the input random noise based on the output predictions in order to obtain results which are less dependent on the sampled random noise used for attack initialization. Next, the Logit-Scaling attack [3, 12] helps yield robust evaluations that are less dependent on the exact scale of output logits predicted by the network, and has been seen to be effective on some defenses which display gradient masking. However, we observe that the proposed method is robust against all such attacks, with the lowest accuracy being attained on the AutoAttack ensemble.

Furthermore, we evaluate the model on PGD 50-step attack run with 1000 restarts. We do indeed confirm that the robust accuracy saturates with increasing restarts, with the final accuracy still being higher than that achieved on AutoAttack. Lastly, we observe that the PGD-1000 attack is weaker than other attacks, confirming that the accuracy does not continually decrease as the number of steps used in the attack increases. Thus, we observe that the proposed approach is robust against a diverse set of attack methods, thereby confirming the absence of gradient masking and that the model is truly robust.