LEARNING DATA-DERIVED PRIVACY PRESERVING REPRESENTATIONS FROM INFORMATION METRICS

ABSTRACT

It is clear that users should own and control their data and privacy. Utility providers are also becoming more interested in guaranteeing data privacy. Therefore, users and providers can and should collaborate in privacy protecting challenges, and this paper addresses this new paradigm. We propose a framework where the user controls what characteristics of the data they wants to share (utility) and what they want to keep private (secret), without necessarily asking the utility provider to change its existing machine learning algorithms. We first analyze the space of privacy-preserving representations, and derive natural information-theoretic bounds on the utility-privacy trade-off when disclosing a sanitized version of the data X. We present explicit architectures to learn privacy-preserving representations that approach this bound in a data-driven fashion. We then describe important use-case scenarios where the utility providers are willing to collaborate, at least partially, with the sanitization process. In this setting, we limit the possible sanitization functions to *space-preserving* transformations, meaning the sanitation maps the data to the same space as the original data, and the utility provider can then use the exact same (existing) algorithm for the original and sanitized data, a novel critical attribute to help service providers to collaborate. We illustrate this framework and show how we can maintain utility while protecting secret information even in cases where the joint distribution of the data X and the utility and secret variables U and S are unknown; and where the difficulty of inferring the utility variable U is much higher than the task of inferring the secret variable S. This is done through the implementation of three use cases; *subject-within-subject*, where we tackle the problem of having an identity detector (from facial images) that works only on a consenting subset of users, an important application, for example, for mobile devices activated by face recognition, helping them to become private to the environment instead of always "listening" as they currently act; *gender-and-subject*, where we want to preserve facial verification (hard) while hiding the gender attribute (easy) for users who choose to do so; and *emotion-and-gender*, where we tackle the issue of hiding independent variables, as is the case of hiding gender while preserving emotion detection.

1 INTRODUCTION, CHALLENGES, AND CONTRIBUTIONS

Individuals are sharing vast amounts of data on a daily basis; at the same time, advances in machine learning mean that service providers that receive this user data can infer increasingly more sensitive attributes about their users. Care must be taken to provide an appropriate protection for users in order to adhere to various privacy, legal, and ethical constraints. Critical to this is the capability of finding effective privacy-preserving data representations in a data-driven manner that are able to accommodate each user's individual needs. It is also in the interest of the utility provider to at least partially collaborate in this endeavor, and the privacy-preserving data representation should be made to account for data processing pipelines that are already in place. It would be impractical to tackle many of the privacy-preserving challenges today using model-based approaches, a data-driven approach is essential in allowing privatization mechanisms to keep up with new applications.

Each user should have the ability to define, at any given time, sensitive and non-sensitive information associated with their data; we propose that a user and the service provider *collaborate* towards achieving *user-specific* privacy. This results in a system where the user sanitizes the data, at the

sensing and/or transmitting stage, if they desire to do so, without affecting the utility they need; at the same time, the provider can use the same processing pipeline for both sanitized and non-sanitized data. This is essential to make sure the system can scale to accommodate for various users with possibly very different privacy preferences.

An example addressed by the proposed framework is to block, even at the sensor level, a device from constantly "listening." For example, mobile devices scan images until they detect the owner, and then they open. But all images not from the owner should be private, not even understood by the face recognition system. The proposed framework will make such devices not to understand the data until the visual or sound trigger is detected, with the capability to do this at the sensor level and without modifying the existing in device recognition system.

This proposed new paradigm of collaborative privacy environment is critical since it has also been shown once and again that, e.g., algorithmic or data augmentation and unpredictable correlations, can easily break privacy Israel et al. (2014); Narayanan & Shmatikov (2008); Oh et al. (2016); Reuben et al. (2016). The impossibility of universal privacy protection has also been studied extensively in the domain of differential privacy Dwork (2008), where a number of authors have shown that assumptions about the data or the adversary must be made in order to be able to provide utility Dwork & Naor (2010); Hardt et al. (2016); Kifer & Machanavajjhala (2011; 2014). We can, however, minimize the amount of privacy we are willing to sacrifice for a given level of utility. Other recent data-driven privacy approaches like Wu et al. (2018) have also explored this notion, but do not, to out knowledge, integrate the additional collaborative constraints.

Therefore, given each individual user specific privacy requirements, it is important to design collaborative systems where each user shares a sanitized version of their data with the service provider in such a way that user-defined non-sensitive tasks can be performed but user-defined sensitive ones cannot, without the service provider requiring to change any data processing pipeline otherwise.

Contributions- We consider a scenario where a user wants to share a sanitized representation of data X in a way that a latent variable U can be inferred, but a sensitive latent variable S remains hidden. We formalize this notion using privacy and transparency definitions. We derive an information-theoretic bound on privacy-preserving representations. The metrics induced by this bound are used to learn such a representation directly from data, without prior knowledge of the joint distribution of the observed data X and the latent variables U and S. This process can accommodate for several user-specific privacy requirements, and can be modified to incorporate constraints about the service provider's existing utility inference algorithms.

We apply this framework to challenging use cases such as hiding gender information from a facial image (a relatively easy task) while preserving subject verification (a much harder task), or designing a sanitization function that preserves subject identification on a consenting subset of users, while disallowing it on the general population (thereby blocking the device from constantly "listening"). Blocking a simpler task while preserving a harder one and blocking a device from constantly listening out-of-sample data are new applications in this work, here addressed with theoretical foundations and respecting the provider's existing algorithms, which can simultaneously handle sanitized and non-sanitized data.

The problem statement is detailed in Section 2, and the information-theoretic bounds are derived in Section 3. Section 4 defines a trainable adversarial game that directly attempts to achieve this bound; the section also discusses how service-provider specific requirements can be incorporated. Examples of this framework are shown in Section 5. The paper is concluded in Section 6. Complementary information and proofs is presented in the Supplementary Material .

2 PROBLEM STATEMENT

We describe a scenario in which we have access to possibly high-dimensional data $X \in \mathcal{X}$, this data depends on two special latent variables U and S. U is called the utility latent variable, and is a variable we want to communicate, while S is called the secret, and is a variable we want to protect. We consider two agents, a service provider that wants to estimate U from X, and an actor that wants to infer S from X.

We define a third agent, the privatizer, that wants to learn a space-preserving stochastic mapping $Q : \mathcal{X} \to \mathcal{Q} \supset \mathcal{X}$ in such a way that $Q(X)$ provides information about the latent variable U, but provides relatively little information of S. In other words, we want to find a data representation that is private with respect to S and transparent with respect to U.[1]

We first recall the definition of privacy presented in Kifer (2009):

Definition 2.1. Privacy: Let δ_s be a measure of distance between probability distributions, $b_s \in \mathcal{R}^+$ a positive real number, and $P(S)$ the marginal distribution of the sensitive attribute S. The stochastic mapping $Q(X)$ is (δ_s, b_s)-private with respect to S if $\delta_s(P(S), P(S|Q(X))) < b_s$.

We can define transparency in the same fashion:

Definition 2.2. Transparency: Let δ_u be a measure of distance between probability distributions, $b_u \in \mathcal{R}^+$ a positive real number, and $P(U|X)$ the posterior conditional distribution of the utility variable U after observing X. The stochastic mapping $Q(X)$ is (δ_u, b_u)-transparent with respect to U if $\delta_u(P(U|X), P(U|Q(X))) < b_u$.

Both definitions depend on the learned mapping Q; in the following section, we derive an information-theoretic bound between privacy and transparency, and show that this bound infers a particular choice of metrics δ_u, δ_s. We then show that this inferred metric can be directly implemented as a loss function to learn privatization transformations from data using standard machine learning tools.

A similar analysis of these bounds for the special case where we directly observe the utility variable U ($X = U$) was analyzed in Calmon et al. (2015) in the context of the Privacy Funnel. Here, we extend this to the more general case where U is observed indirectly. More importantly, these bounds are used to design a data-driven implementation for learning privacy-preserving mappings.

3 INFORMATION-THEORETIC BOUNDS ON PRIVACY

Consider the utility and secret variables U and S defined over discrete alphabets $\mathcal{U}, \mathcal{S}$, and the observed data variable X, defined over $\mathcal{X}$, with joint distribution $P_{X,U,S}$. Figure 1a illustrates this set-up, and shows the fundamental relationship of their entropies $H(\cdot)$ and mutual information.

(a)   (b)

Figure 1: Left of figure (a) shows the dependency graph of the observed variable X and the latent utility and secret variables U and S. Right of figure (a) shows a Venn diagram illustrating conditional mutual informations I that provide constraints on the performance of any sanitization mapping $Q(X)$. Left of figure (b) extends the dependency graph to show the sanitized data $Q(X)$ in red. Right of figure (b) shows that the information leakage $I(S; Q(X))$ and censured information $I(U; X \mid Q(X))$ shown in red and blue respectively cannot be simultaneously set to 0, since they are partially at odds.

We analyze the properties of any mapping $Q : \mathcal{X} \to \mathcal{Q}$, and measure the resulting mutual information between the transformed variable $Q(X)$ and our quantities of interest. Our goal is to find Q such that the information leakage from our sanitized data $I(S; Q(X))$ is minimized, while maximizing the shared information of the utility variable $I(U; Q(X))$. We will later relate these quantities and the bounds here developed with the privacy/utility definitions presented in the previous section.

Maximizing $I(U; Q(X))$ is equivalent to minimizing $I(U; X \mid Q(X))$, since $I(U; X|Q(X)) = I(U; X) - I(U; Q(X))$. The quantity $I(U; X \mid Q(X))$ is the information X contains about U that is censured by the sanitization mapping Q.

---

[1]Note that stochastic mappings are a natural extension of deterministic sanitization mappings. Furthermore, a deterministic mapping only truly destroys information if it is non-invertible.

Figure 1b illustrates $I(S; Q(X))$ and $I(U; X|Q(X))$. One can see that there exists a trade-off area, $I(U, S) - I(U, S|X)$, that is always included in the union of $I(S; Q(X))$ and $I(U; X|Q(X))$. The lower we make $I(S; Q(X))$, the higher we make the censored information $I(U; X|Q(X))$, and vice versa. This induces a lower bound over the performance of the best possible mappings $Q(X)$ that is formalized in the following lemma.

Lemma 3.1. Let X, U, S be three discrete random variables with joint probability distribution $P_{X,U,S}$. For any stochastic mapping $Q : \mathcal{X} \to \mathcal{Q}$ we have

$$I(U; S) - I(U; S|X) \leq [I(S; Q(X)] + [I(U; X|Q(X))]. \tag{1}$$

Proof of this lemma is shown in Supplementary Material. To show that this bound is reachable in some instances, consider the following example. Let U and S be independent discrete random variables, and $X = (U, S)$. The sanitization mapping $Q(X) = U$ satisfies this bound with equality.

We can also prove, trivially, an upper bound for these quantities.

Lemma 3.2. Let X, U, S be three discrete random variables with joint probability distribution $P_{X,U,S}$. For any stochastic mapping $Q : \mathcal{X} \to \mathcal{Q}$ we have:

$$I(S; Q(X)) + I(U; X|Q(X)) \leq I(X; U, S). \tag{2}$$

That simply states that the information leakage about the secret and the censured information on the utility variable cannot exceed the total information present in the original observed variable X.

3.1 Relation With Privacy And Transparency Metrics

We relate the terms $I(S; Q(X))$ and $I(U; X \mid Q(X))$ in Eq.1 back to our definitions of privacy and transparency.

$$
\begin{aligned}
I(U; X \mid Q) &= \sum_{q,x} p(q, x) \sum_u p(u \mid x, q) log \left[\frac{p(u \mid x, q)}{p(u \mid q)} \right], \\
&= \sum_{q,x} p(q, x) \sum_u p(u \mid x) log \left[\frac{p(u \mid x)}{p(u \mid q)} \right], \\
&= E_{X,Q} \left[D_{KL}(p_{U|X} \parallel p_{U|Q}) \right].
\end{aligned}
\tag{3}
$$

Here we used the fact that U is conditionally independent of Q given X. We then observe that Eq. 3 induces the Kullback-Leibler divergence D_{KL} as a natural transparency metric δ_u in Def.2.2.

Similarly, we can analyze $I(S; Q)$ to get,

$$
\begin{aligned}
I(S, Q) &= \sum_q p(q) \sum_s p(s \mid q) log \left[\frac{p(s \mid q)}{p(s)} \right], \\
&= E_{X,Q} \left[RD_{KL}(p_S \parallel p_{S|Q}) \right].
\end{aligned}
\tag{4}
$$

We can see from Eq.4 that the natural induced metric for measuring privacy δ_s in Def,2.1 is the reverse Kullback-Leibler divergence RD_{KL}.

We can thus rewrite our fundamental tradeoff equation as

$$E_{X,Q}[RD_{KL}(p_S \parallel p_{S|Q}) + D_{KL}(p_{U|X} \parallel p_{U|Q})] \geq I(U, S) - I(U, S \mid X). \tag{5}$$

We show next how this bound can be used to define a trainable loss metric, allowing the privatizer to select different points in the transparency-privacy trade-off space.

3.2 Defining a trainable loss metric

Assume that for any given stochastic transformation mapping $Q \sim Q(X)$, we have access to the posterior conditional probability distributions $P(S \mid Q)$, $P(U \mid Q)$, and $P(U \mid X)$. Assume we also have access to the prior distribution of $P(S)$. Inspired by the bounds from the previous section, the proposed privatizer loss is

$$min_Q E_{X,Q}[(1-\alpha)D_{KL}(p_{U|X} \mid\mid p_{U|Q})^2 + \alpha R D_{KL}(p_S \mid\mid p_{S|Q})^2], \tag{6}$$

where $\alpha \in [0,1]$ is a tradeoff constant. A low α value implies a high degree of transparency, while a high value of α implies a high degree of privacy. Using Eq.5 we have a lower bound on how private or transparent the privatizer can be for any given α value, as detailed next.

Theorem 3.3. For any $\alpha \in [0,1]$, and stochastic mapping $Q : \mathcal{X} \to \mathcal{Q}$ the solution to Eq.6 guarantees the following bounds,

$$
\begin{aligned}
E_{X,Q}[D_{KL}(p_{U|X} \mid\mid p_{U|Q})] &\geq \alpha[I(U,S) - I(U,S \mid X)], \\
E_{X,Q}[R D_{KL}(p_S \mid\mid p_{S|Q})] &\geq (1-\alpha)[I(U,S) - I(U,S \mid X)].
\end{aligned}
\tag{7}
$$

The proof is shown in Supplementary Material. To recap, we proposed a privatizer loss Eq.6 with a controllable trade-off parameter α, and showed bounds on how transparent and private our data can be for any given value of α. Next we show how to optimize this utility-privacy formulation.

4 A Data-Driven implementation

Even if the joint distribution of $P(U,S,X)$ is not known, the privatizer can attempt to directly implement Eq.6 in a data-driven architecture to find the optimal Q. Assume the privatizer has access to a dataset $\{(x, s_{gt}, u_{gt})\}$, where s_{gt} and u_{gt} are the ground truth secret and utility values of observation x. Under these conditions, the privatizer searches for a mapping $\hat{Q}(X) : \hat{q} = Q(x)$, and attempts to predict the best possible attack by learning $P_{\hat{S}|\hat{Q}}(s|\hat{q})$, an estimator of $P_{S|\hat{Q}}(s \mid \hat{q})$. The privatizer also needs to estimate $P_{\hat{U}|X}(u|x)$ and $P_{\hat{U}|\hat{Q}}(u|\hat{q})$, estimators of $P_{U|X}(u \mid x)$ and $P_{U|\hat{Q}}(u \mid \hat{q})$, to measure how much information about the utility variable is censored with the proposed mapping. Under this setup Q is obtained by optimizing the following adversarial game:

$$
\begin{aligned}
P_{\hat{S}|\hat{Q}} &= max_{P_{S|\hat{Q}}} E_X[log(P_{S|\hat{Q}}(s_{gt}|\hat{q}))], \\
P_{\hat{U}|\hat{Q}} &= max_{P_{U|\hat{Q}}} E_X[log(P_{U|\hat{Q}}(u_{gt}|\hat{q}))], \\
P_{\hat{U}|X} &= max_{P_{U|X}} E_X[log(P_{U|X}(u_{gt}|x))], \\
\hat{Q} &= min_Q E_X[(1-\alpha)D_{KL}(p_{\hat{U}|X} \mid\mid p_{\hat{U}|Q})^2 + \alpha R D_{KL}(p_S \mid\mid p_{\hat{S}|Q})^2].
\end{aligned}
\tag{8}
$$

4.1 Privacy Under Fixed Utility Inference

The proposed framework naturally provides a means to achieve collaboration from the utility provider. In this scenario, the utility provider wishes to respect the user's desired privacy, but is unwilling to change their estimation algorithm $P_{\hat{U}|X}$, and expects the privatizer to find a mapping that minimally affects its current performance.[2] This is a more challenging scenario, with worse tradeoff characteristics, in which $\hat{Q}$ is obtained by optimizing

$$
\begin{aligned}
P_{\hat{S}|\hat{Q}} &= max_{P_{S|\hat{Q}}} E_X[log(P_{S|\hat{Q}}(s_{gt}|\hat{q}))], \\
\hat{Q} &= min_Q E_X[(1-\alpha)D_{KL}(p_{\hat{U}|X} \mid\mid p_{\hat{U}|X}))^2 + \alpha R D_{KL}(p_S \mid\mid p_{\hat{S}|Q})^2].
\end{aligned}
\tag{9}
$$

---

[2]Recall that the utility provider wants to use the same algorithm for sanitized and non-sanitized data, a unique aspect of the proposed framework and critical to accept its collaboration.

4.2 PRIVACY UNDER FIXED UTILITY AND SECRET INFERENCE

A final scenario addressed by the proposed framework arises when the utility provider is the sole agent to access the sanitized data, and it has estimation algorithms for both the utility and the privacy variable $P_{\hat{U}|X}, P_{\hat{S}|X}$, that it is unwilling to modify. The service provider wishes to reassure the users that they are unable to infer the secret attribute from the sanitized data, if and when the user decides so. Under these conditions, we optimize for

$$\hat{Q} = min_Q E_X[(1 - \alpha)D_{KL}(p_{\hat{U}|X} \parallel p_{\hat{U}|X}))^2 + \alpha R D_{KL}(p_S \parallel p_{\hat{S}|Q})^2]. \tag{10}$$

5 EXPERIMENTS AND RESULTS

The following examples are based on the framework presented in Figure 2. Here we have the three key agents mentioned before: (1) the utility algorithm that is used by the provider to estimate the information of interest. This algorithm can take the raw data (X) or the mapped data $(Q(X))$ and be able to infer the utility; (2) the secret algorithm that is able to operate on the raw data and the mapped data to infer the secret; (3) the privatizer that learns a space preserving mapping Q that allows the provider to learn the utility but prevents the secret algorithm to infer the secret. Initially we assume that the secret algorithm is not specifically tailored to attack the proposed privatization, but instead is a robust commonly used algorithm trained on raw data to infer the secret. The algorithm used to estimate the utility shares this characteristic. In the next examples we show how the proposed framework performs under different scenarios.

Figure 2: Three components of the collaborative privacy framework. Raw data can be directly fed into the secret and utility inferring algorithm. Since the privatization mapping is space preserving, the privatized data can also be directly fed to both tasks without any need for further adaptations.

5.1 SUBJECT WITHIN SUBJECT

We begin by analyzing the *subject-within-subject* problem. Imagine a subset of users wish to unlock their phone using facial identification, while others opt instead to verify their right to access the phone using other methods; in this setting, we would wish the face identification service to work only on the consenting subset of users, but to respect the privacy of the remaining users. We additionally assume that the utility provider wishes to comply with the user's wishes, so we can apply the framework described in Section 4.2. Note that in this problem, the utility and secrecy variables are not independent, but they are mutually exclusive.

We show the feasibility of a solution to this problem by training a space-preserving stochastic mapping Q on facial image data X, where the utility variable U is a categorical variable over the consenting users, and the secrecy variable S is a categorical variable over the non-consenting users. We test this over the FaceScrub dataset Kemelmacher-Shlizerman et al. (2016), using VGGFace2 Cao et al. (2017) as the base utility and secrecy inferring algorithm. The stochastic mapping was implemented using a stochastic adaptation of the UNET Ronneberger et al. (2015), where a Gaussian noise variable is learned along the image transformation, and is then injected before the upsampling stages.

Table 1 shows the top-5 categorical accuracy of the utility network over the sanitized data at various α points in the privacy-utility trade-off. Figure 3 show some representative images on how images are sanitized.

We can see from Table 1 that the sanitization function is able to preserve information about the utility variable while effectively censoring the secret variable. This performance extends to unobserved

		Top-5 Accuracy	
α	CU	OPU	UPU
0	99.8%	99.8%	99.8%
0.3	94.7%	86.1%	87.5%
0.35	93.5%	15.3%	33.6%
0.40	93.0%	14.9%	31.8%
0.45	89.4%	12.6%	30.2%
0.50	70.7%	10.9%	27.0%

(a) Filtered images of consenting users (CU)

(b) Filtered images of private users (PU)

Table 1: Subject detection on users

Figure 3: Left and center figures show images of consenting and nonconsenting (private) users respectively, along with their sanitized counterparts. The identity of consenting users is still easily verified, while the identity of nonconsenting users is effectively censored. The sanitization function learned to do so while preserving the representation space. Table on the right shows Top-5 accuracy performance of the subject detector after sanitization across several sanitation levels α. Performance is shown across 3 subsets, consenting users (CU) are users that decided to be detected by the utility algorithm, observed private users (OPU) are those that explicitly decided to protect their privacy, while unobserved private users (UPU) are users that decided to protect their privacy but where not available during training. Consenting users are still recognized by the system, while nonconsenting users are not. For example, for $\alpha = 0.4$, we significantly block OPU and UPU while preserving CU

images of the consenting subjects, and to unobserved images of non-consenting subjects that were not used to train the sanitization.

5.2 OBFUSCATING EMOTION WHILE PRESERVING GENDER

Here we continue to work on facial image data X, where utility variable U is gender recognition, and the secret variable S is emotion (smiling/non-smiling). In this scenario, variables U and S are independent. We implement this over the CelebA dataset Liu et al. (2015), using Xception networks Chollet (2017) as our utility and privacy estimators. Table.2 shows the distribution of the utility and secrecy estimators over the sanitized data. Figure 4 shows example sanitized images. It is visually possible to identify the gender of the subject but not their emotion. Most importantly, the existing gender detection algorithm still performs correctly over the sanitized images.

Inference	Data	Male	Female
Gender	Raw	94.2%	94.5%
	Sanit.	91.2%	96.1%
Emotion	Raw	93.3%	92.0%
	Sanit.	54.0%	60.0%

Table 2: Gender and emotion detection on users on raw and sanitized data.

Figure 4: Images before and after sanitization for Gender (utility) vs Emotion (privacy).

5.3 SUBJECT PRESERVATION AND GENDER OBFUSCATION

In this setup, we want to find a mapping Q that hides the gender attribute but allows subject verification. The mapping Q should prevent a standard gender detection algorithm from performing its task, while allowing a standard subject detector algorithm to still perform subject verification.

To realize this constrained scenario, we used a WideResNet-based Zagoruyko & Komodakis (2016) implementation of DEXNet Rothe et al. (2018) as our gender detector adversary, and a ResNet-50 implementation of VGGface2 Cao et al. (2017) as a subject identifier. The stochastic mapping was implemented using two differing architectures, the first is a stochastic adaptation of the UNET Ronneberger et al. (2015), and the second a concatenation of a FaderNet Lample et al. (2017) and a UNET Ronneberger et al. (2015) as shown in Bertran et al. (2018).

The mapping that incorporates a pretrained FaderNet was chosen as the baseline for the stochastic mapping function since this network is already trained to defeat a gender discriminator in its *en-*

coding space. This proves a suitable baseline comparison and starting point for a mapping function that needs to fool a gender discriminator *in image space* while simultaneously preserving subject verification performance. We show the performance of using only the pretrained gender FaderNet and demonstrate how we can improve its performance by training a posterior processing mapping (UNET) using the loss proposed in Eq.10.

We tested this framework on the FaceScrub dataset Ng & Winkler (2014). Figures in 5 shows how the output probabilities of the gender classification model approach the prior distribution of the dataset as α increases. We see that images from both female and male subjects produce output gender probabilities close to the dataset prior even for relatively low α values. Last column of figure 5 shows how the top-5 categorical accuracy of the subject verification task varies across different α values. These results suggest that under these conditions we can achieve almost perfect privacy while maintaining reasonable utility performance.

(a) $P(s(Q(x)) = M|s(x) = F, \alpha)$, Stochastic UNET model

(b) $P(s(Q(x)) = M|s(x) = M, \alpha)$, Stochastic UNET model

(c) Top-5 Categorical accuracy, Stochastic UNET model

(d) $P(s(Q(x)) = M|s(x) = F, \alpha)$, FaderNet-UNET model

(e) $P(s(Q(x)) = M|s(x) = M, \alpha)$, FaderNet-UNET model

(f) Top-5 Categorical accuracy, FaderNet-UNET model

Figure 5: First two columns show computed gender probabilities on the sanitized data $Q(X)$ as a function of α, results are split according to real gender (M:Male, F:Female). Whisker plots show median and interquartile ranges, with outliers shown as circles. The baseline of simply using the pretrained FaderNet sampler is also shown for comparison. Third column shows the top-5 categorical accuracy of the subject recognition task as a function of α. Each row correspond to the Stochastic UNET and FaderNet-UNET models. The baseline of simply using the pretrained FaderNet sampler is also shown for comparison. Note that the concatenation the UNET with the FaderNet is able to improve performance on the Top-5 categorical accuracy metric when compared to the baseline model.

6 CONCLUDING REMARKS

Inspired by information-theory bounds on the privacy-utility trade-off, we introduced a new paradigm where users and entities collaborate to achieve both utility and privacy per a user's specific requirements. One salient feature of this paradigm is that it can be completely transparent – involving only the use of a simple user-specific privacy filter applied to user data – in the sense that it requires otherwise no modifications to the system infrastructure, including the service provider algorithmic capability, in order to achieve both utility and privacy.

Representative architectural and system concepts, and results, suggest that such a collaborative based user-controlled privacy approach can be achieved. While the results here presented clearly show the potential of this approach, much has yet to be done, of particular note is extending this approach to continuous utility and privacy variables. While the underlying framework still holds, measuring Kullback-Leibler distances between continuous variables is a more challenging task to directly integrate and optimize for.

REFERENCES

Martin Bertran, Natalia Martinez, Afroditi Papadaki, Qiang Qiu, Miguel Rodrigues, and Guillermo Sapiro. Learning to collaborate for user-controlled privacy. *arXiv preprint arXiv:1805.07410*, 2018.

Flavio P Calmon, Ali Makhdoumi, and Muriel Médard. Fundamental limits of perfect privacy. In *Information Theory (ISIT), 2015 IEEE International Symposium on*, pp. 1796–1800. IEEE, 2015.

Qiong Cao, Li Shen, Weidi Xie, Omkar M Parkhi, and Andrew Zisserman. VGGFace2: A dataset for recognising faces across pose and age. *arXiv preprint arXiv:1710.08092*, 2017.

François Chollet. Xception: Deep learning with depthwise separable convolutions. *arXiv preprint*, pp. 1610–02357, 2017.

Cynthia Dwork. Differential privacy: A survey of results. In *International Conference on Theory and Applications of Models of Computation*, pp. 1–19. Springer, 2008.

Cynthia Dwork and Moni Naor. On the difficulties of disclosure prevention in statistical databases or the case for differential privacy. *Journal of Privacy and Confidentiality*, 2(1), 2010.

Moritz Hardt, Eric Price, and Nathan Srebro. Equality of opportunity in supervised learning. *Advances in Neural Information Processing Systems (NIPS)*, pp. 3315–3323, October 2016.

Salomon Israel, Avshalom Caspi, Daniel W Belsky, HonaLee Harrington, Sean Hogan, Renate Houts, Sandhya Ramrakha, Seth Sanders, Richie Poulton, and Terrie E Moffitt. Credit scores, cardiovascular disease risk, and human capital. *Proceedings of the National Academy of Sciences*, 111(48):17087–17092, 2014.

Ira Kemelmacher-Shlizerman, Steven M Seitz, Daniel Miller, and Evan Brossard. The megaface benchmark: 1 million faces for recognition at scale. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4873–4882, 2016.

Daniel Kifer. Attacks on privacy and definetti's theorem. In *Proceedings of the 2009 ACM SIGMOD International Conference on Management of data*, pp. 127–138. ACM, 2009.

Daniel Kifer and Ashwin Machanavajjhala. No free lunch in data privacy. *ACM SIGMOD International Conference on Management of data*, pp. 193–204, 2011.

Daniel Kifer and Ashwin Machanavajjhala. Pufferfish: A framework for mathematical privacy definitions. *ACM Transactions on Database Systems*, 39(1):3:1–3:36, 2014.

G Lample, N Zeghidour, N Usunier, A Bordes, L Denoyer, and M Ranzato. Fader networks: Manipulating images by sliding attributes. *Advances in Neural Information Processing Systems (NIPS)*, 2017.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of International Conference on Computer Vision (ICCV)*, 2015.

Arvind Narayanan and Vitaly Shmatikov. Robust de-anonymization of large sparse datasets. *IEEE Symposium on Security and Privacy*, pp. 111–125, 2008.

HW Ng and S Winkler. A data-driven approach to cleaning large face datasets. *IEEE International Conference on Image Processing (ICIP)*, pp. 343–347, 2014.

Seong Joon Oh, Rodrigo Benenson, Mario Fritz, and Bernt Schiele. Faceless person recognition; Privacy implications in social media. *European Conference on Computer Vision (ECCV)*, pp. 19–35, 2016.

Aaron Reuben, Terrie E Moffitt, Avshalom Caspi, Daniel W Belsky, Honalee Harrington, Felix Schroeder, Sean Hogan, Sandhya Ramrakha, Richie Poulton, and Andrea Danese. Lest we forget: comparing retrospective and prospective assessments of adverse childhood experiences in the prediction of adult health. *Journal of Child Psychology and Psychiatry*, 57(10):1103–1112, 2016.

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pp. 234–241. Springer, 2015.

Rasmus Rothe, Radu Timofte, and Luc Van Gool. Deep expectation of real and apparent age from a single image without facial landmarks. *International Journal of Computer Vision*, 126(2-4): 144–157, 2018.

Zhenyu Wu, Zhangyang Wang, Zhaowen Wang, and Hailin Jin. Towards privacy-preserving visual recognition via adversarial training: A pilot study. *arXiv preprint arXiv:1807.08379*, 2018.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *arXiv preprint arXiv:1605.07146*, 2016.

7 SUPPLEMENTARY MATERIAL

Proof. Lemma 1

Consider the equality

$$I(U;S) - I(U;S|X) = I(S;Q(X)) - I(S;Q(X)|U) \\ + I(U;X|Q(X)) - I(U;X|Q(X),S). \tag{11}$$

We know that

$$0 \leq I(S;Q(X)|U) \leq I(S;Q(X)), \quad 0 \leq I(U;X|Q(X),S) \leq I(U;X|Q(X)), \tag{12}$$

so we can guarantee

$$I(U;S) - I(U;S|X) \leq I(S;Q(X)) + I(U;X|Q(X)). \tag{13}$$

□

Proof. Theorem 3.3

Consider

$$A_Q = E_{X,Q}[D_{KL}(p_{U|X} \,||\, p_{U|Q})], \\ B_Q = E_{X,Q}[D_{KL}(p_{U|X} \,||\, p_{U|Q})], \tag{14} \\ K = I(U,S) - I(U,S \mid X),$$

and $\alpha \in [0,1]$.

Minimizing Eq.6 respecting Eq.5 and Eq.12 is equivalent to solving:

$$min_Q\{(1-\alpha)A_Q^2 + \alpha B_Q^2\}, \\ s.t. A_Q, B_Q \geq 0, \tag{15} \\ A_Q + B_Q \geq K, \\ \alpha \in [0,1],$$

,

Consider the following relaxation of Eq.15

$$min_{A,B}\{(1-\alpha)A^2 + \alpha B^2\}, \\ s.t. A, B \geq 0, \tag{16} \\ A + B \geq K, \\ \alpha \in [0,1],$$

where A and B are positive real values. Eq.16 is a relaxation of Eq.15 because the space of possible tuples (A_Q, B_Q) is included in the space of possible values of R^{2+}

Suppose Q^* is the solution to Eq.15, with corresponding values (A_{Q^*}, B_{Q^*}), and suppose (A^*, B^*) is the solution to Eq. 16. We know

$$(1-\alpha)A^{*2} + \alpha B^{*2} \leq (1-\alpha)A_{Q^*}^2 + \alpha B_{Q^*}^2, \tag{17}$$

Assume $A^* > A_{Q^*}$, it follows that $(1-\alpha)A_{Q^*} + \alpha B^{*2} \leq (1-\alpha)A^{*2} + \alpha B^{*2}$.

However, $A_{Q^*} > 0$ and $A_{Q^*} + B^* \leq A^* + B^* \leq K$. Therefore, (A_{Q^*}, B^*) is a valid solution to Eq.16, and is smaller than the lower bound (A^*, B^*).

This contradiction arises from assuming $A^* > A_{Q^*}$, we thus conclude that

$$A^* \le A_{Q^*}.$$

Similarly for B^* and B_{Q^*} we get

$$B^* \le B_{Q^*}.$$

Additionally, Eq.16 is easily solvable and has solutions

$$A^* = \alpha K; \qquad B^* = (1 - \alpha)K \qquad (18)$$

Consequently, we proved

$$
\begin{aligned}
E_{X,Q}[D_{KL}(p_{U|X} \parallel p_{U|Q})] &\ge \alpha[I(U, S) - I(U, S \mid X)], \\
E_{X,Q}[RD_{KL}(p_S \parallel p_{S|Q})] &\ge (1 - \alpha)[I(U, S) - I(U, S \mid X)].
\end{aligned}
\qquad (19)
$$

$\square$