Real-world Video Adaptation with Reinforcement Learning

Hongzi Mao [1 2] **Shannon Chen** [2] **Drew Dimmery** [2] **Shaun Singh** [2] **Drew Blaisdell** [2] **Yuandong Tian** [2]
Mohammad Alizadeh [1] **Eytan Bakshy** [2]

Abstract

Client-side video players employ adaptive bitrate (ABR) algorithms to optimize user quality of experience (QoE). We evaluate recently proposed RL-based ABR methods in Facebook's web-based video streaming platform. Real-world ABR contains several challenges that requires customized designs beyond off-the-shelf RL algorithms — we implement a scalable neural network architecture that supports videos with arbitrary bitrate encodings; we design a training method to cope with the variance resulting from the stochasticity in network conditions; and we leverage constrained Bayesian optimization for reward shaping in order to optimize the conflicting QoE objectives. In a week-long worldwide deployment with more than 30 million video streaming sessions, our RL approach consistently outperforms the existing carefully-tuned ABR algorithm.

1. Introduction

The volume of video streaming traffic has been rapidly growing in the recent years (Cisco, 2016; Sandvine, 2015), reaching almost 60% of all the Internet traffic (Sandvine, 2018). Meanwhile, there has been a steady rise in user demands on video quality — viewers quickly leave the video sessions with insufficient quality, leading to significant losses in revenue for content providers (Dobrian et al., 2011). As a result, content providers are striving to improve the video quality they deliver to the users (Krishnan & Sitaraman, 2012).

Adaptive bitrate (ABR) algorithms are a primary tool that content providers use for optimizing video quality. These algorithms run on client-side video players and dynamically choose a bitrate for each video chunk (e.g., 2-second block), based on network and video observations such as network throughput measurements and playback buffer occupancy. Their goal is to optimize the video's quality of experience (QoE) by adapting the video bitrate to the underlying network conditions. However, designing a strong ABR algorithm with hand-tuned heuristics is difficult, mainly due to hard-to-model network variations and hard-to-balance conflicting video QoE objectives (e.g., large bitrate vs. minimal stalls) (Yin et al., 2015).

Facing these difficulties, recent studies have considered using reinforcement learning (RL) as a data-driven approach to automatically optimize the ABR algorithms (Mao et al., 2017). RL optimizes its control policy based on the actual performance of past choices, and it is able to discover policies that outperform algorithms that rely on fixed heuristics or use inaccurate system models. For example, as explained in Mao et al. (2017), RL methods can learn how much playback buffer is necessary to mitigate the risk of stall in a specific network, based on the network's inherent throughput variability. In controlled experiments with a fixed set of videos and network traces, a number of prior work has shown promising results for RL methods (van der Hooft et al.; Claeys et al., 2013). However, it remains unknown how the RL-based methods compare to the already deployed heuristic-based ABR methods in large-scale, real-world settings, where generalization and robustness are crucial for good performance (Systems & Research, 2019).

In this paper, we present the deployment experience of *ABRL*, an RL-based ABR module in Facebook's production web-based video platform. In our design of ABRL, we find that off-the-shelf RL methods are not sufficient to solve the challenges we encounter in the production systems. To learn high-quality ABR algorithms that surpass the deployed heuristics, we had to design new components in ABRL's learning procedure to solve the following challenges.

First, videos in production have different available bitrate encodings, e.g., some videos only have HD/SD encodings, while other videos have a full spectrum of bitrate encodings. However, standard RL approaches use neural networks (Hagan et al., 1996) that provide fixed outputs both in the number of bitrates and the corresponding bitrate levels (e.g., the third output always corresponds to 720P encoding). To represent arbitrary bitrate encodings, we design ABRL's

---

[1]MIT Computer Science and Artificial Intelligence Laboratory [2]Facebook. Correspondence to: Hongzi Mao <hongzi@mit.edu>, Eytan Bakshy <ebakshy@fb.com>.

Reinforcement Learning for Real Life (RL4RealLife) Workshop in the 36th International Conference on Machine Learning, Long Beach, California, USA, 2019. Copyright 2019 by the author(s).

neural network to output a *single* priority value for each bitrate encoding; and we repeatedly use the same copy of the neural network for all encodings of a video. This approach scales to any video ABRL serves and supports end-to-end RL training (§3.2).

Second, ABRL experiences a wide variety of network conditions and different video durations during training. This introduces undesirable variance since conventional RL training algorithms cannot tell whether the observed QoE feedback of two ABR decisions differs due to disparate network conditions, or due to the quality of the learned ABR policy. To cope with the stochasticity of network conditions, we isolate the rewards on the actual network trace experienced in a training session, using a recent technique for RL in environments with stochastic input processes (Mao et al., 2019). This approach separates the contributions of the ABR policy from the overall feedback, enabling ABRL to learn robust policies across different deployment conditions (§3.3).

Third, production ABR requires balancing and co-optimizing multiple objectives together (e.g., maximize bitrate and minimize stalls). But RL requires a single reward value as the training feedback. Prior work merges the multi-dimensional objectives with a weighted sum (Yin et al., 2015). In practice, since ABRL's goal is to outperform the existing ABR algorithm in every dimension of the objective, this does not amount to a specific, pre-defined tradeoff between different objectives. To determine the weights for different reward components, we formulate the multi-objective optimization problem as a constrained optimization problem (i.e., optimizing one dimension subject to bounded degradation on other dimensions). This allows us to use constrained Bayesian optimization (Snoek et al., 2012; Gardner et al., 2014; Letham et al., 2018) to efficiently search for the proper weights (§3.4).

Lastly, for ease of understanding and ensuring safety, we translate ABRL's learned ABR policy into an interpretable form for deployment. Specifically, we realize from the policy visualization that the learned ABR algorithm exhibits approximately linear behavior in the observed state of network and buffer occupancy. Thus, we fit a linear function of network throughput and buffer occupancy to approximate ABRL's learned ABR policy (§3.5). Such translation degrades the average stall rate by 0.8% but provides full interpretability for human engineers. This allows engineers to understand the system behavior well enough to debug it before deployment.

We run A/B tests that compare ABRL with the existing carefully-tuned ABR algorithm on Facebook's web-based video streaming platform. In a week-long worldwide deployment with more than 30 million video streaming sessions (§4), ABRL outperforms the heuristic-based ABR policy by 1.6% in average bitrates and 0.4% in stall time. For video

sessions with poor network connections, in which cases the ABR task is more challenging, ABRL provides 5.9% higher bitrate and 2.4% fewer stalls. For Facebook, even a small improvement in video QoE is substantial given the scale of its video platform, which consists of millions of hours of video watches per day (Wagner, 2016). In this scale, a tenth of a percent consistent reduction in video buffering is considered significant; each day, this would save years of video loading time in aggregate.

2. Background

We provide a review of the basic concepts of adaptive video streaming over HTTP. Videos are stored as multiple chunks, each of which represents a few seconds of video playback. Each chunk is encoded at several discrete bitrates, where a higher bitrate implies a higher resolution and thus a larger chunk size. The chunks are aligned for seamless transitions across bitrates, i.e., video players can switch bitrates at any chunk boundary without fetching redundant bits or skipping parts of the video.

When a client watches a video, the video provider initially sends the client a manifest file that directs the client to a specific source (e.g., a CDN) hosting the video and lists the available bitrates for the video. The client then requests video chunks one by one, using an *adaptive bitrate (ABR) algorithm*. These algorithms use a variety of different inputs (e.g., playback buffer occupancy, throughput measurements, etc.) to select the bitrate for future chunks. As chunks are downloaded, they are stored in the playback buffer on the client. Playback of a given chunk cannot begin until the entire chunk has been downloaded. In our experiments (§4), we deploy ABRL on Facebook's web-based (rather than mobile) video streaming platform, primarily because it has the fastest codebase update cycle.

3. Design

In this section we describe the design of ABRL, a system that generates RL-based ABR policies to deploy in Facebook's production video platform. We start by describing the simulator that hosts RL training in the backend (§3.1). Next, we explain the RL training framework (§3.2), which includes the variance reduction (§3.3) and reward shaping (§3.4) techniques needed for this application. Finally, we describe how ABRL translates the learned ABR policy to deploy in the front end (§3.5). Figure 1 shows an overview.

3.1. Simulator

To train the ABR agent with RL, we first build a simulator that models the playback buffer dynamics during video streaming. The buffer dynamics are governed by the standard ABR procedure described in §2. Specifically, the sim-

Figure 1. Design overview. For each video session in the production experiment, ABRL collects the experience of video watch time and the network bandwidth measurements and predictions. It then simulates the buffer dynamics of the video streaming using these experiences in the backend. After RL training, ABRL deploys the translated ABR model to the user front end.

ulator maintains an internal representation of the client's playback buffer, which includes the current size of buffer and the buffer capacity. The simulator invokes the ABR logic at each video chunk download event, where the ABR logic dictates the bitrate decision for the next chunk. For each chunk download, the simulator determines the download time based on the file size of the video chunk and the network throughput from the traces. Since the video is played in real time, the simulator then drains the playback buffer by the download time of the current chunk representing the video playback during the download. If the size of current playback buffer is smaller than the download time, we empty the buffer and issue a stall event. Subsequently, the buffer adds the duration of the downloaded chunk into the playback buffer. In the case where the buffer exceeds the capacity, the simulator ticks the time forward in the trace without downloading any chunk (i.e., move forward in the bandwidth trace). The simulated video session terminates at the end of each trace (corresponding to the end of a watch). During training, ABRL repeats the simulated video sessions by loading traces randomly at each time.

The simulator harnesses the traces collected from the actual video sessions from the front end. At each video chunk download event for an experiment group of video sessions, we log to the backend a tuple of (1) network bandwidth estimation, (2) bandwidth measurement for the previous chunk download, (3) the elapsed time of downloading the previous chunk and (4) the file sizes corresponding to different bitrate encodings of the video chunk. The bandwidth estimation is an output from a Facebook networking module. Note that the length of the trace varies naturally across different video sessions due to the difference in the watch time. In our training (§3.2), we use more than 100,000 traces from video streaming sessions in production.

3.2. Reinforcement Learning

The training setup shown in Figure 2 follows the standard RL framework. In this section, we describe the details of the RL agent and the policy gradient training algorithm.

Figure 2. Backend RL training framework. ABRL updates the ABR policy neural network by observing the outcome when interacting with a simulator. The simulator uses production traces to simulate the video buffer dynamics.

In particular, we explain the challenges we encountered to motivate the variance reduction (§3.3) and the reward shaping (§3.4) techniques.

RL setup. Upon downloading each video chunk at each step t, the RL agent observes the *state* $s_t = (x_t, o_t, \vec{n}_t)$, where x_t is the bandwidth prediction for the next chunk, o_t is the current buffer occupancy and $\vec{n}_t$ is a vector of the file sizes for the next video chunk. As a feedback for the bitrate *action* a_t, the agent receives a *reward* r_t constructed as a weighted combination of selected bitrate b_t and stall time of the past chunk d_t:

$$r_t = w_b b_t^{p_b} - w_d d_t^{p_d} + w_c[\mathbb{1}(d_t > 0)], \qquad (1)$$

where $\mathbb{1}(\cdot)$ is an indicator function counting for stall events, and w_b, w_d, w_c, p_b, p_d are the tuning weights for the reward. Notice that these weights cannot be predetermined, because the goal of RL-based ABR is to outperform the existing ABR algorithm in every dimension of the metric (i.e., higher bitrate, less stall time and less stall count), which does not amount to a quantitative objective. In §3.4 we describe how we use Bayesian optimization to shape the weights for optimizing the multi-dimensional objective.

Policy. As shown in Figure 3, the agent samples the next bitrate action a_t based on its parametrized policy: $\pi_\theta(a_t|s_t) \rightarrow [0, 1]$. In practice, since the number of bitrate encodings (thus the length of $\vec{n}_t$) varies across different videos (Lederer et al., 2012), we architect the policy network to take an arbitrary number of file sizes as input. Specifically, for each bitrate, the input to the policy network consists of the predicted bandwidth and buffer occupancy, concatenated with the corresponding file size. We then copy the *same* neural network for each of the bitrate encodings (e.g., the neural networks shown in Figure 3 share the same weights θ). Each copy of the policy network outputs a "priority" value q_t^i for selecting the corresponding bitrate i. Afterwards, we use a softmax (Bishop, 2006) operation to map these priority values into a probability distribution p_t^i over each bitrate: $p^i = \exp(q_t^i)/\sum_{i=1}^{M}[\exp(q_t^i)]$. Importantly, the whole policy network architecture is end-to-end differentiable and can be trained with the policy gradient algorithms (Sutton et al., 1999).

Figure 3. Policy network architecture. For each bitrate, the input is fed to a copy of the *same* policy neural network. We then apply a (parameter-free) softmax operator to compute the probability distribution of the next bitrate. This architecture can scale to arbitrary number of bitrate encodings.

Training. We use the policy gradient method (Sutton et al., 1999; Sutton & Barto, 2017; Tian et al., 2017) to update the policy neural network parameters in order to optimize for the objective. Consider a simulated video streaming session of length T, where the agent collects (state, action, reward) experiences, i.e., (s_t, a_t, r_t) at each step t. The policy gradient method updates the policy parameter θ using the estimated gradient of the cumulative reward:

$$\theta \leftarrow \theta + \alpha \sum_{t=1}^{T} \nabla_\theta \log \pi_\theta(s_t, a_t) \left(\sum_{t'=t}^{T} r_{t'} - b_t \right), \quad (2)$$

where α is the learning rate and b_k is a *baseline* for reducing the variance of the policy gradient (Weaver & Tao, 2001).

Notice that the estimation of the advantage over the average case relies on the accurate estimation of the average. For this problem, the standard baselines, such as the time-based baseline (Greensmith et al., 2004; Williams, 1992) or value function (Mnih et al., 2016), suffer from large variance due to the stochasticity in the traces (Mao et al., 2019). We further describe the details of this variance in §3.3 and our approach to reducing it.

3.3. Variance Reduction

ABRL's RL training on the simulator is powered by a large number of network traces collected from the front end video platform (§3.1). During training, ABRL must experience a wide variety of network conditions and video watches in order to generalize its ABR policy well. However, this creates a challenge for training: different traces contain very different network bandwidth and video duration, which significantly affects the total reward observed by the RL agent. Consider an illustrative example shown in Figure 4, where we use a fixed buffer-based ABR policy (Huang et al., 2014) to make the bitrate action at time τ. Even for this fixed policy, if the future trace happens to contain large bandwidth (e.g., Trace 1), the reward feedback will naturally be

Figure 4. Illustrative example of how the difference in the traces of network bandwidth and video watch time creates significant variance for the reward feedback.

large, since the network can support high bitrate without stalls. In contrast, if the future network condition becomes poor (e.g., Trace 2), the reward will likely be lower than average. More importantly, the video duration determines the possible length of ABR interactions, which dictates the *total* reward the RL agent can receive for training (e.g., the longer watch time in Trace 1 leads to larger total reward). The key problem is that the difference across the traces is independent with the bitrate action at time τ — e.g., the future bandwidth might fluctuate due to the inherent stochasticity in the network; or a user might stop watching a video regardless of the quality. As a result, this creates large variance in the reward feedback used for estimating the policy gradient in Equation (2).

To solve this problem, we adopt a recently proposed technique for handling an exogenous, stochastic process in the environment when training RL agents (Mao et al., 2019). The key idea is to modify the baseline in Equation (2) to an "input-dependent" one that takes the input process (e.g., the trace in this problem) into account explicitly. In particular, for this problem, we implement the input-dependent baseline by loading the *same* trace (i.e., the same time-series for network bandwidth and the same video watch time) multiple times and computing the average total reward at each time step among these video sessions. Essentially, this uses the time-based baseline (Greensmith et al., 2004) for Equation (2) but computes the average return conditional on the specific instantiation of a trace. During training, we repeat this procedure for a large number of randomly-sampled network traces. As a result, this approach entirely removes the variance caused by the difference in future network condition or the video duration. Since the difference in the reward feedback is only due to the difference in the actions, this enables the RL agent to assess the quality of different actions much more accurately. In Figure 8, we show how this approach helps improve the training performance.

3.4. Reward Shaping with Bayesian Optimization

The goal of ABRL is to outperform the existing ABR policy in every dimension of the objectives (i.e., increasing the

video quality while reducing the stall time). Recall that the reward weights in Equation (1) dictates the performance of ABRL's learned ABR policy in each of the objective dimensions. These objectives have an inherent trade-off — optimizing one dimension (by tuning up the corresponding reward weight) diminishes the performance in another dimension (e.g., high video quality increases the risk of stalls).

To determine the proper combination of the reward weights, we treat ABRL's RL training module (§3.2, §3.3) as a black-box function $f(\vec{w}) \rightarrow (q, l)$ that maps the reward weights $\vec{w} \triangleq (w_b, w_d, w_c, p_b, p_d)$ from Equation (1) to the average video quality q and stall l in unseen evaluating video sessions. Then, we use Bayesian optimization (Snoek et al., 2012; Shahriari et al., 2016) to efficiently search for the weight combinations that leads to better (q, l), with only a few invocations of the RL training module (i.e., small number of f function calls). Specifically, we formulate the multi-dimensional optimization problem as a constrained optimization problem (Gardner et al., 2014):

$$\text{maximize} \quad q(\vec{w}) \tag{3}$$
$$\text{subject to} \quad l(\vec{w}) \leq (1 + \delta)l^* \tag{4}$$

Here, l^* denotes the best performance in stall time ABRL has discovered so far, and δ is a tolerance factor. Intuitively, the constraint in Equation (4) means that ABRL searches for reward weights which optimize the video quality, conditional on not degrading the stall performance by more than δ (a constant chosen ex ante).

Notice that the function $q(\cdot)$ and $l(\cdot)$ are both unknown and can only be observed by running the RL training module. To solve this problem with Bayesian optimization, we use Gaussian process models (Rasmussen, 2004) to approximate these functions with the observed data. In particular, the Gaussian process starts with a prior, a multivariate Gaussian distribution, for fitting the training outcome from the initial random samples of the reward weights. It then updates the posterior distribution for $q(\cdot)$ and $l(\cdot)$ using the newly observed outcome from each run of the subsequent runs (see Equation (3) in (Frazier, 2018)). These models fit a wide array of smooth functions to data and provide reliable estimates of uncertainty, leading to their use in this context.

To optimize the objective function, Bayesian optimization leverages an acquisition function (Snoek et al., 2012) to search for new reward weights that are most likely to result in the best outcome. The most common acquisition function is expected improvement (EI) (see Frazier (2018, §4.1)). EI measures the expected value of improvement at each point relative to the best observed point: $\alpha_{EI}(\vec{w} \mid q^*) = \mathbb{E}[\max(0, y - q^*)|y \sim g(\vec{w}|\mathcal{D})]$, where $\mathcal{D} \triangleq \{\vec{w}_i, q(\vec{w}_i)\}_{i=1}^N$ represents N runs of data points, $q^* = \max_i q(\vec{w}_i)$ is the current best observation and $g(\vec{w}|\mathcal{D})$ denotes the the posterior distribution of q value from the Gaus-

sian process. To incorporate the constraints from Equation (4) into the acquisition function (Gardner et al., 2014), we use $\alpha_{EIC}(\vec{w} \mid q^*) = \alpha_{EI}(\vec{w} \mid q^*)\mathbb{P}(l(\vec{w}) \leq (1 + \delta)l^*)$, where $\mathbb{P}(\cdot)$ uses the posterior distribution of l from a Gaussian process to measure the probability of constraint satisfaction. The intuition is to suppress the search for the reward weights that are likely to violate the constraint.

In our detailed implementation, it is worth noting that we add two additional enhancements in the design of the acquisition function. First, we use the augmented EI (Huang et al., 2006) that balances exploration and exploitation by adding a multiplier to EI to increase the value of points with high predictive variance. Second, since Bayesian optimization typically assumes noiseless observations, we use batch optimization (§3 in Letham et al. (2018)) to smooth out the acquisition function, which is proven to have better numerical stability under noisy observations (Ginsbourger et al., 2011). We refer the readers to Letham et al. (2018) for more details.

The Bayesian optimization of reward weights converges to the Pareto frontier (Van Den Berg & Friedlander, 2008) of the multi-dimensional objective, i.e., improving on any dimension would degrade the performance on some other dimension of the objective. To determine the reward weights and the corresponding ABR policy for deployment, we choose the points on the Pareto frontier that outperform the existing ABR in all dimensions. This Bayesian procedure of tuning the weights in the reward function is a realization of reward shaping (Ng et al., 1999). Figure 7 visualizes our optimization procedure in practice.

3.5. Policy Translation

In practice, most video players execute the ABR algorithms in the front end to avoid the extra latency connecting to the back end (Akhshabi et al., 2011; Sodagar, 2011; Adhikari et al., 2012; Huang et al., 2014). Therefore, we need to deploy the learned ABR policy to the users directly — i.e., the design of an ABR server in the back end hosting the requests from all users is not ideal (Mao et al., 2017). To massively deploy, we make use of the web-based video platform at Facebook, where the front end service (if uncached) fetches the most up-to-date video player (including the ABR policy) from the back end server at the beginning of a video streaming session.

For ease of understanding and maintenance in deployment, we translate the neural network ABR policy to an interpretable form. In particular, we found that the learned ABR policies approximately exhibit a linear structure — the bitrate decision boundaries are approximately linear and the distances between the boundaries are constant in part of the decision space. As a result, we approximate the learned ABR policy with a deterministic linear fitting

function. Specifically, we first randomly pick N tuples of bandwidth prediction x and buffer occupancy o (see the inputs in Figure 3). Then, for each tuple values (x, o) and for each of the M equally spaced bitrates with file sizes $n^1, n^2, \cdots, n^M$, we invoke the policy network to compute the probability of selecting the corresponding bitrate: $\pi(a^1|x, o, n^1), \pi(a^2|x, o, n^2), \cdots, \pi(a^M|x, o, n^M)$. Next, we determine the "intended" bitrate using a weighted sum: $\bar{n} = \sum_{i=1}^{M} n^i \pi(a^i|x, o, n^i)$. This serves as the target bitrate for the output of the linear fitting function. Finally, we use three parameters a, b, and c, to fit a linear model of bandwidth prediction and buffer occupancy, which minimizes the mean squared error over all N points:

$$\sum_{i=1}^{N} \left| a x_i + b o_i + c - \bar{n}_i \right|^2. \tag{5}$$

Here, we use the standard least square estimator for the model fitting, which is the optimal unbiased linear estimator (Zyskind & Martin, 1969). At inference time, the front end video player uses the fitted linear model to determine the intended bitrate and then selects the maximum available bitrate that is below the intended bitrate.

Translating the neural network ABR policy provides interpretability for human engineers but it is also a compromise in terms of ABR performance (§4.2 empirically evaluates this trade-off). Also, adding more contextual based features would likely require a non-linear policy encoded directly in a neural network (§5). It is worth noting that directly using RL to train a linear policy is a natural choice. However, to our surprise, training ABRL with a linear policy function leads to worse ABR performance than the existing heuristics. We hypothesize this is because policy gradient with a weak function approximator such as a linear one has difficulty converging to the optimal, even though the optimal policy can be simple (Lu et al., 2018; Fujimoto et al., 2018; Fairbank & Alonso, 2012; Achiam et al., 2019).

4. Experiments

We evaluate ABRL with Facebook's web-based production video platform. Our experiments answer the following questions: (1) Does ABRL provide gains in performance over the existing heuristic-based production ABR algorithm? (2) Drilling down to different network conditions, where is the performance gain from? (3) What ABR policy does ABRL learn? (4) During training, how do different design components affect the learning procedure?

4.1. Performance

In a week-long deployment on Facebook's production video platform, we compare the performance of ABRL's translated ABR policy (§3.5) with that of the existing heuristic-

(a) Video quality   (b) Stall rate

Figure 5. A week-long performance comparison with production ABR policy. The comparison is sampled from over 30 million video streaming session. The box spans 95% confidence intervals and the bars spans 99% confidence intervals.

based ABR algorithm. The experiment includes over 30 million worldwide video playback sessions. Figure 5 shows the relative improvement of ABRL in terms of video quality and stall rate.

Overall, ABRL achieves a 1.6% increase in average bitrate and a 0.4% decrease in stall rate. Most notably, ABRL consistently selects higher bitrate through the whole week (99% confidence intervals all positive). However, choosing higher bitrates does *not* sacrifice stall rate — ABRL rivals or outperforms the default scheme on the average stall rate every day, even on Thursday when gains in video quality are highest. This shows ABRL uses the output from the bandwidth prediction module better than the fine-tuned heuristic. By directly interacting with the observed data, ABRL learns quantitatively how conservative or aggressive the ABR should be with different predicted bandwidths. As a result, this also leads to a 0.2% improvement in the end-user video watch time.

These improvement numbers may look modest compared to the those reported by recent academic papers (Huang et al., 2014; Spiteri et al., 2016; Yin et al., 2015; Mao et al., 2017). This is mostly because we only experiment with web based videos, which primarily consist of well-connected desktop or laptop traffic, different from the prior schemes that mostly concern cellular and unstable networks. Nonetheless, any non-zero improvement is significant given the massive volume of Facebook videos. In the following, we profile the performance gain at a more granular level.

4.2. Drill-down Analysis

To better understand how ABRL outperforms the existing ABR scheme, we breakdown the performance gain in different network conditions and we visualize the ABR policy learned by ABRL.

Performance breakdown. In Figure 6, we categorize the video sessions based on the average measured network bandwidths. As shown, ABRL overall achieves a higher bitrate while maintaining fewer stalls in both fast and slow networks. Moreover, ABRL performs significantly better in

(a) Video quality breakdown   (b) Stall rate breakdown

Figure 6. Breakdown the performance comparison with different network quality. "slow network" corresponds to $< 500K$ mbps measured network bandwidth, and "fast network" corresponds to $> 10M$ mbps bandwidth. The box spans 95% confidence intervals and the bars spans 99% confidence intervals.

slow network conditions, where it delivers 5.9% higher bitrate with 2.4% fewer stalls on average. When the network connectivity is unstable, ABR is challenging — a controller must agilely switch to lower bitrate when the bandwidth prediction or buffer level is low, but must avoid being too conservative by persistently sticking with low bitrates (when is is feasible to use higher bitrate without stalling). In the slow network condition, ABRL empirically uses the noisy network bandwith estimation better than the heuristic system in order to maintain better buffer levels. This indicates that ABRL optimizes algorithm performance under network conditions that existing schemes may overlook.

Reward shaping. To optimize the multi-dimensional objective, we use a Bayesian Optimization approach for reward shaping (§3.4). The goal is to tune the weights in the reward function in order to train a policy that operates on the Pareto frontier of video quality and stall (and, ideally, outperform the existing policy in both dimensions). Figure 7 shows the performance from different reward weights during the reward shaping procedure. At each iteration, we set the reward weights using the output from the Bayesian optimization module, and treat ABRL's RL module as a black box, in which the policy is trained until convergence according to the chosen reward weights. The Bayesian optimization module then observes the testing outcomes (both video quality and stall) and sets the search criteria for the next iteration to be "expected improvement in video quality such that stall time degrades no less than 5%". As shown, within three iterations, ABRL is able to hone in on the empirical Pareto frontier. In this search space, there are many more weight configurations that lead to better video quality (i.e., right of the dashed line) than the configurations leading to fewer

Figure 7. Reward shaping. Searching hyperparameters in the reward function with Bayesian optimization. The initial round has 64 random initial parameters. Each optimization round outputs 6 set of parameters to search next. We train each reward set up with the same RL agent. The performance is tested with unseen network traces.

stalls (i.e., lower than the dashed line). Compared to the existing ABR scheme, ABRL finds a few candidate reward weights that lead to better ABR policy both in terms of video quality and stalls (i.e., lower and to the right of the existing policy). For the production experiment in §4.1, we deploy the policies within the region that shows the largest improvement in stall. After this search procedure, engineers on the video team can pick policies based on different deployment objectives as well.

Variance reduction. To reduce the variance introduced by the network and the watch time across different the traces, we compute the baseline for policy gradient by averaging over the cumulative rewards from the same trace (in all the parallel rollouts) at each iteration, effectively achieving the input-dependent baseline (§3.3). For comparison, we also train an agent with the regular state-dependent baseline (i.e., output from a value function that only takes the state observation as input). Figure 8 evaluates the impact of variance reduction by comparing the learning curve trained with the input-dependent baseline to that with the state-dependent baseline. As shown, the agent with the input-dependent baseline achieves about 12% higher eventual total reward (i.e., the direct objective of RL training). Moreover, we find that the agent with input-dependent baseline converges faster in terms of the entropy of the policy, which is also indicated by the narrower shaded area in Figure 8. At each point in the learning curve, the standard deviation of rewards is around half as large under the input-dependent baseline. This is expected because of the large variance in the policy gradient estimation given the uncertainties in the trace. Fixing the trace at each training iteration removes the variance introduced by the external input process, making the training significantly more stable.

Trade-off of performance for interpretability. Figure 9 shows how the testing performance of video quality and

Figure 8. The network condition and watch time in different traces introduces variance in the policy gradient estimation. The input-dependent baseline helps reduce such variance and improve training performance. Shaded area spans ± std.

(a) Video quality   (b) Stall

Figure 9. Performance comparison of ABRL and its linear approximated variant. The agents are tested with unseen traces in simulation. Translating the policy degrades the average performance by 0.8% in stall and 0.6% in quality.

stall in simulation differ between ABRL's original neural network policy and the translated policy (§3.5). Most noticeably, making the ABR policy linear and interpretable incurs a 0.8% and 8.9% degradation in the mean and 95th percentile of stall rate. This accounts for the tradeoff to make the learned ABR policy fully interpretable. Also, we tried to train a linear policy directly from scratch (by removing hidden layers in the neural network and removing all the non-linear transformations). However, the performance of the directly learned linear policy does not outperform the existing baseline. This in part is because over-parametrization in the policy network helps learn a more robust policy (Lu et al., 2018; Fairbank & Alonso, 2012).

5. Discussion

We intend to work on several directions to further enhance ABRL in the production systems. First, ABRL's training is only performed once offline with pre-collected network traces. To better incorporate with the updates in the backend infrastructure, we can set up a continual retraining routine weekly or daily. Prior studies have shown the benefit of continual training with ever updating systems (Systems & Research, 2019).

Second, we primarily evaluate ABRL on Facebook's web-based video platform, because it has the fastest codebase update cycle (unlike mobile development, where the updates are batched in new version releases). However, the network conditions for cellular networks have larger variability and are more unpredictable, where the gain of an RL-based ABR scheme can be larger (e.g., we observed larger performance gain for ABRL when the network condition is poor in §4.2. Developing a similar learning framework for mobile clients can potentially lead to larger ABR improvements.

Third, ABRL uses the same state variables (§3.2) as the current heuristic-based ABR algorithm. In practice, ABRL can also extend its state space to incorporate more contextual features such as video streaming regions, temporal informa-

tion (which may contain different network characteristics) and continuous / many-valued features which engineers cannot easily fold into heuristics. Also, categorizing and optimizing the video quality based on video content types can likely result in better perceptual quality.

Lastly, there exists a discrepancy between simulated buffer dynamics and the real video streaming session in practice. Better bridging this gap can increase the generalizability of ABRL's learned policy. To this end, there is ongoing work addressing the discrepancy between simulation and reality with Bayesian optimization in reward shaping (Letham & Bakshy, 2019). Furthermore, another viable approach is to directly perform RL training on the production system. The challenge for this is to construct a similarly safe training mechanism (Alshiekh et al., 2018) that prevents the initial RL trials from decreasing perceptual quality of a video (e.g., restricting the initial RL policy from randomly select poor bitrates).

6. Conclusion

We presented ABRL, a system that uses RL to automatically learn high-quality ABR algorithms for Facebook's production web-based video platform. ABRL has several customized components for solving the challenges in production deployment, including a scalable architecture for videos with arbitrary bitrates, a variance reduction RL training method and a Bayesian optimization scheme for reward shaping. For deployment, we translate ABRL's policy to an interpretable form for better maintenance and safety. In a week-long worldwide deployment with more than 30 million video streaming sessions, our RL approach outperforms the existing carefully-tuned ABR algorithm by at least 1.6% in video quality and 0.4% in stall.

References

Achiam, J., Knight, E., and Abbeel, P. Towards characterizing divergence in deep q-learning. *arXiv preprint arXiv:1903.08894*, 2019.

Adhikari, V. K., Jain, S., Chen, Y., and Zhang, Z.-L. Vivisecting youtube: An active measurement study. In *2012 Proceedings IEEE INFOCOM*, pp. 2521–2525. IEEE, 2012.

Akhshabi, S., Begen, A. C., and Dovrolis, C. An experimental evaluation of rate-adaptation algorithms in adaptive streaming over http. In *Proceedings of the Second Annual ACM Conference on Multimedia Systems*, MMSys. ACM, 2011.

Alshiekh, M., Bloem, R., Ehlers, R., Könighofer, B., Niekum, S., and Topcu, U. Safe reinforcement learning via shielding. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

Bishop, C. M. *Pattern Recognition and Machine Learning*. Springer, 2006. ISBN 0387310738.

Cisco. Cisco visual networking index: Forecast and methodology, 2015-2020. 2016.

Claeys, M., Latré, S., Famaey, J., Wu, T., Van Leekwijck, W., and De Turck, F. Design of a q-learning-based client quality selection algorithm for http adaptive video streaming. In *Adaptive and Learning Agents Workshop*, 2013.

Dobrian, F., Sekar, V., Awan, A., Stoica, I., Joseph, D., Ganjam, A., Zhan, J., and Zhang, H. Understanding the Impact of Video Quality on User Engagement. In *Proceedings of the ACM SIGCOMM 2011 Conference*, SIGCOMM. ACM, 2011.

Fairbank, M. and Alonso, E. The divergence of reinforcement learning algorithms with value-iteration and function approximation. In *The 2012 International Joint Conference on Neural Networks (IJCNN)*, pp. 1–8. IEEE, 2012.

Frazier, P. I. A tutorial on bayesian optimization. *arXiv preprint arXiv:1807.02811*, 2018.

Fujimoto, S., Hoof, H., and Meger, D. Addressing function approximation error in actor-critic methods. In *International Conference on Machine Learning*, pp. 1582–1591, 2018.

Gardner, J. R., Kusner, M. J., Xu, Z. E., Weinberger, K. Q., and Cunningham, J. P. Bayesian optimization with inequality constraints. In *ICML*, pp. 937–945, 2014.

Ginsbourger, D., Janusevskis, J., and Le Riche, R. Dealing with asynchronicity in parallel gaussian process based global optimization. In *4th International Conference of the ERCIM WG on computing & statistics (ERCIM'11)*, 2011.

Greensmith, E., Bartlett, P. L., and Baxter, J. Variance reduction techniques for gradient estimates in reinforcement learning. *Journal of Machine Learning Research*, 5(Nov): 1471–1530, 2004.

Hagan, M. T., Demuth, H. B., Beale, M. H., and De Jesús, O. *Neural network design*. PWS publishing company Boston, 1996.

Huang, D., Allen, T. T., Notz, W. I., and Zeng, N. Global optimization of stochastic black-box systems via sequential kriging meta-models. *Journal of global optimization*, 34(3):441–466, 2006.

Huang, T.-Y., Johari, R., McKeown, N., Trunnell, M., and Watson, M. A Buffer-based Approach to Rate Adaptation: Evidence from a Large Video Streaming Service. In *Proceedings of the 2014 ACM Conference on SIGCOMM*, SIGCOMM. ACM, 2014.

Krishnan, S. S. and Sitaraman, R. K. Video Stream Quality Impacts Viewer Behavior: Inferring Causality Using Quasi-experimental Designs. In *Proceedings of the 2012 ACM Conference on Internet Measurement Conference*, IMC. ACM, 2012.

Lederer, S., Müller, C., and Timmerer, C. Dynamic adaptive streaming over http dataset. In *Proceedings of the 3rd Multimedia Systems Conference*, pp. 89–94. ACM, 2012.

Letham, B. and Bakshy, E. Bayesian optimization for policy search via online-offline experimentation. *arXiv preprint arXiv:1904.01049*, 2019.

Letham, B., Karrer, B., Ottoni, G., Bakshy, E., et al. Constrained bayesian optimization with noisy experiments. *Bayesian Analysis*, 2018.

Lu, T., Schuurmans, D., and Boutilier, C. Non-delusional q-learning and value-iteration. In Bengio, S., Wallach, H., Larochelle, H., Grauman, K., Cesa-Bianchi, N., and Garnett, R. (eds.), *Advances in Neural Information Processing Systems 31*, pp. 9949–9959. 2018.

Mao, H., Netravali, R., and Alizadeh, M. Neural adaptive video streaming with pensieve. In *Proceedings of the ACM SIGCOMM 2017 Conference*. ACM, 2017.

Mao, H., Venkatakrishnan, S. B., Schwarzkopf, M., and Alizadeh, M. Variance reduction for reinforcement learning in input-driven environments. *Proceedings of the 7th International Conference on Learning Representations (ICLR)*, 2019.

Mnih, V., Badia, A. P., Mirza, M., Graves, A., Harley, T., Lillicrap, T. P., Silver, D., and Kavukcuoglu, K. Asynchronous methods for deep reinforcement learning. In *Proceedings of the International Conference on Machine Learning*, pp. 1928–1937, 2016.

Ng, A. Y., Harada, D., and Russell, S. Policy invariance under reward transformations: Theory and application to reward shaping. In *ICML*, volume 99, pp. 278–287, 1999.

Rasmussen, C. E. Gaussian processes in machine learning. In *Advanced lectures on machine learning*, pp. 63–71. Springer, 2004.

Sandvine. Global internet phenomena-latin american & north america. 2015.

Sandvine, I. Global internet phenomena report. *North America and Latin America*, 2018.

Shahriari, B., Swersky, K., Wang, Z., Adams, R. P., and De Freitas, N. Taking the human out of the loop: A review of bayesian optimization. *Proceedings of the IEEE*, 104 (1):148–175, 2016.

Snoek, J., Larochelle, H., and Adams, R. P. Practical bayesian optimization of machine learning algorithms. In *Advances in Neural Information Processing Systems 25*, pp. 2951–2959. Curran Associates, Inc., 2012.

Sodagar, I. The mpeg-dash standard for multimedia streaming over the internet. *IEEE MultiMedia*, 18(4):62–67, 2011.

Spiteri, K., Urgaonkar, R., and Sitaraman, R. K. BOLA: near-optimal bitrate adaptation for online videos. In *Infocom*, 2016.

Sutton, R. S. and Barto, A. G. *Reinforcement Learning: An Introduction, Second Edition*. MIT Press, 2017.

Sutton, R. S., McAllester, D. A., Singh, S. P., and Mansour, Y. Policy gradient methods for reinforcement learning with function approximation. In *NIPS*, volume 99, pp. 1057–1063, 1999.

Systems, S. and Research, N. Puffer: stream live tv in your browser. https://puffer.stanford.edu/faq/, 2019.

Tian, Y., Gong, Q., Shang, W., Wu, Y., and Zitnick, C. L. Elf: An extensive, lightweight and flexible research platform for real-time strategy games. In *Advances in Neural Information Processing Systems*, pp. 2659–2669, 2017.

Van Den Berg, E. and Friedlander, M. P. Probing the pareto frontier for basis pursuit solutions. *SIAM Journal on Scientific Computing*, 31(2):890–912, 2008.

van der Hooft, J., Petrangeli, S., Claeys, M., Famaey, J., and De Turck, F. A learning-based algorithm for improved bandwidth-awareness of adaptive streaming clients. In *2015 IFIP/IEEE International Symposium on Integrated Network Management*. IEEE.

Wagner, K. Facebook says video is huge – 100-million-hours-per-day huge. https://www.vox.com/2016/1/27/11589140/facebook-says-video-is-huge-100-million-hours-per 2016.

Weaver, L. and Tao, N. The optimal reward baseline for gradient-based reinforcement learning. In *Proceedings of the Seventeenth conference on Uncertainty in artificial intelligence*, pp. 538–545. Morgan Kaufmann Publishers Inc., 2001.

Williams, R. J. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3-4):229–256, 1992.

Yin, X., Jindal, A., Sekar, V., and Sinopoli, B. A Control-Theoretic Approach for Dynamic Adaptive Video Streaming over HTTP. In *Proceedings of the 2015 ACM Conference on Special Interest Group on Data Communication*, SIGCOMM. ACM, 2015.

Zyskind, G. and Martin, F. B. On best linear estimation and general gauss-markov theorem in linear models with arbitrary nonnegative covariance structure. *SIAM Journal on Applied Mathematics*, 17(6):1190–1202, 1969.