ContraNorm: A Contrastive Learning Perspective on Oversmoothing and Beyond

Abstract

Oversmoothing is a common phenomenon in a wide range of Graph Neural Networks (GNNs) and Transformers, where performance degenerates as the layer goes deeper. Instead of characterizing oversmoothing from the view of *complete collapse* in which representations converge to a single point, we dive into a more general perspective *dimensional collapse* in which representations lie in a narrow cone. Accordingly, inspired by the power of contrastive learning in preventing dimensional collapse, we propose a novel normalization layer **ContraNorm**. Intuitively, ContraNorm implicitly shatters representations in the embedding space, leading to a more uniform distribution and slighter dimensional collapse. On the theoretical analysis, we prove that ContraNorm can alleviate both complete collapse and dimensional collapse under some conditions. Our proposed normalization layer can be easily inserted into GNNs and Transformers with negligible parameter overhead. Experiments on various real-world datasets verify the effectiveness of our method.

1 Introduction

Recently, the rise of Graph Neural Networks (GNNs) has enabled important breakthroughs in various fields of graph learning (Ying et al., 2018; Senior et al., 2020). Along the other avenue, although getting rid of bespoke convolution operators, Transformers (Vaswani et al., 2017) also achieve phenomenal success in multiple natural language processing (NLP) tasks (Lan et al., 2020; Liu et al., 2020; Rajpurkar et al., 2018) and be transferred successfully to computer vision (CV) field (Dosovitskiy et al., 2021; Liu et al., 2021; Strudel et al., 2021). Despite sharing different model architectures, GNNs and Transformers are both hindered by oversmoothing problem (Li et al., 2018; Tang et al., 2021), where deeply stacking layers gives rise to indistinguishable representations and significant performance deterioration.

In order to get rid of oversmoothing, we need to dive into the modules inside and understand how oversmoothing happens on the first hand. However, we notice that existing oversmoothing analysis fails to fully characterize the behavior of learned features. A canonical metric for oversmoothing is the average similarity (Zhou et al., 2021; Gong et al., 2021; Wang et al., 2022). The tendency of similarity converging to 1 indicates representations shrink to a single point (complete collapse), as shown in Fig. 1a. However, this metric can not depict a more general collapse case, where representations span a low-dimensional manifold in the embedding space and also sacrifice expressive power in Fig. 1b (dimensional collapse). In such cases, similarity fails to quantify the collapse level. Therefore, we need to go beyond existing measures and take this so-called *dimensional collapse* into consideration. Actually, this dimensional collapse behavior is widely discussed in the contrastive learning literature (Jing et al., 2022; Hua et al., 2021; Chen & He, 2021; Grill et al., 2020), which will hopefully help us characterize the oversmoothing of GNNs and Transformers. The main idea of contrastive learning is maximizing agreement between different augmented views of the same data example (i.e. positive pairs) via a contrastive loss. Common contrastive loss can be decoupled into alignment loss and uniformity loss (Wang & Isola, 2020). The two ingredients correspond to different objectives: alignment loss expects distance between positive pairs to be closer, while uniformity loss measures how well the embeddings are uniformly distributed. Pure training with only alignment loss may lead to a trivial solution where all representations shrink to one single point Fortunately, the existence of uniformity loss naturally helps solve this problem by drawing representations evenly distributed in the embedding space.

In view of the inherent similarities of the two domains, we build a connection between the oversmoothing problem and the representation collapse issue. Instead of directly adding uniformity loss

(a) Complete collapse   (b) Dimensional collapse   (c) No collapse

Figure 1: A direct illustration on the complete collapse and the dimensional collapse.

into model training, we design a normalization layer that can be used out of the box with almost no parameter overhead. For this end, we firstly transfer the uniformity loss used for training to a loss defined over graph node representations, thus it can optimize representation itself rather than model parameters. Intuitively, the loss meets the need of drawing a uniform node distribution. Following research in combining optimization scheme and model architecture (Yang et al., 2021; Zhu et al., 2021; Xie et al., 2021), we use the transferred uniformity loss as an energy function underlying our proposed layer, such that descent steps along it corresponds with the forward pass. By analyzing the unfolding iterations of the principled uniformity loss, we design a new normalization layer **ContraNorm**. Theoretically, we prove ContraNorm increases both average variance and effective rank of representations, thus solving complete collapse and dimensional collapse effectively. We also conduct a comprehensive evaluation of ContraNorm on various tasks. Specifically, we boost the average performance of BERT (Devlin et al., 2018) from 82.59% to 83.54% on the validation set of General Language Understanding Evaluation (GLUE) datasets (Wang et al., 2019), and raise the test accuracy of DeiT (Touvron et al., 2021) with 24 blocks from 77.69% to 78.67% on ImageNet1k (Russakovsky et al., 2015) dataset. For GNNs, experiments are conducted on fully supervised graph node classification tasks, and our proposed model outperforms vanilla Graph Convolution Network (GCN) (Kipf & Welling, 2017) on all depth settings. Our contributions are summarized as:

- We dissect the limitations of existing oversmoothing analysis, and highlight the importance of incorporating the dimensional collapse issue into consideration.

- Inspired by the techniques from contrastive learning to measure and resolve oversmoothing, we propose Contrastive Normalization (ContraNorm) as an optimization-induced normalization layer to prevent dimensional collapse.

- Experiments on a wide range of tasks show that ContraNorm can effectively mitigate dimensional collapse in various model variants, and demonstrate clear benefits across three different scenarios: ViT for image classification, BERT for natural language understanding, and GNNs for node classifications.

2 BACKGROUND & RELATED WORK

Message Passing in Graph Neural Networks. In the literature of GNNs, message-passing graph neural networks (MP-GNNs) are intensively studied. It progressively updates representations by exchanging information with neighbors. The update of node i's representation in l-th layer is formalized as $\boldsymbol{h}_i^{(l)} = \text{UPDATE}\big(\boldsymbol{h}^{(l-1)}, \text{AGGREGATE}(\boldsymbol{h}_i^{(l-1)}, \{\boldsymbol{h}_j^{(l-1)} \mid j \in \mathcal{N}(i)\})\big)$, where $\mathcal{N}(i)$ denotes the neighborhood set of node i, AGGREGATE$(\cdot)$ is the procedure where nodes exchange message, and UPDATE$(\cdot)$ is often a multi-layer perceptron (MLP). A classical MP-GNNs model is GCN (Kipf & Welling, 2017), which propagates messages between 1-hop neighbors using an adjacency matrix.

Self-Attention in Transformers. Transformers encode information in a global scheme with self-attention as the key ingredient. Self-attention module re-weights intermediate representations by aggregating semantically near neighbors. Formally, it estimates similarities between key and query, namely self-attention matrix, as $\bar{\boldsymbol{A}} = \text{softmax}(\boldsymbol{Q}\boldsymbol{K}^T)$, $\boldsymbol{Q} = \boldsymbol{X}\boldsymbol{W}_Q$, and $\boldsymbol{K} = \boldsymbol{X}\boldsymbol{W}_K$ where $\boldsymbol{X}$, $\boldsymbol{W}_Q$, and $\boldsymbol{W}_K$ are the input, weight matrices for query and key, respectively. A multi-head self-attention module with residual connection can be formularized as $\text{Attn}(\boldsymbol{X}) = \boldsymbol{X} + \sum_{k=1}^{h} \bar{\boldsymbol{A}}_k \boldsymbol{X} \boldsymbol{V}_k \boldsymbol{W}_k^T$, where h is the number of heads, and $\boldsymbol{V}$, $\boldsymbol{W}$ are weights for value and final output.

Connections between Message Passing and Self-Attention. Note that the self-attention matrix can be seen as a normalized adjacent matrix of a corresponding graph (Shi et al., 2022). Considering a weighted fully connected graph G with adjacency matrix denoted as $\hat{A}$, we map nodes to token representations and set weights of the edge between node i and node j to $\exp(Q_i^T K_j)$. Then (i, j) entry of a normalized adjacency matrix is $\tilde{A}_{ij} = \hat{A}_{ij}/\hat{D}_{ij} = \exp(Q_i^T K_j)/\sum_k \exp(Q_i^T K_k)$, where diagonal matrix $\hat{D}_{ii} = \sum_j \hat{A}_{ij}$. Apparently, $\tilde{A}$ is equal to the form of self-attention matrix defined in Transformers. Simultaneously, $\tilde{A}$ plays a major part in the message-passing scheme by deciding which nodes to exchange information with.

Oversmoothing in GNNs and Transformers. The term oversmoothing is firstly proposed by Li et al. (2018) in research of GNNs. Intuitively, representations converge to a constant after repeatedly exchanging message with neighbors when layer goes to infinity. Zhou et al. (2020) mathematically proves that under some conditions, the convergence point carries only information of graph topology. Coincidentally, an oversmoothing-like phenomenon is also observed in Transformers. Unlike CNNs, Transformers can not benefit from simply deepening layers, and even saturates with depth increasing. Early works empirically ascribe it to attention/feature collapse or patch/token uniformity (Tang et al., 2021; Zhou et al., 2021; Gong et al., 2021). To be specific, the attention maps tend to be overly similar in later layers, whereby features insufficiently exchange information and lose diversity in the end. Outputs of pure transformers, i.e., attention without skip connections or MLPs, are also observed to converge to a rank-1 matrix (Dong et al., 2021). For illustration proposes, we also refer to the degeneration issue in Transformers as oversmoothing.

3 MITIGATING OVERSMOOTHING FROM THE PERSPECTIVE OF CONTRASTIVE LEARNING

In this section, we first empirically illustrate that current similarity metric fails to characterize dimensional collapse, thus overlooking a crucial part of oversmoothing. In order to solve such dimensional collapse, inspired by contrastive learning whose property of uniformity naturally rules out dimensional collapse, we transfer the uniformity loss to a loss that directly acts on representations, and then by unfolding the optimization steps along such loss we induce a normalization layer ContraNorm. Theoretically, we prove our proposed layer help mitigate dimensional collapse.

3.1 THE CHARACTERIZATION OF OVERSMOOTHING

In this part, we first analyze the defects of current metrics to characterize oversmoothing, which then inspires us to adopt the effective rank metric from contrastive learning to do this.

Taking the oversmoothing problem of Transformers as an example without loss of generality, a prevailing metric is evaluating attention map similarity (Wang et al., 2022; Gong et al., 2021; Shi et al., 2022). As attention map similarity progressively converges to one, attendant high feature similarity brings about loss of representation expressiveness, thus performance declines in the end. However, by conducting experiments on transformer structured models like ViT and BERT, we find that high attention map similarity does not necessarily result in high feature similarity. As shown in Fig. 2a and Fig. 2b, although attention map similarity is close to 0.8 or even higher, the feature similarity keeps lower than 0.5 in most cases. It means the oversmoothing problem still occurs even with a low feature similarity. A natural conclusion comes that feature similarity can not fully depict the quality of representations and the oversmoothing problem.

Intuitively, considering such a case that representations in the latent embedding space do not shrink to one single point but span a low dimensional space, feature similarity may be relatively low, but representations indeed lose expressive power. Such representation degeneration problem is widely discussed in the literature of contrastive learning and often referred to as *dimensional collapse*. In contrastive learning, common practice to describe dimensional collapse is the vanishing distribution of singular values (Gao et al., 2019; Ethayarajh, 2019; Jing et al., 2022). Here, to boil it down to a concise scale, we propose to use a quantifiable metric *effective rank* (Roy & Vetterli, 2007), which is a spectral entropy based method covering the full singular value spectrum.

Definition 3.1 (Effective Rank). *Considering matrix $X \in \mathbb{R}^{m \times n}$ whose singular value decomposition is given by $X = U\Sigma V$, where Σ is a diagonal matrix with singular values $\sigma_1 \geq \sigma_2 \geq \cdots \geq \sigma_Q \geq 0$ with $Q = \min\{m, n\}$. The distribution of singular values is defined as L_1-normalized form $p_i = \sigma_i / \sum_{k=1}^Q |\sigma_k|$. The effective rank of the matrix X, denoted as $\mathrm{erank}(X)$, is defined as*

| (a) Similarity on BERT | (b) Similarity on ViT | (c) Erank on BERT | (d) Erank on ViT |

Figure 2: The tendency of oversmoothing metrics along layer index. Fig. 2a and Fig. 2b show feature and attention map cosine similarity. Fig. 2c and Fig. 2d present effective rank of vanilla models and models with our ContraNorm. Metrics are evaluated with 12-layer BERT on GLUE sub-task STS-B, and with 12-layer Vision Transformer (ViT) on CIFAR10 dataset, respectively. We take the average of similarities in all batches.

$erank(\boldsymbol{X}) = \exp(H\{p_1, p_2, \cdots, p_Q\})$, *where* $H(p_1, p_2, \cdots, p_Q)$ *is the Shannon entropy given by* $H(p_1, p_2, \cdots, p_Q) = -\sum_{k=1}^{Q} p_k \log p_k$.

Based on the metric of effective rank, we revisit the oversmoothing issue of Transformers in Fig. 2c and Fig. 2d. We can see that in ViT and BERT, the effective rank descends along with the number of layers. The tendency not only verifies dimensional collapse does occur in Transformers, but also indicates the effectiveness of effective rank.

3.2 Inspirations from the Uniformity Loss in Contrastive Learning

The core idea of contrastive learning is maximizing agreement between differently augmented views of the same example (i.e., positive pairs) and disagreement of views from different samples (i.e. negative pairs). A popular form of contrastive learning optimizes feature representations using a loss function with limited negative samples Chen et al. (2020). Concretely, given a batch of randomly sampled examples, for each example we generate its augmented positive views and finally get a total of N samples. Considering an encoder function f, the contrastive loss for the positive pair (i, i^+) is

$$\mathcal{L}(i, i^+) = -\log \frac{\exp(f(\boldsymbol{x}_i)^T f(\boldsymbol{x}_{i^+})/\tau)}{\sum_{k=1}^{N} \exp(f(\boldsymbol{x}_i)^T f(\boldsymbol{x}_k)/\tau) - \exp(f(\boldsymbol{x}_i)^T f(\boldsymbol{x}_i)/\tau)}, \quad (1)$$

where τ denotes a temperature factor. The loss can be decoupled into two parts named *alignment loss* and *uniformity loss*:

$$\mathcal{L}_{align}(i, i^+) = -f(\boldsymbol{x}_i)^T f(\boldsymbol{x}_{i^+}) \qquad \mathcal{L}_{uniform}(i, i^+) = \log \sum_{k=1}^{N} \exp(f(\boldsymbol{x}_i)^T f(\boldsymbol{x}_k)). \quad (2)$$

The alignment loss encourages feature representations for positive pairs to be similar, thus be invariant to unnecessary noises. However, training with single alignment loss will result in a trivial solution where all representations are identical. In other words, complete collapse happens. With carefully chosen implementation details, e.g., batch normalization, the problem can be ruled out. But unfortunately, dimensional collapse still has a negative effect on learning.

Thanks to the property of uniformity loss, dimensional collapse can be solved effectively. Reviewing the form of uniformity loss in Eq.(2), it expects average distances between all samples be maximal, thus embeddings will be roughly uniformly distributed in the latent space and preserve much more information. The existence of uniformity loss helps contrastive learning ease dimensional collapse. Intuitively, it can also serve as a sharp tool for alleviating oversmoothing in models like GNNs and Transformers.

Instead of simply adding the uniformity loss to training objective, we aim to design an easy-to-use normalization layer which can be integrated into various models. Concretely, the uniformity loss is used as an energy function underlying our proposed layer, such that descent steps along it corresponds with the forward pass. Similarly, we can also view the layer as the unfolded iterations of a principled optimization function. This perspective is adopted to elucidate GNNs (Yang et al., 2021; Zhu et al., 2021), Transformers (Yang et al., 2022), and classic MLPs (Xie et al., 2021) and CNNs. Unlike previous energy functions for graph regularization or architecture explanation (Yang et al.,

2022), we take the interpretable uniformity loss as energy function, so that node representations are enforced to present a more uniform distribution.

Note that the uniformity loss works by optimizing model parameters while what the normalization layer directly updates is representation itself. So we firstly transfer the uniformity loss, which serves as a training loss, to a kind of architecture loss. Consider a fully connected graph with restricted number of nodes, where node h_i is viewed as representation of a random sample x_i. Reminiscent of $\mathcal{L}_{uniform}$, we define $\dot{\mathcal{L}}_{uniform}$ over all nodes in the graph as

$$\dot{\mathcal{L}}_{uniform} = \sum_i \log \sum_j e^{h_i^T h_j / \tau}. \tag{3}$$

This form of uniformity loss is defined directly on node representations, and we later use it as the underlying energy function for representation update.

3.3 THE PROPOSED CONTRANORM

Till now, we are able to build a connection between layer design and the unfolded iterations of descent steps applied to minimizing uniformity loss. Specifically, we take the derivative of $\dot{L}_{uniform}$ on node representations:

$$\frac{\partial \dot{\mathcal{L}}_{uniform}}{\partial h_i} = \sum_j \frac{\exp(h_i h_j^T)}{\sum_k \exp(h_i h_k^T)} h_j + \sum_j \frac{\exp(h_i h_j^T)}{\sum_k \exp(h_j h_k^T)} h_j, \tag{4}$$

by denoting feature matrix as H with h_i as the i-th row, we rewrite Eq.(4) into a matrix form for simplicity:

$$\frac{\partial \dot{\mathcal{L}}_{uniform}}{\partial H} = (D^{-1}A + AD^{-1})H, \tag{5}$$

where $A = \exp(HH^T)$ and $D = deg(A)$. Naturally, a direct way to reduce uniformity loss is refactoring representations H as

$$H = H - s \times (D^{-1}A + AD^{-1})H, \tag{6}$$

where s is a scalar controlling scale of normalization.

In Eq.(6), there exist two terms $D^{-1}A$ and AD^{-1} multiplied with H. Empirically, the two terms play a similar role in our method. Note that the first term is related to self-attention matrix in Transformers, so we only preserve it and discard the second one. Then Eq.(6) becomes

$$H = H - s \times (D^{-1}A)H = H - s \times \mathrm{softmax}(HH^T)H. \tag{7}$$

In fact, the operation corresponds to the stop-gradient technique, which is widely used in contrastive learning methods (He et al., 2020; Grill et al., 2020). By throwing away some terms in the gradient, stop-gradient makes the training process asymmetric and thus avoids representation collapse with less computational overhead. It verifies the feasibility of our discarding operation. However, the layer induced by Eq.(7) still can not ensure uniformity on representations. Consider an extreme case where $\mathrm{softmax}(HH^T)$ is equal to identity matrix I. Eq.(7) becomes $H = H - s \times H = (1-s)H$, which just makes the scale of H smaller and does not help with alleviating the complete collapse. For the sake of keeping the representation stability, drawing support from layer normalization (Ba et al., 2016), which adjusts the representation according to its mean and variance and thus prevent the representation from shrinking to zero, we append the layer normalization to Eq.(7), namely Contrastive Normalization (**ContraNorm**),

$$H = \mathrm{LayerNorm}\left(H - s \times \mathrm{softmax}(HH^T)H\right). \tag{8}$$

3.4 THEORETICAL ANALYSIS

In this part, we will give some theoretical results on our proposed ContraNorm method. We will show that under some conditions which are easy to satisfy, the ContraNorm update can help alleviate the complete collapse and the dimensional collapse. For the convenience of analysis, we replace the layer normalization with an additional factor $1 + s$ to rescale H, namely

$$H = (1+s)H - s \times \mathrm{softmax}(HH^T)H. \tag{9}$$

Note that Eq.(9) corresponds to uniformity loss with l_2-norm $\ddot{\mathcal{L}}_{uniform} = \sum_i \log \sum_j e^{h_i^T h_j / \tau} - \frac{1}{2}\sum_i \|h_i\|_2^2$, where the negative l_2-norm term can prevent the representations H from dropping to zero.

Proposition 1. *Let $e = (1, 1, \ldots, 1)^T / \sqrt{n}$. For attention matrix $\bar{A} = \text{softmax}(HH^T)$, let $\sigma_{\min}$ be the smallest eigenvalue of $P = (I - ee^T)(I - \bar{A}) + (I - \bar{A})^T(I - ee^T)$. For the ContraNorm update $H^{(1)} = ((1 + s)I - s\bar{A})H^{(0)}$, $s > 0$, we have $Var(H^{(1)}) \geq (1 + s\sigma_{\min}) \cdot Var(H^{(0)})$. Especially, if $\sigma_{\min} \geq 0$, we have $Var(H^{(1)}) \geq Var(H^{(0)})$.*

Proposition 1 gives a bound for the ratio of the variance after and before the update. It shows that the change of the variance is influenced by the symmetric matrix $P = (I - ee^T)(I - \bar{A}) + (I - \bar{A})^T(I - ee^T)$. If P is a semi-positive definite matrix, we will get the result that $Var(H^{(1)}) \geq Var(H^{(0)})$. In Appendix A, we will give out some sufficient conditions for that P is semi-positive definite.

Proposition 2. *Consider the update form*

$$H^{(1)} = (1 + s)H^{(0)} - s(H^{(0)}H^{(0)T})H^{(0)}, \tag{10}$$

let $\sigma_{\max}$ be the largest singular value of $H^{(0)}$. For $s > 0$ satisfying $1 + (1 - \sigma_{\max})s > 0$, we have $\text{erank}(H^{(1)}) > \text{erank}(H^{(0)})$.

Proposition 2 gives a promise of alleviating dimensional collapse under a special update form. Denote $\dot{\mathcal{L}}_{dim} = tr((I - HH^T)^2)/4$, then $\dot{\mathcal{L}}_{dim}$ shares a similar form with Barlow Twins (Zbontar et al., 2021). This loss tries to equate the diagonal elements of the correlation matrix HH^T to 1, and equate the off-diagonal elements of the cross-correlation matrix to 0. This decorrelation reduces the redundancy between dimensions of the representation, thus helps increase the rank of the representation matrix H. Note that

$$\frac{\partial \dot{\mathcal{L}}_{dim}}{\partial H} = (I - HH^T)H. \tag{11}$$

Therefore, Eq.(24) can be rewritten as

$$H^{(1)} = H^{(0)} + s\frac{\partial \dot{\mathcal{L}}_{dim}(H^{(0)})}{\partial H^{(0)}}, \tag{12}$$

which implies that this update form is in fact a ContraNorm with a different uniformity loss. Proposition 2 claims that this update can increase the effective rank of the representation matrix, when s satisfies $1 + (1 - \sigma_{\max})s > 0$. Note that no matter whether $\sigma_{\max} > 0$ or not, if s is sufficiently close to 0, the condition will be satisfied. Under this situation, the update will alleviate the dimensional collapse.

4 EXPERIMENTS

In this section, we demonstrate the effectiveness of ContraNorm by experiments including 1) language understanding tasks on GLUE datasets with BERT and ALBERT (Lan et al., 2020) as the backbones; 2) image classification task on ImageNet100 and ImageNet1k datasets with DeiT as the base model; 3) fully supervised graph node classification task on popular graph datasets with GCN as the backbone. Moreover, we conduct ablative studies on ContraNorm variants comparison and hyperparameters sensitivity analysis.

4.1 EXPERIMENTS ON LANGUAGE MODELS

To corroborate the potential of ContraNorm, we integrate it into two transformer structured models: BERT and ALBERT, and evaluate it on GLUE datasets. GLUE includes three categories of tasks: (i) single-sentence tasks CoLA and SST-2; (ii) similarity and paraphrase tasks MRPC, QQP, and STS-B; (iii) inference tasks MNLI, QNLI, and RTE. For MNLI task, we experiment on both the matched (MNLI-m) and mismatched (MNLI-mm) versions.

We fix the plugging position of ContraNorm after the self-attention module and residual connection. We explore various plugging positions of ContraNorm layer de facto, and find the aforementioned choice is applicable to almost all datasets. For reference, we also report the best performance of each dataset varying position of ContraNorm, denoted as *ContraNorm**. The details of position choices are attached to Appendix C.

Setup. We use a batch size of 32 and fine-tune for 5 epochs over the data for all GLUE tasks. For each task, we select the best scale factor s in Eq.(6) among $(0.005, 0.01, 0.05, 0.1, 0.2)$. We use

| (a) Matthews correlation | (b) Variance | (c) Effective rank |

Figure 3: Comparison of BERT and BERT+ContraNorm with various layer depth settings. Fig.(3a) presents performances of models with block number=12, 24, 36, 48, 60, 72, 84. BERT loses competitive edge when block number exceeds 24, while application of ContraNorm helps it keep advantage till really deep layer setting. Fig.(3b) and Fig.(3c) demonstrate the tendency of features variance and effective rank for models with 72 blocks. It shows ContraNorm alleviates complete collapse and dimensional collapse, explaining the performance advantage over vanilla BERT. We conduct experiments on COLA for resources limited.

Table 1: Results comparison on validation set of GLUE tasks. Following (Devlin et al., 2018), we report F1 scores for QQP and MRPC, Spearman correlations for STS-B, and accuracy scores for the other tasks. ContraNorm* denotes the best model when varying plugging positions of ContraNorm. For each model group, the best performance of each task is bolded.

Dataset	COLA	SST-2	MRPC	QQP	STS-B	MNLI-m	MNLI-mm	QNLI	RTE	Avg
BERT-base	55.28	92.89	88.96	88.24	88.61	84.65	84.61	91.51	68.59	82.59
BERT + ContraNorm	58.83	93.12	89.49	**88.30**	88.66	**84.87**	84.66	**91.78**	70.76	83.39
BERT + ContraNorm*	**59.57**	**93.23**	**89.97**	**88.30**	**88.93**	**84.87**	**84.67**	**91.78**	**70.76**	**83.54**
ALBERT-base	57.35	**93.69**	92.09	87.23	90.54	84.56	84.37	90.90	76.53	83.74
ALBERT + ContraNorm	58.51	92.89	92.86	87.45	90.56	84.33	84.62	91.76	**79.06**	84.67
ALBERT + ContraNorm*	**58.76**	93.23	**92.89**	**87.67**	**90.72**	**84.69**	**84.95**	**92.28**	**79.06**	**84.92**

base models (BERT-base and ALBERT-base) of 12 stacked blocks with hyperparameters fixed for all tasks: number of hidden size 128, number of attention heads 8, maximum sequence length 384. We use Adam (Kingma & Ba, 2014) optimizer with the initial learning rate 0.0001 and the warm-up technique.

Results. As shown in Table 1, ContraNorm substantially improves results on all datasets compared with vanilla BERT. Specifically, our ContraNorm improves the previous average performance from 82.59% to 83.39% for BERT backbone and from 83.74% to 86.47% for ALBERT backbone. We also submit our trained model to GLUE benchmark leaderboard and the results can be found in Appendix D. It is observed that BERT with ContraNorm also outperforms vanilla model across all datasets. To verify the de-oversmoothing effect of ContraNorm. We build models with/without ContraNorm on various layer depth settings. The performance comparison is shown in Fig. 3a. Constant stack of blocks causes obvious deterioration in vanilla BERT, while BERT with ContraNorm maintains competitive advantage. Moreover, for deep models, we also show the tendency of variance and effective rank in Fig. 3b and Fig. 3c, which verifies the power of ContraNorm in alleviating complete collapse and dimensional collapse, respectively.

4.2 EXPERIMENTS ON VISION TRANSFORMERS

We also validate effectiveness of ContraNorm in computer vision filed. We choose DeiT as backbone and models are trained from scratch. Experiments with different depth settings are evaluated on ImageNet100 and ImageNet1k datasets. We insert ContraNorm into base model intermediately following self-attention module. Our implementation is based on the Timm (Wightman, 2019) and DeiT repositories.

Setup. We follow the train recipe of Touvron et al. (2021), and make minimal changes to hyperparameters. Specifically, we use AdamW (Loshchilov & Hutter, 2019) optimizer with consine learning rate decay. We train each model for 150 epochs and the batch size is set to 1024. Augmentation techniques are used to boost the performance. For all experiments, the image size is set to be 224×224.

Table 2: Test accuracy (%) comparison results. For ImageNet100 and ImageNet1k, we use DeiT-tiny and DeiT-small as the baseline respectively. The block number is set to 12, 16 and 24. The best result for each dataset is bolded.

Dataset	Model	#L=12	#L=16	#L=24
ImageNet100	DeiT-tiny	76.58	75.34	76.76
	+ContraNorm	**79.34**	**80.44**	**81.28**
ImageNet1k	DeiT-small	77.32	78.25	77.69
	+ContraNorm	**77.80**	**79.04**	**78.67**

For Imagenet100, we set the scale factor s to 0.2 for all layer depth settings. For Imagenet1k, we set s to 0.2 for models with 12 and 16 blocks, and rise it to 0.3 for models with 24 blocks.

Results. It can be observed from Table 2 that DeiT with ContraNorm outperforms vanilla DeiT with all layer settings on both datasets. Typically, our method shows a gain of nearly 5% on test accuracy for ImageNet100. For ImageNet1k, we boost the performance of DeiT with 24 blocks from 77.69% to 78.67%.

4.3 EXPERIMENTS ON GRAPH NEURAL NETWORKS

We implement ContraNorm as a simple normalization layer after each graph convolution of GCN, and evaluate it on fully supervised graph node classification task. For datasets, we choose two popular citation networks Cora (McCallum et al., 2000) and Citeseer (Giles et al., 1998), and Wikipedia article networks Chameleon and Squirrel (Rozemberczki et al., 2021). More information of datasets are deferred to Appendix E. We compare ContraNorm against a popular normalization layer designed for preventing GCN oversmoothing PairNorm (Zhao & Akoglu, 2020). We also take LayerNorm as a baseline by setting the scale $s = 0$.

Setup. We follow data split setting in Kipf & Welling (2017) with train/validation/test splits of 60%, 20%, 20%, respectively. To keep fair in comparison, we fix the number of channels to 32, dropout rate to 0.6 and L_2 regularization with penalty $5 \cdot 10^{-4}$ as reported in Zhao & Akoglu (2020). We choose the best of scale controller s in range of $\{0.2, 0.5, 0.8, 1.0\}$ for both PairNorm and ContraNorm. For PairNorm, we choose the best variant presented by Zhao & Akoglu (2020).

Results. As shown in Table 3, in shallow layers (e.g., two layer), the addition of ContraNorm reduces the accuracy of vanilla GCN by a small margin, while it help prevent the performance from sharply deteriorating as the layer goes deeper. ContraNorm outperforms PairNorm and LayerNorm in the power of de-oversmoothing. Here, we show the staple in diluting oversmoothing is ContraNorm, and LayerNorm alone fails to prevent GCN from oversmoothing, even amplify the negative effect on Cora with more than 16 layers.

4.4 ABLATION STUDY

Comparison of different ContraNorm variants. Recalling Section 3.3, we improve ContraNorm with stop-gradient technique (SG) by masking the second term. For solving data representation instability, we apply layer normalization (LN) to the original version, while for the convenience of theoretical analysis, layer normalization is replaced by L_2 normalization (L_2N). Here, we investigate the effect of these tricks and the results are shown in Table 4. Compared with the variant with only LayerNorm, ContraNorm with both stop gradient and layer normalization presents better performance. As for the two normalization methods, they are almost comparable for our methods, which verify the applicability of our theoretical analysis.

Hyperparameters sensitivity analysis. We conduct an ablation study regarding the gains of ContraNorm while using different values of scale factor s. Experiments are conducted on GLUE datasets. For each dataset, we vary the normalization scale around the best choice and report the test performance. The results shown in Fig. 4 illustrate that model with ContraNorm is robust in an appropriate range of normalization scaling factor.

Table 3: Test accuracy (%) comparison results. We use GCN as backbone and apply LayerNorm, PairNorm and ContraNorm, respectively. We fairly tune the scale parameter in LayerNorm and ContraNorm. The layer number is set to 2, 4, 8, 16, 32. For every layer setting, the best accuracy is marked in blue background, and the second best is underlined. Results are averaged over 5 runs.

Dataset	Model	#L=2	#L=4	#L=8	#L=16	#L=32
Cora	Vanilla GCN	81.75 ± 0.51	72.61 ± 2.42	17.71 ± 6.89	20.71 ± 8.54	19.69 ± 9.54
	+LayerNorm	79.96 ± 0.73	77.45 ± 0.67	39.09 ± 4.68	7.79 ± 0.00	7.79 ± 0.00
	+PairNorm	75.32 ± 1.05	72.64 ± 2.67	71.86 ± 3.31	54.11 ± 9.49	36.62 ± 2.73
	+ContraNorm	79.75 ± 0.33	77.02 ± 0.96	74.01 ± 0.64	68.75 ± 2.10	46.39 ± 2.46
CiteSeer	Vanilla GCN	69.18 ± 0.34	55.01 ± 4.36	19.65 ± 0.00	19.65 ± 0.00	19.65 ± 0.00
	+LayerNorm	63.27 ± 1.15	60.91 ± 0.76	33.74 ± 6.15	19.65 ± 0.00	19.65 ± 0.00
	+PairNorm	61.59 ± 1.35	53.01 ± 2.19	55.76 ± 4.45	44.21 ± 1.73	36.68 ± 2.55
	+ContraNorm	64.06 ± 0.85	60.55 ± 0.72	59.30 ± 0.67	49.01 ± 3.49	36.94 ± 1.70
Chameleon	Vanilla GCN	45.79 ± 1.20	37.85 ± 1.35	22.37 ± 0.00	22.37 ± 0.00	23.37 ± 0.00
	+LayerNorm	63.95 ± 1.29	55.79 ± 1.25	34.08 ± 2.62	22.37 ± 0.00	22.37 ± 0.00
	+PairNorm	62.24 ± 1.73	58.38 ± 1.48	49.12 ± 2.32	37.54 ± 1.70	30.66 ± 1.58
	+ContraNorm	64.78 ± 1.68	58.73 ± 1.12	48.99 ± 1.52	40.92 ± 1.74	35.44 ± 3.16
Squirrel	Vanilla GCN	29.47 ± 0.96	19.31 ± 0.00	19.31 ± 0.00	19.31 ± 0.00	19.31 ± 0.00
	+LayerNorm	43.04 ± 1.25	29.64 ± 5.50	19.63 ± 0.45	19.96 ± 0.44	19.40 ± 0.19
	+PairNorm	43.86 ± 0.41	40.25 ± 0.55	36.03 ± 1.43	29.55 ± 2.19	29.05 ± 0.91
	+ContraNorm	47.24 ± 0.66	40.31 ± 0.74	35.85 ± 1.58	32.37 ± 0.93	27.80 ± 0.72

Table 4: Performance comparison among different variants of ContraNorm. SG, LN, L_2N are the abbreviations of stop gradient, layer normalization and L_2 normalization, respectively. All experiments are conducted on GLUE tasks with the same parameter settings. We bold the best result for each task.

Variants			Datasets									Avg
SG	LN	L_2N	COLA	SST-2	MRPC	QQP	STS-B	MNLI-m	MNLI-mm	QNLI	RTE	
	✓		58.80	**93.12**	89.60	88.35	**88.97**	84.81	**84.67**	91.47	68.23	83.11
✓		✓	**59.82**	93.00	89.64	**88.37**	88.92	84.72	84.58	**91.58**	**68.95**	83.29
✓	✓		59.57	**93.12**	**89.97**	88.30	88.93	**84.84**	84.67	**91.58**	**68.95**	**83.33**

(a) RTE   (b) CoLA   (c) STS-B   (d) MRPC

Figure 4: Performance when varying scale factor s on GLUE datasets. We choose BERT as the base model. The varying range is an interval containing the best choice of s. Here, we fix it to $[0.005, 0.1]$ for all tasks. More results can be found in Appendix F.

5 CONCLUSION

In this paper, we point out the deficiencies of current metrics in characterizing over-smoothing, and highlight the importance of taking dimensional collapse as the entry point for oversmoothing analysis. Inspired by the uniformity loss in contrastive learning, we design an optimization-induced normalization layer ContraNorm. Our theoretical findings indicate ContraNorm mitigates dimensional collapse successfully by reducing variance and effective rank of representations. Experiments show that ContraNorm boosts the performance of Transformers and GNNs on various tasks. Our work provides a new perspective from contrastive learning on solving the oversmoothing problem, which helps motivate the following extensive research.

REFERENCES

Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016.

Ming Chen, Zhewei Wei, Zengfeng Huang, Bolin Ding, and Yaliang Li. Simple and deep graph convolutional networks. In *ICML*, 2020.

Xinlei Chen and Kaiming He. Exploring simple siamese representation learning. In *CVPR*, 2021.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Yihe Dong, Jean-Baptiste Cordonnier, and Andreas Loukas. Attention is not all you need: Pure attention loses rank doubly exponentially with depth. In *ICML*, 2021.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *ICLR*, 2021.

Kawin Ethayarajh. How contextual are contextualized word representations? comparing the geometry of bert, elmo, and gpt-2 embeddings. *arXiv preprint arXiv:1909.00512*, 2019.

William Fulton. Eigenvalues, invariant factors, highest weights, and schubertcalculus. *Bulletin of The American Mathematical Society - BULL AMER MATH SOC*.

Jun Gao, Di He, Xu Tan, Tao Qin, Liwei Wang, and Tieyan Liu. Representation degeneration problem in training natural language generation models. In *ICLR*, 2019.

C Lee Giles, Kurt D Bollacker, and Steve Lawrence. Citeseer: An automatic citation indexing system. In *Proceedings of the third ACM conference on Digital libraries*, 1998.

Chengyue Gong, Dilin Wang, Meng Li, Vikas Chandra, and Qiang Liu. Vision transformers with patch diversification. *arXiv preprint arXiv:2104.12753*, 2021.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Guo, Mohammad Gheshlaghi Azar, et al. Bootstrap your own latent-a new approach to self-supervised learning. 2020.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *CVPR*, 2020.

Tianyu Hua, Wenxiao Wang, Zihui Xue, Sucheng Ren, Yue Wang, and Hang Zhao. On feature decorrelation in self-supervised learning. In *ICCV*, 2021.

Li Jing, Pascal Vincent, Yann LeCun, and Yuandong Tian. Understanding dimensional collapse in contrastive self-supervised learning. In *ICLR*, 2022.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *ICLR*, 2017.

Zhenzhong Lan, Mingda Chen, Sebastian Goodman, Kevin Gimpel, Piyush Sharma, and Radu Soricut. Albert: A lite bert for self-supervised learning of language representations. In *ICLR*, 2020.

Qimai Li, Zhichao Han, and Xiao-Ming Wu. Deeper insights into graph convolutional networks for semi-supervised learning. In *AAAI*, 2018.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Ro{bert}a: A robustly optimized {bert} pre-training approach, 2020.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *ICCV*, 2021.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *ICLR*, 2019.

Andrew Kachites McCallum, Kamal Nigam, Jason Rennie, and Kristie Seymore. Automating the construction of internet portals with machine learning. *Information Retrieval*, 2000.

Pranav Rajpurkar, Robin Jia, and Percy Liang. Know what you don't know: Unanswerable questions for squad. *arXiv preprint arXiv:1806.03822*, 2018.

Olivier Roy and Martin Vetterli. The effective rank: A measure of effective dimensionality. In *EUSIPCO*, 2007.

Benedek Rozemberczki, Carl Allen, and Rik Sarkar. Multi-scale attributed node embedding. *Journal of Complex Networks*, 2021.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *IJCV*, 2015.

Andrew W Senior, Richard Evans, John Jumper, James Kirkpatrick, Laurent Sifre, Tim Green, Chongli Qin, Augustin Žídek, Alexander WR Nelson, Alex Bridgland, et al. Improved protein structure prediction using potentials from deep learning. *Nature*, 2020.

Han Shi, JIAHUI GAO, Hang Xu, Xiaodan Liang, Zhenguo Li, Lingpeng Kong, Stephen M. S. Lee, and James Kwok. Revisiting over-smoothing in BERT from the perspective of graph. In *ICLR*, 2022.

Robin Strudel, Ricardo Garcia, Ivan Laptev, and Cordelia Schmid. Segmenter: Transformer for semantic segmentation. In *ICCV*, 2021.

Yehui Tang, Kai Han, Chang Xu, An Xiao, Yiping Deng, Chao Xu, and Yunhe Wang. Augmented shortcuts for vision transformers. *NeurIPS*, 2021.

Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. Training data-efficient image transformers & distillation through attention. In *ICML*, 2021.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. 2017.

Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R. Bowman. GLUE: A multi-task benchmark and analysis platform for natural language understanding. In *ICLR*, 2019.

Peihao Wang, Wenqing Zheng, Tianlong Chen, and Zhangyang Wang. Anti-oversmoothing in deep vision transformers via the fourier domain analysis: From theory to practice. *arXiv preprint arXiv:2203.05962*, 2022.

Tongzhou Wang and Phillip Isola. Understanding contrastive representation learning through alignment and uniformity on the hypersphere. In *ICML*, 2020.

Ross Wightman. Pytorch image models. https://github.com/rwightman/pytorch-image-models, 2019.

Xingyu Xie, Qiuhao Wang, Zenan Ling, Xia Li, Yisen Wang, Guangcan Liu, and Zhouchen Lin. Optimization induced equilibrium networks. *arXiv preprint arXiv:2105.13228*, 2021.

Yongyi Yang, Tang Liu, Yangkun Wang, Jinjing Zhou, Quan Gan, Zhewei Wei, Zheng Zhang, Zengfeng Huang, and David Wipf. Graph neural networks inspired by classical iterative algorithms. In *ICML*, 2021.

Yongyi Yang, Zengfeng Huang, and David Wipf. Transformers from an optimization perspective. *arXiv preprint arXiv:2205.13891*, 2022.

Rex Ying, Ruining He, Kaifeng Chen, Pong Eksombatchai, William L Hamilton, and Jure Leskovec. Graph convolutional neural networks for web-scale recommender systems. In *ACM SIGKDD*, 2018.

Jure Zbontar, Li Jing, Ishan Misra, Yann LeCun, and Stéphane Deny. Barlow twins: Self-supervised learning via redundancy reduction. In *ICML*, 2021.

Lingxiao Zhao and Leman Akoglu. Pairnorm: Tackling oversmoothing in gnns. In *ICLR*, 2020.

Daquan Zhou, Bingyi Kang, Xiaojie Jin, Linjie Yang, Xiaochen Lian, Zihang Jiang, Qibin Hou, and Jiashi Feng. Deepvit: Towards deeper vision transformer. *arXiv preprint arXiv:2103.11886*, 2021.

Jie Zhou, Ganqu Cui, Shengding Hu, Zhengyan Zhang, Cheng Yang, Zhiyuan Liu, Lifeng Wang, Changcheng Li, and Maosong Sun. Graph neural networks: A review of methods and applications. *AI Open*, 2020.

Meiqi Zhu, Xiao Wang, Chuan Shi, Houye Ji, and Peng Cui. Interpreting and unifying graph neural networks with an optimization framework. In *Proceedings of the Web Conference 2021*, 2021.

A PROOFS FOR PROPOSITIONS IN SECTION 4.3

We give out two lemmas.

Lemma A.1. Denote $e = [1, 1, \ldots, 1]^T / \sqrt{n}$. For any update form $X^{(1)} = PX^{(0)}$ and $\lambda > 0$, if the eigenvalues of $(I - ee^T) - \lambda P^T (I - ee^T) P$ are all not larger than zero, then we have $\mathrm{Var}(X^{(1)}) \geq \lambda^{-1} \cdot \mathrm{Var}(X^{(0)})$.

Proof. We denote $X^{(0)} X^{(0)T} = Y \mathrm{diag}(\omega_1, \ldots, \omega_n) Y^T$ for the eigen-decomposition of $X^{(0)} X^{(0)T}$, where $Y = [y_1, y_2, \ldots, y_n]$ is the orthogonal basis and all $\omega_i \geq 0$. Note that $(I - ee^T)^2 = (I - ee^T)$. Therefore,

$$
\begin{aligned}
\mathrm{Var}(X^{(0)}) &= \|(I - ee^T) X^{(0)}\|_F^2 \\
&= tr\{|(I - ee^T) X^{(0)} X^{(0)T} (I - ee^T)\} \\
&= tr\{(I - ee^T) Y \mathrm{diag}(\omega_1, \ldots, \omega_n) Y^T (I - ee^T)\} \\
&= tr\{\mathrm{diag}(\omega_1, \ldots, \omega_n) Y^T (I - ee^T)(I - ee^T) Y\} \\
&= tr\{\mathrm{diag}(\omega_1, \ldots, \omega_n) Y^T (I - ee^T) Y\} \\
&= \sum_{i=1}^n \omega_i y_i^T (I - ee^T) y_i
\end{aligned}
\tag{13}
$$

Similarly, we have

$$
\mathrm{Var}(X^{(1)}) = \sum_{i=1}^n \omega_i y_i^T P (I - ee^T) P y_i.
\tag{14}
$$

Therefore, we have

$$
\mathrm{Var}(X^{(0)}) - \lambda \mathrm{Var}(X^{(1)}) = \sum_{i=1}^n \omega_i y_i^T \{(I - ee^T) - \lambda P^T (I - ee^T) P\} y_i.
\tag{15}
$$

Thus, if the eigenvalues of $(I - ee^T) - \lambda P^T (I - ee^T) P := \Sigma$ are all not larger than zero, Σ is semi-negative definite, then we have

$$
y_i^T \{(I - ee^T) - \lambda P^T (I - ee^T) P\} y_i \leq 0,
\tag{16}
$$

which implies that $\mathrm{Var}(X^{(0)}) - \lambda \mathrm{Var}(X^{(1)}) \leq 0$. Therefore, $\mathrm{Var}(X^{(1)}) \geq \lambda^{-1} \cdot \mathrm{Var}(X^{(0)})$. □

The second lemma is from the Eq.(13) in (Fulton).

Lemma A.2. Let A, B, C be symmetric matrices and $C = A + B$. Suppose the eigenvalues of A are $\alpha_1 \geq \alpha_2 \geq \cdots \geq \alpha_n$, the eigenvalues of B are $\beta_1 \geq \beta_2 \geq \cdots \geq \beta_n$, and the eigenvalues of C are $\gamma_1 \geq \gamma_2 \geq \cdots \geq \gamma_n$. Then we have the inequality

$$
\max_{i+j=n+k} \alpha_i + \beta_j \leq \gamma_k \leq \min_{i+j=k+1} \alpha_i + \beta_j.
\tag{17}
$$

We can now start to prove Proposition 1.

Proposition 1. Let $e = (1, 1, \ldots, 1)^T/\sqrt{n}$. For attention matrix $\bar{A} = \text{softmax}(HH^T)$, let $\sigma_{\min}$ be the smallest eigenvalue of $P = (I - ee^T)(I - \bar{A}) + (I - \bar{A})^T(I - ee^T)$. For the ContraNorm update $H^{(1)} = ((1+s)I - s\bar{A})H^{(0)}$, $s > 0$, we have $Var(H^{(1)}) \geq (1 - s\sigma_{\min})^{-1} \cdot Var(H^{(0)})$. Especially, if $\sigma_{\min} \geq 0$, we have $Var(H^{(1)}) \geq Var(H^{(0)})$.

Proof. We denote $\Sigma = (I - ee^T) - \lambda((1+s)I - s\bar{A})^T(I - ee^T)((1+s)I - s\bar{A})$. Then,

$$\Sigma = (1 - \lambda)I - \lambda(s(I - \bar{A})^T(I - ee^T) - s(I - ee^T)(I - \bar{A}) - s^2(I - \bar{A})^T(I - ee^T)(I - \bar{A}))$$
$$= (1 - \lambda)I - \lambda sP - \lambda s^2(I - \bar{A})^T(I - ee^T)(I - \bar{A}). \tag{18}$$

Let $\alpha_1 \geq \alpha_2 \geq \cdots \geq \alpha_n$ be the eigenvalues of Σ. Since $I - ee^T$ has a eigenvalue of 0 and $n - 1$ eigenvalues of 1, $I - ee^T$ is a semi-definite positive matrix. Thus, $s^2(I - \bar{A})^T(I - ee^T)(I - \bar{A})$ is also a semi-definite positive matrix. Notice that the largest eigenvalue of $(1 - \lambda)I - sP$ is $(1 - \lambda) - s\sigma_{\min}$ and the largest eigenvalue of $-s^2(I - \bar{A})^T(I - ee^T)(I - \bar{A})$ is 0. Therefore, by Lemma A.2, the largest eigenvalue of Σ is less or equal to $(1 - \lambda) - s\sigma_{\min}$. Let $\lambda = 1 - s\sigma_{\min}$, then the largest eigenvalue of Σ is less or equal to 0. By Lemma A.1, we have $Var(H^{(1)}) \geq (1 - s\sigma_{\min})^{-1} \cdot Var(H^{(0)})$.

Moreover, if $\sigma_{\min} \geq 0$, then $(1 - s\sigma_{\min})^{-1} \geq 1$, leading to $Var(H^{(1)}) \geq Var(H^{(0)})$. $\square$

Remark. Now we discuss some sufficient conditions for $\sigma_{\min} \geq 0$. If P is a diagonally dominant matrix, then we will have the result $\sigma_{\min} \geq 0$. Denote $a_{ij} = \bar{A}_{ij}$, $b_{ij} = \sigma_{ij} - a_{ij}$ and $Q = (I - ee^T)(I - \bar{A})$, where $\sigma ij = 1$ if $i = j$ and $\sigma ij = 0$ if $i \neq j$, then we have

$$Q_{ij} = b_{ij} - \frac{1}{n}\sum_{k=1}^{n}(b_{kj}). \tag{19}$$

If we have $\sum_{k=1}^{n} a_{kj} \leq 1 + na_{ij}$ for any i, j, then we will have

$$b_{jj} \geq \frac{\sum_{k=1}^{n} b_{kj}}{n} \geq b_{ij}, \ i \neq j. \tag{20}$$

Notice that $\sum_{k=1}^{n} b_{kj} = 0$, we have

$$|Q_{jj}| = |\sum_{k\neq j} Q_{kj}| \tag{21}$$

Since $\bar{A}$ is an attention matrix, we also have

$$|Q_{jj}| = |\sum_{k\neq j} Q_{jk}|. \tag{22}$$

Therefore, we have

$$\begin{aligned}
|P_{jj}| &= 2|Q_{jj}| \\
&= |\sum_{k\neq j} Q_{kj}| + |\sum_{k\neq j} Q_{jk}| \\
&\geq |\sum_{k\neq j} Q_{kj} + \sum_{k\neq j} Q_{jk}| \\
&\geq |\sum_{k\neq j} P_{kj}|,
\end{aligned} \tag{23}$$

which indicates that P is a diagonally dominated matrix, thus $\sigma_{\min} \geq 0$. Therefore, $\sum_{k=1}^{n} a_{kj} \leq 1 + na_{ij}$ for any i, j is just a sufficient condition. A special case for this is $\sum_{k=1}^{n} a_{kj} = 1, \forall k$.

We now move on to the proof of Proposition 2. We first give a lemma on the property of effective rank.

Lemma A.3. Let the eigenvalues of AA^T be $\lambda_1 \geq \lambda_2 \geq \cdots \geq \lambda_n$ and the eigenvalues of BB^T be $\sigma_1 \geq \sigma_2 \geq \ldots \sigma_n$. If σ_i/λ_i is increasing as i increases, then we have $\text{erank}(B) \geq \text{erank}(A)$.

This lemma can be proved just using the definition of the effective rank.

Proposition 2. Consider the update form

$$\boldsymbol{H}^{(1)} = (1+s)\boldsymbol{H}^{(0)} - s(\boldsymbol{H}^{(0)}\boldsymbol{H}^{(0)T})\boldsymbol{H}^{(0)}, \tag{24}$$

let $\sigma_{\max}$ be the largest singular value of $\boldsymbol{H}^{(0)}$. For $s > 0$ satisfying $1 + (1 - \sigma_{\max})s > 0$, we have $\mathrm{erank}(\boldsymbol{H}^{(1)}) > \mathrm{erank}(\boldsymbol{H}^{(0)})$.

Proof. We have

$$\boldsymbol{H}^{(1)} = ((1+s)\boldsymbol{H}^{(0)} - s\boldsymbol{H}^{(0)}\boldsymbol{H}^{(0)T})\boldsymbol{H}^{(0)}. \tag{25}$$

Therefore,

$$\boldsymbol{H}^{(1)}\boldsymbol{H}^{(1)T} = s^2(\boldsymbol{H}^{(0)}\boldsymbol{H}^{(0)T})^3 - 2s(1+s)(\boldsymbol{H}^{(0)}\boldsymbol{H}^{(0)T})^2 + (1+s)^2(\boldsymbol{H}^{(0)}\boldsymbol{H}^{(0)T}) \tag{26}$$

Suppose $\lambda_1 \geq \lambda_2 \geq \cdots \geq \lambda_n$ are the eigenvalues of $\boldsymbol{H}^{(0)}\boldsymbol{H}^{(0)T}$, then $\boldsymbol{H}^{(1)}\boldsymbol{H}^{(1)T}$ has the same eigenvectors as $\boldsymbol{H}^{(0)}\boldsymbol{H}^{(0)T}$, and its eigenvalues are $(\lambda_i s - (1+s))^2 \lambda_i$. Since s satisfies $1 + (1 - \sigma_{\max}s) > 0$, we have $1 + s > \lambda_i s$. Therefore $(\lambda_i s - (1+s))^2$ is increasing as i increases, resulting the fact that $\mathrm{erank}(\boldsymbol{H}^{(1)}) > \mathrm{erank}(\boldsymbol{H}^{(0)})$ by using Lemma A.3. $\qquad\square$

B   METRICS CALCULATING FEATURE AND ATTENTION MAP COSINE SIMILARITY

Following Wang et al. (2022), given feature map $\boldsymbol{H} \in \mathbb{R}^{N \times D}$ and attention map of the h-th head $\boldsymbol{A}^{(h)} \in \mathbb{R}^{N \times N}$ with batch size N and hidden embedding size D, the feature cosine similarity and the attention cosine similarity is computed as

$$\mathrm{sim}_f = \frac{2}{N(N-1)} \sum_{i,j>i} \frac{\boldsymbol{h}_i^T \boldsymbol{h}_j}{\|\boldsymbol{h}_i\|_2 \|\boldsymbol{h}_j\|_2}, \quad \mathrm{sim}_{attn} = \frac{2}{N(N-1)H} \sum_{i,j>i} \frac{\boldsymbol{a}_i^{(h)T} \boldsymbol{a}_j^{(h)}}{\|\boldsymbol{a}_i^{(h)}\|_2 \|\boldsymbol{a}_j^{(h)}\|_2},$$

where $\boldsymbol{h}_i$ denotes the i-th row of $\boldsymbol{H}$, $\boldsymbol{a}_i$ is the i-th column of $\boldsymbol{A}$, and H is the number of attention heads.

C   CHOICES OF CONTRANORM PLUGGING POSITION

We explore two ways to integrate ContraNorm into BERT and ALBERT. Concretely, consider the update of $\boldsymbol{H}^{(l)}$ in l-th block of Transformers

$$\boldsymbol{H}^{(l)} = \mathrm{MultiHeadAttention}(\boldsymbol{H}^{(l)}), \tag{27}$$

$$\boldsymbol{H}^{(l)} = \boldsymbol{H}^{(l)} + \boldsymbol{X}, \tag{28}$$

$$\boldsymbol{H}^{(l)} = \mathrm{LayerNorm}(\boldsymbol{H}^{(l)}), \tag{29}$$

where $\boldsymbol{X} = \boldsymbol{H}^{(0)}$ is the input tensor.

We choose positions 1) between Eq.(27) and Eq.(28), named as *before-residual*; 2) between Eq.(28) and Eq.(29), named as *after-residual*. The performance comparison between the two positions on GLUE datasets are shown in Table.(5). It is observed that put ContraNorm after the residual connection is slightly outperforms that before residual. Therefore, we choose the after-residual variant as our basic ContraNorm.

D   RESULTS ON TEST SET OF GLUE DATASETS

We submit our trained model to GLUE benchmark leaderboard and the resultant feedback of performance is shown in Table (6).

Table 5: Results comparison on different plugging positions of ContraNorm. Experiments are evaluated on the validation set of GLUE tasks. The best result for each task is bolded.

Dataset	COLA	SST-2	MRPC	QQP	STS-B	MNLI-m	MNLI-mm	QNLI	RTE	Avg
BERT-base	55.28	92.89	88.96	88.24	88.61	84.65	84.61	91.51	68.59	82.59
before-residual	59.57	93.12	89.97	88.30	88.93	84.84	84.67	91.58	68.95	83.33
after-residual	58.83	93.12	89.49	88.30	88.66	84.87	84.66	91.78	70.76	83.39

Table 6: Results comparison on test set of GLUE tasks.

Dataset	COLA	SST-2	MRPC	QQP	STS-B	MNLI-m	MNLI-mm	QNLI	RTE	Avg
BERT-base	53.3	92.8	86.8	71.2	82.8	84.4	83.2	90.9	66.3	79.1
BERT + ContraNorm	54.5	93.0	87.9	71.4	83.0	84.5	83.4	91.0	66.9	79.5

E INTRODUCTION OF GRAPH DATASETS

Citation Network. Cora, CiteSeer are three popular citation graph datasets. In these graphs, nodes represent papers and edges correspond to the citation relationship between two papers. Nodes are classified according to academic topics.

Wikipedia Network. Chameleon and Squirrel are Wikipedia page networks on specific topics, where nodes represent web pages and edges are the mutual links between them. Node features are the bag-of-words representation of informative nouns. The nodes are classified into four categories according to the number of the average monthly traffic of the page.

Statics of datasets are shown in Table.(7).

F ABLATION STUDY FULL RESULTS

In Fig.(5), we show the performance of BERT+ContraNorm with varying scaling factor s on GLUE datasets. Other parameters remain consistent.

Figure 5: Performance when varying scale factor s on GLUE datasets. We choose BERT as the base model. The varying range is an interval containing the best choice of s. Here, we fix it to $[0.005, 0.1]$ for all tasks.

Table 7: Graph datasets statics.

Category	Dataset	# Nodes	# Edges	# Features	Degree	# Classes
Citation	Cora	2708	5278	1433	4.90	7
	CiteSeer	3327	4552	3703	3.77	6
Wikipedia	Chameleon	2277	36101	500	5.0	6
	Squirrel	5201	217073	2089	154.0	4