FaceUI: Leveraging Front-Facing Camera Input to Access Mid-Air Spatial Interfaces on Smartphones.

First Last*
Author Affiliation

First Last†
Author Affiliation

First Last‡
Author Affiliation

Figure 1: A FaceUI-based calendar app. A user can access calendar events on a date by moving the phone in mid-air around their face.

ABSTRACT

We present FaceUI, a novel strategy to access mid-air face-centered spatial interfaces with off-the-shelf smartphones. FaceUI uses the smartphone's front-facing camera to track the phone's mid-air position relative to the user's face. This self-contained tracking mechanism opens up new opportunities to enable mid-air interactions on off-the-shelf smartphones. We demonstrate one possibility that leverages the empty mid-air space in front of the user to accommodate virtual windows which the user can browse by moving the phone in the space in front of their face. We inform our implementation of FaceUI by first studying essential design factors, such as the comfortable face-to-phone distance range and appropriate viewing angles for browsing mid-air windows and visually accessing their content. After that, we compare users' performance with FaceUI to their performance when using a touch-based interface in an analytic task that requires browsing multiple windows. We find that FaceUI offers better performance than the traditional touch-based interface. We conclude with recommendations for the design and use of face-centered mid-air interfaces on smartphones.

Index Terms: Human-centered computing—Visualization—Visualization techniques—Treemaps; Human-centered computing—Visualization—Visualization design and evaluation methods

1 INTRODUCTION

When using touch-based input on a smartphone, people typically hold the phone more or less in front of the face. This posture allows for easy visual access to screen content. Clearly, while interacting, having the phone in a stationary position seems preferable, and, accordingly, most smartphone interfaces assume a stable in-front-of-the-face posture. However, many people are also very skilled in

---

*e-mail: author@email.com

†e-mail: author@email.com

‡e-mail: author@email.com

sub-optimal situations when the phone is not still in front of their face, such as to text while walking. In this paper, we explore how to design smartphone interfaces that require that the user deliberately moves the phone in the space in front of the face as part of the interaction. We use the high-resolution front-facing camera on a standard smartphone together with machine learning algorithms [10] to track the spatial location of the phone relative to the user's face. This allows us to integrate the large empty space in front of the user into new spatial interactions and user interfaces.

Prior research have explored ways to extend a smartphone's input capabilities by shifting the interaction space into the empty in-air space surrounding users' bodies or their mobile devices. For instance, Virtual Shelves [27] allows users to point their hand inside a hemisphere in front of their body to access a set of discrete virtual and invisible items, relying heavily on the users' spatial recall. Similarly, the Imaginary Interface [11] is a mid-air interface in front of the user's body that can be used for pointing and drawing activities. In more recent work, Hasan et al. [19] present the AirPane system and demonstrate how the mid-air space surrounding a mobile device can be used for browsing information in an e-commerce application. These and most other prior projects that demonstrate approaches to leverage around-body or around-device interactions rely on external tracking systems, which is not practical in real-life usage situations. Furthermore, most earlier projects are also limited in that they either do not provide any visual representation of the in-air space (and its interaction objects) at all, or they provide very limited visual information that typically is decoupled from the actual location within the in-air space.

In this paper, we present FaceUI, an approach that avoid these shortcomings. FaceUI is a novel strategy that leverages mid-air space in front of the user. FaceUI uses a smartphone's built-in front-facing camera to detect and track the phone's position relative to the user's face. This self-contained tracking approach allows visual access to the in-air space since the screen content is updated depending on the phone's in-air location and the virtual content at that location. The concept is visualized in Figure 1 where a user navigates a FaceUI-based calendar.

To our best knowledge, ways to leverage face-centered in-air spaces to access virtual user interfaces (UIs) with off-the-shelf smart-

phones have never been explored before. With two user studies, we first investigate how the in-air space can be structured to accommodate virtual UIs used for information exploration on smartphones. We identify the comfortable phone-to-face distance range for accessing virtual UIs in the in-air space and suitable viewing angles for browsing and inspecting content that reside in the in-air space. We use this knowledge to design FaceUI-based calendar application. In a third user study, we evaluate users' performance in a calendar browsing task comparing our FaceUI-based calendar with a touch-based calendar interface. Our results show that the FaceUI-approach can offer considerable advantages compared to traditional touch-based interfaces. We end our exploration with showcasing further FaceUI-based applications.

Accordingly, our contributions include: 1) FaceUI, a novel face-centered spatial in-air interface-approach for off-the-shelf smartphones; 2) an exploration of suitable design parameters for FaceUI-based applications; 3) a performance comparison between a FaceUI application and standard touch interface in an analytic task; and 4) showcasing further promising FaceUI-enabled interactive applications that demonstrate the potential of face-centered smartphone interfaces.

2 BACKGROUND AND RELATED WORK

We review prior work that has explored ways to design spatial interfaces, interaction spaces, and interaction techniques. These earlier projects inspired the design of our face-centered spatial user interface, FaceUI. The previous research closely aligned to components of FaceUI falls mainly under around-device interaction, on- and around-body interaction, and Face-Centered Input.

2.1 Around-Device Interaction

There has been substantial prior research work exploring the use of mid-air space around mobile devices. Researchers have demonstrated that the mid-air space can be used for novel interactions, such as for virtual content browsing and selection [14, 17, 19, 23, 37], map navigation [18, 21], mode switching [21] and typing [30]. For instance, AD-Binning [17] leveraged the empty 2D space around a smartphone to off-load and browse content into the space. They further showed that the mid-air space could facilitate faster access to items than the standard touch input. In a similar work, Hasan et al. [19] showed that 3D in-air space around a device could be used for browsing m-commerce applications. Researchers also investigated ways to track users activities around the device with commercial tracking solutions (e.g., Vicon tracking [18, 19]) or using different cameras or sensor-based solutions (e.g., depth camera [7, 24] , distance sensor [6, 23]). Though these solutions offer precise motion capture data, they require either environments, users or devices to be instrumented with sensors. This makes mobile devices less portable to be used in public spaces.

2.2 On- and Around-Body Interaction

Prior work investigated ways to use the on- and around-body space for designing novel interaction with devices [3, 5, 9, 27]. For instance, researchers [11–13] explored the use on body locations such as palm to access on-screen contents. Imaginary Phone [12] used user's palm as the input surface for iPhone. In a similar work, Gustafson et al. [13] investigated palm-based imaginary interface for supporting visually impaired users. Imaginary Interfaces [11] allowed users to perform spatial interaction on empty palm and without visual feedback. In addition, palm has been used for trigger pre-defined functions [26], to perform 3D rotation [24], or use it as an input space for augmenting keyboards [34]. Similarly, researchers explored the skin as an interactive touch surface [16, 39, 40]. They commonly used external depth cameras to detect and track hand and finger activities such as tapping and sliding on body parts.

Researchers also investigated using the mid-air space around the body as a novel interaction space. For instance, Virtual Shelves [27] demonstrated that the mid-air space in front of users could be used to trigger shortcuts. With a study, they showed that users could recall shortcuts by moving their phone into a 7×4 grid on a circular hemisphere in front of them. Yee et al. [38] designed a solution allowing users to move the mobile phone to different locations around the body and change the on-screen content based on the device's location relative to the body. Ens et al. [9] designed Personal Cockpit leveraging the around-body space to display virtual windows in an head-worn displays. In a similar work, Babic et al. [5] explored Gesture Drawer, an one-handed interaction technique allowing users to define and interact with self-define imaginary interfaces while moving their hand to interact with the interfaces. Researchers have also investigated mid-air spatial interface specific to applications in mixed-reality [9, 29, 35], for games [33], workspace navigation [22]. For instance, Lubos et al. [29] introduced kinespheres, an mixed-reality based body-centric spatial interface within arm's reach. They received positive feedback from users on using their method compared to traditional head-centered interaction for mixed-reality. Yan et al. [35] explored an eyes-free target acquisition technique for mixed-reality by placing the targets in around-body space. Way Out [33] is a game scenario where players can navigate through an omni-directional panorama scene by moving the device around the body using the built-in motion sensors in smartphones. In a recent work, Kim et al. [22] demonstrated image and map zoom-in and zoom-out using the vision-based interface OddEyeCam, that detects and tracks the location of the mobile phone with respect to the user's body using external sensors such as wide-view RGB cameras and narrow-view depth cameras.

2.3 Face-Centered Input

Prior research investigated using head and face movements as an input to design new face-centered interactions on devices. For instance, Zhao et al. [41] used a combination of facial movements, device motion and touch for designing face-centered interaction techniques on smartphones. Kumar et al. [25] leveraged eye gaze to scroll mobile phone contents. Yang et al. [36] used a face interpretation engine for enabling face-aware applications for smartphones using the phone's front-facing camera and built-in motion sensors. Similarly, Babie et al. [4] designed Simo that used head movement as input for pointing on a distant large display. Instead of using external cameras, they used the smartphone's front-facing camera to detect face orientation. Rustagi et al. [31] explored touchless typing using head gestures detected by the smartphone's front-facing camera and used them to type on an on-screen QWERTY keyboard. We also observed that the smartphone's front-facing camera could be used to design new strategies such as for rotation of on-screen content on mobile devices by detecting direction changes of objects from the camera view [1, 2, 8].

The manifold opportunities of spatial mid-air interfaces, as demonstrated by earlier projects, inspire us to continue on this promising path. However, in opposite to most previous projects which use external sensors or cameras to identify interaction gestures, we are interested in using a self-contained tracking mechanism to detect in-air movements. Similar to a few face-tracking systems [4, 31, 41], our FaceUI-approach also uses the front-camera of a smartphone to detect changes in the relative positions of the user's face and the phone. However, FaceUI differ from earlier systems in that it does not rely on any other sensors than the smartphone's front-facing camera. Furthermore, we aim at interactions where the user keeps the head still while moving the phone. Earlier approaches [4, 31, 41] require the user to do the opposite, to move the head while holding the phone in a fixed position. In this way, we intend to create the sensation of a hemispherical interaction space that is anchored in front of the user's face but moves along with the

Figure 2: Study 1 task. Using (a) horizontal and (b) vertical mid-air movements to select invisible in-air items. (c) Task prompt. (d) A participant holding the phone in the neutral start position, straight in front of the face.

user (through the self-contained tracking). In this first exploration of such an interaction hemisphere, we focus on using virtual application windows that are located inside the hemisphere. When the user moves the smartphone to a location inside the hemisphere, the content of the virtual window that resides at that location is displayed on the smartphone's screen. When the user re-positions the smartphone inside the hemisphere the screen displays the content of the virtual window that resides at the new position.

Next we describe a few central aspects of the face-detection software and the setup we used in our user studies. After that we present our three studies in turn and order.

3 FACE DETECTION SOFTWARE AND STUDY SETUP

The self-contained tracking software facility we developed for our FaceUI-approach is based on the Face Detection API [10] in Google's ML Kit (*Machine learning for mobile developers*). The API provides a comfortable and reliable way to track the position and orientation of a smartphone relative to the user's face when the front-facing camera is used. Among the available face-tracking related measures, our software relies on *yaw* data (the smartphone's movements to the left or to the right relative to the detected face), *pitch* data (the smartphone's up and down movements in the vertical direction relative to the detected face), and *distance* data (the current distance between the detected face and the camera lens of the front camera on the smartphone). Our software does not use any *roll*-related information. The Face Detection API delivers 0° for both yaw and pitch when the user holds the phone straight in front of the face.

Restrictions related to COVID-19 prevented us from meeting our study participants face-to-face. Instead, we conducted our studies remotely using teleconferencing software. Accordingly, our participants were required to have a laptop or a desktop computer with a stable Internet connection, a microphone, loudspeakers, and a webcam. In the studies our participants used their own smartphone to run the study software. The study software was designed for any phone running Android 4.2 to 11. Our participants received the study software (i.e., the apk file) and all necessary instructions over email and we guided them through the installation process in the beginning of the study session. The data logged during a study session was automatically transferred from the participant's phone to a Cloud-Firestore data base when the participant had completed the last study tasks.

We ran all of our three studies remotely, where participants used the study apps on their smartphones in the wild as opposed to the controlled lab environment. All participants sat in front of their webcam while completing the study tasks. In each study, a study session lasted approximately 45 minutes, including instructions, practice trials, timed study trials, breaks, and completion of questionnaires. As the study apps were designed for the Android platform, we only recruited participants who possessed an Android smartphone.

4 STUDY 1: EXPLORING DIRECTION AND DISTANCE

Prior research has reported arm fatigue and 'heavy arm'-issues related to mid-air interactions [15] and that working with a bent arm in mid-air is more comfortable and less strenuous than working with a stretched arm [20]. Since FaceUI involves mid-air hand movements arm fatigue is a potential problem. Moreover, with FaceUI, the mid-air movements need to be constrained such that the user's face is inside the front-camera's field of view.

With FaceUI, we envision the mid-air interaction space as a semicircular space in front of the user's face. Through a pilot test (with five participants) we found that the face tracking works best when the phone is between 5 and 80 centimetres away from the user's face and the user moves the phone within a longitudinal range of 90° (from -45° to the left of the user's face to 45° to the right of the user's face) and a latitudinal range of 70° (from -35° below the user's nose to 35° above the user's nose). Whereas we know that movements inside this space are accurately tracked, we do not know how accurately, fast, and comfortably people can navigate around in this mid-air space. Accordingly, we want to chart out the suitable dimensions and the granularity of the mid-air interaction space for FaceUI in our first study.

4.1 Study Design and Study Task

We oriented the study task and study design of our first study according to previous projects that have explored the dimensions and the granularity of the mid-air space in front of the user, e.g., the Virtual Shelves [27] and AD-Binning [17] projects. We used a simple item selection task where a trial consists of moving the smartphone to a specified position in mid-air to select the virtual item at that position. We investigated horizontal movements and vertical movements when the phone is close or far from the user's face.

Figure 2 visualizes the study task and setup. We divided the mid-air space along the horizontal into seven equally wide one-dimensional regions – or items –, each 12.85° 'wide' (Figure 2a). We used five one-dimensional regions – or items – in the vertical direction, each 12.85° 'high' (Figure 2b). From a user's perspective, the size of these items in the air in front of the face depends on the distance between the phone and the face: the further away from the face, the larger the item becomes. Accordingly, we decided to also test movements (horizontal and vertical) when performed close to the face and far away from the face.

4.1.1 Study design

With this, we arrive at two independent factors for our study: 1) movement *Direction*: horizontal and vertical, and 2) *Distance*: close and far. Close represents the distance range within which participants commonly and comfortably hold their phone when accessing on-screen content with touch. We regarded any distance beyond that range as far. However, where the comfortable range ends is likely to differ between participants (depending on arm length and preference). Therefore, it is critical to have a user-depended threshold

Figure 3: Result of Study 1. Mean trial time for close and far distance in (a) the horizontal direction and (b) in the vertical direction. (c) Mean error rate for the horizontal and vertical directions at close and far distances. Error bars: 95% CI.

value rather than using a common value for all participants. We calibrated the individual value for each participant in the beginning of the study session. We asked the participant to provide us the phone-to-face distance where it started to feel awkward and less comfortable when moving the phone in front of the face. Once the phone had reached these locations, the study app showed the distance between the face and the phone (in centimetres) on the screen. We asked the participant to move the phone left, right, middle, up, and down and share the distance data. We calculated the participant's upper value for the 'close' (i.e., comfortable) distance for the horizontal direction by averaging the left, right and middle values. For the vertical direction we averaged the up, down, and middle values.

We used a within-subjects study design. All participants performed four series of six blocks of trials, one series of blocks with each of the four *Distance-Direction* combinations: close-horizontal, close-vertical, far-horizontal, and far-vertical. Blocks in the horizontal direction consisted of six trials, one trial for each of the six target items (1, 2, 3, 5, 6, and 7, cf. Figure 2a) in random order. Blocks in the vertical direction consisted of four trials, one trial for each of the four target items (1, 2, 4, and 5, cf. Figure 2b) in random order. Accordingly, each participant performed 120 trials: one block series of 36 horizontal trials at close distance + one block series of 24 vertical trials at close distance and one block series of 36 horizontal trials at far distance + one block series of 24 vertical trials at far distance. Half of the participants started with the two block series at close distance and then completed the two block series at far distance, the other half used the other order. The order of the two directions-series within a distance was random.

4.1.2 Task procedure

To start a trial, the participant moved the phone to the middle region, straight in front of the face. In the horizontal direction, this corresponded to Item 4 in Figure 2a. In the vertical direction Item 3 in Figure 2b was used as the start region. Once the participant moved the phone inside the start region the screen turned green and displayed information for the upcoming trial, including the target prompt with the item number to select next, as shown in Figure 2c. A trial started when the participant pressed down the thumb on the screen. If the phone was moved outside the start region before pressing down with the thumb, the screen turned red and showed instructions to move the phone into the start region. A thumb-press in the start region started timing for the trial. A selection was registered and the trial time stopped when the thumb was released after having moved the phone into one of the items (or regions) outside

the start region. Speech output informed if the participant selected the correct item or not by playing "Correct selection" resp. "Wrong selection". Erroneous trials were re-queued at a random position among the unfinished trials within the current block.

During a running trial we relied on audio to inform participants about the current position of the phone. The app provided speech output when i) the phone entered a new item, by saying the number of the item, when ii) the participant moved the phone at the wrong distance, by playing "Move the phone further away" in far conditions or "Move the phone closer" in close conditions, and when iii) the face tracking software lost track of the face, by playing "Face out of camera view". Working with audio guidance was important: in our first study, we wanted to focus on the motoric aspects and movement properties that determine the dimensions of FaceUI's interaction space. We wanted to exclude aspects that relate to how well a user can read screen content while moving the phone in mid-air space, such as the size of screen content and the viewing angle and distance. We return to such visual issues in our second study.

4.2 Participants

We recruited twelve right-handed participants (mean age 27.08 years, s.d. 5.98, 6 male) via on-campus flyers and word-of-mouth. All participants were daily smartphone users.

4.3 Results

We first report on results regarding participants' comfortable phone-to-face distance (calibrated in the beginning of a study session) that served as the basis for each participant's individual threshold value that separated the close distance from the far distance. After that we report on trial time, error rates, and subjective ratings.

4.3.1 Close/far threshold value

Across all participants, the average face-to-phone distance where movements started to feel less comfortable was 39.31 cm (s.d. 7.61) for horizontal phone movements and 39.38 cm (s.d. 7.34) for vertical movements. This critical threshold varied a lot between participants. In the horizontal movement direction it was between 30 and 61 cm and in the vertical direction between 28 and 61 cm (only one participant had values greater than 50 cm).

4.3.2 Trial time

The trial time analyses are based on error free trials only. Figure 3a shows the mean trial time for each target position at both distances

Figure 4: Study 2 setup. (a) The green screen showing the instruction of locating the phone to a 40° viewing angle on horizontal plane, (b) Participant located the phone to downward at 40° viewing angle on horizontal plane and, (c) located the phone to upward at 40° viewing angle on horizontal plane, (d) selecting the total number of black dots on down and up screen at 40° viewing angle on horizontal plane.

in the horizontal movement direction and Figure 3b shows the corresponding results for the vertical direction. Mean trial times for close and far (across the two directions) were 2.93 sec and 2.99 sec, respectively. The overall mean trial time (across the two distances) for the horizontal and vertical directions were 3.01 sec and 2.90 sec, respectively. A 2×2 RM-ANOVA showed that there was no significant difference between the two distances ($F_{1,11} = 0.09$, $p = 0.76$) or between the two directions ($F_{1,11} = 0.29$, $p = 0.59$). A one-way RM-ANOVA (independent factor block) indicated that participants became faster during the course of the study with significantly longer trial times in the first block of trials than in last two blocks ($F_{5,55} = 5.85$, $p < 0.001$). The mean trial time decreased from 3.43 sec in Block 1 to 2.81 and 2.72 sec in Block 5 and 6, respectively.

In Figure 3 we also see a clear and expected pattern regarding the different target positions: given further phone-movement distances, selecting item at positions close to the start position (Position 4 for horizontal movements and Position 3 for vertical movements, cf. Figure 2) was quicker than selection items further away. This pattern we see for movements in both directions and at both the close and far distances.

4.3.3 Error rate

Figure 3c shows the mean error rates for the four *distance×direction* combinations. A Friedman test identified a significant difference among the combinations ($\chi^2(3, N = 12) = 8.95, p < 0.05$) and post-hoc Wilcoxon tests (Bonferroni adjusted α-level from 0.05 to 0.008) revealed that the close-vertical combination was significantly less error prone than close-horizontal combination and that there were no other pairwise differences.

4.3.4 Subjective feedback

We asked participants to rate the two directions and the two distances according to their overall preference on a 5-point scale with 1 = *bad*, 3 = *neutral*, and 5 = *good*. We found an unsurprising and strong preference for the close distance with mean rating 4.52 compared to the far distance with mean rating 1.91. Participants were not that decided in their opinions regarding the two movement directions. They rated the horizontal movement direction only slighter better than the vertical direction, mean rating 4.23 vs. mean rating 3.1.

4.4 Summary

Results from the subjective feedback indicate that participants had a slight preference for horizontal movements over vertical movements. However, our analyses also revealed that there is no significant difference between the movement directions in regard of trial time. But we see a clear, and unsurprising advantage for the close distance over the far distance. Accordingly, for our future FaceUI explorations, we learn that people are sensitive regarding the phone-to-face distance and that FaceUI-based applications should avoid requiring user to

use large phone-to-face distances. Consequently, in our we continue utilizing regions along both the horizontal and vertical directions. However, we observed increased trial time with items located in certain vertical regions, e.g., Item 1, than others. This warrants further investigation into factors such as visual angles that could influence users' performance when reading screen content when holding the phone in such regions.

5 STUDY 2: EXPLORING TARGET REGION AND TARGET ANGLE

Application interfaces that are placed in FaceUI move in both horizontal and vertical regions with the user's head movement along with the same regions. Therefore, to read content that is located to the right or left on the FaceUI, a user needs to keep their head static and move their eyes to read the content. Prior research [32] showed that such eye movement could cause eyes fatigue, pain and tiredness. Therefore, in this study, we explored suitable viewing angles where users can comfortably access on-screen items on smartphones.

5.1 Participants

We recruited fourteen right-handed participants (mean age 26.78 years, s.d. 6.07, 7 male) via on-campus flyers and word-of-mouth. All participants were daily smartphone users. None of the participants had participated in Study 1.

5.2 Factors

We considered the following factors in this study.

5.2.1 Target Region

In this study, we considered placing items in two regions – vertical (up and down) and horizontal (left and right). Similar to the first study, we kept the middle location reserved as the starting point of a trial.

5.2.2 Target Angle

We decided to place a set of targets at angles both in horizontal and vertical regions. With a pilot study, we choose to place items at ±20°, ±30°, ±40° and ±50° angles where positive and negative angles indicate items to the right and left regions, respectively. Results from our pilot study showed that participants were not able to see items that are located above +30° in the up. Additionally, any items placed below -40° angles for the downward region were not accessible as the phone gets very close to the body. Therefore, we used +20° and +30° for the up region, and -20°, -30° and -40° for the down region.

5.3 Procedure and Tasks

At the beginning of a trial, the participant was required to move the phone to the middle position (straight in front of the face). As long as the phone was still and outside the middle position, the screen remained red and contained instructions to move the phone to the

Figure 5: Result of Study 2. (a) Mean reading time for left, right, down and up target regions and (b) for target angles in each target region. Error bars: 95% CI.

middle position. Once the phone was inside the middle position the screen turned green and displayed the target prompt for the next target (along with block and trial counts), as seen in Figure 4a. Participants were asked to press on the screen with their thumb and move their phone at the target angle while keeping the thumb on the screen. Tapping on the screen also started a timer. The study application then removed the on-screen instructions, replaced with an empty black window, and kept it until participants moved the phone to the target angle. We used circle counting tasks in this study, where participants were required to count the number of circles presented in two windows located at a target angle. For instance, if the target angle was +30° in the right region, we placed two more windows above and below the vertical plane defined by the user's eye. Participants could only see the windows once they reach to the instructed region and angle. They could now move their phone up and down (for horizontal region) or left and right (for vertical region) to access the windows while keeping the phone in the target angle (Figure 4b-c). The windows contained a random number of non-overlapping black circles between 12 and 16. Participants were required to count the total number of circles seen on both screens. Once they believed counting all the circles on both windows, they were asked to lift off their thumb from the touchscreen. This action further popup a window containing multiple options for the summation results (Figure 4d). Once they selected the correct answer, the application stopped the trial time, provided voice feedback on whether they were correct or not and displayed the instruction for the next trial on the screen. If incorrect, the app stopped the trial time, provided audio feedback, and re-queued the trial at a random position among unfinished trials within a block of trials. Participants were then required to move the phone back to the middle and continue trials until all the trials were finished. Note that for either case, the app sent trial-related information (e.g., task completion time, correctness) to a database server.

Each participant completed six blocks of trials with each of the *Target Region* (left, right, up and down) where one block contained one trial for each of the *Target Angles*. Therefore, each participant performed 78 error-free trials (24 trials for left, 24 for right, 12 for up and 18 for down region). The presentation order of the target region were selected randomly between participants and the angles were presented in a random order. Participants were provided with 2 blocks of practice trials. After completing all the trials, we collected the participants' feedback on their preferences on *Target Region* and *Target Angles*. This study required participants around 45 minutes to complete all the tasks.

5.4 Results

Instead of analyzing the trial time, we were interested in the time that participants spent on counting the circles rather than moving the phone to the target position and taking time to answer questions. We called this time as *Reading time*.

5.4.1 Reading time

We used repeated measures ANOVA and post-hoc pairwise comparisons to analyze reading time. Results showed that *Target Region* had significant effects on reading time ($F_{3,39} = 3.24$, $p < 0.05$). Figure 5a shows the mean reading time for all four regions: left (mean 10.40s) and right (mean 11.16s), down (mean 9.76s) and up (mean 13.84s). Post-hoc pairwise comparisons showed that Down was significantly faster than Up while accessing the items. No other pairwise difference was found.

We also analyzed the reading time for each target angle on each target region. Figure 5b shows the mean reading time for all target angle on each target region. Target angles in *Right* showed significant effects on reading time ($F_{3,39} = 6.71$, $p < 0.001$). Post-hoc pairwise comparisons between target angles showed that targets at 50° angle was significantly slower than target angles at 20°. There were no other pairwise statistically significant differences. We also observed that the target angles in *Left* target region had significant effects on reading time ($F_{3,39} = 7.03$, $p < 0.001$). Similar to the right region, targets at 50° angles were significantly slower than targets at 20°. There were no other statistically significant differences between the angles.

Like left and right regions, target angles in *Up* region showed significant effects on reading time ($F_{3,39} = 23.39$, $p < 0.001$). Targets at 30° angles were significantly slower than targets at angle 20°. Target angles in *Down* region also showed significant effects on trial time ($F_{2,26} = 21.12$, $p < 0.001$). Targets at 40° angle were significant slower than targets at 20° and 30°. No other statistically significant differences were observed.

5.4.2 Subjective feedback

Participants rated each target region using a 5-point Likert scale. They preferred the right target region (mean rating 3.85) most, followed by down (mean rating 3.78) and left (mean rating 3.07). Up target region was rated as the least preferred region to access items (mean rating 2.28).

5.5 Summary

The results shows that visually accessing screen content while the phone is positioned in the upper region (up) is slower than when the phone is positioned in any other region (the lower region, the left

Figure 6: Calendar app interfaces. (a) A trial starts with displaying a query, e.g., - *"Find the number of online meetings scheduled on July 6"*. A tap on the start button opens a new window (b) - containing calendar dates for a month at the bottom of the screen. With the touch interface, a tap on a date shows events scheduled on that date (at the top of the screen). A user can further inspect an event by tapping on it. This action triggers a new window (c) with displaying details on the event. The user can return to the previous screen by tapping the back button or swiping left. (d) With FaceUI, virtual windows containing events details are placed in front of the user, which can be accessed by moving the phone in mid-air. After inspecting the event details, the user can tap on a check button to open a popup window containing multiple answers.

and the right areas) of the in-air space. For the target angles for each region, we see that participants' performance degrades significantly at the highest angle in each region. Accordingly, we suggest to avoid the extreme angles, 50° for both right and left, 30° for up, and 40° for down when designing a application that uses FaceUI.

6 STUDY 3: PERFORMANCE ANALYSIS OF FACEUI WITH AN ANALYTIC TASK

We conducted previous two studies exploring different design factors such as target angle and target region that could potentially influence users performance using FaceUI. In this study, we evaluate a practical usage scenario using FaceUI where users are required to browse multiple windows for retrieving information. Consequently, we designed a calendar app and compared the performance of FaceUI with traditional touch interfaces.

6.1 Participants

We recruited twelve right-handed participants (mean age 25.5, s.d. 5.23, 6 male) via on-campus flyers and word-of-mouth. All participants were daily smartphone users. None of the participants had participated in Study 1 or in Study 2.

6.2 Task, Procedure and Design

In this study, we used an analytic task where users were required reviewing information on a calendar before reaching a decision. A trial starts with displaying the question along with a start button (e.g., *"Find the number of online meetings scheduled on July 7"*), as seen in Figure 6a. After reading the question, the user taps on the start button, which also starts the trial time and opens a new window containing calendar dates for a month (e.g., July 2021 in our case) at the bottom of the screen (Figure 6b). Once the user selects a date (e.g., July 7) with touch, the date gets highlighted with green color and a number of calendar events on that specific date is displayed at the top. To find the number of calendar events that should be added for each date, we briefly surveyed students and faculty members and found that they commonly have 3-5 events (e.g., classes or meetings) per day, excluding weekends. Consequently, we added 3 to 5 events, represented with an event title and time (e.g., *"Department Meeting 15:00-16:00"*), for each day except for Saturday and Sunday. Once the user taps on an event, the app opens a new window (i.e., "detailed view") containing detailed information about that event (Figure 6c). The design of detailed view was inspired by the Android's generic calendar applications

that contains event title, event time, persons hosting/attending in the event (e.g., Host, Attendees), event type and mode (weekly meeting, online/in-person), reminder-related information (e.g., reminder type, reminder time). After checking the detailed view, the user can tap the "back" button or swipe left to return to the previous screen to view the other events on that day.

With FaceUI, a trial also starts with showing the screen displaying a query prompt. Once the user taps on the start button, it opens a new window showing calendar dates at the bottom (Figure 6d). While designing FaceUI, we leveraged the empty mid-air space in front of the user to accommodate virtual windows for frequent browsing. Therefore, we used FaceUI in conjunction with traditional touch input where touch is used to select an item (e.g., a date from the calendar) and FaceUI was used for browsing content (e.g., "detailed view") by moving the phone in mid-air space. Note that as we have maximum 5 events for a date, we decide to only place the detailed views between +40° and -40° in the horizontal direction rather than placing them in a grid. Once the user selects a date, FaceUI shows the details of an event (i.e., detailed view) on the top half of the screen and the user can browse other events on the date by moving the phone horizontally in mid-air (Figure 6d). Phone movements along vertical directions are ignored. After inspecting all the event details, the user taps on a check button (for both touch and FaceUI interfaces) to open a popup window containing multiple answers (Figure 6e). Once the user selects an answer and taps the select button, the app provides audio feedback on the correctness of the answer. If the selected answer is correct, the trial time stops, and the next trial is displayed on the screen. If incorrect, audio feedback for incorrect selection is provided, and the user is required to redo the trial immediately.

The study used a 2×3 within-subjects design for factors *Interface* (FaceUI, Touch), and *Number of events* (3, 4, and 5). For each combination of factors, participants performed 10 repetitions resulting in 60 error-free timed trials per participant. The order of the *Interface* was counter-balanced across participants and *Number of events* orders were randomized within each *Interface*. Participants were provided with practice trials for each combination until they felt comfortable operating the two interfaces. A study session lasted approximately 45 minutes.

6.3 Results

Measures: Our study tasks include three sub-tasks: (i) selecting a correct date from the calendar, (ii) browsing event details (i.e.,

Figure 7: Result of Study 3. (a) Mean browsing start time, (b) browsing time and (c) selection time. Error bars: 95% CI.

detailed view) on the selected date and (iii) selecting the correct answer. Therefore, we recorded the following times: *Browsing start time* is the time when the participants read the question and click on the start button to the time when they select the correct date from the calendar; *Browsing time* is the time from when participants select the correct date to the time when they finish browsing detailed view and tap on the check button to open the interface containing four possible answers; and *Selection time* is the time from when they tap on the check button to the time when they select an answer and press the submit button. In addition, we record trials where participants selected a wrong answer.

6.3.1 Error trials, outliers, and trial time

We marked a trial as an error trial if participants answered incorrectly. We observed that participants selected wrong answers in 41 trials (5.38%): 24 with Touch Interface (3.15%) and 17 with FaceUI (2.23%). A Wilcoxon Signed-Rank test showed no difference between the two *Interfaces*. To analyze the times (e.g., browsing start time, browsing time or selection time), we first removed all erroneous trials and then removed eight outlier trials with a total trial time outside of $\pm$ 3 SD. Overall, we found that participants 13% faster with FaceUI than touch interfaces (with FaceUI 15.2s and touch 17.2s). We used Repeated Measures ANOVA and Bonferroni adjusted post-hoc pairwise comparisons to analyze the times.

6.3.2 Browsing start time

Figure 7a shows the browsing start time for the two *Interfaces* and three *Number of events*. There were no significant differences in browsing start time between the two *Interfaces* ($F_{1,11} = 0.04$, $p = 0.84$). Participants with Touch interfaces were (2.31s, SE 0.31) slightly faster than FaceUI (2.35ms, SE 0.30). Similarly, we did not find any significant differences in browsing start time between the *Number of events* ($F_{2,22} = 0.26$, $p = 0.78$). 2, 3 and 4 events were taking 2.28s (SE 0.30), 2.34s (SE 0.28) and 2.38s (SE 0.31), respectively. There was no significant *Interface $\times$ number of events* effect on browsing start time ($F_{2,22} = 0.61$, $p = 0.55$).

6.3.3 Browsing time

Figure 7b displays the browsing time for the two *Interfaces* and three *Number of events*. A RM-ANOVA showed that the browsing time was significantly different depending on *Interfaces* ($F_{1,11} = 6.52$, $p < 0.05$) and the *Number of events* ($F_{2,22} = 39.55$, $p < 0.001$). Bonferroni adjusted post-hoc comparisons showed that FaceUI with 9.4s (SE 0.56) was significantly faster than touch interfaces with 11.4s (SE 0.77). For *number of events*, each pairwise comparison was significant (all p's ¡ 0.001) where the higher number events took longer time than the lower (3 events - 7.95s, SE 0.49, 4 events - 10.24s, SE 0.59 and 5 events - 13.09s, SE 0.82). There was no

significant *Interface $\times$ number of events* on browsing time ($F_{2,22} = 1.70$, $p = 0.21$).

6.3.4 Selection time

Figure 7c shows the selection time. We observed no significant differences in selection time between the two *Interfaces* ($F_{1,11} = 0.92$, $p = 0.36$) or three *Number of events* ($F_{2,22} = 1.28$, $p = 0.30$). 2, 3 and 4 events were taking 1.61s (SE 0.06), 1.59s (SE 0.05) and 1.66s (SE 0.04), respectively. There was no significant *Interface $\times$ number of events* effect on Selection time ($F_{2,22} = 0.80$, $p = 0.46$).

6.3.5 Subjective Feedback

Participants had prior experience with touch interfaces and were very comfortable using smartphones. Once participants mentioned: *"I have been using touch interfaces on smartphones for a long time, I feel comfortable with them"*. We also observed a bias for touch interfaces where we asked participants to rate the two directions according to their overall preference on a 5-point scale. Touch interfaces (mean rating 4.5, SD 0.5) was rated higher than FaceUI (mean rating 3.5, SD 1.1). However, participants acknowledged that the concept of FaceUI was utterly new, and they were not familiar with any similar concepts. Once participants commented: *"It's a new method and I don't have experience with it. However, it seems a potential method for operating smartphones"*. We believe that once such interfaces become available on commercial smartphones, people will feel comfortable using them for accessing on-screen content.

6.4 Summary

Our participants had more than 9 years of prior experience using the traditional touch interfaces where FaceUI was a new experience for them. Despite this, results demonstrated that the FaceUI offers faster access to information than traditional touch interfaces. We found that the browsing start time and the selection time were comparable for both interfaces as participants used the same procedures (i.e., selecting dates or buttons with touches) with both interfaces. However, we observed that participants were significantly faster with browsing information with FaceUI (see figure 7). FaceUI enables quick retrieval of spatially located virtual UIs by moving the phone into large space whereas touch interfaces require users switching between windows with frequent tap and swipe, which is known to be costly [17]. From the results of the studies we believe that FaceUI can be a promising supporting input technique to the conventional touch input and this new interaction can serve the users with the best timing in browsing multiple windows.

7 DESIGN GUIDELINES

We summarize and present our key findings as design guidelines. Our investigation offers the following guidelines to designers for

Figure 8: FaceUI enabled applications. A user (a-b): browse through images by moving the phone along horizontal and vertical directions; (c) scroll through messages to check message history by moving the phone vertically; and (d) navigate a map by moving the phone.

interfaces similar to FaceUI:

7.1 Distance

We found that participants preferred moving their hands within 40cm around the face. Using this space for accessing virtual UIs will also help minimizing concerns related to arm fatigue. Thus, we recommend designers placing UIs in the mid-air space within 40 cm from users' faces.

7.2 Direction and Region

Results indicate that participants preferred the horizontal over the vertical direction for moving the phone to access items. Designers should emphasise placing items in this direction. In addition, participants reported difficulties accessing items in the up region. Thus, limited or no items should be placed in this region.

7.3 Viewing Angle

Items should be placed within a comfortable viewing angle as users performance significantly degrades once the targets are placed far from the comfortable viewing angles. Caution is needed, especially when placing items in extreme angles which could create eyestrain. Results from our study suggest placing items between -40° left and +40° right in the horizontal direction, between +20° up and -30° down in the vertical direction.

7.4 Mid-Air Space for Browsing-Intensive Tasks

Study 3 results showed that mid-air space is more effective for browsing through UIs than the traditional touch interface. This is primarily due to the minimum switching costs (e.g., small device movements) involved with navigating between UIs with FaceUI. Therefore, we suggest that designers consider using mid-air space to place UIs to perform any browsing-intensive tasks with FaceUI-enabled interfaces.

8 FaceUI ENABLED APPLICATIONS

We designed the following three applications to demonstrate how face-centered spatial user interfaces can be used in a off-the-shelf smartphone.

8.1 Image Browser

In Study 3, FaceUI implementation did not consider a scenario where items were located in a grid. However, many FaceUI-enabled application could be benefited from such as an item arrangement style. Consequently, we developed an image browsing app that offloads a set of images into a 5×3 grid on the mid-air space in front of users. Users can browse images by moving the device in horizontal and vertical directions. While browsing the images, users can touch the screen to access further details about an image. Figure 8a-b demonstrates the app scenario where a user is browsing the images by moving the phone along horizontal and vertical directions.

8.2 Message History

Scrolling through items with touch interfaces is cumbersome and time-consuming, especially for one-handed interaction mode [28]. We developed an application leveraging face-centered UIs to scroll through messages in a messenger app with one hand. In our implementation, the app allows users to scroll through messages by moving their phone vertically between +20° up and -30° down (Figure 8c). Clutching can be used to browse extended message history by tapping on the screen.

8.3 Map Navigation

We designed a FaceUI enabled map application where users move the phone in mid-air to zoom and pan the map. Users phone movements to the left/right/up/down (relative to their face) were associated with the map movement in the same direction (Figure 8d). Map zoom in or zoom out was mapped with the distance from the face (smaller the distance, zoomed in the map).

9 LIMITATION AND FUTURE WORK

FaceUI requires users to move the phone in mid-air, which may cause eye and arm fatigues for prolonged use. Further investigation is needed to explore solutions to minimize such fatigues. In addition, using FaceUI in public spaces may trigger feelings such as embarrassment or discomfort due to hand movements which may attract by-passers' attention. Thus, it is also important to carry out studies to explore the social acceptance of FaceUI in public and private spaces. We asked participants to keep the head static and move the phone only during studies. Further studies can explore how to leverage head and smartphone movements to access spatial UIs. While using FaceUI, on-screen information can be viewed by surrounding people, triggering privacy concerns. Future studies need to investigate users and by-passers privacy concerns and explore approaches such as software and hardware-based privacy filters to only keep the information visible to users. We only investigated the performance of FaceUI for accessing windows located in the horizontal direction. Further investigations are needed to explore natural delimiters to switch between FaceUI and touch and the performance of FaceUI-enabled applications, where windows are arranged in both horizontal and vertical directions. We foresee future research exploring ways to reduce switching between UIs for the traditional touch interfaces. Lastly, future work needs to examine the performance of FaceUI in different usage contexts such as standing, sitting or walking in public and private spaces.

10 CONCLUSION

We have presented FaceUI, a novel approach leveraging mid-air space to access face-centered spatial user interfaces. Through two user studies, we first explored different factors that influence the design and performance of FaceUI. Based on the results, we designed a FaceUI-based calendar app and compared users' performance

using the calendar with a touch-based calendar interface. Results showed that FaceUI is a promising approach to enable faster access to UIs than the traditional touch interfaces.

REFERENCES

[1] What is the Smart Scroll™ feature on my Samsung Galaxy Alpha®? `https://www.samsung.com/za/support/mobile-devices/what-is-the-smart-scroll-feature-on-my-samsung-galaxy-alpha/`, 2018. [Online; accessed March 26, 2022].

[2] What is the smart rotation feature on my samsung galaxy s. `https://www.samsung.com/za/support/mobile-devices/what-is-the-smart-rotation-feature-on-my-samsung-galaxy-s5/`, 2021. [Online; accessed March 26, 2022].

[3] D. Ahlström, K. Hasan, and P. Irani. Are you comfortable doing that? acceptance studies of around-device gestures in and for public settings. In *Proceedings of the 16th International Conference on Human-Computer Interaction with Mobile Devices and Services*, MobileHCI '14, p. 193–202. Association for Computing Machinery, New York, NY, USA, 2014. doi: 10.1145/2628363.2628381

[4] T. Babic, F. Perteneder, H. Reiterer, and M. Haller. Simo: Interactions with distant displays by smartphones with simultaneous face and world tracking. In *Extended Abstracts of the 2020 CHI Conference on Human Factors in Computing Systems*, CHI EA '20, p. 1–12. Association for Computing Machinery, New York, NY, USA, 2020. doi: 10.1145/3334480.3382962

[5] T. Babic, H. Reiterer, and M. Haller. Gesturedrawer: One-handed interaction technique for spatial user-defined imaginary interfaces. In *Proceedings of the 5th Symposium on Spatial User Interaction*, SUI '17, p. 128–137. Association for Computing Machinery, New York, NY, USA, 2017. doi: 10.1145/3131277.3132185

[6] A. Butler, S. Izadi, and S. Hodges. Sidesight: Multi-"touch" interaction around small devices. In *Proceedings of the 21st Annual ACM Symposium on User Interface Software and Technology*, UIST '08, p. 201–204. Association for Computing Machinery, New York, NY, USA, 2008. doi: 10.1145/1449715.1449746

[7] X. A. Chen, J. Schwarz, C. Harrison, J. Mankoff, and S. E. Hudson. Air+touch: Interweaving touch & in-air gestures. In *Proceedings of the 27th Annual ACM Symposium on User Interface Software and Technology*, UIST '14, p. 519–525. Association for Computing Machinery, New York, NY, USA, 2014. doi: 10.1145/2642918.2647392

[8] L.-P. Cheng, F.-I. Hsiao, Y.-T. Liu, and M. Y. Chen. *IRotate: Automatic Screen Rotation Based on Face Orientation*, p. 2203–2210. Association for Computing Machinery, New York, NY, USA, 2012.

[9] B. M. Ens, R. Finnegan, and P. P. Irani. The personal cockpit: A spatial interface for effective task switching on head-worn displays. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, CHI '14, p. 3171–3180. Association for Computing Machinery, New York, NY, USA, 2014. doi: 10.1145/2556288.2557058

[10] Google. Face Detection — ML Kit. `https://developers.google.com/ml-kit/vision/face-detection`, 2021. [Online; accessed March 26, 2022].

[11] S. Gustafson, D. Bierwirth, and P. Baudisch. Imaginary interfaces: Spatial interaction with empty hands and without visual feedback. In *Proceedings of the 23nd Annual ACM Symposium on User Interface Software and Technology*, UIST '10, p. 3–12. Association for Computing Machinery, New York, NY, USA, 2010. doi: 10.1145/1866029.1866033

[12] S. Gustafson, C. Holz, and P. Baudisch. Imaginary phone: Learning imaginary interfaces by transferring spatial memory from a familiar device. In *Proceedings of the 24th Annual ACM Symposium on User Interface Software and Technology*, UIST '11, p. 283–292. Association for Computing Machinery, New York, NY, USA, 2011. doi: 10.1145/2047196.2047233

[13] S. G. Gustafson, B. Rabe, and P. M. Baudisch. Understanding palm-based imaginary interfaces: The role of visual and tactile cues when browsing. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, CHI '13, p. 889–898. Association for Computing Machinery, New York, NY, USA, 2013. doi: 10.1145/2470654.2466114

[14] C. Harrison and S. E. Hudson. Abracadabra: Wireless, high-precision, and unpowered finger input for very small mobile devices. In *Proceedings of the 22nd Annual ACM Symposium on User Interface Software and Technology*, UIST '09, p. 121–124. Association for Computing Machinery, New York, NY, USA, 2009. doi: 10.1145/1622176.1622199

[15] C. Harrison, S. Ramamurthy, and S. E. Hudson. On-body interaction: Armed and dangerous. In *Proceedings of the Sixth International Conference on Tangible, Embedded and Embodied Interaction*, TEI '12, p. 69–76. Association for Computing Machinery, New York, NY, USA, 2012. doi: 10.1145/2148131.2148148

[16] C. Harrison, D. Tan, and D. Morris. Skinput: Appropriating the body as an input surface. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, CHI '10, p. 453–462. Association for Computing Machinery, New York, NY, USA, 2010. doi: 10.1145/1753326.1753394

[17] K. Hasan, D. Ahlström, and P. Irani. Ad-binning: Leveraging around device space for storing, browsing and retrieving mobile device content. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, CHI '13, p. 899–908. Association for Computing Machinery, New York, NY, USA, 2013. doi: 10.1145/2470654.2466115

[18] K. Hasan, D. Ahlström, and P. P. Irani. Comparing direct off-screen pointing, peephole, and flick & pinch interaction for map navigation. In *Proceedings of the 3rd ACM Symposium on Spatial User Interaction*, SUI '15, p. 99–102. Association for Computing Machinery, New York, NY, USA, 2015. doi: 10.1145/2788940.2788957

[19] K. Hasan, D. Ahlström, J. Kim, and P. Irani. *AirPanes: Two-Handed Around-Device Interaction for Pane Switching on Smartphones*, p. 679–691. Association for Computing Machinery, New York, NY, USA, 2017.

[20] J. D. Hincapié-Ramos, X. Guo, P. Moghadasian, and P. Irani. Consumed endurance: A metric to quantify arm fatigue of mid-air interactions. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, CHI '14, p. 1063–1072. Association for Computing Machinery, New York, NY, USA, 2014. doi: 10.1145/2556288.2557130

[21] B. Jones, R. Sodhi, D. Forsyth, B. Bailey, and G. Maciocci. Around device interaction for multiscale navigation. In *Proceedings of the 14th International Conference on Human-Computer Interaction with Mobile Devices and Services*, MobileHCI '12, p. 83–92. Association for Computing Machinery, New York, NY, USA, 2012. doi: 10.1145/2371574.2371589

[22] D. Kim, K. Park, and G. Lee. *OddEyeCam: A Sensing Technique for Body-Centric Peephole Interaction Using WFoV RGB and NFoV Depth Cameras*, p. 85–97. Association for Computing Machinery, New York, NY, USA, 2020.

[23] S. Kratz and M. Rohs. Hoverflow: Exploring around-device interaction with ir distance sensors. In *Proceedings of the 11th International Conference on Human-Computer Interaction with Mobile Devices and Services*, MobileHCI '09. Association for Computing Machinery, New York, NY, USA, 2009. doi: 10.1145/1613858.1613912

[24] S. Kratz, M. Rohs, D. Guse, J. Müller, G. Bailly, and M. Nischt. Palmspace: Continuous around-device gestures vs. multitouch for 3d rotation tasks on mobile devices. In *Proceedings of the International Working Conference on Advanced Visual Interfaces*, AVI '12, p. 181–188. Association for Computing Machinery, New York, NY, USA, 2012. doi: 10.1145/2254556.2254590

[25] M. Kumar and T. Winograd. Gaze-enhanced scrolling techniques. In *Proceedings of the 20th Annual ACM Symposium on User Interface Software and Technology*, UIST '07, p. 213–216. Association for Computing Machinery, New York, NY, USA, 2007. doi: 10.1145/1294211.1294249

[26] H. V. Le, T. Kosch, P. Bader, S. Mayer, and N. Henze. *PalmTouch: Using the Palm as an Additional Input Modality on Commodity Smartphones*, p. 1–13. Association for Computing Machinery, New York, NY, USA, 2018.

[27] F. C. Y. Li, D. Dearman, and K. N. Truong. Virtual shelves: Interactions with orientation aware devices. In *Proceedings of the 22nd Annual ACM Symposium on User Interface Software and Technology*, UIST '09, p. 125–128. Association for Computing Machinery, New York,

NY, USA, 2009. doi: 10.1145/1622176.1622200

[28] C. Liu, C. Liu, H. Mao, and W. Su. Tilt-scrolling: A comparative study of scrolling techniques for mobile devices. In D.-S. Huang, Z.-K. Huang, and A. Hussain, eds., *Intelligent Computing Methodologies*, pp. 189–200. Springer International Publishing, Cham, 2019.

[29] P. Lubos, G. Bruder, O. Ariza, and F. Steinicke. Touching the sphere: Leveraging joint-centered kinespheres for spatial user interaction. In *Proceedings of the 2016 Symposium on Spatial User Interaction*, SUI '16, p. 13–22. Association for Computing Machinery, New York, NY, USA, 2016. doi: 10.1145/2983310.2985753

[30] T. Niikura, Y. Hirobe, A. Cassinelli, Y. Watanabe, T. Komuro, and M. Ishikawa. In-air typing interface for mobile devices with vibration feedback. In *ACM SIGGRAPH 2010 Emerging Technologies*, SIG-GRAPH '10. Association for Computing Machinery, New York, NY, USA, 2010. doi: 10.1145/1836821.1836836

[31] S. Rustagi, A. Garg, P. R. Anand, R. Kumar, Y. Kumar, and R. R. Shah. Touchless typing using head movement-based gestures. In *2020 IEEE Sixth International Conference on Multimedia Big Data (BigMM)*, pp. 112–119, 2020. doi: 10.1109/BigMM50055.2020.00025

[32] K.-K. Shieh and D.-S. Lee. Preferred viewing distance and screen angle of electronic paper displays. *Applied Ergonomics*, 38(5):601–608, 2007. doi: 10.1016/j.apergo.2006.06.008

[33] S.-Y. Teng, M.-H. Chen, and Y.-T. Lin. Way out: A multi-layer panorama mobile game using around-body interactions. In *Proceedings of the 2017 CHI Conference Extended Abstracts on Human Factors in Computing Systems*, CHI EA '17, p. 230–233. Association for Computing Machinery, New York, NY, USA, 2017. doi: 10.1145/3027063. 3048410

[34] C.-Y. Wang, W.-C. Chu, P.-T. Chiu, M.-C. Hsiu, Y.-H. Chiang, and M. Y. Chen. Palmtype: Using palms as keyboards for smart glasses. In *Proceedings of the 17th International Conference on Human-Computer Interaction with Mobile Devices and Services*, MobileHCI '15, p. 153–160. Association for Computing Machinery, New York, NY, USA, 2015. doi: 10.1145/2785830.2785886

[35] Y. Yan, C. Yu, X. Ma, S. Huang, H. Iqbal, and Y. Shi. *Eyes-Free Target Acquisition in Interaction Space around the Body for Virtual Reality*, p. 1–13. Association for Computing Machinery, New York, NY, USA, 2018.

[36] X. Yang, C.-W. You, H. Lu, M. Lin, N. D. Lane, and A. T. Campbell. Visage: A face interpretation engine for smartphone applications. In D. Uhler, K. Mehta, and J. L. Wong, eds., *Mobile Computing, Applications, and Services"*, pp. 149–168. Springer Berlin Heidelberg, Berlin, Heidelberg, 2013.

[37] X.-D. Yang, K. Hasan, N. Bruce, and P. Irani. Surround-see: Enabling peripheral vision on smartphones during active use. In *Proceedings of the 26th Annual ACM Symposium on User Interface Software and Technology*, UIST '13, p. 291–300. Association for Computing Machinery, New York, NY, USA, 2013. doi: 10.1145/2501988.2502049

[38] K.-P. Yee. Peephole displays: Pen interaction on spatially aware handheld computers. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, CHI '03, p. 1–8. Association for Computing Machinery, New York, NY, USA, 2003. doi: 10.1145/ 642611.642613

[39] C. Zhang, A. Bedri, G. Reyes, B. Bercik, O. T. Inan, T. E. Starner, and G. D. Abowd. Tapskin: Recognizing on-skin input for smartwatches. In *Proceedings of the 2016 ACM International Conference on Interactive Surfaces and Spaces*, ISS '16, p. 13–22. Association for Computing Machinery, New York, NY, USA, 2016. doi: 10.1145/ 2992154.2992187

[40] Y. Zhang, J. Zhou, G. Laput, and C. Harrison. Skintrack: Using the body as an electrical waveguide for continuous finger tracking on the skin. In *Proceedings of the 2016 CHI Conference on Human Factors in Computing Systems*, CHI '16, p. 1491–1503. Association for Computing Machinery, New York, NY, USA, 2016. doi: 10.1145/ 2858036.2858082

[41] J. Zhao, R. Jota, D. J. Wigdor, and R. Balakrishnan. Augmenting mobile phone interaction with face-engaged gestures. *CoRR*, abs/1610.00214, 2016.