APPROXIMATE PROBABILISTIC INFERENCE WITH COMPOSED FLOWS

ABSTRACT

We study the problem of probabilistic inference on the joint distribution defined by a normalizing flow model. Given a pre-trained flow model $p(\boldsymbol{x})$, we wish to estimate $p(\boldsymbol{x}_2 \mid \boldsymbol{x}_1)$ for some arbitrary partitioning of the variables $\boldsymbol{x} = (\boldsymbol{x}_1, \boldsymbol{x}_2)$. We first show that this task is computationally hard for a large class of flow models. Motivated by this hardness result, we propose a framework for *approximate* probabilistic inference. Specifically, our method trains a new generative model with the property that its composition with the given model approximates the target conditional distribution. By parametrizing this new distribution as another flow model, we can efficiently train it using variational inference and also handle conditioning under arbitrary differentiable transformations. We experimentally demonstrate that our approach outperforms Langevin Dynamics in terms of sample quality, while requiring much fewer parameters and training time compared to regular variational inference. We further validate the flexibility of our method on a variety of inference tasks with applications to inverse problems.

1 INTRODUCTION

Generative modeling has seen an unprecedented growth in the recent years. Building on the success of deep learning, deep generative models have shown impressive ability to model complex distributions in a variety of domains and modalities. Among them, normalizing flow models (see Papamakarios et al. (2019) and references therein) stand out due to their computational flexibility, as they offer efficient sampling, likelihood evaluation, and inversion. While other types of models currently outperform flow models in terms of likelihood and sample quality, flow models have the advantage that they are relatively easy to train using maximum likelihood and do not suffer from issues that other models possess (e.g. mode collapse for GANs, posterior collapse for VAEs, slow sampling for autoregressive models). These characteristics make normalizing flows attractive for a variety of downstream tasks, including density estimation, inverse problems, semi-supervised learning, reinforcement learning, and audio synthesis (Ho et al., 2019; Asim et al., 2019; Atanov et al., 2019; Ward et al., 2019; Oord et al., 2018).

Even with such computational flexibility, how to perform efficient probabilistic inference on a flow model still remains largely unknown. This question is becoming increasingly important as generative models increase in size and the computational resources necessary to train them from scratch are out of reach for many researchers and practitioners[1]. If it was possible to perform probabilistic inference on flow models, we could *re-purpose* these powerful pre-trained generators for numerous custom tasks.

This is the central question we study in this paper: One wishes to estimate the conditional distribution $p(\boldsymbol{x}_2 \mid \boldsymbol{x}_1)$ from a given flow model $p(\boldsymbol{x})$ for some partitioning of variables $\boldsymbol{x} = (\boldsymbol{x}_1, \boldsymbol{x}_2)$. Existing methods for this task largely fall under two categories: Markov Chain Monte Carlo (MCMC) and variational inference (VI). While MCMC methods can perform exact conditional sampling in theory, they often have prohibitively long mixing time for complex high-dimensional distributions and also do not provide likelihoods. On the other hand, VI allows for likelihood evaluation and fast sampling, but at a lower sample quality compared to MCMC counterparts.

---

[1]For example, Kingma & Dhariwal (2018) report that their largest model had 200M parameters and was trained on 40 GPUs for a week.

We propose a novel method that leverages a powerful pre-trained flow model *by constructing carefully designed latent codes* to generate conditional samples. Specifically, we use variational inference to learn a distribution in the latent space of the given model such that, when fed into the pre-trained model, the output approximately matches the samples from the true conditional. Our central finding is that working in the latent space is making it possible to produce high quality conditional samples.

Our contributions:

- We start with an interesting theoretical hardness result. We show that even though flow models are designed to provide efficient inversion and sampling, *exact conditional sampling is provably computationally intractable* for a wide class of flow models. This motivates our approach of *approximate* inference.

- We develop a method to estimate the target conditional distribution by composing a second generative model (which we call the *pre-generator*) with the given model. Specifically, we show how to train the pre-generator to yield structured noise so that the composed model approximately matches the target conditional distribution.

- We experimentally show that our approach is competitive with MCMC methods in terms of speed and various sample quality metrics such as Frechet Inception Distance (Heusel et al., 2017). We also demonstrate that it achieves superior conditional likelihood estimation performance compared to regular variational inference.

- We extend and validate our method for conditioning under arbitrary differentiable transformations with applications to inverse problems. We qualitatively demonstrate its flexibility on various complex inference tasks.

2 BACKGROUND

2.1 NORMALIZING FLOWS

Normalizing flow models (also known as invertible generative models) represent complex probability distributions by transforming a simple input noise $\boldsymbol{z}$ (typically standard Gaussian) through a differentiable bijection $f : \mathbb{R}^d \to \mathbb{R}^d$. Since f is invertible, change of variables formula allows us to compute the probability density of $\boldsymbol{x} = f(\boldsymbol{z})$:

$$\log p(\boldsymbol{x}) = \log p(\boldsymbol{z}) + \log \left| \det \frac{df^{-1}}{d\boldsymbol{x}}(\boldsymbol{x}) \right|,$$

where $\frac{df^{-1}}{d\boldsymbol{x}}$ denotes the Jacobian of the inverse transformation $f^{-1} : \boldsymbol{x} \mapsto \boldsymbol{z}$. Flow models are explicitly designed so that the above expression can be easily computed, including the log-determinant term. This tractability allows them to be directly trained with maximum likelihood objective on data.

Starting from the early works of Dinh et al. (2015) and Rezende & Mohamed (2015), there has been extensive research on invertible architectures for generative modeling. Many of them work by composing a series of invertible layers, such as in RealNVP (Dinh et al., 2016), IAF (Kingma et al., 2016), Glow (Kingma & Dhariwal, 2018), invertible ResNet (Behrmann et al., 2019), and Neural Spline Flows (Durkan et al., 2019).

One of the simplest invertible layer construction is *additive coupling layer* introduced by Dinh et al. (2015), which served as a basis for many other subsequently proposed models mentioned above. In an additive coupling layer, the input variable is partitioned as $\boldsymbol{x} = (\boldsymbol{x}_1, \boldsymbol{x}_2) \in \mathbb{R}^{d_1} \times \mathbb{R}^{d_2}$. The layer is parametrized by a neural network $g(\boldsymbol{x}_1) : \mathbb{R}^{d_1} \to \mathbb{R}^{d_2}$ used to additively transform $\boldsymbol{x}_2$. Thus the layer's output $\boldsymbol{y} = (\boldsymbol{y}_1, \boldsymbol{y}_2) \in \mathbb{R}^{d_1} \times \mathbb{R}^{d_2}$ and its inverse can be computed as follows:

$$\begin{cases} \boldsymbol{y}_1 &= \boldsymbol{x}_1 \\ \boldsymbol{y}_2 &= \boldsymbol{x}_2 + g(\boldsymbol{x}_1) \end{cases} \iff \begin{cases} \boldsymbol{x}_1 &= \boldsymbol{y}_1 \\ \boldsymbol{x}_2 &= \boldsymbol{y}_2 - g(\boldsymbol{y}_1) \end{cases}$$

Notably, the determinant of the Jacobian of this transformation is always 1 for any mapping g.

2.2 VARIATIONAL INFERENCE

Variational inference (VI) is a family of techniques for estimating the conditional distribution of unobserved variables given observed ones (Jordan et al., 1999; Wainwright et al., 2008; Blei et al., 2017). At its core, VI tries to find a tractable approximation of the true conditional density by minimizing the KL divergence between them over a set of distributions called the variational family.

Figure 1: A flow chart of our conditional sampler. First the noise variable ϵ is sampled from $\mathcal{N}(\mathbf{0}, I_d)$. This is fed into our pre-generator $\hat{f}$ to output structured noise $\boldsymbol{z}$, which is driving the pre-trained base model f to generate conditional samples $\boldsymbol{x}$. The central idea is that the pre-generator must produce structured noise $\boldsymbol{z}$ that looks Gaussian (so that the samples are realistic) but also make the pre-trained base model f produce samples that satisfy the conditioning. The final conditional sampler is thus defined by the composition of two flow models.

Within our context of probabilistic inference from a joint distribution $p(\boldsymbol{x}_1, \boldsymbol{x}_2)$, the KL minimization problem we solve is the following:

$$\arg\min_{q \in \mathcal{Q}} D_{\mathrm{KL}}(q(\boldsymbol{x}_2) \parallel p(\boldsymbol{x}_2 \mid \boldsymbol{x}_1 = \boldsymbol{x}_1^*)),$$

where $\boldsymbol{x}_1^*$ is some fixed observation and the variational family $\mathcal{Q}$ is chosen such that efficient sampling and likelihood evaluation are possible for all $q \in \mathcal{Q}$. Note that q is tied to a particular $\boldsymbol{x}_1^*$ and is not shared across different observations.

While the conditional density $p(\boldsymbol{x}_2 \mid \boldsymbol{x}_1 = \boldsymbol{x}_1^*)$ is generally intractable to compute, we can efficiently evaluate the joint density $p(\boldsymbol{x}_1, \boldsymbol{x}_2)$ when it is given as a flow model. Thus, we can rewrite the minimization problem as

$$\min_{q \in \mathcal{Q}} D_{\mathrm{KL}}(q(\boldsymbol{x}_2) \parallel p(\boldsymbol{x}_2 \mid \boldsymbol{x}_1 = \boldsymbol{x}_1^*)) = \min_{q \in \mathcal{Q}} \mathbb{E}_{\boldsymbol{x}_2 \sim q}[\log q(\boldsymbol{x}_2) - \log p(\boldsymbol{x}_1 = \boldsymbol{x}_1^*, \boldsymbol{x}_2)],$$

which is obtained by dropping the $\log p(\boldsymbol{x}_1 = \boldsymbol{x}_1^*)$ term that is constant w.r.t. q. This optimization is possible even when $p(\boldsymbol{x}_2 \mid \boldsymbol{x}_1 = \boldsymbol{x}_1^*)$ is intractable, as long as we can evaluate $p(\boldsymbol{x}_1, \boldsymbol{x}_2)$ efficiently.

3 HARDNESS OF CONDITIONAL SAMPLING ON FLOWS

Before we present our method, we first establish a hardness result for exact conditional sampling for flow models that use additive coupling layer. Specifically, if an algorithm is able to efficiently sample from the conditional distribution of a flow model with additive coupling layers, then this algorithm can be used to solve NP-complete problems efficiently.

Theorem 1. *(Informal) Suppose there is an efficient algorithm that can draw samples from the conditional distribution of a normalizing flow model implemented with additive coupling layers as defined in Dinh et al. (2015). Then $RP = NP$.*

Our hardness result holds even if we allow the conditional sampler to approximately match the conditional distribution. The formal statement of the above theorem and its corollary to the approximate case can be found in Appendix A.

Importantly, this result motivates us to consider a relaxation where the observed variables are not required to match the given observation exactly. We also note that the class of flow models that include additive coupling layers encompasses a large number of existing models (e.g. most of the models in Section 2.1). Thus our hardness result applies to a variety of flow models used in practice.

4 APPROXIMATE PROBABILISTIC INFERENCE WITH COMPOSED FLOWS

Notation. Let $p_f(\boldsymbol{x})$ denote the *base model*, a fixed flow model defined by the invertible mapping $f : \boldsymbol{z} \mapsto \boldsymbol{x}$. The *pre-generator* $p_{\hat{f}}(\boldsymbol{z})$ is similarly defined by the invertible mapping $\hat{f} : \epsilon \mapsto \boldsymbol{z}$ and represents a distribution in the latent space of the base model. We assume that all flow models use standard Gaussian prior, i.e. $\boldsymbol{z} \sim \mathcal{N}(\mathbf{0}, I_d) \to \boldsymbol{x} = f(\boldsymbol{z})$ and $\epsilon \sim \mathcal{N}(\mathbf{0}, I_d) \to \boldsymbol{z} = \hat{f}(\epsilon)$. By composing the base model and the pre-generator, we obtain the *composed model* $p_{f \circ \hat{f}}(\boldsymbol{x})$ whose samples are generated via $\epsilon \sim \mathcal{N}(\mathbf{0}, I_d) \to \boldsymbol{x} = f(\hat{f}(\epsilon))$. Figure 1 details this sampling procedure.

Our method. The key observation we make is that we can leverage the base model by performing inference in its latent space. Because the base model maps Gaussian noise to samples, the pre-generator can simply focus on putting probability mass in the regions of the latent space corresponding to the conditional samples we wish to model. This is in contrast with regular variational inference, which essentially trains an entirely new generative model from scratch to approximate the target conditional density.

Motivated by this observation and the hardness of exact conditional sampling, we propose to perform variational inference *in the latent space on a smoothed version of the problem* where we allow the

(a) Ambient VI (b) Latent VI (c) Latent VI with transformation

Figure 2: Graphical models depicting different ways we perform variational inference. Solid arrows represent the generative direction, and dotted arrows indicate the variational direction.

observed variable to approximately match the given observation. We do this by creating a dummy variable $\tilde{\boldsymbol{x}}_1$ distributed according to $p_\sigma(\tilde{\boldsymbol{x}}_1 \mid \boldsymbol{x}_1) = \mathcal{N}(\tilde{\boldsymbol{x}}_1; \boldsymbol{x}_1, \sigma^2 I_d)$. Here, σ is the *smoothing parameter* that controls the tightness of this relaxation. The objective we minimize is the KL divergence between our variational distribution and the smoothed conditional density:

$$D_{\mathrm{KL}}(p_{f \circ \hat{f}}(\boldsymbol{x}_2) \,\|\, p_f(\boldsymbol{x}_2 \mid \tilde{\boldsymbol{x}}_1 = \boldsymbol{x}_1^*)). \tag{1}$$

For comparison, a direct application of variational inference in the image space (which we refer to as *Ambient VI*) would minimize the following objective:

$$D_{\mathrm{KL}}(p_{\hat{f}}(\boldsymbol{x}_2) \,\|\, p_f(\boldsymbol{x}_2 \mid \tilde{\boldsymbol{x}}_1 = \boldsymbol{x}_1^*)), \tag{2}$$

where we write $p_{\hat{f}}$ to denote the variational distribution which directly models $f(\boldsymbol{x} \mid \tilde{\boldsymbol{y}} = \boldsymbol{y}^*)$.

Note that in our setting, we cannot directly model $p_f(\boldsymbol{x}_2 \mid \tilde{\boldsymbol{x}}_1 = \boldsymbol{x}_1^*)$ because we only have access to the joint distribution $p_f(\boldsymbol{x}_1, \boldsymbol{x}_2)$ through the base model. Thus we instead approximate the *joint* distribution conditioned on our observation, i.e. $p_f(\boldsymbol{x} \mid \tilde{\boldsymbol{x}}_1 = \boldsymbol{x}_1^*)$. Figures 2a and 2b show the graphical models describing this formulation.

Conditioning under differentiable transformations. The flexibility of VI allows us to easily extend our method to conditioning under an arbitrary transformation. Concretely, let $T(\boldsymbol{x})$ be a differentiable function and $\boldsymbol{y}^*$ be some fixed observation in the range of T. We now observe $\boldsymbol{y} = T(\boldsymbol{x})$ instead, so we similarly define a dummy variable $\tilde{\boldsymbol{y}}$ distributed according to $p_\sigma(\tilde{\boldsymbol{y}} \mid \boldsymbol{y}) = \mathcal{N}(\tilde{\boldsymbol{y}}; \boldsymbol{y}, \sigma^2 I_d)$. We estimate the conditional density $p_f(\boldsymbol{x} \mid \tilde{\boldsymbol{y}} = \boldsymbol{y}^*)$ by minimizing the following objective:

$$\begin{aligned} \mathcal{L}_{\mathrm{Ours}}(\hat{f}) &\triangleq D_{\mathrm{KL}}(p_{f \circ \hat{f}}(\boldsymbol{x}) \,\|\, p_f(\boldsymbol{x} \mid \tilde{\boldsymbol{y}} = \boldsymbol{y}^*)) \\ &= D_{\mathrm{KL}}(p_{\hat{f}}(\boldsymbol{z}) \,\|\, p_f(\boldsymbol{z})) + \mathbb{E}_{\boldsymbol{z} \sim p_{\hat{f}}} \left[\frac{1}{2\sigma^2} \|T(f(\boldsymbol{z})) - \boldsymbol{y}^*\|_2^2 \right], \end{aligned} \tag{3}$$

where $p_f(\boldsymbol{z})$ denotes the prior distribution of the base model, i.e. $\mathcal{N}(\boldsymbol{0}, I_d)$. We provide the derivation of eq. (3) in Appendix B. See Figure 2c for a comparison to eq. (1).

This loss function offers an intuitive interpretation. The first term tries to keep the learned distribution $p_{f \circ \hat{f}}$ close to the base distribution by pushing $p_{\hat{f}}$ to match the prior of the base model, while the second term tries to match the observation $\boldsymbol{y}^*$. Moreover, the above expectation can be rewritten in terms of $\boldsymbol{\epsilon}$, which allows us to employ the *reparametrization trick* to obtain a low-variance gradient estimator for training:

$$\begin{aligned} \mathcal{L}_{\mathrm{Ours}}(\hat{f}) &= \mathbb{E}_{\boldsymbol{z} \sim p_{\hat{f}}} \left[\log p_{\hat{f}}(\boldsymbol{z}) - \log p_f(\boldsymbol{z}) + \frac{1}{2\sigma^2} \|T(f(\boldsymbol{z})) - \boldsymbol{y}^*\|_2^2 \right] \\ &= \mathbb{E}_{\boldsymbol{\epsilon} \sim \mathcal{N}(\boldsymbol{0}, I_d)} \left[\log p_{\hat{f}}(\hat{f}(\boldsymbol{\epsilon})) - \log p_f(\hat{f}(\boldsymbol{\epsilon})) + \frac{1}{2\sigma^2} \left\|T(f(\hat{f}(\boldsymbol{\epsilon}))) - \boldsymbol{y}^*\right\|_2^2 \right] \end{aligned} \tag{4}$$

5 RELATED WORK

Conditional Generative Models. There has been a large amount of work on conditional generative modeling, with varying levels of flexibility for what can be conditioned on. In the simplest case, a fixed set of observed variables can be directly fed into the model as an auxiliary conditioning input (Mirza & Osindero, 2014; Sohn et al., 2015; Ardizzone et al., 2019). Some recent works proposed to extend existing models to support conditioning on *arbitrary* subsets of variables (Ivanov et al., 2018; Belghazi et al., 2019; Li et al., 2019). This is a much harder task as there are exponentially many subsets of variables that can be conditioned on.

One key distinction of our work from these approaches is that we estimate the conditional distribution of a *fixed, pre-trained* flow model, rather than training an entire new model from scratch. We highlight several reasons why one might prefer our approach over the above methods: (1) The data used to train the given model may not be available, and only the generative model itself is made public. (2) The given model is too costly to train from scratch. (3) We need to condition on a transformation of the variables, instead of just a subset of them. (4) We want to get some insight on the distribution defined by the given model.

Markov Chain Monte Carlo Methods. When one is only concerned with generating samples, MCMC techniques offer a promising alternative. Unlike variational inference and conditional models, MCMC methods come with asymptotic guarantees to generate correct samples. Though directly applying MCMC methods on complex high-dimensional posteriors parametrized by a neural network often comes with many challenges in practice (Papamarkou et al., 2019), methods based on Langevin Monte Carlo have shown promising results (Neal et al., 2011; Welling & Teh, 2011; Song & Ermon, 2019). Thus we consider sampling via Langevin Dynamics as one of our baselines.

Another recent work of particular interest to us is PL-MCMC (Cannella et al., 2020), a technique designed specifically to sample from the conditional distribution of a flow model. It works by constructing a Markov chain in the latent space, which can then be used with algorithms such as Metropolis-Hastings to sample from the target conditional distribution with asymptotic guarantees.

Inverse Problems with Generative Prior. In a linear inverse problem, a vector $x \in \mathbb{R}^d$ generates a set of measurements $y^* = Ax \in \mathbb{R}^m$, where the number of measurements is much smaller than the dimension: $m \ll d$. The goal is to reconstruct the vector x from y^*. While in general there are (potentially infinitely) many possible values of x that agree with the given measurements, it is possible to identify a unique solution when there is an additional structural assumption on x.

Classically, the simplifying structure was that x is sparse, and there has been extensive work in this setting (Tibshirani, 1996; Candes et al., 2006; Donoho et al., 2006; Bickel et al., 2009; Baraniuk, 2007). Recent work has considered alternative structures, such as the vector x coming from a generative model. Starting with Bora et al. (2017), there has been extensive work in this setting as well (Grover & Ermon, 2019; Mardani et al., 2018; Heckel & Hand, 2019; Mixon & Villar, 2018; Pandit et al., 2019). In particular, Asim et al. (2019) and Shamshad et al. (2019) utilized flow models to solve inverse problems such as compressive sensing, image deblurring, and image inpainting.

It is important to note that the above approaches focus on recovering a single point estimate that best matches the measurements. However, there can be many inputs that fit the measurements and thus uncertainty in the reconstruction. Due to this shortcoming, several recent works focused on recovering the *distribution* of x conditioned on the measurements (Tonolini et al., 2019; Zhang & Jin, 2019; Adler & Öktem, 2018; 2019). We note that our approach differs from these, since they are learning-based methods that require access to the training data. On the contrary, our work attempts to perform conditional sampling using a given pre-trained generative model, leveraging all that previous computation to solve a conditional task with reconstruction diversity.

6 QUANTITATIVE EXPERIMENTS

We validate the efficacy of our proposed method in terms of both sample quality and likelihood on various inference tasks against three baselines: Ambient VI (as defined by the loss in eq. (2)), Langevin Dynamics, and PL-MCMC. We also conduct our experiments on three different datasets (MNIST, CIFAR-10, and CelebA-HQ) to ensure that our method works across a range of settings.

We report four different sample quality metrics: Frechet Inception Distance (FID), Learned Perceptual Image Patch Similarity (LPIPS), and Inception Score (IS) for CIFAR-10 (Heusel et al., 2017; Zhang et al., 2018; Salimans et al., 2016). While not strictly a measure of perceptual similarity, the average mean squared error (MSE) is also reported for completeness.

For all our experiments, we use the multiscale RealNVP architecture (Dinh et al., 2016) for both the base model and the pre-generator. We use Adam optimizer (Kingma & Ba, 2014) to optimize the weights of the pre-generator using the loss defined in Equation (3). The images used to generate observations were taken from the test set and were not used to train the base models. We refer the reader to Appendix C for model hyperparameters and other details of our experiment setup.

Figure 3: Conditional samples generated by our method from observing the upper half of CelebA-HQ faces. We see that our approach is able to produce diverse completions with different jaw lines, mouth shapes, and facial expression.

6.1 IMAGE INPAINTING

We perform inpainting tasks using our approach, where we sample missing pixels conditioned on the visible ones. We consider three different conditioning schemes: the bottom half (MNIST), the upper half (CelebA-HQ), and randomly chosen subpixels (CIFAR-10). For MNIST, we use the smoothing parameter value of $\sigma = 0.1$ and for CIFAR-10 and CelebA-HQ, we use $\sigma = 0.05$.

In Figure 3 we see that our approach produces natural and diverse samples for the missing part of the image. The empirical pixelwise variance (normalized and averaged over the color channels) also confirms that, while the observation is not perfectly matched, most of the high-variance regions are in the unobserved parts as we expect.

We also quantitatively evaluate the quality of the generated samples using widely used sample quality metrics, as shown in Table 1. As we can see, our method outperforms the baseline methods on most of the metrics. Note that PL-MCMC results for CIFAR-10 and CelebA-HQ are omitted because it was prohibitively slow to run for hundreds of images, as each MCMC chain required over 20,000 proposals. Cannella et al. (2020) also report using 25,000 proposals for their experiments.

Table 1: Sample quality metrics for image inpainting tasks on different datasets. The best value is bolded for each metric. As shown below, our method achieves superior sample quality to all baselines.

	MNIST			CIFAR-10 (5-bit)				CelebA-HQ (5-bit)		
	FID	MSE	LPIPS	FID	IS↑	MSE	LPIPS	FID	MSE	LPIPS
Ours	**4.11**	**21.67**	**0.074**	**41.14**	**7.189**	9.71	**0.176**	33.61	**223.06**	**0.208**
Langevin	14.34	36.51	0.135	47.53	6.732	**9.31**	0.201	**30.33**	323.47	0.229
Ambient VI	114.59	65.56	0.290	84.78	5.156	16.74	0.296	289.64	1060.66	0.587
PL-MCMC	21.20	59.89	0.190		N/A				N/A	

6.2 LIKELIHOOD ESTIMATION

Next, we evaluate our method on the task of conditional likelihood estimation. By varying the size of the pre-generator, we also test the parameter efficiency of our method in comparison to Ambient VI. Results are shown in Table 2; we see that our method is able to produce reasonable samples using only *about 1%* of the base model's parameters, confirming the effectiveness of inference in the latent space.

7 QUALITATIVE EXPERIMENTS

Extracting Class-conditional Models: Here we present an interesting application of conditioning under a complex transformation T. Since the only requirement for T is that it must be differentiable, we can set it to be another neural network. For example, if T is a pre-trained binary classifier for a

Table 2: Conditional likelihood estimation performance (measured in bits per dimension) for different pre-generator sizes on the MNIST imputation task. The first row shows the parameter count of the pre-generator relative to the base model.

Observations			
# Parameters	Ours	Ambient VI	Conditional Completions (ours)
1.2%	1.73	6.75	
3.2%	1.64	3.17	
10.6%	1.52	2.71	
39.1%	1.47	2.99	

(a) Each column contains uncurated samples from the posterior conditioned on a specific MNIST class. We emphasize that the base model was trained without any class information.

Original   Inpainting Samples

(b) Conditional samples from image inpainting experiments done with Ambient VI.

Figure 4: Samples from class-conditional models extracted from the unconditional base model (left) and various failure modes of Ambient VI (right).

specific attribute, we can *extract* a model conditioned on the presence (or the absence) of that attribute from an unconditional base model.

We test this idea on the MNIST dataset. We trained 10 binary classifiers on the MNIST dataset, one for each digit $k = 0, \ldots, 9$, to predict whether the given image is k or not. By setting T to be each of those classifiers, we were able to extract the class-conditional model $p_f(\boldsymbol{x} \mid \text{Label}(\boldsymbol{x}) \approx k)$. See Figure 4a for samples generated from the extracted models.

Inverse Problems: We additionally test the applicability of our method to linear inverse problems. In Figure 5, we show the conditional samples obtained by our method on three different tasks: image colorization, super-resolution ($2\times$), and compressed sensing with 500 random Gaussian measurements (for reference, CIFAR-10 images have 3072 dimensions). We notice that the generated samples look natural, even when they do not match the original input perfectly, again showing our method's capability to generate semantically meaningful conditional samples and also provide sample diversity.

7.1 WHY AMBIENT VI FAILS

From Table 1, notice that Ambient VI achieves significantly worse sample quality compared to other methods. The low-quality samples from the image inpainting task in Figure 4b further confirm that Ambient VI is unable to produce good conditional samples, even though the observation is matched well. This may seem initially surprising but is a natural consequence of the VI objective. Recall that our loss function decomposes into two terms: the KL term and the reconstruction term.

$$\mathcal{L}_{\text{Ours}}(\hat{f}) = D_{\text{KL}}(p_{\hat{f}}(\boldsymbol{z}) \,\|\, p_f(\boldsymbol{z})) + \mathbb{E}_{\boldsymbol{z} \sim p_{\hat{f}}} \left[\frac{1}{2\sigma^2} \|T(f(\boldsymbol{z})) - \boldsymbol{y}^*\|_2^2 \right].$$

If we alternatively derive the loss for Ambient VI, we arrive at an analogous objective:

$$\mathcal{L}_{\text{Ambient}}(\hat{f}) = D_{\text{KL}}(p_{\hat{f}}(\boldsymbol{x}) \,\|\, p_f(\boldsymbol{x})) + \mathbb{E}_{\boldsymbol{x} \sim p_{\hat{f}}} \left[\frac{1}{2\sigma^2} \|T(\boldsymbol{x}) - \boldsymbol{y}^*\|_2^2 \right].$$

Figure 5: Results on various inverse problem tasks using our method.

While these two loss functions seem like simple reparametrizations of each other via f, they behave very differently during optimization due to the KL term. Notice that for both loss functions, the first term is the *reverse* KL divergence between the variational distribution and the base distribution $D_{\mathrm{KL}}(p_{\hat{f}} \parallel p_f)$. Because reverse KL divergence places no penalty whenever $p_{\hat{f}}$ is zero regardless of p_f, minimizing the reverse KL is known to have a *mode-seeking* behavior where $p_{\hat{f}}$ fits a single mode of p_f and ignores the rest of the support of p_f (Murphy, 2013, Chapter 21.2.2). In contrast, minimizing the forward KL has a *zero-avoiding* behavior and tries to cover all of p_f's support.

For our method, this is not a problem because the prior distribution of the base model $p_f(\boldsymbol{z})$ is a standard Gaussian and hence unimodal. However, for Ambient VI, $p_f(\boldsymbol{x})$ is the base model itself and is highly multimodal. This can be empirically seen by visualizing the landscape of $\log p_f(\boldsymbol{x})$ projected onto a random 2D subspace. In Figure 6, we clearly see that $p_f(\boldsymbol{x})$ has numerous local maxima. For Ambient VI, the variational distribution collapses into one of these modes.

Figure 6: Contour plot of $\log p_f(\boldsymbol{x})$ around a random point in image space.

8 CONCLUSION

We proposed a new inference algorithm for distributions parametrized by normalizing flow models. The need for approximate inference is motivated by our theoretical hardness result for exact inference, which is surprising given that it applies to invertible models. We also presented a detailed empirical evaluation of our method with both quantitative and qualitative results on a wide range of tasks and datasets.

There are numerous directions for further research. For example, our method can be possibly extended to other latent-variable generators such as VAEs and GANs (Kingma & Welling, 2013; Goodfellow et al., 2014). A significant limitation of our work is that we need to re-train the pre-generator for each observation. It may be possible to avoid retraining by *amortizing* the pre-generator over all possible observations. Studying the various trade-offs resulting from such scheme would be an interesting result similar in spirit to Cremer et al. (2018). Overall, we believe that the idea of a pre-generator creating structured noise is a useful and general method for leveraging pre-trained generators to solve new generative problems.

REFERENCES

Jonas Adler and Ozan Öktem. Deep bayesian inversion. *arXiv preprint arXiv:1811.05910*, 2018.

Jonas Adler and Ozan Öktem. Deep posterior sampling: Uncertainty quantification for large scale inverse problems. 2019.

Lynton Ardizzone, Carsten Lüth, Jakob Kruse, Carsten Rother, and Ullrich Köthe. Guided image generation with conditional invertible neural networks. *arXiv preprint arXiv:1907.02392*, 2019.

Muhammad Asim, Ali Ahmed, and Paul Hand. Invertible generative models for inverse problems: mitigating representation error and dataset bias. *arXiv preprint arXiv:1905.11672*, 2019.

Andrei Atanov, Alexandra Volokhova, Arsenii Ashukha, Ivan Sosnovik, and Dmitry Vetrov. Semi-conditional normalizing flows for semi-supervised learning. *arXiv preprint arXiv:1905.00505*, 2019.

Richard G Baraniuk. Compressive sensing. *IEEE signal processing magazine*, 24(4), 2007.

Jens Behrmann, David Duvenaud, and Jörn-Henrik Jacobsen. Invertible residual networks. *International Conference on Machine Learning*, 2019.

Mohamed Ishmael Belghazi, Maxime Oquab, Yann LeCun, and David Lopez-Paz. Learning about an exponential amount of conditional distributions. *arXiv preprint arXiv:1902.08401*, 2019.

Peter J Bickel, Ya'acov Ritov, Alexandre B Tsybakov, et al. Simultaneous analysis of lasso and dantzig selector. *The Annals of Statistics*, 37(4):1705–1732, 2009.

David M Blei, Alp Kucukelbir, and Jon D McAuliffe. Variational inference: A review for statisticians. *Journal of the American Statistical Association*, 112(518):859–877, 2017.

Ashish Bora, Ajil Jalal, Eric Price, and Alexandros G Dimakis. Compressed sensing using generative models. In *International Conference on Machine Learning*, pp. 537–546. JMLR. org, 2017.

Emmanuel J Candes, Justin K Romberg, and Terence Tao. Stable signal recovery from incomplete and inaccurate measurements. *Communications on Pure and Applied Mathematics: A Journal Issued by the Courant Institute of Mathematical Sciences*, 59(8):1207–1223, 2006.

Chris Cannella, Mohammadreza Soltani, and Vahid Tarokh. Projected latent markov chain monte carlo: Conditional sampling of normalizing flows, 2020.

Chris Cremer, Xuechen Li, and David Duvenaud. Inference suboptimality in variational autoencoders. *arXiv preprint arXiv:1801.03558*, 2018.

Laurent Dinh, David Krueger, and Yoshua Bengio. Nice: Non-linear independent components estimation. In *International Conference on Learning Representations 2015 workshop track*, 2015.

Laurent Dinh, Jascha Sohl-Dickstein, and Samy Bengio. Density estimation using Real NVP. In *International Conference on Learning Representations*, 2016.

David L Donoho et al. Compressed sensing. *IEEE Transactions on information theory*, 52(4): 1289–1306, 2006.

Conor Durkan, Artur Bekasov, Iain Murray, and George Papamakarios. Neural spline flows. In *Neural Information Processing Systems*, 2019.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pp. 2672–2680, 2014.

Aditya Grover and Stefano Ermon. Uncertainty autoencoders: Learning compressed representations via variational information maximization. In *International Conference on Artificial Intelligence and Statistics*, 2019.

Reinhard Heckel and Paul Hand. Deep decoder: Concise image representations from untrained non-convolutional networks. In *International Conference on Learning Representations*, 2019.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In *Advances in neural information processing systems*, pp. 6626–6637, 2017.

Jonathan Ho, Xi Chen, Aravind Srinivas, Yan Duan, and Pieter Abbeel. Flow++: Improving flow-based generative models with variational dequantization and architecture design. In *International Conference on Machine Learning*, pp. 2722–2730, 2019.

Oleg Ivanov, Michael Figurnov, and Dmitry Vetrov. Variational autoencoder with arbitrary conditioning. *arXiv preprint arXiv:1806.02382*, 2018.

Michael I Jordan, Zoubin Ghahramani, Tommi S Jaakkola, and Lawrence K Saul. An introduction to variational methods for graphical models. *Machine learning*, 37(2):183–233, 1999.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Durk P Kingma and Prafulla Dhariwal. Glow: Generative flow with invertible 1x1 convolutions. In *Neural Information Processing Systems*, pp. 10215–10224, 2018.

Durk P Kingma, Tim Salimans, Rafal Jozefowicz, Xi Chen, Ilya Sutskever, and Max Welling. Improved variational inference with inverse autoregressive flow. In *Neural Information Processing Systems*, pp. 4743–4751, 2016.

Yang Li, Shoaib Akbar, and Junier B Oliva. Flow models for arbitrary conditional likelihoods. *arXiv preprint arXiv:1909.06319*, 2019.

Morteza Mardani, Qingyun Sun, David Donoho, Vardan Papyan, Hatef Monajemi, Shreyas Vasanawala, and John Pauly. Neural proximal gradient descent for compressive imaging. In *Neural Information Processing Systems*, pp. 9573–9583, 2018.

Mehdi Mirza and Simon Osindero. Conditional generative adversarial nets. *arXiv preprint arXiv:1411.1784*, 2014.

Dustin G Mixon and Soledad Villar. Sunlayer: Stable denoising with generative networks. *arXiv preprint arXiv:1803.09319*, 2018.

Kevin P. Murphy. *Machine learning : a probabilistic perspective*. MIT Press, Cambridge, Mass. [u.a.], 2013. ISBN 9780262018029 0262018020. URL https://www.amazon.com/Machine-Learning-Probabilistic-Perspective-Computation/dp/0262018020/ref=sr_1_2?ie=UTF8&qid=1336857747&sr=8-2.

Radford M Neal et al. Mcmc using hamiltonian dynamics. *Handbook of markov chain monte carlo*, 2(11):2, 2011.

Aaron Oord, Yazhe Li, Igor Babuschkin, Karen Simonyan, Oriol Vinyals, Koray Kavukcuoglu, George Driessche, Edward Lockhart, Luis Cobo, Florian Stimberg, et al. Parallel wavenet: Fast high-fidelity speech synthesis. In *International conference on machine learning*, pp. 3918–3926. PMLR, 2018.

Parthe Pandit, Mojtaba Sahraee, Sundeep Rangan, and Alyson K Fletcher. Asymptotics of map inference in deep networks. *arXiv preprint arXiv:1903.01293*, 2019.

George Papamakarios, Eric Nalisnick, Danilo Jimenez Rezende, Shakir Mohamed, and Balaji Lakshminarayanan. Normalizing flows for probabilistic modeling and inference. *arXiv preprint arXiv:1912.02762*, 2019.

Theodore Papamarkou, Jacob Hinkle, M Todd Young, and David Womble. Challenges in bayesian inference via markov chain monte carlo for neural networks. *arXiv*, pp. arXiv–1910, 2019.

Danilo Rezende and Shakir Mohamed. Variational inference with normalizing flows. In *International Conference on Machine Learning*, pp. 1530–1538, 2015.

Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. In *Advances in neural information processing systems*, pp. 2234–2242, 2016.

Fahad Shamshad, Asif Hanif, and Ali Ahmed. Subsampled fourier ptychography via pretrained invertible and untrained network priors. In *NeurIPS 2019 Workshop on Solving Inverse Problems with Deep Networks*, 2019.

Kihyuk Sohn, Honglak Lee, and Xinchen Yan. Learning structured output representation using deep conditional generative models. In *Neural Information Processing Systems*, pp. 3483–3491, 2015.

Yang Song and Stefano Ermon. Generative modeling by estimating gradients of the data distribution. In *Advances in Neural Information Processing Systems*, pp. 11918–11930, 2019.

Robert Tibshirani. Regression shrinkage and selection via the lasso. *Journal of the Royal Statistical Society: Series B (Methodological)*, 58(1):267–288, 1996.

Francesco Tonolini, Ashley Lyons, Piergiorgio Caramazza, Daniele Faccio, and Roderick Murray-Smith. Variational inference for computational imaging inverse problems. *arXiv preprint arXiv:1904.06264*, 2019.

Martin J Wainwright, Michael I Jordan, et al. Graphical models, exponential families, and variational inference. *Foundations and Trends® in Machine Learning*, 1(1–2):1–305, 2008.

Patrick Nadeem Ward, Ariella Smofsky, and Avishek Joey Bose. Improving exploration in soft-actor-critic with normalizing flows policies. *arXiv preprint arXiv:1906.02771*, 2019.

Max Welling and Yee W Teh. Bayesian learning via stochastic gradient langevin dynamics. In *Proceedings of the 28th international conference on machine learning (ICML-11)*, pp. 681–688, 2011.

Chen Zhang and Bangti Jin. Probabilistic residual learning for aleatoric uncertainty in image restoration. *arXiv preprint arXiv:1908.01010*, 2019.

Richard Zhang, Phillip Isola, Alexei A Efros, Eli Shechtman, and Oliver Wang. The unreasonable effectiveness of deep features as a perceptual metric. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 586–595, 2018.

A   PROOF OF HARDNESS RESULTS

A.1   PRELIMINARIES

A Boolean variable is a variable that takes a value in $\{-1, 1\}$. A *literal* is a Boolean variable x_i or its negation $\neg x_i$. A *clause* is set of literals combined with the OR operator, e.g., $x_1 \vee \neg x_2 \vee x_3$. A *conjunctive normal form formula* is a set of clauses joined by the AND operator, e.g., $(x_1 \vee \neg x_2 \vee x_3) \wedge (x_1 \vee \neg x_3 \vee x_4)$. A satisfying assignment is an assignment to the variables such that the Boolean formula is true.

The *3-SAT problem* is the problem of deciding if a conjunctive normal form formula with three literals per clause has a satisfying assignment. We will show that conditional sampling from flow models allows us to solve the 3-SAT problem.

We ignore the issue of representing samples from the conditional distribution with a finite number of bits. However the reduction is still valid if the samples are truncated to a constant number of bits.

A.2   DESIGN OF THE ADDITIVE COUPLING NETWORK

Given a Boolean formula, we design a ReLU neural network with 3 hidden layers such that the output is 0 if the input is far from a satisfying assignment, and the output is about a large number M if the input is close to a satisfying assignment.

We will define the following scalar function

$$\delta_\varepsilon(x) = \mathrm{ReLU}\left(\frac{1}{\varepsilon}(x - (1 - \varepsilon))\right) - \mathrm{ReLU}\left(\frac{1}{\varepsilon}(x - (1 - \varepsilon)) - 1\right)$$
$$- \mathrm{ReLU}\left(\frac{1}{\varepsilon}(x - 1)\right) + \mathrm{ReLU}\left(\frac{1}{\varepsilon}(x - 1) - 1\right).$$

This function is 1 if the input is 1, 0 if the input x has $|x - 1| \geq \varepsilon$ and is a linear interpolation on $(1 - \varepsilon, 1 + \varepsilon)$. Note that it can be implemented by a hidden layer of a neural network and a linear transform, which can be absorbed in the following hidden layer. See Figure 7 for a plot of this function.

Figure 7: Plot of the scalar function used to construct an additive coupling layer that can generate samples of satisfying 3-SAT assignments.

For each variable x_i, we create a transformed variable $\tilde{x}_i$ by applying $\tilde{x}_i = \delta_\varepsilon(x_i) - \delta_\varepsilon(-x_i)$. Note that this function is 0 on $(-\infty, -1 - \varepsilon] \cup [-1 + \varepsilon, 1 - \varepsilon] \cup [1 + \varepsilon, \infty)$, -1 at $x_i = -1$, 1 at $x_i = 1$, and a smooth interpolation on the remaining values in the domain.

Every clause has at most 8 satisfying assignments. For each satisfying assignment we will create a neuron with the following process: (1) get the relevant transformed values $\tilde{x}_i, \tilde{x}_j, \tilde{x}_k$, (2) multiply each variable by $1/3$ if it is equal to 1 in the satisfying assignment and $-1/3$ if it is equal to -1 in the satisfying assignment, (3) sum the scaled variables, (4) apply the δ_ε function to the sum.

We will then sum all the neurons corresponding to a satisfying assignment for clause C_j to get the value c_j. The final output is the value $M \times \mathrm{ReLU}(\sum_j c_j - (m - 1))$, where M is a large scalar.

We say that an input to the neural network x corresponds to a Boolean assignment $x' \in \{-1, 1\}^d$ if for every x_i we have $|x_i - x'_i| < \varepsilon$. For $\varepsilon < 1/3$, if the input does not correspond to a satisfying assignment of the given formula, then at least one of the values c_j is 0. The remaining values of c_j are at most 1, so the sum in the output is at most $(m - 1)$, thus the sum is at most zero, so the final output is 0. However, if the input is a satisfying assignment, then every value of $c_j = 1$, so the output is M.

A.3 Generating SAT Solutions from the Conditional Distribution

Our flow model will take in Gaussian noise $x_1, \ldots, x_d, z \sim N(0, 1)$. The values $x_1, \ldots, x_d$ will be passed through to the output. The output variable y will be $z + f_M(x_1, \ldots, x_d)$, where f_M is the neural network described in the previous section, and M is the parameter in the output to be decided later.

Let A be all the valid satisfying assignments to the given formula. For each assignment a, we will define X_a to be the region $X_a = \{x \in \mathbb{R}^d : \|a - x\|_\infty \leq \varepsilon\}$, where as above ε is some constant less than $1/3$. Let $X_A = \bigcup_{a \in A} X_a$.

Given an element $x \in X_a$, we can recreate the corresponding satisfying assignment a. Thus if we have an element of X_A, we can certify that there is a satisfying assignment. We will show that the distribution conditioned on $y = M$ can generate satisfying assignments with high probability.

We have that
$$p(X_A \mid y = M) = \frac{p(y = M, X_A)}{p(y = M, X_A) + p(y = M, \overline{X}_A)}$$
If we can show that $p(y = M, \overline{X}_A) \ll p(y = M, X_A)$, then we have that the generated samples are with high probability satisfying assignments.

Note that,
$$p(y = M, \overline{X}_A) = p(y = M \mid \overline{X}_A)P(\overline{X}_A) \leq p(y = M \mid \overline{X}_A).$$
Also notice that if $x \in \overline{X}_A$, then $f_M(x) = 0$. Thus $y \sim \mathcal{N}(0, 1)$ and $P(y = M \mid \overline{X}_A) = \Theta(\exp(-M^2/2))$.

Now consider any satisfying assignment x_a. Let X'_a be the region $X'_a = \{x \in \mathbb{R}^d : \|a - x\|_\infty \leq \frac{1}{2m}\}$. Note that for every x in this region we have $f_M(x) \geq M/2$. Additionally, we have that $P(X'_a) = \Theta(m)^{-d}$. Thus for any $x \in X'_a$, we have $p(Y = M \mid x) \gtrsim \exp(-M^2/8)$. We can conclude that
$$p(y = M, X_A) \geq p(Y = M, X'_a) = \int_{X'_a} p(Y = M \mid x)p(x)\, dx \gtrsim \exp(-M^2/8 - \Theta(d \log m)).$$
For $M = O(\sqrt{d \log m})$, we have that $p(y = M, \overline{X}_A)$ is exponentially smaller than $p(y = M, X_A)$. This implies that sampling from the distribution conditioned on $y = M$ will return a satisfying assignment with high probability.

A.4 Hardness of Approximate Sampling

Definition 2. The complexity class RP is the class of decision problems with efficient random algorithms that (1) output YES with probability $1/2$ if the true answer is YES and (2) output NO with probability 1 if the true answer is NO. It is widely believed that RP is a strict subset of NP.

A simple extension of the above theorem shows that even approximately matching the true conditional distribution in terms of TV distance is computationally hard. The total variation (TV) distance is defined as $d_{\mathrm{TV}}(p, q) = \sup_E |p(E) - q(E)| \leq 1$, where E is an event. The below corollary shows that it is hard to conditionally sample from a distribution that is even slightly bounded away from 1.

Corollary 3. *The conditional sampling problem remains hard even if we only require the algorithm to sample from a distribution q such that $d_{\mathrm{TV}}(p(\cdot \mid x = x^*), q) \leq 1 - 1/\mathrm{poly}(d)$, where d is the dimension of the distribution.*

We show that the problem is still hard even if we require the algorithm to sample from a distribution q such that $d_{\mathrm{TV}}(p(x \mid y = y^*), q) \geq 1/\mathrm{poly}(d)$.

Consider the event X_A from above. We saw that $p(X_A \mid y = M) \geq 1 - \exp(-\Omega(d))$. We have that $d_{\mathrm{TV}}(p(\cdot \mid y = M), q) \geq 1 - \exp(-\Omega(d) - q(X_A))$.

Suppose that the distribution q has $q(X_A) \geq 1/\text{poly}(d)$. Then by sampling a polynomial number of times from q we sample an element of X_A, which allows us to find a satisfying assignment. Thus if we can efficiently create such a distribution, we would be able to efficiently solve SAT and RP = NP. As we are assuming this is false, we must have $q(X_A) \leq 1/\text{poly}(d)$, which implies $d_{\text{TV}}(p(\cdot \mid y = M), q) \geq 1 - 1/\text{poly}(d)$.

B   DERIVATION OF EQUATION (3)

Here we present a detailed derivation of Equation (3). Note that this equality is true *up to a constant w.r.t.* $\hat{f}$, which is fine as we use this as the optimization objective.

$$
\begin{aligned}
\mathcal{L}_{\text{Ours}}(\hat{f}) &\triangleq D_{\text{KL}}(p_{f \circ \hat{f}}(\boldsymbol{x}) \parallel p_f(\boldsymbol{x} \mid \tilde{\boldsymbol{y}} = \boldsymbol{y}^*)) \\
&= \mathbb{E}_{\boldsymbol{x} \sim p_{f \circ \hat{f}}} \left[\log p_{f \circ \hat{f}}(\boldsymbol{x}) - \log p_f(\boldsymbol{x}, \tilde{\boldsymbol{y}} = \boldsymbol{y}^*) \right] + \log p_f(\tilde{\boldsymbol{y}} = \boldsymbol{y}^*) \\
&\overset{A}{\triangleq} \mathbb{E}_{\boldsymbol{x} \sim p_{f \circ \hat{f}}} \left[\log p_{f \circ \hat{f}}(\boldsymbol{x}) - \log p_f(\boldsymbol{x}) - \log p_\sigma(\tilde{\boldsymbol{y}} = \boldsymbol{y}^* \mid \boldsymbol{x}) \right] \\
&= \mathbb{E}_{\boldsymbol{x} \sim p_{f \circ \hat{f}}} \left[\log p_{f \circ \hat{f}}(\boldsymbol{x}) - \log p_f(\boldsymbol{x}) \right] + E_{\boldsymbol{x} \sim p_{f \circ \hat{f}}} \left[-\log p_\sigma(\tilde{\boldsymbol{y}} = \boldsymbol{y}^* \mid \boldsymbol{y} = T(\boldsymbol{x})) \right] \\
&= D_{\text{KL}}(p_{f \circ \hat{f}}(\boldsymbol{x}) \parallel p_f(\boldsymbol{x})) + E_{\boldsymbol{x} \sim p_{f \circ \hat{f}}} \left[-\log p_\sigma(\tilde{\boldsymbol{y}} = \boldsymbol{y}^* \mid \boldsymbol{y} = T(\boldsymbol{x})) \right] \\
&\overset{B}{=} D_{\text{KL}}(p_{\hat{f}}(\boldsymbol{z}) \parallel p_f(\boldsymbol{z})) + E_{\boldsymbol{z} \sim p_{\hat{f}}} \left[\frac{1}{2\sigma^2} \left\| T(f(\boldsymbol{z})) - \boldsymbol{y}^* \right\|_2^2 \right]
\end{aligned}
$$

In (A), we drop the $\log p_f(\tilde{\boldsymbol{y}} = \boldsymbol{y}^*)$ term as it is constant w.r.t. $\hat{f}$.
In (B), we use the invariance of KL divergence under invertible transformation to rewrite the KL divergence in terms of $\boldsymbol{z}$.

C   EXPERIMENT DETAILS

C.1   OUR ALGORITHM

Algorithm 1 Training the pre-generator for a given observation under transformation. We assume that $\hat{f}$ is an invertible neural network with parameters θ.

1: **Input**: $\boldsymbol{y}^*$: observation we are conditioning on, $T(\boldsymbol{x})$: differentiable transformation of $\boldsymbol{x}$.
2: **for** $i = 1 \dots \text{num\_steps}$ **do**
3:     **for** $j = 1 \dots m$ **do**   ▷ generate m latent codes from $p_{\hat{f}}(\boldsymbol{z})$
4:         Sample $\boldsymbol{\epsilon}^{(j)} \sim \mathcal{N}(\boldsymbol{0}, I_d)$
5:         $\boldsymbol{z}^{(j)} \leftarrow \hat{f}(\boldsymbol{\epsilon}^{(j)})$
6:     **end for**
7:     $\mathcal{L} \leftarrow \frac{1}{m} \sum_{j=1}^{m} \left[\log p_{\hat{f}}(\boldsymbol{z}^{(j)}) - \log p_{\text{normal}}(\boldsymbol{z}^{(j)}) + \frac{1}{2\sigma^2} \left\| T(f(\boldsymbol{z}^{(j)})) - \boldsymbol{y}^* \right\|_2^2 \right]$
8:     $\theta \leftarrow \theta - \nabla_\theta \mathcal{L}$ ▷ gradient step
9: **end for**

C.2   HYPERPARAMETERS: BASE MODEL AND PRE-GENERATOR

See Table 3 and Table 4 for the hyperparameters used to define the network architectures train them. For the color datasets CIFAR-10 and CelebA-HQ, we used 5-bit pixel quantization following Kingma & Dhariwal (2018). Additionally for CelebA-HQ, we used the same train-test split (27,000/3,000) of Kingma & Dhariwal (2018) and resized the images to 64×64 resolution.

C.3   HYPERPARAMETERS: IMAGE INPAINTING

We randomly chose 900/500/300 images from MNIST/CIFAR-10/CelebA-HQ test sets, applied masks defined in Section 6.1, and generated samples conditioned on the remaining parts. FID and other sample quality metrics were computed using 32 conditional samples per test image for VI methods (ours and Ambient VI), 8 for Langevin Dynamics, and 6 for PL-MCMC. We note that using more samples for VI methods do not unfairly affect the result of sample quality evaluation, i.e. there

Table 3: Hyperparameters used to train the base models used in our experiments.

Base Models	MNIST	CIFAR-10	CelebA-HQ
Image resolution	28×28	32×32	64×64
Num. scales	3	6	6
Res. blocks per scale	8	12	10
Res. block channels	32	64	80
Bits per pixel	8	5	5
Batch size	128	64	32
Learning rate	0.001	0.001	0.001
Num. epochs	200		

Table 4: Hyperparameters used to define and train the pre-generator for each of our experiments.

Base Models	MNIST	CIFAR-10	CelebA-HQ
Image resolution	28×28	32×32	64×64
Num. scales	3	4	3
Res. blocks per scale	3	4	3
Res. block channels	32	48	48
Batch size	64	32	8

was no appreciable difference when using 8 vs. 32 samples to compute FID. We used more samples simply because it is much cheaper for VI methods to generate samples compared to MCMC methods.

For VI Methods (Ours & Ambient VI)

- Learning rate: $1e-3$ for MNIST; $5e-4$ for the others
- Number of training steps: 2000 for CelebA-HQ; 1000 for the others

For Langevin Dynamics

- Learning rate: $5e-4$ for all datasets
- Length of chain: 1000 for CIFAR-10; 2000 for the others

For PL-MCMC

- Learning rate: $5e-4$
- Length of chain: 2000 for MNIST
- $\sigma_a = 1e-3$, $\sigma_p = 0.05$

C.4 HYPERPARAMETERS: INVERSE PROBLEMS

	Colorization	Compressed Sensing	Compressed Sensing	Super-resolution
Learning rate	$5e-4$	$5e-4$	$5e-4$	$5e-4$
σ	0.05	0.05	0.05	0.05
Dataset	CelebA-HQ	CelebA-HQ	CIFAR-10	CIFAR-10
Batch size	8	8	32	32
Number of steps	1000	2000	1000	1000