A SIMPLE APPROACH TO DEFINE CURRICULA FOR TRAINING NEURAL NETWORKS

ABSTRACT

In practice, sequence of mini-batches generated by uniform sampling of examples from the entire data is used for training neural networks. Curriculum learning is a training strategy that sorts the training examples by their difficulty and gradually exposes them to the learner. In this work, we propose two novel curriculum learning algorithms and empirically show their improvements in performance with convolutional and fully-connected neural networks on multiple real image datasets. Our dynamic curriculum learning algorithm tries to reduce the distance between the network weight and the optimal weight at any training step by greedily sampling examples with gradients that are directed towards the optimal weight. It achieves a speedup of $\sim 45\%$ in our experiments. We also introduce a new task-specific curriculum learning strategy that uses statistical measures such as standard deviation and entropy values to score the difficulty of data points in natural image datasets. We show that this new approach yields a mean speedup of $\sim 43\%$ in the experiments we perform. Further, we also use our algorithms to learn why curriculum learning works. Based on our study, we argue that curriculum learning removes noisy examples from the initial phases of training, and gradually exposes them to the learner acting like a regularizer that helps in improving the generalization ability of the learner.

1 INTRODUCTION

Stochastic Gradient Descent (SGD) (Robbins & Monro, 1951) is a simple yet widely used algorithm used in machine learning optimization. There have been many efforts to improve its performance. A number of such directions, such as AdaGrad (Duchi et al., 2011), RMSProp (Tieleman & Hinton, 2012), and Adam (Kingma & Ba, 2014), improve upon SGD by fine-tuning its learning rate, often adaptively. However, Wilson et al. (2017) has shown that the solutions found by adaptive methods generalize worse even for simple overparameterized problems. Reddi et al. (2019) introduced AMS-Grad hoping to solve this issue. Yet there is performance gap between AMSGrad and SGD in terms of the ability to generalize (Keskar & Socher, 2017). Hence, SGD still remains one of the main workhorses of the ML optimization toolkit.

SGD samples examples from data uniformly at random. However, this approach does not match the way humans typically learn various tasks. We learn a concept faster if we are presented the easy examples first and then gradually exposed to examples with more complexity, based on a curriculum. An orthogonal extension to SGD, that has some promise in improving its performance is to choose examples according to a specific strategy, driven by cognitive science – this is curriculum learning (CL) (Bengio et al., 2009), wherein the examples are shown to the learner based on a curriculum. (Bengio et al., 2009) formalized the idea of CL in machine learning framework where the examples are fed to the learner in an order based on its *difficulty*. The notation of difficulty of examples has not really been formalized and various heuristics have been tried out: Bengio et al. (2009) uses manually crafted scores, self-paced learning (SPL) (Kumar et al., 2010) uses the loss values with respect to the learner's current parameters, and CL by transfer learning uses the loss values with respect to a pre-trained learner to rate the difficulty of examples in data. Among these works, what makes SPL particular is that they use a dynamic CL (DCL) strategy, i.e. the preferred ordering is determined dynamically over the course of the optimization. However, SPL does not really improve the performance of deep learning models, as noted in (Fan et al., 2018). Graves et al. (2017) and Matiisen et al. (2020) propose teacher-guided automatic CL algorithms that employ various super-

vised measures to define dynamic curricula. The most recent works in CL show its advantages in reinforcement learning (Portelas et al., 2020; Zhang et al., 2020).

The recent work by Weinshall & Cohen (2018) introduces the notion of *ideal difficult score* to rate the difficulty of examples based on the loss values with respect to the set of optimal hypotheses. They theoretically show that for linear regression, the expected rate of convergence at a training step t for an example monotonically decreases with its ideal difficulty score. This is practically validated by Hacohen & Weinshall (2019) by sorting the training examples based on the performance of a network trained through transfer learning. However, there is no theoretical evidence to show that CL improves the performance of a completely trained network. Thus, while CL indicate that it is possible to improve the performance of SGD by a judicial ordering, both the theoretical insights as well as concrete empirical guidelines to create this ordering remain unclear.

In this context, our work proposes two simple and novel algorithms for CL. We do a thorough empirical study of our algorithms and provide some more insights into why CL works. Our contributions are as follows:

- We propose a novel dynamic curriculum learning (DCL) algorithm that uses the gradient information to reduce the distance of the weight parameters from the local minima after every training step with a greedy approach. We empirically show the improvement over convergence with our DCL algorithm. We use this framework to study the behaviour of CL.

- Our DCL algorithm generates a natural ordering for training the examples. Previous CL works have demonstrated that exposing a part of the data initially and then gradually exposing the rest is a standard way to setup a curriculum. We use two variants of our DCL framework to show that it is not just the subset of data which is exposed to the model that matters, but also the ordering within the data partition that is exposed.

- Our second contribution is a novel CL approach for image classification tasks that does the ordering of examples in a completely unsupervised manner using statistical measures. Our insight is that *useful* statistical measures could have an association with the difficulty of examples in real data. We empirically analyze our argument of using statistical scoring measures (especially standard deviation) over permutations of multiple datasets and networks. Additionally, we study why CL based on standard deviation scoring works using our DCL framework. We also corroborate why CL works in general based on empirical evidences.

2 PRELIMINARIES

At any training step t, SGD updates the weight $\boldsymbol{w}_t$ using $\nabla f_i(\boldsymbol{w}_t)$ which is the gradient of loss of example $\boldsymbol{x}_i$ with respect to the current weight. The learning rate and the data are denoted by η and $\mathcal{X} = \{(\boldsymbol{x}_i, y_i)\}_{i=0}^{N-1}$ respectively, where $\boldsymbol{x}_i \in \mathbb{R}^d$ denotes a data point and $y_i \in [K]$ its corresponding label for a dataset with K classes. We denote the learner as $h_\vartheta : \mathbb{R}^d \to [K]$. Generally, SGD is used to train h_ϑ by giving the model a sequence of mini-batches $[B_0, B_1, ..., B_{T-1}]$, where $B_i \subseteq \mathcal{X} \; \forall i \in [T]$. Each B_i is generated by uniformly sampling examples from the data. We denote this approach as *vanilla*.

In CL, the curriculum is defined by two functions, namely the scoring function and the pacing function. The scoring function, $score_\vartheta(\boldsymbol{x}_i, y_i) : \mathbb{R}^d \times [K] \to \mathbb{R}$, scores each example in the dataset. Scoring function is used to sort $\mathcal{X}$ in an ascending order of difficulty. A data point $(\boldsymbol{x}_i, y_i)$ is said to be easier than $(\boldsymbol{x}_j, y_j)$ if $score_\vartheta(\boldsymbol{x}_i, y_i) < score_\vartheta(\boldsymbol{x}_j, y_j)$, where both the examples belong to $\mathcal{X}$. The pacing function, $pace_\vartheta(t) : [T] \to [N]$, determines how much of the data is to be exposed at a training step $t \in [T]$.

3 DYNAMIC CURRICULUM LEARNING

For DCL algorithms (Kumar et al., 2010; Graves et al., 2017; Matiisen et al., 2020), examples are scored and sorted after every few training steps since the parameters of the scoring function change dynamically with the learner as training proceeds. Hacohen & Weinshall (2019) and Bengio

(a) Experiment 1   (b) Experiment 2

Figure 1: Learning curves of experiments 1 and 2 comparing *DCL+*, *DCL-*, and *vanilla* SGDs. Error bars signify the standard error of the mean (STE) after 30 independent trials.

et al. (2009) use a fixed scoring function and pace function for the entire training process. They empirically show that a curriculum helps to learn fast in the initial phase of the training process. In this section, we propose and analyze our novel DCL algorithm that updates the difficulty scores of all the examples in the training data at every epoch using their gradient information.

Our DCL algorithm iteratively works on reducing the L2 distance, R_t, between the weight parameter $\boldsymbol{w}_t$ and a given optimal weight $\bar{\boldsymbol{w}}$ at any training step t using a greedy approach. Let us define $\boldsymbol{a}_t = (\bar{\boldsymbol{w}} - \boldsymbol{w}_t)$, $R_t = \|\boldsymbol{a}_t\|_2$, and θ_i^t as the angle between $\nabla f_i(\boldsymbol{w}_t)$ and $\boldsymbol{a}_t$. Suppose, for any $\tilde{t} < t$, $S_{\tilde{t},t}$ is the ordered set containing the $(t - \tilde{t} + 1)$ indices of training examples that are to be shown to the learner from the training steps $\tilde{t}$ through t. Then, using a geometrical argument, (see Figure 3),

$$
\begin{aligned}
R_t^2 &= \left(R_{\tilde{t}} - \eta \sum_{j=\tilde{t},\, i \in S_{\tilde{t},t}}^{j=t-1} \left(\|\nabla f_i(\boldsymbol{w}_j)\|_2 \cos \theta_i^{\tilde{t}} \right) \right)^2 + \eta^2 \left(\sum_{j=\tilde{t},\, i \in S_{\tilde{t},t}}^{j=t-1} \left(\|\nabla f_i(\boldsymbol{w}_j)\|_2 \sin \theta_i^{\tilde{t}} \right) \right)^2 \\
&= R_{\tilde{t}}^2 - 2\eta R_{\tilde{t}} \sum_{j=\tilde{t},\, i \in S_{\tilde{t},t}}^{j=t-1} \left(\|\nabla f_i(\boldsymbol{w}_j)\|_2 \cos \theta_i^{\tilde{t}} \right) + \eta^2 \left(\sum_{j=\tilde{t},\, i \in S_{\tilde{t},t}}^{j=t-1} \left(\|\nabla f_i(\boldsymbol{w}_j)\|_2 \cos \theta_i^{\tilde{t}} \right) \right)^2 \\
&\quad + \eta^2 \left(\sum_{j=\tilde{t},\, i \in S_{\tilde{t},t}}^{j=t-1} \left(\|\nabla f_i(\boldsymbol{w}_j)\|_2 \sin \theta_i^{\tilde{t}} \right) \right)^2
\end{aligned}
\tag{1}
$$

For a *vanilla* model, $S_{\tilde{t},t}$ is generated by uniformly sampling indices from $[N]$ with replacement. Since, finding a set $S_{0,T}$ to minimize R_T^2 and an optimal $\bar{\boldsymbol{w}}$ are intractable for nonconvex optimization problems, we propose an approximate DCL algorithm (*DCL+*, see Algorithm 1). We approximate $\bar{\boldsymbol{w}}$ with $\tilde{\boldsymbol{w}}$, which is a local minima obtained from training the *vanilla* SGD model. Also, to reduce computational expense while sampling examples, we neglect the terms with coefficient η^2 in equation 1 while designing our algorithm. Algorithm 1 uses a greedy approach to minimize R_t^2 by sampling examples at every epoch using the scoring function

$$
score_t(\boldsymbol{x}_i) = -\|\nabla f_i(\boldsymbol{w}_t)\|_2 \cos \theta_i^t = -\frac{\boldsymbol{a}_t^{\mathrm{T}} \cdot \nabla f_i(\boldsymbol{w}_t)}{\|\boldsymbol{a}_t\|_2} = \rho_{t,i}.
$$

Figure 2: Learning curves for experiment 2 with varying $pace(t) = \lfloor kN \rfloor$ for *DCL+*. The parameter k needs to be finely tuned for improving the generalization of the network. A low k value exposes only examples with low noise to the network at every epoch whereas a high k value exposes most of the dataset including highly noisy examples to the network. A moderate k value shows less noisy examples along with some examples with moderate level of noise to the learner. Here, a moderate $k = 0.6$ generalizes the best.

Algorithm 1 Approximate greedy dynamic curriculum learning (*DCL+*).

Input: Data $\mathcal{X}$, local minima $\tilde{w}$, weight w_t, batch size b, and pacing function $pace$.

Output: Sequence of mini-batches B_t for the next training epoch.

1: $\tilde{a}_t \leftarrow \tilde{w} - w_t$
2: $\rho_t \leftarrow [\ ]$
3: $B_t \leftarrow [\ ]$
4: **for** $(i = 0;\ N;\ 1)$ **do**
5:      append $-\dfrac{\tilde{a}_t^{\mathrm{T}} \cdot \nabla f_i(w_t)}{\|\tilde{a}_t\|_2}$ to ρ_t
6: **end for**
7: $\tilde{\mathcal{X}} \leftarrow \mathcal{X}$ sorted according to ρ_t, in ascending order
8: $size \leftarrow pace(t)$
9: **for** $(i = 0;\ size;\ b)$ **do**
10:      append $\tilde{\mathcal{X}}[i, ..., i + b - 1]$ to B_t
11: **end for**
12: **return** B_t

Figure 3: A geometrical interpretation of gradient steps for the understanding of equation 1.

Let us denote the models that use the natural ordering of mini-batches greedily generated by Algorithm 1 for training networks as *DCL+*. *DCL-* uses the same sequence of mini-batches that *DCL+* exposes to the network at any given epoch, but the order is reversed. We empirically show that *DCL+* achieves a faster and better convergence with various initializations of w_0. We use learning rates with an exponential decay rate for the optimizers in all our experiments as traditionally done (Simonyan & Zisserman, 2014; Szegedy et al., 2016). For a fair comparison, we tune the learning rates and decay rates of the models. In our experiments, we set $pace(t) = \lfloor kN \rfloor\ \forall t$, where $k \in [b/N, 1]$ is a tunable hyper-parameter. Fine tuning of k is crucial for improving the performance of *DCL+* on the test set (see Figure 2). We use a 2-layer fully-connected network (FCN) with 10 hidden neurons and Exponential Linear Unit (ELU) nonlinearities to empirically validate our algorithms ($k = 0.9$) on a subset of the MNIST dataset with class labels 0 and 1 (Experiment 1). Since, this is a very easy task (as the *vanilla* model accuracy is as high as $\sim 99.9\%$), we compare the test loss values across training steps in Figure 1a to see the behaviour of DCL on an easy task. *DCL+* shows the fastest convergence, although all the networks achieve the same test accuracy. *DCL+* achieves *vanilla*'s final test loss score at training step 682 ($\sim 30\%$ speedup). In Experiment 2, we use a 2-layered FCN with 128 hidden neurons and ELU nonlinearities to evaluate our DCL algorithms ($k = 0.6$) on a relatively difficult small_mammals dataset, a super-class of CIFAR-100. Figure 1b shows that

DCL+ achieves a faster and better convergence than *vanilla* with respect to the test set accuracy. *DCL+* achieves *vanilla*'s convergence test accuracy score at training step 1896 ($\sim 60\%$ speedup).

4 WHY IS A CURRICULUM USEFUL?

At an intuitive level, we can say that *DCL+* converges faster than the *vanilla* SGD as we greedily sample those examples whose gradient steps are the most aligned towards the optimal weight vector. In previous CL works, mini-batches are generated by uniformly sampling examples from a partition of the dataset which is made by putting a threshold on the difficulty scores of the examples. Notice that our *DCL* algorithms generate mini-batches with a natural ordering at every epoch. We design *DCL+* and *DCL-* to investigate an important question: can CL benefit from having a set of mini-batches with a specific order or is it just the subset of data that is exposed to the learner that matters? With our empirical results, we argue that the ordering of mini-batches does matter.

Firstly, why does a curriculum work? Bengio et al. (2009) illustrates that removing examples that slow down convergence ("noisy" examples) provides a good curriculum for training networks. To an extent, all the CL algorithms effectively aim to remove noisy examples. SPL tries to remove examples that might be misclassified during a training step by avoiding examples with high loss. CL by transfer learning avoids examples that are noisy to an approximate optimal hypotheses in the initial phases of training. *DCL+* and *DCL-* also try to avoid examples with noisy gradients that might slow down the convergence towards the desired optimal minima. Guo et al. (2018) empirically shows that avoiding noisy examples improves the initial learning of convolutional neural networks (CNNs). According to their work, adding noisy examples to later phases of training serves as a regularizer and improves the generalization capability of CNNs. *DCL+* uses its pace function to avoid highly noisy examples (in terms of gradients). In our experiments, the parameter k is chosen such that few moderately noisy examples (examples present in the last few mini-batches within an epoch) are included in training along with lesser noisy examples to improve the network's generalization. We show the importance of tuning the pace function for *DCL+* in Figure 2. Hence, the parameter k serves as a regularizer.

Figure 1 shows that the ordering of mini-batches matters while comparing *DCL+* and *DCL-*, which expose the same set of examples to the learner in any training epoch. Once the mini-batch sequence for an epoch is computed, *DCL-* provides mini-batches to the learner in the decreasing order of noise. This is the reason for *DCL-* to have high discontinuities in the test loss curve after every epoch in Figure 1a. From this we corroborate that ordering in CL plays an important role.

5 STATISTICAL MEASURES FOR DEFINING CURRICULA

Previous works on CL employ tedious methods to score the difficulty level of the examples such as manual labelling (Bengio et al., 2009), using the loss values from pre-trained networks (Weinshall & Cohen, 2018), and using teacher networks to define curricula dynamically as training progresses (Matiisen et al., 2020). A recent work by Hu et al. (2020) uses the number of audio sources to determine the difficulty for audiovisual learning. Liu et al. (2020) uses the norm of word embeddings as a difficulty measure for CL for neural machine translation. In this section, we discuss the idea of using task-specific statistical measures to score examples making it easy to perform CL on real image datasets without the aid of any pre-trained network. We perform experiments and validate our proposal over various image classification datatsets with different network architectures.

Based on the classification task, one could find a statistical measure that could serve the purpose of a scoring function for defining a curriculum. For instance, standard deviation and entropy are informative statistical measures for images and used widely in digital image processing (DIP) tasks (Kumar & Gupta, 2012; Arora, 1981). Mastriani & Giraldez (2016) uses standard deviation filters for effective edge-preserving smoothing of radar images. Natural images might have a higher standard deviation if they have a lot of edges and/or vibrant range of colors. Edges and colours are among the most important features that help in image classification at a higher level. Figure 4 shows 10 images that have the lowest and highest standard deviations in the CIFAR-100 dataset. Entropy measure gives a measure of image information content and is used for various DIP tasks such as automatic image annotation (Jeon & Manmatha, 2004). We experiment using the standard deviation measure ($stddev$), the Shanon's entropy measure ($entropy$) (Arora, 1981), and different norm measures as

Figure 4: Top 10 images with the highest standard deviation values (top row) and top 10 images with the lowest standard deviation values (bottom row) in CIFAR-100 dataset.

Figure 5: Learning curves for experiments 3 (top) and 4 (bottom). Error bars represent the STE after 25 independent trials.

scoring function for CL (see Algorithm 2). The performance improvement with norm measures is not consistent and significant over the experiments we perform (see Appendix A for details). For a flattened image example represented as $\boldsymbol{x} = [x_{(0)}, x_{(1)}, ..., x_{(d-1)}]^{\mathrm{T}} \in \mathbb{R}^d$, we define

$$\mu(\boldsymbol{x}) = \frac{\sum_{i=0}^{d-1} x_{(i)}}{d} \qquad \text{and}$$

$$stddev(\boldsymbol{x}) = \sqrt{\frac{\sum_{i=0}^{d-1}(x_{(i)} - \mu(\boldsymbol{x}))^2}{d}}.$$

(2)

| (a) Experiment 3 | (b) Experiment 4 | (c) Experiment 5 | (d) Experiment 6 | (e) Experiment 7 |

Figure 6: Bars represent the final mean top-1 test accuracy (in %) achieved by models in experiments $3 - 7$. Error bars represent the STE after 25 independent trials for experiments $3, 4$ and 7, and 10 independent trials for experiments 5 and 6.

Algorithm 2 Curriculum learning method.

Input: Data $\mathcal{X}$, batch size b, scoring function $score$, and pacing function $pace$.
Output: Sequence of mini-batches $[B_0, B_1, ..., B_{T-1}]$.
1: sort $\mathcal{X}$ according to $score$, in ascending order
2: $B \leftarrow [\,]$
3: **for** $(i = 1;\ T;\ 1)$ **do**
4:      $size \leftarrow pace(i)$
5:      $\tilde{\mathcal{X}}_i \leftarrow \mathcal{X}[0, 1, ..., size - 1]$
6:      uniformly sample B_i of size b from $\tilde{\mathcal{X}}_i$
7: **end for**
8: **return** B

We use a fixed exponential pace function that exponentially increases the amount of data exposed to the network after every fixed $step\_length$ number of training steps. For a training step i, it is formally given as: $pace(i) = \lfloor \min(1, starting\_fraction \cdot inc^{\lfloor \frac{i}{step\_length} \rfloor}) \cdot N \rfloor$, where $starting\_fraction$ is the fraction of the data that is exposed to the model initially, inc is the exponential factor by which the the pace function value increases after a step, and N is the total number of examples in the data.

We denote CL models with scoring function $stddev$ as *stddev+*, $-stddev$ as *stddev-*, $entropy$ as *entropy+*, and $-entropy$ as *entropy-*. Even though *vanilla* is a competitive benchmark, we also use the CL by transfer learning framework (Hacohen & Weinshall, 2019) (denoted as *TL*) as a baseline. We employ two network architectures for our experiments: a) FCN-512 – A 2-layer FCN with 512 hidden neurons and ELU nonlinearities, and b) CNN-8 – A moderately deep CNN with 8 convolution layers and 2 fully-connected layers. We perform the following experiments: CNN-8 with a) CIFAR-100 (Experiment 3), b) CIFAR-10 (Experiment 4), c) small_mammals (Experiment 5) (these are the benchmark experiments used in Hacohen & Weinshall (2019)), and FCN-512 with d) MNIST (Experiment 6), e) Fashion-MNIST (Experiment 7). For experiments $3 - 5$, we use the same experimental setup as used in Hacohen & Weinshall (2019). More experimental details are deferred to Appendix B. In all our experiments, the models use fine-tuned hyper-parameters for the purpose of an unbiased comparison. Our experiments (3 and 4) show that both $stddev$ and $entropy$ measures as scoring function provide superior results. Since $stddev$ performs the best, we further investigate its benefits on multiple tasks (experiments $5, 6$, and 7). Figures 5 and 6 show the results from our experiments. The best CL models achieve speedups of $56.6\%, 55.0\%, 46.9\%, 8.1\%$, and 50.1% on experiments $3 - 7$, respectively. With these empirical evidences we argue that $stddev$ is a good measure to define curricula for image classification tasks.

Figure 7: Correlation between ρ and $stddev$ vales of examples after epochs $1, 5,$ and 100 for experiments 1 (top row) and 2 (bottom row).

We use our DCL framework to understand why *stddev* works as a scoring function. We try to analyze the correlation between the standard deviation and $\rho_{t,i}$ values of examples over training epochs. Figure 7 shows the plots of standard deviations on the Y-axis against examples plotted on the X-axis ranked based on their $\rho_{t,i}$ values in an ascending order. It shows the dynamics of $\rho_{t,i}$ over initial, intermediate and final stages of training. Correlation between $\rho_{t,i}$ and $stddev$ is evident from these plots. This shows that $stddev$ can also be useful in removing noisy examples from the initial phases of training and hence help in defining a good curriculum.

6 CONCLUSION

In this paper, we propose two novel CL algorithms that display improvement in performance over multiple image classification tasks with CNNs and FCNs. Our DCL algorithm greedily samples data to move towards the optimal weight in a faster manner. It tries to avoid noisy gradients from slowing down the convergence. Its two variants, *DCL+* and *DCL-* provide insights on how important ordering is for a curriculum. The requirement to finely tune the pace function of *DCL+* shows that adding a moderate amount of noisy examples to training helps in improving the network's generalization capability. In this work, a fresh approach to define curricula for image classification tasks based on statistical measures is introduced. This technique makes it easy to score examples in a completely unsupervised manner without the aid of any teacher network. We thoroughly evaluate our new CL method and find it benefits from a faster (mean speedup of $\sim 43\%$) and better convergence (test accuracy improvement of $\sim 0.2\% - 2.2\%$). We use our DCL framework to analyze how the gradients at different stages of training change for examples with a fixed standard deviation. With our results, we argue that CL algorithms help in faster initial learning by removing noisy examples that slow down the convergence towards the minima. Gradually they add noisy examples to training in order to improve the performance of the network on unseen data.

REFERENCES

PN Arora. On the shannon measure of entropy. *Information Sciences*, 1981.

Yoshua Bengio, Jérôme Louradour, Ronan Collobert, and Jason Weston. Curriculum learning. In *Proceedings of the 26th Annual International Conference on Machine Learning*, 2009.

John Duchi, Elad Hazan, and Yoram Singer. Adaptive subgradient methods for online learning and stochastic optimization. *J. Mach. Learn. Res.*, 2011.

Yang Fan, Fei Tian, Tao Qin, Xiang-Yang Li, and Tie-Yan Liu. Learning to teach. In *International Conference on Learning Representations*, 2018.

Alex Graves, Marc G. Bellemare, Jacob Menick, Rémi Munos, and Koray Kavukcuoglu. Automated curriculum learning for neural networks. In *Proceedings of the 34th International Conference on Machine Learning*, 2017.

Sheng Guo, Weilin Huang, Haozhi Zhang, Chenfan Zhuang, Dengke Dong, Matthew R Scott, and Dinglong Huang. Curriculumnet: Weakly supervised learning from large-scale web images. In *Proceedings of the European Conference on Computer Vision (ECCV)*, 2018.

Guy Hacohen and Daphna Weinshall. On the power of curriculum learning in training deep networks. *CoRR*, abs/1904.03626, 2019.

Di Hu, Zheng Wang, Haoyi Xiong, Dong Wang, Feiping Nie, and Dejing Dou. Curriculum audio-visual learning. *arXiv preprint arXiv:2001.09414*, 2020.

Jiwoon Jeon and R Manmatha. Using maximum entropy for automatic image annotation. In *International Conference on Image and Video Retrieval*, 2004.

Nitish Shirish Keskar and Richard Socher. Improving generalization performance by switching from adam to SGD. *CoRR*, abs/1712.07628, 2017.

Diederik Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *International Conference on Learning Representations*, 2014.

M. P. Kumar, Benjamin Packer, and Daphne Koller. Self-paced learning for latent variable models. In *Advances in Neural Information Processing Systems*. 2010.

V. Kumar and Priyanka Gupta. Importance of statistical measures in digital image processing. 2012.

Xuebo Liu, Houtim Lai, Derek F Wong, and Lidia S Chao. Norm-based curriculum learning for neural machine translation. *arXiv preprint arXiv:2006.02014*, 2020.

Mario Mastriani and Alberto E. Giraldez. Enhanced directional smoothing algorithm for edge-preserving smoothing of synthetic-aperture radar images. *CoRR*, abs/1608.01993, 2016.

T. Matiisen, A. Oliver, T. Cohen, and J. Schulman. Teacher–student curriculum learning. *IEEE Transactions on Neural Networks and Learning Systems*, 2020.

Rémy Portelas, Cédric Colas, Katja Hofmann, and Pierre-Yves Oudeyer. Teacher algorithms for curriculum learning of deep rl in continuously parameterized environments. In *Conference on Robot Learning*, 2020.

Sashank J. Reddi, Satyen Kale, and Sanjiv Kumar. On the convergence of adam and beyond. *CoRR*, abs/1904.09237, 2019.

Herbert Robbins and Sutton Monro. A stochastic approximation method. *Ann. Math. Statist.*, 1951.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2016.

Tijmen Tieleman and Geoffrey Hinton. Lecture 6.5-rmsprop: Divide the gradient by a running average of its recent magnitude. *COURSERA: Neural networks for machine learning*, 2012.

Daphna Weinshall and Gad Cohen. Curriculum learning by transfer learning: Theory and experiments with deep networks. *CoRR*, abs/1802.03796, 2018.

Ashia C Wilson, Rebecca Roelofs, Mitchell Stern, Nati Srebro, and Benjamin Recht. The marginal value of adaptive gradient methods in machine learning. In *Advances in Neural Information Processing Systems*. 2017.

Yunzhi Zhang, Pieter Abbeel, and Lerrel Pinto. Automatic curriculum learning through value disagreement. *arXiv preprint arXiv:2006.09641*, 2020.

A   ADDITIONAL EMPIRICAL RESULTS

In Section 5, we study the performance of CL using $stddev$ and $entropy$ as scoring measures. Other important statistical measures are mode, median, and norm (Kumar & Gupta, 2012). A high standard deviation for a real image could mean that the image is having a lot of edges and a wide range of colors. A low entropy could mean that an image is less noisy. Norm of an image gives information about its brightness. Intuitively, norm is not a good measure for determining difficulty of images as low norm valued images are really dark and high norm valued images are really bright. We experiment with different norm measures and find that they do not serve as a good CL scoring measure since they have lesser improvement with higher accuracy variance over multiple trials when compared to *stddev-* on the CIFAR datasets. We use two norm measures

$$norm(\boldsymbol{x}) = ||\boldsymbol{x}||_2, \qquad \text{and}$$
$$class\_norm(\boldsymbol{x}) = ||\boldsymbol{x} - \mu_{\boldsymbol{x}}||_2 \qquad\qquad (3)$$

where $\boldsymbol{x}$ is an image in the dataset represented as a vector, and $\mu_{\boldsymbol{x}}$ is the mean of all the images belonging to the class of $\boldsymbol{x}$. All the orderings are performed based on the scoring function and the examples are then arranged to avoid class imbalance within a mini-batch in our experiments. Let us denote the models that use the scoring functions $norm$ as *norm+*, $-norm$ as *norm-*, $class\_norm$ as *class_norm+*, and $-class\_norm$ as *-class_norm*.

Figure 8 shows the results of our experiments on CIFAR-100 and CIFAR-10 datasets with CNN-8 using $norm$ and $class\_norm$ scoring functions. We find that the improvements reported for *norm-*, the best model among the models that use norm measures, have a lower improvement than *stddev-*. Also, *norm-* has a higher STE when compared to both *vanilla* and *stddev-*. Hence, based on our results, we suggest that standard deviation is a more useful statistical measure than norm measures for defining curricula for image classification tasks.

B   EXPERIMENTAL DETAILS

B.1   NETWORK ARCHITECTURES

All FCNs (denoted as FCN-M) we use are 2-layered with a hidden layer consisting of M neurons with ELU nonlinearities. Experiment 1 employs FCN-10 while experiment 2 employs FCN-128 with no bias parameters. The outputs from the last layer is fed into a softmax layer. Experiments 6 and 7 employ FCN-512 with bias terms. The batch-size is 50.

For experiments $3 - 5$, we use the CNN architecture that is used in Hacohen & Weinshall (2019). The codes are available in their GitHub repository. The network (CNN-8) contains 8 convolution layers with $32, 32, 64, 64, 128, 128, 256,$ and 256 filters respectively and ELU nonlinearities. Except for the last two layers with filter size 2×2, all other layers have a fliter size of 3×3. Batch normalization is performed after every convolution layer, and 2×2 max-pooling and 0.25 dropout layers after every two convolution layers. The output from the CNN is flattened and fed into a fully-connected layer with 512 neurons followed by a 0.5 dropout layer. A softmax layer follows the fully-connected output layer that has a number of neurons same as the number of classes in the dataset. The batch-size is 100. All the CNNs and FCNs are trained using SGD with cross-entropy loss. SGD uses a decaying learning rate. Our codes will be published on acceptance.

B.2   HYPER-PARAMETER TUNING

For fair comparison of models, the hyper-parameters should be finely tuned as rightly mentioned in Hacohen & Weinshall (2019). We exploit hyper-parameter grid-search to tune the hyper-parameters of the models in our experiments. For *vanilla* models, grid-search is easier since they do not have a pace function. For CL models, we follow a coarse two-step tuning process as they have a lot of hyper-parameters. First we tune the optimizer hyper-parameters fixing other hyper-parameters. Then we fix the obtained optimizer parameters and tune other hyper-parameters.

(a) CIFAR-100 with CNN-8   (b) CIFAR-10 with CNN-8

Figure 8: Bars represent the final mean top-1 test accuracy (in %) achieved by models. Error bars represent the STE after 10 independent trials.

B.3 DATASET DETAILS

We use CIFAR-100, CIFAR-10, small_mammals, MNIST, and Fashion-MNIST datasets. CIFAR-100 and CIFAR-10 contain $50,000$ training and $10,000$ test images of shape $32 \times 32 \times 3$ belonging to 100 and 10 classes, respectively. small_mammals is a super-class of CIFAR-100 containing 5 classes. It has $2,500$ training and 500 test images. MNIST and Fashion-MNIST contain $60,000$ training and $10,000$ test gray-scale images of shape 28×28 belonging to 10 different classes. All the datasets are pre-processed before training to have a zero mean and unit standard deviation across each channel.