Provable Benefit of Multitask Representation Learning in Reinforcement Learning

Abstract

As representation learning becomes a powerful technique to reduce sample complexity in reinforcement learning (RL) in practice, theoretical understanding of its advantage is still limited. In this paper, we theoretically characterize the benefit of representation learning under the low-rank Markov decision process (MDP) model. We first study multitask low-rank RL (as upstream training), where all tasks share a common representation, and propose a new multitask reward-free algorithm called REFUEL. REFUEL learns both the transition kernel and the near-optimal policy for each task, and outputs a well-learned representation for downstream tasks. Our result demonstrates that multitask representation learning is provably more sample-efficient than learning each task individually, as long as the total number of tasks is above a certain threshold. We then study the downstream offline RL, where the agent is given a new task sharing the same representation as the upstream tasks and an offline dataset, and aims to find a near-optimal policy. We develop a sample-efficient algorithm with the suboptimality gap bounded by the estimation error of the learned representation in the upstream plus a vanishing term that decreases as the number of offline samples becomes large. Our result further captures the benefit of employing the learned representation from upstream training as opposed to learning the representation of the low-rank model directly. To the best of our knowledge, this is the first theoretical study that characterizes the benefit of representation learning in exploration-based reward-free multitask RL.

1 Introduction

Multitask representation learning has arisen as a popular and powerful framework to deal with data-scarce environment in supervised learning, bandits and reinforcement learning (RL) recently (Maurer et al., 2016; Du et al., 2020; Tripuraneni et al., 2021; Yang et al., 2021; Cella et al., 2022; Lu et al., 2021; Arora et al., 2020; Hu et al., 2021). The general multitask representation learning framework consists of both upstream multiple source tasks learning and downstream target task learning. In RL applications, in upstream, the agent is assigned with T source tasks sharing a common representation and the goal is to learn a near-optimal policy for each task via learning the representation. In downstream, with the help of the learned representation, the agent aims to find a near-optimal policy of a new task that shares the same representation as the source tasks. While representation learning has achieved great success in supervised learning (Du et al., 2020; Tripuraneni et al., 2021; Maurer et al., 2016; Kong et al., 2020) and multi-armed bandits (MAB) problems (Yang et al., 2021; Qin et al., 2022; Cella et al., 2022), most works in multitask RL mainly focus on empirical algorithms (Sodhani et al., 2021; Arulkumaran et al., 2022; Teh et al., 2017) with limited theoretical works (Arora et al., 2020; Hu et al., 2021; Brunskill and Li, 2013; Müller and Pacchiano, 2022; Calandriello et al., 2015; Lu et al., 2021; D'Eramo et al., 2020). Generally speaking, there are two main challenges for multitask representation learning in RL. First, differently from

supervised learning with static datasets, in MAB and RL, representation learning and data collection are intertwined with each other. The agent has to choose an exploration policy in each iteration based on the representation learned in the past. Such iterative process introduces temporal dependence to the collected data. Note that none of the aforementioned theoretical multitask RL studies took the influence of sequential exploration and temporal dependence in data into consideration. Second, data distribution mismatch between the target task and the source tasks may occur. Additional assumption is usually required in order to ensure the representation learned from sources task will benefit the target task (Lu et al., 2021).

In this work, we aim to unveil the fundamental impact of multitask representation learning on RL by answering the following two open questions:

- First, in the upstream, is it possible to design exploration-based multitask representation learning algorithms for RL to achieve efficiency gain compared with single-task RL after taking the interactive data collection process and temporal data dependency into account?

- Second, can the learned representation from upstream bring efficiency gain to the downstream learning?

Main contributions: We focus on multitask representation learning under low-rank MDPs (Agarwal et al., 2020), where the transition kernel admits a low-rank decomposition that naturally involves representation learning. It answers the aforementioned questions affirmatively, as summarized below.

- First, we propose a new multitask representation learning algorithm called REFUEL under low-rank MDPs in upstream. REFUEL features joint modeling learning, pseudo cumulative value function construction for exploration, joint exploration policy learning and a unique termination criterion. These novel designs enable REFUEL to leverage the shared representation across source tasks to improve the learning efficiency.

- We show that REFUEL can 1) find a near-optimal policy and 2) learn a near-accurate model for each of T source tasks to certain average accuracy ϵ_u, with a sample complexity of
$\widetilde{O}\left(\frac{H^3 d^2 K^2}{T\epsilon_u^2} + \frac{\left(H^3 d^4 K + H^5 dK^2 + H^5 d^3 K\right)}{\epsilon_u^2} + \frac{H^5 K^3}{dT\epsilon_u^2}\right)$, where H, K, d denote the horizon steps, the cardinality of action space and the low-rank dimension, respectively. Compared with state-of-the-art single-task representation in low-rank MDPs (Uehara et al., 2022), REFUEL achieves reduced sample complexity as long as $T = \Omega\left(\frac{K}{d^5}\right)$, which shows the benefit of multitask learning provably. To the best of our knowledge, this is the first theoretical result demonstrating the benefit of representation learning in exploration-based reward-free multitask RL.

- Finally, when the learned representation from REFUEL is leveraged for downstream offline learning, we propose a new sample efficient algorithm with suboptimality gap of $\widetilde{O}(H\sqrt{d}\xi_{\text{down}} + Hd/\sqrt{N_{\text{down}}})$, where N_{down} is the number of samples of offline dataset. The first term captures the **approximation error** ξ_{down} that measures the quality of the learned representation from upstream, and is negligible when the upstream learning is sufficiently accurate, and the second term improves the dependency on H and d compared with the state-of-the-art (Uehara et al., 2022) without knowledge of the upstream representation, showing the benefit of employing the learned representation from upstream.

Notations: Throughout the paper, we use $[N]$ to denote set $\{1, \ldots, N\}$ for $N \in \mathbb{N}$, use $\|x\|_2$ to denote the ℓ_2 norm of vector x, use $\|X\|_{\text{F}}$ to denote the Frobenius norm of matrix X, use $\triangle(\mathcal{A})$ to denote the probability simplex over set $\mathcal{A}$, and use $\mathcal{U}(\mathcal{A})$ to denote uniform sampling over $\mathcal{A}$, given $|\mathcal{A}| < \infty$. Furthermore, for any symmetric positive definite matrix Σ, we let $\|x\|_\Sigma := \sqrt{x^\top \Sigma x}$.

2 Related work

Multitask bandits, multitask RL and meta-RL: The benefit of multitask learning in linear bandits has been investigated in Yang et al. (2021); Qin et al. (2022); Cella et al. (2022); Azizi et al. (2022); Deshmukh et al. (2017); Cella and Pontil (2021); Hu et al. (2021). For multitask RL, Arora et al. (2020) showed that representation learning can reduce sample complexity for imitation learning. Calandriello et al. (2015) studied multitask learning under linear MDPs with known representation. Hu et al. (2021) studied multi-task RL with low inherent Bellman error (Zanette et al., 2020) with known representation. Assuming all tasks are sampled from an unknown distribution, Brunskill and Li (2013) studied the benefit of multitask RL when each task is sampled independently from a

distribution over a finite set of MDPs while Müller and Pacchiano (2022) focused on meta-RL for linear mixture model (Yang and Wang, 2020). Considering all tasks share a common representation, D'Eramo et al. (2020) showed the benefit in the convergence rate on value iteration and Lu et al. (2021) proved the sample efficiency gain of multitask RL under low-rank MDPs. None of the above works took the influence of sequential exploration and temporal dependence in data into consideration, where Lu et al. (2021) assumed a generative model is accessible and D'Eramo et al. (2020) assumed that the dataset is given in prior. In our study, we design reward-free exploration for multitask RL.

Single task RL under low-rank MDPs: Low-rank MDPs are first studied byAgarwal et al. (2020), and then Uehara et al. (2022) studied low-rank MDPs for both online and offline RL. Modi et al. (2021) proposed a model-free algorithm MOFFLE for reward-free RL under low-nonnegative-rank MDPs. Du et al. (2019); Misra et al. (2020); Zhang et al. (2022) studied *block MDP* which is a special case of low-rank MDPs.

Offine RL under linear and low-rank MDPs: Most of the existing works on offline RL focus on single-task learning, among which Jin et al. (2021) studied offline RL under linear MDPs and proposed an algorithm called PEVI with provable suboptimality gap, Uehara et al. (2022) studied offline RL under low-rank MDPs and proposed an algorithm called REP-LCB that leverages pessimism to learn under a partial coverage condition, and Yin et al. (2022) studied offline RL leveraging variance information.

3   Problem formulation

3.1   Episodic MDP

Consider an episodic non-stationary Markov Decision Process (MDP) with finite horizon H, denoted by $\mathcal{M} = (\mathcal{S}, \mathcal{A}, H, P, r)$, where $\mathcal{S}$ is the state space (possibly infinite), $\mathcal{A}$ is the finite action space with cardinality K, H is the number of steps in each episode, $P = \{P_h\}_{h \in [H]}$ is the collection of transition measures with $P_h : \mathcal{S} \times \mathcal{A} \mapsto \triangle(\mathcal{S})$, $r = \{r_h\}_{h \in [H]}$ is the collection of deterministic reward functions with $r_h : \mathcal{S} \times \mathcal{A} \mapsto [0, 1]$. The initial state s_1 is assumed to be fixed for each episode and the sum of the reward is normalized with $\sum_{h=1}^{H} r_h \in [0, 1]$.

Denote policy $\pi = \{\pi_h\}_{h \in [H]}$ as a sequence of mappings where $\pi_h : \mathcal{S} \mapsto \triangle(\mathcal{A})$. We use $\pi_h(a|s)$ to denote the probability of selecting action a in state s at step h. Given a starting state s_h, we use $s_{h'} \sim (P, \pi)$ to denote a state sampled by executing policy π under the transition model P for $h' - h$ steps and $\mathbb{E}_{(s_h, a_h) \sim (P, \pi)}[\cdot]$ to denote the expectation over states $s_h \sim (P, \pi)$ and actions $a_h \sim \pi$. Given policy π and a state s at step h, the (state) value function is defined as $V_{h,P,r}^{\pi}(s) := \mathbb{E}_{(s_{h'}, a_{h'}) \sim (P, \pi)}\left[\sum_{h'=h}^{H} r_{h'}(s_{h'}, a_{h'})\Big| s_h = s\right]$. Similarly, the (state-)action value function for a given state-action pair (s, a) under policy π at step h is defined as $Q_{h,P,r}^{\pi}(s, a) = r_h(s, a) + (P_h V_{h+1,P,r}^{\pi})(s, a)$, where $(P_h f)(s, a) = \mathbb{E}_{s' \sim P_h(\cdot|s,a)}[f(s')]$ for any function $f : \mathcal{S} \mapsto \mathbb{R}$. For simplicity, we omit subscript h for $h = 1$. Since the MDP begins with the same initial state s_1, to simplify the notation, we use $V_{P,r}^{\pi}$ to denote $V_{1,P,r}^{\pi}(s_1)$ without causing ambiguity in the following. Let P^* denote the transition kernel of the underlying environment. Given a reward function r, there always exists an optimal policy π^* that yields the optimal value function $V_{P^*,r}^{\pi^*} = \sup_{\pi} V_{P^*,r}^{\pi}$, abbreviated as $V_{P^*,r}^*$.

This paper focuses on low-rank MDPs (Jiang et al., 2017; Agarwal et al., 2020) defined as follows.

Definition 1 (Low-rank MDPs). A transition kernel $P_h^* : \mathcal{S} \times \mathcal{A} \to \triangle(\mathcal{A})$ admits a low-rank decomposition with dimension $d \in \mathbb{N}$ if there exists two embedding functions $\phi_h^* : \mathcal{S} \times \mathcal{A} \to \mathbb{R}^d$ and $\mu_h^* : \mathcal{S} \to \mathbb{R}^d$ such that

$$P_h^*(s'|s, a) = \langle \phi_h^*(s, a), \mu_h^*(s') \rangle, \quad \forall s, s' \in \mathcal{S}, a \in \mathcal{A}.$$

Without loss of generality, we assume $\|\phi_h^*(s, a)\|_2 \leq 1$ for all $(s, a) \in \mathcal{S} \times \mathcal{A}$ and for any function $g : \mathcal{S} \mapsto [0, 1]$, $\left\|\int \mu_h^*(s) g(s) ds\right\|_2 \leq \sqrt{d}$. An MDP is a low-rank MDP with dimension d if for $h \in [H]$, its transition kernel P_h^* admits a low rank decomposition with dimension d. Let $\phi^* = \{\phi_h^*\}_{h \in [H]}$ and $\mu^* = \{\mu_h^*\}_{h \in [H]}$ be the embeddings for P^*, where ϕ^* is also called representation in RL literature.

3.2   Reward-free multitask RL and its downstream learning

We consider a multitask RL consisting of reward-free upstream and reward-known downstream.

In **reward-free multitask** upstream learning, the agent is expected to conduct **reward-free exploration** over T source tasks, where all reward functions $\{r^t\}_{t\in[T]}$ are unknown. Each task $t \in [T]$ is associated with a low-rank MDP $\mathcal{M}^t = (\mathcal{S}, \mathcal{A}, H, P^t, r^t)$. All T tasks are identical except for (a) their transition model P^t, which admits a low-rank decomposition with dimension d: $P^t(s'|s,a) = \langle \phi^*(s'), \mu^{(*,t)}(s,a) \rangle$ for all $t \in [T]$ and (b) their reward r^t. Namely, **all tasks share the same feature function** ϕ^*, but may differ in $\mu^{(*,t)}$ as well as reward r^t. The goal of upstream learning is to find a near-optimal policy and a near-accurate model for any task $t \in [T]$ and any reward function $r^t, t \in [T]$ via sufficient reward-free exploration, and output a well-learned representation for downstream task. For each $t \in [T]$, we use $P^{(*,t)}$ to denote the true transition kernel of task t.

In downstream learning, the agent is assigned with a new target task $T + 1$ associated with a low-rank MDP $\mathcal{M}^{T+1} = (\mathcal{S}, \mathcal{A}, H, P^{T+1}, r^{T+1})$. The task shares the same $\mathcal{S}, \mathcal{A}, H$ and ϕ^* with the T upstream tasks, but has a task-specific $\mu^{(*,T+1)}$. We also assume that the reward for the new task r^{T+1} is given to the agent. Here, the agent is assumed to take the learned representation function $\widehat{\phi}$ during the upstream training, and then interacts with the new task environment $\mathcal{M}^{T+1}$ in an offline manner to find a near-optimal policy for the new task. By utilizing the representation learned in the upstream, the agent is expected to achieve better sample efficiency in the downstream. Finally, we use $P^{(*,T+1)}$ to denote the true transition kernel of task $T + 1$.

4 Upstream reward-free multitask RL

In this section, we present our proposed algorithm for upstream reward-free multitask RL in low-rank MDPs and characterize its theoretical performance.

Since it is impossible to learn a model in polynomial time if there is no assumption on features ϕ_h and μ_h, we first adopt the following conventional assumption (Agarwal et al., 2020).

Assumption 1. (Realizability). A learning agent can access to a model class $\{(\Phi, \Psi)\}$ that contains the true model, namely, for any $h \in [H], t \in [T]$, the embeddings $\phi_h^* \in \Phi, \mu_h^{(*,t)} \in \Psi$.

While we assume the cardinality of function classes to be finite for simplicity, extensions to infinite classes with bounded statistical complexity are not difficult (Sun et al., 2019; Agarwal et al., 2020).

4.1 Algorithm design

We first describe our proposed algorithm REFUEL depicted in Algorithm 1.

In each iteration n, for each task t and time step h, the agent executes the exploration policy π_t^{n-1} followed by two uniformly chosen actions to collect trajectories for H episodes. Note that π_t^{n-1} is designed at the previous iteration. Then, to utilize the common feature of data collected from different source tasks, the agent processes the data jointly as following steps.

Joint MLE-based Modeling Learning: The agent passes all previously collected data to estimate the low-rank components $\widehat{\phi}_h^{(n)}, \widehat{\mu}_h^{(n,1)}, \ldots, \widehat{\mu}_h^{(n,t)}$ simultaneously via the MLE oracle $MLE\left(\bigcup_{t\in[T]} \mathcal{D}_h^{(n,t)}\right)$ (line 9) on the joint distribution defined as follows:

$$\left(\widehat{\phi}_h^{(n)}, \widehat{\mu}_h^{(n,1)}, \ldots, \widehat{\mu}_h^{(n,T)}\right) = \arg\max_{\phi_h \in \Phi, \mu_h^1, \ldots, \mu_h^T \in \Psi} \sum_{n=1}^N \log \left(\prod_{t=1}^T \langle \phi_h(s_h^{(n,t,h)}, a_h^{(n,t,h)}), \mu_h^t(s_{h+1}^{(n,t,h)}) \rangle \right). \quad (1)$$

The MLE oracle above generalizes the MLE oracle commonly adopted for single-task RL in the literature (Agarwal et al., 2020; Uehara et al., 2022). In practice, MLE oracle can be efficiently implemented if the model classes Φ, Ψ are properly parameterized such as by neural networks.

Next, for each task t, the agent uses the learned embeddings $\widehat{\phi}_h^{(n)}, \widehat{\mu}_h^{(n,t)}$ to update the estimated transition kernel $\widehat{P}^{(n,t)}$ at each step h as

$$\widehat{P}_h^{(n,t)}(s'|s,a) = \langle \widehat{\phi}_h^{(n)}(s,a), \widehat{\mu}_h^{(n,t)}(s') \rangle. \quad (2)$$

Pseudo Cumulative Value Function Construction for Exploration: The agent first uses the representation estimator $\widehat{\phi}_h^{(n)}$ to update the empirical covariance matrix $\widehat{U}_h^{(n,t)}$ as

$$\widehat{U}_h^{(n,t)} = \sum_{\tau=1}^n \widehat{\phi}_h^{(n)}(s_h^{(\tau,t,h+1)}, a_h^{(\tau,t,h+1)})(\widehat{\phi}_h^{(n)}(s_h^{(\tau,t,h+1)}, a_h^{(\tau,t,h+1)}))^\top + \lambda_n I, \quad (3)$$

Algorithm 1 REFUEL (REward **F**ree m**U**ltitask r**E**presentation Learning)

1: **Input:** Regularizer λ_n, parameter $\widetilde{\alpha}_n$, ζ_n, B, δ, ϵ_u, Models $\{(\mu, \phi) : \mu \in \Psi, \phi \in \Phi\}$.
2: Initialize $\pi_0(\cdot|s)$ to be uniform, set $\mathcal{D}_h^{(0,t)} = \emptyset$ for $h \in [H], t \in [T]$.
3: **for** $n = 1, \ldots, N_u$ **do**
4:    **for** $h = 1, \ldots, H$ **do**
5:       **for** $t = 1, \ldots, T$ **do**
6:          Under MDP $\mathcal{M}^t$, use π_t^{n-1} to roll into $s_{h-1}^{(n,t,h)}$, uniformly choose $a_{h-1}^{(n,t,h)}, a_h^{(n,t,h)}$ and
           enter into $s_h^{(n,t,h)}, s_{h+1}^{(n,t,h)}$ and collect data $s_1^{(n,t,h)}, a_1^{(n,t,h)}, \ldots, s_h^{(n,t,h)}, a_h^{(n,t,h)}, s_{h+1}^{(n,t,h)}$.
7:          Add the triple $(s_h^{(n,t,h)}, a_h^{(n,t,h)}, s_{h+1}^{(n,t,h)})$ to the dataset $\mathcal{D}_h^{(n,t)} = \mathcal{D}_h^{(n-1,t)} \cup$
           $\{(s_h^{(n,t,h)}, a_h^{(n,t,h)}, s_{h+1}^{(n,t,h)})\}$.
8:       **end for**
9:       Learn $\left(\widehat{\phi}_h^{(n)}, \widehat{\mu}_h^{(n,1)}, \ldots, \widehat{\mu}_h^{(n,T)}\right)$ via $MLE\left(\bigcup_{t \in [T]} \mathcal{D}_h^{(n,t)}\right)$ as Equation (1).
10:       **for** $t = 1, \ldots, T$ **do**
11:          Update estimated transition kernels $\widehat{P}_h^{(n,t)}(\cdot|\cdot, \cdot)$ as Equation (2), empirical covariance
           matrix $\widehat{U}_h^{(n,t)}$ as Equation (3) and exploration-driven reward $\widehat{b}^{(n,t)}(\cdot, \cdot)$ as Equation (4).
12:       **end for**
13:    **end for**
14:    Set **Pseudo Cumulative Value Function** $PCV\left(\widehat{P}^{(n,t)}, \widehat{b}_h^{(n,t)}, \pi_t; T\right)$ as Equation (5).
15:    Get exploration policy $\pi_1^n, \ldots, \pi_T^n = \arg\max_{\pi_1, \ldots, \pi_T} PCV\left(\widehat{P}^{(n,t)}, \widehat{b}_h^{(n,t)}, \pi_t; T\right)$.
16:    **if** $2PCV\left(\widehat{P}^{(n,t)}, \widehat{b}_h^{(n,t)}, \pi_t; T\right) + 2\sqrt{KT\zeta_n} \leq T\epsilon_u$ **then**
17:       **Terminate** and set $n_u = n$ and **output** $\widehat{\phi} = \widehat{\phi}^{(n_u)}, \widehat{P}^{(1)} = \widehat{P}^{(n_u,1)}, \ldots, \widehat{P}^{(T)} = \widehat{P}^{(n_u,T)}$.
18:    **end if**
19: **end for**
20: **Output:** $\widehat{\phi} = \widehat{\phi}^{(n_u)}, \widehat{P}^{(1)} = \widehat{P}^{(n_u,1)}, \ldots, \widehat{P}^{(T)} = \widehat{P}^{(n_u,T)}$.

---

where $\{s_h^{(\tau,t,h+1)}, a_h^{(\tau,t,h+1)}, s_{h+1}^{(\tau,t,h+1)}\}$ is the tuple collected at the τ-th iteration, $(h+1)$-th episode, and step h. Then, the agent uses both $\widehat{\phi}_h^{(n)}$ and $\widehat{U}_h^{(n,t)}$ to provide an exploration-driven reward as

$$\widehat{b}_h^{(n,t)}(s_h, a_h) = \min\left\{\widetilde{\alpha}_n \left\|\widehat{\phi}_h^{(n)}(s_h, a_h)\right\|_{(\widehat{U}_h^{(n,t)})^{-1}}, B\right\}, \tag{4}$$

where B and $\widetilde{\alpha}_n$ are pre-determined parameters. To integrate information of learned models and exploration-driven rewards for T tasks, we define a **Pseudo Cumulative Value Function** (PCV) as

$$PCV\left(\widehat{P}^{(n,t)}, \widehat{b}_h^{(n,t)}, \pi_t; T\right) = \sum_{h=1}^{H-1} \sqrt{\sum_{t=1}^{T}\left\{\mathbb{E}_{\substack{s_h \sim (\widehat{P}^{(n,t)}, \pi_t) \\ a_h \sim \pi_t}}\left[\widehat{b}_h^{(n,t)}(s_h, a_h)\right]\right\}^2}. \tag{5}$$

Joint Policy Learning for Exploration: The agent then learns T policies via optimization over the PCV, and uses these policies as the exploration policy for each task in the next iteration. Since PCV measures the cumulative model estimation error over all tasks, these policies will explore the state-action space where the model estimation has large uncertainty on average of T tasks. Here we adopt an optimization oracle for line 15 in Algorithm 1.

Termination: REFUEL is equipped with a termination condition and outputs the current estimated model and representation during iterations if the PCV plus certain minor term is below a threshold, which suffices to guarantee that for each task t, the returned model $\widehat{P}^{(t)}$ from REFUEL reaches an average proximity to the true model $P^{(*,t)}$.

The joint learning and decision making among all tasks involved in the four main components differentiate REFUEL from single-task RL algorithms, and enable it to exploit the shared representation across the source tasks to improve the sample efficiency.

4.2 Theoretical results on sample complexity

In this section, we first establish the sample complexity upper bound for REFUEL and then compare our multitask result with that of single-task RL.

Theorem 1. *For any fixed $\delta \in (0, |\Psi|^{\min\{T, -\frac{K}{d^2}\}})$, set $\lambda_n = O(d\log(|\Phi|nTH/\delta))$, $\zeta_n = O(\log(|\Phi||\Psi|^T nH/\delta)/n)$, $\widetilde{\alpha}_n = O(\sqrt{K\log(|\Phi||\Psi|^T nH/\delta) + \lambda_n dT})$ and $B = O(\sqrt{T + K/d^2})$. Let $\widehat{\phi}, \widehat{P}^{(1)}, \dots, \widehat{P}^{(T)}$ be the output of Algorithm 1. Then, under Assumption 1, with probability at least $1 - \delta$, for any policy π_t of task $t \in [T]$ and any step $h \in [H]$, we have*

$$\frac{1}{T}\sum_{t=1}^{T}\mathbb{E}_{s_h \sim (P^{(*,t)}, \pi_t), a_h \sim \pi_t}\left[\left\|\widehat{P}_h^{(t)}(\cdot|s_h, a_h) - P_h^{(*,t)}(\cdot|s_h, a_h)\right\|_{TV}\right] \leq \epsilon_u. \tag{6}$$

Further, for any task t, given any reward r^t, let $\widehat{\pi}_t = \arg\max_\pi V^\pi_{\widehat{P}^{(t)}, r^t}$. Then with probability at least $1 - \delta$, $\frac{1}{T}\sum_{t=1}^{T}[V^*_{P^{(*,t)}, r^t} - V^{\widehat{\pi}_t}_{P^{(*,t)}, r^t}] \leq \epsilon_u$.

Meanwhile, the number of trajectories collected by each task is at most

$$\widetilde{O}\left(\frac{H^3 d^2 K^2}{T\epsilon_u^2} + \frac{\left(H^3 d^4 K + H^5 dK^2 + H^5 d^3 K\right)}{\epsilon_u^2} + \frac{H^5 K^3}{dT\epsilon_u^2}\right). \tag{7}$$

Equation (6) in Theorem 1 indicates that the estimated transition kernels of the T MDPs meet the required accuracy on average. Theorem 1 further indicates that with the data collected during such reward-free exploration, if every task is further given any reward function, near-optimal policies can be found for all tasks on average as well.

For the sample complexity bound in Equation (7), the first term is inversely proportional to T, which captures sample-benefit for each task due to learning the T models jointly. The second term is related to the number of samples to guarantee the concentration of empirical covariance matrix $\widehat{U}_h^{(n,t)}$ in order to identify desirable exploration policies. Such concentration needs to be satisfied for each task t independently and can not be implemented jointly, which makes the second term independent with T. The third term originally arises from the model estimation error shift among T tasks when implementing joint MLE-based model estimation. In the algorithm, this error shift is then transferred to B defined in Equation (4), which provides an explicit upper bound for the exploration-driven reward $\widehat{b}_h^{(n,t)}$. Note that $\widehat{b}_h^{(n,t)}$ consists the PCV to guide exploration, which finally contributes to convergence of REFUEL and affects its sample complexity.

Compared with the state-of-the-art sample complexity that scales in $\widetilde{O}\left(\frac{H^5 d^4 K^2}{\epsilon_u^2}\right)$[1] when performing T single-task RL independently (Uehara et al., 2022), REFUEL achieves lower sample complexity when $T = \Omega\left(\frac{K}{d^5}\right)$, and it reduces the single-task sample complexity in (Uehara et al., 2022) by an order of $O\left(\min\{H^2 d^2 T, H^2 K, d^3, dK, \frac{d^5 T}{K}\}\right)$.

Technically, the joint learning feature of REFUEL requires new analytical techniques. We outline the main steps of the proof of Theorem 1 here and defer the detailed proof to Appendix A. **Step 1:** We develop a new upper bound on model estimation error for each task, which captures the advantage of joint MLE model estimation over single-task learning, as shown in Proposition 1. **Step 2:** We establish the PCV as an uncertainty measure that captures the difference between the estimated and ground truth models. This justifies using such a PCV as a guidance for further exploration, as shown in Proposition 2. **Step 3:** We show that the summation of the PCVs over all iterations is sublinear with respect to the total number N_u of iterations, as shown in Proposition 3, which further implies polynomial efficiency of REFUEL in learning the models.

5   Downstream offline RL

In downstream RL, the agent is given a new target task $T + 1$ under MDP $\mathcal{M}^{T+1}$ and aims to find a near-optimal policy for it. The downstream task is assumed to share the same representation as the upstream tasks, and hence the agent can adopt the representation learned from the upstream to expedite its learning. Since the agent does not know the task-specific embedding function μ^{T+1}, she is allowed to have access to an offline dataset $\mathcal{D}_{\text{down}} = \{(s_h^\tau, a_h^\tau, r_h^\tau, s_{h+1}^\tau)\}_{\tau, h=1}^{N_{\text{down}}, H}$, which is rolled out from some behavior policy ρ.

In this section, we provide an algorithm for downstream offline RL, introduce the connections between upstream and downstream MDPs, and characterize the suboptimality gap of the algorithm.

---

[1]We convert their results in discounted setting to our episodic MDP setting by replacing $1/(1-\gamma) = \Theta(H)$.

5.1 Algorithm for downstream offline RL

We present our pessimistic value iteration algorithm for downstream offline RL in Algorithm 2. Although our algorithm shares similar design principles as traditional algorithms for linear MDPs (Jin et al., 2021), it differs from them significantly as described in the following, due to the misspecification of representation from upstream and the general rather than linear reward function adopted. For ease of exposition, we define Bellman operator $\mathbb{B}_h$ as $(\mathbb{B}_h f)(s, a) = r_h(s, a) + (P_h^{(*, T+1)} f)(s, a)$ for any $f : \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}$. The main body of the algorithm consists of a backward iteration over steps. In each iteration h, the agent executes the following main steps.

Algorithm 2 Downstream Offline RL

1: **Input:** Feature $\widehat{\phi}$, dataset $\mathcal{D}_{\text{down}} = \{(s_h^\tau, a_h^\tau, r_h^\tau, s_{h+1}^\tau)\}_{\tau, h=1}^{N_{\text{down}}, H}$, parameters λ, β, ξ_{down}.

2: **Initialization:** $\widehat{V}_{H+1} = 0$.

3: **for** $h = H, H-1, \ldots, 1$ **do**

4: $\quad \widehat{w}_h = \Lambda_h^{-1} \sum_{\tau=1}^{N_{\text{down}}} \widehat{\phi}_h(s_h^\tau, a_h^\tau) \widehat{V}_{h+1}(s_{h+1}^\tau)$ where $\Lambda_h = \sum_{\tau=1}^{N_{\text{down}}} \widehat{\phi}_h(s_h^\tau, a_h^\tau) \widehat{\phi}_h(s_h^\tau, a_h^\tau)^\top + \lambda I_d$.

5: $\quad \widehat{Q}_h(\cdot, \cdot) = \min\{r_h(\cdot, \cdot) + \widehat{\phi}_h(\cdot, \cdot)^\top \widehat{w} - \Gamma_h(\cdot, \cdot), 1\}^+$, where $\Gamma_h(\cdot, \cdot) = \xi_{\text{down}} + \beta[\widehat{\phi}_h(\cdot, \cdot)^\top \Lambda_h^{-1} \widehat{\phi}_h(\cdot, \cdot)]^{1/2}$.

6: $\quad \widehat{V}_h(\cdot) = \widehat{Q}_h(\cdot, \widehat{\pi}_h(\cdot))$, where $\widehat{\pi}_h(\cdot) = \arg\max_{\pi_h} \widehat{Q}_h(\cdot, \widehat{\pi}_h(\cdot))$.

7: **end for**

8: Output: $\{\widehat{\pi}_h\}_{h=1}^H$.

Approximate Bellman update with general reward function. We construct an estimated Bellman update $\widehat{\mathbb{B}}_h \widehat{V}_{h+1}$ based on the dataset $\mathcal{D}_{\text{down}}$ to approximate $\mathbb{B}_h \widehat{V}_{h+1}$. Here $\widehat{V}_{h+1}$ is an estimated value function constructed in the previous iteration based on $\mathcal{D}_{\text{down}}$. Since our reward function is more general and not necessarily linear in the feature, we choose to parameterized $P_h^{(*, T+1)} V_{h+1}^*$ instead of $Q_h^*(s, a) = r_h(s, a) + (P_h^{(*, T+1)} V_{h+1}^*)(s, a)$ due to the linear structure of $P_h^{(*, T+1)}$. Although the ground truth representation is unknown, the agent is able to use the estimated representation learned from the upstream learning to parameterize the linear term $(P_h^{(*, T+1)} V_{h+1}^*)(s, a)$. Then, the coefficient w_h^* can be estimated by solving the following regularized least squares problem:

$$\widehat{w}_h = \operatorname{argmin}_{w \in \mathbb{R}^d} \lambda \|w\|_2^2 + \sum_{\tau=1}^{N_{\text{down}}} \left[w^\top \widehat{\phi}_h(s_h^\tau, a_h^\tau) - \widehat{V}_{h+1}(s_{h+1}^\tau)\right]^2, \tag{8}$$

which has the closed-from solution $\widehat{w}_h = \Lambda_h^{-1} \sum_{\tau=1}^{N_{\text{down}}} \widehat{\phi}_h(s_h^\tau, a_h^\tau) \widehat{V}_{h+1}(s_{h+1}^\tau)$ with $\Lambda_h = \lambda I + \sum_{\tau=1}^{N_{\text{down}}} \widehat{\phi}_h(s_h^\tau, a_h^\tau) \widehat{\phi}_h(s_h^\tau, a_h^\tau)^\top$. We obtain an estimate $(\widehat{\mathbb{B}}_h \widehat{V}_{h+1})(\cdot, \cdot) = r_h(\cdot, \cdot) + \widehat{w}_h^\top \widehat{\phi}_h(\cdot, \cdot)$.

Design pessimism for incorporating upstream misspecification of representation. Pessimism is realized by subtracting an uncertainty metric Γ_h from $\widehat{Q}_h$ (line 5). The uncertainty metric Γ_h quantifies the Bellman update error $|(\widehat{\mathbb{B}}_h \widehat{V}_{h+1} - \mathbb{B}_h \widehat{V}_{h+1})(s, a)|$ at step h. Our selection of Γ_h is in the form of $\xi_{\text{down}} + \beta(\widehat{\phi}_h \Lambda_h^{-1} \widehat{\phi}_h)^{1/2}$, which captures both the **approximation error** (first term) and the **estimation error** in the Bellman update (second term). Both of the above errors are affected by the misspecification of representation from upstream learning. Intuitively, $m := (\widehat{\phi}_h \Lambda_h^{-1} \widehat{\phi}_h)^{-1}$ represents the effective number of samples the agent has explored along the $\widehat{\phi}$ direction, and the penalty term $\beta/\sqrt{m}$ represents the uncertainty along the $\widehat{\phi}$ direction. By choosing a proper value for β, we can prove that with high probability, the uncertainty metric Γ_h always upper bounds the Bellman update error.

Select greedy policy. Line 6 executes a greedy policy $\widehat{\pi}_h$ to maximize $\widehat{Q}_h$, which will be the output of the algorithm after the backward iteration over steps completes.

5.2 Connections between upstream and downstream MDPs

In downstream RL tasks, the agent will adopt the feature $\widehat{\phi}$ learned from upstream Algorithm 1. To ensure that the feature learned in upstream can still work well in downstream tasks, upstream and downstream MDPs should have certain connections. We next elaborate some reasonable assumptions on transition kernels to build such connections.

278 The following reachability assumption is common in relevant literature (Modi et al., 2021).

279 **Assumption 2** (Reachability). For each source task t in upstream, whose transition kernel is $P^{(*,t)}$,

280 there exists a policy π_t^0 such that $\min_{s \in \mathcal{S}} \mathbb{P}_h^{(\pi_t^0,t)}(s) \geq \kappa_u$, where $\mathbb{P}_h^{(\pi_t^0,t)}(\cdot) : \mathcal{S} \to \mathbb{R}$ is the density

281 function over $\mathcal{S}$ using policy π_t^0 to roll into state s at timestep h.

282 **Assumption 3.** The state space $\mathcal{S}$ is compact.

283 Combining Assumption 3 with Assumption 2, it can be shown that there exists a uniform distribution

284 on $\mathcal{S}$ has the density function $f(s) = \upsilon$, where $1/\upsilon$ is the measure of $\mathcal{S}$. Then, we denote $\mathcal{U}(\mathcal{S})$ as

285 the uniform distribution over $\mathcal{S}$ and $\mathcal{U}(\mathcal{S},\mathcal{A})$ as the uniform distribution over $\mathcal{S} \times \mathcal{A}$.

286 **Assumption 4.** For any two different models in the model class $\{(\Phi, \Psi)\}$, say $P^1(s'|s,a) =$

287 $\langle \phi^1(s,a), \mu^1(s') \rangle$ and $P^2(s'|s,a) = \langle \phi^2(s,a), \mu^2(s') \rangle$, there exists a constant C_R such that for all

288 $(s,a) \in \mathcal{S} \times \mathcal{A}$ and $h \in [H]$,

$$\|P_h^1(\cdot|s,a) - P_h^2(\cdot|s,a)\|_{TV} \leq C_R \mathbb{E}_{(s_h,a_h) \sim \mathcal{U}(\mathcal{S},\mathcal{A})} \|P_h^1(\cdot|s_h,a_h) - P_h^2(\cdot|s_h,a_h)\|_{TV}. \quad (9)$$

289 For normalization, we assume that for any $\phi \in \Phi$, $\|\phi(s,a)\|_2 \leq 1$ and for any $\mu \in \Psi$ and any

290 function $g : \mathcal{S} \to [0,1], \left\|\int \mu_h(s)g(s)ds\right\|_2 \leq \sqrt{d}$.

291 Assumption 4 ensures that for each source task t any $(s,a) \in \mathcal{S} \times \mathcal{A}$, the total variation distance

292 between the learned $\widehat{P}^{(t)}(\cdot|s,a)$ and true transition kernels $\widehat{P}^{(*,t)}(\cdot|s,a)$ will not be too large when

293 the expectation of the total variation distance over the entire state action space is small.

294 **Assumption 5.** For the underlying MDP of task $T+1$, we assume that the reward function r^{T+1} is

295 chosen from a function class $\mathcal{R}$ with ε-covering number $\mathcal{N}_{\mathcal{R}}(\varepsilon)$ for any given ε, and $\mathcal{N}_{\mathcal{R}}(\varepsilon) = \widetilde{O}\left(\frac{1}{\varepsilon^p}\right)$.

296 The true transition kernel $P^{(*,T+1)}$ can be ξ-approximated by a linear combination of T source tasks,

297 i.e. there exist T (unknown) coefficients $c_1, \ldots, c_T \in [0, C_L]$ such that

$$\forall (s,a) \in \mathcal{S} \times \mathcal{A}, h \in [H], \quad \left\|P^{(*,T+1)}(\cdot|s,a) - \sum_{t=1}^{T} c_t P^{(*,t)}(\cdot|s,a)\right\|_{TV} \leq \xi. \quad (10)$$

298 Assumption 5 establishes the underlying connection between upstream source tasks and the down-

299 stream target task. The assumption on $\mathcal{N}_{\varepsilon}(\mathcal{R})$ is more general than the common assumption on

300 reward under linear MDP and can be easily achieved in practice. For example, if the reward is

301 linear with respect to an unknown feature $\widetilde{\phi} : \mathcal{S} \times \mathcal{A} \to \mathbb{R}^p$, i.e., there exists $\theta \in \mathbb{R}^p$ and $\|\theta\| \leq R$,

302 $r(s,a) = \langle \widetilde{\phi}(s,a), \theta \rangle$, then $\mathcal{N}_{\varepsilon}(\mathcal{R}) = \widetilde{O}\left(\left(1 + \frac{2R}{\varepsilon}\right)^p\right)$ (see Lemma D.5 in Jin et al. (2020)), which

303 satisfies the assumption. We remark here $\widetilde{\phi}$ is not necessarily the same as ϕ^*, even its dimension p

304 can be different from d.

305 Finally, we make the following coverage assumption for the estimated feature, which can be easily

306 checked in practice.

307 **Assumption 6** (Feature coverage). There exists absolute constant κ_ρ such that

$$\forall h \in [H], \quad \lambda_{\min}(\Sigma_h) \geq \kappa_\rho, \text{ where } \Sigma_h = \mathbb{E}_\rho[\widehat{\phi}_h(s_h,a_h)\widehat{\phi}_h(s_h,a_h)^\top | s_1 = s].$$

5.3 Sample complexity for downstream offline RL

309 Since the downstream task applies the estimated feature from the upstream, the downstream perfor-

310 mance is highly affected by the upstream estimation accuracy of the feature. Hence, we first introduce

311 the definition of ϵ-approximate linear MDP, and provide a guarantee for the estimated feature.

312 **Definition 2** (ϵ-Approximate linear MDP). For any $\epsilon > 0$, MDP $\mathcal{M} = (\mathcal{S}, \mathcal{A}, H, P, r)$ is an ϵ-

313 approximate linear MDP with a time-dependent feature map $\phi : \mathcal{S} \times \mathcal{A} \to \mathbb{R}^d$ if, for any $h \in [H]$,

314 there exist a time-dependent unknown (signed) measures μ over $\mathcal{S}$ such that for any $(s,a) \in \mathcal{S} \times \mathcal{A}$,

315 we have

$$\|P_h(\cdot|s,a) - \langle \phi_h(s,a), \mu_h(\cdot) \rangle\|_{TV} \leq \epsilon. \quad (11)$$

316 Any ϕ satisfying Equation (11) is called an ϵ-approximate feature map for $\mathcal{M}$.

317 Let $\xi_{down} = \xi + \frac{C_L C_R T \upsilon \epsilon_u}{\kappa_u}$. The following lemma shows that the feature $\widehat{\phi}$ learned in upstream is a

318 ξ_{down}-approximate feature map and can approximate the true feature in the new task.

Lemma 1. *Under Assumptions 2 to 5, the output of Algorithm 1 $\widehat{\phi}$ is a ξ_{down}-approximate feature for MDP $\mathcal{M}^{T+1} = (\mathcal{S}, \mathcal{A}, H, P^{(*,T+1)}, r, s_1)$, i.e. there exist a time-dependent unknown (signed) measures $\widehat{\mu}^*$ over $\mathcal{S}$ such that for any $(s, a) \in \mathcal{S} \times \mathcal{A}$, we have*

$$\left\| P_h^{(*,T+1)}(\cdot | s, a) - \left\langle \widehat{\phi}_h(s, a), \widehat{\mu}_h^*(\cdot) \right\rangle \right\|_{TV} \leq \xi_{down}. \tag{12}$$

Furthermore, for any $g : \mathcal{S} \to [0, 1]$, $\left\| \int \widehat{\mu}_h^*(s) g(s) ds \right\|_2 \leq C_L \sqrt{d}$.

Now we are ready to provide our main result in the following theorem.

Theorem 2. *Under Assumptions 2 to 5, for any $\delta \in (0, 1)$, if we set $\lambda = 1$ and $\beta = O\left(d\sqrt{\iota} + \sqrt{dN_{\text{down}}}\xi_{\text{down}} + \sqrt{p \log N_{\text{down}}}\right)$, where $\iota = O\left(\log\left(pdHN_{\text{down}} \max\{\xi_{\text{down}}, 1\}/\delta\right)\right)$, then with probability at least $1 - \delta$, the suboptimality gap of Algorithm 2 is at most*

$$V_{P^{(*,T+1)}, r}^* - V_{P^{(*,T+1)}, r}^{\widehat{\pi}} \leq 2H\xi_{\text{down}} + 2\beta \sum_{h=1}^{H} \mathbb{E}_{\pi^*}\left[\left\|\widehat{\phi}_h(s_h, a_h)\right\|_{\Lambda_h^{-1}} \Big| s_1 = s\right]. \tag{13}$$

If additionally Assumption 6 holds, sample size satisfies $N_{\text{down}} \geq 40\kappa_\rho \cdot \log(4dH/\delta)$, then the suboptimality gap is at most

$$O\left(\kappa_\rho^{-1/2} H d^{1/2} \xi_{\text{down}} + \kappa_\rho^{-1/2} H d \sqrt{\frac{\log(pdHN_{\text{down}} \max\{\xi_{\text{down}}, 1\}/\delta)}{N_{\text{down}}}} + \kappa_\rho^{-1/2} H \sqrt{\frac{p \log N_{\text{down}}}{N_{\text{down}}}}\right). \tag{14}$$

To the best of our knowledge, Theorem 2 provides the first suboptimality gap with approximation error in representation. Our first result characterizes the suboptimality gap if offline data is rolled out from a behavior policy[2]. If the offline data satisfies the feature coverage assumption, we are able to further upper bound the suboptimality gap by three terms as stated in Theorem 2.

We note that Equation (14) can be simplified as $\widetilde{O}\left(H d^{1/2} \xi_{\text{down}} + N_{\text{down}}^{-1/2} H \max\{d, \sqrt{p}\}\right)$, where the first term is a constant error that arises from the **approximation error** in Bellman update. The second term diminishes as N_{down} grows to infinity, and it arises from the **estimation error** of $\widehat{w}_h$ in regularized linear regression. The dependence on d and $\sqrt{p}$ arises from the model complexity of linear function approximation class when we seek a concentration of the estimated value function.

Such an suboptimality also demonstrates that our downstream offline RL benefits from the learned representation from upstream. Namely, as long as the estimated representation in upstream approximates the ground truth well (i.e., ξ_{down} is small), then the remaining term $\widetilde{O}\left(N_{\text{down}}^{-1/2} H \max\{d, \sqrt{p}\}\right)$ of the suboptimality gap improves $\widetilde{O}(H^2 d^2)$[3] of REP-LCB (Uehara et al., 2022) under low-rank MDP with unknown representation, with better dependence on H and d due to the benefit of upstream representation learning.

Further, compared to standard linear MDP with the knowledge of ground truth representation Jin et al. (2021), our suboptimality gap contains an additional upstream misspecification error (i.e., ξ_{down}). The remaining term yields an order of $\widetilde{O}(Hd)$ which matches that in Jin et al. (2021) if we specialize our reward to be linear with $p = O(d)$.

6 Conclusion

In this paper, we show a shared representation of low rank MDPs can be learned efficiently and transferred. We provide upper bound on both the sample complexity of upstream reward-free multitask RL and the suboptimality gap of downstream offline RL with the help of the learned representation from upstream. Our results show that multitask representation learning is provably more sample efficient than learning each task individually and capture the benefit of employing the learned representation from upstream to learn a near-optimal policy of a new similar task in downstream. As future work, we note that our analysis of the downstream offline RL depends on some assumptions that connect between the upstream and downstream MDPs. It is interesting to explore whether these assumptions can be further relaxed.

---

[2]The result remains valid if offline data is compliant with MDP $\mathcal{M}^{T+1}$ (Assumption 2.2 in Jin et al. (2021)).

[3]We convert their results in discounted setting to our episodic MDP setting by replacing $1/(1 - \gamma) = \Theta(H)$.

References

Agarwal, A., Kakade, S., Krishnamurthy, A., and Sun, W. (2020). Flambe: Structural complexity and representation learning of low rank mdps. In Larochelle, H., Ranzato, M., Hadsell, R., Balcan, M. F., and Lin, H., editors, *Advances in Neural Information Processing Systems*, volume 33, pages 20095–20107. Curran Associates, Inc.

Arora, S., Du, S. S., Kakade, S. M., Luo, Y., and Saunshi, N. (2020). Provable representation learning for imitation learning via bi-level optimization. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pages 367–376. PMLR.

Arulkumaran, K., Ashley, D. R., Schmidhuber, J., and Srivastava, R. K. (2022). All you need is supervised learning: From imitation learning to meta-rl with upside down RL. *CoRR*, abs/2202.11960.

Azizi, M. J., Duong, T., Abbasi-Yadkori, Y., György, A., Vernade, C., and Ghavamzadeh, M. (2022). Non-stationary bandits and meta-learning with a small set of optimal arms. *CoRR*, abs/2202.13001.

Barreto, A., Dabney, W., Munos, R., Hunt, J. J., Schaul, T., van Hasselt, H. P., and Silver, D. (2017). Successor features for transfer in reinforcement learning. In Guyon, I., Luxburg, U. V., Bengio, S., Wallach, H., Fergus, R., Vishwanathan, S., and Garnett, R., editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc.

Brunskill, E. and Li, L. (2013). Sample complexity of multi-task reinforcement learning. In Nicholson, A. E. and Smyth, P., editors, *Proceedings of the Twenty-Ninth Conference on Uncertainty in Artificial Intelligence, UAI 2013, Bellevue, WA, USA, August 11-15, 2013*. AUAI Press.

Calandriello, D., Lazaric, A., and Restelli, M. (2015). Sparse multi-task reinforcement learning. *Intelligenza Artificiale*, 9(1):5–20.

Cella, L., Lounici, K., and Pontil, M. (2022). Multi-task representation learning with stochastic linear bandits. *CoRR*, abs/2202.10066.

Cella, L. and Pontil, M. (2021). Multi-task and meta-learning with sparse linear bandits. In de Campos, C. P., Maathuis, M. H., and Quaeghebeur, E., editors, *Proceedings of the Thirty-Seventh Conference on Uncertainty in Artificial Intelligence, UAI 2021, Virtual Event, 27-30 July 2021*, volume 161 of *Proceedings of Machine Learning Research*, pages 1692–1702. AUAI Press.

Dann, C., Lattimore, T., and Brunskill, E. (2017). Unifying pac and regret: Uniform pac bounds for episodic reinforcement learning. *arXiv preprint arXiv:1703.07710*.

D'Eramo, C., Tateo, D., Bonarini, A., Restelli, M., and Peters, J. (2020). Sharing knowledge in multi-task deep reinforcement learning. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net.

Deshmukh, A. A., Dogan, Ü., and Scott, C. (2017). Multi-task learning for contextual bandits. In Guyon, I., von Luxburg, U., Bengio, S., Wallach, H. M., Fergus, R., Vishwanathan, S. V. N., and Garnett, R., editors, *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pages 4848–4856.

Du, S., Krishnamurthy, A., Jiang, N., Agarwal, A., Dudik, M., and Langford, J. (2019). Provably efficient rl with rich observations via latent state decoding. In *International Conference on Machine Learning*, pages 1665–1674. PMLR.

Du, S. S., Hu, W., Kakade, S. M., Lee, J. D., and Lei, Q. (2020). Few-shot learning via learning the representation, provably. *arXiv preprint arXiv:2002.09434*.

Hu, J., Chen, X., Jin, C., Li, L., and Wang, L. (2021). Near-optimal representation learning for linear bandits and linear RL. In Meila, M. and Zhang, T., editors, *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pages 4349–4358. PMLR.

Jiang, N., Krishnamurthy, A., Agarwal, A., Langford, J., and Schapire, R. E. (2017). Contextual decision processes with low bellman rank are pac-learnable. In *International Conference on Machine Learning*, pages 1704–1713. PMLR.

Jin, C., Yang, Z., Wang, Z., and Jordan, M. I. (2020). Provably efficient reinforcement learning with linear function approximation. In *Conference on Learning Theory*, pages 2137–2143. PMLR.

Jin, Y., Yang, Z., and Wang, Z. (2021). Is pessimism provably efficient for offline rl? In Meila, M. and Zhang, T., editors, *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pages 5084–5096. PMLR.

Kong, W., Somani, R., Song, Z., Kakade, S. M., and Oh, S. (2020). Meta-learning for mixed linear regression. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pages 5394–5404. PMLR.

Lehnert, L. and Littman, M. L. (2020). Successor features combine elements of model-free and model-based reinforcement learning. *J. Mach. Learn. Res.*, 21:196:1–196:53.

Lu, R., Huang, G., and Du, S. S. (2021). On the power of multitask representation learning in linear mdp. *arXiv preprint arXiv:2106.08053*.

Maurer, A., Pontil, M., and Romera-Paredes, B. (2016). The benefit of multitask representation learning. *J. Mach. Learn. Res.*, 17:81:1–81:32.

Misra, D., Henaff, M., Krishnamurthy, A., and Langford, J. (2020). Kinematic state abstraction and provably efficient rich-observation reinforcement learning. In *International conference on machine learning*, pages 6961–6971. PMLR.

Modi, A., Chen, J., Krishnamurthy, A., Jiang, N., and Agarwal, A. (2021). Model-free Representation Learning and Exploration in Low-rank MDPs. *arXiv e-prints*, page arXiv:2102.07035.

Müller, R. and Pacchiano, A. (2022). Meta learning mdps with linear transition models. *CoRR*, abs/2201.08732.

Qin, Y., Menara, T., Oymak, S., Ching, S., and Pasqualetti, F. (2022). Non-stationary representation learning in sequential linear bandits. *CoRR*, abs/2201.04805.

Sodhani, S., Zhang, A., and Pineau, J. (2021). Multi-task reinforcement learning with context-based representations. In Meila, M. and Zhang, T., editors, *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pages 9767–9779. PMLR.

Sun, W., Jiang, N., Krishnamurthy, A., Agarwal, A., and Langford, J. (2019). Model-based rl in contextual decision processes: Pac bounds and exponential improvements over model-free approaches. In *Conference on learning theory*, pages 2898–2933. PMLR.

Teh, Y. W., Bapst, V., Czarnecki, W. M., Quan, J., Kirkpatrick, J., Hadsell, R., Heess, N., and Pascanu, R. (2017). Distral: Robust multitask reinforcement learning. In Guyon, I., von Luxburg, U., Bengio, S., Wallach, H. M., Fergus, R., Vishwanathan, S. V. N., and Garnett, R., editors, *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pages 4496–4506.

Tripuraneni, N., Jin, C., and Jordan, M. I. (2021). Provable meta-learning of linear representations. In Meila, M. and Zhang, T., editors, *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pages 10434–10443. PMLR.

Uehara, M., Zhang, X., and Sun, W. (2022). Representation learning for online and offline RL in low-rank MDPs. In *International Conference on Learning Representations*.

Yang, J., Hu, W., Lee, J. D., and Du, S. S. (2021). Impact of representation learning in linear bandits. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net.

Yang, L. and Wang, M. (2020). Reinforcement learning in feature space: Matrix bandit, kernels, and regret bound. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pages 10746–10756. PMLR.

Yin, M., Duan, Y., Wang, M., and Wang, Y.-X. (2022). Near-optimal Offline Reinforcement Learning with Linear Representation: Leveraging Variance Information with Pessimism. *arXiv e-prints*, page arXiv:2203.05804.

Zanette, A., Lazaric, A., Kochenderfer, M., and Brunskill, E. (2020). Learning near optimal policies with low inherent bellman error. In *International Conference on Machine Learning*, pages 10978–10989. PMLR.

Zhang, X., Song, Y., Uehara, M., Wang, M., Sun, W., and Agarwal, A. (2022). Efficient reinforcement learning in block mdps: A model-free representation learning approach. *arXiv preprint arXiv:2202.00063*.