Understanding Robust Learning through the Lens of Representation Similarities

Abstract

Representation learning, *i.e.* the generation of representations useful for down-stream applications, is a task of fundamental importance that underlies much of the success of deep neural networks (DNNs). Recently, *robustness to adversarial examples* has emerged as a desirable property for DNNs, spurring the development of robust training methods that account for adversarial examples. In this paper, we aim to understand how the properties of representations learned by robust training differ from those obtained from standard, non-robust training. This is critical to diagnosing numerous salient pitfalls in robust networks, such as, degradation of performance on benign inputs, poor generalization of robustness, and increase in over-fitting. We utilize a powerful set of tools known as representation similarity metrics, across three vision datasets, to obtain layer-wise comparisons between robust and non-robust DNNs with different architectures, training procedures and adversarial constraints. Our experiments highlight hitherto unseen properties of robust representations that we posit underlie the behavioral differences of robust networks. We discover a lack of specialization in robust networks' representations along with a disappearance of 'block structure'. We also find overfitting during robust training largely impacts deeper layers. These, along with other findings, suggest ways forward for the design and training of better robust networks.

1 Introduction

Representation learning is fundamental to machine learning and a task on which deep neural networks perform remarkably well. Given complex high-dimensional input signals, such as images, speech or text, deep neural networks (DNNs) can learn meaningful, lower-dimensional representations [22, 6, 37, 11, 17, 10, 44]. The downstream utility of these representations underlies DNNs' success on different tasks [5, 13, 33, 24, 3]. For standard image classification, neural networks learn well-separated representations of inputs from different classes to achieve high accuracy. The discovery of adversarial examples, perturbed inputs that induce high error in model predictions, even for well-trained classifiers has motivated the need for another desirable property: *robustness*. Robust training methods typically protect against adversarial examples during the training phase by converting the standard empirical risk minimization objective to a min-max one (Figure 1) [23, 32, 43]. However, they typically have far worse performance on benign inputs, converge slower and appear to require larger architectures to be effective [14, 26, 36, 39]. Given the importance of representation learning for good downstream performance, we posit that an effective method to identify potential improvements for robust training is via developing a better understanding of robustly learned representations.

Our approach is to juxtapose representations of non-robust and robust networks and analyze them through a unified lens. Aggregate metrics like loss and accuracy do shed some light on the differences, but these are task-driven and do not admit a layer-wise comparison of representations [1, 15]. We

need a comprehensive analysis of the impact of choice of architecture, nature of threat model and corresponding attack strength, and the choice of dataset on robustly learned representations and their link to downstream performance.

To this end, we leverage recent work on representation similiarity (RS) that enables fine-grained comparisons of representations obtained across all layers in a deep neural network (DNN) [20, 30]. Our key findings, using both benign and adversarial inputs as probes over CIFAR-10 [21] and the Imagenette and Imagewoof subsets of Imagenet [18] dataset, are:

Non-robust classification   Robust classification

Robust representations are less specialized (§3): Robust networks exhibit much higher similarity across spatially distant layers compared to non-robust networks, which have far more localized similarity. The latter thus exhibit the expected specialization in layers, which is unexpectedly missing in the former. Further, we find reducing the width of the network has a similar effect to increasing the budget used in robust training, with both changes increasing long-range similarity among the learned representations. This indicates that the relative capacity of a network drops as the budget is increased.

Figure 1: **Non-robust vs robust training.** Robust training aims to learn decision boundaries that are robust to adversarial perturbations (ℓ_∞ in this sketch), naturally learning complex decision boundaries than non-robust training.

Early layers are largely unaffected by adversarial examples (§4): The representations of perturbed inputs from non-robust and robust networks are, as expected, starkly different. On the other hand, the representations of benign and perturbed inputs from robust networks are indistinguishable from one another with regards to representation similarity metrics.

Deeper layers overfit (§5): For both non-robust and robust training, early layers in the network converge within the first few epochs, and exhibit very little variation in subsequent training. This indicates they perform similar roles in both benign and robust networks. Deeper layers converge slower while visiting drastically different representations over the course of training. These different representations usually occur when the loss indicates overfitting, leading us to conclude that *deeper layers overfit during robust training*.

Visually dissimilar adversarial constraints can lead to similar robust representations (§6): Regardless of the adversarial constraint, we find a high degree of similarity between the representations of perturbed and benign inputs for robust networks. Representations from networks robust to different, but allied (*e.g.* ℓ_p), threat models are similar across attack strength. We find surprising similarities between the representations of visually unrelated threat models at lower attack strengths.

What do our findings imply? The lack of specialization in robust networks even with heavily overparametrized architectures suggests a need for explicit tools to differentiate between layers during training. Further, the overfitting we find in deeper layers of neural networks is an indication that layer-wise specialized regularization methods need to be adopted for robust training. We hope the lessons from this paper and the accompanying open-source code spur the development of robust learning-specific architectures and training methods.

Paper Layout. We provide an overview of RS tools and robust training methods in §2. We compare representations from non-robust and robust networks using benign inputs in §3. §4 repeats this analysis with perturbed inputs. The evolution of robust representations over training is studied in §5 while the impact of different threat models is in §6. §7 concludes with lessons learned from the analysis.

2 Background and Setup

We provide a brief overview of the techniques we use to train robust networks and the tools we use to probe the intermediate representations of neural networks. Further related work is in Appendix A.

2.1 Adversarial Examples and Robust Learning

Adversarial examples are perturbed inputs to machine learning models that intentionally induce misclassification [4, 34]. For an input $\mathbf{x}$, an untargeted adversarial example with respect to a model f and loss function $\ell(\cdot)$ is generated by adding a perturbation $\boldsymbol{\delta}$ such that $\boldsymbol{\delta} = \arg\max_{\mathbf{x}+\boldsymbol{\delta} \in N(\mathbf{x})} \ell(f(\mathbf{x}+\boldsymbol{\delta}), y)$, where y is the label of the original class and $N(\cdot)$ represents the adversarial constraint or neighborhood. The most commonly used constraints are L_p-ball based, although we also experiment with other unrelated classes of attacks, such as JPEG, Gabor, or Snow based perturbations [19]. We characterize activations of internal layer in a network as: 1) *Benign representation:* if input is non-adversarial 2) *Adversarial representations:* if input is an adversarial example.

Adversarial training [23] has emerged as the most effective methods to train robust classifiers [7], where it accounts for adversarial examples during training. It modifies the empirical risk minimization procedure in non-robust training to a min-max optimization, where the inner maximization focuses on finding the strongest adversarial example for each input during training:

Table 1: Performance of non-robust and robust networks on CIFAR-10 dataset, in particular, the high generalization gap in robust network (WRN-28-10).

Network	Benign accuracy			Robust accuracy		
	Train	Test	Δ	Train	Test	Δ
Non-robust	100.0%	94.9%	5.1%	0.0%	0.0%	0.0%
Robust	100.0%	87.6%	12.4%	98.2%	44.2%	54.0%

$$\min_{\theta} \mathbb{E}_{(\mathbf{x},y) \in \mathcal{D}} \left[\max_{\mathbf{x}+\boldsymbol{\delta} \in N(\mathbf{x})} \ell(f_{\theta}(\mathbf{x}+\boldsymbol{\delta}), y) \right], \qquad (1)$$

where $\mathcal{D}$ is a data distribution and f_{θ} is a model with parameters θ. Newer methods, like TRADES [43], attempt to improve on adversarial training by better balancing the tradeoff between robustness and accuracy. We refer to models trained using methods that account for adversarial examples as *robust* models and those trained without these methods as *non-robust* models.

We refer to accuracy on non-perturbed input as *benign accuracy* and on adversarial examples as *robust accuracy*. Adversarial training is well known to trade-off benign accuracy to gain robustness and exhibits a high generalization gap in robust accuracy (as we show in Table 1 for CIFAR-10 dataset).

2.2 Probing Neural Network Representations

Representation similarity (RS) metrics allow for the quantitative comparison of the activations of different sets of neurons on a given dataset. Comparing learned, internal representations within and between neural networks of different architectures is important for understanding the performance and behavior of these networks under changing conditions. Several metrics have been proposed for this purpose: Canonical Correlation Analysis (CCA) [16] and its extensions, Singular Vector CCA (SVCCA) [30] and Projection Weighted CCA (PWCCA) [25], Centered Kernel Alignment (CKA) [20], the Orthogonal Procrustes distance [12] and model stitching [2, 8]. These metrics can all handle different sized representations, but require that the number of datapoints be the same.

We choose CKA to measure representation similarity, due to its desirable properties such as orthogonal and isotropic invariance, and wide use in previous work [27, 28, 29, 38]. Ding et al. [12] have shown that CKA is nevertheless insensitive to deletions of principal components of representations that strongly correlate with model accuracy. However, this property does not impact the manner in which we use CKA. The Appendix contains experiments with other RS metrics, yielding similar discoveries.

Centred Kernel Alignment (CKA): Let $\boldsymbol{X} \in \mathbb{R}^{n \times p_1}$ with rows $\boldsymbol{x}_i$, and $\boldsymbol{Y} \in \mathbb{R}^{n \times p_2}$ with rows $\boldsymbol{y}_i$ be the activation matrices of layers with p_1 and p_2 neurons respectively, defined on the same set of n points. These activation matrices are then the representations induced by a particular layer. We also define a $n \times n$ centering matrix $\boldsymbol{H} = \boldsymbol{I}_n - \mathbf{11}^{\top}$. The CKA between these activation matrices is then

$$\text{CKA}(\boldsymbol{K}, \boldsymbol{L}) = \frac{\text{tr}(\boldsymbol{K}\boldsymbol{H}\boldsymbol{L}\boldsymbol{H})}{\sqrt{\text{tr}(\boldsymbol{K}\boldsymbol{H}\boldsymbol{K}\boldsymbol{H})\text{tr}(\boldsymbol{L}\boldsymbol{H}\boldsymbol{L}\boldsymbol{H})}}, \qquad (2)$$

where $\boldsymbol{K}_{ij} = k(\boldsymbol{x}_i, \boldsymbol{x}_j)$, $\boldsymbol{L}_{ij} = l(\boldsymbol{y}_i, \boldsymbol{y}_j)$, with k and l being kernels. When the kernels are linear and the activation matrices are centered, we get the Linear CKA between activation matrices to be

$$\text{Linear CKA} = \frac{\|\boldsymbol{Y}^{\top}\boldsymbol{X}\|_F^2}{\|\boldsymbol{X}^{\top}\boldsymbol{X}\|_F \|\boldsymbol{Y}^{\top}\boldsymbol{Y}\|_F} = \frac{\langle \text{vec}(\boldsymbol{X}\boldsymbol{X}^{\top}), \text{vec}(\boldsymbol{Y}\boldsymbol{Y}^{\top}) \rangle}{\|\boldsymbol{X}^{\top}\boldsymbol{X}\|_F \|\boldsymbol{Y}^{\top}\boldsymbol{Y}\|_F}. \qquad (3)$$

(a) CIFAR-10

(b) ImageNette

(c) ImageWoof

(d) Similarity between representations of Non-robust and robust models.

Figure 2: **Stark differences in the cross-layer similarity and block structure for robust networks.** We measure the similarity of benign representations across all pairs of layers in both non-robust and robust networks. *(a, b, c):* Robust networks have an amplified degree of cross-layer similarity, even at long-range, which leads to vanishing of the well known block structure characteristic observed in non-robust networks [28].*(d)* We only observe a poor similarity between representations of benign and robust models, when experimental setup is identical for both.

Since Kornblith et al. [20] find the use of a linear kernel to be as accurate as and much faster than the RBF kernel, we focus only on linear kernels. For further speed-ups, we use online CKA which uses batching to get an unbiased estimate of CKA [28].

2.3 Experimental Setup

We provide a brief overview of our experimental setup here. All of our experiments were run on machines which has either NVidia Titan X or 2080Ti GPUs with 8GB of memory. Further details are in Appendix A.

Models and datasets. We consider three commonly used image dataset: CIFAR-10 [21], ImageNette [18], and ImageWoof [18], where latter two are subsets of ImageNet dataset [9], which we use due to the high cost of adversarial training on the full ImageNet dataset. We use the Wide Resnet [41] class of models on CIFAR-10 dataset and ImageNet-based ResNets for ImageNette and Imagewoof datasets.

Adversarial training. We follow standard convention with ℓ_∞ perturbations and use $\epsilon = \frac{8}{255}$ for CIFAR-10 and $\epsilon = \frac{4}{255}$ for ImageNet based datasets. We use 10-step projected gradient descent (PGD) attack during training and use 20 steps at test time to calculate adversarial representations.

Representation similarity. We will be using mainly using CKA to compare activation matrices derived from different benign or adversarial images. In online CKA, we use a batch-size of 1024 and take 3 passes over the dataset to reduce any stochasticity in the output similarity score. In layer-wise similarity analyses, we consider all layers, including convolutions, pooling, activation, and batch-normalization layers.

3 How do representations from robust and non-robust networks differ?

Robust training is expected to be a harder training objective than non-robust training, since it optimizes for both accuracy and robustness. The resulting trade-off is also reflected in final performance, where the benign accuracy of robust networks is much lower than non-robust networks [23]. In this section, we aim to understand the impact of robust training on internal representations, in particular by

Figure 3: **Delving deeper into cross-layer similarity.** To better understand the unique cross-layer characteristics in robust networks (Figure 2), we ablate along two main design choices: 1) Strength of adversarial attacks in robust training (by increasing perturbation budget (ϵ)) 2) Changing network size (by increasing network width). We observe that the strength of adversarial perturbations predominantly leads to amplification of cross-layer similarity, i.e., higher degree of brightness in the plots. Increase network capacity, even by an order of magnitude, doesn't substantially change this phenomenon. We use Wide-ResNet architectures with CIFAR-10 dataset for this experiment.

comparing benign representations in non-robust and robust networks. Further experiments and results from this section are included in Appendix B. We take the following two-fold approach:

1) Comparing characteristics: Absence of block structure. When comparing layerwise similarity in non-robust networks, numerous works have revealed a 'block structure', with high similarity between the layers comprising a block, and low similarity outside it [20, 28, 31] (Non-robust network plots in Figure 2).We observe that when moving from benign to robust training, while keeping everything else constant, the *block structure all but disappears*. The lack of a block structure in robustly trained networks is accompanied by the presence of *long-range similarities* between layers, with layers having high similarity to those much farther away in the network (Figure 2).

2) Direct comparison: Poor similarity between non-robust and robust network representations. To further investigate the unique characteristic of robust networks, we conduct a cross-layer comparison of benign representations in non-robust and robust networks (Figure 2d). We find a very low degree of similarity across both network representations, which further shows that robust networks had indeed learned strikingly different representations than non-robust networks.

We also show that both of these observations generalize across architectures, datasets and threat models. We now delving deeper in *analyzing cross-layer characteristics of robust networks representations*.

Impact of robust training strength. We investigate this disappearance of block structure in robustly trained networks further by varying both the adversarial budget (ϵ) used for training and the width of the network (Figure 3). As the training ϵ increases, the block structure becomes fainter, eventually disappearing entirely. The block structure is also impacted by network width, with it being marginally more pronounced in larger networks. However, this distinction is largely absent at larger values of ϵ. This establishes that increasing the value of ϵ is making the task more complex, so maintaining the same model capacity leads to a decrease in relative capacity (indicated by high similarity across representations).

| (a) Cross-layer (CIFAR-10) | (b) CIFAR-10 | (c) ImageNette | (d) ImageWoof |

Figure 4: **Divergence of adversarial representations from benign ones.** We compare how adversarial perturbations leads, which intends to heavily model output, distort the internal representations w.r.t. non-adversarial representations. In *(a)* we analyze it across all layers, while in *(b, c, d)* we study it across identical layers, but for different datasets. As expected, adversarial representations in non-robust network are highly dissimilar from benign ones near the end of network. Unexpectedly, such divergence is very small for a non-trivial fraction of early layers (up to one-third). Robust training successfully reduces the impact of adversarial perturbations, thus leading to similar benign and adversarial representations in robust networks.

Impact of architecture. Previously Nguyen et al. [28] observed that increasing network width, thus capacity, leads to emergence of block-structure in non-robust networks. Thus we incrementally increase the width of robust Wide-ResNet architecture on CIFAR-10 dataset and measure the cross-layer representation similarity of benign features (Figure 3, expanded on in App. B). Even after increasing network capacity by an order of magnitude, we don't see significant variation in the characteristics of robust network representations. These results suggest that while increasing width in robust networks doesn't lead a drastic shift in similarity of internal layer representations.

4 Probing the impact of adversarial perturbations on representations

Robust training aims to learn both high quality benign and robust representations. In the previous section we characterized the impact of robust training on benign representations. In this section, we focus on understanding the characteristics of adversarial representations in robust networks. Detailed results, as well as ablations on architecture and threat model, are available in Appendix C. We first analyze how adversarial perturbations distorts the internal representations as we go deeper into the network, i.e., compare adversarial and benign internal representations. Next we analyze whether the distortions introduced by adversarial perturbations can also provide insights into why such perturbations transfer between different networks.

4.1 Impact of adversarial perturbations across layers in non-robust and robust networks

In this experiment, we measure the CKA similarity between benign image representations and corresponding adversarial images representations.

A fraction of early layers are largely unaffected. Adversarial perturbation are crafted to corrupt final layer representations, where as expected, the similarity score decays to near zero by final layer (Figure 4). However, we also observe another surprising trend where the adversarial representations shares a high degree of similarity with a fraction (up to one-third for ImageNette and Imagewoof datasets) of early layers. We find this observation holds across architectures and budgets, indicating that earlier layers representations, even in benign networks, are robust to adversarial perturbations.

Robust networks successfully prevent the distortion of internal representations. For robustly trained networks, benign and robust representations maintain a high degree of similarity throughout the network, with divergence only occurring in the last 10 layers or so. In our ablation on network size, we see that increasing the size of the network leads to increased differentiation, implying sufficient capacity for increased separability between benign and perturbed representations.

4.2 Understanding transferability through the lens of internal representation similarity

It is well-known that adversarial examples are *transferable* from one architecture to another, i.e., adversarial example generated on one network achieve the misclassification objective on others too. In Figure 5a, we measure the transferability among non-robust and robust networks. Intriguingly,

(a) Transfer accuracy of adversarial examples.

(b) *Non-robust* WRN-28-10 vs. *non-robust* Wide Resnets.

(c) *Robust* WRN-28-10 and other *robust* Wide Resnets.

(d) *Robust* WRN-28-10 and other *non-robust* Wide Resnets

Figure 5: **Analyzing cross-architecture representations to understand similairty.** *(a)* Measuring the robust accuracy of adversarial examples transferred among robust (R) and non-robust (NR) Wide-ResNet networks of varying width (e.g., R-5 refers to Robust WRN-28-5). Low robust accuracy implies high transferability. *(b, c, d)* We measure RS between source and target networks, where these representations are extracted using adversarial examples generated for the source network. When both networks are trained in the same fashion (benign or robust), the layer wise similarity is generally high at earlier layers but drops off towards the end. In contrast, it drops right after the first layer from robust to non-robust network, a set of networks which also have least transferability.

as previous also validate by [7], transferability is higher among some networks (non-robust to non-robust) while much poorer for other (robust to non-robust). High transfer ability indicates that the target network has learned similar decision boundary. We aim to better understand this phenomenon by comparing the internal representations of source and target networks. We first generate adversarial example, and their corresponding internal layer representations, from a source network (WRN-28-10 in this case). We compare it with internal layer representations of these adversarial examples on target network. We consider transfer from non-robust to robust, robust to robust, and robust to non-robust networks [1] (Figure 5).

For transfer from non-robust to non-robust or robust-robust, where highest transferability occurs, we observe high degree of similarity between representations at early layers. It indicates that the transferred adversarial examples distort the internal representations in a similar fashion as source network. The most intriguing aspect in Figure 5a is extremely poor transferability from robust to non-robust networks. We establish that this is due to significant differences in representations where, even across identical architectures, we observe a large drop in CKA right after input layer. It shows that adversarial perturbations from robust nework distorts the internal representations of non-robust network in a strikingly different manner (even at very early layers), which likely renders them ineffective to cause an adversarial effect at the output of the network.

5 Evolution of internal representation dynamics during robust training

In this section, we track the evolution of representations learned by robust training methods over the course of training epochs in the optimization process. We study following two convergence properties: 1) Rate of convergence at different layers, 2) Stability of different layers throughout learning. As in earlier sections, we use CKA to measure similarity, but in this section we *compare the benign representations of the same layer across time*. We present our results for Wide-ResNet architecture in figure 6, where we compare the representations at each epoch to the final epoch (epoch 100). We further investigate it across architectures, different layers, and attack budgets in Appendix D.

Early layers converge faster than later layers. Benign representations after the first two blocks of WRN-28-10 are highly similar to the representation obtained at the end of training, after just ten epochs (Figure 6). This is true for all the training methods considered. In App. D, we show this largely holds true across architectures and smaller budgets. Our observation relates to the intuition that early layers learn simpler features [22, 40, 42], thus are learned much faster than complex feature learned by later layers. Only with high budget ($\epsilon = \frac{16}{255}$), i.e., stronger attacks, we observe a deviation from this trend where second block convergence is slower.

Overfitting is predominantly visible in later layers. From the cross-epoch heatmap of similarities between adversarial representations (App. D), we observe that later layer representations only exhibit

---

[1]Robust networks are known to be highly resilient to adversarial examples generated from non-robust networks (see Figure 5a).

Figure 6: **Variation in convergence of different layers.** To study it, we measure similarity of each epoch representations with fully trained network representations across both non-robust and robust (both PGD-based and Trades) training techniques. We observe that representations obtained after the first two blocks converge to their final state very early in the training process and have very little variation in both non-robust and robust network. We also find that later layers exhibit more complex behavior, with signs of overfitting when early stopping is not used, and a lack of stability from one epoch to the next.

similarity off-diagonal at the beginning (until epoch 30) and end of training. This clearly shows that multiple local minima are found during training. This is true to a less pronounced degree for benign representations. In Fig. 6, we also observe the adversarial validation loss increasing after around 30 epochs, while the training loss keeps decreasing, indicating overfitting. After this point in training, the CKA similarity between drops with respect to both the epoch 30 and final representation drops significantly in later layers, while the earlier layers remain unaffected. This strongly indicates that the later layers have overfit to the training data.

Adversarial training reduces stability of internal representations during training. While subsequent epoch representations tend to be very similar to each other in non-robust training, there there can be very large jumps in similarity between one epoch and the next, indicating a less stable convergence. This effect further accentuates when training with a higher perturbation budget or when training a larger network (App. D).

6 How does the threat model impact representations?

Throughout the paper, we have focused on a single threat model: ℓ_∞ perturbations. In this section, we extend our analysis of robust representations to understand what exactly is the link between the visual similarity of threat models and the representations of models trained to be robust to them. To this end, we consider *four* additional threat models: ℓ_2, JPEG, Gabor and Snow [19] (visualized in App. A). We also examine the generalizability of our earlier results across these threat models. For space reasons, all associated figures from this section are in App. E.

Do visually similar attacks lead to similar robust representations? RS gives us a method by which we can compare how different classes of adversarial perturbations affect learned representations. Using CKA, we plotted the cross-layer similarity of robust WRN-28-10 networks adversarially trained against five different threat models (ℓ_2, ℓ_∞, JPEG, Gabor, and Snow) (Figure 7). These comparisons lend credence to conventional knowledge about these threat models. The layerwise similarity plot between l_2 and l_∞ robust models is strikingly similar to CKA plots between robust models trained on the same threat model. This mirrors theoretical results on correspondences between ℓ_p threat models [35]. We also observe a higher average similarity when comparing an ℓ_∞ model with a JPEG model than with Snow or Gabor models. This makes intuitive sense, given the ℓ_∞ constraint inherent in the JPEG attack. When using CKA to compare against the Snow threat model, we observe that the

Figure 7: **Layer-wise similarity plots between different threat models**. The top row shows comparisons between all threat models and l_∞, and the second row shows comparisons between all threat models and Snow.

highest average similarity is achieved with Gabor. This represents a novel insight into these threat classes, as correspondence between the two was not previously known.

Alignment of budgets across different attacks. CKA can also give insight into the varying effects of changing perturbation strengths within different threat models. Expanding on our experiments above (all figures are in App. E), we compared representations between different threat models while varying perturbation strengths. Between ℓ_∞ and Gabor models, the layerwise similarity structure is much more sensitive to changes in the strength used in ℓ_∞-robust training than in Gabor-robust training. For more closely related attacks, like ℓ_∞ and JPEG, we see similar degradations of the structure when changing the strength of either attack. Furthermore, the structure is largely preserved when the attack strengths are changed in tandem. These results may be useful for developing techniques for training models to be jointly-robust against different classes of attack.

Layerwise structure across threat models. We find that across all threat models except Snow, robust and benign activations exhibit high similarity (figures in App. E). Further, as we change budgets across the same threat model, we find that ℓ_p threat models have representations that evolve more gradually.

7   Discussion

In this paper, we demonstrated the ability of representation similarity metrics to enable a better understanding of robust neural networks. We identified several salient differences between internal representations of non-robust and robust models. We showed that robust models exhibit far higher inter-layer similarity and are prone to overfitting in deeper layers. These observations highlight that robust networks could be improved by encouraging greater differentiation between layers during training as well as targeted reduction of capacity in deeper layers. In addition, we showed why transferability is so low from adversarial examples from robust models to non-robust ones. Our results on different threat models indicate a path forward for networks robust to multiple attackers as well by allowing for the determination of budgets and layers leading to the best alignment in features.

The key limitations of our study arise from the fundamental disjunct between aggregate properties and layer-wise representation similarity metrics. The latter serve mainly to highlight trends and differences between different models, but do not provide a direct method to improve upon aggregate properties like loss and accuracy. These improvements have to be inferred from a careful analysis of similarities, and future work needs to build upon the observations in this paper for actionable changes to training strategies and architectures.

References

[1] Andriushchenko, M. and Flammarion, N. (2020). Understanding and improving fast adversarial training. *Advances in Neural Information Processing Systems*, 33:16048–16059.

[2] Bansal, Y., Nakkiran, P., and Barak, B. (2021). Revisiting model stitching to compare neural representations. *Advances in Neural Information Processing Systems*, 34.

[3] Beal, J., Wu, H.-Y., Park, D. H., Zhai, A., and Kislyuk, D. (2022). Billion-scale pretraining with vision transformers for multi-task visual representations. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 564–573.

[4] Biggio, B., Corona, I., Nelson, B., Rubinstein, B. I., Maiorca, D., Fumera, G., Giacinto, G., and Roli, F. (2014). Security evaluation of support vector machines in adversarial environments. In *Support Vector Machines Applications*, pages 105–153. Springer.

[5] Brown, T., Mann, B., Ryder, N., Subbiah, M., Kaplan, J. D., Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., et al. (2020). Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.

[6] Conneau, A., Khandelwal, K., Goyal, N., Chaudhary, V., Wenzek, G., Guzmán, F., Grave, E., Ott, M., Zettlemoyer, L., and Stoyanov, V. (2019). Unsupervised cross-lingual representation learning at scale. *arXiv preprint arXiv:1911.02116*.

[7] Croce, F., Andriushchenko, M., Sehwag, V., Debenedetti, E., Flammarion, N., Chiang, M., Mittal, P., and Hein, M. (2020). Robustbench: a standardized adversarial robustness benchmark. *arXiv preprint arXiv:2010.09670*.

[8] Csiszárik, A., Kőrösi-Szabó, P., Matszangosz, Á., Papp, G., and Varga, D. (2021). Similarity and matching of neural network representations. *Advances in Neural Information Processing Systems*, 34.

[9] Deng, J., Dong, W., Socher, R., Li, L.-J., Li, K., and Fei-Fei, L. (2009). Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pages 248–255. Ieee.

[10] Deng, J., Guo, J., Xue, N., and Zafeiriou, S. (2019). Arcface: Additive angular margin loss for deep face recognition. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 4690–4699.

[11] Devlin, J., Chang, M.-W., Lee, K., and Toutanova, K. (2018). Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*.

[12] Ding, F., Denain, J.-S., and Steinhardt, J. (2021). Grounding representation similarity through statistical testing. *Advances in Neural Information Processing Systems*, 34.

[13] Dosovitskiy, A., Beyer, L., Kolesnikov, A., Weissenborn, D., Zhai, X., Unterthiner, T., Dehghani, M., Minderer, M., Heigold, G., Gelly, S., Uszkoreit, J., and Houlsby, N. (2021). An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*.

[14] Gao, R., Cai, T., Li, H., Hsieh, C.-J., Wang, L., and Lee, J. D. (2019). Convergence of adversarial training in overparametrized neural networks. *Advances in Neural Information Processing Systems*, 32.

[15] Gowal, S., Qin, C., Uesato, J., Mann, T., and Kohli, P. (2020). Uncovering the limits of adversarial training against norm-bounded adversarial examples. *arXiv preprint arXiv:2010.03593*.

[16] Hardoon, D. R., Szedmak, S., and Shawe-Taylor, J. (2004). Canonical correlation analysis: An overview with application to learning methods. *Neural computation*.

[17] Hinton, G., Deng, L., Yu, D., Dahl, G. E., Mohamed, A.-r., Jaitly, N., Senior, A., Vanhoucke, V., Nguyen, P., Sainath, T. N., et al. (2012). Deep neural networks for acoustic modeling in speech recognition: The shared views of four research groups. *IEEE Signal processing magazine*, 29(6):82–97.

[18] Howard, J. (2020). imagenette. `https://github.com/fastai/imagenette`.

[19] Kang, D., Sun, Y., Hendrycks, D., Brown, T., and Steinhardt, J. (2019). Testing robustness against unforeseen adversaries. *arXiv preprint arXiv:1908.08016*.

[20] Kornblith, S., Norouzi, M., Lee, H., and Hinton, G. (2019). Similarity of neural network representations revisited. In *International Conference on Machine Learning*, pages 3519–3529. PMLR.

[21] Krizhevsky, A., Hinton, G., et al. (2009). Learning multiple layers of features from tiny images.

[22] Krizhevsky, A., Sutskever, I., and Hinton, G. E. (2012). Imagenet classification with deep convolutional neural networks. *Advances in neural information processing systems*, 25.

[23] Madry, A., Makelov, A., Schmidt, L., Tsipras, D., and Vladu, A. (2018). Towards deep learning models resistant to adversarial attacks. In *ICLR*.

[24] Mahajan, D., Girshick, R., Ramanathan, V., He, K., Paluri, M., Li, Y., Bharambe, A., and Van Der Maaten, L. (2018). Exploring the limits of weakly supervised pretraining. In *Proceedings of the European conference on computer vision (ECCV)*, pages 181–196.

[25] Morcos, A., Raghu, M., and Bengio, S. (2018). Insights on representational similarity in neural networks with canonical correlation. *Advances in Neural Information Processing Systems*, 31.

[26] Nakkiran, P. (2019). Adversarial robustness may be at odds with simplicity. *arXiv preprint arXiv:1901.00532*.

[27] Neyshabur, B., Sedghi, H., and Zhang, C. (2020). What is being transferred in transfer learning? *Advances in neural information processing systems*, 33:512–523.

[28] Nguyen, T., Raghu, M., and Kornblith, S. (2020). Do wide and deep networks learn the same things? uncovering how neural network representations vary with width and depth. *arXiv preprint arXiv:2010.15327*.

[29] Raghu, A., Raghu, M., Bengio, S., and Vinyals, O. (2020). Rapid learning or feature reuse? towards understanding the effectiveness of maml. In *International Conference on Learning Representations*.

[30] Raghu, M., Gilmer, J., Yosinski, J., and Sohl-Dickstein, J. (2017). Svcca: Singular vector canonical correlation analysis for deep learning dynamics and interpretability. *Advances in neural information processing systems*, 30.

[31] Raghu, M., Unterthiner, T., Kornblith, S., Zhang, C., and Dosovitskiy, A. (2021). Do vision transformers see like convolutional neural networks? *Advances in Neural Information Processing Systems*, 34.

[32] Raghunathan, A., Steinhardt, J., and Liang, P. (2018). Certified defenses against adversarial examples. In *International Conference on Learning Representations*.

[33] Shen, J., Pang, R., Weiss, R. J., Schuster, M., Jaitly, N., Yang, Z., Chen, Z., Zhang, Y., Wang, Y., Skerrv-Ryan, R., et al. (2018). Natural tts synthesis by conditioning wavenet on mel spectrogram predictions. In *2018 IEEE international conference on acoustics, speech and signal processing (ICASSP)*, pages 4779–4783. IEEE.

[34] Szegedy, C., Zaremba, W., Sutskever, I., Bruna, J., Erhan, D., Goodfellow, I., and Fergus, R. (2013). Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*.

[35] Tramèr, F. and Boneh, D. (2019). Adversarial training and robustness for multiple perturbations. In *Advances in Neural Information Processing Systems*, pages 5866–5876.

[36] Tsipras, D., Santurkar, S., Engstrom, L., Turner, A., and Madry, A. (2018). Robustness may be at odds with accuracy. *arXiv preprint arXiv:1805.12152*.

[37] Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., and Polosukhin, I. (2017). Attention is all you need. *Advances in neural information processing systems*, 30.

[38] Vulić, I., Ponti, E. M., Litschko, R., Glavaš, G., and Korhonen, A. (2020). Probing pretrained language models for lexical semantics. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 7222–7240, Online. Association for Computational Linguistics.

[39] Xie, C. and Yuille, A. (2020). Intriguing properties of adversarial training at scale. In *ICLR*. arXiv: 1906.03787.

[40] Yosinski, J., Clune, J., Nguyen, A., Fuchs, T., and Lipson, H. (2015). Understanding neural networks through deep visualization. *arXiv preprint arXiv:1506.06579*.

[41] Zagoruyko, S. and Komodakis, N. (2016). Wide residual networks. *arXiv preprint arXiv:1605.07146*.

[42] Zeiler, M. D. and Fergus, R. (2014). Visualizing and understanding convolutional networks. In *European conference on computer vision*, pages 818–833. Springer.

[43] Zhang, H., Yu, Y., Jiao, J., Xing, E., El Ghaoui, L., and Jordan, M. (2019). Theoretically principled trade-off between robustness and accuracy. In *International conference on machine learning*, pages 7472–7482. PMLR.

[44] Zhou, J., Cui, G., Hu, S., Zhang, Z., Yang, C., Liu, Z., Wang, L., Li, C., and Sun, M. (2020). Graph neural networks: A review of methods and applications. *AI Open*, 1:57–81.