Oracle-Efficient Online Learning for Smoothed Adversaries (with Appendices)

Abstract

In this paper, we study oracle-efficient algorithms for smoothed analysis of online learning. In this setting, an adversary is constrained to generating samples from distributions whose density is upper bounded by $1/\sigma$ times the uniform density. Given access to an offline optimization oracle, we give the first computationally efficient online algorithms whose sublinear regret depends only on the pseudo/VC dimension d of the class and the smoothness parameter σ. In particular, we achieve oracle-efficient regret bounds of $O(\sqrt{Td\sigma^{-1}})$ for learning real-valued functions and $O(\sqrt{Td\sigma^{-\frac{1}{2}}})$ for learning binary-valued functions. This contrasts the computational separation between online learning with worst-case adversaries and offline learning established by [HK16]. In the binary setting, our algorithms also achieve improved bounds for worst-case setting with small domains. In particular, we give an oracle-efficient algorithm with regret of $O(\sqrt{T(d|\mathcal{X}|)^{1/2}})$, which is a refinement of the earlier $O(\sqrt{T|\mathcal{X}|})$ bound by [DS16].

1 Introduction

Adversarial online learning is a cornerstone of modern machine learning and has led to significant advances in computer science broadly. A recent line of work on "beyond the worst-case analysis" of online learning has brought into light the overly pessimistic nature of standard characterizations of online learnability [RST11, GR17, HRS20, HRS21]. This is exemplified by the results of [HRS21] showing that adversarial online learnability is *statistically* as easy as PAC learnability, in presence of noise. That is, under *smoothed analysis*, online and offline learnability are both characterized by the finiteness of the VC dimension of a hypothesis class as opposed to the much larger Littlestone dimension that characterizes online learnability in the worst-case [BDPSS09]. However, to fully deliver on the promise revealed by these statistical insights, there needs to be an algorithmic framework for realizing this connection between online and offline learnability. In this paper, we ask

> *Do efficient offline learning algorithms lead to efficient online learning algorithms*
> *with comparable regret guarantees, under the smoothed analysis framework?*

In more detail, smoothed analysis is a perspective on algorithm design, introduced by [ST04] and formalized for online learning by [RSS12, HRS20], in which the adversary is restricted to generating an instance at every round from a distribution that is not overly concentrated, i.e. a distribution whose density is upper bounded by $1/\sigma$ times that of the uniform distribution[1]. The smoothness of the adversary's actions captures the noise and imprecision inherent in the real world and as a

---

[1]While we use the uniform distribution as the base measure for ease of exposition, our results also generalize to arbitrary known base measures.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

		Regret Bound	Method	Reference
Statistical Upper Bound	Binary	$\widetilde{O}\left(\sqrt{dT\log(\sigma^{-1})}\right)$	Coupling-based Analysis and ϵ-Net	[HRS21, Thm 3.1]
	Real-values	$\widetilde{O}\left(\sqrt{dT\log(\sigma^{-1})}\right)$		Thm E.1
Computational Upper Bound	Binary	$\widetilde{O}\left(\sqrt{dT\sigma^{-1/2}}\right)$	FTPL with Poissonization 1 oracle call per round	Thm 3.2
	Binary	$\widetilde{O}\left(\sqrt{dT\sigma^{-1}}\right)$	Relaxation-Based (Monotonicity) 2 oracle calls per round	Thm 3.1
	Real-values	$\widetilde{O}\left(\sqrt{dT\sigma^{-1}}\right)$		Thm 3.1
Lower Bound	Alg-independent	$\Omega\left(\sqrt{T(d/\sigma)^{1/2}}\right)$	For any algorithm with running time $o(\sqrt{d/\sigma})$	Thm 5.1
	FTPL/Relaxation	$\Omega\left(\sqrt{dT\sigma^{-1/2}}\right)$		Thm D.1
Implications	Small-domain	$O\left(\sqrt{T(d|\mathcal{X}|)^{1/2}}\right)$	FTPL with Poissonization	Cor 3.3
	Transductive learning	$O\left(T^{3/4}d^{1/4}\right)$		Cor 3.3

Table 1: Main Results. In the above table, d represents the pseudo dimension or VC dimension of the hypothesis class $\mathcal{H}$, σ is the smoothness parameter, and T is the number of time steps.

model gracefully captures the expressivity of worst-case instances while circumventing the overly pessimistic nature of the worst-case analysis.

The question of whether offline learning algorithms can lead to online learning algorithms is naturally captured by the *oracle-efficiency* framework (e.g., [DHL+17, KV05, HK16]). In this setting, we have access to an offline learning algorithm or equivalently an *empirical risk minimization (ERM)* oracle which can compute an optimal hypothesis given any history of the actions of the adversary. Our computationally efficient online algorithms can be design to utilize polynomial number of calls to the ERM oracle.

Our main goal is to design oracle-efficient online algorithms whose regret is characterized by offline statistical complexity measures, such as the VC dimension or pseudo dimension of a hypothesis class. Interestingly, in the worst-case instances (in absence of smoothed analysis) [HK16] showed that such algorithms cannot exist. Thus, positively resolving this question will show that smoothed analysis simultaneously overcomes both statistical and computational impossibilities. This is indeed what we show by the main contributions of our work.

1.1 Main Results

We give the first oracle-efficient online learning algorithms whose regret is characterized by the statistical offline complexity measures, under smoothed analysis. In particular, we show that there are efficient algorithms, given access to an ERM oracle, that achieve sublinear regret that depends only on the pseudo- (or VC) dimension of a class of hypothesis. We summarize our main results in Table 1.

We study both the real-valued and binary valued losses. For the real-valued case, we show a regret bound of $O(\sqrt{Td\sigma^{-1}})$. We improve upon this bound for the binary classification setting achieving regret of $O(\sqrt{Td\sigma^{-1/2}})$. While these bounds demonstrate sublinear regret that only depends on d and σ^{-1}, their dependence on σ^{-1} does not match the (non-efficient) statistical regret bound of [HRS21], which gave a $\sqrt{Td\log(\sigma^{-1})}$ dependence. We further discuss this computational-statistical gap between online learning algorithms by presenting lower bounds for efficient algorithms in presence of beyond worst-case adversaries and highlight important directions for future research.

In addition to the application of our algorithms in the smoothed setting, with appropriate settings of parameters, our algorithms improve upon the regret dependence in terms of the domain size $|\mathcal{X}|$ in the worst case binary classification with regret $O(\sqrt{T(d|\mathcal{X}|)^{1/2}})$, improving upon the $O(\sqrt{T|\mathcal{X}|})$ bound of [DS16] and the regret dependence in terms of the VC dimension d in transductive binary classification to $O(T^{3/4}d^{1/4})$, improving upon the $O(T^{3/4}d^{1/2})$ bound in [KK06].

1.2 Technical Overview

Random Playout for Beyond Worst-Case Adversaries. Our algorithms are based on the random playout design principles, including the *admissible relaxation* framework of [RSS12] and the *Follow-*

the-Perturbed-Leader framework of [KV05]. We show that this framework is useful for analyzing online learning algorithms in the beyond worst-case setting, especially in smoothed analysis. In this setting, smoothness captures a level of predictability about the future. This is made formal by a technique from [HRS21] that shows that any sequence of T instances generated by adaptive smoothed adversaries can be seen as a subset of T/σ uniformly random instances from $\mathcal{X}$ with high probability. We implement this algorithmically by self-generating random instances and labels as a stand-in for the future. While the self-generated samples may not include adversary's next choice with some probability, these frameworks can be used to account for the uncertainty in each step. Furthermore, we show that the inclusion of additional self-generated samples has a small impact on the achievable regret by proving that the *regularized Rademacher complexity* (which acts as an admissible relaxation) is monotone in the set of generated samples (Lemma 4.1). This monotonicity property leads to regret bounds that gracefully degrade as a small function of $1/\sigma$.

Stability, Poissonization and Generalization. To obtain even stronger regret bounds for the binary setting, our analysis builds on the notion of *stability*, i.e., how little the distribution of learner's actions changes across time steps. A crucial ingredient in controlling stability is our novel Poissonization technique that randomly sets the *number of* samples to be self-generated from an appropriately chosen Poisson distribution. This allows us an additional degree of independence that is essential for controlling the loss from one step to the next using information theoretic techniques.

The stability analysis of the algorithm also depends crucially on a *modified generalization error* of the ERM, when it is trained on uniformly generated training samples and tested on smoothly distributed fresh instances. To bound this, we show a strong conditional independence property satisfied by the coupling from [HRS21]. This is instrumental for bounding the generalization error by allowing us to extract smooth variables from a set of uniform variables, which can then be used for symmetrization. We expect that this approach will be of independent interest for future work.

1.3 Related works

Our work relates to several paradigms and approaches to online learnability.

Oracle-Efficient Online Learning. Since the seminal work of [KV05], inspired by application domains such as game theory, there has been a long line of work elucidating the computational aspects of online learning. [KV05] proposed the influential follow-the-perturbed-leader algorithm. [KKL07] study notions of regret when the learner is given access to an approximate optimization oracle. [KK06] study the transductive learning setting and give an efficient algorithm that converts offline learnablity to online learnability. [RSS12] propose a general *admissible relaxation* framework to develop efficient algorithms based on the upper bound of the value of the game. [DHL$^+$17] present the computationally efficient Generalized-FTPL algorithm and provide conditions under which it achieves vanishing regret. On the flip size, [HK16] show that an $\Omega(\sqrt{N})$ lower bound is unavoidable in general in order to obtain nontrivial regret where the N is the number of actions of the learner suggesting that one needs to look beyond the worst-case in order to get truly efficient algorithms.

Beyond Worst-case Approaches to Online Learning. Various notion of beyond worst-case behavior of online learning has been studied in the literature [RST11, HRS20, RS13b, DFHJ17, BCKP20]. Most closely related are [RST11, HRS20, HRS21]. [RST11] studied smoothed analysis of online learning but only gave explicit regret bounds for simple classes such as thresholds. [HRS20, HRS21] both study the notion of smoothed analysis with adaptive adversary and show that statistically the regret is bounded by $O(\sqrt{Td\log(1/\sigma)})$ but do not provide efficient algorithms.

Concurrent Work. In a concurrent and independent work, [BDGR22] also gives oracle-efficient algorithms for smoothed online learning. In the binary classification setting, [BDGR22] obtains a regret bound of $\widetilde{O}(\sqrt{Td\sigma^{-1}})$ using an FTPL-based algorithm. In comparison, our result (Theorem 3.2) demonstrates a regret bound of $\widetilde{O}(\sqrt{Td\sigma^{-\frac{1}{2}}})$ with strictly better dependence on σ. Our regret bound's improved dependence on parameter σ can be attributed to our novel technical innovations, including the introduction and careful analysis of *modified generalization error* and *stability* via a new coupling-based argument, and a Poissonization approach for *self-generating* samples that can leverage information theoretic arguments. For the case of real-valued functions with pseudo

dimension d, [BDGR22] achieve regret $\widetilde{O}(\sigma^{-1}\sqrt{Td})$ with $\widetilde{O}(\sqrt{T})$ calls to the oracle per round. In our paper, we obtain better regret of order $\widetilde{O}(\sqrt{Td\sigma^{-1}})$ using only 2 oracle calls per round [2]. Our stronger regret bounds are due to the fact that their algorithm is constrained to self-generating T-long sequences as a stand-in for the future, while we are generating substantially longer sequences that allow us to leverage the monotonicity of Rademacher complexity.

2 Preliminaries

2.1 Smoothed Online Learning

Let $\mathcal{X}$ be the space of instances, $\mathcal{Y} = [-1, 1]$ be the space of labels, and $\mathcal{H} : \mathcal{X} \to \mathcal{Y}$ be the hypothesis class with pseudo dimension d (See definition B.1 or [AB99] for the definition of pseudo dimension). Let $l : \mathcal{Y} \times \mathcal{Y} \to [0, 1]$ be a convex loss function with Lipschitz constant G in its first component. We also consider the special case where $\mathcal{Y} = \{-1, +1\}$ is binary and the hypothesis class $\mathcal{H}$ has VC dimension d. In this case, we consider the classification loss $l(\widehat{y}, y) = \mathbf{1}\{\widehat{y} \neq y\}$.

We work with the smoothed adaptive online adversarial setting from [HRS21]. We will consider σ-smooth adversaries, where a distribution is σ-smooth if its density is upper bounded by $1/\sigma$ times the density of the uniform distribution over the same domain. We remark that all of our results generalize to arbitrary known base distributions as well.

Definition 2.1 (σ-smoothness)**.** *Let $\mathcal{X}$ be a domain that supports a uniform distribution $\mathcal{U}$. A measure μ on $\mathcal{X}$ is σ-smooth if for all measurable subsets $A \subseteq \mathcal{X}$, $\mu(A) \leq \frac{\mathcal{U}(A)}{\sigma}$. The set of all σ-smooth distributions on domain $\mathcal{X}$ is denoted by $\Delta_\sigma(\mathcal{X})$.*

In online learning with adaptive smoothed adversaries, the learner and the adversary plays a repeated game for T time steps. At each time step $t \in [T]$, the adversary chooses a σ-smooth distribution $\mathcal{D}_t^{\mathcal{X}} \in \Delta(\mathcal{X})$. A random instance $x_t \sim \mathcal{D}_t^{\mathcal{X}}$ is then drawn and presented to the learner. After receiving x_t, the learner predicts its label to be $\widehat{y}_t \in \mathcal{Y}$, while the adversary simultaneously chooses $y_t \in \mathcal{Y}$ as its true label. The learner then suffers loss $l(\widehat{y}_t, y_t)$. The above protocol is equivalent to a setting where the adversary chooses a distribution $\mathcal{D}_t \in \Delta(\mathcal{X} \times \mathcal{Y})$ over labeled instances $s_t = (x_t, y_t)$ whose marginal on $\mathcal{X}$ is σ-smooth, and the learner simultaneously chooses a classifier $h_t \in \mathcal{Y}^{\mathcal{X}}$. It is not hard to see that this equivalence holds for both randomized and deterministic interactions, see [RS14, Section 7.6] for a more detailed discussion. We will abbreviate $\mathcal{D}_t^{\mathcal{X}}$ to $\mathcal{D}_t$ when it is clear from the context.

We allow the adversary to be adaptive, i.e., the choice of $\mathcal{D}_t$ can depend on the realization of previous instances $\{(x_i, y_i)\}_{i=1}^{t-1}$ as well as the learner's previous predictions. We denote with $\mathscr{D}_\sigma$ the adaptive sequence of σ-smooth distributions $\mathcal{D}_1, \cdots, \mathcal{D}_T$ on the instances. Accordingly, let $\mathcal{Q}_t \in \Delta(\mathcal{Y})$ denote the learner's prediction rule on instance x_t, and let $\mathscr{Q}$ denote the adaptive sequence of distributions $\mathcal{Q}_1, \cdots, \mathcal{Q}_T$. We denote the expected regret of a learner with prediction rules $\mathscr{Q}$ on the adaptive sequence $\mathscr{D}_\sigma$ by

$$\mathbb{E}[\text{REGRET}(T, \mathscr{D}, \mathscr{Q}_\sigma)] = \mathop{\mathbb{E}}_{\mathscr{D}_\sigma, \mathscr{Q}} \left[\sum_{t=1}^T l(\widehat{y}_t, y_t) - \inf_{h \in \mathcal{H}} \sum_{t=1}^T l(h(x_t), y_t) \right].$$

We remove $\mathscr{D}_\sigma$ and $\mathscr{Q}$ from this notation when they are clear from the context.

An important property of smoothness is that it implies coupling between uniform and adaptive smooth processes. We will consider the original result from [HRS21] in Lemma B.1 and a slightly strengthened statement in Lemma C.6.

2.2 Offline Optimization Oracle

We consider computationally efficient algorithms given access to an offline optimization oracle. For the case of binary classification, the oracle outputs the solution of empirical risk minimization on the input data.

Definition 2.2 (ERM Oracle)**.** *For a hypothesis class $\mathcal{H}$ and a loss function l, the oracle OPT (opt) takes a set [3] of inputs $S = \{(x_i, y_i)\}_{i \in [I]}$ where $(x_i, y_i) \in \mathcal{X} \times \mathcal{Y}$ for all $i \in [I]$ and returns*

---

[2] Subsequent to when the first versions of both papers were made available online, [BDGR22] improved their relaxation technique and now demonstrate the same regret bound as ours, while still using more oracle calls.

[3] The inputs to the oracle are multisets. Unless specified otherwise, all the sets in this paper refer to multisets.

$$\mathsf{OPT}_{\mathcal{H},l}(S) = \min_{h \in \mathcal{H}} \sum_{i=1}^{I} l(h(x_i), y_i) \;\; and \;\; \mathsf{opt}_{\mathcal{H},l}(S) \in \arg\min_{h \in \mathcal{H}} \sum_{i=1}^{I} l(h(x_i), y_i).$$

For the case of real-valued functions, we consider an oracle that can minimize a mixture of binary and real-valued loss values defined below.

Definition 2.3 (Real-valued optimization oracle). *For a hypothesis class $\mathcal{H}$ and two loss functions l^r and l^b, the oracle OPT takes two sets of inputs S and S' over $\mathcal{X} \times \mathcal{Y}$ and returns*

$$\mathsf{OPT}_{\mathcal{H},l^r,l^b}(S; S') = \min_{h \in \mathcal{H}} \Big(\sum_{(x,y) \in S} l^r(h(x), y) + \sum_{(x',y') \in S'} l^b(h(x'), y') \Big).$$

We remark that these oracles are used in most previous works, including [RSS12]. They constitute a special form of regularized loss minimization oracles, where the regularization is given directly by a random process. For the binary setting where $\mathcal{Y} = \{\pm 1\}$ and $l^r = l^b = \mathbf{1}\{\widehat{y} \neq y\}$, the above optimization oracle is equivalent to ERM oracles.

We consider each call to the offline optimization oracle as having unit cost plus the additional runtime needed for creating and inputting the set of inputs that is linear in the length of the said histories. We note that our approach and results directly extend to using ERM oracles with (arbitrarily small) additive approximation error, such as those guaranteed by FPTAS optimization algorithms, using standard techniques presented by [DHL+17, Section 6].

3 Oracle-Efficient Online Learning

3.1 Learning with Real-Valued Functions

In this section, we propose an oracle-efficient algorithm for real-valued functions with regret $\widetilde{O}(\sqrt{dT/\sigma})$. We consider the optimization oracle defined in Definition 2.3 with the loss functions specified by $l^r(\hat{y}, y) = \frac{1}{2G} l(\hat{y}, y)$ and $l^b(\hat{y}, y) = \mathbf{1}\{\widehat{y} \neq y\} - \frac{1}{2}$.

We begin by describing our algorithm. At each time step $t \in [T]$, the algorithm draws $\widetilde{O}\left(\frac{T-t}{\sigma}\right)$ fresh new instances from the uniform distribution, denoted with $V^{(t)}$, together with their random labels $\mathcal{E}^{(t)}$ that are drawn i.i.d. from the Rademacher distribution, and treat them as hints for the future. Let $S^{(t)}$ denote the set of labeled instances $(V^{(t)}, \mathcal{E}^{(t)})$. Our algorithm then applies the offline optimization oracle to two input sequences: one where the real history $s_{1:t-1}$ is mixed with two copies[4] of $S^{(t)}$ and the current instance is labeled $+1$, and another, where the current label is labeled -1. Formally, we consider

$$\widehat{y}_t = \mathsf{OPT}\left(s_{1:t-1}; S^{(t)} \cup S^{(t)} \cup \{(x_t, -1)\}\right) - \mathsf{OPT}\left(s_{1:t-1}; S^{(t)} \cup S^{(t)} \cup \{(x_t, +1)\}\right). \quad (1)$$

Since the two input sequences to the optimization oracle only disagree on one label, the difference in the optimal errors is always bounded within $[-1, +1]$, thus guarantees $\widehat{y}_t \in \mathcal{Y}$. Intuitively, the reason $\widehat{y}_t$ includes the gap between the error of these two optimal classifiers is to make the algorithm hedge its bets against which instances will be generated by the adversary next. A formal description of the algorithm is given in Algorithm 1.

The main motivation for the algorithm is the coupling lemma from [HRS21]. It states that a sample from any σ-smooth distribution can be thought of as generated by first sampling $O\left(\sigma^{-1}\right)$ samples from the uniform distribution and then selecting one of them as the sample. The algorithm thus can be thought of as generating samples from the uniform distribution to account for the uncertainty in the choice of the adversary. We will discuss this intuition and sketch a proof of the following theorem in Section 4.3.

Theorem 3.1 (Regret Upper Bound). *For any σ-smooth adversary $\mathscr{D}_\sigma$, Algorithm 1 has expected regret upper bounded by $\widetilde{O}(G\sqrt{Td/\sigma})$, where $\widetilde{O}$ hides factors that are polynomial in $\log(T)$ and $\log(1/\sigma)$. Here G is the Lipschitz constant of the loss and d is the pseudodimension of the class. Furthermore, the algorithm is oracle-efficient: at every round t, this algorithm uses two oracle calls with histories of length $\widetilde{O}(T/\sigma)$.*

---

[4]We use two copies to scale the loss appropriately.

Algorithm 1: Oracle-Efficient Smoothed Online Learning for Real-valued Functions

---

Input: T, σ

1 $K \leftarrow 100 \log T/\sigma$.

2 for $t \leftarrow 1$ **to** T **do**

3 $\quad$ Receive x_t.

4 $\quad$ **for** $i = t+1, \cdots, T; k = 1, \cdots, K$ **do**

5 $\quad\quad$ Draw new $v_{i,k}^{(t)} \sim \mathcal{U}(\mathcal{X})$.

6 $\quad\quad$ Draw new $\epsilon_{i,k}^{(t)} \sim \mathcal{U}(\{-1, +1\})$.

7 $\quad$ **end**

8 $\quad S^{(t)} \leftarrow \left\{ (v_{i,k}^{(t)}, \epsilon_{i,k}^{(t)}) \right\}_{\substack{i=t+1:T \\ k=1:K}}$.

9 $\quad \widehat{y}_t \leftarrow \mathsf{OPT}\left(s_{1:t-1}; S^{(t)} \cup S^{(t)} \cup \{(x_t, -1)\}\right) - \mathsf{OPT}\left(s_{1:t-1}; S^{(t)} \cup S^{(t)} \cup \{(x_t, +1)\}\right)$.

10 $\quad$ Receive y_t, suffer loss $l(\widehat{y}_t, y_t)$.

11 end

3.2 Improved Bounds for Binary Classification

In this section, we focus on the important special case where the labels are binary and the loss function is the classification loss $\mathbf{1}\{\widehat{y} \neq y\}$. We present Algorithm 2 that achieves regret $\widetilde{O}(\sqrt{Td\sigma^{-1/2}})$ with better dependence on the smoothness parameter σ compared to Algorithm 1.

Theorem 3.2 (Regret Bound for Efficient Smoothed Online Learning). *In the setting of binary classification with σ-smoothed adversaries, Algorithm 2 has expected regret that is at most*

$$\widetilde{O}\left(\min\left\{ \sqrt{Td\sigma^{-1/2}}, \sqrt{T(d|\mathcal{X}|)^{1/2}} \right\} \right).$$

Furthermore, Algorithm 2 is a proper *learning oracle-efficient algorithm: at every round t, this algorithm uses a single ERM oracle call on a history that is of length $t + O(T/\sqrt{\sigma})$ with high probability.*

Unlike the algorithm for the real-valued case, the improved algorithm uses the FTPL framework. The algorithm itself is easy to describe: the algorithm generates a random number N from the Poisson distribution with an appropriately chosen parameter, generates N uniformly random points along with random labels and then predicts using the hypothesis that has the lowest error on the past data appended with the newly sampled data. On the surface, this algorithm seems similar to Algorithm 1. But there are two key differences: unlike Algorithm 1 which uses the difference in value of two optimizations, Algorithm 2 follows the prediction of the hypothesis with the lowest error. This makes Algorithm 2 a proper online learning algorithm. Secondly, unlike Algorithm 1 which uses a decreasing number of random examples over time, Algorithm 2 has the number of samples distributed according to a Poisson (with the same parameter in each step). The fact that the number of hints is drawn from the Poisson distribution is crucial for our analysis of the stability of the algorithm. We sketch the proof of the regret bounds in Section 4.4.

Algorithm 2: Smoothed Online Learning based on Poisson Number of Hints

---

Input: time horizon T, smoothness parameter σ, VC dimension d

1 $n \leftarrow \min\{T/\sqrt{\sigma}, T\sqrt{|\mathcal{X}|/d}\}$;

2 for $t \leftarrow 1$ **to** T **do**

3 $\quad$ generate $N^{(t)} \sim \mathrm{Poi}(n)$ fresh hallucinated samples $(\widetilde{x}_1^{(t)}, \widetilde{y}_1^{(t)}), \cdots, (\widetilde{x}_N^{(t)}, \widetilde{y}_N^{(t)})$, which are

$\quad\quad$ i.i.d. conditioned on N with $\widetilde{x}_i^{(t)} \sim \mathcal{U}(\mathcal{X})$ and $\widetilde{y}_i^{(t)} \sim \mathcal{U}(\{\pm 1\})$;

4 $\quad$ call the ERM oracle to compute $h_t \leftarrow \mathrm{opt}_{\mathcal{H}, l}\left(\{(\widetilde{x}_i^{(t)}, \widetilde{y}_i^{(t)})\}_{i \in [N^{(t)}]} \cup \{x_\tau, y_\tau\}_{\tau \in [t-1]} \right)$;

5 $\quad$ observe x_t, predict $\widehat{y}_t = h_t(x_t)$, and receive y_t.

6 end

While our main interest is on beyond the worst-case adversaries, our results improve upon existing results for worst-case analysis of online learning as well. For finite domain and binary-valued loss settings where worst-case adversaries are vacuously σ-smooth for $1/\sigma = |\mathcal{X}|$, Theorem 3.2 also achieves an oracle-efficient regret bound of $O(\sqrt{T}(d|\mathcal{X}|)^{1/2})$, which is a refinement of $O(\sqrt{T|\mathcal{X}|})$ bound of [DS16], because VC dimension d is at most $\mathcal{X}$, and is usually much smaller. Similarly, our bound can be instantiated in the setting of transductive learning with $|\mathcal{X}| = T$, which improves $O(T^{3/4}\sqrt{d})$ bound of [KK06] to $O(T^{3/4}d^{1/4})$.

Corollary 3.3 (Regret for Small Domain). *There is an oracle-efficient algorithm for online learning with binary labels (in the worst-case) that achieves an expected regret of $O(\sqrt{T}(d|\mathcal{X}|)^{1/2})$ for any hypothesis class with VC dimension d on domain $\mathcal{X}$. For transductive learning with binary labels, there is an oracle efficient algorithm, with expected regret $O\left(T^{3/4}d^{1/4}\right)$.*

4 Proof Sketches for Main Regret Bounds

Before discussing the proof sketches for the main regret bounds, we will first introduce two frameworks for designing efficient algorithms for online learning.

4.1 Relaxations and Admissibility

The proof of Theorem 3.1 relies on the *admissible relaxation* framework proposed in [RSS12]. A relaxation $\mathbf{Rel}_T$ is a sequence of functions $\mathbf{Rel}_T(\mathcal{H}|s_{1:t})$ for each $t \in [T]$, which map the history of the play to real values that upper bounds the conditional value of the game. We will make use of an important algorithmic aspect of the relaxation framework, which states that whenever an algorithm is *admissible* with respect to some relaxation, its expected regret can be upper bounded in terms of the value of the relaxation at the beginning of the game.

Definition 4.1 (Admissibility). *In the smoothed online learning setting, let $\mathcal{Q}$ be an algorithm that gives rise to a sequence of distributions $\mathcal{Q}_1, \cdots, \mathcal{Q}_T$ on the predicted labels. We say $\mathcal{Q}$ is admissible with respect to a relaxation $\{\mathbf{Rel}_T(\mathcal{H} \mid s_{1:t})\}_{t=0}^T$, if for any sequence of instances $s_{1:T}$,*

1. For all $t \in [T]$,
$$\sup_{\mathcal{D}_t \in \Delta_\sigma(\mathcal{X})} \mathbb{E}_{x_t \sim \mathcal{D}_t} \sup_{y_t \in \mathcal{Y}} \left\{ \mathbb{E}_{\widehat{y}_t \sim \mathcal{Q}_t} [l(\widehat{y}_t, y_t)] + \mathbf{Rel}_T(\mathcal{H} \mid s_{1:t-1} \cup (x_t, y_t)) \right\} \leq \mathbf{Rel}_T(\mathcal{H} \mid s_{1:t-1}),$$

where $\Delta_\sigma(\mathcal{X})$ is the set of σ-smooth distributions on $\mathcal{X}$;

2. The final value satisfies $\mathbf{Rel}_T(\mathcal{H} \mid s_{1:T}) \geq -\inf_{h \in \mathcal{H}} L(h, s_{1:T})$.

The following proposition is the analog of the results of [RSS12] when the adversary is smooth. The full proof is presented in Appendix F.

Proposition 4.1 (Regret Bound via Admissibility). *In the smoothed online learning setting, let $\mathcal{Q} = (\mathcal{Q}_1, \cdots, \mathcal{Q}_T)$ be an algorithm that is admissible with respect to relaxations $\mathbf{Rel}_T(\mathcal{H})$, then the following bound on the expected regret holds regardless of the strategies $\mathcal{D}_\sigma$ of the adversary:*
$$\mathbb{E}[\textsc{Regret}(T, \mathcal{Q}, \mathcal{D}_\sigma)] \leq \mathbf{Rel}_T(\mathcal{H} \mid \emptyset) + O(\sqrt{T}).$$

4.2 Follow the Perturbed Leader

When the labels are binary, Algorithm 2 achieves an improved regret using the Follow the Perturbed Leader (FTPL) principle [KV05]. An FTPL algorithm makes predictions by applying ERM oracle to the perturbed histories of the play. At every time step $t \in [T]$, the algorithm chooses a distribution over labeled instances, from which it draws N random instances $(\widetilde{x}_1^{(t)}, \widetilde{y}_1^{(t)}), \cdots, (\widetilde{x}_N^{(t)}, \widetilde{y}_N^{(t)})$. The predicted label is then given by $\widehat{y}_t = h_t(x_t)$, where

$$h_t \leftarrow \mathsf{opt}_{\mathcal{H}, l} \left(s_{1:t-1} \cup \{(\widetilde{x}_i^{(t)}, \widetilde{y}_i^{(t)})\}_{i \in [N]} \right).$$

The standard analysis of FTPL bounds the expected regret as follows:

$$\mathbb{E}[\textsc{Regret}] \leq \underbrace{\mathbb{E}\left[\sum_{t=1}^T l(h_t(x_t), y_t) - l(h_{t+1}(x_t), y_t) \right]}_{\text{Stability}} + \underbrace{\mathbb{E}\left[\sup_{h \in \mathcal{H}} \sum_{i=1}^N l(h(\widetilde{x}_i), \widetilde{y}_i) - \sum_{i=1}^N l(h^*(\widetilde{x}_i), \widetilde{y}_i) \right]}_{\text{Perturbation}},$$

where $h^* = \arg\inf_{h \in \mathcal{H}} \sum_{t=1}^{T} l(h(x_t), y_t)$.

Note that the perturbation term is already well-understood from statistical learning theory since it is essentially the Rademacher complexity of $\mathcal{H}$ for sample size N. Therefore, we will focus on bounding the stability term by designing perturbations that can leverage the anti-concentration property of smoothed adversaries.

4.3 Proof Sketch of Theorem 3.1

Elaborating on the intuition laid out in Section 3, we will use the coupling technique introduced by [HRS21] (see Lemma B.1 for a complete description) to replace the sequence of T random inputs $\{x_1, \cdots, x_T\}$ generated by the adaptive adversary with TK inputs $\{z_{t,k}\}_{t \in [T], k \in [K]}$ that are generated i.i.d. from the uniform distribution over $\mathcal{X}$, such that with high probability $\{x_1, \cdots, x_T\} \subseteq \{z_{t,k}\}_{t \in [T], k \in [K]}$. This implies that, up to a small probability of failure, it is sufficient to consider a simpler setting where the adversary is promised to pick future instances from a larger set of uniformly distributed samples (which we call *the set of hints*). This setting differs from the standard transductive learning setting [KK06, CbS11] in two significant ways: 1) The set of hints is not revealed to the learner beforehand; 2) the hint set is larger, by a multiplicative factor of $K \approx 1/\sigma$, than the set of realized instances.

It turns out that both issues can be handled elegantly in the admissible relaxations framework of [RSS12]. For the first issue, note that the Algorithm 1 can be seen as self-generating hints and although they do not necessarily correspond to the adversary's sample, the relaxation-based argument guarantees that matching the randomness of hints at a distribution level suffices to bound the regret of the algorithm (see Appendix B.7 for more details). For the second issue, our relaxation will be based on a characterization of the uncertainty in the future that is *monotone* in the set of hints, which we call *regularized Rademacher complexity*. Formally, for a set of unlabeled instances $Z = \{z_i\}_{i=1}^{I}$ and a function $\Phi : \mathcal{H} \to \mathbb{R}$, the Rademacher complexity for set Z regularized by Φ is defined as

$$\mathfrak{R}(\Phi, Z) = \mathop{\mathbb{E}}_{\epsilon_{1:I} \overset{\text{iid}}{\sim} \mathcal{U}(\pm 1)} \left[\sup_{h \in \mathcal{H}} \left\{ \sum_{i \leq I} \epsilon_i h(z_i) + \Phi(h) \right\} \right].$$

We show that regularized Rademacher complexity is monotone as a function of the dataset. See Appendix B.2 for a proof of Lemma 4.1.

Lemma 4.1 (Monotonicity of Regularized Rademacher Complexity). *For any dataset $z_{1:m} \in \mathcal{X}^m$ and any additional data point $x \in \mathcal{X}$, we have $\mathfrak{R}(\Phi, z_{1:m}) \leq \mathfrak{R}(\Phi, z_{1:m} \cup \{x\})$.*

This monotonicity ensures that using the hint set, which is a superset of possible instances, will still lead to a no-regret algorithm.

Finally, the relaxation we use to analyze Algorithm 1 is the expected Rademacher complexity of the union of future hints, regularized by the past total loss, i.e.,

$$\textbf{Rel}_T(\mathcal{H} \mid s_{1:t}) = 2G \mathop{\mathbb{E}}_{V^{(t)} \overset{\text{iid}}{\sim} \mathcal{U}(\mathcal{X})} \left[\mathfrak{R}(-L^{\text{r}}(\cdot, s_{1:t}), V^{(t)}) \right] + 2G\beta(T - t),$$

where $L^{\text{r}}(h, s_{1:t}) = \sum_{i=1}^{t} l^{\text{r}}(h(x_i), y_i)$ for $h \in \mathcal{H}$. Here $\beta = 10TK(1 - \sigma)^K \in o(1/T)$ represents the penalty caused by the failure of coupling. Once admissibility is established, we will obtain a regret bound using Proposition 4.1. See Appendix B for a complete proof of the theorem. We remark that the final regret bound can also be stated in terms of the Rademacher complexity which is data dependent and adapts readily to benign structures of the instance domain.

4.4 Proof Sketch of Theorem 3.2

Let $\mathcal{Q}_t$ be the distribution of the learner's action $h_t \in \mathcal{H}$ in Algorithm 2 and $\mathcal{D}_t$ denote the distribution of the adversary at time t. The main quantity we will use to analyze the algorithm is the stability

$$\text{Stability} = \mathop{\mathbb{E}}_{s_t \sim \mathcal{D}_t} \left(\mathop{\mathbb{E}}_{h_t \sim \mathcal{Q}_t} [L(h_t, s_t)] - \mathop{\mathbb{E}}_{h_{t+1} \sim \mathcal{Q}_{t+1}} [L(h_{t+1}, s_t)] \right).$$

We analyze this expression by breaking it down into a sum of two quantities:

$$\text{Stability} \leq \text{TV}(\mathcal{Q}_t, \mathop{\mathbb{E}}_{s_t \sim \mathcal{D}_t} [\mathcal{Q}_{t+1}]) + \underbrace{\mathop{\mathbb{E}}_{s_t, s_t' \sim \mathcal{D}_t; R^{(t+1)}} [L(h_{t+1}, s_t') - L(h_{t+1}, s_t)]}_{\text{Modified generalization error}}.$$

295   Here, $R^{(t)}$ is the fresh randomness generated by the algorithm at the beginning of time t.

296   In order to see where this expression comes from, note that the first term itself would be an upper
297   bound on the stability, if neither of $\mathcal{Q}_t$ and $\mathcal{Q}_{t+1}$ depend on the new observation $s_t = (x_t, y_t)$ at time
298   t. However, while $\mathcal{Q}_t$ is independent of s_t, $\mathcal{Q}_{t+1}$ does depend on s_t because h_{t+1} is trained on s_t. To
299   overcome this dependence, we introduce a ghost sample s'_t that allows us to decouple $h_{t+1} \sim \mathcal{Q}_{t+1}$
300   and the new observation. This gives rise to the second term which we call *modified generalization*
301   *error*. We formally discuss this decomposition in Appendix C.2.

302   The first term is the total variation (TV) distance between $\mathcal{Q}_t$ and the mixture distribution
303   $\mathbb{E}_{s_t \sim \mathcal{D}_t}[\mathcal{Q}_{t+1}]$. In order to bound this term, we closely use the independence properties of the
304   Poisson distribution which allows us to write an explicit expression for the total variation distance
305   which we can then bound using the Ingster–Suslina method. We formally prove this in Lemma C.4.

306   The intuitive idea behind bounding the second term is as follows. Consider the simpler setting of
307   $t = 1$ (i.e. no history) and $\mathcal{D}_t = \mathcal{U}(\mathcal{X} \times \{\pm 1\})$ (i.e. the new observation s_t follows the same
308   distribution as the self-generated samples). In this case, the generalization error is precisely the
309   difference between the test error and the training error with $N + 1$ iid training data, and classical
310   Rademacher complexity gives an upper bound $O(\sqrt{d/N})$. For general σ-smooth $\mathcal{D}_t$, we establish a
311   strong conditional independence property of the coupling argument from [HRS21]. This states that
312   there exists a coupling between uniform and adaptive smooth processes, such that when the inclusion
313   property is satisfied, the distribution of the realized uniform variables *conditional on the unrealized*
314   *uniform variables* is also identical to the smooth distributions given by the adversary. This will be
315   instrumental for bounding the generalization error by allowing us to extract smooth variables from a
316   set of uniform variables, which can then be used to for the purpose of symmetrization. We formally
317   prove the upper bound on the modified generalization in Lemma C.5.

318   Using this bound on stability, we can get a bound on the regret of the algorithm using analysis
319   techniques for FTPL. For a full proof, see Appendix C.

320   **Remark 1.** *The proof for the modified generalization needs the smoothness of both the covariates x*
321   *and labels y. This can be ensured with a loss of a constant in the binary (and generally the finite label*
322   *space) setting. This is the main reason that this proof does not generalize to the real valued setting.*

5   Discussion, Additional Results, and Open Problems

324   **Computational Lower Bounds.** Our main contribution is oracle-efficient online learning algo-
325   rithms in the smoothed setting that achieve an $O(\sqrt{dT\sigma^{-1}})$ regret upper bound in the real-valued
326   case, and an $O(\sqrt{dT\sigma^{-1/2}})$ upper bound for binary classification. However, neither of these upper
327   bounds is statistically optimal; the statistically optimal regret here is $\widetilde{\Theta}(\sqrt{dT\log(1/\sigma)})$ [HRS21].
328   We ask the following question: is the above discrepancy an artifact of our regret analysis, or an
329   intrinsic limitation of our or all oracle-efficient algorithms.

330   We show in Theorem D.1 that the regret of our current family of algorithms cannot be improved by
331   tuning parameters. In addition, we also show the following general lower bound for computationally
332   efficient algorithms. See Appendix D for the proofs and more details.

333   **Theorem 5.1** (Computational Lower Bound for Smoothed Online Learning)**.** *For $1/\sigma \geq$*
334   *d, any proper algorithm which only has access to the ERM oracle and achieves a regret*
335   *$o(\min\{T, \sqrt{T(d/\sigma)^{1/2}}\})$ for any σ-smoothed online learning problem must have an $\omega(\sqrt{d/\sigma})$*
336   *total running time. Here, the total running time refers to the total number of operations performed by*
337   *our algorithm, in which each oracle call takes unit time, and maintaining each element in the input to*
338   *the oracle also takes unit time.*

339   Theorem 5.1 implies an exponential statistical-computational gap in smoothed online learning: for
340   exponentially small σ, achieving the statistical regret $\widetilde{O}(\sqrt{Td\log(1/\sigma)})$ requires an exponential
341   running time. However, Theorem 5.1 still exhibits gaps to our computational upper bounds. We
342   discuss this further in the appendix and present the following open problem.

343   **Open Question.** *For $d/\sigma \gg T^2$ in the smoothed setting, does any algorithm achieving $o(T)$ regret*
344   *require $\Omega(\mathrm{poly}(T, 2^d, 1/\sigma))$ computational time given access to the ERM oracle?*

References

[AB99]   Martin Anthony and Peter L Bartlett. *Neural network learning: Theoretical foundations*, volume 9. cambridge university press Cambridge, 1999.

[Bar06]   Peter Bartlett. Lecture notes in statistical learning theory, Spring 2006.

[BCKP20]   Aditya Bhaskara, Ashok Cutkosky, Ravi Kumar, and Manish Purohit. Online learning with imperfect hints. In *International Conference on Machine Learning*, pages 822–831. PMLR, 2020.

[BDGR22]   Adam Block, Yuval Dagan, Noah Golowich, and Alexander Rakhlin. Smoothed online learning is as easy as statistical learning. *arXiv preprint arXiv:2202.04690*, 2022.

[BDPSS09]   Shai Ben-David, Dávid Pál, and Shai Shalev-Shwartz. Agnostic online learning. In *Proceedings of the 22nd Annual Conference on Learning Theory (COLT)*, 2009.

[BKP97]   Peter L Bartlett, Sanjeev R Kulkarni, and S Eli Posner. Covering numbers for real-valued function classes. *IEEE transactions on information theory*, 43(5):1721–1724, 1997.

[CAK17]   Vincent Cohen-Addad and Varun Kanade. Online Optimization of Smoothed Piecewise Constant Functions. In *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics (AISTATS)*, pages 412–420, 2017.

[CbS11]   Nicolò Cesa-bianchi and Ohad Shamir. Efficient online learning via randomized rounding. *Advances in Neural Information Processing Systems*, 24:343–351, 2011.

[DFHJ17]   Ofer Dekel, Arthur Flajolet, Nika Haghtalab, and Patrick Jaillet. Online learning with a hint. In *Advances in Neural Information Processing Systems (NeurIPS) 30*, pages 5299–5308. 2017.

[DHL$^+$17]   Miroslav Dudík, Nika Haghtalab, Hiapeng Luo, Robert Schapire, Vassilis Syrgkanis, and Jennifer Wortman Vaughan. Oracle-efficient online learning and auction design. In *Proceedings of the 58th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 528–539, 2017.

[DS16]   Constantinos Daskalakis and Vasilis Syrgkanis. Learning in auctions: Regret is hard, envy is easy. In *2016 ieee 57th annual symposium on foundations of computer science (focs)*, pages 219–228. IEEE, 2016.

[GK06]   Evarist Giné and Vladimir Koltchinskii. Concentration inequalities and asymptotic results for ratio type empirical processes. *The Annals of Probability*, 34(3):1143–1216, 2006.

[GR17]   Rishi Gupta and Tim Roughgarden. A PAC approach to application-specific algorithm selection. *SIAM Journal on Computing*, 46(3):992–1017, 2017.

[HK10]   Elad Hazan and Satyen Kale. Extracting certainty from uncertainty: Regret bounded by variation in costs. *Machine learning*, 80(2):165–188, 2010.

[HK16]   Elad Hazan and Tomer Koren. The computational power of optimization in online learning. In *Proceedings of the 48th Annual ACM Symposium on Theory of Computing (STOC)*, page 128–141, 2016.

[HM07]   Elad Hazan and Nimrod Megiddo. Online learning with prior knowledge. In *International Conference on Computational Learning Theory*, pages 499–513. Springer, 2007.

[HRS20]   Nika Haghtalab, Tim Roughgarden, and Abhishek Shetty. Smoothed analysis of online and differentially private learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[HRS21]   Nika Haghtalab, Tim Roughgarden, and Abhishek Shetty. Smoothed analysis with adaptive adversaries. *arXiv preprint arXiv:2102.08446*, 2021.

[IS03]   Yuri I. Ingster and Irina A. Suslina. *Nonparametric goodness-of-fit testing under Gaussian models*, volume 169. Springer Science & Business Media, 2003.

[KAH+19]   Akshay Krishnamurthy, Alekh Agarwal, Tzu-Kuo Huang, Hal Daumé III, and John Langford. Active learning for cost-sensitive classification. *J. Mach. Learn. Res.*, 20:65:1–65:50, 2019.

[KK06]   Sham Kakade and Adam Tauman Kalai. From batch to transductive online learning. In Y. Weiss, B. Schölkopf, and J. Platt, editors, *Advances in Neural Information Processing Systems*, volume 18. MIT Press, 2006.

[KKL07]   Sham M. Kakade, Adam Tauman Kalai, and Katrina Ligett. Playing games with approximation algorithms. In *Proceedings of the Thirty-Ninth Annual ACM Symposium on Theory of Computing*, STOC '07, page 546–555, New York, NY, USA, 2007. Association for Computing Machinery.

[KMR+18]   Sampath Kannan, Jamie H Morgenstern, Aaron Roth, Bo Waggoner, and Zhiwei Steven Wu. A smoothed analysis of the greedy algorithm for the linear contextual bandit problem. In *Advances in Neural Information Processing Systems (NeurIPS) 31*, pages 2227–2236. 2018.

[KV05]   Adam Tauman Kalai and Santosh Vempala. Efficient algorithms for online decision problems. *Journal of Computer and System Sciences*, 71(3):291 – 307, 2005.

[MY16]   Mehryar Mohri and Scott Yang. Accelerating online convex optimization via adaptive prediction. In *Artificial Intelligence and Statistics*, pages 848–856. PMLR, 2016.

[RS13a]   Alexander Rakhlin and Karthik Sridharan. Online learning with predictable sequences. In *Conference on Learning Theory*, pages 993–1019. PMLR, 2013.

[RS13b]   Alexander Rakhlin and Karthik Sridharan. Optimization, learning, and games with predictable sequences. In *Advances in Neural Information Processing Systems (NeurIPS) 26*, pages 3066–3074. 2013.

[RS14]   Alexander Rakhlin and Karthik Sridharan. Statistical learning and sequential prediction, September 2014.

[RSS12]   Alexander Rakhlin, Ohad Shamir, and Karthik Sridharan. Relax and randomize: From value to algorithms. In *Proceedings of the 25th International Conference on Neural Information Processing Systems - Volume 2*, NIPS'12, page 2141–2149, Red Hook, NY, USA, 2012. Curran Associates Inc.

[RST11]   Alexander Rakhlin, Karthik Sridharan, and Ambuj Tewari. Online learning: Stochastic, constrained, and smoothed adversaries. In *Advances in Neural Information Processing Systems (NeurIPS) 24*, pages 1764–1772. 2011.

[RSWW18]   Manish Raghavan, Aleksandrs Slivkins, Jennifer Vaughan Wortman, and Zhiwei Steven Wu. The externalities of exploration and how data diversity helps exploitation. In *Proceedings of the 31st Conference On Learning Theory (COLT)*, pages 1724–1738, 2018.

[SL14]   Jacob Steinhardt and Percy Liang. Adaptivity and optimism: An improved exponentiated gradient algorithm. In *International Conference on Machine Learning*, pages 1593–1601. PMLR, 2014.

[ST04]   Daniel A. Spielman and Shang-Hua Teng. Smoothed analysis of algorithms: Why the simplex algorithm usually takes polynomial time. *Journal of the ACM*, 51(3):385–463, May 2004.

[Tsy09]   A. Tsybakov. *Introduction to Nonparametric Estimation*. Springer-Verlag, 2009.

6 Check List