Zeroth-Order Negative Curvature Finding: Escaping Saddle Points without Gradients

Abstract

We consider escaping saddle points of nonconvex problems where only the function evaluations can be accessed. Although a variety of works have been proposed, the majority of them require either second or first-order information, and only a few of them have exploited zeroth-order methods, particularly the technique of negative curvature finding with zeroth-order methods which has been proven to be the most efficient method for escaping saddle points. To fill this gap, in this paper, we propose two zeroth-order negative curvature finding frameworks that can replace Hessian-vector product computations without increasing the iteration complexity. We apply the proposed frameworks to ZO-GD, ZO-SGD, ZO-SCSG, ZO-SPIDER and prove that these ZO algorithms can converge to (ϵ, δ)-approximate second-order stationary points with less query complexity compared with prior zeroth-order works for finding local minima.

1 Introduction

Nonconvex optimization has received wide attention in recent years due to its popularity in modern machine learning (ML) and deep learning (DL) tasks. Specifically, in this paper, we study the following unconstrained optimization problem:

$$\min_{x \in \mathbb{R}^d} f(x) := \frac{1}{n} \sum_{i=1}^{n} f_i(x), \tag{1}$$

where both $f_i(\cdot)$ and $f(\cdot)$ can be nonconvex. In general, finding the global optima of nonconvex functions is NP-hard. Fortunately, finding local optima is an alternative because it has been shown in theory and practice that local optima have comparable performance capabilities to global optima in many machine learning problems [13, 14, 25, 16, 15, 18, 26]. Gradient-based methods have been shown to be able to find an ϵ-approximate first-order stationary point ($\|\nabla f(x)\| \leq \epsilon$) efficiently, both in the deterministic setting (*e.g.*, gradient descent [31]; accelerated gradient descent [8, 28]) and stochastic setting (*e.g.*, stochastic gradient descent [31, 36]; SCSG [27]; SPIDER [12]). However, in nonconvex settings, first-order stationary points can be local minima, global minima, or even saddle points. Converging to saddle points will lead to highly suboptimal solutions [19, 38] and destroy the model's performance. Thus, escaping saddle points has recently become an important research topic in nonconvex optimization.

Several classical results have shown that using the second-order information like computing the Hessian [32] or Hessian-vector products [1, 9, 2], one can find an ϵ-approximate second-order stationary point (SOSP, $\|\nabla f(x)\| \leq \epsilon$ and $\nabla^2 f(x) \succeq -\sqrt{\rho\epsilon}\mathbf{I}$). However, when the dimension of x is large, even once access to the Hessian is computationally infeasible. A recent line of work shows that, by adding uniform random perturbations, first-order (FO) methods can efficiently escape saddle points and converge to SOSP. In the deterministic setting, [21] proposed the perturbed gradient

34 descent (PGD) algorithm with gradient query complexity $\tilde{\mathcal{O}}(\log^4 d/\epsilon^2)$ by adding uniform random
35 perturbation into the standard gradient descent algorithm. This complexity is later improved to
36 $\tilde{\mathcal{O}}(\log^6 d/\epsilon^{1.75})$ by the perturbed accelerated gradient descent [23] which replaces the gradient
37 descent step in PGD by Nesterov's accelerated gradient descent.

Table 1: A summary of the results of finding (ϵ, δ)-approximate SOSPs (see Definition 2) by the zeroth-order algorithms. (CoordGE, GaussGE, and RandGE are abbreviations of "coordinate-wise gradient estimator", "Gaussian random gradient estimator" and "uniform random gradient estimator", respectively. RP, RS, and CR are abbreviations of "random perturbation", "random search" and "cubic regularization", respectively.)

Algorithm	Setting	ZO Oracle	Main Techniques	Function Queries
ZPSGD [22]	Deterministic	GaussGE + Noise	RP	$\tilde{\mathcal{O}}\left(\frac{d^2}{\epsilon^5}\right)$ †
PAGD [40]	Deterministic	CoordGE	RP	$\mathcal{O}\left(\frac{d\log^4 d}{\epsilon^2}\right)$ †
RSPI [29]	Deterministic	CoordGE	RS + NCF	$\mathcal{O}(\frac{d\log d}{\epsilon^{8/3}})$ ‡
Theorem. 4	Deterministic	CoordGE	NCF	$\mathcal{O}\left(\frac{d}{\epsilon^2} + \frac{d\log d}{\delta^{3.5}}\right)$
ZO-SCRN [5]	Stochastic	GaussGE	CR	$\tilde{\mathcal{O}}\left(\frac{d}{\epsilon^{3.5}} + \frac{d^4}{\epsilon^{2.5}}\right)$ †
Theorem. 3	Stochastic	CoordGE	NCF	$\tilde{\mathcal{O}}\left(\frac{d}{\epsilon^4} + \frac{d}{\epsilon^2\delta^3} + \frac{d}{\delta^5}\right)$
Theorem. 5	Stochastic	CoordGE + (RandGE)	NCF	$\tilde{\mathcal{O}}\left(\frac{d}{\epsilon^{10/3}} + \frac{d}{\epsilon^2\delta^3} + \frac{d}{\delta^5}\right)$
Theorem. 6	Stochastic	CoordGE	NCF	$\tilde{\mathcal{O}}\left(\frac{d}{\epsilon^3} + \frac{d}{\epsilon^2\delta^2} + \frac{d}{\delta^5}\right)$

† guarantees $(\epsilon, \mathcal{O}(\sqrt{\epsilon}))$-approximate SOSP, and ‡ guarantees $(\epsilon, \epsilon^{2/3})$-approximate SOSP.

38 Another line of work for escaping saddle points is to utilize the negative curvature finding (NCF),
39 which can be combined with ϵ-approximate first-order stationary point (FOSP) finding algorithms
40 to find an (ϵ, δ)-approximate SOSP. The main task of NCF is to calculate the approximate smallest
41 eigenvector of the Hessian for a given point. Classical methods for solving NCF like the power
42 method and Oja's method need the computation of Hessian-vector products. Based on the fact the
43 Hessian-vector product can be approximated by the finite difference between two gradients, [41, 4]
44 proposed the FO NCF frameworks Neon+ and Neon2, respectively. In general, adding perturbations
45 in the negative curvature direction can escape saddle points more efficiently than adding random
46 perturbations by a factor of $\tilde{\mathcal{O}}(\text{poly}(\log d))$ in theory. Specifically, in the deterministic setting,
47 CDHS [9] combined with Neon2 can find an (ϵ, δ)-approximate SOSP in gradient query complexity
48 $\tilde{\mathcal{O}}(\log d/\epsilon^{1.75})$. Recently, the same result was achieved by a simple single-loop algorithm [43], which
49 combined the techniques of perturbed accelerated gradient descent and accelerated negative curvature
50 finding. In the online stochastic setting, the best gradient query complexity result $\tilde{\mathcal{O}}(1/\epsilon^3)$ is achieved
51 by SPIDER-SFO$^+$ [12], which combined the near-optimal ϵ-approximate FOSP finding algorithm
52 SPIDER and the NCF framework Neon2 to find an (ϵ, δ)-approximate SOSP.

53 However, the gradient information is not always accessible. Many machine learning and deep learning
54 applications often encounter situations where the calculation of explicit gradients is expensive or
55 even infeasible, such as black-box adversarial attack on deep neural networks [35, 30, 10, 6, 39] and
56 policy search in reinforcement learning [37, 11, 24]. Thus, zeroth-order (ZO) optimization, which
57 uses function values to estimate the explicit gradients as an important gradient-based black-box
58 method, is one of the best options for solving this type of ML/DL problem. A considerable body
59 of work has shown that ZO algorithms based on gradient estimation have comparable convergence
60 rates to their gradient-based counterparts. Although many gradient estimation-based ZO algorithms
61 have been proposed in recent years, most of them focus on the performance of converging to FOSPs
62 [33, 17, 20, 12], and only a few of them on SOSPs [22, 40, 29, 5].

63 As mentioned above, although there have been several works of finding local minima via ZO
64 methods, they utilized the techniques of random perturbations [22, 40], random search [29], and
65 cubic regularization [5], as shown in Table 1, which are not the most efficient ones of escaping saddle
66 points as discussed before. Specifically, in the deterministic setting, [22] proposed the ZO perturbed
67 stochastic gradient (ZPSGD) method, which uses a batch of Gaussian smoothing based stochastic ZO
68 gradient estimators and adds a random perturbation in each iteration. As a result, ZPSGD can find an
69 ϵ-approximate SOSP using $\tilde{\mathcal{O}}\left(d^2/\epsilon^5\right)$ function queries. [40] proposed the perturbed approximate

gradient descent (PAGD) method which iteratively conducts the gradient descent steps by utilizing the forward difference version of the coordinate-wise gradient estimators until it reaches a point with a small gradient. Then, PAGD adds a uniform perturbation and continues the gradient descent steps. The total function queries of PAGD to find an ϵ-approximate SOSP is $\tilde{\mathcal{O}}\left(d\log^4 d/\epsilon^2\right)$. Recently, [29] proposed the random search power iteration (RSPI) method, which alternately performs random search steps and power iteration steps. The power iteration step contains an inexact power iteration subroutine using only the ZO oracle to conduct the NCF, and the core idea is to use a finite difference approach to approximate the Hessian-vector product. In the stochastic setting, [5] proposed a zeroth-order stochastic cubic regularization newton (ZO-SCRN) method with function query complexity $\tilde{\mathcal{O}}\left(d/\epsilon^{7/2}\right)$ using Gaussian sampling-based gradient estimator and Hessian estimator. Unfortunately, each iteration of ZO-SCRN needs to solve a cubic minimization subproblem, which does not have a closed-form solution. Typically, inexact solvers for solving the cubic minimization subproblem need additional computations of the Hessian-vector product [1] or the gradient [7].

Thus, it is then natural to explore faster ZO negative curvature finding based algorithms to make escaping saddle points more efficient. To the best of our knowledge, negative curvature finding algorithms with access only to ZO oracle is still a vacancy in the stochastic setting. Inspired by the fact that the gradient can be approximated by the finite difference of function queries with high accuracy, a natural question is: *Can we turn FO NCF methods (especially the state-of-the-art Neon2) into ZO methods without increasing the iteration complexity and turn ZO algorithms of finding FOSPs into the ones of finding SOSPs?*

Contributions. We summarize our main contributions as follows:

- We give an affirmative answer to the above question. We propose two ZO negative curvature finding frameworks, which use only function queries and can detect whether there is a negative curvature direction at a given point x on a smooth, Hessian-Lipschitz function $f : \mathbb{R}^d \to \mathbb{R}$ in offline deterministic and online stochastic settings, respectively.

- We apply the proposed frameworks to four ZO algorithms and prove that these ZO algorithms can converge to (ϵ, δ)-approximate SOSPs, which are ZO-GD, ZO-SGD, ZO-SCSG, and ZO-SPIDER.

- In the deterministic setting, compared with the classical setting where $\delta = \mathcal{O}(\sqrt{\epsilon})$ [21, 23, 22, 40], or the special case $\delta = \epsilon^{2/3}$ [29], our Theorem 4 is always not worse than other algorithms in Table 1. In the online stochastic setting, all of our algorithms don't need to solve the cubic subproblem as in ZO-SCRN and our Theorem 6 improves the best function query complexity by a factor of $\tilde{\mathcal{O}}(1/\sqrt{\epsilon})$.

2 Preliminaries

Throughout this paper, we use $\|\cdot\|$ to denote the Euclidean norm of a vector and the spectral norm of a matrix. We use $\tilde{\mathcal{O}}(\cdot)$ to hide the poly-logarithmic terms. For a given set $\mathcal{S}$ drawn from $[n] := \{1, 2, \ldots, n\}$, define $f_{\mathcal{S}}(\cdot) := \frac{1}{|\mathcal{S}|}\sum_{i \in \mathcal{S}} f_i(\cdot)$.

Definition 1. *For a twice differentiable nonconvex function $f\colon \mathbb{R}^d \to \mathbb{R}$,*

- *f is ℓ-Lipschitz smooth if $\forall x, y \in \mathbb{R}^d$, $\|\nabla f(x) - \nabla f(y)\| \leq \ell\|x - y\|$.*
- *f is ρ-Hessian Lipschitz if $\forall x, y \in \mathbb{R}^d$, $\|\nabla^2 f(x) - \nabla^2 f(y)\| \leq \rho\|x - y\|$.*

Definition 2. *For a twice differentiable nonconvex function $f\colon \mathbb{R}^d \to \mathbb{R}$, we say*

- *$x \in \mathbb{R}^d$ is an ϵ-approximate first-order stationary point if $\|\nabla f(x)\| \leq \epsilon$.*
- *$x \in \mathbb{R}^d$ is an (ϵ, δ)-approximate second-order stationary point if $\|\nabla f(x)\| \leq \epsilon, \nabla^2 f(x) \succeq -\delta\mathbf{I}$.*

We need the following assumptions which are standard in the literature of finding SOSPs [4, 12, 43].

Assumption 1. *We assume that $f(\cdot)$ in (1) satisfies:*

- *$\Delta_f := f(x_0) - f(x^*) < \infty$ where $x^* := \operatorname{argmin}_x f(x)$.*
- *Each component function $f_i(x)$ is ℓ-Lipschitz smooth and ρ-Hessian Lipschitz.*
- *(For online case only) The variance of the stochastic gradient is bounded: $\forall x \in \mathbb{R}^d$, $\mathbb{E}\|\nabla f_i(x) - \nabla f(x)\|^2 \leq \sigma^2$.*

We'll also need the following more stringent assumption to get high-probability convergence results of ZO-SPIDER in subsection 4.3.

Assumption 2. *We assume that Assumption 1 holds, and in addition, the gradient of each component function $f_i(x)$ satisfies $\forall i, x \in \mathbb{R}^d$, $\|\nabla f_i(x) - \nabla f(x)\|^2 \le \sigma^2$.*

2.1 ZO Gradient Estimators

Given a smooth, Hessian Lipschitz function f, a central difference version of the deterministic coordinate-wise gradient estimator is defined by

$$\hat{\nabla}_{coord} f(x) = \sum_{i=1}^{d} \frac{f(x + \mu e_i) - f(x - \mu e_i)}{2\mu} e_i, \qquad \text{(CoordGradEst)}$$

where e_i denotes a standard basis vector with 1 at its i-th coordinate and 0 otherwise. A central difference version of the random gradient estimator is defined by

$$\hat{\nabla}_{rand} f(x) = d \frac{f(x + \mu u) - f(x - \mu u)}{2\mu} u, \qquad \text{(RandGradEst)}$$

where $u \in \mathbb{R}^d$ is a random direction drawn from a uniform distribution over the unit sphere.

Remark 1. ***Deterministic vs. Random****: CoordGradEst needs d times more function queries than RandGradEst. However, as will be discussed in section 4, it has a lower approximation error and thus can reduce the iteration complexity. **Central Difference vs. Forward Difference** (please refer to Appendix B.1): Under the assumption of Hessian Lipschitz, a smaller approximation error bound can be obtained by the central difference version of both CoordGradEst and RandGradEst.*

2.2 ZO Hessian-Vector Product Estimator

By the definition of derivative: $\nabla^2 f(x) \cdot v = \lim_{\mu \to 0} \frac{\nabla f(x + \mu v) - \nabla f(x)}{\mu}$, we have $\nabla^2 f(x) \cdot v$ can be approximated by the difference of two gradients $\nabla f(x + v) - \nabla f(x)$ for some v with small magnitude. On the other hand, $\nabla f(x + v), \nabla f(x)$ can be approximated by $\hat{\nabla}_{coord} f(x + v), \hat{\nabla}_{coord} f(x)$ with high accuracy, respectively. Then the coordinate-wise Hessian-vector product estimator is defined by:

$$\mathcal{H}_f(x)v \triangleq \sum_{i=1}^{d} \frac{f(x + v + \mu e_i) - f(x + v - \mu e_i) + f(x - \mu e_i) - f(x + \mu e_i)}{2\mu} e_i. \qquad (2)$$

Note that we do not need to know the explicit representation of $\mathcal{H}_f(x)$. It is merely used as a notation for a virtual matrix and can be viewed as the Hessian $\nabla^2 f(x_0)$ with minor perturbations. As stated in the following lemma, the approximation error is efficiently upper bounded.

Lemma 1. *If f is assumed to be ρ-Hessian Lipschitz, then for any smoothing parameter μ and $x \in \mathbb{R}^d$, we have*

$$\|\mathcal{H}_f(x)v - \nabla^2 f(x)v\| \le \rho \left(\|v\|^2 / 2 + \sqrt{d}\mu^2 / 3 \right). \qquad (3)$$

The ZO Hessian-vector product estimator was previously studied in [42, 29], but we provide a tighter bound than that in Lemma 6 in [29]. This is because we utilize properties of the central difference version of the coordinate-wise gradient estimator under the Hessian Lipschitz assumption. It is then directly concluded that, if $f(\cdot)$ is quadratic, we have $\rho = 0$ and $\|\mathcal{H}_f(x)v - \nabla^2 f(x)v\| = 0$.

3 Zeroth-Order Negative Curvature Finding

In this section, we introduce how to find the negative curvature direction near the saddle point using zeroth-order methods. Recently, based on the fact that the Hessian-vector product $\nabla^2 f(x) \cdot v$ can be approximated by $\nabla f(x + v) - \nabla f(x)$ with approximation error up to $\mathcal{O}(\|v\|^2)$, [4] proposed a FO framework named Neon2 that can replace the Hessian-vector product computations in NCF subroutine with gradient computations and thus can turn a FO algorithm for finding FOSPs into a FO algorithm for finding SOSPs. Enlightened by Neon2, we propose two zeroth-order NCF frameworks (*i.e.*, *ZO-NCF-Online* and *ZO-NCF-Deterministic*) using only function queries to solve nonconvex problems in the online stochastic setting and offline deterministic setting, respectively.

Algorithm 1 ZO-NCF-Online-Weak (f, x_0, δ)	**Algorithm 2** ZO-NCF-Online
1: $\eta \leftarrow \frac{\delta}{C_0^2 \ell^2 \log(100d)}$, $T \leftarrow \frac{C_0^2 \log(100d)}{\eta \delta}$, $\sigma \leftarrow \frac{\eta^2 \delta^3}{(100d)^{3C_0} \rho}$, $r \leftarrow (100d)^{C_0} \sigma$	**Input:** $f(\cdot) = \frac{1}{n} \sum_{i=1}^n f_i(\cdot)$, x_0, $\delta > 0$, $p \in (0, 1]$.
2: $\xi \leftarrow \sigma \frac{\xi'}{\|\xi'\|}$, with $\xi' \sim \mathcal{N}(0, \mathbf{I})$	1: **for** $j = 1, 2, \cdots, \Theta(\log(1/p))$ **do**
3: $x_1 \leftarrow x_0 + \xi$	2: $\quad v_j \leftarrow$ ZO-NCF-Online-Weak (f, x_0, δ)
4: **for** $t = 1, \ldots, T$ **do**	3: $\quad$ **if** $v_j \neq \perp$ **then**
5: $\quad \mu_t \leftarrow \|x_t - x_0\|$	4: $\quad\quad m \leftarrow \Theta(\frac{\ell^2 \log(1/p)}{\delta^2})$, $v' \leftarrow \Theta(\frac{\delta}{d\rho})v_j$
6: $\quad x_{t+1} = x_t - \eta \mathcal{H}_{f_i}(x_0)(x_t - x_0)$ with $\mu = \mu_t$ and $i \in [n]$	5: $\quad\quad$ Draw $i_1, \ldots, i_m$ uniformly randomly from $[n]$
7: $\quad$ **if** $\|x_{t+1} - x_0\| \geq r$ **then return** $v = \frac{x_s - x_0}{\|x_s - x_0\|}$ for a uniformly random $s \in [t]$	6: $\quad\quad z_j = \frac{1}{m} \sum_{j=1}^m \frac{(v')^\top \mathcal{H}_{f_{i_j}}(x_0)v'}{\|v'\|^2}$
	7: $\quad\quad$ **if** $z_j \leq -\frac{3\delta}{4}$ **then return** $v = v_j$
Return $v = \perp$	**Return** $v = \perp$

3.1 Stochastic Setting

In this subsection, we focus on solving the NCF problem with zeroth-order methods under the online stochastic setting and propose *ZO-NCF-Online*. Before introducing *ZO-NCF-Online*, we first introduce *ZO-NCF-Online-Weak* with weak confidence of 2/3 for solving the NCF problem.

We summarize *ZO-NCF-Online-Weak* in Algorithm 1. Specifically, *ZO-NCF-Online-Weak* consists of at most $T = \mathcal{O}(\frac{\log^2 d}{\delta^2})$ iterations and works as follows: Given a detection point x_0, add a random perturbation with small magnitude σ as the starting point. At the t-th iteration where $t = 1, \ldots, T$, set $\mu_t = \|x_t - x_0\|$ to be the smoothing parameter μ in (2). Then we keep updating $x_{t+1} = x_t - \eta \mathcal{H}_{f_i}(x_0)(x_t - x_0)$ where $\mathcal{H}_{f_i}(x_0)(x_t - x_0)$ is the ZO Hessian-vector product estimator and stops whenever $\|x_{t+1} - x_0\| \geq r$ or the maximum iteration number T is reached. Thus as long as Algorithm 1 does not terminate, we have that the approximation error $\|\mathcal{H}_{f_i}(x_0)(x_t - x_0) - \nabla^2 f_i(x_0)(x_t - x_0)\|$ can be bounded by $\mathcal{O}(\sqrt{d}r^2)$ according to Lemma 1. Note that, although the error bound is poor by a factor of $\mathcal{O}(\sqrt{d})$ as compared to $Neon_{weak}^{online}$ in [4] which used the difference of two gradients to approximate the Hessian-vector product and achieve an approximation error up to $\mathcal{O}(r^2)$. With proper choice of r in Algorithm 1, our error term is still efficiently upper bounded.

Other than the additional error term caused by ZO approximation, the motivation of *ZO-NCF-Online-Weak* is almost the same as $Neon_{weak}^{online}$. That is, under reasonable control of the approximation error of the Hessian-vector product, using the update rule of Oja's method [34] to approximately calculate the eigenvector corresponding to the minimum eigenvalue of $\nabla^2 f(x_0) = \frac{1}{n} \sum_{i=1}^n \nabla^2 f_i(x_0)$. Under similar analysis, we conclude that as long as the minimum eigenvalue of $\nabla^2 f(x_0)$ satisfies $\lambda_{min}(\nabla^2 f(x_0)) \leq -\delta$, *ZO-NCF-Online-Weak* will stop before T and find a negative curvature direction that aligns well with the eigenvector corresponding to the minimum eigenvalue of $\nabla f^2(x_0)$. Then we have the following lemma:

Lemma 2 (ZO-NCF-Online-Weak). *The output v of Algorithm 1 satisfies: If $\lambda_{min}(\nabla^2 f(x_0)) \leq -\delta$, then with probability at least 2/3, $v \neq \perp$ and $v^\top \nabla^2 f(x_0)v \leq -\frac{3}{4}\delta$.*

We summarize *ZO-NCF-Online* in Algorithm 2. Specifically, *ZO-NCF-Online* repeatedly calls *ZO-NCF-Online-Weak* for $\Theta(\log(1/p))$ times to boost the confidence of solving the NCF problem from 2/3 to $1 - p$. We have the following results:

Lemma 3. *In the same setting as in Algorithm 2, define $z = \frac{1}{m} \sum_{j=1}^m v^\top (\mathcal{H}_{f_{i_j}}(x_0))v$. Then, if $\|v\| \leq \frac{\delta}{16d\rho}$ and $m = \Theta(\frac{\ell^2}{\delta^2})$, with probability at least $1 - p$, we have $\left| \frac{z}{\|v\|^2} - \frac{v^\top \nabla^2 f(x)v}{\|v\|^2} \right| \leq \frac{\delta}{4}$.*

Theorem 1. *Let $f(x) = \frac{1}{n} \sum_{i=1}^n f_i(x)$ where each f_i is ℓ-smooth and ρ-Hessian Lipschitz. For every point $x_0 \in \mathbb{R}^d$, every $\delta \in (0, \ell)$, the output of Algorithm 2 v satisfies that, with probability at least $1 - p$: If $v = \perp$, then $\nabla^2 f(x_0) \succeq -\delta\mathbf{I}$; If $v \neq \perp$, then $\|v\| = 1$ and $v^\top \nabla^2 f(x_0)v \leq -\frac{\delta}{2}$. The total function query complexity is $\mathcal{O}\left(\frac{d\log^2(d/p)\ell^2}{\delta^2}\right)$.*

3.2 Deterministic Setting

In this subsection, we focus on solving the NCF problem with zeroth-order methods under the offline deterministic setting and propose *ZO-NCF-Deterministic*. We summarize *ZO-NCF-Deterministic* in Algorithm 3. Since we want to compute the eigenvector corresponding to the most negative eigenvalue of $\nabla^2 f(x_0)$ approximately, one can convert it into an approximated top eigenvector computation problem of $\mathbf{M} := -\frac{1}{\ell}\nabla^2 f(x_0) + (1 - \frac{3\delta}{4\ell})\mathbf{I}$. This is because all eigenvalues of $\nabla^2 f(x_0)$ in $[\frac{-3\delta}{\ell}, \ell]$ will be mapped to eigenvalues of $\mathbf{M}$ in $[-1, 1]$, and all eigenvalues of $\nabla^2 f(x_0)$ smaller than $-\delta$ will be mapped to eigenvalues of $\mathbf{M}$ greater than $1 + \frac{\delta}{4\ell}$.

Algorithm 3 ZO-NCF-Deterministic

Input: Function $f(\cdot)$, point x_0, negative curvature $\delta > 0$, confidence $p \in (0, 1]$.

1: $T \leftarrow \frac{C_1^2 \log \frac{d}{p} \sqrt{\ell}}{\sqrt{\delta}}, \sigma \triangleq (d/p)^{-2C_1} \frac{\delta}{T^4 \rho}, r \triangleq (d/p)^{C_1} \sigma$

2: $\xi \leftarrow \sigma \frac{\xi'}{\|\xi'\|}$, with $\xi' \sim \mathcal{N}(0, \mathbf{I})$

3: $x_1 \leftarrow x_0 + \xi, y_0 \leftarrow 0, y_1 \leftarrow \xi$

4: **for** $t = 1, \ldots, T$ **do**

5:      $\mu_t = \|y_t\|$

6:      $y_{t+1} = 2\mathcal{M}(y_t) - y_{t-1}$ where $\mathcal{M}(y) = (-\frac{1}{\ell}\mathcal{H}_f(x_0) + (1 - \frac{3\delta}{4\ell}))y$

7:      $x_{t+1} = x_0 + y_{t+1} - \mathcal{M}(y_t)$

8:      **if** $\|x_{t+1} - x_0\| \geq r$ **then return** $v = \frac{x_{t+1} - x_0}{\|x_{t+1} - x_0\|}$

Return $v = \bot$.

Similar to *ZO-NCF-Online-Weak*, *ZO-NCF-Deterministic* starts by adding a random perturbation ξ to the detection point x_0. To find the negative curvature direction v of $\nabla^2 f(x_0)$ such that $v^\intercal \nabla^2 f(x_0) v \leq -\frac{\delta}{2}$, the classical power method which updates through $x_{T+1} = x_0 + \mathbf{M}^T \xi$ [29] will take $T \geq \tilde{\Omega}(\frac{\ell}{\delta})$ number of iterations since eigenvalues of $\mathbf{M}$ greater than $1 + \frac{\delta}{4\ell}$ grows in a speed $(1 + \delta/\ell)^T$. To reduce the iteration complexity T, we can replace the matrix polynomial $\mathbf{M}^T$ with the matrix Chebyshev polynomial $\mathcal{T}_T(\mathbf{M})$ and virtually update $x_{T+1} = x_0 + \mathcal{T}_T(\mathbf{M})\xi$.

Definition 3. *Chebyshev polynomial $\{\mathcal{T}_n(x)\}_{n \geq 0}$ of the first kind is*

$$\mathcal{T}_0(x) = 1, \quad \mathcal{T}_1(x) = x, \quad \mathcal{T}_{n+1}(x) = 2x \cdot \mathcal{T}_n(x) - \mathcal{T}_{n-1}(x),$$

then it satisfies $\mathcal{T}_t(x) = \begin{cases} \cos(n \arccos(x)), & x \in [-1, 1] \\ \frac{1}{2}[(x - \sqrt{x^2 - 1})^n + (x + \sqrt{x^2 - 1})^n], & x > 1 \end{cases}$.

In the matrix case, we have the so-called matrix Chebyshev polynomial $\mathcal{T}_t(\mathbf{M})$ [3], which satisfies: $\mathcal{T}_{t+1}(\mathbf{M})\xi = 2\mathbf{M}\mathcal{T}_t(\mathbf{M})\xi - \mathcal{T}_{t-1}(\mathbf{M})\xi$. Thus, eigenvalues of $\mathbf{M}$ greater than $1 + \frac{\delta}{4\ell}$ will grow to $\left(1 + \delta/4\ell + \sqrt{(\delta/4\ell)^2 + \delta/2\ell}\right)^T \approx \left(1 + \sqrt{\delta/\ell}\right)^T$, so we only need to choose $T \geq \sqrt{\ell/\delta}$.

On the other hand, since we only have access to the zeroth-order information, we need to stably compute the matrix Chebyshev polynomial. In algorithm 3, we set $\mu_t = \|y_t\|$ and use $\mathcal{M}(y_t) = (-\frac{1}{\ell}\mathcal{H}_f(x_0) + (1 - \frac{3\delta}{4\ell}))y_t$ to approximate $\mathbf{M}y_t$ with approximation error up to $\frac{2\rho\sqrt{d}rt}{\ell}\|y_t\|$. With proper choice of r, it allows us to use the inexact backward recurrence [3] to ensure a stable computation of matrix Chebyshev polynomial:

$$y_0 = 0, \quad y_1 = \xi, \quad y_{t+1} = 2\mathcal{M}(y_t) - y_{t-1}.$$

Then the output $x_{T+1} = x_0 + y_{T+1} - \mathcal{M}(y_T)$ is close to $x_0 + \mathcal{T}_T(\mathbf{M})\xi$ with a small approximation error. Finally, we have the following theorem:

Theorem 2. *Let* $f(x) = \frac{1}{n}\sum_{i=1}^n f_i(x)$ *where each* f_i *is* ℓ-*smooth and* ρ-*Hessian Lipschitz. For every point* $x_0 \in \mathbb{R}^d$, *every* $\delta \in (0, \ell]$, *the output of Algorithm 3* v *satisfies that, with probability at least* $1 - p$: *If* $v = \bot$, *then* $\nabla^2 f(x_0) \succeq -\delta\mathbf{I}$; *If* $v \neq \bot$, *then* $\|v\| = 1$ *and* $v^\intercal \nabla^2 f(x_0) v \leq -\frac{\delta}{2}$. *The function query complexity is* $\mathcal{O}(\frac{d \log \frac{d}{p} \sqrt{\ell}}{\sqrt{\delta}})$.

Algorithm 4 ZO-SGD-NCF	**Algorithm 5** ZO-GD-NCF
Input: Function f, starting point x_0, confidence $p \in (0,1)$, $\epsilon > 0$ and $\delta > 0$.	**Input:** Function f, starting point x_0, confidence $p \in (0,1)$, $\epsilon > 0$ and $\delta > 0$.
1: **for** $t = 0, \dots, K-1$ **do**	1: **for** $t = 0, \dots, K-1$ **do**
2: uniformly randomly choose $S \subseteq [n]$	2: **Option I :** $\bar{x}_{t+1} \leftarrow x_t - \eta \hat{\nabla}_{coord} f(x_t)$
3: **Option I :** $\bar{x}_{t+1} \leftarrow x_t - \eta \hat{\nabla}_{coord} f_S(x_t)$	3: **Option II :** $\bar{x}_{t+1} \leftarrow x_t - \eta \hat{\nabla}_{rand} f(x_t)$
4: **Option II :** $\bar{x}_{t+1} \leftarrow x_t - \eta \hat{\nabla}_{rand} f_S(x_t)$	4: **if** $\|\hat{\nabla}_{coord} f(x_t)\| \geq \frac{3\epsilon}{4}$ **then**
5: **if** $\|\nabla f(x_t)\| \geq \frac{\epsilon}{2}$ **then**	5: $x_{t+1} = \bar{x}_{t+1}$
6: $x_{t+1} = \bar{x}_{t+1}$	6: **else**
7: **else**	7: $v \leftarrow$ ZO-NCF-Deterministic $(f, x_t, \delta, \frac{p}{K})$
8: $v \leftarrow$ ZO-NCF-Online $(f, x_t, \delta, \frac{p}{2K})$	8: **if** $v = \perp$ **then return** x_t
9: **if** $v = \perp$ **then return** x_t	9: **else** $x_{t+1} = x_t \pm \frac{\delta}{\rho} v$
10: **else** $x_{t+1} = x_t \pm \frac{\delta}{\rho} v$	

4 Applications of Zeroth-Order Negative Curvature Finding

In this section, we focus on applying the zeroth-order negative curvature frameworks to the following ZO algorithms: ZO-GD, ZO-SGD, ZO-SCSG, and ZO-SPIDER. The following result shows that one can verify if a point x is an ϵ-approximate FOSP using CoordGradEst.

Proposition 1. *In the online setting, using $\mathcal{O}\left(\left(\frac{128\sigma^2}{\epsilon^2} + 1\right)\log\frac{1}{p}\right)$ CoordGradEst with smoothing parameter $\mu \leq \sqrt{\frac{3\epsilon}{4\rho\sqrt{d}}}$, we can verify with probability at least $1-p$, either $\|\nabla f(x)\| \geq \epsilon/2$ or $\|\nabla f(x)\| \leq \epsilon$. In the deterministic setting, using once computation of CoordGradEst with smoothing parameter $\mu \leq \sqrt{\frac{3\epsilon}{2\rho\sqrt{d}}}$, we can verify with probability 1, either $\|\nabla f(x)\| \geq \epsilon/2$ or $\|\nabla f(x)\| \leq \epsilon$.*

4.1 Applying Zeroth-Order Negative Curvature Finding to ZO-GD and ZO-SGD

We apply ZO-NCF-Online to ZO-SGD to turn it into a local minima finding algorithm, and propose ZO-SGD-NCF in Algorithm 4. At each iteration, ZO-SGD-NCF either estimates the gradient $\nabla f_S(x_t) = \frac{1}{|S|}\sum_{i\in S}\nabla f_i(x_t)$ by CoordGradEst (**Option I**) or RandGradEst (**Option II**) with both mini-batch size $\mathcal{O}(\frac{\sigma^2}{\epsilon^2})$. Then, we use $\mathcal{O}\left(\frac{\sigma^2}{\epsilon^2}\log\left(\frac{2K}{p}\right)\right)$ CoordGradEst to verify if x_t is an ϵ-approximate stationary point, if so, we call the ZO-NCF-Online subroutine. If we find an approximate negative curvature direction v around x_t, then we update x_{t+1} by moving from x_t in the direction v with step-size δ/ρ. We have the following theorem:

Theorem 3. *Under Assumption 1, set the parameters as follows, **Option I:** $|S| = \max\{\frac{32\sigma^2}{\epsilon^2}, 1\}$, $K = \mathcal{O}(\frac{\rho^2\Delta_f}{\delta^3} + \frac{\ell\Delta_f}{\epsilon^2})$, $\eta = \frac{1}{4\ell}$, $\mu_1 = \sqrt{\frac{3\epsilon}{4\rho\sqrt{d}}}$, $\mu_2 = \sqrt{\frac{3\epsilon}{4\rho\sqrt{d}}}$; **Option II:** $|S| = \max\{\frac{32\sigma^2}{\epsilon^2}, 1\}$, $K = \mathcal{O}(\frac{\rho^2\Delta_f}{\delta^3} + \frac{d\ell\Delta_f}{\epsilon^2})$, $\eta = \frac{1}{8d\ell}$, $\mu_1 = \min\left\{\sqrt{\frac{3\epsilon}{4\rho d}}, \frac{\epsilon}{16\sqrt{d\ell}}\right\}$, $\mu_2 = \sqrt{\frac{3\epsilon}{4\rho\sqrt{d}}}$, where μ_1 and μ_2 are only used in Line 4 and Line 5 of Algorithm 4, respectively. With probability at least $1-p$, Algorithm 4 outputs an (ϵ, δ)-approximate local minimum in function query complexity*

$$\textbf{Option I:}\tilde{\mathcal{O}}(\frac{d\sigma^2\ell\Delta_f}{\epsilon^4} + \frac{d\sigma^2\rho^2\Delta_f}{\epsilon^2\delta^3} + \frac{d\ell^2\rho^2\Delta_f}{\delta^5}); \textbf{Option II:}\tilde{\mathcal{O}}(\frac{d^2\sigma^2\ell\Delta_f}{\epsilon^4} + \frac{d\sigma^2\rho^2\Delta_f}{\epsilon^2\delta^3} + \frac{d\ell^2\rho^2\Delta_f}{\delta^5}).$$

Remark 2. *Note that the dominant term of the function query complexity in **Option I** is $\tilde{\mathcal{O}}(\frac{d}{\epsilon^2})$, while in **Option II** is $\tilde{\mathcal{O}}(\frac{d^2}{\epsilon^2})$. This is because CoordGradEst has a lower approximation error and thus can reduce the iteration complexity by a fact of d. Then the function query complexity of **Option II** is dominated by evaluating the magnitude of the gradient (Line 5 in Algorithm 4).*

In the Deterministic setting, we apply ZO-NCF-Deterministic to ZO-GD to turn it into a local minima finding algorithm and propose ZO-NCF-GD in Algorithm 5. The update rule of ZO-NCF-GD is similar to that in ZO-NCF-SGD, the only difference is that we don't need to use mini-batch sampling of the stochastic gradient. Similarly, we have the following theorem:

Theorem 4. *Under Assumption 1, set the parameters as follows, **Option I:** $\eta = \frac{1}{4\ell}$, $\mu_1 = \sqrt{\frac{3\epsilon}{4\rho\sqrt{d}}}$, $\mu_2 = \sqrt{\frac{3\epsilon}{2\rho\sqrt{d}}}$; **Option II:** $\eta = \frac{1}{8d\ell}$, $\mu_1 = \min\left\{\sqrt{\frac{3\epsilon}{4\rho d}}, \frac{\epsilon}{16\sqrt{d\ell}}\right\}$, $\mu_2 = \sqrt{\frac{3\epsilon}{2\rho\sqrt{d}}}$, where*

μ_1 and μ_2 are only used in Line 3 and Line 4 of Algorithm 5, respectively. With probability at least $1 - p$, Algorithm 5 outputs an (ϵ, δ)-approximate local minimum in function query complexity

$$\textbf{\textit{Option I:}} \quad \tilde{\mathcal{O}}(\frac{d\ell\Delta_f}{\epsilon^2} + d\frac{\sqrt{\ell}}{\sqrt{\delta}}\frac{\rho^2\Delta_f}{\delta^3}); \quad \textbf{\textit{Option II:}} \quad \tilde{\mathcal{O}}(\frac{d^2\ell\Delta_f}{\epsilon^2} + d\frac{\sqrt{\ell}}{\sqrt{\delta}}\frac{\rho^2\Delta_f}{\delta^3}).$$

4.2 Applying Zeroth-Order Negative Curvature Finding to ZO-SCSG

In this subsection, we first propose a zeroth-order variant of the SCSG [27] method in Algorithm 6. At the beginning of the j-th epoch, we estimate the gradient $\nabla f_{\mathcal{I}_j}(\tilde{x}_{j-1})$ by CoordGradEst over a batch sampling set $\mathcal{I}_j$ with size B. In the inner loop iterations, the stochastic gradient estimator v_{k-1}^j is either constructed by CoordGradEst or by RandGradEst over a mini-batch sampling set $\mathcal{I}_{k-1}^j$ with size b. After running ZO-SCSG for one epoch, we have the following lemma:

Algorithm 6 ZO-SCSG

Input: Number of stages T, initial point $\tilde{x}_0$, batch size B, mini-bath size b, learning rate $\eta > 0$.
1: **for** $j = 1, \ldots, T$ **do**
2:     Uniformly randomly sample a batch $\mathcal{I}_j \subset [n]$ with $|\mathcal{I}_j| = B$
3:     $v_j = \hat{\nabla}_{coord} f_{\mathcal{I}_j}(\tilde{x}_{j-1})$
4:     $x_0^j = \tilde{x}_{j-1}$
5:     **Option I:** $N_j \sim \text{Geom}(\frac{B}{B+b})$ **Option II:** $N_j \sim \text{Geom}(\frac{B}{B+b/d})$
6:     **for** $k = 1, \ldots, N_j$ **do**
7:         Randomly pick $\mathcal{I}_{k-1}^j \subset [n]$ with size b
8:         **Option I:** $v_{k-1}^j = \hat{\nabla}_{coord} f_{\mathcal{I}_{k-1}^j}(x_{k-1}^j) - \hat{\nabla}_{coord} f_{\mathcal{I}_{k-1}^j}(x_0^j) + v_j$
9:         **Option II:** $v_{k-1}^j = \hat{\nabla}_{rand} f_{\mathcal{I}_{k-1}^j}(x_{k-1}^j) - \hat{\nabla}_{rand} f_{\mathcal{I}_{k-1}^j}(x_0^j) + v_j$
10:         $x_k^j = x_{k-1}^j - \eta v_{k-1}^j$
11:     $\tilde{x}_j = x_{N_j}^j$

Algorithm 7 ZO-SCSG-NCF

Input: Function f, starting point x_0, batch size B, mini-batch size b, K, $\epsilon > 0$ and $\delta > 0$.
1: **if** $b > B$ **then return** ZO-SGD$(f, x_0, \frac{2}{3}, \epsilon, \delta)$
2: **for** $t = 0, \ldots, K - 1$ **do**
3:     $\bar{x}_{t+1} \leftarrow$ apply ZO-SCSG on x_t for one epoch with batch size B and mini-batch size b
4:     **if** $\|\nabla f(x_t)\| \geq \frac{\epsilon}{2}$ **then**
5:         $x_{t+1} = \bar{x}_{t+1}$
6:     **else**
7:         $v \leftarrow$ ZO-NCF-Online $(f, x_t, \delta, \frac{1}{20K})$
8:         **if** $v = \perp$ **then return** x_t
9:         **else** $x_{t+1} = x_t \pm \frac{\delta}{\rho}v$

Lemma 4 (One epoch analysis). *Under Assumption 1, **Option I:** Let $\eta\ell = \gamma\left(\frac{b}{B}\right)^{\frac{2}{3}}$. Suppose $\gamma \leq \frac{1}{4}$, $B \geq 8b$ and $b \geq 1$, then after running ZO-SCSG for one epoch, we have*

$$\left(\frac{B}{b}\right)^{\frac{1}{3}} \mathbb{E}\|\nabla f(\tilde{x}_j)\|^2 \leq \frac{4\ell}{\gamma}\left(f(\tilde{x}_{j-1}) - f(\tilde{x}_j)\right) + \frac{30\sigma^2}{b^{\frac{1}{3}}B^{\frac{2}{3}}} + c\left(\frac{B}{b}\right)^{\frac{1}{3}}\ell^2 d\mu^2, \quad (4)$$

*where c is a sufficiently large constant. **Option II:** Let $\eta\ell = \gamma\left(\frac{b/d}{B}\right)^{\frac{2}{3}}$. Suppose $\gamma \leq \frac{1}{8}$, $B \geq 8b/d$ and $b \geq d$, then after running ZO-SCSG for one epoch, we have*

$$\left(\frac{B}{b/d}\right)^{\frac{1}{3}} \mathbb{E}\|\nabla f(\tilde{x}_j)\|^2 \leq \frac{8\ell}{\gamma}\mathbb{E}\left(f(\tilde{x}_{j-1}) - f(\tilde{x}_j)\right) + \frac{72\sigma^2}{(b/d)^{\frac{1}{3}}B^{\frac{2}{3}}} + c\left(\frac{B}{b/d}\right)^{\frac{1}{3}}\ell^2 d^2\mu^2, \quad (5)$$

where c is a sufficiently large constant.

Remark 3. *The epoch size N_j obeys the Geometric distribution, i.e., $N_j \sim Geom(\frac{B}{B+b})$ in **Option I** and $N_j \sim Geom(\frac{B}{B+b/d})$ in **Option II**. Since in expectation we have $\mathbb{E}(N_j)_{N_j \sim Geom(\theta)} = \frac{\theta}{1-\theta}$ [27], then for both **Option I** and **Option II**, the function query complexity in each epoch is $\mathcal{O}(d \cdot B)$.*

Theorem 5. *Under Assumption 1, if we set the parameters as follows, **Option I:** $B = \max\{\frac{480\sigma^2}{\epsilon^2}, 1\}, b = \max\{1, \Theta(\frac{(\epsilon^2+\sigma^2)\epsilon^4\rho^6}{\delta^9\ell^3})\}, K = \Theta(\frac{\ell b^{\frac{1}{3}}\Delta_f}{\epsilon^2 B^{\frac{1}{3}}}), \mu_1 = \frac{\epsilon}{4\sqrt{cd}\ell}, \mu_2 = \sqrt{\frac{3\epsilon}{4\rho\sqrt{d}}}$; **Option II:** $B = \max\{1, \frac{1152\sigma^2}{\epsilon^2}\}, b = \max\{1, d\Theta(\frac{(\epsilon^2+\sigma^2)\epsilon^4\rho^6}{\delta^9\ell^3})\}, K = \Theta(\frac{\ell(b/d)^{\frac{1}{3}}\Delta_f}{\epsilon^2 B^{\frac{1}{3}}}), \mu_1 = \frac{\epsilon}{4\sqrt{dd}\ell}, \mu_2 = \sqrt{\frac{3\epsilon}{4\rho\sqrt{d}}}$, where μ_1 and μ_2 are only use in Line 3 and Line 4 of Algorithm 7, respectively. With probability at least $\frac{2}{3}$, for both **Option I** and **Option II**, Algorithm 7 outputs an (ϵ, δ)-approximate local minimum in function query complexity*

$$\tilde{\mathcal{O}}(d(\frac{\ell\Delta_f}{\epsilon^{\frac{4}{3}}\sigma^{\frac{2}{3}}} + \frac{\rho^2\Delta_f}{\delta^3})(\frac{\sigma^2}{\epsilon^2} + \frac{\ell^2}{\delta^2}) + d\frac{\ell\Delta_f}{\epsilon^2}\frac{\ell^2}{\delta^2}).$$

Remark 4. *The problem described in Remark 2 doesn't exist in ZO-SCSG-NCF as we only evaluate the magnitude of the gradient after each epoch (i.e., Line 4 in Algorithm 7), and the function query complexity is almost the same in the inner loop for both **Option I** and **Option II**.*

4.3 Applying Zeroth-Order Negative Curvature Finding to ZO-SPIDER

In this subsection, we apply ZO-NCF-Online to ZO-SPIDER to turn it into a local minima finding algorithm and propose ZO-SPIDER-NCF in Algorithm 8. As a by-product, we also propose a zeroth-order variant of the SPIDER method in Appendix G that can converge to an ϵ-approximate FOSP with high probability rather than expectation. Using the same technique as in SPIDER-SFO$^+$ [12], that is, instead of moving in a large single step with size δ/ρ along the approximate negative curvature direction as in ZO-SGD-NCF and ZO-SCSG-NCF, we can split it into $\delta/(\rho\eta)$ equal length mini-steps with size η. As a result, we can maintain the SPIDER estimates and improve the so-called non-improvable coupling term $\frac{1}{\delta^3\epsilon^2}$ by a fact of δ.

Algorithm 8 ZO-SPIDER-NCF

Input: Function f, starting point x_0, $\epsilon > 0$ and $\delta > 0$.
1: **for** $j = 0$ to J **do**
2:      $w_1 \leftarrow$ ZO-NCF-Online $(f, x_k, \delta, \frac{1}{16J})$
3:      Randomly flip a sign, and set $w_2 = \pm\eta w_1$
4:      **for** k to $k + \mathscr{K}$ **do**
5:          **if** k mod q = 0 **then**
6:              Sample $\mathcal{S}_1$ from $[n]$ without replacement, $v_k = \hat{\nabla}_{coord}f_{\mathcal{S}_1}(x_k)$
7:          **else**
8:              Sample $\mathcal{S}_2$ from $[n]$ with replacement,
9:              $v_k = \hat{\nabla}_{coord}f_{\mathcal{S}_2}(x_k) - \hat{\nabla}_{coord}f_{\mathcal{S}_2}(x_{k-1}) + v_{k-1}$
10:          **if** $w_1 \neq \perp$ **then**
11:              $x_{k+1} = x_k - w_2$
12:          **else**
13:              **if** $\|v_k\| \leq 2\tilde{\epsilon}$ **then**
14:                  **return** x_k
15:              $x_{k+1} = x_k - \eta(v_k/\|v_k\|)$

Theorem 6. *Under Assumption 2, if we set $\tilde{\epsilon} = 10\epsilon \log(128(K_0+1)), |\mathcal{S}_1| = \frac{16\sigma^2}{\epsilon^2}, |\mathcal{S}_2| = \frac{16\sigma}{\epsilon n_0}, \eta = \frac{\epsilon}{\ell n_0}, q = \frac{\sigma n_0}{\epsilon}, \mu = \left(\frac{\epsilon\cdot\tilde{\epsilon}}{8q^2\rho^2 d}\right)^{\frac{1}{4}} = \tilde{O}(\frac{\epsilon}{d^{1/4}}), \mathscr{K} = \frac{\delta\ell n_0}{\rho\epsilon}$, where $n_0 \in [1, \frac{2\sigma}{\epsilon}]$, then with probability at least $\frac{3}{4}$, Algorithm 8 outputs x_k with $j \leq J = 8\left(\left\lceil \max\left(\frac{12\rho^2\Delta_f}{\delta^3}, \frac{4\rho\Delta_f}{\delta\epsilon}\right)\right\rceil + 1\right), k \leq K_0 = J\mathscr{K}$ satisfying $\|\nabla f(x_k)\| \leq 3\tilde{\epsilon}, \lambda_{min}(\nabla^2 f(x_k)) \geq -2\delta$ with $\tilde{\epsilon} = 10\epsilon \log(128(K_0+1)) = \tilde{\mathcal{O}}(\epsilon)$. The total function query complexity is bounded by*

$$\tilde{\mathcal{O}}\left(d\left(\frac{\sigma\ell\Delta_f}{\epsilon^3} + \frac{\sigma\ell\rho\Delta_f}{\epsilon^2\delta^2} + \frac{\ell^2\rho\Delta_f}{\delta^3\epsilon} + \frac{\ell^2\rho^2\Delta_f}{\delta^5} + \frac{\sigma^2}{\epsilon^2} + \frac{\sigma\delta\ell}{\rho\epsilon^2} + \frac{\ell^2}{\delta^2}\right)\right).$$

References

[1] Naman Agarwal, Zeyuan Allen-Zhu, Brian Bullins, Elad Hazan, and Tengyu Ma. Finding approximate local minima faster than gradient descent. In *Proceedings of the 49th Annual ACM SIGACT Symposium on Theory of Computing*, pages 1195–1199, 2017.

[2] Zeyuan Allen-Zhu. Natasha 2: Faster non-convex optimization than sgd. *Advances in Neural Information Processing Systems*, 31, 2018.

[3] Zeyuan Allen-Zhu and Yuanzhi Li. Faster principal component regression and stable matrix chebyshev approximation. In *International Conference on Machine Learning*, pages 107–115. PMLR, 2017.

[4] Zeyuan Allen-Zhu and Yuanzhi Li. Neon2: Finding local minima via first-order oracles. *Advances in Neural Information Processing Systems*, 31, 2018.

[5] Krishnakumar Balasubramanian and Saeed Ghadimi. Zeroth-order nonconvex stochastic optimization: Handling constraints, high dimensionality, and saddle points. *Foundations of Computational Mathematics*, 22(1):35–76, 2022.

[6] Arjun Nitin Bhagoji, Warren He, Bo Li, and Dawn Song. Practical black-box attacks on deep neural networks using efficient query mechanisms. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 154–169, 2018.

[7] Yair Carmon and John C Duchi. Gradient descent efficiently finds the cubic-regularized non-convex newton step. *arXiv preprint arXiv:1612.00547*, 2016.

[8] Yair Carmon, John C Duchi, Oliver Hinder, and Aaron Sidford. "convex until proven guilty": Dimension-free acceleration of gradient descent on non-convex functions. In *International Conference on Machine Learning*, pages 654–663. PMLR, 2017.

[9] Yair Carmon, John C Duchi, Oliver Hinder, and Aaron Sidford. Accelerated methods for nonconvex optimization. *SIAM Journal on Optimization*, 28(2):1751–1772, 2018.

[10] Pin-Yu Chen, Huan Zhang, Yash Sharma, Jinfeng Yi, and Cho-Jui Hsieh. Zoo: Zeroth order optimization based black-box attacks to deep neural networks without training substitute models. In *Proceedings of the 10th ACM Workshop on Artificial Intelligence and Security*, pages 15–26, 2017.

[11] Krzysztof Choromanski, Mark Rowland, Vikas Sindhwani, Richard Turner, and Adrian Weller. Structured evolution with compact architectures for scalable policy optimization. In *International Conference on Machine Learning*, pages 970–978. PMLR, 2018.

[12] Cong Fang, Chris Junchi Li, Zhouchen Lin, and Tong Zhang. Spider: Near-optimal non-convex optimization via stochastic path-integrated differential estimator. *Advances in Neural Information Processing Systems*, 31, 2018.

[13] Rong Ge, Furong Huang, Chi Jin, and Yang Yuan. Escaping from saddle points-online stochastic gradient for tensor decomposition. In *Conference on learning theory*, pages 797–842. PMLR, 2015.

[14] Rong Ge, Jason D Lee, and Tengyu Ma. Matrix completion has no spurious local minimum. *Advances in Neural Information Processing Systems*, 29, 2016.

[15] Rong Ge, Jason D. Lee, and Tengyu Ma. Learning one-hidden-layer neural networks with landscape design. In *International Conference on Learning Representations*, 2018.

[16] Rong Ge and Tengyu Ma. On the optimization landscape of tensor decompositions. *Advances in Neural Information Processing Systems*, 30, 2017.

[17] Saeed Ghadimi and Guanghui Lan. Stochastic first-and zeroth-order methods for nonconvex stochastic programming. *SIAM Journal on Optimization*, 23(4):2341–2368, 2013.

[18] Moritz Hardt, Tengyu Ma, and Benjamin Recht. Gradient descent learns linear dynamical systems. *Journal of Machine Learning Research*, 19(29):1–44, 2018.

[19] Prateek Jain, Chi Jin, Sham Kakade, and Praneeth Netrapalli. Global convergence of non-convex gradient descent for computing matrix squareroot. In *Artificial Intelligence and Statistics*, pages 479–488. PMLR, 2017.

[20] Kaiyi Ji, Zhe Wang, Yi Zhou, and Yingbin Liang. Improved zeroth-order variance reduced algorithms and analysis for nonconvex optimization. In *International Conference on Machine Learning*, pages 3100–3109. PMLR, 2019.

[21] Chi Jin, Rong Ge, Praneeth Netrapalli, Sham M Kakade, and Michael I Jordan. How to escape saddle points efficiently. In *International Conference on Machine Learning*, pages 1724–1732. PMLR, 2017.

[22] Chi Jin, Lydia T Liu, Rong Ge, and Michael I Jordan. On the local minima of the empirical risk. *Advances in Neural Information Processing Systems*, 31, 2018.

[23] Chi Jin, Praneeth Netrapalli, and Michael I Jordan. Accelerated gradient descent escapes saddle points faster than gradient descent. In *Conference On Learning Theory*, pages 1042–1085. PMLR, 2018.

[24] Gangshan Jing, He Bai, Jemin George, Aranya Chakrabortty, and Piyush K Sharma. Asynchronous distributed reinforcement learning for lqr control via zeroth-order block coordinate descent. *arXiv preprint arXiv:2107.12416*, 2021.

[25] Kenji Kawaguchi. Deep learning without poor local minima. *Advances in Neural Information Processing Systems*, 29, 2016.

[26] Kenji Kawaguchi, Jiaoyang Huang, and Leslie Pack Kaelbling. Every local minimum value is the global minimum value of induced model in nonconvex machine learning. *Neural Computation*, 31(12):2293–2323, 2019.

[27] Lihua Lei, Cheng Ju, Jianbo Chen, and Michael I Jordan. Non-convex finite-sum optimization via scsg methods. *Advances in Neural Information Processing Systems*, 30, 2017.

[28] Huan Li and Zhouchen Lin. Restarted nonconvex accelerated gradient descent: No more polylogarithmic factor in the $\mathcal{O}(\epsilon^{-7/4})$ complexity. *arXiv preprint arXiv:2201.11411*, 2022.

[29] Aurelien Lucchi, Antonio Orvieto, and Adamos Solomou. On the second-order convergence properties of random search methods. *Advances in Neural Information Processing Systems*, 34, 2021.

[30] Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *International Conference on Learning Representations*, 2018.

[31] Yurii Nesterov. *Introductory lectures on convex optimization: A basic course*, volume 87. Springer Science & Business Media, 2003.

[32] Yurii Nesterov and Boris T Polyak. Cubic regularization of newton method and its global performance. *Mathematical Programming*, 108(1):177–205, 2006.

[33] Yurii Nesterov and Vladimir Spokoiny. Random gradient-free minimization of convex functions. *Foundations of Computational Mathematics*, 17(2):527–566, 2017.

[34] Erkki Oja. Simplified neuron model as a principal component analyzer. *Journal of Mathematical Biology*, 15(3):267–273, 1982.

[35] Nicolas Papernot, Patrick McDaniel, Ian Goodfellow, Somesh Jha, Z Berkay Celik, and Ananthram Swami. Practical black-box attacks against machine learning. In *Proceedings of the 2017 ACM on Asia Conference on Computer and Communications Security*, pages 506–519, 2017.

[36] Sashank J Reddi, Ahmed Hefny, Suvrit Sra, Barnabas Poczos, and Alex Smola. Stochastic variance reduction for nonconvex optimization. In *International Conference on Machine Learning*, pages 314–323. PMLR, 2016.

[37] Tim Salimans, Jonathan Ho, Xi Chen, Szymon Sidor, and Ilya Sutskever. Evolution strategies as a scalable alternative to reinforcement learning. *arXiv preprint arXiv:1703.03864*, 2017.

[38] Ju Sun, Qing Qu, and John Wright. A geometric analysis of phase retrieval. *Foundations of Computational Mathematics*, 18(5):1131–1198, 2018.

[39] Chun-Chen Tu, Paishun Ting, Pin-Yu Chen, Sijia Liu, Huan Zhang, Jinfeng Yi, Cho-Jui Hsieh, and Shin-Ming Cheng. Autozoom: Autoencoder-based zeroth order optimization method for attacking black-box neural networks. *Proceedings of the AAAI Conference on Artificial Intelligence*, 33:742–749, 07 2019.

[40] Emmanouil-Vasileios Vlatakis-Gkaragkounis, Lampros Flokas, and Georgios Piliouras. Efficiently avoiding saddle points with zero order methods: No gradients required. *Advances in Neural Information Processing Systems*, 32, 2019.

[41] Yi Xu, Rong Jin, and Tianbao Yang. Neon+: Accelerated gradient methods for extracting negative curvature for non-convex optimization. *arXiv preprint arXiv:1712.01033*, 2017.

[42] Haishan Ye, Zhichao Huang, Cong Fang, Chris Junchi Li, and Tong Zhang. Hessian-aware zeroth-order optimization for black-box adversarial attack. *arXiv preprint arXiv:1812.11377*, 2018.

[43] Chenyi Zhang and Tongyang Li. Escape saddle points by a simple gradient-descent based algorithm. *Advances in Neural Information Processing Systems*, 34, 2021.