MedKGEval: A Knowledge Graph-Based Multi-Turn Evaluation Framework for Open-Ended Patient Interactions with Clinical LLMs

Abstract

The reliable evaluation of large language models (LLMs) in medicine remains an open challenge, particularly in capturing the dynamic, multi-turn nature of doctor-patient interactions. Conventional methods, which rely on post-hoc transcript review, fail to assess the context-sensitive and evolving informational needs inherent to clinical dialogue. To address this, we introduce MedKGEval, a novel multi-turn evaluation framework grounded in structured medical knowledge. Our approach features three key contributions: (1) a knowledge graph-driven patient simulation, where a control module retrieves medically relevant facts to guide a realistic patient agent—the knowledge graph is constructed by integrating open-source resources with triples extracted from expert-annotated data; (2) an in-situ, turn-level evaluation performed by a Judge Agent that assesses each model response for clinical appropriateness, factual correctness, and safety using fine-grained metrics as the dialogue unfolds; and (3) a comprehensive benchmark across eight state-of-the-art LLMs, revealing subtle behavioral flaws and safety risks overlooked by conventional pipelines. Although initially applied to Chinese and English medical contexts, MedKGEval is extensible to other languages via interchangeable knowledge graphs. Code and datasets are available at https://anonymous.4open.science/r/MedKGEval-4F2E/.

1 Introduction

Large language models (LLMs) show strong performance in medical tasks like question answering, diagnosis support, and triage (Brown et al., 2020; Singhal et al., 2023), and their fluent, context-aware responses make them promising for clinical decision support and patient-facing applications (Spotnitz et al., 2024; Wang et al., 2023). Yet reliably evaluating LLMs in healthcare remains challenging—especially for open-ended, multi-turn dialogues that mimic real doctor-patient interactions.

Such conversations evolve dynamically: each turn builds on prior context and new patient disclosures. For example, a patient might report a persistent cough; the physician asks about fever or shortness of breath; the patient adds details about a recent fever; and the exchange continues until enough information is gathered for clinical reasoning. This open-ended, context-dependent structure increases complexity and complicates evaluation.

Current evaluation methods rely on static benchmarks (Liu et al., 2024; Arora et al., 2025) or post-hoc transcript analysis (Jeblick et al., 2024; Singhal et al., 2025), which ignore the evolving nature of medical dialogue. They fail to track how clinical relevance, factual accuracy, and safety may shift across turns, missing issues like error propagation or context drift that emerge over time. Recent efforts use interactive patient simulators (Liao et al., 2024; Johri et al., 2025) or integrate medical knowledge (Zuo et al., 2025), but still evaluate retrospectively and lack turn-by-turn integration of domain knowledge.

To address these gaps, we introduce MedKGEval—a knowledge graph–driven multi-agent framework for simulating realistic medical dialogues and evaluating LLMs in real time. As shown in Figure 1, MedKGEval models four roles: (i) a Doctor Agent (the LLM under test) that diagnoses or recommends treatments; (ii) a Patient Agent that responds naturally based on a predefined persona and medical facts; (iii) a Judge Agent that assesses each doctor response for clinical appropriateness, accuracy, and safety at every turn; and (iv) a Director Agent that initializes patient profiles, resolves symptom conflicts, and enforces clinical realism. A shared knowledge graph ensures consistent access to symptom–disease–medication relationships across all agents.

By embedding evaluation into the interaction

loop, MedKGEval enables fine-grained, turn-by-turn assessment of how accuracy and relevance evolve—capturing the open-ended, multi-turn nature of clinical conversations. This design detects context drift, error propagation, and safety issues early, overcoming the retrospective limitations of prior benchmarks.

We validate our approach on two scenarios—medication consultation and disease diagnosis—evaluating both general and domain-specific LLMs. An example diagnosis case is shown in Figure 2. Results show MedKGEval reveals subtle clinical oversights and behavioral flaws missed by conventional methods. Our contributions are:

- A novel knowledge graph–based evaluation framework for realistic, scalable multi-turn testing of clinical LLMs.

- A Judge Agent that performs real-time, turn-level assessment of clinical appropriateness, factual accuracy, and safety using task-specific metrics.

- Empirical evidence that our framework uncovers clinically relevant failure modes across diverse models and tasks.

2 Related Work

Evaluation Benchmarks for Medical LLMs. Benchmarks such as MedBench (Liu et al., 2024) and HealthBench (Arora et al., 2025) focus on single-turn question answering or summarization tasks using static datasets. While useful for broad coverage, they fall short in evaluating the longitudinal reasoning and safety awareness required in real clinical conversations. Furthermore, closed evaluations based on fixed datasets risk triggering an "overfitting during evaluation" phenomenon—models may achieve artificially inflated scores by memorizing high-frequency question patterns, yet significantly underperform in actual open-domain conversational scenarios.

Knowledge Graph Applications in Medical LLMs. Emerging research demonstrates how knowledge graphs (KGs) address critical limitations of LLMs in clinical applications. (Yang et al., 2024b) proposed KG-Rank, which integrates medical KGs with ranking-enhanced triplet retrieval to improve clinical QA accuracy. For complex decision-making tasks, (Jiang et al., 2025) developed KARE, a framework that combines hierarchical KG community detection with LLM reasoning, reducing clinical prediction hallucinations through context-aware knowledge aggregation. However, existing KG applications primarily focus on model training or clinical decision support, leaving underexplored their potential in constructing evaluation benchmarks. KGs are well-suited for benchmarks: their structured, composable relations (e.g., diagnoses, treatments, adverse events, temporal and lab findings) and multi-hop paths enable gold-standard reasoning chains and assessment of procedural reasoning, path consistency, and factual faithfulness. Thus, KGs offer an interpretable, controllable, and scalable basis for benchmark construction, addressing gaps in content breadth and process-aware evaluation.

Multi-Turn and Interactive Evaluation. Several frameworks have been proposed to move toward interactive evaluation, including MT-Eval (Kwan et al., 2024) and MultiChalleng (Deshpande et al., 2025). These efforts evaluate multi-turn conversation as a whole, thus fails to provide more fine-grained evaluation result up to each turn. (Liao et al., 2024) reformulates medical multiple-choice questions into patient information and diagnostic tasks. However, their work is limited by the finite nature of the datasets derived from medical exams, which restricts the scalability of the evaluation scenarios. In contrast, our framework leverages a knowledge graph-based framework, allowing for the dynamic and virtually limitless expansion of consultation tasks. This graph-based pipeline not only enhances the diversity of the evaluation but also ensures that the system can be readily updated with new medical knowledge. Furthermore, under the guidance of a dedicated control module, our Patient Agent demonstrates stable and consistent interactions, maintaining coherence in communication throughout the consultation process.

3 Dataset Construction

To support structured and clinically grounded evaluation of medical LLMs across both Chinese and English settings, we construct task-specific medical knowledge graphs, which we collectively term **MedKG**. These graphs are used to systematically generate multi-turn test cases for our evaluation scenarios. Specifically, the Chinese version of MedKG

Figure 1: Overview of the MedKGEval pipeline. The framework simulates doctor-patient interactions based on the knowledge graph. A director agent is engaged to promise the patient agent's stable and consistent behavior in communication. The judge agent enables comperhensive assesment of the LLM's performance on multi-turn conversation.

is built upon CMeKG (Byambasuren et al., 2019), an open-source medical KG, and the English version is built upon PrimeKG (Chandak et al., 2023); both are selectively curated and extended to focus on entities and relations most relevant to our two core evaluation tasks: *disease diagnosis* and *medication consultation*.

Specifically, we extract a disease-centered subgraph by identifying all disease nodes and retrieving their directly associated *symptoms* and *drugs*. For each drug entity, we further incorporate key clinical attributes such as *indications*, *contraindications*, *precautions*, and *drug-drug interactions*, capturing the contextual factors critical to appropriate drug usage. To improve domain coverage and factual reliability, we augment the initial graph with additional triples extracted from high-quality medical QA corpora, including MedQA (Jin et al., 2021) and NLPEC (Li et al., 2020), emphasizing pharmacological relations with high semantic confidence.

In practice, medical knowledge graphs often aggregate heterogeneous sources—including clinical statistics, historical case archives, and standardized medical textbooks—which may introduce biologically inconsistent or clinically implausible associations (Wu et al., 2023). For example, naive integration can result in symptom clusters that violate basic medical logic, such as male patients presenting with ovarian cysts.

To mitigate such noise and enhance the clinical realism of simulated interactions, we design a domain-specific cleaning process consisting of: (1) *semantic–consistency filtering*, which removes medically invalid triples that conflict with basic constraints such as gender, anatomy, or pathophysiology; and (2) *discriminative–symptom selection*, which prioritizes diagnostically distinctive features (e.g., Koplik spots for measles, resting tremor for Parkinson's disease). The resulting graph thus provides a high-quality, clinically coherent foundation for downstream case generation and evaluation, ensuring that medical facts and symptom–disease–medication relationships are consistently available during doctor-aptient conversations. An illustration of our graph is shown in Figure 3, and Table 1 presents its statistical overview.

Table 1: Statistics of entities in the knowledge graph.

Category	Count
Relations	651,463
Drugs	15,164
Diseases	15,898
Symptoms	32,248
Indications	54,203
Complication	31,924
Adverse Reactions	165,976
Precautions	26,414

4 Pipeline Construction

To capture complementary aspects of clinical reasoning, we design two evaluation scenarios:

- **Medication Consultation:** The patient queries about a target drug across multiple turns, each focusing on a different attribute

Figure 2: An example case of MedKGEval in the disease-diagnosis task.

Figure 3: Illustration of the curated medical knowledge graph used for evaluation.

(indications, contraindications, precautions) retrieved from the KG. A judge evaluates each doctor response for accuracy and comprehensiveness.

- **Disease Diagnosis:** The patient incrementally reveals symptoms from a predefined disease profile over multiple turns. The doctor must gather sufficient information through history-taking before offering a diagnosis. Performance is scored on both final correctness and history-taking quality.

These scenarios enable MedKGEval to assess both knowledge application in medication-related decision-making and reasoning in diagnostic settings. To implement them, MedKGEval comprises four specialized agents:

Doctor Agent. This is the primary evaluation target—the medical LLM under assessment. It receives patient inputs turn by turn and responds accordingly, simulating the role of a clinician. The doctor agent remains stateless across different test cases but accumulates dialogue history within each session to enable context-aware reasoning.

Director Agent. As noted in Section 3, the Director Agent serves as a centralized controller. It retrieves relevant information from the knowledge graph and filters the extracted subgraph nodes according to medical rationale to construct clinically plausible patient profiles. The agent then dynamically determines the next intent or query to guide the simulated patient: for drug-related tasks, it sequentially reveals attributes such as contraindications or precautions; for diagnostic tasks, it modulates the pace of symptom disclosure and controls the dialogue length. When the Doctor Agent inquires about additional details, the Director Agent supplies disease-specific guidance to the Patient Agent, preventing responses from straying from realistic clinical presentations and thereby preserving the diagnostic validity of the disclosed symptoms.

Patient Agent. Guided by the Director Agent's instructions, the Patient Agent produces natural-language utterances that mimic real patient behavior. It faithfully follows the assigned persona—age, medical history, and communication style—and

introduces symptom descriptions or medication-related questions in a coherent, human-like manner. Crucially, the Patient Agent begins with limited medical knowledge, reflecting real-world clinical encounters where patients often struggle to articulate precise symptoms or identify relevant details during initial consultations. The Director Agent therefore unveils critical medical information gradually, timing each disclosure to match the natural flow of a physician's diagnostic questioning.

Judge Agent. Our Judge Agent, leveraging multi-turn dialogue history and relevant medical knowledge, assesses model behavior along the two tasks: *Medication Consultation* and *Disease Diagnosis*. For each task, we move beyond binary correctness and introduce multi-level scoring frameworks that reflect the nuanced requirements of clinical decision-making.

For **Medication Consultation**, we focus on two core criteria: (1) **Accuracy**—whether the model's response aligns with established pharmacological knowledge and avoids harmful misinformation; and (2) **Comprehensiveness**—whether the model delivers a thorough and informative response addressing all key aspects of the user's query.

For **Disease Diagnosis**, we assess two key dimensions: (1) **Correctness**—whether the model's final prediction aligns semantically or ontologically with the reference disease; and (2) **History-taking Skill**—whether the model effectively gathers relevant clinical information across turns to support accurate differential diagnosis.

Notably, our framework introduces a novel history-taking metric—absent in prior benchmarks that focus only on final diagnoses—that evaluates the incremental gathering and synthesis of symptoms and background information, a cornerstone of safe clinical reasoning (Johri et al., 2025). Crucial in multi-turn dialogues, where each follow-up question influences diagnostic accuracy, this skill is assessed turn-by-turn via an in-situ scoring protocol that enables fine-grained detection of reasoning gaps. The detailed scoring rubrics for all dimensions, along with the specific prompts designed for each agent, are provided in Appendix A, making our approach both clinically grounded and methodologically distinct.

5 Experiments

In our evaluation setup, the primary objective is to rigorously assess the capabilities and safety of the

Doctor Agent. Our framework incorporates benchmark testing with state-of-the-art models including Qwen3, GPT-4o, LLaMA3.1, DeepSeek-R1 (general-purpose) and Lingshu, MedGemma, Citrus, Huatuo (medical-specialized). The evaluation tasks focus on two clinical dimensions:

- Medication Consultation: Evaluated on 500 Chinese and 500 English subgraphs derived from **MedKG**, centered on medications with nodes for drug names, indications, contraindications, and precautions.

- Disease Diagnosis: Evaluated on 500 Chinese and 500 English subgraphs derived from **MedKG**, centered on diseases with nodes describing pathological entities, clinical symptoms, and comorbid conditions.

To enable this, our pipeline first requires the careful selection of three supporting agents—*Director Agent*, *Patient Agent*, and *Judge Agent*—each serving a distinct functional role within the evaluation process.

5.1 Agent Configuration

Director Agent. As the orchestrator of the dialogue environment, the Director Agent must possess strong general reasoning ability, robust instruction-following behavior, and broad domain knowledge across both Chinese and English. To this end, we adopt DeepSeek-R1-671B (Guo et al., 2025), which demonstrates state-of-the-art performance in Chinese language understanding and generation, while also maintaining highly competitive capabilities in English. This makes it well-suited for multilingual dialogue scenarios, including complex domains such as medicine.

Judge Agent. The Judge Agent is responsible for assessing the correctness and comprehensiveness of each Doctor Agent's responses. Since our tasks are defined by a powerful Director with standardized answers, the evaluation architecture can adopt a more lightweight model paradigm that focuses on rule comprehension and reference knowledge validation, rather than open-ended correctness verification. In this closed-domain setting, we prioritize strong bilingual (Chinese and English) language competency alongside efficient validation capabilities when selecting models. We therefore conduct a human-in-the-loop agreement test using several large language models that demonstrate high performance in both Chinese and English, including

QwQ-32B (Yang et al., 2024a), Qwen3-32B (Yang et al., 2025), and DeepSeek-R1-32B (Guo et al., 2025). Our preliminary results show that QwQ-32B achieves the highest agreement with expert human raters. Detailed agreement statistics are presented in Table 2.

Table 2: Mean Absolute Error (MAE) between Judge Agent ratings and human ratings across different metrics for Medication Consultation (**MC**) and Disease Diagnosis (**DD**) tasks. **Note:** "**Corr**" denotes Correctness, "**Comp**" denotes Comprehensiveness and "**HT**" denotes History-taking.

Model	MC		DD	
	Corr	Comp	Corr	HT
QwQ-32B	**0.1370**	**0.2911**	**0.3569**	**0.2815**
Qwen3-32B	0.2204	0.3871	0.6316	0.5081
DeepSeek-R1-32B	0.2173	0.3858	0.6361	0.4783

Patient Agent. To minimize noise and maintain consistency across evaluations, the Patient Agent must exhibit stable and controlled behavior. Thus we compare three candidate models—QwQ-32B, Qwen3-32B, and DeepSeek-R1-32B—in terms of their dialogue querys consistency when coummunicate with different Doctor Agents. Using BGE-M3(Chen et al., 2024), we compute the average embedding similarity across querys sets to quantify intra-agent variability. Specifically, the consistency score (Cons) is calculated as follows:

$$\text{Cons} = \frac{1}{|D|} \sum_{d \in D} \left(\frac{2}{n_d(n_d - 1)} \sum_{1 \leq i < j \leq n_d} \text{sim}(R_{d,i}, R_{d,j}) \right)$$

(1)

where D denotes the set of diseases, n_d is the number of patient querys for disease d, and $\text{sim}(R_{d,i}, R_{d,j})$ denotes the similarity between the i-th and j-th patient's querys for disease d. This metric thus first computes the average pairwise similarity of patient's querys under each disease and then averages across all diseases.

The results show that QwQ-32B achieves the highest consistency with an average similarity score of **83.86**, outperforming Qwen3-32B (**81.95**) and DeepSeek-R1-32B (**81.34**). This superior stability leads us to select QwQ-32B as the final Patient Agent. The specific consistency scores and detailed statistics are shown in Table 3.

5.2 Results on evaluating MedLLMs

We evaluate eight state-of-the-art language models as Doctor Agents, focusing on their multilingual

Table 3: Consistency Scores of the Patient Agent in Medication Consultation (**MC**) and Disease Diagnosis (**DD**) tasks.

Model	MC	DD	Avg.
QwQ-32B	**84.18%**	**83.53%**	**83.86%**
Qwen3-32B	82.06%	81.84%	81.95%
DeepSeek-R1-32B	81.79%	80.88%	81.34%

performance in Chinese and English across two clinical tasks: Medication Consultation and Disease Diagnosis. Each model is assessed using our scoring rubric and multi-agent evaluation pipeline (see Appendix **Model Description** for model details).

Medication Consultation. Table 4 shows normalized scores (0–1) for multi-turn Medication Consultation, measuring *correctness* and *comprehensiveness*. General-purpose large models consistently outperform smaller medical-specific ones. DeepSeek-R1-671B leads in both languages, with correctness scores of 0.8858 (ZH) / 0.8763 (EN) and comprehensiveness scores of 0.7581 / 0.8351, demonstrating robust cross-lingual medical knowledge. Qwen3-235B-A22B and Citrus-72B follow closely in Chinese, while HuatuoGPT-72B—the top medical-specialized model—matches general models in Chinese but drops significantly in English (correctness: 0.5833 vs. 0.8548).

MedGemma-27B lags in both metrics, indicating that domain specialization alone is insufficient without adequate model capacity. Across all models, *correctness* exceeds *comprehensiveness*, revealing a tendency to provide factually valid but incomplete guidance—a critical safety concern.

Disease Diagnosis. Results reveal more nuanced patterns. In Chinese, DeepSeek-R1-671B leads on both metrics, while LLaMA3.1-70B excels at history-taking (0.6314) but underperforms in diagnostic correctness—suggesting strong conversational scaffolding but weak synthesis. Domain-specific models (HuatuoGPT, Lingshu) similarly show better history-taking than final diagnosis, likely reflecting QA-style training emphasizing symptom recall over end-to-end reasoning.

In English, rankings shift: LLaMA3.1-70B achieves the best multi-turn performance (0.4796/0.6973), while GPT-4o leads in single-turn (0.4879). DeepSeek underperforms notably in English history-taking (0.2821), issuing diagnoses prematurely after only 1.11 turns on average (vs.

Table 4: General Performance of eight LLMs on Medication Consultation(**MC**) and Disease Diagnosis(**DD**) tasks in English (EN) and Chinese (ZH) scenario. **Note:** "**Corr**" denotes correctness, "**Comp**" denotes comprehensiveness and "**HT**" denotes history-taking.

Task	Metric	Language	Qwen3	GPT-4o	LLaMA3.1	DeepSeek	Citrus	Lingshu	Huatuo	MedGemma
MC	Corr (multi-turn)	EN	0.7642	0.6267	0.7408	**0.8763**	0.6911	0.5911	0.5833	0.6606
	Comp (multi-turn)	EN	0.6580	0.5701	0.6099	**0.8351**	0.5733	0.4609	0.5182	0.5674
	Corr (multi-turn)	ZH	0.8497	0.8330	0.7300	**0.8858**	0.8534	0.8270	0.8548	0.6697
	Comp (multi-turn)	ZH	0.6837	0.6406	0.6278	**0.7581**	0.6850	0.6685	0.7021	0.5442
DD	Corr (multi-turn)	EN	0.4733	0.4572	**0.4796**	0.4471	0.4274	0.4352	0.4467	0.3991
	HT (multi-turn)	EN	0.3000	0.4844	**0.6973**	0.2821	0.4983	0.3488	0.4689	0.3080
	Corr (sigle-turn)	EN	0.4828	**0.4879**	0.4408	0.4739	0.4717	0.4212	0.4411	0.4358
	Corr (multi-turn)	ZH	0.3985	0.4375	0.4321	**0.4888**	0.3890	0.3677	0.3875	0.3333
	HT (multi-turn)	ZH	0.2763	0.5000	0.6314	**0.6894**	0.3175	0.4510	0.5670	0.3463
	Corr (sigle-turn)	ZH	0.4627	0.4751	0.4384	**0.4974**	0.4703	0.3985	0.4639	0.4490

Figure 4: Correctness (a) and History taking scores (b) of eight models in a Chinese disease-diagnosis scenario at different turn counts. Larger circles indicate more cases that ended the dialogue at that turn and received the corresponding score.

2.78 in Chinese)—indicating insufficient information gathering likely due to limited English multi-turn clinical data in training.

Cross-lingually, GPT-4o remains the most consistent (ZH: 0.438/0.500; EN: 0.457/0.484). Several models (GPT-4o, Qwen3, DeepSeek, Citrus) slightly favor single-turn, while LLaMA3.1 uniquely benefits from multi-turn context in English (0.4796 > 0.4408). Overall, diagnosis proves more challenging than Medication Consultation, with the persistent gap between history-taking and final correctness underscoring that clinical reasoning demands more than information retrieval.

Impact of Dialogue Turn Count. To investigate how dialogue length influences model performance in disease diagnosis, we categorize test cases by turn count and analyze their cor-

responding scores. In the Chinese scenario, as shown in Figure 4, both diagnostic correctness and history-taking ability tend to degrade as the number of turns increases. Large-parameter, general-purpose models—DeepSeek-R1-671B, GPT-4o and LLaMA3.1-70B—display greater resilience: they engage in extended, multi-turn reasoning and thereby arrive at more accurate diagnoses. In contrast, small-parameter, MoE or specialized models often jump prematurely to an answer; consistent with the results in Table 4, their overall correctness and history-taking scores are noticeably lower. These findings indicate that, although some models stay coherent across extended dialogues, many falter when required to perform multi-step reasoning or to retain context—capabilities that are essential for complex diagnostic work. In the English scenario (Figure 13; corresponding figure in the

Appendix), the overall trend largely mirrors the Chinese case. While DeepSeek-R1-671B stands out as an exception, issuing diagnoses after fewer turns on average, which is consistent with its general performance profile.

5.3 Ablation Study: Effect of Director Agent Control

To assess the Director Agent's role in enforcing medically grounded, knowledge-aligned conversations, we conduct an ablation study comparing the proportion of key entity mentions in patient queries that match knowledge graph entries—with versus without Director Agent control—across both Medication Consultation and Disease Diagnosis tasks. Results are shown in Table 5.

Table 5: The percentage of patient utterances containing entity mentions consistent with the knowledge graph in Medication Consultation (**MC**) and Disease Diagnosis (**DD**) tasks.

Task	With Director Agent	Without Director Agent
MC	**91.4%**	63.4%
DD	**95.26%**	59.6%

The results clearly demonstrate that the use of a Director Agent significantly improves the semantic alignment between patient queries and medically validated knowledge. Without guided control, patient utterances frequently drift into generic or inconsistent expressions, resulting in substantial knowledge loss and decreased evaluation fidelity.

To further quantify the impact of the Director Agent on the conversation, we examine the performance degradation of the doctor model (DeepSeek-R1-671B) on the disease diagnosis task when the Director Agent is removed. As shown in Table 6, both the diagnostic correctness and history-taking ability drop significantly in the absence of Director-guided patient behaviors.

These results validate that Director Agent-controlled patient simulation not only enhances the alignment between patient utterances and the medical knowledge graph, but also enables more informative and structured interactions that directly benefit the diagnostic capabilities of clinical LLMs under evaluation.

6 Conclusion

In this paper, we present a scalable, knowledge-graph–driven framework for multi-turn evaluation

Table 6: Correctness (**Corr**) and history-taking (**HT**) scores of DeepSeek-R1-671B on multi-turn disease diagnosis tasks with and without Director Agent.

Metric	With Director Agent	Without Director Agent
Corr	**48.88%**	37.62%
HT	**68.94%**	33.42%

of clinical LLMs. The knowledge graph is assembled by merging open-source resources with additional triples extracted from expert-annotated datasets. Guided by a Director Agent, the Patient Agent engages in coherent, realistic dialogues that remain stable across turns. We also introduce a quantitative metric that captures an LLM's proficiency in step-by-step history taking. Using this framework, we benchmark eight state-of-the-art LLMs, uncovering subtle behavioral shortcomings that conventional single-turn evaluations fail to reveal.

Our MedKGEval framework stands out for its flexibility and scalability. By leveraging subgraph extraction from the knowledge graph, MedKGEval can be effortlessly adapted to a wide range of medical tasks beyond disease diagnosis and medication consultation, such as treatment planning and postoperative management. Looking ahead, MedKGEval can also be integrated into reinforcement learning (RL) architectures for medical LLMs, automatically generating challenging prompts and providing reward signals. This integration has the potential to further enhance the multi-turn reasoning and dialogue capabilities of medical LLMs, driving ongoing improvements in both reliability and safety.

7 Limitations

Our current approach only covers two specific application scenarios, Medication Consultation and Disease Diagnosis. Although these domains are important, the method could be extended to incorporate a broader spectrum of knowledge contained in the medical knowledge graph, such as surgical decision making and other real-world clinical applications. Future work will focus on extending our approach to cover more complex healthcare scenarios and multi-language medical knowledge graphs to further enhance applicability and robustness.

References

Rahul K. Arora, Jason Wei, Rebecca Soskin Hicks, Preston Bowman, Joaquin Quiñonero-Candela, Foivos Tsimpourlas, Michael Sharman, Meghan Shah, Andrea Vallone, Alex Beutel, Johannes Heidecke, and Karan Singhal. 2025. Healthbench: Evaluating large language models towards improved human health. *Preprint*, arXiv:2505.08775.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, and 12 others. 2020. Language models are few-shot learners. In *Advances in Neural Information Processing Systems*, volume 33, pages 1877–1901. Curran Associates, Inc.

Odma Byambasuren, Yunfei Yang, Zhifang Sui, Damai Dai, Baobao Chang, Sujian Li, and Hongying Zan. 2019. Preliminary study on the construction of chinese medical knowledge graph. *Journal of Chinese Information Processing*, 33(10):1–9.

Payal Chandak, Kexin Huang, and Marinka Zitnik. 2023. Building a knowledge graph to enable precision medicine. *Scientific Data*, 10(1):67.

Jianlyu Chen, Shitao Xiao, Peitian Zhang, Kun Luo, Defu Lian, and Zheng Liu. 2024. M3-embedding: Multi-linguality, multi-functionality, multi-granularity text embeddings through self-knowledge distillation. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 2318–2335, Bangkok, Thailand. Association for Computational Linguistics.

Junying Chen, Zhenyang Cai, Ke Ji, Xidong Wang, Wanlong Liu, Rongsheng Wang, and Benyou Wang. 2025. Towards medical complex reasoning with LLMs through medical verifiable problems. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 14552–14573, Vienna, Austria. Association for Computational Linguistics.

Kaustubh Deshpande, Ved Sirdeshmukh, Johannes Baptist Mols, Lifeng Jin, Ed-Yeremai Hernandez-Cardona, Dean Lee, Jeremy Kritz, Willow E. Primack, Summer Yue, and Chen Xing. 2025. Multi-Challenge: A realistic multi-turn conversation evaluation benchmark challenging to frontier LLMs. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 18632–18702, Vienna, Austria. Association for Computational Linguistics.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, and 542 others. 2024. The llama 3 herd of models. *Preprint*, arXiv:2407.21783.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Peiyi Wang, Qihao Zhu, Runxin Xu, Ruoyu Zhang, Shirong Ma, Xiao Bi, Xiaokang Zhang, Xingkai Yu, Yu Wu, Z. F. Wu, Zhibin Gou, Zhihong Shao, Zhuoshu Li, Ziyi Gao, Aixin Liu, and 175 others. 2025. Deepseek-r1 incentivizes reasoning in llms through reinforcement learning. *Nature*, 645(8081):633–638.

Katharina Jeblick, Balthasar Schachtner, Jakob Dexl, Andreas Mittermeier, Anna Theresa Stüber, Johanna Topalis, Tobias Weber, Philipp Wesp, Bastian Oliver Sabel, Jens Ricke, and 1 others. 2024. Chatgpt makes medicine easy to swallow: an exploratory case study on simplified radiology reports. *European radiology*, 34(5):2817–2825.

Pengcheng Jiang, Cao Xiao, Minhao Jiang, Parminder Bhatia, Taha Kass-Hout, Jimeng Sun, and Jiawei Han. 2025. Reasoning-enhanced healthcare predictions with knowledge graph community retrieval. In *The Thirteenth International Conference on Learning Representations*.

Di Jin, Eileen Pan, Nassim Oufattole, Wei-Hung Weng, Hanyi Fang, and Peter Szolovits. 2021. What disease does this patient have? a large-scale open domain question answering dataset from medical exams. *Applied Sciences*, 11(14):6421.

Shreya Johri, Jaehwan Jeong, Benjamin A Tran, Daniel I Schlessinger, Shannon Wongvibulsin, Leandra A Barnes, Hong-Yu Zhou, Zhuo Ran Cai, Eliezer M Van Allen, David Kim, and 1 others. 2025. An evaluation framework for clinical use of large language models in patient interaction tasks. *Nature medicine*, 31(1):77–86.

Wai-Chung Kwan, Xingshan Zeng, Yuxin Jiang, Yufei Wang, Liangyou Li, Lifeng Shang, Xin Jiang, Qun Liu, and Kam-Fai Wong. 2024. MT-eval: A multi-turn capabilities evaluation benchmark for large language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 20153–20177, Miami, Florida, USA. Association for Computational Linguistics.

Dongfang Li, Baotian Hu, Qingcai Chen, Weihua Peng, and Anqi Wang. 2020. Towards medical machine reading comprehension with structural knowledge and plain text. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 1427–1438, Online. Association for Computational Linguistics.

Yusheng Liao, Yutong Meng, Yuhao Wang, Hongcheng Liu, Yanfeng Wang, and Yu Wang. 2024. Automatic interactive evaluation for large language models with state aware patient simulator. *Preprint*, arXiv:2403.08495.

Mianxin Liu, Weiguo Hu, Jinru Ding, Jie Xu, Xiaoyang Li, Lifeng Zhu, Zhian Bai, Xiaoming Shi, Benyou Wang, Haitao Song, and 1 others. 2024. Medbench: A comprehensive, standardized, and reliable benchmarking system for evaluating chinese medical large

language models. *Big Data Mining and Analytics*, 7(4):1116–1128.

OpenAI, :, Aaron Hurst, Adam Lerer, Adam P. Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, Aleksander Mądry, Alex Baker-Whitcomb, Alex Beutel, Alex Borzunov, Alex Carney, Alex Chow, Alex Kirillov, and 401 others. 2024. Gpt-4o system card. *Preprint*, arXiv:2410.21276.

Andrew Sellergren, Sahar Kazemzadeh, Tiam Jaroensri, Atilla Kiraly, Madeleine Traverse, Timo Kohlberger, Shawn Xu, Fayaz Jamil, Cían Hughes, Charles Lau, Justin Chen, Fereshteh Mahvar, Liron Yatziv, Tiffany Chen, Bram Sterling, Stefanie Anna Baby, Susanna Maria Baby, Jeremy Lai, Samuel Schmidgall, and 62 others. 2025. Medgemma technical report. *Preprint*, arXiv:2507.05201.

Karan Singhal, Shekoofeh Azizi, Tao Tu, S Sara Mahdavi, Jason Wei, Hyung Won Chung, Nathan Scales, Ajay Tanwani, Heather Cole-Lewis, Stephen Pfohl, and 1 others. 2023. Large language models encode clinical knowledge. *Nature*, 620(7972):172–180.

Karan Singhal, Tao Tu, Juraj Gottweis, Rory Sayres, Ellery Wulczyn, Mohamed Amin, Le Hou, Kevin Clark, Stephen R Pfohl, Heather Cole-Lewis, and 1 others. 2025. Toward expert-level medical question answering with large language models. *Nature Medicine*, 31(3):943–950.

Matthew Spotnitz, Betina Idnay, Emily R Gordon, Rebecca Shyu, Gongbo Zhang, Cong Liu, James J Cimino, and Chunhua Weng. 2024. A survey of clinicians' views of the utility of large language models. *Applied Clinical Informatics*, 15(02):306–312.

LASA Team, Weiwen Xu, Hou Pong Chan, Long Li, Mahani Aljunied, Ruifeng Yuan, Jianyu Wang, Chenghao Xiao, Guizhen Chen, Chaoqun Liu, Zhaodonghui Li, Yu Sun, Junao Shen, Chaojun Wang, Jie Tan, Deli Zhao, Tingyang Xu, Hao Zhang, and Yu Rong. 2025. Lingshu: A generalist foundation model for unified multimodal medical understanding and reasoning. *Preprint*, arXiv:2506.07044.

Guoxin Wang, Minyu Gao, Shuai Yang, Ya Zhang, Lizhi He, Liang Huang, Hanlin Xiao, Yexuan Zhang, Wanyue Li, Lu Chen, Jintao Fei, and Xin Li. 2025. Citrus: Leveraging expert cognitive pathways in a medical language model for advanced medical decision support. *Preprint*, arXiv:2502.18274.

Yuqing Wang, Yun Zhao, and Linda Petzold. 2023. Are large language models ready for healthcare? a comparative study on clinical language understanding. In *Proceedings of the 8th Machine Learning for Healthcare Conference*, volume 219 of *Proceedings of Machine Learning Research*, pages 804–823. PMLR.

Xuehong Wu, Junwen Duan, Yi Pan, and Min Li. 2023. Medical knowledge graph: Data sources, construction, reasoning, and applications. *Big Data Mining and Analytics*, 6(2):201–217.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao Ge, Haoran Wei, Huan Lin, Jialong Tang, and 41 others. 2025. Qwen3 technical report. *Preprint*, arXiv:2505.09388.

An Yang, Beichen Zhang, Binyuan Hui, Bofei Gao, Bowen Yu, Chengpeng Li, Dayiheng Liu, Jianhong Tu, Jingren Zhou, Junyang Lin, Keming Lu, Mingfeng Xue, Runji Lin, Tianyu Liu, Xingzhang Ren, and Zhenru Zhang. 2024a. Qwen2.5-math technical report: Toward mathematical expert model via self-improvement. *Preprint*, arXiv:2409.12122.

Rui Yang, Haoran Liu, Edison Marrese-Taylor, Qingcheng Zeng, Yuhe Ke, Wanxin Li, Lechao Cheng, Qingyu Chen, James Caverlee, Yutaka Matsuo, and Irene Li. 2024b. KG-rank: Enhancing large language models for medical QA with knowledge graphs and ranking techniques. In *Proceedings of the 23rd Workshop on Biomedical Natural Language Processing*, pages 155–166, Bangkok, Thailand. Association for Computational Linguistics.

Kaiwen Zuo, Yirui Jiang, Fan Mo, and Pietro Lio. 2025. Kg4diagnosis: A hierarchical multi-agent llm framework with knowledge graph enhancement for medical diagnosis. In *AAAI Bridge Program on AI for Medicine and Healthcare*, pages 195–204. PMLR.

A Implementation Details: Prompts and Scoring Rubrics

To ensure the reproducibility and extensibility of the MedKGEval framework, this appendix provides detailed examples of the system prompts for the four core agents (Doctor, Patient, Director, and Judge) as well as the comprehensive scoring rubrics employed by the Judge Agent. Each agent relies on structured and modular prompts to fulfill its specific role within the pipeline.

A.1 Scoring Rubrics

The Judge Agent evaluates the Doctor Agent's responses using a tailored, multi-dimensional scoring system. Table 7 details the specific rubrics across the Medication Consultation and Disease Diagnosis scenarios, designed to capture both the factual reliability and the clinical reasoning process of the evaluated LLMs.

A.2 Agent Prompts

The following figures illustrate the core system prompts used to instantiate the specialized agents. These prompts are designed to be modular, ensuring that the pipeline can be easily extended to other medical domains or languages.

Table 7: Scoring rubric for Judge Agent across Medication Consultation and Disease Diagnosis.

Task	Score	Criteria Description
Drug Accuracy	0	All key facts incorrect; content contradicts medical knowledge.
	1	Mixed correctness; some key facts incorrect, others accurate.
	2	Fully accurate; all key facts align with reference.
Drug Comprehensiveness	0	Omits all relevant information.
	1	Includes partial relevant info; misses minor but meaningful points.
	2	Fully covers all user-query-relevant information.
Disease Correctness	0	Diagnosis is clinically unrelated to ground truth (no symptom, cause, or taxonomy overlap).
	1	Clinically similar but no ontological relation (e.g., symptom overlap but different categories).
	2	Ontologically related (e.g., parent-child disease, shared mechanism).
	3	Exact match or clinical synonym.
Disease History-taking	0	Collected info is irrelevant; cannot support any differential diagnosis.
	1	Partial core info collected; misses discriminative/exclusionary features.
	2	Structured inquiry; covers key disease-specific features.

A.2.1 Doctor Agent

The system prompt for the Doctor Agent defines the physician's behavior within different task environments, encompassing specific instructions for symptom gathering and specifications for dialogue conduct.

A.2.2 Patient Agent

The Patient Agent's system prompt defines the behavioral patterns and communication tones of the simulated patient across different task environments. It is designed to generate patient descriptions and inquiries that align with realistic clinical scenarios.

A.2.3 Director Agent

The Director Agent's system prompt is utilized to control scenario logic and knowledge retrieval strategies, coordinating the interaction behaviors of various agents across different task environments. The prompt templates encompass two types of tasks—Disease Diagnosis and Medication Consultation—as well as sub-scenarios including role configuration and symptom screening logic. These are designed to guarantee the overall medical rationality and dynamic pacing of the evaluation.

A.2.4 Judge Agent

The Judge Agent's system prompt defines the scoring criteria and parsing logic for model outputs. It is used to automatically assess the accuracy and comprehensiveness of the Doctor Agent's responses in both Medication Consultation and Disease Diagnosis tasks, thereby enabling fine-grained, objective scoring.

B Model Descriptions

Table 8 provides a brief overview of the eight evaluated models, including model size, training type (general vs. medical-specific), and open-source status. This serves to contextualize performance differences observed in Section **Experiments**.

GPT-4o. (OpenAI et al., 2024) A proprietary general-purpose LLM by OpenAI, GPT-4o offers advanced multilingual language understanding and multimodal capabilities. Though not open source, it represents a strong benchmark for clinical evaluation performance.

Qwen3-235B-A22B. (Yang et al., 2025) An open-source general LLM developed by Alibaba Cloud, Qwen-72B and its variants (including 235B) are trained on over 2–3 trillion tokens across multiple languages and domains. It supports long-context inputs and achieves strong performance in reasoning, translation, and general NLP tasks.

LLaMA3.1-70B. (Grattafiori et al., 2024) A general-purpose open LLM from Meta, LLaMA3.1 demonstrates high performance on reasoning, code completion, and conversational tasks, widely used in research and benchmarking.

DeepSeek-R1-671B. (Guo et al., 2025) Developed by DeepSeek AI, DeepSeek-R1 (67B) is an open-source reasoning-focused model using MoE and RLHF-style training. It achieves competitive results in clinical decision support tasks (e.g., USMLE), math, and code while maintaining efficient inference capacity.

Prompt Template (Doctor Agent, System Prompt, English)

Disease Diagnosis

You are a professional large model specializing in the healthcare field. Your core responsibility is to assist users in accurately solving various medical and health-related issues using professional medical knowledge. To provide users with more precise, specific, and personalized disease diagnosis solutions, you may use concise questioning to collect more necessary information from users. Specific requirements are as follows:
- Your main task is disease diagnosis. Each time, you will receive the patient's query and historical conversation records. You need to determine whether the current information is sufficient to directly provide a diagnosis based on the user's query and historical conversation.
- If the information is insufficient, ask a short question without line breaks and not repeated in the historical conversation, to obtain more critical information through different questions, avoiding confusion for the patient.
- If there is enough information, directly provide a brief final diagnosis. The response must start with "Final Diagnosis:" and include 1-3 possible diagnostic results, no more than 3, otherwise, you will be penalized.

Drug Recommendation

You are a professional large model specializing in the healthcare field. Your core responsibility is to assist users in accurately solving various medical and health-related issues using professional medical knowledge. You can directly answer user questions or use concise questioning to collect more necessary information from users. Specific requirements are as follows:
- Each time, you will receive the patient's query and historical conversation records. You need to determine whether the current information is sufficient to directly provide an answer based on the user's query and historical conversation.
- If the information is insufficient, ask a short question without line breaks and not repeated in the historical conversation, to obtain more critical information through different questions, avoiding confusion for the patient.
- If there is enough information, directly provide the answer.

Figure 5: System Prompt for the Doctor Agent (English).

Prompt Template (Patient Agent, System Prompt, English)

Disease Diagnosis

1. You are the patient; remember your identity; just answer the doctor's questions and engage in normal conversation.
2. Only describe the symptoms given to you, and do not describe other symptoms; if the information provided is insufficient to answer the doctor's question, say that you are unsure, and do not make things up.
3. Do not over-speculate or make assumptions about your condition.

Drug Recommendation

1. You are the patient; remember your identity; just answer the doctor's questions and engage in normal conversation.
2. Only ask questions related to the selected drug, and do not elaborate unnecessarily; if the information provided is insufficient to answer the doctor's question, say that you are unsure, and do not make things up.
3. Do not over-speculate or make assumptions about your condition.

Figure 6: System Prompt for the Patient Agent (English).

Prompt Template (Director Agent, Disease Diagnosis, English)

Your role is to guide my patients on how to answer the doctor's questions. You will know the patient's true disease and all their symptoms, but you cannot disclose the true disease to the patient. Based on your professional knowledge, you should describe the manifestation of symptoms in detail according to the true disease to help the patient respond to the doctor's inquiries.
Points to note:
1. Only describe the details of the symptoms specifically asked by the doctor in the last round of questioning, and ensure the descriptions revolve around the symptoms associated with the true disease.
2. Your guidance should be concise, without excessive elaboration or examples!!!!!!!
I will provide the historical dialogue between the patient and the doctor.
Examples are as follows:
Input:
```
{{
    "mode": "disease_diagnosis",
    "conversation": [
        {
        "turn": 1,
        "patient": "Doctor, I've been having headaches and palpitations recently.",
        "doctor": "Can you specify where the headache is located? Is it around the temples, at the back of the head, or all over? Also, is the pain a throbbing sensation like a blood vessel pulsating, or more like a tight band squeezing your head?"
        "revealed_symptoms": ["Headache","Palpitations"]
        },
        {
        "turn": 2,
        "revealed_symptoms": ["Headache","Palpitations","Vomiting"]
        }
    ],
    "disease": "Hypertension",
    "all_symptoms": ["Headache","Palpitations","Dizziness","Fatigue","Increased nocturia","Neck stiffness","Hyperreflexia","Vomiting"]
}}
```

Output:

The headache is mainly at the back of the head, but sometimes I feel a little pain around the temples. This pain feels more like a throbbing sensation, not a tight band-like pressure.

Example ends

Figure 7: Director Agent System Prompt (Disease Diagnosis Task, English).

Figure 8: Director Agent System Prompt (Medication Consultation Task, English).

Figure 9: Director Agent System Prompt (Role Setting Template, English).

Figure 10: Director Agent System Prompt (Symptom Screening Logic, English).

Prompt Template (Judge Agent, Disease Diagnosis, English)

Task Description:
You are a medical expert, and your task is to evaluate the diagnostic process in the "model's output" from a medical professional perspective. You will assign scores across two dimensions, ensuring that each dimension contains only one number. The following information will be provided sequentially:
Doctor-Patient Conversation Record (history): Where "patient" refers to the patient's questions, and "doctor" refers to the model's output.
Patient's True Disease Ground Truth (disease): The reference answer indicating the disease the patient actually has.
Patient's Symptoms (symptoms): The current symptoms exhibited by the patient.
Your scoring criteria consist of two dimensions, and you must strictly follow the requirements below for scoring.
Scoring Criteria (scoring method for each dimension):
Accuracy
Core Requirement: Based on the reference answer (the patient's true disease, i.e., disease ground truth), assess the medical accuracy of the model's response. Focus on the logical relationship between the final diagnostic conclusion and the target disease. If the final diagnosis includes multiple diseases, only consider the one most closely related to the target disease.
0 points: The final diagnostic conclusion is unrelated to the reference disease (no hierarchical, causal, or clinical similarity).
Example: Reference Answer: Pneumonia ❌ Model Diagnosis: "Asthma"
1 point: The final diagnostic conclusion shows clinical similarity but lacks a hierarchical relationship with the reference disease (must share primary symptoms/signs but belong to different disease categories).
Example: Reference Answer: Pharyngitis ❓ Diagnosis: "Acute Tonsillitis" (both exhibit sore throat/fever symptoms but differ anatomically)
2 points: The final diagnostic conclusion is in a direct hierarchical relationship with the reference disease (subclass/superclass disease, with consistent pathological mechanisms).
Example: Reference Answer: Pharyngitis ✅ Diagnosis: "Streptococcal Pharyngitis" (a subclass of pharyngitis)
3 points: The final diagnostic conclusion is completely consistent with the reference answer or is a synonym (e.g., "Myocardial Infarction" vs. "Heart Attack").
Example: Reference Answer: Gastroesophageal Reflux Disease ✅ Diagnosis: "Gastroesophageal Reflux Disease"
History-Taking Ability
Evaluate the model's ability to collect the patient's medical history during the response process.
0 points: The information collected by the model cannot support any differential diagnosis:
Only asks about irrelevant symptoms (e.g., "Do you have a rash?").
1 point: The model collects some core information but has the following issues:
Fails to capture specific indicators for the target disease (e.g., not asking about "sputum characteristics" in pneumonia cases) or exclusion indicators (e.g., not asking about "the association between chest pain and breathing" to rule out pulmonary embolism).
2 points: The model fully covers the following information through structured questioning:
Diagnostic elements of the target disease (e.g., nature of cough, fever pattern, lung auscultation in pneumonia);
Important exclusion indicators for differential diseases (e.g., low-grade fever and night sweats for tuberculosis, orthopnea for heart failure).
Relevance Explanation
Definition of Diagnostic Hierarchical Relationships:
Subclass diseases must fall under the same pathological mechanism but represent a more specific type (e.g., "Community-Acquired Pneumonia" → "Pneumococcal Pneumonia"). If the reference answer is "Pneumonia," diagnosing "Bronchitis" would be considered unrelated (different anatomical location).
Key Points for History-Taking:
The information collected must demonstrate diagnostic relevance. For example, for suspected myocardial infarction patients, it is essential to include targeted information such as "radiation of chest pain" and "response to nitroglycerin", rather than broadly asking "whether there is insomnia."
Below is the history to be evaluated, where "patient" refers to the user's dialogue, "doctor" refers to the model's response, along with the patient's true disease (disease ground truth) and their symptoms (symptoms):
Doctor-Patient Conversation History:\n{history_now}
Patient's True Disease Ground Truth: {disease}
Patient's Symptoms: {symptoms}
Please analyze first, then provide your evaluation results in the following JSON format:
{'Accuracy':'0-2', 'Reason for Accuracy Score':'Please provide the reason for the accuracy score', 'History-Taking Ability':'0-2', 'Reason for History-Taking Ability Score':'Please provide the reason for the history-taking ability score'}

Figure 11: Judge Agent System Prompt (Disease Diagnosis Scoring, English).

Prompt Template (Judge Agent, Medication Consultation, English)

Task Description:
You are a medical expert, and your task is to evaluate the medication-related responses in the "model's output" based on the given information, using a medical professional perspective. You will assign scores across two dimensions, and each dimension should contain only one number. The following information will be provided sequentially:
Question (query): The input received by the model.
Model's Output (response): The content that needs to be scored.
Reference Answer (gt): The relevant medical reference information for the current input.
Your scoring criteria consist of two dimensions, and you must strictly follow the instructions below:
Scoring Criteria (for each dimension):
Accuracy
Evaluate whether there are any medical errors in the model's response. This can be judged based on the provided reference answer, similar to assessing the precision of the model's medical content compared to the reference answer.
0 points: The model's response is completely inconsistent with medical facts, all key information is incorrect, and no part aligns with the reference answer.
1 point: Part of the model's response contains medical errors; some key information does not match the reference answer, but there are still some correct parts.
2 points: The model's response is fully consistent with medical facts; all key information matches the reference answer without any medical errors.
Comprehensiveness
Evaluate whether the model's response is comprehensive. This judgment should consider both the query and the provided reference answer (gt). If the user's query only asks about part of the reference answer, only the corresponding part of the reference answer needs to be assessed, and the model doesn't need to address unrelated information. This is similar to assessing the recall rate of the model's medical content regarding the query-relevant reference answer.
0 points: The model's response fails to include any key information from the reference answer related to the user's query, resulting in an incomplete expression of core ideas.
1 point: The model's response includes some key information from the reference answer related to the user's query but omits some secondary yet relevant information.
2 points: The model's response covers all key information from the reference answer related to the user's query, with no omission of critical details. Minor irrelevant information can be ignored, and the response comprehensively expresses the relevant viewpoints.
Below is the user query, the model's response, and the current reference answer (gt):
query:{query}
response:{response}
gt:{gt}
Please analyze first and then provide the evaluation results in the following JSON format:
{'Accuracy':'0-2','Reason for Accuracy Score':'Please provide the reason for the accuracy score','Comprehensiveness':'0-2','Reason for Comprehensiveness Score':'Please provide the reason for the comprehensiveness score'}

Figure 12: Judge Agent System Prompt (Medication Consultation Scoring, English).

Table 8: Summary of Evaluated Models

Model	Size	Domain	Open Source
GPT-4o	-	General	NO
Qwen3-235B-A22B	235B	General	YES
LLaMA3.1-70B	70B	General	YES
DeepSeek-R1-671B	671B	General	YES
Citrus-Qwen-72B	72B	Medical	YES
HuatuoGPT-o1-72B	72B	Medical	YES
Lingshu-32B	32B	Medical	YES
MedGemma-27B	27B	Medical	YES

Citrus-Qwen-72B. (Wang et al., 2025) A medical-specialized LLM built upon the Qwen-72B backbone, Citrus is fine-tuned on synthetic expert reasoning datasets to emulate clinician decision pathways. It is designed explicitly for medical diagnosis and treatment recommendation tasks.

HuatuoGPT-o1-72B. (Chen et al., 2025) A publicly released medical-focused LLM with 72B parameters, trained on medical dialogue and QA corpora. While domain-specific data increases its symptom recall, peer public documentation is limited; it is included as representative of instruction-tuned Chinese medical models.

Lingshu-32B. (Team et al., 2025) A 32B-parameter Chinese medical LLM, emphasizing lightweight inference and deployment. Designed for clinical consultation and triage, it reflects trade-offs between size and domain specialization in resource-constrained settings.

MedGemma-27B-text-it. (Sellergren et al., 2025) An open-source 27B-parameter model developed by Google Health, optimized exclusively on medical text (no image modality). MedGemma is tailored for clinical reasoning, report generation, triaging and medical summarization, and has shown strong generalization in health AI benchmarks.

C Additional Experimental Results

In this section, we report detailed experimental breakdowns not included in the main text due to space constraints.

C.1 Turn-level Analysis in English Scenarios

Figure 13 illustrates the distribution of Correctness and History-taking scores relative to the number of dialogue turns in the English disease diagnosis task. Consistent with the quantitative results in the main text, **LLaMA3.1-70B** demonstrates robust performance across multi-turn interactions, maintaining high scores in both correctness and history-taking as dialogues progress.

In contrast, **DeepSeek-R1-671B** exhibits a distinct behavior characterized by premature diagnostic closure in English. As shown by the large circles in the early turns of Figure 13, a significant portion of its dialogues terminate after only 1–2 turns (average 1.11 turns), leading to insufficient information gathering and lower history-taking scores compared to the Chinese setting. This visualization highlights the cross-lingual behavioral gap, where models proficient in one language may struggle to maintain the same depth of clinical inquiry in another.

C.2 Patient Agent Consistency Analysis

To ensure fair and reproducible evaluations, we assess the consistency of candidate Patient Agents—**QwQ-32B**, **Qwen3-32B**, and **DeepSeek-R1-32B**—by computing the average pairwise similarity of their responses to the same Doctor Agent prompts. We use bge-m3 embeddings to quantify semantic similarity. As shown in Table 9, **QwQ-32B** exhibits the narrowest variance and highest average similarity, indicating robust and stable behavior.

Table 9: Average embedding similarity scores for Patient Agent candidates.

Model	Avg. Similarity Score
QwQ-32B	**0.8353**
Qwen3-32B	0.8184
DeepSeek-R1-32B	0.8088

Figure 13: Correctness (a) and History taking scores (b) of eight models in an English disease-diagnosis scenario at different turn counts. Larger circles indicate more cases that ended the dialogue at that turn and received the corresponding score.