Multilayer Neuromodulated Architectures for Memory-Constrained Online Continual Learning

Abstract

In this work we focus on the problem of how to achieve online continual learning under memory-constrained conditions where the input data may not be known *a priori*. These are restrictions that are expected in edge computing scenarios. We have developed an architecture where processing and online learning over data streams are integrated in a single recurrent network architecture. This allows us to cast metalearning optimization as a mixed integer optimization problem, where different synaptic plasticity algorithms and feature extraction layers can be swapped out and their hyperparameters optimized to identify optimal architectures for different sets of tasks. We utilize a Bayesian optimization method to search over a design space that spans multiple learning algorithms, their specific hyperparameters, and feature extraction layers. We demonstrate our approach for online non-incremental (MNIST, F-MNIST, E-MNIST) and class-incremental learning for the Split-MNIST and Permuted-MNIST assays. Our optimization algorithm finds configurations that achieve superior continual learning performance on Split-MNIST and Permuted-MNIST data as compared to other memory-constrained learning approaches and matches that of the state-of-the-art memory replay-based approaches without explicit data storage and replay. Our approach allows us to explore the transferability of optimal learning conditions to tasks and datasets that have not been previously seen. We demonstrate that the accuracy of our transfer metalearning across datasets can be largely explained through a transfer coefficient that can be based on metrics of dimensionality and distance between datasets.

---

[1]Anonymous Institution, Anonymous City, Anonymous Region, Anonymous Country. Correspondence to: Anonymous Author <anon.email@domain.com>.

Preliminary work. Under review by the International Conference on Machine Learning (ICML). Do not distribute.

1 Introduction

The ability to learn and generalize from a few examples is present on a wide range species, from the fruit fly to humans. It is therefore not surprising that biological systems have served as inspiration for the exploration of continual or incremental learning. How to achieve the right balance between plasticity and consolidation, and therefore how to avoid catastrophic forgetting, has long been one of the central areas of research in the area of continual learning. However, the design of systems intended for edge computing brings up an additional set of questions and constraints, such as how to design systems that have to learn inputs that are not known during the design phase, how to achieve high accuracy when the system has no external way of replaying data (i.e. stream processing), or what is the trade-off between performance and size.

These resource constraints may cause performance penalties with respect to online and continual learning strategies that are not bounded by memory, and that keep a detailed record of past performance and data. On the other hand, these constraints are also present in biological systems, but they excel in many continual learning tasks. Neuro-inspired approaches can therefore provide useful insights that complement other machine learning approaches.

One of the salient features of the central nervous systems is its heterogeneity in terms of architecture, types of neurons, and neurochemistry, including where, when, and how learning takes place within the brain. If we focus on synaptic plasticity mechanisms, there is a wide diversity not only on the hyperparameters of a specific mechanism or on where learning takes place, but in the nature of the synaptic plasticity mechanism itself. For instance, while Hebbian rules and spike timing dependent plasticity have attracted the bulk of the attention in the machine learning and neuromorphic computing communities, it is well known that anti-Hebbian and non-Hebbian rules abound (Dayan, 2001). For instance, in some key learning centers it has been shown that synaptic plasticity is independent of post-synaptic activity. Moreover, variations in the local learning rules have been found even in areas that are otherwise morphologically equivalent, but that are assigned to different tasks. It becomes apparent that, if

we want to develop robust continual learning approaches, we need to pay attention to this diversity, and develop a better understanding of the interplay between these heterogeneity and continual learning across very different tasks, which is often overlooked in continual learning across diverse tasks.

To this end, we make the following contributions:

- We propose a neuromorphic architecture which consists of multiple layers for feature extraction and neuromodulated supervised learning, can incorporate diverse synaptic plasticity mechanisms, and hence is capable of online continual learning without explicit data storage and replay.

- We cast the problem of metalearning task-specific architecture choice as a mixed integer black-box optimization problem and develop a technique based on transfer coefficients to explain the accuracy differences when the metalearned configurations are transferred across datasets and tasks

- We evaluate our approach in an online non-incremental learning and class-incremental learning scenarios and demonstrate that the accuracy values are on par with the shallow networks in the former scenario, and outperform other memory-free continual learning approaches while obtaining accuracies similar to the memory-replay based approaches without memory overhead in the later scenario.

2   Multilayer Neuromodulated Architecture

In this work we consider multilayer, recurrent architectures integrating both processing and learning into the networks as shown in Fig. 1.

Figure 1: Multilayer neuromodulated architecture that consists of feature extraction and neuromodulated learning layers that incorporate synaptic plasticity mechanisms through local learning rules.

2.1   Processing component

The processing component comprises a feed-forward neural network. Conceptually we have divided the network in two components:

Feature extraction layers: In this work we have focused on a feature extraction layer based on sparse projection (SPARSE) of the N-dimensional input into a much larger M-dimensional space. Each neuron receives K inputs, with $K \ll N$. In addition, dynamic thresholding followed by rectification ensures that only the most salient features are included in the representation:

$$\mathbf{v} = \text{ReLU}\left(W_e \mathbf{u} - \mu - \beta_r^1 \sigma\right) \qquad (1)$$

where W_e is the sparse projection matrix, μ and σ are the mean and standard deviation of the matrix multiplication product $W_e \mathbf{u}$, and β_r^1 is a constant controlling the cutoff. This approach highlights correlations between different input channels, and represents the broadest possible prior for feature extraction, since it does not assume any spatial dependence or correlations between inputs. This layer is similar to that used in previous models inspired in the cerebellum and the mushroom body, two of the biological instances of this architecture (Litwin-Kumar et al., 2017). A key distinction is that W_e, K, and β_r^1 can all be adjusted through our optimization algorithm.

Neuromodulated learning layer: This comprises one or more layers where supervised learning occurs. Synaptic weights are treated as first-class network elements that can be updated in real time using a series of local learning rules codified in the learning component.

2.2   Learning component

The learning component comprises the recurrent version of the network, implementing local learning rules. These local learning rules are defined as functions:

$$W_l(t+1) = F\left(W_l(t), \mathbf{x}_e, \mathbf{x}_o, \mathbf{x}_m; \beta^l\right), \qquad (2)$$

where W represents the synaptic weights, $\mathbf{x}_e$ and $\mathbf{x}_o$ are the presynaptic and postsynaptic activities, and $\mathbf{x}_m$ represents a vector of modulatory signals controlling learning in real time, and β^l represents a discrete number of hyperparameters that are specific of a given learning rule. By using a consistent interface, we can swap out learning rules without having to further modify our architecture. This allows us to treat metalearning as a combined architecture + hyperparameter optimization process.

The architecture receives real time feedback on its performance while learning (i.e. the label). The modulatory component transforms this feedback into the modulatory signals that are fed into the local learning rules. Here, we use the following synaptic plasticity rules:

- *Generalized Hebbian model (GEN):* the generalized Hebbian model is a modulated version of the covariance rule commonly used in neuroscience. The synaptic weight

evolution is given by:

$$\tau \frac{dW_l}{dt} = \mathbf{x}_m(\mathbf{x}_e - \beta_1^l)(\mathbf{x}_o - \beta_2^l) \quad (3)$$

It has long been known that this rule is unstable, and that clamping of a regularization mechanism needs to be included to keep the synaptic weights bounded. This rule is at the core of some of the neuromodulation-based approaches recently developed.(Miconi et al., 2018)

- *Oja rule (OJA):* a modification of the basic Hebb's rule providing a normalization mechanisms through a first order loss term:(Oja, 1982)

$$\tau \frac{dW_l}{dt} = \mathbf{x}_m(\mathbf{x}_e \mathbf{x}_o - \beta_1^l x_o^2 W_l) \quad (4)$$

- *MSE, non-Hebbian rule:* We have introduced this rule based on recent experimental results on synaptic plasticity mechanisms in the mushroom body. The key assumptions are that learning is independent of postsynaptic activity, and that instead post-synaptic activity modulates regulates synaptic plasticity:

$$\tau \frac{dW_l}{dt} = (\mathbf{x}_m - \mathbf{x}_o)\mathbf{x}_e \quad (5)$$

This rule is consistent with the MSE cost function used in stochastic gradient descent methods.

These are just a few of the many non-equivalent possible formulations of synaptic plasticity rules. In this work, we have treated these models as categorical variable that can be swapped during the metalearning optimization process. Moreover, we have added two additional conditions that allow us to externally tune the learning rate as a function of time, and to provide symmetric or positive clamping of the synaptic weights in order to prevent instabilities in the algorithms.

2.3 Mixed-Integer Optimization Framework

The parameter space in the proposed multilayer neuromodulated architecture is composed of categorical variables (e.g., the selection of the local learning rule), integer parameters (e.g., the dimension of hidden layer), and continuous parameters in each of the learning rule. Hence, we adopt a parallel asynchronous model based search approach (AMBS) (Balaprakash et al., 2018) to find the optimal parameter configuration in this mixed (categorical, continuous, integer) search space. Our AMBS approach adopts an asynchronous Bayesian optimization method (Shahriari et al., 2016) that consists of sampling a number of parameter configurations and progressively fitting a surrogate model over the parameter configurations' accuracy metric space. This surrogate model is asynchronously updated as new configurations

are being evaluated by the parallel processes, which are then used to obtain configurations that will be subsequently evaluated in the next iteration.

Crucial to the optimization approach is the choice of the surrogate model, as this model generates the configuration to evaluate in the mixed search space. Hence, we adopt the *random forest* approach model that is able to build efficient regression models on this search space. Random forest is an ensemble learning approach that builds multiple decision trees and uses bootstrap aggregation (or bagging) to combine them to produce a model with better predictive accuracy and lower variance. Another key choice for the AMBS approach is the acquisition function, which encapsulates criteria to choose the most promising configurations to evaluate next. Hence, the acquisition function is key to maintain the exploration-exploitation balance during the search. We adopt the *Lower Confidence Bound* (LCB) acquisition function and set the kappa to a large value, which increases exploration. We do so to accommodate the high variability we observed in the accuracy metrics within and across the local learning rules which let them to local minimum when a smaller value of kappa was used.

3 Online and Continual Learning Experiments

In this work, we have focused on a specific type of experiment, in which the system is subject to a stream of data and labels during a predetermined number of epochs. This constitutes a single episode. Through the synaptic plasticity mechanisms implemented in the network, the weights evolve during the episode. At the end of the episode, the system is evaluated against the testing dataset to validate its accuracy. By concatenating multiple episodes involving different tasks and datasets, we can create a curriculum to evaluate the system's ability to carry out continual learning.

The resulting accuracy is the metric that the optimization framework uses to carry out the exploration of the architecture and hyperparameter space and find the optimal configurations. As part of the optimization process, multiple episodes are run for systems with different architectures and specific hyperparameters. In all these cases the system starts from identical starting conditions, so that there is no knowledge transferred between episodes that do not belong to the same curriculum.

We consider two different learning modalities to evaluate the proposed approach:
(a) Non-Incremental Learning: In this scenario, there is a single episode in the curriculum, which has access to all the data and hence performs a single task (e.g., multi-class classification);
(b) Class-Incremental Learning: In this scenario, the

synaptic weights are updated incrementally, where a specific task (e.g., two-class classification) is performed in each episode using data streams from distinct (clearly separated) classes. The curriculum would involve a concatenation of multiple episodes such that the final accuracy measures the model's ability to predict on test data from all the classes, spanning across episodes.

By changing tasks, datasets, and learning modalities, we build a collection of optimal configurations for each type of experiment. We can use these configuration to explore the transferability of optimal learning conditions to other datasets or to different types of tasks.

4 Results and Discussion

We first describe the results obtained in the non-incremental learning scenario, followed by incremental learning scenario results and finally the experiments exploring the transferability of optimal learning conditions to tasks and datasets.

4.1 Non-Incremental Learning

We consider MNIST, Fashion MNIST (Xiao et al., 2017) (F-MNIST), Extended MNIST (Cohen et al., 2017) (E-MNIST) datasets to study the modeling capability and the effect of the proposed multi-layer neuromodulated learning framework in the non-incremental learning scenario. These datasets were chosen due to the homogeneity in image and class sizes and the existence of benchmarks in continual learning. For each data set, we jointly optimize over the local learning rules and their parameters to find the optimal configuration.

In this work we employed SPARSE as feature representation layer, and three supervised learning rules (MSE, GEN, OJA) for label prediction. While there is a difference in the number of parameters in each of the learning rule, the search space is defined to exploit the common parameters, whose dimensionality is defined by the rule with maximum parameters. In addition, only the subset of parameters present in the local-learning rule are active at search time. For example, the parameter β_l^3 defines the weight clamping, and is common to the three rules, the GEN rule has all the parameters $(\beta_l^1, \beta_l^2, \beta_l^3)$ active while MSE has only β_l^3 active, so the other parameters (β_l^1, β_l^2) are set to *None* while exploring the search space. For each configuration evaluated during the optimization, the model is run for 0.5 epochs. The best accuracy obtained, and the corresponding optimal parameters for all the datasets is shown in Table 1. The search trajectory showing the learning rule, test accuracy of the configurations evaluated as a function of time is shown Fig. 2 for MNIST and F-MNIST. In both the cases, the initial configurations range across the different learning rules but the algorithm quickly finds the potential learning rule and evaluates more configurations from it.

(a) MNIST

(b) F-MNIST

Figure 2: Search trajectory obtained for MNIST and F-MNIST datasets from the mixed-integer black-box optimization.

4.2 Incremental Learning

We evaluate our method on the Split-MNIST (Farquhar & Gal, 2018) and Permuted-MNIST (Goodfellow et al., 2013) incremental learning benchmarks that have been extensively adopted in the literature (Shin et al., 2017; Zenke et al., 2017; Nguyen et al., 2017). The Split-MNIST data is prepared by splitting the original MNIST dataset (both training and testing splits) consisting of ten digits into five two-class classification tasks. This defines an incremental learning scenario in which the model sees these five tasks incremental one after the other. The Permuted-MNIST is also prepared from the original MNIST data by permuting the pixels in the images. A unique permutation is applied to all the images in order to generate a new ten-class classification task. The number of distinct permutations applied represents the length of the task sequence. For instance, we adopted a ten-permuted MNIST, which produces ten (ten-class classification) tasks that are sequentially seen by the model. The first task is the original MNIST data while the subsequent nine tasks are obtained by permuting the original data.

Following (Hsu et al., 2018), for Split-MNIST, a simple two layer multi-layered perceptron (MLP) neural network with 400 neurons per layer is adopted to evaluate the baseline accuracy, as well as the accuracy with other incremental

Table 1: Optimal configurations obtained for MNIST, F-MNIST and E-MNIST datasets using the mixed-integer black box optimization approach, where each configuration was evaluated after 0.5 epochs of training.

Dataset	Acc.	Srule	N_H^F	β_1^F	β_2^F	β_3^F	γ^F	α^F	β_1^M	β_2^M	β_3^M	γ^M	α^F
MNIST	96.20	MSE	9000	0.022	0.326	1.658	0.968	0.225	–	–	0.585	0.013	0.260
F-MNIST	94.38	GEN	7000	0.957	0.003	6.025	0.332	0.578	0.083	0.103	0.400	0.810	0.077
E-MNIST	96.41	MSE	9000	0.027	0.306	1.918	0.984	0.678	–	–	0.531	0.189	0.350

Table 2: Classification accuracy in the non-incremental learning scenario for MNIST, F-MNIST and E-MNIST datasets after four epochs using the optimal configurations learned through the optimization framework.

MNIST	F-MNIST	E-MNIST
97.45	94.32	97.34

learning algorithms. Similarly, for Permuted-MNIST, we use two layer MLP with 1000 neurons per layer to evaluate the baseline and other incremental learning algorithm accuracy. See (Hsu et al., 2018) for more details on the hyperparameters used for both these models. First baseline is a naive approach in which the MLP network (with Adagrad optimizer) is trained by progressively updating the parameters through backpropagation as new tasks are observed. The second baseline is a naive rehearsal (experience replay) approach that stores a fraction of data from previous tasks randomly and use that while training incrementally. Among the popular incremental learning approaches, we choose representative ones from regularization-based (Online EWC (Schwarz et al., 2018), SI (Zenke et al., 2017), MAS (Aljundi et al., 2018)) and memory-based methods (GEM (Lopez-Paz & Ranzato, 2017), DGR (Shin et al., 2017), Rtf (van de Ven & Tolias, 2018)). We also compare the non-incremental learning scenario with the corresponding baseline models for both datasets as well as our multilayer neuromodulated learning approach. The results of the incremental learning experiments are shown in Table 3.

For the non-incremental learning case, where the data from all tasks are provided at the same time, the baseline MLP model gives a accuracy of 97.53% and 97.95% for the Split-MNIST and Permuted-MNIST datasets respectively after 4 epochs of training for the former and 10 epochs for the latter, following (Hsu et al., 2018). We use the best performing parameter configuration for MNIST data obtained for the non-incremental learning (Table 1) to evaluate the performance of our architecture in these two datasets. This transfer of parameter configuration from non-incremental to the incremental learning scenario is further discussed in the next section. With this parameter configuration, we found that the accuracy of our model is 97.45 on Split-MNIST trained for 4 epochs and 96.69% on the Permuted-MNIST

trained for just 1 epoch. These values are very close to the MLP model accuracy – 97.53 on Split-MNIST trained for 4 epochs and 97.95% on the Permuted-MNIST trained for 10 epochs .

For the class-incremental learning on Split-MNIST and the Permuted-MNIST, our model (using MNIST parameter configuration from Table 1) significantly outperforms both the baseline and other non-memory based incremental learning approaches considered. In addition, we obtain accuracy comparable to the state-of-the-art memory-based models for Split-MNIST data, and outperform all the other incremental learning algorithms on the Permuted-MNIST data with only three epochs (as compares to ten epochs for all the other algorithms). Its is interesting that the Naive rehearsal approach outperforms all the other approaches, but it of course comes with the additional memory overhead.

4.3 Transferability Study

Identification of the best configuration for each group of classes (a dataset) is based on the assumption that all the data is available at the beginning of the training procedure. However, for many online learning scenarios, both incremental and non-incremental, this configuration might not be known *a priori*. This raises the question of transfer metalearning, how to effectively optimize a learning algorithm to learn unknown tasks and data. To address this problem, we empirically study the effect of transferring optimal configurations tasks for the incremental learning scenario, and across datasets in non-incremental learning case.

Across tasks: The best configuration obtained through the joint optimization on each data set separately (Table 1) is used to evaluate the incremental learning accuracy with Split-MNIST and Permuted-MNIST datasets. The results using the configurations corresponding to MNIST, F-MNIST and E-MNIST are shown in Table 4. We observe that the configuration learned on the MNIST dataset is readily transferable to incremental learning on Split-MNIST and the Permuted-MNIST data as seen in the previous section. The configuration learned with the E-MNIST data leads to an accuracy difference of only 0.71% and 0.50% respectively on these incremental learning datasets. F-MNIST configurations on the other hand leads to an accuracy drop of 0.98% and 4.14% respectively on them. This observation

Table 3: Classification accuracy comparison for the class-incremental learning experiments on Split-MNIST and Permuted-MNIST datasets.

	Method	Split-MNIST	Permuted-MNIST
Non-incremental	MLP	97.53	97.95
	SPA+MSE	97.45	96.69 (1 epoch)
Baseline	Adagrad	19.75	79.50
	Naive rehearsal-C (*)	94.35	97.15
Incremental Learning (*) → Memory-based	Online EWC	19.71	86.57
	SI	20.88	79.36
	MAS	19.98	73.82
	GEM (*)	92.20	96.72
	DGR (*)	91.24	92.19
	Rtf (*)	92.56	96.23
	SPA+MSE	92.76	96.62 (1 epoch)

suggests that the transfer learning configuration (both the local learning rule and it's corresponding parameters) to the incremental learning experiments need to be done carefully, which other wise would lead to sub-optimal accuracy.

Across datasets: In this experiment, we seek to understand and characterize the dependence of dataset similarity (defined as a distance metric) and the transferability of optimal configurations learned on a dataset to other (different) datasets. To this end, we choose the best configuration obtained through the joint optimization on each data set (Table 1) and use that to transfer learn and evaluate the accuracy for the remaining datasets. The results for transfer learning across MNIST, F-MNIST and E-MNIST are summarized in Table 4, where a column represents the accuracy on a particular dataset obtained by transfer learning through the optimal configurations learned on standalone MNIST, F-MNIST and E-MNIST datasets. The diagonal elements are same as the accuracy values obtained previously for four epoch runs with same data-optimal configuration combination (Table 2). We find that the configurations learned on MNIST and the E-MNIST are readily exchangeable without significant loss in accuracy. These configurations however do not transfer well to the F-MNIST dataset as seen by the accuracy decrease of 11.45% and 11.12% respectively with MNIST and E-MNIST. On the other hand, the F-MNIST configurations also lead to decrease in accuracy by 5.53% and 3.75% respectively when transferred to MNIST and E-MNIST data.

Distance metrics as a measure of transferability: In order to rationalize the results shown in Table 4 we have explored the correlation between the drop in performance between datasets and their effective dimensionality and the distance between datasets. Here we have focus on a definitions of dimensionality derived from the covariance matrix of the complete dataset. The eigenvalues of the covariance

matrix yields the principal components of the dataset. Here we have considered as a metric of dimensionality the sum of squares of the eigenvalues (λ), so that:

$$d = (\sum_i \lambda_i)^2 / \sum_i \lambda_i^2 \qquad (6)$$

This metric has been used in the past to characterize sparse representations.(Litwin-Kumar et al., 2017) The interpretation of this metric is that when the variance is equally distributed across all dimensions, Eq. 6 yields a dimension $d = N$, where N is the number of dimensions in the space (784 in this case). If all the variance is concentrated in a single eigenvalue, then $d = 1$.

In order to quantify the distance and separability between categories in the dataset we have used the cosine distance metric. In Table 6 we have applied the traditional definition of distance between two clusters and calculated the minimum distance between any two categories of two datasets. We also show the maximum separation for comparison. When these metrics are used within a given dataset, we obtain the minimum and maximum distance between two categories of the same dataset, which could be interpreted as a measure of separability.

In Figure 3 we have the drop in classification accuracy during transfer metalearning as a function of a *transfer coefficient* obtained from two different metrics: the relative difference in the eigenvalue dimension given by Eq. 6, and the minimum cosine distance between the two datasets. Both values are normalized as:

$$D = |M_1 - M_2| / M_1 \qquad (7)$$

where M_1 is the metric of the dataset selected to run the experiment and M_2 is the metric of the dataset whose optimal configuration is used. Note that this transfer coefficient is

Table 4: Accuracy due to transfer metalearning in class-incremental and non-incremental learning experiments.

Config (↓), Dataset (→)	Non-Incremental Learning			Class-Incremental Learning	
	MNIST	F-MNIST	E-MNIST	SplitMNIST	P-MNIST
MNIST	97.35	82.87	97.69	92.76	96.62
F-MNIST	91.82	94.32	93.59	91.78	92.48
E-MNIST	96.93	83.20	97.34	93.47	96.12

Table 5: PCA metric of dimensionality for each of the datasets (Eq. 6)

Data	MNIST	F-MNIST	E-MNIST
Eigen-Dim	30.69	7.91	27.09

Table 6: Minimum and maximum cosine distances between centroids of the categories of different datasets

Data	MNIST	F-MNIST	E-MNIST
MNIST	(0.073,0.55)	(0.17,0.54)	(0.044,0.59)
F-MNIST		(0.012,0.56)	(0.13,0.57)
E-MNIST			(0.098,0.52)

not symmetric due to the different normalization in Eq. 7, as should be expected since transfer metalearning is directional. The results clearly show that as the distance between the datasets increase, transfer learning the configurations across them lead to decrease in accuracy.

5 Related Work

Incremental learning, also referred to as continual or lifelong learning (Thrun & Pratt, 2012) describes a learning modality in which a model seeks to learn from data and tasks that are sequentially presented to it. Several incremental learning approaches have been developed in the literature, which can loosely be categorized into three classes: (1) Novel neural architectures or customization of the common ones; (2) Regularization strategies that impose constraints to boost knowledge retainment; (3) Meta-learning, that seeks to learn a common parameter configuration using a series of tasks, that is easily adaptable for new tasks. Some algorithms in the first category include bio-inspired dual-memory architecture (Parisi et al., 2019), progressive neural networks (Rusu et al., 2016) that explicitly support information transfer across sequences of tasks through network expansion, deep generative replay (Shin et al., 2017), that proposed a co-operative dual model architecture framework inspired by hippocampus, that retains past knowledge by the concurrent replay of generated pseudo-data. The second category consists of algorithms such as Elastic weight consolidation (EWC) (Kirkpatrick et al., 2017) that computes synaptic importance using a Fisher importance matrix-based regularization, synaptic intelligence (SI) (Zenke et al., 2017),

Figure 3: Drop in classification accuracy during transfer metalearning as a function of a transfer coefficient obtained for PCA metric and minimum cosine distance metric.

whose regularization penalty is similar to EWC, but is computed online at per-synapse level, learning without forgetting (Li & Hoiem, 2017) that applies a distillation loss on the attention-enabled deep networks seeking to minimize task overlap. The third category consists of algorithms such as online meta learning (OML) (Javed & White, 2019), Neuromodulated Meta-Learning Algorithm (ANML) (Beaulieu et al., 2020), and Incremental Task-Agnostic Meta-learning (iTAML) (Rajasegaran et al., 2020) that show great promise, but are not particularly suited for the memory-constrained continual learning scenarios that could be relevant in edge computing. These algorithms are characterized by large network sizes, memory buffer requirements, as well as few restricting assumptions on the structure of the data, hence we do not include a comparison with this class of approaches. The multilayer neuromodulated architecture approach we proposed falls under the first class of continual learning methods discussed earlier.

6 Conclusions

In this work, we developed a multilayer, recurrent neuromorphic architecture capable of online continual learning in memory-constrained setting where large models, and data storage/replay is limited. The proposed architecture consists of a processing component and a learning component, where learning can be viewed as a dynamic process that alters the architecture itself via recurrent interactions as it processes

and assigns valence to certain inputs and create associations over time. Our approach parameterizes multiple synaptic plasticity mechanisms as layers of this network sharing a common interface. This allows us to cast the optimization of the architecture's learning capabilities as an optimization problem, and to employ a Bayesian optimization-based search to find optimal task-specific configurations in the mixed (categorical, continuous) space that spans over the choice of the learning algorithms, their specific hyperparameters and feature extraction layers.

We demonstrate our approach using two different learning scenarios. The first is a non-incremental learning case, where the learning curriculum consists of a episode that has access to all tasks, and the model is updated online as the data streams in. The second is a class-incremental learning scenario, where data from each task are presented sequentially such that each episode in the learning curriculum consists of a unique task. The model is then updated online in each episode and continually with a sequence of these episodes. In the non-incremental learning case, our algorithm identified configurations capable of obtaining online learning accuracies of 97.45 for MNIST, 94.32 for Fashion MNIST, 97.34 for Extended MNIST, which was on par (or outperformed) the performance of static shallow neural networks run for four epochs. The optimal configurations in our architecture were obtained imposing a limit of 0.5 epochs to learn each dataset, which was cheap computationally and led to good configurations. In the class-incremental learning case, we obtained an accuracy of 92.76 and 96.62 on the Split-MNIST and Permuted-MNIST data which consisted of five and ten sequential tasks respectively. Hence, our approach clearly outperformed the memory-free approaches, whose accuracies obtained a maximum of 20.88 and 85.57 respectively. The memory replay-based continual learning approaches gave a maximum accuracy of 92.56 with Rtf and 96.72 with GEM using four and ten epoch of training respectively on the two datasets, while our approach produced an accuracy of 92.76 with four epochs on Split-MNIST and 96.62 with one epoch on Permuted-MNIST. This demonstrates that memoryless approaches such as the one proposed here can achieve performances on par with the memory-replay based approaches used as benchmarks, without the additional memory overhead. This suggests the need to identify more challenging continual learning assays.

Finally, our approach allowed us to explore the transferability of optimal learning conditions across datasets and tasks to understand the interplay between task-heterogeneity and continual learning across very different tasks. We demonstrated through systematic experiments that accuracy of this transfer metalearning to datasets previously not seen can be largely explained through a transfer coefficient that can be based on metrics of dimensionality and distance between datasets.

References

Aljundi, R., Babiloni, F., Elhoseiny, M., Rohrbach, M., and Tuytelaars, T. Memory aware synapses: Learning what (not) to forget. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 139–154, 2018.

Balaprakash, P., Salim, M., Uram, T., Vishwanath, V., and Wild, S. Deephyper: Asynchronous hyperparameter search for deep neural networks. In *2018 IEEE 25th International Conference on High Performance Computing (HiPC)*, pp. 42–51, Dec 2018. doi: 10.1109/HiPC. 2018.00014.

Beaulieu, S., Frati, L., Miconi, T., Lehman, J., Stanley, K. O., Clune, J., and Cheney, N. Learning to continually learn. *arXiv preprint arXiv:2002.09571*, 2020.

Cohen, G., Afshar, S., Tapson, J., and Van Schaik, A. Emnist: Extending mnist to handwritten letters. In *2017 International Joint Conference on Neural Networks (IJCNN)*, pp. 2921–2926. IEEE, 2017.

Dayan, P. *Theoretical neuroscience : computational and mathematical modeling of neural systems.* Computational neuroscience. Massachusetts Institute of Technology Press, Cambridge, Mass., 2001. ISBN 0262041995.

Farquhar, S. and Gal, Y. Towards robust evaluations of continual learning. *arXiv preprint arXiv:1805.09733*, 2018.

Goodfellow, I. J., Mirza, M., Xiao, D., Courville, A., and Bengio, Y. An empirical investigation of catastrophic forgetting in gradient-based neural networks. *arXiv preprint arXiv:1312.6211*, 2013.

Hsu, Y.-C., Liu, Y.-C., Ramasamy, A., and Kira, Z. Re-evaluating continual learning scenarios: A categorization and case for strong baselines. *arXiv preprint arXiv:1810.12488*, 2018.

Javed, K. and White, M. Meta-learning representations for continual learning. In *Advances in Neural Information Processing Systems*, pp. 1818–1828, 2019.

Kirkpatrick, J., Pascanu, R., Rabinowitz, N., Veness, J., Desjardins, G., Rusu, A. A., Milan, K., Quan, J., Ramalho, T., Grabska-Barwinska, A., et al. Overcoming catastrophic forgetting in neural networks. *Proceedings of the national academy of sciences*, 114(13):3521–3526, 2017.

Li, Z. and Hoiem, D. Learning without forgetting. *IEEE transactions on pattern analysis and machine intelligence*, 40(12):2935–2947, 2017.

Litwin-Kumar, A., Harris, K. D., Axel, R., Sompolinsky, H., and Abbott, L. F. Optimal degrees of synaptic connectivity. *Neuron*, 93(5):1153–1164.e7, 2020/06/10 2017. doi: 10.1016/j.neuron.2017.01.030. URL https://doi.org/10.1016/j.neuron.2017.01.030.

Lopez-Paz, D. and Ranzato, M. Gradient episodic memory for continual learning. In *Advances in Neural Information Processing Systems*, pp. 6467–6476, 2017.

Miconi, T., Clune, J., and Stanley, K. O. Differentiable plasticity: training plastic neural networks with backpropagation. *CoRR*, abs/1804.02464, 2018. URL http://arxiv.org/abs/1804.02464.

Nguyen, C. V., Li, Y., Bui, T. D., and Turner, R. E. Variational continual learning. *arXiv preprint arXiv:1710.10628*, 2017.

Oja, E. Simplified neuron model as a principal component analyzer. *Journal of Mathematical Biology*, 15(3):267–273, 1982. doi: 10.1007/BF00275687. URL https://doi.org/10.1007/BF00275687.

Parisi, G. I., Kemker, R., Part, J. L., Kanan, C., and Wermter, S. Continual lifelong learning with neural networks: A review. *Neural Networks*, 2019.

Rajasegaran, J., Khan, S., Hayat, M., Khan, F. S., and Shah, M. itaml: An incremental task-agnostic meta-learning approach. *arXiv preprint arXiv:2003.11652*, 2020.

Rusu, A. A., Rabinowitz, N. C., Desjardins, G., Soyer, H., Kirkpatrick, J., Kavukcuoglu, K., Pascanu, R., and Hadsell, R. Progressive neural networks. *arXiv preprint arXiv:1606.04671*, 2016.

Schwarz, J., Czarnecki, W., Luketina, J., Grabska-Barwinska, A., Teh, Y. W., Pascanu, R., and Hadsell, R. Progress & compress: A scalable framework for continual learning. In *International Conference on Machine Learning*, pp. 4528–4537, 2018.

Shahriari, B., Swersky, K., Wang, Z., Adams, R. P., and De Freitas, N. Taking the human out of the loop: A review of Bayesian optimization. *Proceedings of the IEEE*, 104(1):148–175, 2016.

Shin, H., Lee, J. K., Kim, J., and Kim, J. Continual learning with deep generative replay. In *Advances in Neural Information Processing Systems*, pp. 2990–2999, 2017.

Thrun, S. and Pratt, L. *Learning to learn*. Springer Science & Business Media, 2012.

van de Ven, G. M. and Tolias, A. S. Generative replay with feedback connections as a general strategy for continual learning. *arXiv preprint arXiv:1809.10635*, 2018.

Xiao, H., Rasul, K., and Vollgraf, R. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms. *arXiv preprint arXiv:1708.07747*, 2017.

Zenke, F., Poole, B., and Ganguli, S. Continual learning through synaptic intelligence. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 3987–3995. JMLR. org, 2017.