REPLAY MEMORY AS AN EMPIRICAL MDP: COMBINING CONSERVATIVE ESTIMATION WITH EXPERIENCE REPLAY

ABSTRACT

Experience replay, which stores transitions in a replay memory for repeated use, plays an important role of improving sample efficiency in reinforcement learning. Existing techniques such as reweighted sampling, episodic learning and reverse sweep update further process the information in the replay memory to make experience replay more efficient. In this work, we further exploit the information in the replay memory by treating it as an empirical *Replay Memory MDP (RM-MDP)*. By solving it with dynamic programming, we learn a conservative value estimate that *only* considers transitions observed in the replay memory. Both value and policy regularizers based on this conservative estimate are developed and integrated with model-free learning algorithms. We design the metric *memory density* to measure the quality of RM-MDP. Our empirical studies quantitatively find a strong correlation between performance improvement and memory density. Our method combines *Conservative Estimation with Experience Replay (CEER)*, improving sample efficiency by a large margin, especially when the memory density is high. Even when the memory density is low, such a conservative estimate can still help to avoid suicidal actions and thereby improve performance.

1 INTRODUCTION

Improving sample efficiency is an essential challenge for deep reinforcement learning (DRL). Experience replay (Lin, 1992) stores transitions in a replay memory and reuses them multiple times. This technique plays an important role for the success of DRL algorithms, such as Deep Q-Networks (DQN) (Mnih et al., 2015; Hessel et al., 2018), Deep Deterministic Policy Gradient (DDPG) (Lillicrap et al., 2015; Haarnoja et al., 2018) and AlphaGo (Silver et al., 2016; 2017). DRL algorithms use gradient-based optimizers to incrementally update parameters. The learning is slow and requires several orders of magnitude more training samples than a human learning the same task. To speed up learning, many researchers focus on how to better process information in the replay memory before updating networks, to make experience replay more efficient.

One direction is to measure the importance of transitions and sample transitions with priorities. Criteria of measuring the importance include temporal-difference (TD) error (Schaul et al., 2016), "ages" of transitions [1] (Zhang & Sutton, 2017; Novati & Koumoutsakos, 2019; Sun et al., 2020; Wang et al., 2020; Sinha et al., 2022), errors of target values (Kumar et al., 2020a), the coverage of the sample space (Oh et al., 2021; Pan et al., 2022), etc. Another direction is to analyze the trait of transitions. For examples, learning should start in a backward manner that allows sparse and delayed rewards to propagate faster (Lee et al., 2019); the best episodic experiences can be memorized and supervise the agent during learning (Lin et al., 2018); similar episodes may latch on and provide more information for update (Zhu et al., 2020; Hong et al., 2022; Jiang et al., 2022).

Can we further improve the use of the replay memory? In our work, we consider the Replay Memory as an empirical MDP, called RM-MDP. Solving RM-MDP provides us an estimate that considers all existing transitions in the replay memory, not just single samples or trajectories. The estimate is also conservative because some actions may not be contained in the memory. We propose to use

---

[1]Transitions collected by more recent policies are new, otherwise are old (Fedus et al., 2020).

the conservative estimate $\hat{Q}$ from RM-MDP to regularize the learning of Q network on the original MDP. We design two regularizers, value regularizer and policy regularizer. The value regularizer computes the target value by combining the estimate from $\hat{Q}$ and Q network. For the policy regularizer, we derive Boltzmann policies from $\hat{Q}$ and Q network, and constrains the distance between the two policies using Kullback–Leibler (KL) divergence.

Our contribution is four-fold: (1) We consider the replay memory as an empirical Replay Memory MDP (RM-MDP) and obtain a conservative estimate by solving this empirical MDP. (2) We design value and policy regularizers based on the **C**onservative **E**stimate, and combine them with **E**xperience **R**eplay (CEER) to regularize the learning of DQN algorithm. (3) We design *memory density* to measure the quality of RM-MDP, and find a strong correlation between the performance improvement and memory density. The relationship gives us a clear illustration when our method will help. (4) Experiments on Sokoban (Schrader, 2018), MiniGrid (Chevalier-Boisvert et al., 2018) and MinAtar (Young & Tian, 2019) environments show that our method improve sample efficiency to a large margin especially when the memory density is high. Even if the memory density is low, the conservative estimate can help to avoid suicidal actions and still benefit the learning. Besides, our method is insensitive to environments with sparse and delayed rewards.

2 RELATED WORK.

Reweighted Experience Replay. Experience replay (Lin, 1992) stores transitions in a replay memory and reuses then multiple times. Since DQN (Mnih et al., 2015) replays experiences uniformly to update Q network and achieve human-level performance on Atari games, improving experience replay becomes an active direction. Prioritized Experience Replay (PER) (Schaul et al., 2016) is the first and most famous improvement. It replays important transitions more frequently measured by temporal-difference (TD) error. ReF-ER (Novati & Koumoutsakos, 2019), AER (Sun et al., 2020) and ERE (Wang et al., 2020) find old transitions will hurt the update since current policy is much different from previous one. These methods emphasize sampling more recent transitions. DisCor (Kumar et al., 2020a) aims to provide accurate target values for each update. Transitions sampled from the replay memory are reweighted with weights that are inversely proportional to the estimated errors in their target values. NERS (Oh et al., 2021) emphasizes sample coverage and proposes a learning-based sampling method that considers both local and global contexts.

Experience Replay with Episodic RL. Episodic RL (Blundell et al., 2016; Pritzel et al., 2017; Hansen et al., 2018) designs a separate lookup table to memorize the best experiences that have ever met. EMDQN (Lin et al., 2018) uses the maximum return from episodic memory as target value, this supervised manner compensates the disadvantage of slow learning resulted by single step reward update. ERLAM (Zhu et al., 2020) additionally build a graph on top of state transitions and use it as early guidance . Our method is similar to these methods if we only use the value regularizer. The difference is that our value regularizer computes the target value based on all transitions rather than within each single trajectory, and is also suitable for stochastic environments.

Experience Replay with Reverse Update. Some researchers focus on the sequential character of trajectories (Dai & Hansen, 2007; Goyal et al., 2019). They argue that a state's correct Q value preconditions on the accurate successor states' Q value. EBU (Lin et al., 2018) samples a whole episode and successively propagates the value of a state to its previous states. This assure that at least one transition with a non-zero reward is used for the value update. TER (Hong et al., 2022) further build a graph to remember all the predecessors of each state, then performs update from terminal states successively moving backward via breadth-first search. Our method propagates rewards when solving RM-MDP, thereby the sequential character of trajectories is considered in the regularizers.

3 BACKGROUND

Markov Decision Process (MDP). The interaction of an agent with its environment can be modeled as a MDP $\mathcal{M} = (\mathcal{S}, \mathcal{A}, R, P, \rho_0, \gamma)$. $\mathcal{S}$ is the state space, $\mathcal{A}$ is the action space, $P : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to [0, 1]$ is the environment transition dynamics, $R : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to \mathbb{R}$ is the reward function, $\rho_0 : \mathcal{S} \to \mathbb{R}$ is the initial state distribution and $\gamma \in (0, 1)$ is the discount factor. The goal of the agent is to learn the optimal policy that maximizes the expected cumulative rewards $\mathbb{E}[\sum_{t=0}^{\infty} \gamma^t r_t]$. Q-learning is a classic algorithm to learn the optimal policy. It learns the Q function with Bellman optimality

Figure 1: An overview of our method. Transitions from the interaction with environment constructs RM-MDP, which is part of the environment MDP. Green circles denote states in the memory. The solid lines denote existing transitions, and dashed lines denote transitions not in the memory. We obtain value and policy estimates from RM-MDP, which will be provided to regularize the learning.

equation, $Q^*(s,a) = \mathbb{E}[r + \gamma \max_{a'} Q^*(s',a')]$. The optimal policy is derived by taking the action with maximum Q value at each state. DQN (Mnih et al., 2015) scales up tabular Q-learning using deep neural networks (Goodfellow et al., 2016) and experience replay (Lin, 1992).

Solving Empirical MDP. We treat the replay memory $\hat{M}$ as an empirical *Replay Memory MDP (RM-MDP)*, $\hat{\mathcal{M}} = (\mathcal{S}, \mathcal{A}, R, \hat{P}, \rho_0, \gamma)$. All components are the same as $\mathcal{M}$ except $\hat{P}$. $\hat{P}$ is the empirical transition dynamics summarized from the transitions in $\hat{M}$ collected by behavior policy β. We have $\hat{p}(s,a,s') = 0$ if $\beta(a|s) = 0$. Let $\hat{Q}$ be the action value function of RM-MDP, solving RM-MDP equals to solving the following equation:

$$\hat{Q}^*(s,a) = \mathbb{E}_{(s,a,s')\sim\hat{P}}[r + \gamma \max_{a':\beta(a'|s')>0} \hat{Q}^*(s',a')], \tag{1}$$

where $\hat{Q}^*$ is the optimal action value function for RM-MDP [2]. This is a fundamental problem in offline/batch reinforcement learning (Lange et al., 2012; Levine et al., 2020). The learning goal is to maximize the cumulative rewards but limited within a static dataset, which returns a conservative policy with best possible performance. The constraint avoids distributional shift caused by taking actions outside the dataset when estimates target values. Though the replay memory in online learning is usually a time-changing first in first out queue, at a specific time step, the memory can be considered as a static dataset that contains finite transitions. Thus, solving RM-MDP is similar to offline RL setting that solves an empirical MDP and finally results in a conservative estimate.

4 METHOD

Our intuition is to regularize online RL agents with the conservative estimation from replay memory. Figure 1 shows the overview of our method. We first construct the RM-MDP with transitions in the replay memory. Then we get a conservative estimate by solving RM-MDP. Finally we design value and policy regularizers based on the estimate to help the learning. In Section 4.1, we describe the way to construct the RM-MDP by building the replay memory as a graph. In Section 4.2, we describe the way we solve the RM-MDP. And in Section 4.3, we describe how we design the value and policy regularizers and summarize the whole method.

4.1 GRAPH BUILDING

Since the replay memory is time-changing during online learning, and offline DRL methods usually take tens of thousands of gradient steps to extract a good policy (Fujimoto et al., 2019; Kumar et al., 2020b; Kostrikov et al., 2022). To get quick and stable estimation from RM-MDP, we focus on constructing the replay memory as a graph, which can be solved with tabular methods.

Data structure. As introduced in Section 3, $\hat{M}$ is the replay memory and $\hat{\mathcal{M}} = (\mathcal{S}, \mathcal{A}, R, \hat{P}, \gamma)$ is the corresponding RM-MDP. To obtain $\hat{\mathcal{M}}$, we construct the replay memory as a directed graph $\mathcal{G}$:

$$\mathcal{G} = (V, E), V = \{\phi(s)|(s,\hat{Q}(s,\cdot))\}, E = \{\phi(s) \xrightarrow{a} \phi(s')|(a,r,N(s,a,s'))\}. \tag{2}$$

---

[2] In the remaining paper, we use Q and $\hat{Q}$ to denote the estimation from network and RM-MDP respectively.

In the graph $\mathcal{G}$, V denotes the set of vertices, E denotes the set of edges. V contains states and action value estimation $\hat{Q}(s, \cdot)$. ϕ is an embedding function to map the high-dimensional states to a low-dimensional representation for fast query (keys in the graph $\mathcal{G}$). We store vertices in a dictionary with ϕ as a hashing function serving as keys, thus we can retrieve a state in $\mathcal{O}(1)$ time. $\hat{Q}(s, \cdot)$ only contains values for actions that were taken by behavior policy β, i.e., $a : \beta(a|s) > 0$. E contains actions a, rewards r and visit counts $N(s, a, s')$. These statistics are similar to that in AlphaGo (Silver et al., 2016; 2017; 2018; Schrittwieser et al., 2020), which are stored in a tree structure and used for Monte Carlo Tree Search (MCTS) (Kocsis & Szepesvári, 2006; Browne et al., 2012). Each edge is identified by the tuple $(\phi(s), a, \phi(s'))$, thus we can also query the statistics on an edge in $\mathcal{O}(1)$ time. In addition, our graph has no limitation for the RM-MDP, the graph can have cycles and the environment dynamics can be stochastic. We estimate $\hat{P}$ for transition (s_t, a_t, s_{t+1}) with visit counts:

$$\hat{p}(s_{t+1}|s_t, a_t) = \frac{N(s_t, a_t, s_{t+1})}{\sum_{s_{t+1}} N(s_t, a_t, s_{t+1})}. \tag{3}$$

Update rule. Except for the graph structure, this graphed memory maintains the same features as the replay memory used in DQN. It stores most recent experiences with a fixed memory size. Since all these statistics are scalars, memory consumption is mostly on account of states s in vertices V. We count the memory size by the number of vertices. When a new transition (s, a, r, s') comes, we first check if $\phi(s)$ exists in the graph. If not, we create a new vertex and edge and initialize $\hat{Q}(s, a) = 0, N(s, a, s') = 1$. Otherwise, if $\phi(s)$ already exists, we merge the same states into one node and update the visit count $N(s, a, s') = N(s, a, s') + 1$. It means different trajectories that have the same state representation will intersect with each other. If there is no intersection between all trajectories, it degenerates to the replay memory used in DQN.

4.2 Solving RM-MDP

With the graph $\mathcal{G}$, we have all elements of RM-MDP $\hat{\mathcal{M}}$. We use value iteration to update $\hat{Q}$:

$$\hat{Q}(s, a) \leftarrow \sum_{s'} \hat{p}(s'|s, a)[r + \gamma \max_{a':\beta(a'|s')>0} \hat{Q}(s', a')], \tag{4}$$

where $\hat{p}$ is the empirical dynamics computed by equation 3, γ is discount factor, $\hat{Q}(s', \cdot)$ and r can be queried from corresponding vertex and edge in $\mathcal{O}(1)$ time. During the learning, each interaction step will add a new transition to the memory. We use a sampling-based method to update $\hat{Q}$ instead of updating the whole memory at each step. In DQN, the Q function is updated with a sampling batch every four environmental steps (Mnih et al., 2015). We use the same batch to update $\hat{Q}$ with equation 4 before updating the Q networks. Besides, when an episode ends, we update $\hat{Q}$ along the episode in reversed order. This is similar to EBU (Lee et al., 2019) but we do the backward update for the memory rather than for Q networks. The sampling-based update and episode-based update allow sparse and delayed rewards to propagate quickly through all transitions of related trajectories. There is no extra computation for sampling, and the time consumption for equation 4 can be ignored comparing with the update of Q networks.

4.3 Regularize Deep-Q Networks

With the conservative estimation from replay memory, we design two regularizers. One is value regularizer, and another is policy regularizer.

Value regularizer. The popular DQN algorithm is known to suffer from substantial overestimation. Our $\hat{Q}$ value from RM-MDP is constrained in the replay memory that will never overestimate. It can be a good complementary to compute target Q value. Let $q(s, a) = r + \gamma \max_a Q(s', a)$ be the target Q value estimated by Q network for state-action pair (s, a), $\hat{q}(s, a)$ computed by equation 4 be the value estimated from RM-MDP. The target value for state action pair (s, a) is:

$$q_{\text{target}}(s, a) = (1 - \alpha)q(s, a) + \alpha \hat{q}(s, a), \tag{5}$$

where $\alpha \in [0, 1]$ is a parameter. Using mean square error with a sample batch $\mathcal{D}$, our TD loss is:

$$\mathcal{L}_{TD} = \frac{1}{|\mathcal{D}|} \sum_{(s,a) \in \mathcal{D}} (q_{\text{target}}(s, a) - Q(s, a))^2. \tag{6}$$

Policy regularizer. Since the purpose of learning is to derive an optimal policy from Q network. We design a policy regularizer to accelerate the policy learning. Let $\hat{\pi}(s) = \text{softmax}_{\tau, a:\beta(a|s)>0}(\hat{Q}(s, \cdot))$ be the Boltzmann policy derive from $\hat{Q}$ at state s, where τ is the softmax temperature. Action a is constrained by behavior policy β, thus policy $\hat{\pi}$ is conservative. Similarly, we have another policy $\pi(s) = \text{softmax}_{\tau, a:\beta(a|s)>0}(Q(s, \cdot))$ derived from Q network. We regularize policy π by minimizing the Kullback–Leibler (KL) divergence between $\hat{\pi}$ and π:

$$\mathcal{L}_{policy} = \frac{\lambda}{|\mathcal{D}|} \sum_{s \in \mathcal{D}} D_{KL}(\hat{\pi}(s) \parallel \pi(s)) \tag{7}$$

where $\lambda > 0$ is a parameter, $\mathcal{D}$ is a batch of experiences. The intuition for policy regularizer is that because policy $\hat{\pi}$ is a conservative estimation, it lower bounds the performance of policy π. If RM-MDP $\hat{\mathcal{M}}$ is a good approximation of a local part of the environment MDP $\mathcal{M}$, $\hat{\pi}$ approximates to the optimal policy in $\mathcal{M}$ and thereby accelerate the learning. Even if not, $\hat{\pi}$ can still help by avoiding suicidal actions in some games and improve the performance.

Combining the two regularizers, the update loss is:

$$\mathcal{L} = \mathcal{L}_{TD} + \mathcal{L}_{policy}. \tag{8}$$

The pseudo-code is shown in Algorithm 1.

Algorithm 1 Combine Conservative Estimation with Experience Replay (CEER)

1: Initialize replay memory $\hat{M}$ with fixed memory size
2: Initialize action value network Q with weights θ, target network $\bar{Q}$ with weights $\bar{\theta} \leftarrow \theta$
3: Initialize the environment $s_0 \leftarrow Env$
4: **for** environments step $t = 0$ **to** T **do**
5:     Select an action a_t by ϵ-greedy with respect to $Q(s_t, \cdot; \theta)$
6:     Execute a_t in Env and get r_t, s_{t+1}
7:     Store the transition (s_t, a_t, r_t, s_{t+1}) in $\hat{M}$ and update visit count $N(s_t, a_t, s_{t+1})$
8:     Sample random minibatch of transitions from $\hat{M}$
9:     Update $\hat{Q}(s_t, a_t)$ via equation 4 and store the result to $\hat{M}$
10:     Update $Q(s_t, a_t; \theta)$ by minimizing $\mathcal{L}$ via equation 8
11:     Update $\bar{\theta} \leftarrow \theta$ every C steps
12: **end for**

---

5 EXPERIMENTS

In this section, we aim to answer the following questions: (1) Does conservative estimation-based experience replay (CEER) speed up learning? (2) In which circumstances will CEER help? (3) What are the effects of value and policy regularizers, and what if we learn from $\hat{Q}$ in a supervised manner similar to EMDQN (Lin et al., 2018) and ERLAM (Zhu et al., 2022)?

5.1 SETUP

Environments. We evaluate our method on environments Sokoban (Schrader, 2018), Mini-Grid (Chevalier-Boisvert et al., 2018) and MinAtar (Young & Tian, 2019) based on OpenAI Gym interface (Brockman et al., 2016). Sokoban is Japanese for warehouse keeper and a traditional video game. The player has to push all boxes in the room on the storage locations/targets. The possibility of making irreversible mistakes makes these puzzles so challenging especially for RL algorithms, which mostly lack the ability to think ahead. MiniGrid implements many tasks in the grid world environment. Most of the games are designed with sparse rewards. MinAtar is image-based miniaturized version of Atari games (Bellemare et al., 2013) which maintains the mechanics of the original games as much as possible and is much faster than original version. For Sokoban and MiniGrid, the map is randomly generated at each episode. For MinAtar, objects are randomly generated at different time steps. So all these environments needs the policy to generalize across different configurations. More details for these environments can be found in Appendix B.

Baselines. We compare our method CEER with DQN (Mnih et al., 2015), PER (Schaul et al., 2016), EBU (Lee et al., 2019), DisCor (Kumar et al., 2020a) and TER (Hong et al., 2022). DQN is the classic algorithm that first achieves human-level performance on video games. PER is the first algorithm to sample experiences with importance measure. EBU samples a whole episode and updates in reversed order. It is similar to our method, which we do the reverse update based on RM-MDP rather than directly on the Q network. DisCor samples transitions proportional to the accuracy of target value. In contrast, our method computes the target value by combining conservative estimation $\hat{Q}$ from RM-MDP with network estimation Q. TER builds a graph to latch on different trajectories and makes use of the orders across trajectories.

Implementation Details. We use the same network architecture for all algorithms and environments. The architecture is the same as in MinAtar (Young & Tian, 2019) baselines. It contains a single convolutional layer with 16 3×3 convolutions with stride 1, and a fully connected hidden layer with 128 units. The replay ratio is 0.25 (Fedus et al., 2020), that is the Q function is updated once per four environmental steps. We search the learning rates for all baselines among {3e-3,1e-3,3e-4,1e-4,3e-5,1e-5} and report the best performance. For our method, we fix the learning rate to 1e-4 and search our particular parameters. Value regularizer weight $\alpha \in \{0,0.2,0.5,0.8,1\}$ and policy regularizer weight $\lambda \in \{0,0.01,1,2,5\}$. All other common parameters are set the same and shown in Appendix A Table 2. We run each experiment with 20 different random seeds and show the mean score and standard error with solid line and shaded area. Each learning consists of 2 million steps of interaction with the environment. The performance is evaluated by running 100 episodes after every 100k environmental steps. More implementation details can be found in Appendix A.

5.2 A TOY EXAMPLE

We first give a toy example to show the benefit of regularizing DQN with conservative estimation. We consider a simple case, Cliffworld, introduced by Sutton & Barto (2018) as shown in Figure 5 Appendix B. There are 48 states in total and the action space is 4 with left, right, up and down. The goal is to reach state G starting from state S. The reward of reaching the goal is 1, dropped into the cliff gives -1, otherwise is 0. This environment can be easily solved by tabular method such as Q-learning, but when combining with deep neural networks such as DQN, things get difficult because of incremental update and parameters interference. In this example, the net-

(a) Learning curves. (b) Q value error.

Figure 2: **(a)** The learning curve of each algorithm. CEER achieves comparable learning speed with Q-learning. The policy regularizer contributes more on policy learning. **(b)** The value error compared with optimal Q value during learning. The value regularizer contributes more on reducing the value error.

work architecture are two fully connected layers with 64 units, and tanh as activation function.

We show the learning curves of mean score, and the mean square error of Q value comparing with optimal Q in Figure 2. **Only_value** and **Only_policy** denote the methods that with only one regularizer. Our method, CEER, uses both regularizers. DQN uses no regularizer and Q-learning is a tabular method without using network. We can find DQN struggles and cannot find the goal state within 100k interactions with the environment. With the two regularizers, the performance improves a lot and the learning speed is in par with Q-learning. And from the performance of **Only_value** and **Only_policy**, it is clear that each regularizer plays an important and different role. The value regularizer helps learn the optimal value faster. The policy regularizer focuses more on the policy learning, while the Q value loss decreases slower. In this simple case, the replay memory contains almost all the transitions so that we can consider $\hat{\mathcal{M}} \approx \mathcal{M}$, i.e., the RM-MDP is almost the same as the environment MDP, thus the conservative policy is a perfect approximation of optimal policy for $\mathcal{M}$. Next, we will show that the two regularizers still help in more complex environments, even when $\hat{\mathcal{M}}$ is much smaller than $\mathcal{M}$.

5.3 OVERALL PERFORMANCE

We show the final scores on Sokoban (Schrader, 2018), MiniGrid (Chevalier-Boisvert et al., 2018) and MinAtar (Young & Tian, 2019) environments in Table 1. Our method achieves the best performance on most of the environments, especially in hard environments with sparse and delayed rewards. On Sokoban, we evaluate our method on seven environments with increasing difficulties. The numbers denote the map size and number of boxes. For example, 5x5-1 means a map with size 5×5 and 1 box to push. We can find that on easy environments like map size 5×5 with one or two boxes, almost all methods achieve the best performance. But when the difficulty increases, only our method handle these environments such as environments Push-6×6-3 and Push-7×7-2. Similar results can be found in MiniGrid environments. When the difficulty increases, our methods outperforms other baselines to a large margin for example on LavaCrossing-Hard. These results show that our method is good at handling environments with sparse and delayed rewards. In addition to above goal-conditioned tasks and navigation tasks, our method can also handle video games with complex mechanics. On MinAtar environments, our method performs best or achieves competitive performance on four out of five games. Especially on Breakout, the final score is twice more than other algorithms. These results indicate that our method is suitable for different tasks. Besides the final scores in Table 1, we show the learning curves for each environment in Appendix C Figure 9, 10, 11.

Table 1: Overall performance on Sokoban, MiniGrid and MinAtar environments. Numbers in bold represent the method that achieves the highest final scores.

	Environment	DQN	DDQN	PER	EBU	DisCor	TER	CEER
Sokoban	Push-5×5-1	**10.82**	10.78	10.81	7.68	10.76	**10.82**	**10.82**
	Push-5×5-2	10.52	8.72	9.61	6.12	8.39	11.10	**11.62**
	Push-6×6-1	9.26	0.01	0.33	-3.55	-0.04	8.48	**10.73**
	Push-6×6-2	-1.93	-9.71	-9.81	-11.59	-10.43	-10.40	**10.54**
	Push-6×6-3	-10.06	-10.03	-10.27	-11.71	-10.56	-11.80	**7.65**
	Push-7×7-1	5.78	-5.60	-4.61	-6.39	-4.14	-0.69	**10.65**
	Push-7×7-2	-2.96	-11.76	-11.60	-11.86	-11.81	-11.90	**9.97**
MiniGrid	DoorKey	1.19	3.43	3.45	-3.60	-0.63	-3.60	**3.50**
	Unlock	-0.87	2.72	2.74	-2.88	-2.72	2.59	**2.80**
	RedBlueDoors	5.40	4.67	7.06	-7.22	5.77	6.70	**7.09**
	SimpleCrossing-Easy	3.08	3.09	3.07	2.98	3.02	3.08	**3.11**
	SimpleCrossing-Hard	3.03	3.02	3.02	-2.85	2.70	3.01	**3.09**
	LavaCrossing-Easy	0.58	2.24	1.52	-3.00	-1.13	-2.28	**3.10**
	LavaCrossing-Hard	-3.34	-3.37	-3.38	-3.31	-3.38	-3.09	**3.05**
MinAtar	Asterix	19.82	20.1	25.8	26.0	**31.19**	3.07	19.82
	Breakout	13.57	16.25	17.76	19.97	17.14	12.73	**42.53**
	Freeway	57.85	57.66	57.79	**59.07**	56.85	22.08	58.77
	Seaquest	14.73	**18.57**	17.48	12.65	16.69	1.62	17.96
	SpaceInvaders	50.71	51.15	55.09	71.83	57.85	45.29	**73.43**

5.4 RELATIONSHIP OF PERFORMANCE IMPROVEMENT AND CONSERVATIVE ESTIMATION

To better understand the relationship between performance improvement and conservative estimation, we design *Average Relative Performance Improvement* (ARPI) to measure the performance improvement, and *Memory Density* to measure the quality of RM-MDP.

Average Relative Performance Improvement (ARPI). Since the final score cannot represent the whole learning process, and almost all methods can achieve near-highest final scores on simple environments like Sokoban Push-5×5-1 and MiniGrid SimpleCrossing-Easy. We design another metric, ARPI, to measure the performance improvement for the whole learning process rather than only considering the final score. Suppose we want to compare the performance of method A with method B. Let $R_k(A)$ and $R_k(B)$ be the cumulative rewards of A and B at evaluating iteration k. $R_{\max} = \max(\max_k R_k(A), \max_k R_k(B))$ is the maximum cumulative reward that the two methods achieved during the learning process. We define ARPI($A|B$) as:

$$\text{ARPI}(A|B) = \frac{1}{K} \sum_{k=1}^{K} \frac{R_k(A) - R_k(B)}{R_{\max} - R_k(B)} \leq 1. \tag{9}$$

ARPI($A|B$) presents the relative performance difference of method A compared with method B. If ARPI($A|B$) > 0, it means A performs better than B. When A achieves the maximum cumulative reward $R_{\max}$ at each evaluation k, ARPI($A|B$) $= 1$ shows the maximum performance improvement.

Memory Density. To measure the quality of estimation from RM-MDP, we design a metric based on the density of memory. The intuition here is, if we have tried more different actions at a state, we should have a better understanding of the state. Let $D_{\text{out}}(s)$ be the out-degree of the vertex at state s, $|\mathcal{A}|$ is the size of action space, $\hat{M}$ is the replay memory. We define the average out-degree of the memory as $D_{\text{out}}(\hat{M}) = \frac{1}{|\hat{M}|} \sum_{s \in \hat{M}} D_{\text{out}}(s)$. Since states are appeared as trajectories, usually there is at least one out-degree for each state vertex, and the maximum out-degree is the size of action space. We have $1 \leq D_{\text{out}}(\hat{M}) \leq |\mathcal{A}|$. We define the memory density as:

$$\text{Density}(\hat{M}) = \frac{D_{\text{out}}(\hat{M}) - 1}{|\mathcal{A}| - 1} \in [0, 1]. \tag{10}$$

We minus 1 for numerator and denominator to normalize Density($\hat{M}$) between 0 and 1. Though the out-degree here is based on the size of action space, the memory density is not limited to discrete action space. For continuous action space, we can discretize the action space, or use the policy variance to measure the density, which we leave for future work.

Correlation between ARPI and Density.
We compare CEER with DQN algorithm and compute Pearson Correlation Coefficient (PCC) (Pearson, 1896; Lee Rodgers & Nicewander, 1988) to quantify the correlation. PCC is a measure of linear correlation between two sets of data. The definition is: $\rho_{X,Y} = \frac{\text{Cov}(X,Y)}{\sigma_X \sigma_Y} \in [-1, 1]$, where $\text{Cov}(X,Y)$ is the covariance of variables X and Y, σ_X and σ_Y are the standard deviations of X, Y. Our data is the final performance and density on all environments. In our results, we get $\rho = 0.881$ which means there is a very strong linear correlation between the performance improvement and the density of the memory.

Figure 3: Relationship between memory density and the performance improvement. We compare CEER with DQN. The memory density is the average value during learning. The oblique line shows the result of linear regression. There is a strong correlation between memory density and ARPI.

We present the relationship in Figure 3. Each point denotes an environment, the oblique line shows the result of linear regression. We find when the memory density increases, the performance improves. And even with a low memory density on MinAtar environments like Asterix and SpaceInvaders, there are still obvious improvements. This is because the conservative estimation can help the agent avoid suicidal actions, thereby the agent lives longer and gets higher reward. One exception is Freeway, though the final performance is competitive as shown in Table 1, the whole learning is slower compared with DQN which is shown in Appendix C Figure 11. We dig into the environment and find that the randomly generated objects in Freeway will move with different speeds as the game progresses. This feature is not included in the state representation, which breaches the Markov property of MDP. The graph will merge different states into one vertex and thus provides wrong estimation.

5.5 ABLATION STUDY

We answer two questions. (1) What are the effects of the value and policy regularizers on environments with different memory density? (2) What is the performance of the conservative policy derived from the replay memory on environments with different memory density? We choose four environments with increasing memory densities, SpaceInvaders (0.01), Breakout (0.34), Sokoban 6×6-3 (0.53), SimpleCrossing-Easy (0.89). Other results are given in Appendix C Figure 12, 13, 14.

(a) SpaceInvaders   (b) Breakout   (c) Push 6x6-3   (d) SimpleCrossing-Easy

Figure 4: Ablation studies of the two regularizers across environments with different memory densities. **Only_value** and **Only_policy** mean only use value regularizer or policy regularizer, **Conservative_policy** is the policy derived from RM-MDP by supervised learning. CEER combines both regularizers.

In Figure 4, we show the learning curves that with and without regularizers. Compared with DQN, we can find both regularizers benefit the learning. Policy regularizer plays a more important role on performance improvement, and value regularizer further helps. This indicates both regularizers are important for the performance improvement. On Sokoban Push 6×6-3, **Only_value** performs worse than DQN, this is because though the mean square error is reduced, the correct order of actions is not maintained due to the function approximation error induced by neural networks. This is similar to the result on Cliffworld environment as shown in Figure 2, the Q value error of **Only_value** reduces faster than **Only_policy** while the performance improves slower.

We answer the second question with the learning curves of **Conservative_policy**, which show results of the conservative policy derived from the replay memory. We remove the target estimation from Q network, that means **Conservative_policy** learns from $\hat{Q}$ in a supervised manner with value weight $\alpha = 1$. This is similar to EMDQN (Lin et al., 2018) and ERLAM (Zhu et al., 2020) as mentioned in Section 2. The difference is that we still maintain the policy regularizer since we find with only supervised learning from $\hat{Q}$, the correct order of actions is hard to maintain and results in worse performance. From Figure 4, we can find when memory density is high, **Conservative_policy** outperforms DQN. It highlights that when the memory is dense, the conservative estimation from RM-MDP can help accelerate the learning. We also find **Conservative_policy** is worse than our method CEER, which emphasizes the importance of combing estimation from both RM-MDP and Q network in target value. When the memory density decreases, **Conservative_policy** even performs worse than DQN. This may because the conservative policy will hurt the exploration and thereby slow down the learning. This indicates that though the conservative estimation can avoid suicidal actions, it will also miss optimal actions. In this case, bootstrapping from Q network will contribute more to the performance improvement.

6 CONCLUSION

In this work, we propose to consider the replay memory as an empirical Replay Memory MDP (RM-MDP). Solving RM-MDP considers existing experiences in replay memory and gives us a conservative estimate. We further design two regularizers based on the estimation to accelerate online DRL algorithms. We justify the effectiveness of our method on all kinds of environments and provide a strong correlation between the performance improvement and memory density of RM-MDP. Results show that our method improves the sample efficiency to a large margin, especially when the memory density is high. And even when the memory density is low, using such a conservative estimate can still help to avoid suicidal actions and thereby improve performance. In addition, our method is also insensitive to environments with sparse and delayed rewards.

There are two promising directions for future work. Since we have shown the strong correlation between memory density and performance improvement, designing state abstraction method to merge information from similar states is a significant direction, which can increase the memory density and further improve the performance. Another direction is extending CEER to environments with continuous action space. We can use discretization techniques or clustering methods to construct RM-MDP with a graph structure, or solve it using existing offline RL methods by sampling.

REFERENCES

Marc G Bellemare, Yavar Naddaf, Joel Veness, and Michael Bowling. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47: 253–279, 2013.

Charles Blundell, Benigno Uria, Alexander Pritzel, Yazhe Li, Avraham Ruderman, Joel Z Leibo, Jack Rae, Daan Wierstra, and Demis Hassabis. Model-free episodic control. *arXiv preprint arXiv:1606.04460*, 2016.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. OpenAI Gym. *arXiv preprint arXiv:1606.01540*, 2016.

Cameron B Browne, Edward Powley, Daniel Whitehouse, Simon M Lucas, Peter I Cowling, Philipp Rohlfshagen, Stephen Tavener, Diego Perez, Spyridon Samothrakis, and Simon Colton. A survey of Monte Carlo Tree Search methods. *IEEE Transactions on Computational Intelligence and AI in games*, 4(1):1–43, 2012.

Maxime Chevalier-Boisvert, Lucas Willems, and Suman Pal. Minimalistic gridworld environment for openai gym. https://github.com/maximecb/gym-minigrid, 2018.

Peng Dai and Eric A Hansen. Prioritizing bellman backups without a priority queue. In *ICAPS*, pp. 113–119, 2007.

William Fedus, Prajit Ramachandran, Rishabh Agarwal, Yoshua Bengio, Hugo Larochelle, Mark Rowland, and Will Dabney. Revisiting fundamentals of experience replay. In *International Conference on Machine Learning*, pp. 3061–3071. PMLR, 2020.

Scott Fujimoto, David Meger, and Doina Precup. Off-policy deep reinforcement learning without exploration. In *International Conference on Machine Learning*, pp. 2052–2062. PMLR, 2019.

Ian Goodfellow, Yoshua Bengio, Aaron Courville, and Yoshua Bengio. *Deep learning*, volume 1. MIT Press, 2016.

Anirudh Goyal, Philemon Brakel, William Fedus, Soumye Singhal, Timothy Lillicrap, Sergey Levine, Hugo Larochelle, and Yoshua Bengio. Recall traces: Backtracking models for efficient reinforcement learning. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=HygsfnR9Ym.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International conference on machine learning*, pp. 1861–1870. PMLR, 2018.

Steven Hansen, Alexander Pritzel, Pablo Sprechmann, André Barreto, and Charles Blundell. Fast deep reinforcement learning using online adjustments from the past. *Advances in Neural Information Processing Systems*, 31, 2018.

Matteo Hessel, Joseph Modayil, Hado Van Hasselt, Tom Schaul, Georg Ostrovski, Will Dabney, Dan Horgan, Bilal Piot, Mohammad Azar, and David Silver. Rainbow: Combining improvements in deep reinforcement learning. In *Thirty-second AAAI conference on artificial intelligence*, 2018.

Zhang-Wei Hong, Tao Chen, Yen-Chen Lin, Joni Pajarinen, and Pulkit Agrawal. Topological experience replay. In *International Conference on Learning Representations*, 2022.

Zhengyao Jiang, Tianjun Zhang, Robert Kirk, Tim Rocktäschel, and Edward Grefenstette. Graph backup: Data efficient backup exploiting markovian transitions. *arXiv preprint arXiv:2205.15824*, 2022.

Andreas Junghanns and Jonathan Schaeffer. Sokoban: A challenging single-agent search problem. In *In IJCAI Workshop on Using Games as an Experimental Testbed for AI Reasearch*. Citeseer, 1997.

Levente Kocsis and Csaba Szepesvári. Bandit based Monte-Carlo planning. In *ECML'06 Proceedings of the 17th European conference on Machine Learning*, pp. 282–293, 2006.

Ilya Kostrikov, Ashvin Nair, and Sergey Levine. Offline reinforcement learning with implicit q-learning. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=68n2s9ZJWF8.

Aviral Kumar, Abhishek Gupta, and Sergey Levine. Discor: Corrective feedback in reinforcement learning via distribution correction. *Advances in Neural Information Processing Systems*, 33: 18560–18572, 2020a.

Aviral Kumar, Aurick Zhou, George Tucker, and Sergey Levine. Conservative Q-learning for offline reinforcement learning. *Advances in Neural Information Processing Systems*, 33:1179–1191, 2020b.

Sascha Lange, Thomas Gabel, and Martin Riedmiller. Batch reinforcement learning. In *Reinforcement learning*, pp. 45–73. Springer, 2012.

Su Young Lee, Choi Sungik, and Sae-Young Chung. Sample-efficient deep reinforcement learning via episodic backward update. *Advances in Neural Information Processing Systems*, 32, 2019.

Joseph Lee Rodgers and W Alan Nicewander. Thirteen ways to look at the correlation coefficient. *The American Statistician*, 42(1):59–66, 1988.

Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *arXiv preprint arXiv:2005.01643*, 2020.

Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. *arXiv preprint arXiv:1509.02971*, 2015.

Long-Ji Lin. Self-improving reactive agents based on reinforcement learning, planning and teaching. *Machine learning*, 8(3):293–321, 1992.

Zichuan Lin, Tianqi Zhao, Guangwen Yang, and Lintao Zhang. Episodic memory deep Q-networks. In *Proceedings of the 27th International Joint Conference on Artificial Intelligence*, pp. 2433–2439, 2018.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A. Rusu, Joel Veness, Marc G. Bellemare, Alex Graves, Martin Riedmiller, Andreas K. Fidjeland, Georg Ostrovski, Stig Petersen, Charles Beattie, Amir Sadik, Ioannis Antonoglou, Helen King, Dharshan Kumaran, Daan Wierstra, Shane Legg, and Demis Hassabis. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.

Guido Novati and Petros Koumoutsakos. Remember and forget for experience replay. In *International Conference on Machine Learning*, pp. 4851–4860. PMLR, 2019.

Youngmin Oh, Kimin Lee, Jinwoo Shin, Eunho Yang, and Sung Ju Hwang. Learning to sample with local and global contexts in experience replay buffer. In *International Conference on Learning Representations*, 2021.

Yangchen Pan, Jincheng Mei, Amir-massoud Farahmand, Martha White, Hengshuai Yao, Mohsen Rohani, and Jun Luo. Understanding and mitigating the limitations of prioritized replay. In *The 38th Conference on Uncertainty in Artificial Intelligence*, 2022.

Karl Pearson. Vii. mathematical contributions to the theory of evolution.—iii. regression, heredity, and panmixia. *Philosophical Transactions of the Royal Society of London. Series A, containing papers of a mathematical or physical character*, pp. 253–318, 1896.

Alexander Pritzel, Benigno Uria, Sriram Srinivasan, Adria Puigdomenech Badia, Oriol Vinyals, Demis Hassabis, Daan Wierstra, and Charles Blundell. Neural episodic control. In *International Conference on Machine Learning*, pp. 2827–2836. PMLR, 2017.

Tom Schaul, John Quan, Ioannis Antonoglou, and David Silver. Prioritized experience replay. In *ICLR (Poster)*, 2016.

Max-Philipp B. Schrader. gym-sokoban. https://github.com/mpSchrader/gym-sokoban, 2018.

Julian Schrittwieser, Ioannis Antonoglou, Thomas Hubert, Karen Simonyan, Laurent Sifre, Simon Schmitt, Arthur Guez, Edward Lockhart, Demis Hassabis, Thore Graepel, Timothy P. Lillicrap, and David Silver. Mastering Atari, Go, chess and shogi by planning with a learned model. *Nature*, 588(7839):604–609, 2020.

David Silver, Aja Huang, Christopher J. Maddison, Arthur Guez, Laurent Sifre, George van den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, Sander Dieleman, Dominik Grewe, John Nham, Nal Kalchbrenner, Ilya Sutskever, Timothy Lillicrap, Madeleine Leach, Koray Kavukcuoglu, Thore Graepel, and Demis Hassabis. Mastering the game of Go with deep neural networks and tree search. *Nature*, 529(7587):484–489, 2016.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, Yutian Chen, Timothy P. Lillicrap, Fan Hui, Laurent Sifre, George van den Driessche, Thore Graepel, and Demis Hassabis. Mastering the game of Go without human knowledge. *Nature*, 550(7676):354–359, 2017.

David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Arthur Guez, Marc Lanctot, Laurent Sifre, Dharshan Kumaran, Thore Graepel, Timothy Lillicrap, Karen Simonyan, and Demis Hassabis. A general reinforcement learning algorithm that masters chess, shogi, and Go through self-play. *Science*, 362(6419):1140–1144, 2018.

Samarth Sinha, Jiaming Song, Animesh Garg, and Stefano Ermon. Experience replay with likelihood-free importance weights. In *Learning for Dynamics and Control Conference*, pp. 110–123. PMLR, 2022.

Peiquan Sun, Wengang Zhou, and Houqiang Li. Attentive experience replay. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 5900–5907, 2020.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

Hado Van Hasselt, Arthur Guez, and David Silver. Deep reinforcement learning with double Q-learning. In *Proceedings of the AAAI conference on artificial intelligence*, volume 30, 2016.

Che Wang, Yanqiu Wu, Quan Vuong, and Keith Ross. Striving for simplicity and performance in off-policy DRL: Output normalization and non-uniform sampling. In *International Conference on Machine Learning*, pp. 10070–10080. PMLR, 2020.

Kenny Young and Tian Tian. Minatar: An Atari-inspired testbed for thorough and reproducible reinforcement learning experiments. *arXiv preprint arXiv:1903.03176*, 2019.

Shangtong Zhang and Richard S Sutton. A deeper look at experience replay. *arXiv preprint arXiv:1712.01275*, 2017.

Deyao Zhu, Li Erran Li, and Mohamed Elhoseiny. Value memory graph: A graph-structured world model for offline reinforcement learning. *arXiv preprint arXiv:2206.04384*, 2022.

Guangxiang Zhu, Zichuan Lin, Guangwen Yang, and Chongjie Zhang. Episodic reinforcement learning with associative memory. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=HkxjqxBYDB.

APPENDIX

A   IMPLEMENTATION DETAILS

Network Architecture. For the toy example Cliffworld (Sutton & Barto, 2018) in Section 5.2, we use a network with two fully connected layers. Each layer has 64 units, and we use tanh as activation function. Q-learning does not use network, it maintains a Q table with size $|\mathcal{S}| \times |\mathcal{A}|$.

For Sokoban, MiniGrid and MinAtar environments, We use a convolutional neural network. The architecture is the same as used in MinAtar (Young & Tian, 2019) baselines. It consists of a single convolutional layer, followed by a fully connected layer. The convolutional layer has 16 3×3 convolutions with stride 1, and the fully connected layer has 128 units. These settings are one quarter of the final convolutional layer and fully connected layer of the network used in DQN (Mnih et al., 2015).

Hyper-parameters. Our method is based on DQN, other baselines additionally incorporate double Q-learning technique (Van Hasselt et al., 2016). We maintain most parameters the same as original DQN and reduce the interaction steps to run more different random seeds. We run each experiment with 2 million steps of interaction with the environment. We proportionally reduce other parameters based on the interaction steps. The ϵ-greedy exploration is linearly decayed from 1 to 0.01 in 1 million steps. The target network is updated every 1000 steps. The replay memory size is set as 100,000. The minibatch size is 32 and the replay ratio is 0.25 (Fedus et al., 2020), that is the Q function is updated once per four environmental steps. The optimizer for network is Adam. The discount factor is 0.99. Table 2 shows the details of hyper-parameters that used for all methods.

Besides the common parameters, there are other parameters that are specific to different methods. For PER (Schaul et al., 2016), the parameter α in sampling probability is set as 0.4, and the parameter β in importance-sampling (IS) weights is linearly annealed from 0.4 to 1 within 0.5 million environmental steps. For EBU (Lee et al., 2019), the diffusion factor β is set as 0.5. For DisCor (Kumar et al., 2020a), the initial temperature τ is set as 10, and the error network Δ_θ has one extra fully connected layer as suggested in original paper. For TER (Hong et al., 2022), the batch mixing ratio η is 0.5 for MiniGrid and MinAtar, and 0.1 for Sokoban. We search the replay memory size for TER within {100K,500K,1M} to ensure there are enough terminal nodes when sampling. We search the learning rates for all baselines among {3e-3,1e-3,3e-4,1e-4,3e-5,1e-5} and report the best performance. For our method, we fix the learning rate to 1e-4 and search our particular parameters. Value regularizer weight $\alpha \in \{0,0.2,0.5,0.8,1\}$ and policy regularizer weight $\lambda \in \{0,0.01,1,2,5\}$.

Evaluation. We run each method on each environment with 20 different random seeds, and show the mean score and standard error with solid line and shaded area. The performance is evaluated by running 100 episodes after every 100K environmental steps. We use ϵ-greedy exploration at evaluation with $\epsilon = 0.01$ to prevent the agent from being stuck at the same state.

Table 2: Hyper-parameters of DQN on Sokoban, MiniGrid and MinAtar environments.

Hyperparameter	Value
Minibatch size	32
Replay memory size	100,000
Target network update frequency	1,000
Replay ratio	0.25
Discount factor	0.99
Optimizer	Adam
Initial exploration	1
Final exploration	0.01
Exploration decay steps	1M
Total steps in environment	2M

B ENVIRONMENT DETAILS

B.1 CLIFFWORLD

Cliffworld is a simple navigation task introduced by Sutton & Barto (2018) as shown in Figure 5. There are 48 states in total which is presented as two-dimensional coordinate axes x and y. The size of action space is 4, with left, right, up and down. The agent needs to reach the goal state G starting from the start state S. The reward of reaching the goal is +1, dropped into the cliff gives -1, otherwise is 0. We set the discount factor as 0.99 and the max episode steps as 100. The arrow on the figure shows the optimal path.

Figure 5: The illustration of Cliffworld environment. Each grid denotes a state, the arrow shows the optimal path from start state S to goal state G.

B.2 SOKOBAN

Sokoban (Junghanns & Schaeffer, 1997; Schrader, 2018) is a Japanese puzzle video game. The game is played on a board of squares, where each square is a floor or a wall. Some floor squares contain boxes, and some floor squares are marked as storage/target locations. The player needs to push all boxes on the target locations. The number of boxes equals the number of target locations. The puzzle is solved when all boxes are placed at target locations. The boxes cannot be pulled, it means a wrong action may lead to irreversible mistakes, which makes these puzzles so challenging especially for reinforcement learning algorithms, which mostly lack the ability to think ahead.

The room is randomly generated at each episode. Each time the environment is reset, the walls, the target locations, and the locations of the player and boxes will change. Therefore, it allows to train networks without overfitting on a set of predefined rooms. We choose seven tasks with increasing difficulties from Push-5×5-1 to Push-7×7-2. The number in the task name denotes the size of the map and the number of boxes. For example, 5x5-1 means a map with size 5×5 and 1 box to push. Figure 6 gives the visualization of the seven Sokoban tasks we choose.

State Space. We use an image-based state in our experiments. The state has three channels which denote RGB, the size of each channel is the same as the room size. Before inputting a state to the neural network, we divide it by 255 to normalize each pixel into $[0, 1]$.

Action Space. The action space is 8 in total, it consists of moving and pushing both in the 4 cardinal directions, left, right, up and down.

Reward Function. Pushing a box on the target location gets reward +1. Finishing the game gets reward +10. Each step will have a penalty reward of -0.1. And the max episode steps is 120. So in principle, the maximum reward we can achieve is near to 10 plus the number of boxes. And the minimum rewards is -12.

B.3 MINIGRID

MiniGrid (Chevalier-Boisvert et al., 2018) is a gridworld Gymnasium (Brockman et al., 2016) environment, which is designed to be particularly simple, lightweight and fast. It implements many tasks in the gridworld environment and most of the games are designed with sparse rewards. We choose seven different tasks as shown in Figure 7.

(a) Push_5x5_1	(b) Push_5x5_2	(c) Push_6x6_1	(d) Push_6x6_2

(e) Push_6x6_3	(f) Push_7x7_1	(g) Push_7x7_2

Figure 6: Visualization of Sokoban environments.

The map for each task is randomly generated at each episode to avoid overfitting to a fixed map. The state is an array with the same size of the map. The red triangle denotes the player, and other objects are denoted with different symbols. The action space is different from tasks. For navigation tasks like SimpleCrossing and LavaCrossing, actions only include turn left, turn right and move forward. For other tasks like DoorKey and Unlock, actions also include pickup a key and open a door. Let MaxSteps be the max episode steps, MapWidth and MapHeight be the width and height of the map. We introduce each task as follows.

DoorKey. This task is to first pickup the key, then open the door, and finally reach the goal state (green block). MaxSteps is defined as $10 \times \text{MapWidth} \times \text{MapHeight}$. Reaching the goal state will get reward +MaxSteps/100, otherwise there is a penalty reward -0.01 for each step.

Unlock. This task is to first pickup the key and then open the door. MaxSteps is defined as $8 \times \text{MapHeight}^2$. Opening the door will get reward +MaxSteps/100, otherwise there is a penalty reward -0.01 for each step.

RedBlueDoors. This task is to first open the red door and then open the blue door. MaxSteps is defined as $20 \times \text{MapHeight}^2$. The agent will get reward +MaxSteps/100 after the red door and the blue door are opened sequentially, otherwise there is a penalty reward -0.01 for each step.

SimpleCross-Easy/Hard. This task is to navigate through the room and reach the goal state (green block). Knocking into the wall will keep the agent unmoved. MaxSteps is defined as $4 \times \text{MapWidth} \times \text{MapHeight}$. Reaching the goal state will get reward +MaxSteps/100, otherwise there is a penalty reward -0.01 for each step.

LavaCross-Easy/Hard. This task is to reach the goal state (green block). Falling into the lava (orange block) will terminate the episode immediately. MaxSteps is defined as $4 \times \text{MapWidth} \times \text{MapHeight}$. Reaching the goal state will get reward +MaxSteps/100, falling into the lava will get reward -MaxSteps/100, otherwise there is a penalty reward -0.01 for each step.

B.4 MINATAR

MinAtar (Young & Tian, 2019) is image-based miniaturized version of Atari environments (Bellemare et al., 2013), which maintains the mechanics of the original games as much as possible and is much faster than original version. MinAtar implements five Atari games in total, we show the visualization of each game in Figure 8.

(a) DoorKey   (b) Unlock   (c) RedBlueDoors

(d) SimpleCross-Easy   (e) SimpleCross-Hard   (f) LavaCrossing-Easy   (g) LavaCrossing-Hard

Figure 7: Visualization of MiniGrid environments.

State Space. Each game provides the agent with a $10 \times 10 \times n$ binary state representation. The n channels correspond to game specific objects, such as ball, paddle and brick in the game Breakout. The objects in each game are randomly generated at different time steps. The difficulty will change as the game progresses, for examples, there will be more objects and the objects will move faster. So these environments needs the policy to generalize across different configurations.

Action Space. The action space consists of moving in the 4 cardinal directions, firing, and no-op, and omits diagonal movement as well as actions with simultaneous firing and movement. This simplification increases the difficulty for decision making. In addition, MinAtar games add stochasticity by incorporating sticky-actions, that the environment repeats the last action with probability 0.1 instead of executing the agent's current action. This can avoid deterministic behaviour that simply repeats specific sequences of actions, rather than learning policies that generalize.

Reward Function. The rewards in most of the MinAtar environments are either 1 or 0. The only exception is Seaquest, where a bonus reward between 0 and 10 is given proportional to remaining oxygen when surfacing with six divers.

(a) Asterix   (b) Breakout   (c) Freeway   (d) Seaquest   (e) SpaceInvaders

Figure 8: Visualization of MinAtar environments.

C   ADDITIONAL EXPERIMENTAL RESULTS

C.1   OVERALL PERFORMANCE

We show the learning curves of each method on Sokoban, MiniGrid and MinAtar in Figure 9, 10 and 11. Each line is the running of 20 different random seeds. The solid line shows the mean score and the shaded area shows the standard error. We can find our method CEER achieves the

best performance on most of environments, which indicates the conservative estimation helps the learning to a large margin. When the difficulty increases, the performance of CEER remains strong. Since Sokoban and MiniGrid are environments with sparse and delayed rewards, we conclude that our method is also stable on tasks with sparse and delayed rewards. This highlights that our methods is a general method that is suitable for all kinds of tasks.

Figure 9: Learning curves on Sokoban environments. CEER outperforms other method to a large margin. When the difficulty increases, other methods failed while CEER still achieved high performance.

Figure 10: Learning curves on MiniGrid environments. CEER performs consistently well across all tasks, which shows our method is insensitive to sparse and delayed rewards environments.

Figure 11: Learning curves on MinAtar environment. CEER performs best or achieves comparable performance on four out of five games. And on Breakout, the final score of CEER is twice more than other methods.

C.2 ABLATION STUDIES

We show the ablation studies of CEER on Sokoban, MiniGrid and MinAtar in Figure 12, 13 and 14. **Only_value** and **Only_policy** denote the methods that with only value or policy regularizer. CEER uses both regularizers and DQN uses no regularizer. **Conservative_policy** shows the result of the conservative policy derived from the replay memory. It uses the value regularizer with $\alpha = 1$ and maintains the policy regularizer unchanged.

We can find that our method, CEER, combines the benefits of both value and policy regularizers and achieves the highest final scores on almost all of the environments. **Only_policy** can achieve comparable performance as CEER on most of environments. It indicates the policy regularizer makes the most contribution for CEER. We can also find that the performance of **Only_value** and **Conservative_policy** is not consistent and even decrease on some environments. For examples, **Only_value** performs worse than DQN on environments like Push_6x6_1, SimpleCross-Hard and Asterix. **Conservative_policy** performs worse on environments like Asterix, Freeway and SpaceInvaders. Combining with the memory density of each environment as shown in Figure 3 and Table 3, we can find **Only_value** and **Conservative_policy** perform worse when the memory density decreases, especially for **Only_value**.

This is because only using value regularizer is not a direct regularization on learned policy, which may not maintain the correct order of actions. This emphasizes the importance of policy regularizer. And only learning from the conservative estimation is also not enough, especially on complex video games. The reason may because though the conservative estimation can help avoid dangerous actions that are never tried, it will also restrict exploring better actions. This highlights the necessary of learning from Q network, which may take aggressive actions. We can consider the estimation of Q network and the conservative estimation $\hat{Q}$ from RM-MDP as one kind of trade-off between exploration and exploitation. How to balance it is a promising topic which we leave for future work.

C.3 MEMORY DENSITY AND ARPI FOR EACH ENVIRONMENT

We additionally show the statistics of memory density and ARPI for each environment in Table 3. Here, the memory density is the measurement of the RM-MDP's quality, and ARPI measures the

Figure 12: Ablation study on Sokoban environments. **Only_policy** achieves comparable performance as CEER. This indicates the policy regularizer makes the most contribution for CEER.

Figure 13: Ablation study on MiniGrid environments. **Only_value** fails on most of the tasks, which shows value regularizer is not a direct regularization on learned policy and cannot maintain the correct order of actions in some cases.

relative performance improvement during learning. The definition can be found in Section 5.4. In Table 3, the memory density is the average during the whole learning, and the ARPI is the comparison between CEER and DQN.

On Seaquest environment, though the memory density is 0, we still find some improvement compared with DQN. This highlights that even the memory density is low, the conservative estimation can still help the learning. Freeway is the only exception that the performance decreases. The rea-

Figure 14: Ablation study on MinAtar environments. **Conservative_policy** performs poor on most of the environments. It shows though the conservative estimation can help avoid dangerous actions, it may also restrict exploring good actions.

son is that the speed of objects are not included into the state representation. The graph will merge different states into one vertex and provides wrong estimation, which is harmful for the learning. In addition, since the strong correlation between memory density and ARPI, memory density can be a measurement for the difficulty of environment, which is an interesting topic. For example, we can conclude that Push-6×6-3 is harder than Push-7×7-1 and Push-7×7-2.

Table 3: The memory density and ARPI on all environments during learning. The memory density is the average during learning, and ARPI shows the comparison between CEER and DQN.

Environment		Memory Density	ARPI (CCER|DQN)
Sokoban	Push-5×5-1	0.93	0.56
	Push-5×5-2	0.84	0.76
	Push-6×6-1	0.88	0.65
	Push-6×6-2	0.63	0.70
	Push-6×6-3	0.53	0.66
	Push-7×7-1	0.83	0.68
	Push-7×7-2	0.56	0.64
MiniGrid	DoorKey	0.70	0.77
	Unlock	0.67	0.77
	RedBlueDoors	0.88	0.67
	SimpleCrossing-Easy	0.89	0.58
	SimpleCrossing-Hard	0.65	0.45
	LavaCrossing-Easy	0.86	0.75
	LavaCrossing-Hard	0.64	0.68
MinAtar	Asterix	0.03	0.18
	Breakout	0.34	0.38
	Freeway	0.02	-0.08
	Seaquest	0.00	0.04
	SpaceInvaders	0.01	0.10