Randomized Douglas-Rachford Splitting Algorithms for Nonconvex Composite Optimization in Federated Learning

Abstract

We develop two new algorithms, called, **FedDR** and **asyncFedDR**, for solving a fundamental nonconvex composite optimization problem in federated learning. Our algorithms rely on a novel combination between a nonconvex Douglas-Rachford splitting method, randomized block-coordinate strategies, and asynchronous implementation. They can also handle convex regularizers. Unlike recent methods in the literature, e.g., FedSplit and FedPD, our algorithms update only a subset of users at each communication round, and possibly in an asynchronous manner, making them more practical. These new algorithms also achieve communication efficiency and more importantly can handle statistical and system heterogeneity, which are the two main challenges in federated learning. Our convergence analysis shows that the new algorithms match the communication complexity lower bound up to a constant factor under standard assumptions. Our numerical experiments illustrate the advantages of our methods compared to existing ones on several datasets.

1 Introduction

Training machine learning models in a centralized fashion becomes more challenging and marginally inaccessible for a large number of users, especially when the size of datasets and models is growing substantially larger. Consequently, training algorithms using decentralized and distributed approaches comes in as a natural replacement. Among several approaches, federated learning (FL) has received tremendous attention in the past few years since it was first introduced in [18, 29]. In this setting, a central server coordinates between many local users (also called agents or devices) to perform their local updates, then the global model will get updated, e.g., by averaging or aggregating local models.

Challenges. FL provides a promising solution for many machine learning applications such as learning over smartphones or cross organizations, and internet of things, where privacy protection is one of the most critical requirements. However, this training mechanism faces a number of fundamental challenges, see, e.g., [30]. First, when the number of users gets substantially large, it creates *communication bottleneck* during model exchange process between server and users. Second, the local data stored in each local user may be different in terms of sizes and distribution which poses a challenge: *data or statistical heterogeneity*. Third, the variety of users with different local storage, computational power, and network connectivity participating into the system also creates a major challenge, known as *system heterogeneity*. This challenge also causes unstable connection between server and users, where some users may be disconnected from the server or simply dropped out during training. In practice, we can expect only a subset of users to participate in each round of communication. Another challenge in FL is *privacy concern*. Distributed methods often exchange the full model of local users while it is not permitted in FL as the private data can be exposed from the shared model such as the objective gradients [49]. Therefore, FL methods normally send the

global model to each user at the start of each communication round, each user will perform its local update and send back only the necessary update for aggregation.

Our goal and approach. Our goal in this paper is to further and simultaneously address these fundamental challenges by proposing two new algorithms to train the underlying common optimization model in FL. Our approach relies on a novel combination between randomized block-coordinate strategy, nonconvex Douglas-Rachford (DR) splitting, and asynchronous implementation. While each individual technique or partial combinations is not new, our combination of three as in this paper appears to be the first in the literature. To the best of our knowledge, this is the first work developing randomized block-coordinate DR splitting methods for nonconvex composite FL optimization models, and they are fundamentally different from some works in the convex setting, e.g., [7, 8].

Contribution. Our contribution is summarized as follows.

(a) We develop a new FL algorithm, called **FedDR** (**Fed**erated **D**ouglas-**R**achford), by combining the well-known DR splitting technique and randomized block-coordinate strategy for the common nonconvex composite optimization problem in FL. Our algorithm can handle nonsmooth convex regularizers and allows inexact evaluation of the underlying proximal operators. It also achieves the best known $\mathcal{O}\left(\varepsilon^{-2}\right)$ communication complexity for finding a stationary point under standard assumptions (Assumptions 2.1-2.2), where ε is a given accuracy. More importantly, unlike FedSplit [32] and FedPD [47], our algorithm does not require all users to participate in each communication round.

(b) Next, we propose an asynchronous algorithm, **asyncFedDR**, where each user can asynchronously perform local update and periodically send the update to the server for proximal aggregation. We show that **asyncFedDR** achieves the same communication complexity $\mathcal{O}\left(\varepsilon^{-2}\right)$ as **FedDR** (up to a constant factor) under the same standard assumptions. This algorithm is expected to fairly and simultaneously address all challenges discussed above.

Let us emphasize some key points of our contribution. First, the best known $\mathcal{O}\left(\varepsilon^{-2}\right)$ communication complexity of our methods matches the lower bound complexity up to a constant factor as shown in [47]. Second, our methods rely on a DR splitting technique for nonconvex optimization and can handle [nonsmooth] convex regularizers, which allows us to deal with a larger class of applications and with constraints, and some statistical and system heterogeneity as discussed in FedSplit [32] and FedPD [47]. However, FedSplit only considers the convex case, and both FedSplit and FedPD require all users to update at each communication round, making them less practical and applicable in FL. Our methods only require a subset of users or even one user to participate in each communication round. Third, we allow inexact evaluation of proximal operators of each user's loss function with adaptive accuracies. Fourth, requiring synchronous aggregation at the end of each communication round may lead to slow-down in training due to the heterogeneity in computing power and communication capability of local users. It is natural to have asynchronous update from local users as in, e.g., [33, 34, 37]. Our asynchronous variant, **asyncFedDR**, can fairly address this challenge. Moreover, it uses a general probabilistic model recently introduced in [5], which allows us to capture the variety of asynchronous environments and architectures compared to existing methods, e.g., [37, 42]. Finally, our methods only require users to send the increment of an intermediate iterate to the server instead full local vectors or gradients, which may prevent it from adversarial attacks or leaking data.

Related work and comparison. Federated Averaging (FedAvg) is perhaps the early method used in FL. In FedAvg, users perform stochastic gradient descent (SGD) updates for a number of epochs then send updated models to server for aggregation. FedAvg's practical performance has been shown in many early works, e.g., [18, 28, 46] and tends to become the most popular method for solving FL applications. [26] show that local SGD where users perform a number of local updates before global communication takes place as in FedAvg may offer benefit over minibatch SGD. Similar comparison between minibatch SGD and local SGD has been done in [40, 41]. Analyzing convergence of FedAvg was very challenging at its early time due to the complexity in its update as well as data heterogeneity. One of the early attempt to show the convergence of FedAvg is in [37] for convex problems under the iid data setting and a set of assumptions. [43] also considers local SGD in the nonconvex setting. Without using an additional bounded gradient assumption as in [37, 43], [39] improves the complexity for the general nonconvex setting while [11] uses a Polyak-Łojasiewicz (PL) condition to improve FedAvg's convergence results. In the heterogeneous data settings, [17] analyzes local GD, where users performs gradient descent (GD) updates instead of SGD. The analysis of FedAvg for non-iid

data is given in [24]. The analysis of local GD/SGD for nonconvex problems has been studied in [13]. However, FedAvg might not converge with non-iid data as shown in [32, 47, 48].

FedProx [23] is a generalization of FedAvg, which deals with heterogeneity in federated networks by introducing a proximal term to the objective in local updates to improve stability. FedProx has been shown to achieve better performance than FedAvg in heterogeneous setting. Another method to deal with data heterogeneity is SCAFFOLD [16] which uses a control variates to correct the "client-drift" in local update of FedAvg. MIME [15] is another framework that uses control variate to improve FedAvg for heterogeneous settings. However, SCAFFOLD and MIME require to commnicate extra information apart from local model. Compared to aforementioned works, our methods deal with nonconvex problems under standard assumptions and with composite settings.

FedSplit [32] instead employs a DR splitting scheme to solve a constrained reformulation of the original problem. In fact, FedSplit can be viewed as a variant of Tseng's splitting scheme [1] applied to FL. [32] show that FedSplit can find a solution of the FL problem under only convexity without imposing any additional assumptions on system or data homogeneity. [47] proposes FedPD, which is essentially a variant of the standard augmented Lagrangian method in nonlinear optimization. Other algorithms for FL can be found, e.g., in [6, 10, 12, 14, 25, 44].

Our approach in this paper relies on nonconvex DR splitting method, which can handle the heterogeneity as discussed in [32]. While the DR method is classical, its nonconvex variants have been recently studied e.g., in [9, 21, 38]. However, the combination of DR and randomized block-coordinate strategy remains limited [7, 8] even in the convex settings. Alternatively, asynchronous algorithms have been extensively studied in the literature, also for FL, see, e.g., [2, 33, 34]. For instance, a recent work [42] analyzes an asynchronous variant of FedAvg under bounded delay assumption and constraint on the number of local updates. [37] proposes an asynchronous local SGD to solve convex problems under iid data. However, to our best knowledge, there has existed no asynchronous method using DR splitting techniques with convergence guarantee for FL. In addition, most existing algorithms only focus on non-composite settings. Hence, our work here appears to be the first.

Content. The rest of this paper is organized as follows. Section 2 states our FL optimization model and our assumptions. Section 3 develops **FedDR** and studies its convergence. Section 4 considers an asynchronous variant, **asyncFedDR**. Section 5 is devoted for numerical experiments. Due to space limit, all technical details and proofs can be found in Supplementary Document (Supp. Doc.).

2 Nonconvex Optimization Models in Federated Learning

The underlying optimization model of many FL applications can be written into the following form:

$$\min_{x \in \mathbb{R}^p} \left\{ F(x) := f(x) + g(x) = \frac{1}{n} \sum_{i=1}^{n} f_i(x) + g(x) \right\}, \tag{1}$$

where n is the number of users, and each f_i is a local loss of the i-th user, which is assumed to be nonconvex and L-smooth (see Assumptions 2.1 and 2.2 below), and g is a proper, closed, and convex regularizer. Apart from these assumptions, we will not make any additional assumption on (1). We emphasize that the use of regularizers g has been motivated in several works, including [45].

Let $\mathrm{dom}(F) := \{x \in \mathbb{R}^p : F(x) < +\infty\}$ be the domain of F and ∂g be the subdifferential of g [1]. Since (1) is nonconvex, we only expect to find a stationary point, which is characterized by the following optimality condition.

Definition 2.1. If $0 \in \nabla f(x^*) + \partial g(x^*)$, then x^* is called a [first-order] stationary point of (1).

The algorithms for solving (1) developed in this paper will rely on the following assumptions.

Assumption 2.1 (Boundedness from below). $\mathrm{dom}(F) \neq \emptyset$ and $F^\star := \inf_{x \in \mathbb{R}^p} F(x) > -\infty$.

Assumption 2.2 (*L*-smoothness). All functions $f_i(\cdot)$ for $i \in [n] := \{1, \cdots, n\}$ are L-smooth, i.e., f_i is continuously differentiable and there exists $L \in (0, +\infty)$ such that

$$\|\nabla f_i(x) - \nabla f_i(y)\| \leq L\|x - y\|, \quad \forall x, y \in \mathrm{dom}(f_i). \tag{2}$$

Assumptions 2.1 and 2.2 are very standard in nonconvex optimization. Assumption 2.1 guarantees the well-definedness of (1) and is independent of algorithms. Assuming the same Lipschitz constant

137 L for all f_i is not restrictive since if f_i is L_i-smooth, then by scaling variables of its constrained
138 formulation (see (11) in Supp. Doc.), we can get the same Lipschitz constant L of all f_i.

Proximal operators and evaluation. Our methods make use of the proximal operators of both f_i
140 and g. Although f_i is L-smooth and nonconvex, we still define its proximal operator as

$$\text{prox}_{\eta f_i}(x) := \underset{y}{\text{argmin}} \left\{ f_i(y) + \frac{1}{2\eta} \|y - x\|^2 \right\}, \tag{3}$$

141 where $\eta > 0$. Even f_i is nonconvex, under Assumption 2.2, if we choose $0 < \eta < \frac{1}{L}$, then $\text{prox}_{\eta f_i}$
142 is well-defined and single-valued. Evaluating $\text{prox}_{\eta f_i}$ requires to solve a strongly convex program.
143 If $\text{prox}_{\eta f_i}$ can only be computed approximately up to an accuracy $\epsilon \geq 0$ to obtain z, denoted by
144 $x_+ :\approx \text{prox}_{\eta f_i}(x)$, if $\|x_+ - \text{prox}_{\eta f_i}(x)\| \leq \epsilon_i$. For the convex function g, its proximal operator
145 $\text{prox}_{\eta g}$ is defined in the same way as (3).

Gradient mapping. As usual, let us define the following gradient mapping of F in (1).

$$\mathcal{G}_\beta(x) := \frac{1}{\beta}\left(x - \text{prox}_{\beta g}(x - \beta \nabla f(x))\right), \quad \beta > 0. \tag{4}$$

147 Then, the optimality condition $0 \in \nabla f(x^*) + \partial g(x^*)$ of (1) is equivalent to $\mathcal{G}_\beta(x^*) = 0$. However,
148 in practice, we often wish to find an ε-approximate stationary point to (1) defined as follows.

149 **Definition 2.2.** If $\tilde{x} \in \text{dom}(F)$ satisfies $\mathbb{E}\left[\|\mathcal{G}_\beta(\tilde{x})\|^2\right] \leq \varepsilon^2$, then $\tilde{x}$ is called an ε-stationary point of
150 (1), where the expectation is taken overall the randomness generated by the underlying algorithm.

3 FedDR Algorithm and Its Convergence Guarantee

152 The Douglas-Rachford splitting method has been specified in [32], called FedSplit, to handle convex
153 and non-composite instances of (1). FedSplit can overcome some of the key challenges as discussed
154 earlier. Following this idea, we first derive a new variant of the DR splitting method to handle
155 nonconvex problem (1). This new algorithm is synchronous and we call it **FedDR**. Unlike FedSplit,
156 **FedDR** is a randomized block-coordinate method and can handle nonconvex composite problems.

157 The complete algorithm is presented in Algorithm 1, where its full derivation is in Supp. Doc. A.1.

Algorithm 1 (FL with Randomized DR (**FedDR**))

1: **Initialization:** Take $x^0 \in \text{dom}(F)$. Choose $\eta > 0$ and $\alpha > 0$, and accuracies $\epsilon_{i,0} \geq 0$ $(i \in [n])$.
   Initialize the server with $\bar{x}^0 := x^0$, $\tilde{x}^0 := x^0$, and $y^0 := x^0$.
   Initialize each user $i \in [n]$ with $y_i^0 := x^0$, $x_i^0 :\approx \text{prox}_{\eta f_i}(y_i^0)$, and $\hat{x}_i^0 := 2x_i^0 - y_i^0$.
2: **For** $k := 0, \cdots, K$ **do**
3:    [*Active users*] Generate a proper realization $\mathcal{S}_k \subseteq [n]$ of $\hat{\mathcal{S}}$ (see Assumption 3.1).
4:    [*Communication*] Each user $i \in \mathcal{S}_k$ receives $\bar{x}^k$ from the server.
5:    [*Local update*] **For each user** $i \in \mathcal{S}_k$ **do**: Choose $\epsilon_{i,k+1} \geq 0$ and update

   $$y_i^{k+1} := y_i^k + \alpha(\bar{x}^k - x_i^k), \quad x_i^{k+1} :\approx \text{prox}_{\eta f_i}(y_i^{k+1}), \quad \text{and} \quad \hat{x}_i^{k+1} := 2x_i^{k+1} - y_i^{k+1}.$$

6:    [*Communication*] Each user $i \in \mathcal{S}_k$ sends $\Delta \hat{x}_i^k := \hat{x}_i^{k+1} - \hat{x}_i^k$ back to the server.
7:    [*Sever update*] The server computes $y^{k+1} := y^k + \alpha(\bar{x}^k - y^k)$ and $\tilde{x}^{k+1} := \tilde{x}^k + \frac{1}{n}\sum_{i \in \mathcal{S}_k} \Delta \hat{x}_i^k$.
8:    [*Sever update*] Then, the sever updates $\bar{x}^{k+1} := \text{prox}_{\frac{n\eta}{n+1} g}\left(\frac{n}{n+1}\tilde{x}^{k+1} + \frac{1}{n+1}y^{k+1}\right)$.
9: **End For**

---

158 Let us make the following remarks. First, we allow x_i^k to be an approximation of $\text{prox}_{\eta f_i}(y_i^k)$ up to
159 an accuracy $\epsilon_{i,k} \geq 0$ as defined in (3), i.e., $\|x_i^k - \text{prox}_{\eta f_i}(y_i^k)\| \leq \epsilon_{i,k}$ for all $i \in [n]$ if $k = 0$ and
160 for all $i \in \mathcal{S}_{k-1}$ if $k > 0$. If $\epsilon_{i,k} = 0$, then we get the exact evaluation $x_i^k := \text{prox}_{\eta f_i}(y_i^k)$. Second,
161 Algorithm 1 is different from existing randomized proximal gradient-based methods since we rely
162 on a DR splitting scheme and can handle composite settings. Here, three iterates y_i^k, x_i^k, and $\hat{x}_i^k$ at
163 Step 5 are updated sequentially, making it challenging to analyze convergence. Third, the subset of
164 active users $\mathcal{S}_k$ is sampled from a random set-valued mapping $\hat{\mathcal{S}}$. As specified in Assumption 3.1,
165 this sampling mechanism covers a wide range of sampling strategies. Clearly, if $\mathcal{S}_k = [n]$ and $g = 0$,
166 then Algorithm 1 reduces to FedSplit, but for the nonconvex case. Hence, our convergence guarantee
167 below remains applicable, and the guarantee is sure. Algorithm 1 is completely different from [45].

3.1 Convergence of Algorithm 1

Let us consider a proper sampling scheme $\hat{\mathcal{S}}$ of $[n]$, which is a random set-valued mapping with values in $2^{[n]}$, the collection of all subsets of $[n]$. Let $\mathcal{S}_k$ be an iid realization of $\hat{\mathcal{S}}$ and $\mathcal{F}_k := \sigma(\mathcal{S}_0, \cdots, \mathcal{S}_k)$ be the σ-algebra generated by $\mathcal{S}_0, \cdots, \mathcal{S}_k$. We first impose the following assumption about the distribution of our sampling scheme $\hat{\mathcal{S}}$.

Assumption 3.1. There exist $\mathbf{p}_1, \cdots, \mathbf{p}_n > 0$ such that $\mathbb{P}(i \in \hat{\mathcal{S}}) = \mathbf{p}_i > 0$ for alll $i \in [n]$.

This assumption covers a large class of sampling schemes as discussed in [35], including non-overlapping uniform and doubly uniform. This assumption guarantees that every user has a non-negligible probability to be updated. Note that $\mathbf{p}_i = \sum_{\mathcal{S}:i\in\mathcal{S}} \mathbb{P}(\mathcal{S})$ due to Assumption 3.1. For the sake of notation, we also denote $\hat{\mathbf{p}} := \min\{\mathbf{p}_i : i \in [n]\} > 0$.

For the sake of presentation, we only provide here the convergence of the exact variant of Algorithm 1 in the following theorem. The full results for its inexact variant can be found in Supp. Doc. A.4.

Theorem 3.1. *Suppose that Assumptions 2.1, 2.2, and 3.1 hold. Let $\{(x_i^k, y_i^k, y^k, \hat{x}_i^k, \bar{x}^k)\}$ be generated by the exact variant of Algorithm 1 using $0 < \alpha < 2$ and $0 < \eta < \frac{2-\alpha}{2L}$. Then, we have*

$$\frac{1}{K+1} \sum_{k=0}^{K} \mathbb{E}\left[\|\mathcal{G}_{\frac{n\eta}{n+1}}(\bar{x}^k)\|^2\right] \leq \frac{C[F(x^0) - F^\star]}{K+1}, \tag{5}$$

where $C := \frac{2(n+1)}{n\eta\alpha}\left[\frac{2(1+\eta L)^2(1+L^2\eta^2)}{\hat{\mathbf{p}}(2-\alpha(L\eta+1)-2L^2\eta^2)} + \frac{1}{2-\alpha}\right] > 0$.

Consequently, let $\tilde{x}^K$ be selected uniformly at random from $\{\bar{x}^0, \cdots, \bar{x}^K\}$ as the output of the exact variant of Algorithm 1. Then, if we run this variant for at most $K := \left\lfloor \frac{C[F(x^0) - F^\star]}{\varepsilon^2} \right\rfloor \equiv \mathcal{O}\left(\varepsilon^{-2}\right)$ iterations, then $\tilde{x}^K$ is an ε-stationary point of (1) as in Definition 2.2.

Remark 3.1 (**Comparison**). Since (1) is nonconvex, our $\mathcal{O}\left(\varepsilon^{-2}\right)$ communication complexity is the state-of-the-art, matching the lower bound complexity (up to a constant factor) [47]. However, unlike FedSplit and FedPD [47], our flexible sampling scheme allows us to update a subset of users at each round. This can potentially further resolve the communication bottleneck [22].

4 AsyncFedDR and Its Convergence Guarantee

Motivation. Although **FedDR** has been shown to converge, it is more practical to account for the system heterogeneity of local users. Requiring synchronous aggregation at the end of each communication round may lead to slow-down in training. It is natural to have asynchronous update from local users as seen, e.g., in [34, 37]. However, asynchronous implementation remains limited in FL. Motivated by this argument, we propose **asyncFedDR**, an asynchronous variant of **FedDR**, and analyze its convergence guarantee. For the sake of our analysis, we limit our consideration to the case $\mathcal{S}_k := \{i_k\}$, and using exact evaluation of $\text{prox}_{\eta f_i}$ and bounded delay.

4.1 Derivation of asyncFedDR

Let us first explain the main idea of **asyncFedDR**. At each iteration k, each user receives a delay copy $\bar{x}^{k-d_{i_k}^k}$ of $\bar{x}^k$ from the server with a delay $d_{i_k}^k$. The active user i_k will update its own local model $(y_i^k, x_i^k, \hat{x}_i^k)$ in an asynchronous mode without waiting for others to complete. Once competing its update, user i_k just sends an increment $\Delta\hat{x}_{i_k}^k$ to the server to update the global model, while others may be reading. Overall, the complete **asyncFedDR** is presented in Algorithm 2.

In our analysis below, a transition of iteration from k to $k+1$ is triggered whenever a user completes its update. Moreover, at Step 3, active user i_k is chosen from a realization (i_k, d^k) of a joint random vector $(\hat{i}_k, \hat{d}^k)$ at the k-th iteration. Here, we do not assume i_k to be uniformly random or independent of the delay d^k. This allows Algorithm 2 to capture the variety of asynchronous implementations and architectures. Note that $\bar{x}^{k-d_{i_k}^k}$ at Step 4 is a delayed version of $\bar{x}^k$, which only exists on the server when user i_k is reading. However, right after, $\bar{x}^k$ may be updated by another user. In contrast, since y^k is on the server, y^{k+1} updated at Step 7 uses the most recent vector $\bar{x}^k$ instead of its delayed copy.

Algorithm 2 (Asynchronous FedDR (**asyncFedDR**))

1: **Initialization:** Take $x^0 \in \text{dom}(F)$ and choose $\eta > 0$ and $\alpha > 0$.
   Initialize the server with $\bar{x}^0 := x^0$, $\tilde{x}^0 := 0$, and $y^0 := x^0$.
   Initialize each user $i \in [n]$ with $y_i^0 := x^0$, $x_i^0 := \text{prox}_{\eta f_i}(y_i^0)$, and $\hat{x}_i^0 := 2x_i^0 - y_i^0$.

2: **For** $k := 0, \cdots, K$ **do**

3: Select i_k such that (i_k, d^k) is a realization of $(\hat{i}_k, \hat{d}^k)$.

4: [*Communication*] User i_k receives $\bar{x}^{k-d_{i_k}^k}$, a delayed version of $\bar{x}^k$ with the delay $d_{i_k}^k$.

5: [*Local update*] User i_k updates

$$y_{i_k}^{k+1} := y_{i_k}^k + \alpha(\bar{x}^{k-d_{i_k}^k} - x_{i_k}^k), \quad x_{i_k}^{k+1} := \text{prox}_{\eta f_{i_k}}(y_{i_k}^{k+1}), \quad \text{and} \quad \hat{x}_{i_k}^{k+1} := 2x_{i_k}^{k+1} - y_{i_k}^{k+1}.$$

Other users maintain $y_i^{k+1} := y_i^k$, $x_i^{k+1} := x_i^k$, and $\hat{x}_i^{k+1} := \hat{x}_i^k$ for $i \neq i_k$.

6: [*Communication*] User i_k sends $\Delta_{i_k}^k := \hat{x}_{i_k}^{k+1} - \hat{x}_{i_k}^k$ back to the server.

7: [*Sever update*] The server computes $y^{k+1} := y^k + \alpha(\bar{x}^k - y^k)$ and $\tilde{x}^{k+1} := \tilde{x}^k + \frac{1}{n}\Delta_{i_k}^k$.

8: [*Sever update*] Then, the sever updates $\bar{x}^{k+1} := \text{prox}_{\frac{n\eta}{n+1}g}\left(\frac{n}{n+1}\tilde{x}^{k+1} + \frac{1}{n+1}y^{k+1}\right)$.

9: **End For**

Illustrative example. To better understand the update of **asyncFedDR**, Figure 1 depicts a simple scenario where there are 4 users ($C1$ - $C4$) asynchronously perform updates and with $g(\cdot) = 0$. At iteration $k = 4$, user $C4$ finishes its update so that the server performs updates. During this process, user $C1$ starts its update by receiving a global model $\bar{x}^{4-d_{i_4}^4}$ from server which is the average of $(\hat{x}_1^4, \hat{x}_2^4, \hat{x}_3^4, \hat{x}_4^4)$. At iteration $t = 7$, $C1$ finishes its update. Although $\hat{x}_1$ and $\hat{x}_4$ do not change during this time, i.e. $\hat{x}_1^6 = \hat{x}_1^4$ and $\hat{x}_4^6 = \hat{x}_4^4$, $\hat{x}_2$ and $\hat{x}_3$ have been updated at $k = 5, 6$ from user $C2$ and $C3$, respectively. Therefore, the global model $\bar{x}^k$ used to perform the update at $k = 7$ is actually aggregated from $(\hat{x}_1^6, \hat{x}_2^4, \hat{x}_3^5, \hat{x}_4^6)$ not $(\hat{x}_1^6, \hat{x}_2^6, \hat{x}_3^6, \hat{x}_4^6)$. In other words, each user receives a delay estimate $\bar{x}^{k-d^k}$ where $d^k = (d_1^k, \cdots, d_n^k)$ is a delay vector and $d_i^k = \max\{t \in [k] : i_t = i\}$, i.e. the last time $\hat{x}_i$ gets updated up to iteration k. Note that when $d_i^k = 0$ for all i, Algorithm 2 reduces to its synchronous variant, i.e. a special variant of Algorithm 1 with $\mathcal{S}_k = \{i_k\}$.

Figure 1: Asynchronous update with 4 users and without regularizer g. Here, "A" blocks represent server process and "UP" blocks represent user process; C_1-C_4 are communication rounds.

4.2 Convergence analysis

Since we treat the active user i_k and the delay vector d^k jointly at each iteration k as a realization of a joint random vector $(\hat{i}_k, \hat{d}^k)$, we adopt the probabilistic model from [5] to analyze Algorithm 2. This new model allows us to cope with a more general class of asynchronous variants of our method.

Probabilistic model. Let $\xi^k := (i_k, d^k)$ be a realization of a random vector $\hat{\xi}^k := (\hat{i}_k, \hat{d}^k)$ containing the user index $\hat{i}_k \in [n]$ and the delay vector $\hat{d}^k = (\hat{d}_1^k, \cdots, \hat{d}_n^k) \in \mathcal{D} := \{0, 1, \cdots, \tau\}^n$ presented at the k-the iteration, respectively. We consider $k + 1$ random variables that form a random vector $\hat{\xi}^{0:k} := (\hat{\xi}^0, \cdots, \hat{\xi}^k)$. We also use $\xi^{0:k} = (\xi^0, \xi^1, \cdots, \xi^k)$ for $k + 1$ possible values of the random vector $\hat{\xi}^{0:k}$. Let Ω be the sample space of all sequences $\omega := \{(i_k, d^k)\}_{k \geq 0}$. We define a cylinder $\mathcal{C}_k(\xi^{0:k}) := \{\omega \in \Omega : (\omega_0, \cdots, \omega_k) = \xi^{0:k}\}$ and $\mathcal{C}_k$ is the set of all possible $\mathcal{C}_k(\xi^{0:k})$ when ξ^t, $t = 0, \cdots, k$ take all possible values, where ω_l is the l-th element of ω. Let $\mathcal{F}_k := \sigma(\mathcal{C}_k)$ be the σ-algebra generated by $\mathcal{C}_k$ and $\mathcal{F} := \sigma(\cup_{k=0}^{\infty}\mathcal{C}_k)$. For each $\mathcal{C}_k(\xi^{0:k})$ we also equip with a probability $\mathbf{p}(\xi^{0:k}) := \mathbb{P}(\mathcal{C}_k(\xi^{0:k}))$. Then, $(\Omega, \mathcal{F}, \mathbb{P})$ forms a probability space. Assume that

$\mathbf{p}(\xi^{0:k}) := \mathbb{P}(\hat{\xi}^{0:k} = \xi^{0:k}) > 0$. Our conditional probability is defined as $\mathbf{p}((i,d) \mid \xi^{0:k}) :=$
$\mathbb{P}(\mathcal{C}_{k+1}(\xi^{0:k+1}))/\mathbb{P}(\mathcal{C}_k(\xi^{0:k}))$, where $\mathbf{p}((i,d) \mid \xi^{0:k}) := 0$ if $\mathbf{p}(\xi^{0:k}) = 0$. We refer to Supp. Doc.
B.2 for more details of our probabilistic model.

To analyze Algorithm 2, we impose Assumption 4.1 on the implementation below.

Assumption 4.1. For all $i \in [n]$ and $\omega \in \Omega$, there exists at least one $t \in \{0, 1, \cdots, T\}$ with $T > 0$,
such that

$$\sum_{d \in \mathcal{D}} \mathbf{p}((i,d) \mid \xi^{0:k+t-1}) \geq \hat{\mathbf{p}} \quad \text{if } \mathbf{p}(\xi^{0:k}) > 0, \tag{6}$$

for a given $\hat{\mathbf{p}} > 0$ and any $k \geq 0$. Assume also that $d_i^k \leq \tau$ and $d_{i_k}^k = 0$ for all $k \geq 0$ and $i, i_k \in [n]$.

Assumption 4.1 implies that during an interval of T iterations, every user has a non-negligible positive
probability to be updated. Note that if the user i_k is active, then it uses recent value with no delay,
i.e., $d_{i_k}^k = 0$ as in Assumption 4.1. Moreover, the bounded delay assumption $d_i^k \leq \tau$ is standard to
analyze convergence of asynchronous algorithms, see e.g., [5, 31, 33, 34, 42].

Suppose that we choose $0 < \alpha < \bar{\alpha}$ and $0 < \eta < \bar{\eta}$ in Algorithm 2, where $c := \frac{2\tau^2 - n - 1}{(n+1)^2}$ is given,
and $\bar{\alpha} > 0$ and $\bar{\eta} > 0$ are respectively computed by

$$\bar{\alpha} := \begin{cases} 1 & \text{if } 2\tau^2 \leq n+1, \\ \frac{1}{1+2c} & \text{otherwise,} \end{cases} \quad \text{and} \quad \bar{\eta} := \begin{cases} \frac{\sqrt{16-8\alpha-7\alpha^2}-\alpha}{2L(2+\alpha)} & \text{if } 2\tau^2 \leq n+1, \\ \frac{\sqrt{16-8\alpha-(7+16c+64c^2)\alpha^2}-\alpha}{2L[2+(1+4c)\alpha]} & \text{otherwise.} \end{cases} \tag{7}$$

Next, we introduce the following two parameters:

$$\begin{cases} \rho := \begin{cases} \frac{2(1-\alpha)-(2+\alpha)L^2\eta^2-L\alpha\eta}{\alpha\eta n} & \text{if } 2\tau^2 \leq n+1, \\ \frac{2(1-\alpha-2c\alpha)-(2+\alpha+4c\alpha)L^2\eta^2-L\alpha\eta}{\alpha\eta n} & \text{otherwise,} \end{cases} \\ \theta := \begin{cases} \frac{\alpha(2-\alpha)}{n\eta} & \text{if } 2\tau^2 \leq n+1, \\ \frac{\alpha(2-\alpha-2c\alpha)}{\eta n} & \text{otherwise.} \end{cases} \end{cases} \tag{8}$$

Then, both ρ and θ are positive. For the sake of notation, we also introduce two positive parameters:

$$D_1 := \frac{16\alpha^2(1+L^2\eta^2)(\tau^2+2Tn\hat{\mathbf{p}}) + 8(n+1)^2(1+L^2\eta^2+T\alpha^2\hat{\mathbf{p}})}{\hat{\mathbf{p}}\alpha^2(n+1)^2} \quad \text{and} \quad D_2 := \frac{8\alpha^2(\tau^2+2\hat{\mathbf{p}}Tn)}{\hat{\mathbf{p}}(n+1)^2}. \tag{9}$$

We emphasize that though these formulas look complicated, they are computed explicitly without any
tuning. Theorem 4.1 proves the convergence of Algorithm 2, whose analysis is in Supp. Doc. B.

Theorem 4.1. *Suppose that Assumption 2.1, 2.2, and 4.1 hold. Let $\bar{\alpha}, \bar{\eta}, \rho, \theta, D_1,$ and D_2 be given
by (7), (8), and (9), respectively. Let $\{(x_i^k, y_i^k, y^k, \bar{x}^k)\}$ be generated by Algorithm 2 with stepsizes
$\alpha \in (0, \bar{\alpha})$ and $\eta \in (0, \bar{\eta})$. Then, the following bound holds:*

$$\frac{1}{K+1}\sum_{k=0}^{K} \mathbb{E}\big[\|\mathcal{G}_{\frac{n\eta}{n+1}}(\bar{x}^k)\|^2\big] \leq \frac{\hat{C}\big[F(x^0)-F^\star\big]}{K+1}, \tag{10}$$

where $\hat{C} := \frac{2(n+1)}{n^2\eta^2}\left[\frac{(1+\eta L)^2 D_1}{\rho} + \frac{(1+\eta L)^2 D_2+1}{\theta}\right] > 0$ depending on $n, L, \eta, \alpha, \tau, T,$ and $\hat{\mathbf{p}}$.

*Let $\tilde{x}_K$ be selected uniformly at random from $\{\bar{x}^0, \cdots, \bar{x}^K\}$ as the output of Algorithm 2. Then, after
at most $K := \mathcal{O}\left(\varepsilon^{-2}\right)$ iterations, $\tilde{x}^K$ is an ε-stationary point of (1) as in Definition 2.2.*

Remark 4.1. From Theorem 4.1, we can see that **asyncFedDR** achieves the same worst-case commu-
nication complexity $\mathcal{O}\left(\varepsilon^{-2}\right)$ (up to a constant factor) as **FedDR**, but with smaller α and η.

5 Numerical Experiments

To evaluate the performance of **FedDR** and **asyncFedDR**, we conduct multiple experiments using
both synthetic and real datasets. Since most existing methods are developed for non-composite
problems, we also implement three other methods: **FedAvg**, **FedProx**, and **FedPD** to compare for
this setting. We use training loss, training accuracy, and test accuracy as our performance metrics.

Implementation. To compare synchronous algorithms, we reuse the implementation of FedAvg
and FedProx in [23] and implement FedDR and FedPD on top of it. To conduct the asynchronous

examples, we implement our algorithms based on the asynchronous framework in [3]. All experiments are run on a Linux-based server with multiple nodes and configuration: 24-core 2.50GHz Intel processors, 30M cache, and 256GB RAM.

Models and hyperparameters selection. Our models are neural networks, and their detail is given in Supp. Doc. C. As in [23], we use the same local solver (SGD) for all algorithms. Parameters for each algorithm such as μ for FedProx, η for FedPD, and α and η for FedDR are tuned from a wide range of values. For each dataset, we pick the parameters that work best for each algorithm and plot their performance on the chosen parameters.

Results on synthetic datasets. We compare these algorithms using synthetic dataset in both iid and non-iid settings. We follow the data generation procedures described in [23, 36] to generate one iid dataset `synthetic-iid` and three non-iid datasets: `synthetic-(r,s)` for $(r,s) = \{(0,0),(0.5,0.5),(1,1)\}$. We first compare these algorithms without using the user sampling scheme, i.e. all users perform update at each communication round, and for non-composite model of (1).

Figure 2: The performance of 4 algorithms on non-iid synthetic datasets without user sampling

We report the performance of these algorithms on one non-iid dataset in Figure 2, but more results can be found in Sup. Doc. C. FedDR and FedPD are comparable in these datasets and they both outperform FedProx and FedAvg. FedProx works better than FedAvg which aligns with the results in [23]. However, when comparing on more datasets, our algorithm overall performs better than others.

Now we compare these algorithms where we sample 10 users out of 30 to perform update at each communication round for FedAvg, FedProx, and FedDR while we use all users for FedPD since FedPD only has convergence guarantee for this setting. In this test, the evaluation metric is plotted in terms of the number of bytes communicated between users and server at each communication round. Note that using user sampling scheme in this case can save one-third of communication cost each round. Figure 3 depicts the performance of 4 algorithms on one dataset, see also Sup. Doc. C.

Figure 3: The performance of 4 algorithms with user sampling scheme on non-iid synthetic datasets.

From Figure 3, FedDR performs well compared to others. FedProx using user sampling scheme performs better and is slightly behind FedPD while FedDR, FedPD, and FedProx outperform FedAvg.

Results on FEMNIST datasets. FEMNIST [4] is an extended version of the MNIST dataset [19] where the data is partitioned by the writer of the digit/character. It has a total of 62 classes (10 digits, 26 upper-case and 26 lower-case letters) with over 800,000 samples. In this example, there are total of 200 users and we sample 50 users to perform update at each round of communication for FedAvg, FedProx, and FedDR while we use all users to perform update for FedPD. Fig. 4 depicts the performance of 4 algorithms in terms of communication cost. From Fig. 4, FedDR can achieve lower loss value and higher training accuracy than other algorithms while FedPD can reach the same test accuracy as ours at the end. Overall, FedDR seems working better than other algorithms in this test.

Figure 4: The performance of 4 algorithms on the FEMNIST dataset.

Results with the ℓ_1-norm regularizer. We now consider the composite setting with $g(x) :=$
$0.01 \left\| x \right\|_1$ to verify Algorithm 1 on different inexactness levels $\epsilon_{i,k}$ by varying the learning rate (lr)
and the number of local SGD epochs to approximately evaluate $\mathrm{prox}_{\eta f_i}(y_i^k)$. We run Algorithm 1 on
the FEMNIST dataset, and the results are shown in Figure 5.

Figure 5: The performance of **FedDR** on `FEMNIST` dataset in composite setting.

We observe that Algorithm 1 works best when local learning rate is 0.003 which aligns with [23] for
the non-composite case. It also performs better when we decrease $\epsilon_{i,k}$ by increasing the number of
epochs in evaluating $\mathrm{prox}_{\eta f_i}$. This performance confirms our theoretical results in Supp. Doc. A.4.

Results using asynchronous update. To illustrate the advantage of asyncFedDR over FedDR, we
conduct another example to train MNIST dataset using 20 users. Since we run these experiments
on computing nodes with identical configurations, we simulate the case with computing power
discrepancy between users by adding variable delay to each user's update process such that the
difference between the fastest user may be up to twice as fast as the slowest one.

Figure 6: The performance of **FedDR** and **asyncFedDR** on the MNIST dataset.

The results of two variants are presented in Figure 6, see Supp. Doc. C for more examples. We can
see that asyncFedDR can achieve better performance than FedDR in terms of training time which
illustrate the advantage of asynchronous update in heterogeneous computing power.

References

[1] H. H. Bauschke and P. Combettes. *Convex analysis and monotone operators theory in Hilbert spaces*. Springer-Verlag, 2nd edition, 2017.

[2] D.P. Bertsekas and J. N. Tsitsiklis. *Parallel and distributed computation: Numerical methods*. Prentice Hall, 1989.

[3] Jesse Cai. Implementing DistBelief. https://jcaip.github.io/Distbelief/, 2018.

[4] S. Caldas, S. M. K. Duddu, P. Wu, T. Li, J. Konečnỳ, H. B. McMahan, V. Smith, and A. Talwalkar. Leaf: A benchmark for federated settings. *arXiv preprint arXiv:1812.01097*, 2018.

[5] L. Cannelli, F. Facchinei, V. Kungurtsev, and G. Scutari. Asynchronous parallel algorithms for nonconvex optimization. *Math. Program.*, pages 1–34, 2019.

[6] Z. Charles and J. Konečnỳ. Convergence and accuracy trade-offs in federated learning and meta-learning. In *International Conference on Artificial Intelligence and Statistics*, pages 2575–2583. PMLR, 2021.

[7] P. Combettes and J. Eckstein. Asynchronous block-iterative primal-dual decomposition methods for monotone inclusions. *Mathematical Programming*, 168(1):645–672, 2018.

[8] P. L. Combettes and J.-C. Pesquet. Stochastic quasi-Fejér block-coordinate fixed point iterations with random sweeping. *SIAM J. Optim.*, 25(2):1221–1248, 2015.

[9] M. N. Dao and M. K. Tam. A Lyapunov-type approach to convergence of the Douglas–Rachford algorithm for a nonconvex setting. *Journal of Global Optimization*, 73(1):83–112, 2019.

[10] E. Gorbunov, F. Hanzely, and P. Richtárik. Local SGD: Unified theory and new efficient methods. In *International Conference on Artificial Intelligence and Statistics*, pages 3556–3564. PMLR, 2021.

[11] F. Haddadpour, M. M. Kamani, M. Mahdavi, and V. Cadambe. Local SGD with periodic averaging: Tighter analysis and adaptive synchronization. In *Advances in Neural Information Processing Systems*, pages 11082–11094, 2019.

[12] F. Haddadpour, M. M. Kamani, A. Mokhtari, and M. Mahdavi. Federated learning with compression: Unified analysis and sharp guarantees. In *International Conference on Artificial Intelligence and Statistics*, pages 2350–2358. PMLR, 2021.

[13] F. Haddadpour and M. Mahdavi. On the convergence of local descent methods in federated learning. *arXiv preprint arXiv:1910.14425*, 2019.

[14] F. Hanzely, S. Hanzely, S. Horváth, and P. Richtárik. Lower bounds and optimal algorithms for personalized federated learning. *arXiv preprint arXiv:2010.02372*, 2020.

[15] S. P. Karimireddy, M. Jaggi, S. Kale, M. Mohri, S. J. Reddi, S. U. Stich, and A. A. Suresh. Mime: Mimicking centralized stochastic algorithms in federated learning. *arXiv preprint arXiv:2008.03606*, 2020.

[16] S. P. Karimireddy, S. Kale, M. Mohri, S. Reddi, S. Stich, and A. T. Suresh. Scaffold: Stochastic controlled averaging for federated learning. In *International Conference on Machine Learning*, pages 5132–5143. PMLR, 2020.

[17] A. Khaled, K. Mishchenko, and P. Richtárik. First analysis of local GD on heterogeneous data. *arXiv preprint arXiv:1909.04715*, 2019.

[18] J. Konečnỳ, H. B. McMahan, D. Ramage, and P. Richtárik. Federated optimization: Distributed machine learning for on-device intelligence. *arXiv preprint arXiv:1610.02527*, 2016.

[19] Y. LeCun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

[20] G. Li and T. K. Pong. Global convergence of splitting methods for nonconvex composite optimization. *SIAM J. Optim.*, 25(4):2434–2460, 2015.

[21] G. Li and T. K. Pong. Douglas–Rachford splitting for nonconvex optimization with application to nonconvex feasibility problems. *Mathematical programming*, 159(1-2):371–401, 2016.

[22] T. Li, A. K. Sahu, A. Talwalkar, and V. Smith. Federated learning: Challenges, methods, and future directions. *IEEE Signal Processing Magazine*, 37(3):50–60, 2020.

[23] T. Li, A. K. Sahu, M. Zaheer, M. Sanjabi, A. Talwalkar, and V. Smith. Federated optimization in heterogeneous networks. In I. Dhillon, D. Papailiopoulos, and V. Sze, editors, *Proceedings of Machine Learning and Systems*, volume 2, pages 429–450, 2020.

[24] X. Li, K. Huang, W. Yang, S. Wang, and Z. Zhang. On the convergence of FedAvg on non-iid data. *arXiv preprint arXiv:1907.02189*, 2019.

[25] X. Li, M. Jiang, X. Zhang, M. Kamp, and Q. Dou. FedBN: Federated learning on non-iid features via local batch normalization. *arXiv preprint arXiv:2102.07623*, 2021.

[26] T. Lin, S. U. Stich, K. K. Patel, and M. Jaggi. Don't use large mini-batches, use local SGD. *arXiv preprint arXiv:1808.07217*, 2018.

[27] P. L. Lions and B. Mercier. Splitting algorithms for the sum of two nonlinear operators. *SIAM J. Num. Anal.*, 16:964–979, 1979.

[28] B. McMahan, E. Moore, D. Ramage, S. Hampson, and B. A. y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Artificial Intelligence and Statistics*, pages 1273–1282. PMLR, 2017.

[29] B. McMahan and D. Ramage. Federated learning: Collaborative machine learning without centralized training data, Jul 2017.

[30] H Brendan McMahan et al. Advances and open problems in federated learning. *Foundations and Trends® in Machine Learning*, 14(1), 2021.

[31] L. Nguyen, P. H. Nguyen, M. Dijk, P. Richtárik, K. Scheinberg, and M. Takác. SGD and Hogwild! convergence without the bounded gradients assumption. In *International Conference on Machine Learning*, pages 3750–3758. PMLR, 2018.

[32] R. Pathak and M. J. Wainwright. FedSplit: An algorithmic framework for fast federated optimization. *arXiv preprint arXiv:2005.05238*, 2020.

[33] Z. Peng, Y. Xu, M. Yan, and W. Yin. ARock: an algorithmic framework for asynchronous parallel coordinate updates. *SIAM J. Scientific Comput.*, 38(5):2851–2879, 2016.

[34] Benjamin Recht, Christopher Re, Stephen Wright, and Feng Niu. Hogwild!: A Lock-Free Approach to Parallelizing Stochastic Gradient Descent. In J. Shawe-Taylor, R. S. Zemel, P. L. Bartlett, F. Pereira, and K. Q. Weinberger, editors, *Advances in Neural Information Processing Systems 24*, pages 693–701. Curran Associates, Inc., 2011.

[35] P. Richtárik and M. Takáč. Parallel coordinate descent methods for big data optimization. *Math. Program.*, 156(1-2):433–484, 2016.

[36] O. Shamir, N. Srebro, and T. Zhang. Communication-efficient distributed optimization using an approximate newton-type method. In *International conference on machine learning*, pages 1000–1008, 2014.

[37] S. U. Stich. Local SGD converges fast and communicates little. *arXiv preprint arXiv:1805.09767*, 2018.

[38] A. Themelis and P. Patrinos. Douglas–Rachford splitting and ADMM for nonconvex optimization: Tight convergence results. *SIAM Journal on Optimization*, 30(1):149–181, 2020.

[39] J. Wang and G. Joshi. Cooperative SGD: A unified framework for the design and analysis of communication-efficient SGD algorithms. *arXiv preprint arXiv:1808.07576*, 2018.

[40] B. Woodworth, K. K. Patel, and N. Srebro. Minibatch vs local SGD for heterogeneous distributed learning. *arXiv preprint arXiv:2006.04735*, 2020.

[41] B. Woodworth, K. K. Patel, S. U. Stich, Z. Dai, B. Bullins, H. B. McMahan, O. Shamir, and N. Srebro. Is local SGD better than minibatch SGD? *arXiv preprint arXiv:2002.07839*, 2020.

[42] C. Xie, S. Koyejo, and I. Gupta. Asynchronous federated optimization. *arXiv preprint arXiv:1903.03934*, 2019.

[43] H. Yu, S. Yang, and S. Zhu. Parallel restarted sgd with faster convergence and less communication: Demystifying why model averaging works for deep learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 5693–5700, 2019.

[44] P. Yu, L. Wynter, and S. H. Lim. Fed+: A family of fusion algorithms for federated learning. *arXiv preprint arXiv:2009.06303*, 2020.

[45] H. Yuan, M. Zaheer, and S. Reddi. Federated composite optimization. *arXiv preprint arXiv:2011.08474*, 2020.

[46] J. Zhang, C. De Sa, I. Mitliagkas, and C. Ré. Parallel sgd: When does averaging help? *arXiv preprint arXiv:1606.07365*, 2016.

[47] X. Zhang, M. Hong, S. Dhople, W. Yin, and Y. Liu. FedPD: A federated learning framework with optimal rates and adaptivity to non-iid data. *arXiv preprint arXiv:2005.11418*, 2020.

[48] Y. Zhao, M. Li, L. Lai, N. Suda, D. Civin, and V. Chandra. Federated learning with non-iid data. *arXiv preprint arXiv:1806.00582*, 2018.

[49] L. Zhu, Z. Liu, and S. Han. Deep leakage from gradients. In *Advances in Neural Information Processing Systems*, pages 14774–14784, 2019.