Compact Encoding of Words for Efficient Character-level Convolutional Neural Network Text Classification

Abstract

This paper reports the empirical exploration of a novel approach to encode words using compressing inspired techniques for use on convolutional neural networks at character-level. This approach reduces drastically the number of parameters to be optimized using deep learning, resulting in competitive classification accuracy values in only a fraction of the time spent by characters level convolutional neural networks, enabling training in simpler hardware.

1 Introduction

Document classification is one of the principal tasks addressed in the context of natural language processing (Sebastiani, 2002). It implies associating a document —or any text fragment, for that matter— with a category or label relying on their content.

The increasing availability of texts in digital form, especially through the Internet, has called for the development of statistical and artificial intelligence tools for automating this process. Spam detectors, sentiment analysis, news archiving, among many others, demand high-quality text classifiers.

Work on document classification encompasses a broad range of approaches (see (Sebastiani, 2002; Aggarwal & Zhai, 2012; Hotho et al., 2005; Kosala & Blockeel, 2000)). An important portion of those approaches relies on a representation that handles words as the atomic element of text. Consequently, those methods carry out their analysis through statistics of words occurrence (Zhang et al., 2015). However, the variability of words and structures belonging to a language makes this task difficult. That is why, such models have a superior performance in specific domains, where the vocabulary can be restricted to a relatively small number of words, possibly chosen by a specialist. Furthermore, such modeling becomes specific to a language, causing the replication process in another language to be carried out from scratch (Zhang et al., 2015).

In recent years, we have experienced a revolution in the machine learning with the advent of deep learning methods (Goodfellow et al., 2016). The development of convolutional neural networks (CNNs) (LeCun et al., 1998) coupled with the popularization of parallel computing libraries (e. g. Theano (Bergstra et al., 2010), Tensorflow (Abadi et al., 2015), Keras (Chollet et al., 2015), etc.) that simplify general-purpose computing on graphics processing units (GPGPU) (Mittal & Vetter, 2015) has been successful in tackling image classification problem (Krizhevsky et al., 2012) quickly becoming the state of the art of the field.

The success of CNNs in the image classification domain has prompted the interest to extend the deep learning principles to the document classification domain. Some existing methods have been updated but the clear majority are still based on the tokenization of words and the inference of their statistics. Bag of Words (BOW) (Johnson & Zhang, 2014) and word2vec (Mikolov et al., 2013) are some of the most popular strategies.

The replication of image classification success in the documents domain faces as main challenge the difficulty of representing text as numerical tensors. In a groundbreaking paper, Zhang et al. (2015) suggested an approach that considers the characters as the atomic elements of a text. This representation provides a robust, language-independent representation of texts as matrices, that were used as inputs of different CNNs. Their experimental results showed that this approach was able to attain and, in some cases, improve the state of the art results in complex text classification problems.

In spite of that, the impact of this idea was hampered by the large computational demands of the approach, since its training can took days per epoch in complex problems.

In this paper, we propose an efficient character-level encoding of text derived from the tagged Huffman (Silva de Moura et al., 2000) information compression technique that takes into account the character frequency to assign shorter codes to the most frequently used ones. This novel text encoding makes the idea put forward by Zhang et al. (2015) more computationally accessible by reducing its training requirements in terms of time and memory.

The proposed encoding makes possible to represent larger portions of texts in a less sparse form while preserving the ability to encode any word, even those not present in the training dataset ones. In order to study the impact of this encoding, we coupled it with two convolutional neural networks architectures. The experimental studies performed showed that we managed to achieve a performance similar or in some cases better than the state of the art at a fraction of the training time even if we employed a simpler hardware setup.

Our main contribution is to show that this novel character-level text encoding produces a reduced input matrix, leading to a substantial reduction in training times while producing comparable or better results in terms of accuracy than the original approach by Zhang et al. (2015). This opens the door to more complex applications, the use of devices with lower computational power and the exploration of other approaches that can be coupled with input representation.

The rest of the paper is structured as follows. In the next section, we deal with the theoretical foundations and motivation that are required for the ensuing discussions. There we also analyze the alternatives to character-level text compression that were taken into account for producing our proposal. After that, in Section 3, we describe the encoding procedure and the neural network architectures that will take part of the experiments. Subsequently, in Section 4, we replicate the experiments of Zhang et al. (2015) in order to contrast our proposal with theirs under comparable conditions. Finally, in Section 5, we provide some final remarks, conclusive comments and outline our future work directions.

2 Preliminaries

The success in using Convolutional Neural Networks (CNNs) (LeCun et al., 1998) in image classification (Krizhevsky et al., 2012) flourish with the development of many libraries (Chetlur et al., 2014; Chollet et al., 2015; Bergstra et al., 2010), techniques and hardware. The effort to use CNNs for text classification tasks is justified by the possibility of appropriating these tools for obtaining better results and more robust algorithms, facilitating the use of the same approach for several applications.

There are two usual approaches to use CNNs for handling textual information: the (i) bag of words (BoW) (Johnson & Zhang, 2014) and (ii) word2vec (Mikolov et al., 2013) approaches.

In the case of BoW and some of its variants, for representing each word in a vocabulary of size N, a digit 1 is placed in the correspondent position of that word in a $1 \times N$ vector, all others positions remaining with digit 0. Since natural languages usually have a large vocabulary, a limited subset of the vocabulary must be used in order to make viable to perform the necessary computations in terms of memory requirements. The chosen subset of the vocabulary must be representative of the texts. Therefore, in practical problems, a great deal of attention is devoted to this matter. In particular, it is common to involve an application domain specialist or use some kind of word frequency statistic or relevance metric, where the most frequent and rare words are excluded.

In the word2vec approach, each word is projected via a metric embedding of fixed size, representing its co-occurrence in a large corpus of text in the same language of the texts of interest. It is possible to use pretrained vectors or readjust the representation with new words. The main problem with both strategies is that it does not allows to represent words that are not in the training dataset. Typos, spelling errors, mixed up letters and text written in languages with a complex structure (declensions, conjugations, etc.) are completely ignored.

Establishing the character as the basic unit of text formation provides a better opportunity to be robust to typos, acceptance of neologisms, and other textual forms as equations and chemical formulas, abbreviations and idiosyncrasies of written language on the internet, such as emoticons, slang and

dialects of the online world, etc. Assuming the word as a base item, much of this ability is lost, especially when models assume that text producers use a formal language.

Zhang et al. (2015) put forward an important innovation in this regard. They represent text as a sequence of characters, not words. Consequently, they are capable of reducing the vocabulary of symbols to the size of the alphabet (69 in the case of the paper) and thus allowing the use of one-hot encoding (Harris & Harris, 2012).In the paper, they represented a text as a matrix of size 1014×69 where each row corresponds to a position in the text sequence and columns with the presence or not of a given character. Therefore, a row with a 1 in a given column indicates that the presence of the corresponding character in that point of the text. With this representation on hand, they applied a CNN and obtained results competitive with other techniques, and in some cases improving the state of the art. However, the main drawback of its large computational requirements, that in some cases called for one or two days per training epoch.

The results obtained by them suggest that language, and therefore, text, can be treated as a sequence of signals, like any other (Zhang et al., 2015). However, the training times and the dimension of the matrices to be computed are still obstacles to the most effective use of the method. That is why a better encoding of text could be a right path towards a substantial improvement if this issue.

3 COMPRESSED ENCODING FOR CNN-BASED TEXT CLASSIFICATION

Searching for a way to reduce these training time while retaining the flexibility and power of character-level convolutional to classify text, we found a way to better encode texts. Our approach, with competitive accuracy, achieve a significant reduction in time execution from hours to minutes and from days to hours, by epoch.

To achieve this performance in execution, our approach consisted of two elements:

- *Obtaining a shorter representation*: At first, we though of using some form of encoding each character, and use the same approach of Zhang et al. (2015) but we realize that using a variable length encoding for each word could be more efficient. To do this we need a way to encode each char, generating distinct concatenated code for representing each word and that words with the same prefix were near each other, especially to respond well to declensions.

- *Obtaining a sparse representation*: To take full advantage of libraries of tensor multiplications like NVidia CuDNN (Chetlur et al., 2014), we need a representation that was sparse, so our code should be composed of many 0s and a few 1s.

3.1 COMPRESSED REPRESENTATIONS

Although the Huffman encoding (Huffman, 1952) yields shortest possible, it does not generate unique representations once we concatenate encoded characters to form a word. We investigated encoding of Brisaboa et al. (2003) and found promising alternatives.

Our approach is based on the Tagged Huffman encoding (Silva de Moura et al., 2000), where a pair of '0' digits is the signal and the digit '1' is the tag of beginning and end code, the only difference is that for our approach, we need a shorter version to reduce the size of input matrix, so we choose to use only one digit 0 instead of two for each char, marking the beginning and the end of each char code with a digit 1, the same way.

As in the approach by Silva de Moura et al. (2000), the coding we employ has the following advantages (Brisaboa et al., 2003):

1. No character code is a prefix of another, that is, the match is one-to-one.

2. It allows a direct search, that is, to search for a word in an encoded document, just encode the word and use traditional methods of comparing strings with the encoded document.

3. This encoding approach is a compression technique, so it also allows saving already encoded text documents permanently using a binary system, requiring less storage space.

Table 1: Example of coding using English language ranking of characters. Characters shown are the ones used in the subsequent examples.

CHARACTER	FREQ. RANK	COMPRESSED ENCODING
␣	0	11
e	1	101
a	2	1001
t	3	10001
i	4	100001
s	5	1000001
n	7	100000001
r	8	1000000001
d	10	100000000001
h	11	1000000000001
c	12	10000000000001
g	17	1000000000000000001
⋮	⋮	⋮
	n	$'1' + n \times '0' + '1'$

These advantages become attractive especially if the goal is to extract knowledge about files in a repository to perform various classifications on different dimensions with the same files.

A possible advantage of this encoding over others strategies that use a word as an atomic representation of text is better respond to unseen words on training data, once that the network at least have some prefix to guess the meaning of the word, the same way we humans do. This is especially interesting in languages where there are a lot of declensions like Portuguese, Spanish, Italian, French, Russian, German, Arabic and Turkish, for example.

The coding procedure is not restricted to any size of vocabulary, the only problem is that less frequent characters will generate bigger codes, consequently, bigger encoding matrix. If your database has a lot of them, you could use a higher word code size.

Our main contribution is demonstrate that such approach reduces the dimensionality of the encoded matrix, substantially reducing training time and allow the use of devices with lower computational power, remaining with competitive accuracy.

3.2 ENCODING PROCEDURE

In all of our experiments, we used the following procedure to encode words:

- *Obtaining a character frequency rank*: We read the text database and count the frequency of each character, generating a list sorted by frequency of occurrence. Then we create a rank with only the relative positions of the characters. For a given language, this rank is quite stable since only the order of the rank is used. This means that if all documents are in the same idiom, this procedure can be replaced by a list with the characters rank of frequency for that language.

- *Creating a mapping from character to compress code*: To encode each character, we insert the digit 0 in the same amount of the rank position of the character, between a 1 digit to signal the begin and another 1 digit to signal the end of the code. Table 1 have some examples of encoded characters.

To encode each word, we just concatenate the codes of each character. As an example, we provide in Table 2 some examples of plain text words and their corresponding encoding.

Given a document, we consider that it is composed of words, being those any set of characters limited by the space character. This means 'word' could be math equations, web addresses, LaTeX code, computer programming commands, etc. In Table 2 we can see that this encoding could represent words with the same prefix in vectors that have same initial coordinates. Slangs like *tl;dr : too long,*

Table 2: Example of coding using English language ranking of characters. Prefix common to more than an word are underscored

TEXT	ENCODED TEXT
science	10000011000000000001100001101100000000110000000000001101
scientist	10000011000000000001100001101100000000110001100001100000110001
art	1001100000000110001
artist	1001100000000110001100001100000110001
tl;dr	10001100000000011000000000000000000000000000001100000000000011000000001
u2	100000000000000011000000000000000000000000000001
e^a	1011000000000000000000000000000000000000000000000000000000000011001

Figure 1: Matrix encoding of sentence 'Research is an art and a science'. The text is encoded one word per row. Each word is underscored for easy identification.

10000000011011000001101100110000000011000000000000110000000000010
100001100000100000000000000000000000000000000000000000000000000000
1001100000000100000000000000000000000000000000000000000000000000000
1001100000000110001000000000000000000000000000000000000000000000000
10011000000001100000000010000000000000000000000000000000000000000000
100100000000000000000000000000000000000000000000000000000000000000000
1000001100000000000011000011011000000001100000000000001101000000000000
0000000000000000000000000000000000000000000000000000000000000000000

did not read and *u2 : you too* as well mathematical expressions like e^a could be manipulated. In the matrix representation of the document, each row represents a properly encoded word.

The code for each word is then embedded in a matrix of $number\ of\ words \times code\ size$ with its first symbol in column 1. Columns that were not occupied are padded with 0, larger codes are represented up to the chosen limit. Unoccupied lines are filled with 0 and larger documents are represented only up to the chosen maximum number of words, ignoring the last remaining ones. As an example, we represent a document in an 8×65 matrix in Figure 1.

In the example in Figure 1 we used a 8×65 matrix (520 elements) to encode the text with a certain amount of slack. At the very least, we would need 7×64 (448 elements). In contrast, the approach of Zhang et al. (2015) would employ at least 69×32 (2208) elements to represent the same sentence.

In our experiments, 256 coordinates were enough to represent 99.5% of the words from one of the databases studied. In all datasets studied in this paper, we choose 128 as a limit of words to represent a document, encoding each text in a 128×256 matrix.

3.2.1 CONVOLUTIONAL NETWORK MODEL

As mentioned before, this work was prompted by the results of Zhang et al. (2015). In their original approach, they encode each character using one-hot encoding in a vocabulary of 69 elements. The non-space characters are letters, numbers and punctuation. The model is composed of 9 layers, 6 of convolutions and 3 fully connected. Their architecture is described in Table 3.

They used stochastic gradient descent (SGD) with a minibatch of size 128, using momentum 0.9 and initial step size 0.01 which is halved every 3 epochs for 10 times. So, their results were obtained in at least 30 epochs.

3.3 NEURAL NETWORK ARCHITECTURES

To verify the efficiency of the encoding procedure, we realized 2 experiments, named CNN1 and CNN2:

Figure 2: Network architectures used coupled with the compressed encoding.

3.4 CNN1 TOPOLOGY

At first, we choose a network architecture that we usually use to classify text using an embedding created by word2vec (Mikolov et al., 2013), the only difference is that instead of 300 features, we reduce the input size to 256. This architecture we named CNN1. It is based on concatenation of convolutions in a shallow way, inspired by work of Kim (2014), who achieve state of the art results for some databases.

We trained this model for 5 epochs. The neural network architecture is summarized in Figure 2a as a diagram.

3.5 CNN2 TOPOLOGY

Prompted by the positive outcome of CNN1, we decided to investigate others possible architectures. We created another shallow but wide convolution architecture following the recommendations of

Table 3: Architecture of Zhang et al. (2015). Lg-Large, Sm- Small

CONVOLUTIONS

Layer	Large Feature	Small Feature	Kernel	Poll
1	1024	256	7	3
2	1024	256	7	3
3	1024	256	3	—
4	1024	256	3	-
5	1024	256	3	-
6	1024	256	3	3

FULLY CONNECTED

Layer	Large Feature Out	Small Feature Out	Dropout
7	2048	1014	.5
8	2048	1014	.5
9	Depends on the problem		

Zhang & Wallace (2015) for choosing parameters, executing training on dataset ag_news, for being the smallest of our test datasets. This architecture is composed by:

- *Convolution width filter*: a combination of region sizes near the optimal single best region size outperforms using multiple region sizes far from the optimal single region size (Zhang & Wallace, 2015). We scan the width from 1 to 7 comparing accuracy performance. In these evaluations, the convolution of width 1 was a better option.

- *Pooling size*: max pooling consistently performs better than alternative strategies for the task of sentence classification (Zhang & Wallace, 2015).

4 EXPERIMENTAL STUDY

An essential part of this work is to contrast our proposal both within the context of character-level text classification and with other state-of-the-art approaches.

The databases used were the same as those cited in an article by Zhang et al. (2015), where there is an extensive description of them.[1] A detailed analysis of these datasets is out of the scope of this paper, instead, we will only summarize the main characteristics:

- **Ag_news**: categorized news articles from more than 2000 news sources. Four classes (World, Sports, Business, SciTech).The dataset contains 120k train samples and 7.6k test samples equally distributed (Zhang et al., 2015).

- **Sogou_news**: categorized news articles originally in Chinese. Zhang et al. (2015) applied a *pypinyin* package combined with *jieba* Chinese segmentation system to produce Pinyin – a phonetic romanization of Chinese. Five classes (sports, finance, entertainment, automobile and technology). The dataset contains 450k train samples and 60k test samples equally distributed (Zhang et al., 2015).

- **DBpedia**: title and abstract from Wikipedia articles available in DBpedia crowd-sourced community (Lehmann et al., 2015). Fourteen 14 nonoverlapping classes from DBpedia 2014. The dataset contains 560k train samples and 70k test samples equally distributed (Zhang et al., 2015).

---

[1]For the sake of replicability we have made all the datasets available via `https://drive.google.com/open?id=1o5CNT0UHuFfHBxC-Mz4ImFpN2-Lcllmx`.

- **Yelp_full**: sentiment analysis from the Yelp Dataset Challenge in 2015[2]. Five classes representing the number of stars a user has given.The dataset contains 560k train samples and 38k test samples equally distributed. (Zhang et al., 2015).

- **Yelp_full**: sentiment analysis from the Yelp Dataset Challenge in 2015[2]. Rating of 1 and 2 stars are represented as Bad and 4 and 5 as Good. The dataset contains 560k train samples and 50k test samples equally distributed. (Zhang et al., 2015).

- **Yahoo_answers**: questions and their answers from Yahoo Answers. Ten classes (Society & Culture, Science & Mathematics, Health, Education & Reference, Computers & Internet, Sports, Business & Finance, Entertainment & Music, Family & Relationships, Politics & Government). Each sample contains question title, question content and best answer.The dataset contains 1400k train samples and 60k test samples (Zhang et al., 2015).

- **Amazon_full**: sentiment analysis from Amazon review dataset from the Stanford Network Analysis Project (SNAP) (McAuley & Leskovec, 2013). Five classes representing the number of stars a user has given. The dataset contains 3000k train samples and 650k test samples.(Zhang et al., 2015).

- **Amazon_polarity**: sentiment analysis from Amazon review dataset from the Stanford Network Analysis Project (SNAP) (McAuley & Leskovec, 2013). Two classes, rating of 1 and 2 stars are represented as Bad and 4 and 5 as Good. Dataset contains 3000k train samples and 650k test samples.(Zhang et al., 2015). The dataset contains 3600k train samples and 400k test samples equally distributed.(Zhang et al., 2015).

The baseline comparison models are the same of Zhang et al. (2015) where there is an extensive description of them, we just reproduce their results, the only difference is that they report loss error and for better comprehension, we translated it to accuracy. In Zhang et al. (2015) there is an extensive description of them. In this paper, we just summarize the main information:

- **Bag of Words (BoW) and its term-frequency inverse-document-frequency (BoW TFIDF)**: For each dataset, they selected 50,000 most frequent words from the training subset. For the normal bag-of-words, they used the counts of each word as the features and for the TFIDF they used the counts as the term-frequency (Zhang et al., 2015).

- **Bag-of-ngrams (Ngrams) and its TFIDF (Ngrams TFIDF)**: The bag-of-ngrams models were constructed by selecting the 500,000 most frequent n-grams (up to 5-grams) from the training subset for each dataset. The feature values were computed the same way as in the bag-of-words model (Zhang et al., 2015).

- **Bag-of-means on word embedding**: an experimental model that uses k-means on word2vec (Mikolov et al., 2013) learned from the training subset of each dataset, and then used these learned means as representatives of the clustered words. Took into consideration all the words that appeared more than 5 times in the training subset. The dimension of the embedding is 300. The bag-of-means features are computed the same way as in the bag-of-words model. The number of means is 5000 (Zhang et al., 2015).

- **Long Short Term Memory (LSTM)**: The LSTM (Mikolov et al., 2013) model used in our case is word-based, using pretrained word2vec embedding of size 300. The model is formed by taking a mean of the outputs of all LSTM cells to form a feature vector, and then using multinomial logistic regression on this feature vector. The output dimension is 512 (Zhang et al., 2015).

For all the experiments, we used the environment and parameters settings listed in Table 4. Besides the encoding procedure, we do not use any preprocessing strategy except the use of lowercase letters. No data enhancement technique was employed.

All the results and comparison with traditional models and the approach of Zhang et al. (2015) is shown in Table 5. On Table 6, we did a time execution comparison, based on reports available by Zhang et al. (2015).

The main objective of this research was to evaluate the possibility of using a coding approach that contemplated the construction of words using characters as basic tokens. Our main contribution is

---

[2]https://www.yelp.com/dataset/challenge

Table 4: Training environment and parameters

DESCRIPTION	PARAMETERS	OBSERVATION
Neural Net Lib.	Keras 2.0	
Tensor Backend	Theano 0.9	
GPU Interface	Cuda 8	with cuBLAS Patch Update
CNN optimizer	Nvidia Cudnn 5.1	
Program. Lang.	Python 3.6	using Anaconda 4.4.0
Superbatch	10000	Number of matrixes sent to gpu each time
Minibatch	32	Batch to update the network weights
Optimizer	ADAM (Zeiler, 2012)	$lr = 10^{-3}$, $\beta_1 = 0.9$, $\beta_2 = 0.999$, $\epsilon = 10^{-8}$
Epochs	5	
Op. System	Windows 10	
GPU	Nvidia GeForce 1080ti	Nvidia GeForce 930M for time comparison
RAM Memory	16 GB	

Table 5: Test set accuracy comparison among traditional models the Zhang et al. (2015) models 'large' and 'small' and our approaches, CNN1 and CNN2.

MODEL		AG	SOGOU	DBP	YLP P	YLP	YAH	AMZ F	AMZ P
BoW		88.81	92.85	96.61	92.24	57.99	68.89	54.64	90.40
BoW TFIDF		89.64	93.45	97.37	93.66	59.86	71.04	55.26	91.00
Ngrams		92.04	97.08	98.63	95.64	56.26	68.47	54.27	92.02
Ngrams TFIDF		92.36	97.19	98.69	95.44	54.80	68.51	52.44	91.54
Bag-of-Means		83.09	89.21	90.45	87.33	52.54	60.55	44.13	81.61
LSTM		86.06	95.18	98.55	94.74	58.17	70.84	59.43	93.90
Zhang et al.	Large	87.18	95.12	98.27	94.11	60.38	70.45	58.69	94.49
	Small	84.35	91.35	98.02	93.47	59.16	70.16	59.47	94.50
Ours	CNN1	87.67	95.16	97.93	92.04	58.00	68.10	58.09	93.69
	CNN2	91.43	93.96	98.03	91.53	57.03	70.24	55.72	91.23

demonstrate that such approach allows reducing the dimensionality of the encoding matrix, allowing substantial shorter optimization times and the use of devices with lower computational power. Some datasets of text have peculiarities that were not addressed by word frequency methods (i.e. BoW and word2vec), like declensions and new vocabulary. The article of Zhang et al. (2015) was a great innovation in this regard. However, the training times are still obstacles to the most effective use of the technique. We thought of a better representation should be a solution.

To make a comparison, perform the training of architecture CNN1 with an output of 4 classes make necessary to optimize 1,837,188 parameters. As a comparison, in the architecture suggested by Zhang et al. (2015) it is necessary to optimize 11,337,988 parameters (Zhang et al., 2015).

As one of our concerns was to make our proposal usable on commodity hardware we focused our studies in that hardware configuration. The major bottleneck for analyzing this large amount of matrix-encoded text is the need for intensive use of RAM. Our approach generates a 128×256 matrix, smaller than the 1014×69 generated by Zhang et al. (2015). In spite of that, a large set of them quickly occupies the available RAM memory on a regular computer. On the machine we used, there were 16 GB available, which is not uncommon in modern personal computers. Therefore, the use of generators to control the number of matrices generated and sent to GPU is an important detail in the implementation of this optimization algorithm. If your computer has only 8 GB of RAM or less, you should reduce the number of superbatch to fit the memory.

The results that we obtained are very competitive with the approach o Zhang et al. (2015) and traditional techniques. Observing our results, we see even that we could find parameters that result

Table 6: Time per epoch as reported by Zhang et al. (2015) models and the ones used by CNN1 and CNN2 on an NVidia GeForce GF 1080ti GPU.

DATASET	TRAIN SET SIZE	TEST SET SIZE	Zhang et al. (2015)		Ours	
			large	small	CNN1	CNN2
ag_news	120 k	7.6 k	1 h	3 h	3 min	4 min
sogou_news	450 k	60 k	N/A	N/A	23 min	27 min
dbpedia	560 k	70 k	2 h	5 h	18 min	20 min
yelp_polarity	560 k	38 k	N/A	N/A	21 min	31 min
yelp_full	650 k	50 k	N/A	N/A	27 min	46 min
yahoo_answers	1,400 k	60 k	8 h	1 days	47 min	55 min
amazon_full	3,000 k	650 k	2 days	5 days	2 h	2 h 30 min
amazon_polarity	3,600 k	400 k	2 days	5 days	2h 13 min	2 h 31 min

in excellent performance on ag_news dataset, following the suggestions of Zhang & Wallace (2015). One of advantage of a faster algorithm is that if your dataset is not so big, you could scan the feature width to find a solution that optimizes accuracy. Another advantage is the possibility to realize k-folds validation, to have a better perspective on how well it will perform for your specific dataset on real life.

We are certain that our algorithm implementation could be even faster. For our inability, we could not find a way to make CPU and GPU working in parallel. Using a GPU Geforce 1080ti, each of the superbatch of 10000 arrays have its weights updated in 30 seconds. Only 6 seconds is consumed by GPU, another 24 seconds is spent in encoding all the matrix and delivery it on GPU. Using a multithread strategy could help in this regard.

The results obtained strongly indicate that the use of this coding is a possibility. We emphasize that we used is a fairly simple network, enough to demonstrate the feasibility of the encoding approach with the time and computational resources that we have. Possibly there are several architectures that can generate better results. In addition, the dimensionality reduction provided enables several architectures to be verified in a reasonable time.

5 FINAL REMARKS

In this paper, we proposed an efficient character-level encoding of text derived from the tagged Huffman (Silva de Moura et al., 2000) information compression method and applied it as input transformation step for character-level CNN text classification.

This novel text encoding dramatically reduces the time required for training CNNs and, therefore, makes the application of this novel approach more accessible. The proposed encoding makes possible to represent larger portions of texts in a compact form while preserving the ability to encode any word, even those not present in the training dataset ones.

The experimental studies carried out as part of the paper coupled the encoding with two convolutional neural networks architectures. These experiments showed that we managed to achieve a performance similar to the one achieved by Zhang et al. (2015) a fraction of the training time even if we employed a simpler hardware setup.

This novel character-level text encoding produces a reduced input matrix, leading to a substantial reduction in training times while producing comparable or better results in terms of accuracy than the original approach by Zhang et al. (2015). This opens the door to more complex applications, the use of devices with lower computational power and the exploration of other approaches that can be coupled with input representation.

Using a compressing technique is a convenient possibility to represent words for use in Convolutional Neural Networks to classify text. Encoding words using characters could be relevant especially on less curated texts datasets, being robust to typos, slangs, and others usual characteristics of internet texts.

With our results, we reinforce Zhang et al. (2015) conclusions, which states that language could be treated as a signal, no different from any other. We demonstrated that using the approach suggested reduce the dimensionality of the matrix representation of texts and allow the use of simpler hardware than character level one hot encoding, allowing a drastic reduction of training time. We performed a comparative test with the approach of Zhang et al. (2015) and others traditional techniques and found competitive results.

It should be noted that the main objective of the paper was to show the viability of the text encoding, not producing better results *per se*. Consequently, we have focused our efforts on the comparative study. Probably, custom neural network architectures should be devised to this new encoding, perhaps combining it with LSTMs to make overcome the fixed matrix size limitation. In the near future, we will focus on devising these new architectures that may further favor this strategy.

This study also opens a door to other information-theoretic-based methods for information representation to be used to create a numerical representation of texts.

It must be outlined the fact that this compact numeric representation of text is not limited to the domain of CNN or neural networks, for that matter. It could be interesting to assess its impact as a preprocessing step, perhaps with a minor modification, for other classification algorithms.

REFERENCES

Martín Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S. Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian Goodfellow, Andrew Harp, Geoffrey Irving, Michael Isard, Yangqing Jia, Rafal Jozefowicz, Lukasz Kaiser, Manjunath Kudlur, Josh Levenberg, Dan Mané, Rajat Monga, Sherry Moore, Derek Murray, Chris Olah, Mike Schuster, Jonathon Shlens, Benoit Steiner, Ilya Sutskever, Kunal Talwar, Paul Tucker, Vincent Vanhoucke, Vijay Vasudevan, Fernanda Viégas, Oriol Vinyals, Pete Warden, Martin Wattenberg, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. TensorFlow: Large-scale machine learning on heterogeneous systems, 2015. URL https://www.tensorflow.org/. Software available from tensorflow.org.

Charu C. Aggarwal and Cheng Xiang Zhai. A survey of text classification algorithms. In Charu C. Aggarwal and Cheng Xiang Zhai (eds.), *Mining Text Data*, pp. 163–222. Springer US, 2012. ISBN 978-1-4614-3222-7. doi: 10.1007/978-1-4614-3223-4_6. URL http://dx.doi.org/10.1007/978-1-4614-3223-4_6.

James Bergstra, Olivier Breuleux, Frédéric Bastien, Pascal Lamblin, Razvan Pascanu, Guillaume Desjardins, Joseph Turian, David Warde-Farley, and Yoshua Bengio. Theano: a CPU and GPU math expression compiler. In *Proceedings of the Python for Scientific Computing Conference (SciPy)*, June 2010. Oral Presentation.

Nieves Brisaboa, Eva Iglesias, Gonzalo Navarro, and José Paramá. An efficient compression code for text databases. *Advances in Information Retrieval*, pp. 78–78, 2003.

Sharan Chetlur, Cliff Woolley, Philippe Vandermersch, Jonathan Cohen, John Tran, Bryan Catanzaro, and Evan Shelhamer. cudnn: Efficient primitives for deep learning. *CoRR*, abs/1410.0759, 2014. URL http://arxiv.org/abs/1410.0759.

François Chollet et al. Keras. https://github.com/fchollet/keras, 2015.

Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep Learning*. MIT Press, 2016. http://www.deeplearningbook.org.

David Harris and Sarah Harris. *Digital design and computer architecture*. Morgan Kaufmann, San Francisco, CA, USA, 2nd edition, 2012.

Andreas Hotho, Andreas Nrnberger, and Gerhard Paa. A brief survey of text mining. *LDV Forum - GLDV Journal for Computational Linguistics and Language Technology*, 20(1):19–62, May 2005. ISSN 0175-1336. URL http://www.kde.cs.uni-kassel.de/hotho/pub/2005/hotho05TextMining.pdf.

David A. Huffman. A method for the construction of minimum-redundancy codes. *Proceedings of the Institute of Radio Engineers*, 40(9):1098–1101, September 1952.

Rie Johnson and Tong Zhang. Effective use of word order for text categorization with convolutional neural networks. *CoRR*, abs/1412.1058, 2014. URL http://arxiv.org/abs/1412.1058.

Yoon Kim. Convolutional neural networks for sentence classification. *CoRR*, abs/1408.5882, 2014. URL http://arxiv.org/abs/1408.5882.

Raymond Kosala and Hendrik Blockeel. Web mining research: a survey. *SIGKDD Explor. Newsl.*, 2(1):1–15, June 2000. doi: http://dx.doi.org/10.1145/360402.360406. URL http://dx.doi.org/10.1145/360402.360406.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in Neural Information Processing Systems (NIPS)*, pp. 1097–1105, 2012.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. In *Proceedings of the IEEE*, pp. 2278–2324, 1998.

Jens Lehmann, Robert Isele, Max Jakob, Anja Jentzsch, Dimitris Kontokostas, Pablo N. Mendes, Sebastian Hellmann, Mohamed Morsey, Patrick van Kleef, Sören Auer, and Christian Bizer. DBpedia - a large-scale, multilingual knowledge base extracted from wikipedia. *Semantic Web Journal*, 6(2):167–195, 2015. URL http://jens-lehmann.org/files/2015/swj_dbpedia.pdf.

Julian McAuley and Jure Leskovec. Hidden factors and hidden topics: Understanding rating dimensions with review text. In *Proceedings of the 7th ACM Conference on Recommender Systems*, RecSys '13, pp. 165–172, New York, NY, USA, 2013. ACM. ISBN 978-1-4503-2409-0. doi: 10.1145/2507157.2507163. URL http://doi.acm.org/10.1145/2507157.2507163.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. Distributed representations of words and phrases and their compositionality. In *Advances in Neural Information Processing Systems (NIPS)*, pp. 3111–3119, 2013.

Sparsh Mittal and Jeffrey S. Vetter. A survey of CPU-GPU heterogeneous computing techniques. *ACM Computing Surveys*, 47(4):69:1–69:35, July 2015. ISSN 0360-0300. doi: 10.1145/2788396. URL http://doi.acm.org/10.1145/2788396.

Fabrizio Sebastiani. Machine learning in automated text categorization. *ACM Computing Surveys*, 34(1):1–47, March 2002. ISSN 0360-0300. doi: 10.1145/505282.505283. URL http://doi.acm.org/10.1145/505282.505283.

Edleno Silva de Moura, Gonzalo Navarro, Nivio Ziviani, and Ricardo Baeza-Yates. Fast and flexible word searching on compressed text. *ACM Trans. Inf. Syst.*, 18(2):113–139, April 2000. ISSN 1046-8188. doi: 10.1145/348751.348754. URL http://doi.acm.org/10.1145/348751.348754.

Matthew D. Zeiler. ADADELTA: An adaptive learning rate method. *CoRR*, abs/1212.5701, 2012. URL http://dblp.uni-trier.de/db/journals/corr/corr1212.html#abs-1212-5701.

Xiang Zhang, Junbo Zhao, and Yann LeCun. Character-level convolutional networks for text classification. In *Advances in neural information processing systems*, pp. 649–657, 2015.

Ye Zhang and Byron C. Wallace. A sensitivity analysis of (and practitioners' guide to) convolutional neural networks for sentence classification. *CoRR*, abs/1510.03820, 2015. URL http://arxiv.org/abs/1510.03820.