NETWORK OF GRAPH CONVOLUTIONAL NETWORKS TRAINED ON RANDOM WALKS

ABSTRACT

Semi-supervised learning on graph-structured data has recently progressed with the introduction of Graph Convolutional Networks (GCNs). At the same time, unsupervised learning of graph embeddings has benefited from random walks. In this paper, we marry the two, by feeding random walk statistics to multiple instances of GCNs, combining their output into a classification sub-network. Our overall architecture, Network of GCNs, is able to utilize information from near and distant neighbors. We evaluate on challenging node classification tasks, when the training data is scarce, and we achieve state-of-the-art performance on Cora, Citeseer, and Pubmed. Further, we inspect how the classification sub-network circumvents adversarial input perturbations by shifting attention to distant nodes.

1 INTRODUCTION

Semi-supervised learning on graphs is important in many real-world applications, where the goal is to recover labels for all nodes given only a fraction of labeled ones. Some applications include social networks, where one wishes to predict user interests, or in health care, where one wishes to predict whether a patient should be screened for cancer. In many such cases, collecting node labels can be prohibitive. However, edges between nodes can be easier to obtain, either using an explicit graph (e.g. social network) or implicitly by calculating pairwise similarities (e.g. using a patient-patient similarity kernel Merdan et al., 2017).

Convolutional Neural Networks (LeCun et al., 1998) learn location-invariant hierarchical filters, enabling significant improvements on Computer Vision tasks (Krizhevsky et al., 2012; Szegedy et al., 2015; He et al., 2016). This success has motivated researchers (Bruna et al., 2014) to extend convolutions from spatial (i.e. regular lattice) domains to graph-structured (i.e. irregular) domains, yielding a class of algorithms known as Graph Convolutional Networks (GCNs).

Formally, we are interested in semi-supervised learning where we are given a graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ with $N = |\mathcal{V}|$ nodes; adjacency matrix A; and matrix $X \in \mathbb{R}^{N \times F}$ of node features. Labels for only a subset of nodes $\mathcal{V}_L \subset \mathcal{V}$ observed. In general, $|\mathcal{V}_L| \ll |\mathcal{V}|$. Our goal is to recover labels for all unlabeled nodes $\mathcal{V}_U = \mathcal{V} - \mathcal{V}_L$, using the feature matrix X, the known labels for nodes in $\mathcal{V}_L$, and the graph G. In this setting, one treats the graph as the "unsupervised" and labels of $\mathcal{V}_L$ as the "supervised" portions of the data.

Depicted in Figure 1, our model for semi-supervised node classification builds on the GCN module proposed by Kipf & Welling (2017), which operates on the normalized adjacency matrix $\hat{A}$, as in GCN($\hat{A}$), where $\hat{A} = D^{-\frac{1}{2}} A D^{-\frac{1}{2}}$, and D is diagonal matrix of node degrees. Our proposed extension of GCNs is inspired by the recent advancements in random walk based graph embeddings (e.g. Perozzi et al., 2014; Grover & Leskovec, 2016; Abu-El-Haija et al., 2017). We make a Network of GCN modules (N-GCN), feeding each module a different power of $\hat{A}$, as in $\{\text{GCN}(\hat{A}^0), \text{GCN}(\hat{A}^1), \text{GCN}(\hat{A}^2), \dots\}$. The k'th power contains statistics from the k-th step of a random walk on the graph. Therefore, our N-GCN model is able to combine information from various step-sizes. We then combine the output of all GCN modules into a classification sub-network, and we jointly train all GCN modules and the classification sub-network on the upstream objective, semi-supervised node classificaiton. Weights of the classification sub-network give us insight on how the N-GCN model works. For instance, in the presence of input perturbations, we observe that the classification sub-network weights shift towards GCN modules utilizing higher powers of the

(a) NGCN Architecture

(b) t-SNE visualization of fully-connected (fc) hidden layer of NGCN when trained over Cora graph.

Figure 1: Left: Model architecture, where $\hat{A}$ is the normalized normalized adjacency matrix, I is the identity matrix, X is node features matrix, and $\times$ is matrix-matrix multiply operator. We calculate K powers of the $\hat{A}$, feeding each power into r GCNs, along with X. The output of all $K \times r$ GCNs can be concatenated along the column dimension, then fed into fully-connected layers, outputting C channels per node, where C is size of label space. We calculate cross entropy error, between rows *prediction* $N \times C$ with known labels, and use them to update parameters of classification sub-network and all GCNs. Right: pre-relu activations after the first fully-connected layer of a 2-layer classification sub-network. Activations are PCA-ed to 50 dimensions then visualized using t-SNE.

adjacency matrix, effectively widening the "receptive field" of the (spectral) convolutional filters. We achieve state-of-the-art on several semi-supervised graph learning tasks, showing that explicit random walks enhance the representational power of vanilla GCN's.

The rest of this paper is organized as follows. Section 2 reviews background work that provides the foundation for this paper. In Section 3, we describe our proposed method, followed by experimental evaluation in Section 4. We compare our work with recent closely-related methods in Section 5. Finally, we conclude with our contributions and future work in Section 6.

2 BACKGROUND

2.1 SEMI-SUPERVISED NODE CLASSIFICATION

Traditional label propagation algorithms (Weston et al., 2012; Belkin et al., 2006a) learn a model that transforms node features into node labels and uses the graph to add a regularizer term:

$$\mathcal{L}_{\text{label.propagation}} = \mathcal{L}_{\text{classification}} + \mathcal{L}_{reg} = \mathcal{L}_{\text{classification}} + \lambda f(X)^T \Delta f(X), \tag{1}$$

where $f : \mathbb{R}^{N \times d_0} \to \mathbb{R}^{N \times C}$ is the model, Δ is the graph Laplacian, and $\lambda \in \mathbb{R}$ is regularization coefficient hyperparameter.

2.2 GRAPH CONVOLUTIONAL NETWORKS

Graph Convolution (Bruna et al., 2014) generalizes convolution from Euclidean domains to graph-structured data. Convolving a "filter" over a signal on graph nodes can be calculated by transforming both the filter and the signal to the Fourier domain, multiplying them, and then transforming the result back into the discrete domain. The signal transform is achieved by multiplying with the eigenvectors of the graph Laplacian. The transformation requires a quadratic eigendecomposition of the symmetric Laplacian; however, the low-rank approximation of the eigendecomposition can be calculated using truncated Chebyshev polynomials (Hammond et al., 2011). For instance, Kipf & Welling (2017) calculates a rank-1 approximation of the decomposition. They propose a multi-layer Graph Convolutional Networks (GCNs) for semi-supervised graph learning. Every layer computes

the transformation:

$$H^{(l+1)} = \sigma\left(\hat{A}H^{(l)}W^{(l)}\right),\tag{2}$$

where $H^{(l)} \in \mathbb{R}^{N \times d_l}$ is the input activation matrix to the l-th hidden layer with row $H_i^{(l)}$ containing a d_l-dimensional feature vector for vertex $i \in \mathcal{V}$, and $W^{(l)} \in \mathbb{R}^{d_l \times d_{l+1}}$ is the layer's trainable weights. The first hidden layer $H^{(0)}$ is set to the input features X. A softmax on the last layer is used to classify labels. All layers use the same "normalized adjacency" $\hat{A}$, obtained by the "renormalization trick" utilized by Kipf & Welling (2017), as $\hat{A} = D^{-\frac{1}{2}}AD^{-\frac{1}{2}}$.[1]

Eq. (2) is a first order approximation of convolving filter $W^{(l)}$ over signal $H^{(l)}$ (Hammond et al., 2011; Kipf & Welling, 2017). The left-multiplication with $\hat{A}$ averages node features with their direct neighbors; this signal is then passed through a non-linearity function $\sigma(\cdot)$ (e.g, ReLU$(z) = \max(0, z)$). Successive layers effectively *diffuse* signals from nodes to neighbors.

Two-layer GCN model can be defined in terms of vertex features X and normalized adjacency $\hat{A}$ as:

$$\text{GCN}_{\text{2-layer}}(\hat{A}, X; \theta) = \text{softmax}\left(\hat{A}\sigma(\hat{A}XW^{(0)})W^{(1)}\right),\tag{3}$$

where the GCN parameters $\theta = \left\{W^{(0)}, W^{(1)}\right\}$ are trained to minimize the cross-entropy error over labeled examples. The output of the GCN model is a matrix $\mathbb{R}^{N \times C}$, where N is the number of nodes and C is the number of labels. Each row contains the label scores for one node, assuming there are C classes.

2.3 GRAPH EMBEDDINGS

Node Embedding methods represent graph nodes in a continuous vector space. They learn a dictionary $Z \in \mathbb{R}^{N \times d}$, with one d-dimensional embedding per node. Traditional methods use the adjacency matrix to learn embeddings. For example, Eigenmaps (Belkin & Niyogi, 2003) calculates the following constrained optimization:

$$\sum_{i,j} ||A_{ij}(Z_i - Z_J)|| \quad \text{s.t.} \;\; Z^T D Z = I,\tag{4}$$

where I is identity vector. Skipgram models on text corpora (Mikolov et al., 2013) inspired modern graph embedding methods, which simulate random walks to learn node embeddings (Perozzi et al., 2014; Grover & Leskovec, 2016). Each random walk generates a sequence of nodes. Sequences are converted to textual paragraphs, and are passed to a word2vec-style embedding learning algorithm (Mikolov et al., 2013). As shown in Abu-El-Haija et al. (2017), this learning-by-simulation is equivalent, in expectation, to the decomposition of a random walk co-occurrence statistics matrix $\mathcal{D}$. The expectation on $\mathcal{D}$ can be written as:

$$\mathbb{E}[\mathcal{D}] \propto \mathbb{E}_{q \sim \mathcal{Q}}\left[(\mathcal{T})^q\right] = \mathbb{E}_{q \sim \mathcal{Q}}\left[\left(D^{-1}A\right)^q\right],\tag{5}$$

where $\mathcal{T} = D^{-1}A$ is the row-normalized transition matrix (a.k.a right-stochastic adjacency matrix), and $\mathcal{Q}$ is a "context distribution" that is determined by random walk hyperparameters, such as the length of the random walk. The expectation therefore weights the importance of one node on another as a function of the distance between them. The main difference between traditional node embedding methods and random walk methods is the optimization criteria: the former minimizes a loss on representing the adjacency matrix A (see Eq. 4), while the latter minimizes a loss on representing random walk co-occurrence statistics $\mathcal{D}$.

3 OUR METHOD

3.1 MOTIVATION

Graph Convolutional Networks and random walk graph embeddings are individually powerful. Kipf & Welling (2017) uses GCNs for semi-supervised node classification. Instead of following traditional methods that use the graph for regularization (e.g. Eq. 4), Kipf & Welling (2017) use the

---

[1]with added self-connections added as $A_{ii} = 1$, similar to Kipf & Welling (2017)

adjacency matrix for training and inference, effectively diffusing information across edges at all GCN layers (see Eq. 6). Separately, recent work has showed that random walk statistics can be very powerful for learning an unsupervised representation of nodes that can preserve the structure of the graph (Perozzi et al., 2014; Grover & Leskovec, 2016; Abu-El-Haija et al., 2017).

Under special conditions, it is possible for the GCN model to learn random walks. In particular, consider a two-layer GCN defined in Eq. 6 with the assumption that first-layer activation is identity as $\sigma(z) = z$, and weight $W^{(0)}$ is an identity matrix (either explicitly set or learned to satisfy the upstream objective). Under these two identity conditions, the model reduces to:

$$\text{GCN}_{\text{2-layer-special}}(\hat{A}, X) = \text{softmax}\left(\hat{A}\hat{A}XW^{(1)}\right) = \text{softmax}\left(\hat{A}^2 XW^{(1)}\right), \tag{6}$$

where $\hat{A}^2$ can be expanded as:

$$\hat{A}^2 = \left(D^{-\frac{1}{2}}AD^{-\frac{1}{2}}\right)\left(D^{-\frac{1}{2}}AD^{-\frac{1}{2}}\right) = D^{-\frac{1}{2}}A\left[D^{-1}A\right]D^{-\frac{1}{2}} = D^{-\frac{1}{2}}A\mathcal{T}D^{-\frac{1}{2}}. \tag{7}$$

By multiplying the adjacency A with the transition matrix $\mathcal{T}$ before normalization, the GCN is effectively doing a one-step random walk.

3.2 EXPLICIT RANDOM WALKS

The special conditions described above are not true in practice. Although stacking hidden GCN layers allows information to flow through graph edges, this flow is *indirect* as the information goes through feature reduction (matrix multiplication) and a non-linearity (activation function $\sigma(\cdot)$). Therefore, the vanilla GCN cannot directly learn high powers of $\hat{A}$, and could struggle with modeling information across distant nodes. We hypothesize that making the GCN directly operate on random walk statistics will allow the network to better utilize information across distant nodes, in the same way that node embedding methods (e.g. DeepWalk, Perozzi et al. (2014)) operating on $\mathcal{D}$ are superior to traditional embedding methods operating on the adjacency matrix (e.g. Eigenmaps, Belkin & Niyogi (2003)). Therefore, in addition to feeding only $\hat{A}$ to the GCN model as proposed by Kipf & Welling (2017) (see Eq. 6), we propose to feed a K-degree polynomial of $\hat{A}$ to K instantiations of GCN. Generalizing Eq. (7) gives:

$$\hat{A}^k = D^{-\frac{1}{2}}A\mathcal{T}^{k-1}D^{-\frac{1}{2}}. \tag{8}$$

We also define $\hat{A}^0$ to be the identity matrix. Similar to Kipf & Welling (2017), we add self-connections and convert directed graphs to undirected ones, making $\hat{A}$ and hence $\hat{A}^k$ symmetric matrices. The eigendecomposition of symmetric matrices is real. Therefore, the low-rank approximation of the eigendecomposition Hammond et al. (2011) is still valid, and a one layer of Kipf & Welling (2017) utilizing $\hat{A}^k$ should still approximate multiplication in the Fourier domain.

3.3 NETWORK OF GCNS

Consider K instantiations of $\{\text{GCN}(\hat{A}^0, X), \text{GCN}(\hat{A}^1, X), \ldots, \text{GCN}(\hat{A}^{K-1}, X)\}$. Each GCN outputs a matrix $\mathbb{R}^{N \times C_k}$, where the v-th row describes a latent representation of that particular GCN for node $v \in \mathcal{V}$, and where C_k is the latent dimensionality. Though C_k can be different for each GCN, we set all C_k to be the same for simplicity. We then combine the output of all K GCN and feed them into a classification sub-network, allowing us to jointly train all GCNs and the classification sub-network via backpropagation. This should allow the classification sub-network to choose features from the various GCNs, effectively allowing the overall model to learn a combination of features using the raw (normalized) adjacency, different steps of random walks, and the input features X (as they are multiplied by identity $\hat{A}^0$).

3.3.1 FULLY-CONNECTED CLASSIFICATION NETWORK

From a deep learning prospective, it is straight-forward to represent the classification network as a fully-connected layer. We can concatenate the output of the K GCNs along the column dimension, i.e. concatenating all $\text{GCN}(X, \hat{A}^k)$, each $\in \mathbb{R}^{N \times C_k}$ into matrix $\in \mathbb{R}^{N \times C_K}$ where $C_K = \sum_k C_k$.

We add a fully-connected layer $f_{\text{fc}} : \mathbb{R}^{N \times C_K} \to \mathbb{R}^{N \times C}$, with trainable parameter matrix $W_{\text{fc}} \in \mathbb{R}^{C_K \times C}$, written as:

$$\text{N-GCN}_{\text{fc}}(\hat{A}, A; W_{\text{fc}}, \theta) = \text{softmax}\left(\left[\ \text{GCN}(\hat{A}^0, X; \theta^{(0)}) \ \vdots \ \text{GCN}(\hat{A}^1, X; \theta^{(1)}) \ \vdots \ \dots \ \right] W_{\text{fc}}\right). \quad (9)$$

The classifier parameters W_{fc} are jointly trained with GCN parameters $\theta = \{\theta^{(0)}, \theta^{(1)}, \dots\}$. We use subscript fc on N-GCN to indicate the classification network is a fully-connected layer.

3.3.2 Attention Classification Network

We also propose a classification network based on "softmax attention", which learns a convex combination of the GCN instantiations. Our attention model (N-GCN$_a$) is parametrized by vector $\widetilde{m} \in \mathbb{R}^K$, one scalar for each GCN. It can be written as:

$$\text{N-GCN}_{\text{a}}(\hat{A}, X; m, \theta) = \sum_k m_k \text{GCN}(\hat{A}^k, X; \theta^{(k)}) \quad (10)$$

where m is output of a softmax: $m = \text{softmax}(\widetilde{m})$.

This softmax attention is similar to "Mixture of Experts" model, especially if we set the number of output channels for all GCNs equal to the number of classes, as in $C_0 = C_1 = \dots = C$. This allows us to add cross entropy loss terms on all GCN outputs in addition to the loss applied at the output NGCN, forcing all GCN's to be independently useful. It is possible to set the $m \in \mathbb{R}^K$ parameter vector "by hand" using the validation split, especially for reasonable K such as $K \leq 6$. One possible choice might be setting m_0 to some small value and remaining $m_1, \dots, m_{K-1}$ to the harmonic series $\frac{1}{k}$; another choice may be linear decay $\frac{K-k}{K-1}$. These are respectively similar to the context distributions of GloVe (Pennington et al., 2014) and word2vec (Mikolov et al., 2013; Levy et al., 2015). We note that if on average a node's information is captured by its direct or nearby neighbors, then the output of GCNs consuming lower powers of $\hat{A}$ should be weighted highly.

3.4 Training

We minimize the cross entropy between our model output and the known training labels Y as:

$$\min \text{diag}(\mathcal{V}_L)\left[Y \circ \log \text{N-GCN}(X, \hat{A})\right], \quad (11)$$

where $\circ$ is Hadamard product, and $\text{diag}(\mathcal{V}_L)$ denotes a diagonal matrix, with entry at (i, i) set to 1 if $i \in \mathcal{V}_L$ and 0 otherwise. In addition, we can apply intermediate supervision for the NGCN$_a$ to attempt make all GCN become independently useful, yielding minimization objective:

$$\min_{m, \theta} \text{diag}(\mathcal{V}_L)\left[Y \circ \log \text{N-GCN}_{\text{a}}(\hat{A}, X; m, \theta) + \sum_k Y \circ \log \text{GCN}(\hat{A}^k, X; \theta^{(k)})\right]. \quad (12)$$

3.5 GCN Replication

To simplify notation, our N-GCN derivations (e.g. Eq. 9) assumes that there is one GCN per $\hat{A}$ power. However, our implementation feeds every $\hat{A}$ to r GCN modules, as shown in Fig. 1.

3.6 Generalization to other Graph Models

In addition to vanilla GCNs (e.g. Kipf & Welling, 2017), our derivation also applies to other graph models including GraphSAGE (SAGE, Hamilton et al., 2017). Algorithm 1 shows a generalization that allows us to make a network of arbitrary graph models (e.g. GCN, SAGE, or others). Algorithm 2 show psuedocode for vanilla GCN. Finally, Algorithm 3 defines our full Network of GCN model (N-GCN) by plugging Algorithm 2 into Algorithm 1. Similarly, we list the algorithms for SAGE and Network of SAGE (N-SAGE) in the Appendix.

We can recover the original algorithms GCN (Kipf & Welling, 2017) and SAGE (Hamilton et al., 2017), respectively, by using Algorithms 3 (N-GCN) and 5 (N-SAGE, listed in Appendix) with $r = 1$, $K = 1$, identity CLASSIFIERFN, and modifying line 2 in Algorithm 1 to $P \leftarrow \hat{A}$. Moreover, we can recover original DCNN (Atwood & Towsley, 2016) by calling Algorithm 3 with $L = 1$, $r = 1$, modifying line 3 to $\hat{A} \leftarrow D^{-1}A$, and keeping $K > 1$ as their proposed model operates on the power series of the transition matrix i.e. *unmodified* random walks, like ours.

Algorithm 1 General Implementation: Network of Graph Models

Require: $\hat{A}$ is a normalization of A
1: **function** NETWORK(GRAPHMODELFN, $\hat{A}$, X, L, $r = 4$, $K = 6$, CLASSIFIERFN=FCLAYER)
2:     $P \leftarrow I$
3:     GraphModels $\leftarrow$ []
4:     **for** $k = 1$ to K **do**
5:         **for** $i = 1$ to r **do**
6:             GraphModels.append(GRAPHMODELFN(P, X, L))
7:         $P \leftarrow \hat{A}P$
8:     **return** CLASSIFIERFN(GraphModels)

Algorithm 2 GCN (Kipf & Welling, 2017)

Require: $\hat{A}$ is a normalization of A
1: **function** GCNMODEL($\hat{A}$, X, L)
2:     $Z \leftarrow X$
3:     **for** $i = 1$ to L **do**
4:         $Z \leftarrow \sigma(\hat{A}ZW^{(i)})$
5:     **return** Z

Algorithm 3 N-GCN

1: **function** NGCN(A, X, $L = 2$)
2:     $D \leftarrow \mathbf{diag}(A\mathbf{1})$ ▷ Sum rows
3:     $\hat{A} \leftarrow D^{-1/2}AD^{-1/2}$
4:     **return** NETWORK(GCNMODEL, $\hat{A}$, X, L)

---

4 EXPERIMENTS

We follow the experimental setup by Kipf & Welling (2017) and Yang et al. (2016), including the provided dataset splits (train, validattion, test) produced by Yang et al. (2016).

4.1 DATASETS

We experiment on three citation datasets: Pubmed, Citeseer, and Cora. Table 1 summarizes dataset statistics. In each dataset, a node represents an article published in the corresponding journal; an edge between two nodes represents a citation from one article to another; and a label represents the category or subject of the article. Each dataset contains a binary Bag-of-Words (BoW) feature vector for each node. The BoW are extracted from the article abstract. Therefore, the task is to predict the subject of articles, given the BoW of their abstract and the citations to other (possibly labeled) articles. We choose the aforementioned datasets because the (train, validation, test) splits used by Yang et al. (2016) are available online and our baseline method, (GCN, Kipf & Welling, 2017), uses the same splits. Following Kipf & Welling (2017), we use 500 nodes for *validation* for each dataset. We note that the validation set is larger than training $|\mathcal{V}_L|$ for all datasets!

4.2 BASELINE METHODS

We compare against the baseline methods used by Kipf & Welling (2017). These include label propagation (LP, Zhu et al. (2003)); semi-supervised embedding (SemiEmb, Weston et al. (2012)); manifold regularization (ManiReg, Belkin et al. (2006b)); skip-gram graph embeddings (DeepWalk Perozzi et al., 2014); Iterative Classification Algorithm (ICA, Lu & Getoor, 2003); Planetoid (Yang et al., 2016); vanilla GCN (Kipf & Welling, 2017); and SAGE (Hamilton et al., 2017). The last two can be run using our implementation, as we can recover them as special cases of our algorithm as explained in Section 3.6.

4.3 IMPLEMENTATION

We use TensorFlow(Abadi et al., 2015) to implement our methods, which we use to also measure the performance of baselines GCN, SAGE, and DCNN. For our methods and baselines, all GCN and SAGE modules that we train are 2 layers, where the first outputs 16 dimensions per node and the second outputs the number of classes (dataset-dependant). DCNN baseline has one layer and outputs

Dataset	Nodes $|\mathcal{V}|$	Edges $|\mathcal{E}|$	Classes C	Features F	Labeled nodes $|\mathcal{V}_L|$
Citeseer	3,327	4,732	6	3,703	120
Cora	2,708	5,429	7	1,433	140
Pubmed	19,717	44,338	3	500	60

Table 1: Dataset statistics used for experiments. The number of nodes with observed labels is small ($|\mathcal{V}_L| = 20 \times C$)

	Method	Pubmed	Citeseer	Cora
(a)	ManiReg (Belkin et al., 2006b)	70.7	60.1	59.5
(b)	SemiEmb (Weston et al., 2012)	71.1	59.6	59.0
(c)	LP (Zhu et al., 2003)	63.0	45.3	68.0
(d)	DeepWalk (Perozzi et al., 2014)	65.3	43.2	67.2
(e)	ICA (Lu & Getoor, 2003)	73.9	69.1	75.1
(f)	Planetoid (Yang et al., 2016)	77.2	64.7	75.7
(g)	GCN (Kipf & Welling, 2017)	79.0	70.3	81.5
(i)	DCNN (our implementation)	79.3	71.1	81.3
(j)	GCN (our implementation)	78.8	71.2	81.0
(k)	SAGE (our implementation)	77.6	63.5	77.4
(m)	N-GCN (ours)	**80.4**	**72.2**	**83.0**
(n)	N-SAGE (ours)	79.4	71.0	81.8

Table 2: Node classification accuracy (in %) for various graph datasets, using data splits of Yang et al. (2016); Kipf & Welling (2017). We report the test accuracy corresponding to the run with the highest validation accuracy. Results in rows (a) through (b) are copied from Kipf & Welling (2017), rows (i) through (k) are generated using our code since we can recover other algorithms as explained in Section 3.6. Rows (m) and (n) are our models. We show parameter sensitivity in Appendix.

16 dimensions per node, and its channels (one per transition matrix power) are concatenated into a fully-connected layer that outputs the number of classes. We use 50% dropout L2 regularization of 10^{-5} for all forementioned models.

We start with 20 different random initializations for every model (baselines and ours), train using Adam optimizer (Ba & Kingma, 2015) with learning rate of 0.01 for 600 steps, and we capture the model parameters at peak validation accuracy to avoid overfitting. For our models, we sweep our hyperparameters r, K, and choice of classification sub-network $\in \{\text{fc}, \text{a}\}$. For baselines and our models, we choose the model with the best accuracy on validation set and use it to record numbers on the test set in Table 2. We show in the Appendix sensitivity analysis on our hyperparameters.

4.4 NODE CLASSIFICATION ACCURACY

Table 2 shows that N-GCN outperforms GCN (Kipf & Welling, 2017) and all other baselines on the attempted datasets with 20 labeled nodes per class. In addition, N-SAGE improves on SAGE for all datasets, showing that *unmodified* random walks indeed help in semi-supervised node classification.

4.5 TOLERANCE TO FEATURE NOISE

We test our method under feature noise perturbations by removing node features at random. This is practical, as article authors might forget to include relevant terms in the article abstract, and more generally not all nodes will have the same amount of detailed information. Figure 2 shows that when features are removed, methods utilizing unmodified random walks: N-GCN, N-SAGE, and DCNN, outperform convolutional methods including GCN and SAGE. Moreover, the performance gap widens as we remove more features. This suggests that our methods can somewhat recover removed features by *directly* pulling-in features from nearby and distant neighbors, according to

Nodes per class	5	10	20	100
DCNN (our implementation)	63.0 ± 1.0	72.3 ± 0.4	79.2 ± 0.2	82.6 ± 0.3
GCN (our implementation)	64.6 ± 0.3	70.0 ± 3.7	79.1 ± 0.3	81.8 ± 0.3
SAGE (our implementation)	69.0 ± 1.4	72.0 ± 1.3	77.2 ± 0.5	80.7 ± 0.7
N-GCN$_a$ (ours)	65.1 ± 0.7	71.2 ± 1.1	79.7 ± 0.4	83.0 ± 0.4
N-GCN$_{fc}$ (ours)	65.0 ± 2.1	71.7 ± 0.7	79.3 ± 0.6	82.9 ± 0.3
N-SAGE$_a$ (ours)	66.9 ± 0.4	73.4 ± 0.7	79.0 ± 0.3	82.5 ± 0.2
N-SAGE$_{fc}$ (ours)	70.7 ± 0.4	74.1 ± 0.8	78.7 ± 0.8	81.8 ± 0.3

Table 3: Node classification accuracy (in %) for our largest dataset (Pubmed) as we vary size of training data $\frac{|\mathcal{V}|}{C} \in \{5, 10, 20, 100\}$. We report the average and standard deviations on 10 runs. We use a different random seed for every run (i.e. selecting different labeled nodes), but the same 10 random seeds across models. Note that convolution-based methods (e.g. SAGE) work well with few training examples, but *unmodified* random walk methods (e.g. DCNN) work well with more training data. Our methods combine convolution and unmodified random walks, making them work well in both conditions.

Figure 2: Classification accuracy for the Cora dataset with 20 labeled nodes per class ($|\mathcal{V}| = 20 \times C$), but features removed at random, averaging 10 runs. We use a different random seed for every run (i.e. removing different features per node), but the same 10 random seeds across models.

the attention vector m. We visualize in Figure 3 the attention weights as a function of % features removed. With little feature removal, there is some weight on $\hat{A}^0$, and the attention weights for $\hat{A}^1, \hat{A}^2, \ldots$ follow some decay function. Maliciously dropping features causes our model to shift its attention weights towards higher powers of $\hat{A}$.

5 RELATED WORK

The field of graph learning algorithms is quickly evolving. This section focuses on work that is most similar to ours.

Defferrard et al. (2016) define graph convolutions as a K-degree polynomial of the Laplacian, where the polynomial coefficients are learned. In their setup, the K-th degree Laplacian is a sparse square matrix where entry at (i, j) will be zero if nodes i and j are more than K hops apart. Their sparsity

Figure 3: Attention weights (m) for N-GCN$_a$ when trained with feature removal perturbation on the Cora dataset. Removing features shifts the attention weights to the right, suggesting the model is relying more on long range dependencies.

analysis also applies here. A minor difference is our adjacency normlization. We use $\hat{A}$ whereas they use the Laplacian defined as $I - \hat{A}$. Raising $\hat{A}$ to power K will produce a square matrix with entry (i, j) being the probability of random walker ending at node i after K steps from node j. The major difference is the order of random walk versus non-linearity. In particular, their model calculates learns a linear combination of K-degree polynomial and pass through classifier function g, as in $g(\sum_k q_k \widetilde{A}^k)$, while our (e.g. N-GCN) model calculates $\sum_k q_k g(\widetilde{A}^k)$, where $\widetilde{A}$ is $\hat{A}$ in our model and $I - \hat{A}$ in theirs, and our g can be a GCN module. In fact, Defferrard et al. (2016) is also similar to work by Abu-El-Haija et al. (2017), as they both learn polynomial coefficients to some normalized adjacency matrix.

Atwood & Towsley (2016) propose DCNN, which calculates powers of the transition matrix and keeps each power in a separate channel until the classification sub-network at the end. Their model is therefore similar to our work in that it also falls under $\sum_k q_k g(\widetilde{A}^k)$. However, where their model multiplies features with each power $\widetilde{A}^k$ once, our model makes use of GCN's (Kipf & Welling, 2017) that multiply by $\widetilde{A}^k$ at every GCN layer (see Eq. 2). Thus, DCNN model (Atwood & Towsley, 2016) is a special case of ours, when GCN module contains only one layer, as explained in Section 3.6.

6 CONCLUSIONS AND FUTURE WORK

In this paper, we propose a metamodel combines wraps Graph Convolution models, such as GCN (Kipf & Welling, 2017) and SAGE (Kipf & Welling, 2017), extend Graph Convolutional Networks (GCNs) with random walk methods. Traditional GCNs operate on the normalized adjacency matrix. We make multiple instantiations of GCNs, feeding each a power of the adjacency matrix, and then feed the total output into a classification sub-network. Our model, Network of GCNs, is end-to-end trainable, and is able to directly learn information across near or distant neighbors. We inspect the distribution of parameter weights in our classification sub-network, and show that our model is effectively able to circumvent adverserial perturbations on the input by shifting weights towards GCNs consuming higher powers of the adjacency matrix. For future work, we plan to extend our methods to a stochastic implementation and tackle other (larger) graph datasets. We also plan on using our implementation to gain valuable insight in real world graph learning tasks.

ACKNOWLEDGMENTS

We would like to thank meaningful discussions with **anonymous researchers** which had a significant impact on the quality of our work.

REFERENCES

Martín Abadi, Ashish Agarwal, and TensorFlow Team. TensorFlow: Large-scale machine learning on heterogeneous systems. 2015.

Sami Abu-El-Haija, Bryan Perozzi, Rami Al-Rfou, and Alex Alemi. Watch your step: Learning graph embeddings through attention. In *arxiv*, 2017.

James Atwood and Don Towsley. Diffusion-convolutional neural networks. In *Advances in Neural Information Processing Systems (NIPS)*, 2016.

Jimmy Ba and Diederik Kingma. Adam: A method for stochastic optimization. In *International Conference on Learning Representations*, 2015.

Mikhail Belkin and Partha Niyogi. Laplacian eigenmaps for dimensionality reduction and data representation. In *Neural Computation*, 2003.

Mikhail Belkin, Partha Niyogi, and Vikas Sindhwani. Manifold regularization: A geometric framework for learning from labeled and unlabeled examples. In *Journal of machine learning research (JMLR)*, 2006a.

Mikhail Belkin, Partha Niyogi, and Vikas Sindhwani. Manifold regularization: A geometric framework for learning from labeled and unlabeled examples. In *Journal of machine learning research (JMLR)*, 2006b.

J. Bruna, W. Zaremba, A. Szlam, and Y. LeCun. Spectral networks and locally connected networks on graphs. In *International Conference on Learning Representations*, 2014.

Michaël Defferrard, Xavier Bresson, and Pierre Vandergheynst. Convolutional neural networks on graphs with fast localized spectral filtering. In *Advances in Neural Information Processing Systems (NIPS)*, 2016.

A. Grover and J. Leskovec. node2vec: Scalable feature learning for networks. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 2016.

W. Hamilton, R. Ying, and J. Leskovec. Inductive representation learning on large graphs. In *NIPS*, 2017.

David K. Hammond, Pierre Vandergheynst, and R. Gribonval. Wavelets on graphs via spectral graph theory. In *Applied and Computational Harmonic Analysis*, 2011.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016.

G. Hinton J. Ba, J. Kiros. Layer normalization. In *arxiv 1607.06450*, 2016.

T. Kipf and M. Welling. Semi-supervised classification with graph convolutional networks. In *International Conference on Learning Representations*, 2017.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in Neural Information Processing Systems*, 2012.

Y. LeCun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. In *Proceedings of the IEEE*, 1998.

Omer Levy, Yoav Goldberg, and Ido Dagan. Improving distributional similarity with lessons learned from word embeddings. In *Transactions of the Association for Computational Linguistics (TACL)*, 2015.

Qing Lu and Lise Getoor. Link-based classification. In *International Conference on Machine Learning (ICML)*, 2003.

Selin Merdan, Christine L. Barnett, and Brian T. Denton. Data analytics for optimal detection of metastatic prostate cancer. 2017.

T. Mikolov, I. Sutskever, K. Chen, G. Corrado, and J. Dean. Distributed representations of words and phrases and their compositionality. In *Advances in Neural Information Processing Systems*, 2013.

Jeffrey Pennington, Richard Socher, and Christopher D. Manning. Glove: Global vectors for word representation. In *Conference on Empirical Methods in Natural Language Processing, EMNLP*, 2014.

B. Perozzi, R. Al-Rfou, and S. Skiena. Deepwalk: Online learning of social representations. In *Knowledge Discovery and Data Mining*, 2014.

Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott E. Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, and Andrew Rabinovich. Going deeper with convolutions. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2015.

Jason Weston, Frederic Ratle, Hossein Mobahi, and Ronan Collobert. Deeplearning via semi-supervised embedding. In *Neural Networks: Tricks of the Trade*, pp. 639–655, 2012.

Z. Yang, W. Cohen, and R. Salakhutdinov. Revisiting semi-supervised learning with graph embeddings. In *International Conference on Machine Learning (ICML)*, 2016.

Xiaojin Zhu, Zoubin Ghahramani, and John Lafferty. Semi-supervised learning using gaussian fields and harmonic functions. In *International Conference on Machine Learning (ICML)*, 2003.

APPENDIX

Algorithms 4 and 5, respectively, define SAGE Hamilton et al. (2017) and Network of SAGE (N-Sage). Algorithm 4 assumes mean-pool aggregation by Hamilton et al. (2017), which performs on-par to their top performer max-pool aggregation. Further, Algorithm 4 operates in full-batch while Hamilton et al. (2017) offer a stochastic implementation with edge sampling. Nonetheless, their proposed stochastic implementation should be wrapped in a network, though we would need a way to approximate (e.g. sample entries) from dense $\hat{A}^k$ as k increases. We leave this as future work.

Algorithm 4 SAGE Model (Hamilton et al., 2017)

Require: $\hat{A}$ is a normalization of A
1: **function** SAGEMODEL($\hat{A}$, X, L)
2:      $Z \leftarrow X$
3:      **for** $i = 1$ to L **do**
4:          $Z \leftarrow \sigma(\begin{bmatrix} Z & \hat{A}Z \end{bmatrix} W^{(i)})$
5:          $Z \leftarrow$ L2NORMALIZEROWS(Z)
6:      **return** Z

Algorithm 5 N-SAGE

1: **function** NSAGE(A, X)
2:      $D \leftarrow$ **diag**($A\mathbf{1}$)   ▷ Sum rows
3:      $\hat{A} \leftarrow D^{-1}A$
4:      **return** NETWORK(SAGEMODEL, $\hat{A}$, X, 2)

Using SAGE with mean-pooling aggregation is very similar to a vanilla GCN model but with three differences. First, the choice of adjacency normalization ($D^{-1}A$ versus $D^{-\frac{1}{2}}AD^{-\frac{1}{2}}$). Second, the skip connections in line 4, which concatenates the features with the adjacency-multiplied (i.e. diffused) features. We believe this is analogous in intuition of incorporating $\hat{A}^0$ in our model, which keeps the original features. Third, the use of node-wise L2 feature normalization at line 5, which is equivalent to applying a layernorm transformation J. Ba (2016). Nonetheless, it is worth noting Hamilton et al. (2017)'s formulation of SAGE is flexible to allow different aggregations, such as max-pooling or LSTM, which further deviates SAGE from GCN.

6.1 SENSITIVITY ANALYSIS

Earlier, in Table 2, we showed the test performance corresponding to the model performing best on the validation split. The number of labeled nodes are small, and such model selection is important to avoid overfitting. For example, there can be up to 10% relative test accuracy difference when training the *same* model architecture but with *different* random seed. In this section, we programatically sweep hyperparameters r, K, choice of classification network ($\in \{fc, a\}$), and whether or not we enable $\hat{A}^0$, for both N-GCN and N-SAGE models.

The settings when ($K = 1$, $r = 1$, and $\hat{A}^0$ disabled), correspond to the vanilla base model. Further, the settings when ($K = 1$, $r > 1$, and $\hat{A}^0$ disabled), correspond to an ensemble of the base model. These cases are outperformed when $K > 1$, showing that *unmodified* random walks indeed help these convolutional methods perform better, by gathering information from nearby and distant nodes.

The automatically generated tables are shown below:

	$K = 1$	$K = 2$	$K = 3$	$K = 4$	$K = 5$
$r = 1$	79.0 ± 0.125	79.5 ± 0.098	79.5 ± 0.236	79.5 ± 0.174	79.5 ± 0.450
$r = 2$	79.2 ± 0.180	79.4 ± 0.242	79.4 ± 0.130	79.4 ± 0.125	79.3 ± 0.047
$r = 4$	78.9 ± 0.206	79.2 ± 0.087	79.2 ± 0.170	79.6 ± 0.309	79.4 ± 0.170

Table 4: N-GCN$_a$ results on Citeseer dataset, with $\hat{A}^0$ disabled. Top-left entry corresponds to vanilla GCN. Left column corresponds to ensemble of GCN models.

	$K=1$	$K=2$	$K=3$	$K=4$	$K=5$
$r=1$	78.2 ± 0.383	79.6 ± 0.327	79.8 ± 0.163	79.8 ± 0.094	79.4 ± 0.216
$r=2$	77.3 ± 0.148	79.6 ± 0.170	79.7 ± 0.141	79.6 ± 0.083	79.9 ± 0.245
$r=4$	77.3 ± 0.314	79.4 ± 0.447	79.5 ± 0.268	79.7 ± 0.125	79.9 ± 0.125

Table 5: N-GCN$_a$ results on Citeseer dataset, with $\hat{A}^0$ enabled.

	$K=1$	$K=2$	$K=3$	$K=4$	$K=5$
$r=1$	$-$	78.4 ± 0.758	78.6 ± 0.460	79.0 ± 0.497	78.4 ± 0.873
$r=2$	78.5 ± 0.361	77.8 ± 0.245	78.6 ± 0.857	78.8 ± 0.411	78.8 ± 0.050
$r=4$	78.6 ± 0.412	78.2 ± 0.806	79.0 ± 0.262	79.0 ± 0.216	79.0 ± 0.047

Table 6: N-GCN$_{fc}$ results on Citeseer dataset, with $\hat{A}^0$ disabled. Left column corresponds to ensemble of GCN models.

	$K=1$	$K=2$	$K=3$	$K=4$	$K=5$
$r=1$	76.0 ± 1.070	78.2 ± 1.290	79.2 ± 1.141	78.5 ± 0.818	78.8 ± 0.918
$r=2$	76.7 ± 1.156	77.1 ± 1.152	79.0 ± 0.779	79.6 ± 0.713	79.0 ± 0.300
$r=4$	76.3 ± 0.758	77.4 ± 0.791	78.6 ± 0.974	78.7 ± 1.003	79.1 ± 0.216

Table 7: N-GCN$_{fc}$ results on Citeseer dataset, with $\hat{A}^0$ enabled.

	$K=1$	$K=2$	$K=3$	$K=4$	$K=5$
$r=1$	76.0 ± 1.239	76.9 ± 0.863	77.6 ± 0.256	77.4 ± 0.419	76.4 ± 0.668
$r=2$	76.4 ± 1.219	77.7 ± 0.546	77.5 ± 0.352	77.8 ± 0.712	78.1 ± 0.245
$r=4$	76.5 ± 0.914	77.4 ± 0.094	78.0 ± 0.260	78.3 ± 0.245	77.6 ± 0.377

Table 8: N-SAGE$_a$ results on Citeseer dataset, with $\hat{A}^0$ disabled. Top-left entry corresponds to vanilla SAGE. Left column corresponds to ensemble of SAGE models.

	$K=1$	$K=2$	$K=3$	$K=4$	$K=5$
$r=1$	73.0 ± 0.828	76.1 ± 0.306	76.8 ± 0.647	76.6 ± 0.623	76.9 ± 0.300
$r=2$	75.2 ± 0.597	76.1 ± 0.449	76.4 ± 0.241	77.2 ± 0.277	77.5 ± 1.178
$r=4$	74.9 ± 0.574	77.1 ± 0.228	77.1 ± 0.141	77.5 ± 0.525	77.5 ± 0.356

Table 9: N-SAGE$_a$ results on Citeseer dataset, with $\hat{A}^0$ enabled.

	$K=1$	$K=2$	$K=3$	$K=4$	$K=5$
$r=1$	$-$	75.8 ± 1.404	77.0 ± 0.858	77.6 ± 0.287	77.0 ± 0.573
$r=2$	76.9 ± 1.396	76.9 ± 1.296	78.1 ± 0.634	77.6 ± 0.860	77.5 ± 0.400
$r=4$	76.5 ± 0.602	78.7 ± 0.665	77.6 ± 0.287	76.9 ± 0.544	78.3 ± 0.386

Table 10: N-SAGE$_{fc}$ results on Citeseer dataset, with $\hat{A}^0$ disabled. Left column corresponds to ensemble of SAGE models.

	$K=1$	$K=2$	$K=3$	$K=4$	$K=5$
$r=1$	73.0 ± 0.977	75.6 ± 0.887	75.4 ± 0.450	77.6 ± 1.349	77.0 ± 0.500
$r=2$	75.3 ± 0.748	76.0 ± 1.347	76.6 ± 0.759	76.4 ± 0.403	76.0 ± 0.591
$r=4$	75.5 ± 1.960	76.4 ± 1.186	76.7 ± 0.648	76.7 ± 0.531	77.9 ± 0.000

Table 11: N-SAGE$_{fc}$ results on Citeseer dataset, with $\hat{A}^0$ enabled.

	$K=1$	$K=2$	$K=3$	$K=4$	$K=5$
$r=1$	79.0 ± 0.125	79.5 ± 0.098	79.5 ± 0.236	79.5 ± 0.174	79.5 ± 0.450
$r=2$	79.2 ± 0.180	79.4 ± 0.242	79.4 ± 0.130	79.4 ± 0.125	79.3 ± 0.047
$r=4$	78.9 ± 0.206	79.2 ± 0.087	79.2 ± 0.170	79.6 ± 0.309	79.4 ± 0.170

Table 12: N-GCN$_a$ results on Cora dataset, with $\hat{A}^0$ disabled. Top-left entry corresponds to vanilla GCN. Left column corresponds to ensemble of GCN models.

	$K = 1$	$K = 2$	$K = 3$	$K = 4$	$K = 5$
$r = 1$	78.2 ± 0.383	79.6 ± 0.327	79.8 ± 0.163	79.8 ± 0.094	79.4 ± 0.216
$r = 2$	77.3 ± 0.148	79.6 ± 0.170	79.7 ± 0.141	79.6 ± 0.083	79.9 ± 0.245
$r = 4$	77.3 ± 0.314	79.4 ± 0.447	79.5 ± 0.268	79.7 ± 0.125	79.9 ± 0.125

Table 13: N-GCN$_{\text{a}}$ results on Cora dataset, with $\hat{A}^0$ enabled.

	$K = 1$	$K = 2$	$K = 3$	$K = 4$	$K = 5$
$r = 1$	$-$	78.4 ± 0.758	78.6 ± 0.460	79.0 ± 0.497	78.4 ± 0.873
$r = 2$	78.5 ± 0.361	77.8 ± 0.245	78.6 ± 0.857	78.8 ± 0.411	78.8 ± 0.050
$r = 4$	78.6 ± 0.412	78.2 ± 0.806	79.0 ± 0.262	79.0 ± 0.216	79.0 ± 0.047

Table 14: N-GCN$_{\text{fc}}$ results on Cora dataset, with $\hat{A}^0$ disabled. Left column corresponds to ensemble of GCN models.

	$K = 1$	$K = 2$	$K = 3$	$K = 4$	$K = 5$
$r = 1$	76.0 ± 1.070	78.2 ± 1.290	79.2 ± 1.141	78.5 ± 0.818	78.8 ± 0.918
$r = 2$	76.7 ± 1.156	77.1 ± 1.152	79.0 ± 0.779	79.6 ± 0.713	79.0 ± 0.300
$r = 4$	76.3 ± 0.758	77.4 ± 0.791	78.6 ± 0.974	78.7 ± 1.003	79.1 ± 0.216

Table 15: N-GCN$_{\text{fc}}$ results on Cora dataset, with $\hat{A}^0$ enabled.

	$K = 1$	$K = 2$	$K = 3$	$K = 4$	$K = 5$
$r = 1$	76.0 ± 1.239	76.9 ± 0.863	77.6 ± 0.256	77.4 ± 0.419	76.4 ± 0.668
$r = 2$	76.4 ± 1.219	77.7 ± 0.546	77.5 ± 0.352	77.8 ± 0.712	78.1 ± 0.245
$r = 4$	76.5 ± 0.914	77.4 ± 0.094	78.0 ± 0.260	78.3 ± 0.245	77.6 ± 0.377

Table 16: N-SAGE$_{\text{a}}$ results on Cora dataset, with $\hat{A}^0$ disabled. Top-left entry corresponds to vanilla SAGE. Left column corresponds to ensemble of SAGE models.

	$K = 1$	$K = 2$	$K = 3$	$K = 4$	$K = 5$
$r = 1$	73.0 ± 0.828	76.1 ± 0.306	76.8 ± 0.647	76.6 ± 0.623	76.9 ± 0.300
$r = 2$	75.2 ± 0.597	76.1 ± 0.449	76.4 ± 0.241	77.2 ± 0.277	77.5 ± 1.178
$r = 4$	74.9 ± 0.574	77.1 ± 0.228	77.1 ± 0.141	77.5 ± 0.525	77.5 ± 0.356

Table 17: N-SAGE$_{\text{a}}$ results on Cora dataset, with $\hat{A}^0$ enabled.

	$K = 1$	$K = 2$	$K = 3$	$K = 4$	$K = 5$
$r = 1$	$-$	75.8 ± 1.404	77.0 ± 0.858	77.6 ± 0.287	77.0 ± 0.573
$r = 2$	76.9 ± 1.396	76.9 ± 1.296	78.1 ± 0.634	77.6 ± 0.860	77.5 ± 0.400
$r = 4$	76.5 ± 0.602	78.7 ± 0.665	77.6 ± 0.287	76.9 ± 0.544	78.3 ± 0.386

Table 18: N-SAGE$_{\text{fc}}$ results on Cora dataset, with $\hat{A}^0$ disabled. Left column corresponds to ensemble of SAGE models.

	$K = 1$	$K = 2$	$K = 3$	$K = 4$	$K = 5$
$r = 1$	73.0 ± 0.977	75.6 ± 0.887	75.4 ± 0.450	77.6 ± 1.349	77.0 ± 0.500
$r = 2$	75.3 ± 0.748	76.0 ± 1.347	76.6 ± 0.759	76.4 ± 0.403	76.0 ± 0.591
$r = 4$	75.5 ± 1.960	76.4 ± 1.186	76.7 ± 0.648	76.7 ± 0.531	77.9 ± 0.000

Table 19: N-SAGE$_{\text{fc}}$ results on Cora dataset, with $\hat{A}^0$ enabled.

	$K = 1$	$K = 2$	$K = 3$	$K = 4$	$K = 5$
$r = 1$	79.0 ± 0.125	79.5 ± 0.098	79.5 ± 0.236	79.5 ± 0.174	79.5 ± 0.450
$r = 2$	79.2 ± 0.180	79.4 ± 0.242	79.4 ± 0.130	79.4 ± 0.125	79.3 ± 0.047
$r = 4$	78.9 ± 0.206	79.2 ± 0.087	79.2 ± 0.170	79.6 ± 0.309	79.4 ± 0.170

Table 20: N-GCN$_{\text{a}}$ results on Pubmed dataset, with $\hat{A}^0$ disabled. Top-left entry corresponds to vanilla GCN. Left column corresponds to ensemble of GCN models.

	$K = 1$	$K = 2$	$K = 3$	$K = 4$	$K = 5$
$r = 1$	78.2 ± 0.383	79.6 ± 0.327	79.8 ± 0.163	79.8 ± 0.094	79.4 ± 0.216
$r = 2$	77.3 ± 0.148	79.6 ± 0.170	79.7 ± 0.141	79.6 ± 0.083	79.9 ± 0.245
$r = 4$	77.3 ± 0.314	79.4 ± 0.447	79.5 ± 0.268	79.7 ± 0.125	79.9 ± 0.125

Table 21: N-GCN$_a$ results on Pubmed dataset, with $\hat{A}^0$ enabled.

	$K = 1$	$K = 2$	$K = 3$	$K = 4$	$K = 5$
$r = 1$	–	78.4 ± 0.758	78.6 ± 0.460	79.0 ± 0.497	78.4 ± 0.873
$r = 2$	78.5 ± 0.361	77.8 ± 0.245	78.6 ± 0.857	78.8 ± 0.411	78.8 ± 0.050
$r = 4$	78.6 ± 0.412	78.2 ± 0.806	79.0 ± 0.262	79.0 ± 0.216	79.0 ± 0.047

Table 22: N-GCN$_{fc}$ results on Pubmed dataset, with $\hat{A}^0$ disabled. Left column corresponds to ensemble of GCN models.

	$K = 1$	$K = 2$	$K = 3$	$K = 4$	$K = 5$
$r = 1$	76.0 ± 1.070	78.2 ± 1.290	79.2 ± 1.141	78.5 ± 0.818	78.8 ± 0.918
$r = 2$	76.7 ± 1.156	77.1 ± 1.152	79.0 ± 0.779	79.6 ± 0.713	79.0 ± 0.300
$r = 4$	76.3 ± 0.758	77.4 ± 0.791	78.6 ± 0.974	78.7 ± 1.003	79.1 ± 0.216

Table 23: N-GCN$_{fc}$ results on Pubmed dataset, with $\hat{A}^0$ enabled.

	$K = 1$	$K = 2$	$K = 3$	$K = 4$	$K = 5$
$r = 1$	76.0 ± 1.239	76.9 ± 0.863	77.6 ± 0.256	77.4 ± 0.419	76.4 ± 0.668
$r = 2$	76.4 ± 1.219	77.7 ± 0.546	77.5 ± 0.352	77.8 ± 0.712	78.1 ± 0.245
$r = 4$	76.5 ± 0.914	77.4 ± 0.094	78.0 ± 0.260	78.3 ± 0.245	77.6 ± 0.377

Table 24: N-SAGE$_a$ results on Pubmed dataset, with $\hat{A}^0$ disabled. Top-left entry corresponds to vanilla SAGE. Left column corresponds to ensemble of SAGE models.

	$K = 1$	$K = 2$	$K = 3$	$K = 4$	$K = 5$
$r = 1$	73.0 ± 0.828	76.1 ± 0.306	76.8 ± 0.647	76.6 ± 0.623	76.9 ± 0.300
$r = 2$	75.2 ± 0.597	76.1 ± 0.449	76.4 ± 0.241	77.2 ± 0.277	77.5 ± 1.178
$r = 4$	74.9 ± 0.574	77.1 ± 0.228	77.1 ± 0.141	77.5 ± 0.525	77.5 ± 0.356

Table 25: N-SAGE$_a$ results on Pubmed dataset, with $\hat{A}^0$ enabled.

	$K = 1$	$K = 2$	$K = 3$	$K = 4$	$K = 5$
$r = 1$	–	75.8 ± 1.404	77.0 ± 0.858	77.6 ± 0.287	77.0 ± 0.573
$r = 2$	76.9 ± 1.396	76.9 ± 1.296	78.1 ± 0.634	77.6 ± 0.860	77.5 ± 0.400
$r = 4$	76.5 ± 0.602	78.7 ± 0.665	77.6 ± 0.287	76.9 ± 0.544	78.3 ± 0.386

Table 26: N-SAGE$_{fc}$ results on Pubmed dataset, with $\hat{A}^0$ disabled. Left column corresponds to ensemble of SAGE models.

	$K = 1$	$K = 2$	$K = 3$	$K = 4$	$K = 5$
$r = 1$	73.0 ± 0.977	75.6 ± 0.887	75.4 ± 0.450	77.6 ± 1.349	77.0 ± 0.500
$r = 2$	75.3 ± 0.748	76.0 ± 1.347	76.6 ± 0.759	76.4 ± 0.403	76.0 ± 0.591
$r = 4$	75.5 ± 1.960	76.4 ± 1.186	76.7 ± 0.648	76.7 ± 0.531	77.9 ± 0.000

Table 27: N-SAGE$_{fc}$ results on Pubmed dataset, with $\hat{A}^0$ enabled.