MAKING CONVOLUTIONAL NETWORKS SHIFT-INVARIANT AGAIN

ABSTRACT

Modern convolutional networks are not shift-invariant, despite their convolutional nature: small shifts in the input can cause drastic changes in the internal feature maps and output. In this paper, we isolate the cause – the downsampling operation in convolutional and pooling layers – and apply the appropriate signal processing fix – low-pass filtering before downsampling. This simple architectural modification boosts the shift-equivariance of the internal representations and consequently, shift-invariance of the output. Importantly, this is achieved while maintaining downstream classification performance. In addition, incorporating the inductive bias of shift-invariance largely removes the need for shift-based data augmentation. Lastly, we observe that the modification induces spatially-smoother learned convolutional kernels. Our results suggest that this classical signal processing technique has a place in modern deep networks.

1 INTRODUCTION

Deep convolutional neural networks (CNNs) are designed to perform high-level tasks and be robust to low-level nuisance factors. For example, small shifts in the input *should* simply shift the internal feature maps (shift-equivariance), and leave the output relatively unaffected (shift-invariance). This property has been explicitly engineered through convolutional and pooling layers, where the same function is applied on a local region across the image in a sliding window fashion. However, recent work (Engstrom et al., 2017; Azulay & Weiss, 2018) has found that small shifts can drastically change the output of a classification network. Why is this the case?

Shift-invariance is lost when spatial resolution is lost, for example, from pooling layers. Our insight is that conventional strided-pooling, as shown in Fig. 1 (top), is inherently composed of two operations: (1) evaluating the pooling operator densely (without striding), and (2) downsampling. Naive downsampling loses shift-equivariance, as high-frequency components of the signal alias into low-frequencies. This phenomenon is commonly illustrated in movies, where wheels appear to spin backwards, due to the frame rate not meeting the Nyquist sampling criterion (known as the Stroboscopic effect). Separating out these operations is important, as it allows us to keep the advantages of the pooling operation, which preserves shift-equivariance, while applying the appropriate fix to the downsampling operation.

We propose to add the signal processing tool of *low-pass filtering before downsampling*, as shown in Fig. 1 (bottom). By low-pass filtering, the high-frequency components of the signal are reduced, reducing aliasing and better preserving shift-equivariance. This ultimately cascades into better shift-invariance in the output. We show example classification instabilities in Fig. 2.

A potential concern is that over-aggressive low-pass filtering can result in heavy loss of information. However, we find that with a reasonable selection of low-pass filter weights, we can maintain classification performance while increasing shift-invariance. Furthermore, we show that without shift-based data augmentation, incorporating this inductive bias actually improves performance.

We find that the learned filters also naturally become smoother after adding the blurring layer. These results indicate that incorporating this small modification not only induces shift-invariance, but causes the network to learn a smoother feature extractor.

In summary, our contributions are as follows:

Figure 1: (Top) Pooling does not preserve shift-equivariance. It is functionally equivalent to densely evaluated pooling (which preserves shift-equivariance), followed by naive downsampling. The latter operation ignores the Nyquist sampling theorem and loses shift-equivariance. **(Bottom)** We propose to low-pass filter between the pooling and downsampling operations. This modification allows us to keep the original pooling operation of choice untouched, while applying antialiasing to the appropriate signal before the downsampling operation. This equivalent analysis and modification can be applied to any type of strided layer, such as convolution.

- We isolate the cause for loss of shift-invariance – downsampling. Separating the downsampling and pooling operations enables us to keep the desired pooling function, while fixing the loss of shift-equivariance. We propose to low-pass filter before downsampling, a common signal processing technique.

- We validate on a classification task, and demonstrate increased shift-equivariance in the features and shift-invariance in the output.

- In addition, we observe large improvements in classification performance when training without shift-augmentation, indicating more efficient usage of data.

2 RELATED WORK

Local connectivity and weight sharing have been a central tenet of neural networks, including the Neocognitron (Fukushima & Miyake, 1982), LeNet (LeCun et al., 1998) and modern networks such as Alexnet (Krizhevsky et al., 2012), VGG (Simonyan & Zisserman, 2014), ResNet (He et al., 2016), and DenseNet (Huang et al., 2017). In biological systems, local connectivity was famously discovered observed in a cat's visual system by Hubel & Wiesel (1962). Recent work has strived to build in additional types of invariances, such as rotation, reflection, and scaling (Sifre & Mallat, 2013; Bruna & Mallat, 2013; Esteves et al., 2017; Kanazawa et al., 2014; Worrall et al., 2017; Cohen & Welling, 2016). Our work focusses on the elusive goal of shift-invariance.

Though properties such as shift-equivariance have been engineered into networks, what factors and invariances does an emergent representation actually learn? Analysis of deep networks have included qualitative approaches, such as showing patches which activate hidden units (Girshick et al., 2014; Zhou et al., 2014), actively maximizing hidden units (Mordvintsev et al., 2015), and mapping features back into pixel space (Dosovitskiy & Brox, 2016a;b; Mahendran & Vedaldi, 2015; Zeiler & Fergus, 2014; Nguyen et al., 2017; Hénaff & Simoncelli, 2015). Our analysis is focussed on a specific, low-level property and is complementary to these qualitative approaches.

Figure 2: Classification stability for selected images. We show how probability of correct classification changes when applying a diagonal shift. The baseline classifications (black) exhibit chaotic behavior, which is stabilized by our method (blue).

A more quantitative approach for analyzing networks is measuring representation or output changes (or robustness to changes) in response to manually generated perturbations to the input, such as image transformations (Goodfellow et al., 2009; Lenc & Vedaldi, 2015; Azulay & Weiss, 2018), geometric transforms (Ruderman et al., 2018; Fawzi & Frossard, 2015), and CG renderings with various shape, poses, and colors (Aubry & Russell, 2015). A related line of work is in adversarial examples, where directed perturbations in the input can result in large changes in the output. These perturbations can be directly on pixels (Goodfellow et al., 2014a;b), a single pixel (Su et al., 2017), small deformations (Xiao et al., 2018), or even affine transformations (Engstrom et al., 2017). We aim make the network robust to the simplest of these types of attacks and perturbations: shifts. Both Hénaff & Simoncelli (2015) and Azulay & Weiss (2018) identify that modern deep networks ignore the Nyquist sampling criterion when downsampling. In our work, we propose and empirically validate an easily adoptable fix which minimally perturbs the existing network architecture.

Classic hand-engineered computer vision and image processing representations, such as SIFT (Lowe, 1999), wavelets, and image pyramids (Burt & Adelson, 1987; Adelson et al., 1984) also extract features in a sliding window manner, often with some subsampling factor. As discussed in Simoncelli et al. (1992), literal shift-equivariance cannot hold when with subsampling. Shift-equivariance can be recovered if features are extracted densely, for example textons (Leung & Malik, 2001), the Stationary Wavelet Transform (Fowler, 2005), and DenseSIFT (Vedaldi & Fulkerson, 2010). Deep networks can also be evaluated densely, by removing striding and making appropriate changes to subsequent layers by using *á trous*/dilated convolutions (Chen et al., 2014; 2018; Yu & Koltun, 2015). This comes at great computation and memory cost. Our work investigates achieving shift-equivariance with minimal additional computation.

3 METHODS

3.1 PRELIMINARIES

Deep convolutional networks as feature extractors Let an image with resolution $H \times W$ be represented by $X \in \mathbb{R}^{H \times W \times 3}$. An L-layer deep can be expressed as a feature extractor $\mathcal{F}_l(X) \in \mathbb{R}^{H_l \times W_l \times C_l}$, with layer $l \in [0, L]$, spatial resolution $H_l \times W_l$ and C_l channels. Each feature map can also be upsampled to original resolution, $\widetilde{\mathcal{F}}_l(X) \in \mathbb{R}^{H \times W \times C}$.

Shift-equivariance and shift-invariance A representation $\widetilde{\mathcal{F}}$ is shift-equivariant if shifting the input produces a shifted feature map, meaning that shifting and feature extraction are commutable.

$$\text{Shift}_{\Delta h, \Delta w}(\widetilde{\mathcal{F}}(X)) = \widetilde{\mathcal{F}}(\text{Shift}_{\Delta h, \Delta w}(X)) \quad \forall (\Delta h, \Delta w) \tag{1}$$

A representation is shift-invariant if shifting the input results in an *identical* representation.

$$\widetilde{\mathcal{F}}(X) = \widetilde{\mathcal{F}}(\text{Shift}_{\Delta h, \Delta w}(X)) \quad \forall (\Delta h, \Delta w) \tag{2}$$

Figure 3: Example of sensitivity to shifts when downsampling. We show a simple example of max-pooling, to illustrate how downsampling affects shift-equivariance. **(Top-Left)** We show a toy signal in light gray. Max-pooling this signal with (kernel 2, stride 2) is shown in blue. **(Top-Right)** Simply shifting the input signal provides a completely different max-pooled result, shown in red. **(Bot-Left)** Max-pooling densely (kernel 2, stride 1) is shown in **thick black**. The blue and red points are inherently sampled from this intermediate signal. The red and blue are far from each other, and shift-equivariance is lost. **(Bot-Right)** In the proposed method, we sample from the low-passed version of the signal (low-pass kernel of [0.25, 0.5, 0.25]), shown in green and magenta. Shift-equivariance is better preserved (though not perfectly).

For modern classifiers, layer $l = 0$ is the raw pixels, and final layer L is a probability distribution over D classes, $\mathcal{F}_L \in \Delta^{1 \times 1 \times D}$. The network typically reduces spatial resolution throughout the network, until all spatial resolution is lost and features are of shape $\mathbb{R}^{1 \times 1 \times C_l}$. A common technique, such as used in (He et al., 2016; Lin et al., 2013), is to average across the entire feature map spatially, and use fully-connected layers in all subsequent layers, which can be expressed as 1×1 convolutions (Long et al., 2015). In such a setting, as proven by Azulay & Weiss (2018), shift-invariance on the output will necessarily emerge from shift-equivariance in the convolutional features.

Modulo-N shift-equivariance/invariance In some cases, the definitions in Equations 1, 2 may hold only when shifts $(\Delta h, \Delta w)$ are integer multiples of N. We refer to these scenarios as modulo-N shift-equivariance or invariance. For example, modulo-2 shift-invariance means that even-pixel shifts of the input result in an identical representation, but odd-pixel shifts may not.

3.2 CONVENTIONAL POOLING VS PROPOSED POOL-BLUR-DOWNSAMPLE

Conventional strided pooling breaks shift-equivariance In Fig. 3, we show an example 1-D signal $[0, 0, 1, 1, 0, 0, 1, 1]$. Max-pooling (with kernel size 2, stride 2) will result in $[0, 1, 0, 1]$. Simply shifting the input by one index results a dramatically different answer, $[1, 1, 1, 1]$. Shift-equivariance is lost. As seen in the middle-left, both of these results are inherently downsampling from an intermediate signal – a dense max-pooling (kernel size 2, stride 1) of the original signal. We can write a max-pooling layer as a composition of two functions, max-pooling densely evaluated, followed by naive downsampling: $\text{MaxPool}_{k,s}(X) = \text{Downsample}_s(\text{MaxPool}_{k,1}(X))$.

In the illustrative example, there is significant energy in the high-frequency in this intermediate signal. Max-pooling preserves shift-equivariance (when evaluated densely), but naive downsampling does not.

Blurring before downsampling better preserves shift-equivariance We propose to low-pass filter the intermediate signal before downsampling, as shown in Fig. 3(mid-right). We define our Max-PoolBlurDownsample operator below.

$$\text{MaxPoolBlurDS}_{k,s}(X) = \text{Downsample}_s(\text{Blur}_{k_{blur}}(\text{MaxPool}_{k,1}(X))) \tag{3}$$

Sampling from the low-pass filtered signal gives $[.5, .1, .5, 1]$ and $[.75, .75, .75, .75]$ (Fig. 3 mid-right). These are closer to each other and better representations of the intermediate signal.

The method allows for a choice of blur kernel. In image processing, small kernels are often used across applications such as edge detection (Canny, 1986) and image pyramids (Adelson et al., 1984).

(a) MaxPool (Baseline)

(b) MaxPoolBlurDownsample (Proposed) with 5×5 Triangle Low-Pass Filter

Figure 4: Shift equivariance throughout the network. We show how close each layer is to satisfying shift-equivariance condition by commuting the shift and feature extraction operations, and computing their distance in feature space across the test set. Each point in each heatmap is a value of $(\Delta h, \Delta w)$. Resolution of the layer written in [brackets]. The last three layers have no spatial information, and shift-equivariance is equivalent to shift-invariance. Layers `pix-pool1(dense)` have perfect equivariance (distance 0 at all shifts, shown by blue). Red is half mean distance between two random *different* images. **(a)** On the baseline VGG13 net, shift-equivariance is reduced each time downsampling takes place. Modulo-N shift-equivariance holds with N doubling with each downsampling. **(b)** With our proposed change, shift-equivariance is better maintained throughout the network, and the resulting classifications (softmax) layer is more shift-invariant.

We try a number of kernels, ranging from size 2×2 to 7×7. As the blur kernels are separable, it can be implemented as a series of two convolutions (vertical blur followed by horizontal), and added computation scales linearly with k_{blur}, rather than quadratically.

4 EXPERIMENTS

4.1 EXPERIMENTAL SETUP

Data, architecture, training schedule We test on CIFAR10 classification (Krizhevsky & Hinton, 2009), which consists of 50k training and 10k testing images at resolution 32×32. We use the VGG13 architecture (Simonyan & Zisserman, 2014). Each block consists of 2 `Conv-BatchNorm-ReLU` chunks, followed by a `MaxPool`. Each block doubles the feature channels and reduces spatial resolution by a factor of 2, until all spatial resolution is lost. A final softmax layer predicts a probability vector. We use stochastic gradient descent (SGD) with momentum 0.9 and batch size 128. We train for 100 epochs at the initial learning rate 0.1 and 50 additional epochs at 0.01 and 0.01. We use the PyTorch framework (Paszke et al., 2017) and will make code available.

Low-pass filter kernels We try a number of standard low-pass filters, shown in Table 1, ranging from size 2×2 to 7×7. All filters allow the DC signal pass and suppress (or completely kill) the highest frequency. Variations in filters correspond to tradeoffs between location of the cutoff frequency, slope of the cutoff, and variation of lobes in the passband and stopband. These properties are well-studied in the context of finite impulse response (FIR) filter design. However, it is unclear which types of filters are best suited for deep networks, so we empirically investigate their effects.

Circular convolution and shifting Edge artifacts are an important consideration. When an image is shifted, information is necessarily lost on one side, and has to be filled in on the other. In all our experiments, we use circular shifting and convolution. When the convolutional kernel hits the edge, it wraps to the other side. When shifting, pixels are "rolled" off the edge to the other side.

$$[\text{Shift}_{\Delta h, \Delta w}(X)]_{h,w,c} = X_{(h-\Delta h)\%H,(w-\Delta w)\%W,c} \text{ , where } \% \text{ is the modulus function} \quad (4)$$

Figure 5: **Classification consistency vs. classification.** We show networks trained **(left)** without and **(right)** with shift-based data augmentation, using various blurring filters. Consistency is computed by computing classification of an image with two random shifts, and checking for agreement. Up (more consistent) and to the right (more accurate) is better. Number of sides corresponds to number of filter taps used (e.g., diamond for 4-tap filter); colors correspond to different methods for generating FIR filters. We highlight Triangle-5 and Pascal-7, which perform consistently well.

Filter shape	# Taps	Weights	Train with no augmentation				Train with Augmentation			
			Test accuracy		Classification	Average	Test accuracy		Classification	Average
			None	Random	Consistency		None	Rand	Consistency	
Delta (baseline)	1	[1]	91.6%	87.5%	88.1%	89.9%	93.4%	93.8%	96.6%	95.0%
Rectangle	2	[1, 1]	92.8%	89.2%	90.5%	91.6%	93.9%	93.7%	97.6%	95.8%
Rectangle	3	[1, 1, 1]	93.4%	91.9%	94.5%	93.9%	93.6%	93.7%	97.9%	95.7%
Rectangle	4	[1, 1, 1, 1]	93.2%	92.8%	97.7%	95.4%	93.4%	93.4%	98.5%	95.9%
Rectangle	5	[1, 1, 1, 1, 1]	92.2%	92.0%	98.3%	95.2%	92.4%	92.6%	98.7%	95.6%
Rectangle	6	[1, 1, 1, 1, 1, 1]	91.4%	91.3%	97.3%	94.4%	91.4%	91.4%	98.9%	95.2%
Rectangle	7	[1, 1, 1, 1, 1, 1, 1]	90.8%	90.7%	98.8%	94.8%	90.5%	90.6%	99.0%	94.8%
Triangle	3	[1, 2, 1]	93.1%	91.7%	93.9%	93.5%	93.6%	93.6%	98.0%	95.8%
Triangle	5	[1, 2, 3, 2, 1]	93.3%	93.3%	98.2%	95.7%	93.3%	93.3%	98.6%	96.0%
Triangle	7	[1, 2, 3, 4, 3, 2, 1]	92.3%	92.3%	98.8%	95.5%	92.4%	92.3%	99.0%	95.7%
Pascal	4	[1, 3, 3, 1]	93.0%	91.5%	93.2%	93.1%	93.4%	93.2%	98.1%	95.7%
Pascal	5	[1, 4, 6, 4, 1]	93.2%	92.2%	96.3%	94.8%	93.1%	93.2%	98.4%	95.8%
Pascal	6	[1, 5, 10, 10, 5, 1]	93.0%	92.3%	96.9%	94.9%	93.4%	93.4%	98.6%	96.0%
Pascal	7	[1, 6, 15, 20, 15, 6, 1]	93.0%	93.0%	98.1%	95.5%	93.2%	93.2%	98.8%	96.0%
Window	3	[1, 1.57, 1]	93.3%	91.5%	94.2%	93.8%	93.5%	93.6%	98.0%	95.7%
Window	6	[-1, 1.67, 5, 5, 1.67, -1]	92.9%	90.2%	91.4%	92.1%	93.4%	93.5%	98.1%	95.7%
Window	7	[-1, 0, 3, 4.71, 3, 0, -1]	92.4%	91.5%	94.0%	93.2%	93.4%	93.5%	97.8%	95.6%
Least Squares	3	[1, 1,63, 1]	93.1%	91.5%	93.8%	93.4%	93.7%	93.8%	98.0%	95.9%
Least Squares	7	[-1, 0, 3.80, 6.13, 3.80, 0, -1]	92.7%	91.2%	93.9%	93.3%	93.4%	93.6%	97.9%	95.6%

Table 1: **Results** We show results across blurring filters and training scenarios (without and with data augmentation). We evaluate on classification accuracy without shifts (**Test accuracy – none**) and on random shifts (**Test accuracy – Random**), as well as **classification consistency**. We also compute an **average** of test accuracy (without shifting) and classification consistency and highlight top and bottom 3 performers. We use standard low-pass filters (note that weights are normalized to sum to 1): **Rectangle** – a moving average over neighboring values, **Triangle** linearly decreases weight of neighbor values, **Pascal** – [1, 1] filter convolved with itself repeatedly, **Window** – filter produced using the window method (`firwin`) and **Least Squares** error minimization (`firls`), from Python `scipy.signal` toolbox. Triangle-5 and Pascal-7 perform well.

This modification minorly decreases classification performance, 93.8% vs 93.4% with data augmentation. This could potentially be mitigated by additional padding, at the expense of memory and computation. But more importantly, this methodology affords us a clean testbed. Any loss in shift-equivariance or invariance is purely due to characteristics of the feature extractor.

4.2 ANALYSIS

We use the following metrics to characterize shift-equivariance and invariance.

1. **Feature distance (lower is better)** We test how close shift-equivariance and invariance are to being fulfilled by computing $d(\text{Shift}_{\Delta h, \Delta w}(\widetilde{\mathcal{F}}(X)), \widetilde{\mathcal{F}}(\text{Shift}_{\Delta h, \Delta w}(X)))$ and $d(\widetilde{\mathcal{F}}(X), \widetilde{\mathcal{F}}(\text{Shift}_{\Delta h, \Delta w}(X))$ (left & right-hand sides of Eq. 1, 2), respectively. We use cosine distance, which is commonly used for deep features (Kiros et al., 2015; Zhang et al., 2018).

Figure 6: Distribution of per-image classification variation. For each image in the test set, we compute the classification variation over shifts, and measure its variation. We compute the distribution of variations observed for networks trained with different blurring filters, both **(left)** without and **(right)** with data augmentation at training. Lower variation means more consistent classifications (and increased shift-invariance). Training with data augmentation drastically reduces variation in classification. Adding filtering further decreases variation.

2. **Classification consistency (higher is better)** The metric above can be used to measure shift-invariance of the output classification. Perhaps of greater interest is the actual decisions the classifier makes. We can measure its consistency by checking how often the network outputs the same classification, given the same image with two different shifts: $\mathbb{E}_{(X,h_1,w_1,h_2,w_2)} \mathbb{1}\{\arg\max P(\text{Shift}_{h_1,w_1}(X)) = \arg\max P(\text{Shift}_{h_2,w_2}(X))\}$.

3. **Classification variation (lower is better)** Similar to Azulay & Weiss (2018), we trace the variation in probability of correct classification, given different shifts. We can capture the variation across all possible shifts: $\sqrt{Var_{h,w}(\{P_{\text{correct class}}(\text{Shift}_{h,w}(X))\}})$.

Table 1 shows results across a number of different low-pass filters, training with and without data augmentation. We dissect the results below.

How shift-equivariant are deep features? In Fig. 4 (top), we compute distance from shift-equivariance, as a function of all possible shift-offsets $(\Delta h, \Delta w)$ and layers. `MaxPool` layers are broken into two components – before and after downsampling. Pixels are trivially shift-equivariant, as are all layers before the first downsampling. Once downsampling occurs in `pool1(ds)`, shift-equivariance is lost. However, modulo-N shift-equivariance still holds, and each subsequent downsampling doubles the factor.

Additionally, we observe that before the downsampling operation, the pooling layer first increases shift-equivariance (e.g., `conv3_2` to `pool3(dense)`). This is consistent with the long-held intuition that pooling build invariances inside the network (LeCun et al., 1990) and isolates the downsampling operation as the culprit behind loss of shift-equivariance.

Does blurring before downsampling achieve better shift-equivariance? In Fig. 4 (bottom), we add a blurring filter to the `MaxPool` layers, as proposed in Section 3, and again plot shift-equivariance maps for each layer. Shift-equivariance is clearly better preserved. In particular, the severe drop-offs in downsampling layers do not occur. Improved shift-equivariance throughout the network cascades into more consistent classifications in the final softmax layer.

Some selected examples are in Fig. 2. Our method stabilizes the classifications. In Fig. 6, we show the distribution of classification variations, before and after adding in the low-pass filter. Even a small 2×2 filter, immediately variation. As the filter size is increased, the output classification variation decreases. This has a larger effect when training without data augmentation, but is still observable when training with data augmentation.

Does shift-invariance degrade performance? Our method produces more shift-equivariant feature maps and consequently, more shift-invariant outputs. However, does this come at a cost?

We study the output classification consistency versus classification accuracy. In Fig. 5 (left), we show results, trained without shift-based data augmentation. Training with the baseline MaxPooling gives accuracy 91.6% and consistency 88.1%. Our proposed change – with a 5×5 triangle filter

improves accuracy to 93.3% and consistency to 98.2%. This indicates that low-pass filtering does not destroy the signal, or make learning harder. On the contrary, preserving shift-equivariance serves as "built-in" augmentation, indicating more efficient data usage.

In principle, networks can *learn* to be shift-invariant from data. Does adding shift-based data augmentation remove the benefit from method? Shift-based data augmentation with the baseline network results in consistency of 96.6%, lower than our method trained *without* data augmentation. In addition, as seen in Fig. 5 (right), applying out method *with* data augmentation provides an immediate jump in classification consistency, while maintaining accuracy. From there, a clear tradeoff appears – higher amounts of shift-invariance can be achieved at the cost of decreased accuracy. For example, very large rectangular filters over-aggressively smooth the signal. Downstream applications may favor one factor over another, and the choice of filter allows one to explore this space.

Figure 7: Total Variation (TV) by layer. We compute average smoothness of learned conv filters per layer (lower is smoother). Baseline MaxPool is in black, and adding additional blurring is shown in colors. Note that the *learned* convolutional layers become smoother, indicating that a smoother feature extractor is induced. The Pascal-7 filter produces consistently strong results, in both consistency and accuracy.

Fig. 6 investigates the distribution of classification variations. Training with data augmentation with the baseline network reduces variation (black distributions on left and right plots). Adding our method reduces variation in both scenarios. More aggressive filtering further decreases variation.

How do the learned convolutional filters change with the proposed modification? We measure spatial smoothness using the normalized Total Variation (TV) metric proposed in Ruderman et al. (2018). Our proposed change smooths the internal feature maps for purposes of downsampling. As shown in Fig. 7, this induces smoother *learned* filters throughout the network. Adding in more aggressive blur kernels further decreases the TV (increasing smoothness). This indicates that our modification actually induces a smoother feature extractor overall.

How does the proposed method affect timing? In Tab. 2, we show the added time each element of the proposed method takes: evaluating the MaxPool layer at stride 1 instead of stride 2, and running a blurring filter. Since the blurring filters are separable, time increases linearly with filter size. The largest filter adds 12.3% per forward pass. This is significantly cheaper than evaluating multiple forward passes in an ensembling approach. These timings are on our VGG13 network setup. With deeper networks, the relative added computation decreases.

Model	Timing [ms]	% added
Baseline	10.19	+0.00%
+ dense pool	10.50	+3.04%
+ dense pool + 3×3 filter	11.06	+8.52%
+ dense pool + 5×5 filter	11.27	+10.6%
+ dense pool + 7×7 filter	11.45	+12.3%

Table 2: Timing analysis We test the average speed of a forward pass on a GTX1080Ti Nvidia GPU for a batch size of 100 of 32×32 image with the VGG13 network.

5 CONCLUSIONS AND DISCUSSION

In summary, we show that shift-invariance is lost through a deep network as downsampling in pooling layers do not meet the Nyquist criteria. We propose a simple architectural modification, following signal processing principles, to improve shift-equivariance. This change allows the network architecture designer to keep their pooling layer of choice untouched.

We achieve higher consistency while maintaining classification performance. In addition, we show large improvements in both performance and consistency when training without data augmentation. This is potentially applicable to online learning scenarios, where the data distribution is changing. Future directions include exploring the potential benefit to downstream applications, such as nearest-neighbor retrieval, improving temporal consistency in video models, robustness to adversarial examples, and high-level vision tasks such as detection. Another possible future direction is learning the downsampling kernels. Overall, our experiments indicate that this classical signal processing technique has a place in modern deep networks.

REFERENCES

Edward H Adelson, Charles H Anderson, James R Bergen, Peter J Burt, and Joan M Ogden. Pyramid methods in image processing. *RCA engineer*, 29(6):33–41, 1984.

Mathieu Aubry and Bryan C Russell. Understanding deep features with computer-generated imagery. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 2875–2883, 2015.

Aharon Azulay and Yair Weiss. Why do deep convolutional networks generalize so poorly to small image transformations? *arXiv preprint arXiv:1805.12177*, 2018.

Joan Bruna and Stéphane Mallat. Invariant scattering convolution networks. *IEEE transactions on pattern analysis and machine intelligence*, 35(8):1872–1886, 2013.

Peter J Burt and Edward H Adelson. The laplacian pyramid as a compact image code. In *Readings in Computer Vision*, pp. 671–679. Elsevier, 1987.

John Canny. A computational approach to edge detection. *IEEE Transactions on pattern analysis and machine intelligence*, (6):679–698, 1986.

Liang-Chieh Chen, George Papandreou, Iasonas Kokkinos, Kevin Murphy, and Alan L Yuille. Semantic image segmentation with deep convolutional nets and fully connected crfs. *arXiv preprint arXiv:1412.7062*, 2014.

Liang-Chieh Chen, George Papandreou, Iasonas Kokkinos, Kevin Murphy, and Alan L Yuille. Deeplab: Semantic image segmentation with deep convolutional nets, atrous convolution, and fully connected crfs. *IEEE transactions on pattern analysis and machine intelligence*, 40(4): 834–848, 2018.

Taco Cohen and Max Welling. Group equivariant convolutional networks. In *International conference on machine learning*, pp. 2990–2999, 2016.

Alexey Dosovitskiy and Thomas Brox. Generating images with perceptual similarity metrics based on deep networks. In *Advances in Neural Information Processing Systems*, pp. 658–666, 2016a.

Alexey Dosovitskiy and Thomas Brox. Inverting visual representations with convolutional networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4829–4837, 2016b.

Logan Engstrom, Dimitris Tsipras, Ludwig Schmidt, and Aleksander Madry. A rotation and a translation suffice: Fooling cnns with simple transformations. *arXiv preprint arXiv:1712.02779*, 2017.

Carlos Esteves, Christine Allen-Blanchette, Xiaowei Zhou, and Kostas Daniilidis. Polar transformer networks. *arXiv preprint arXiv:1709.01889*, 2017.

Alhussein Fawzi and Pascal Frossard. Manitest: Are classifiers really invariant? *arXiv preprint arXiv:1507.06535*, 2015.

James E Fowler. The redundant discrete wavelet transform and additive noise. *IEEE Signal Processing Letters*, 12(9):629–632, 2005.

Kunihiko Fukushima and Sei Miyake. Neocognitron: A self-organizing neural network model for a mechanism of visual pattern recognition. In *Competition and cooperation in neural nets*, pp. 267–285. Springer, 1982.

Ross Girshick, Jeff Donahue, Trevor Darrell, and Jitendra Malik. Rich feature hierarchies for accurate object detection and semantic segmentation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 580–587, 2014.

Ian Goodfellow, Honglak Lee, Quoc V Le, Andrew Saxe, and Andrew Y Ng. Measuring invariances in deep networks. In *Advances in neural information processing systems*, pp. 646–654, 2009.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in Neural Information Processing systems*, 2014a.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014b.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Computer Vision and Pattern Recognition (CVPR)*, June 2016.

Olivier J Hénaff and Eero P Simoncelli. Geodesics of learned representations. *arXiv preprint arXiv:1511.06394*, 2015.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *CVPR*, volume 1, pp. 3, 2017.

David H Hubel and Torsten N Wiesel. Receptive fields, binocular interaction and functional architecture in the cat's visual cortex. *The Journal of physiology*, 160(1):106–154, 1962.

Angjoo Kanazawa, Abhishek Sharma, and David Jacobs. Locally scale-invariant convolutional neural networks. *arXiv preprint arXiv:1412.5104*, 2014.

Ryan Kiros, Yukun Zhu, Ruslan R Salakhutdinov, Richard Zemel, Raquel Urtasun, Antonio Torralba, and Sanja Fidler. Skip-thought vectors. In *Advances in neural information processing systems*, pp. 3294–3302, 2015.

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. Technical report, Citeseer, 2009.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pp. 1097–1105, 2012.

Yann LeCun, Bernhard E Boser, John S Denker, Donnie Henderson, Richard E Howard, Wayne E Hubbard, and Lawrence D Jackel. Handwritten digit recognition with a back-propagation network. In *Advances in neural information processing systems*, pp. 396–404, 1990.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Karel Lenc and Andrea Vedaldi. Understanding image representations by measuring their equivariance and equivalence. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 991–999, 2015.

Thomas Leung and Jitendra Malik. Representing and recognizing the visual appearance of materials using three-dimensional textons. *International journal of computer vision*, 43(1):29–44, 2001.

Min Lin, Qiang Chen, and Shuicheng Yan. Network in network. *arXiv preprint arXiv:1312.4400*, 2013.

Jonathan Long, Evan Shelhamer, and Trevor Darrell. Fully convolutional networks for semantic segmentation. In *Computer Vision and Pattern Recognition (CVPR)*, 2015.

David G Lowe. Object recognition from local scale-invariant features. In *Computer vision, 1999. The proceedings of the seventh IEEE international conference on*, volume 2, pp. 1150–1157. Ieee, 1999.

Aravindh Mahendran and Andrea Vedaldi. Understanding deep image representations by inverting them. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 5188–5196, 2015.

Alexander Mordvintsev, Christopher Olah, and Mike Tyka. Deepdream-a code example for visualizing neural networks. *Google Research*, 2:5, 2015.

Anh Nguyen, Jeff Clune, Yoshua Bengio, Alexey Dosovitskiy, and Jason Yosinski. Plug & play generative networks: Conditional iterative generation of images in latent space. In *CVPR*, volume 2, pp. 7, 2017.

Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in pytorch. 2017.

Avraham Ruderman, Neil C Rabinowitz, Ari S Morcos, and Daniel Zoran. Pooling is neither necessary nor sufficient for appropriate deformation stability in cnns. *arXiv preprint arXiv:1804.04438*, 2018.

Laurent Sifre and Stéphane Mallat. Rotation, scaling and deformation invariant scattering for texture discrimination. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1233–1240, 2013.

Eero P Simoncelli, William T Freeman, Edward H Adelson, and David J Heeger. Shiftable multi-scale transforms. *IEEE transactions on Information Theory*, 38(2):587–607, 1992.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

Jiawei Su, Danilo Vasconcellos Vargas, and Sakurai Kouichi. One pixel attack for fooling deep neural networks. *arXiv preprint arXiv:1710.08864*, 2017.

Andrea Vedaldi and Brian Fulkerson. Vlfeat: An open and portable library of computer vision algorithms. In *Proceedings of the 18th ACM international conference on Multimedia*, pp. 1469–1472. ACM, 2010.

Daniel E Worrall, Stephan J Garbin, Daniyar Turmukhambetov, and Gabriel J Brostow. Harmonic networks: Deep translation and rotation equivariance. In *Proc. IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, volume 2, 2017.

Chaowei Xiao, Jun-Yan Zhu, Bo Li, Warren He, Mingyan Liu, and Dawn Song. Spatially transformed adversarial examples. *arXiv preprint arXiv:1801.02612*, 2018.

Fisher Yu and Vladlen Koltun. Multi-scale context aggregation by dilated convolutions. *arXiv preprint arXiv:1511.07122*, 2015.

Matthew D Zeiler and Rob Fergus. Visualizing and understanding convolutional networks. In *European conference on computer vision*, pp. 818–833. Springer, 2014.

Richard Zhang, Phillip Isola, Alexei A Efros, Eli Shechtman, and Oliver Wang. The unreasonable effectiveness of deep features as a perceptual metric. In *CVPR*, 2018.

Bolei Zhou, Aditya Khosla, Agata Lapedriza, Aude Oliva, and Antonio Torralba. Object detectors emerge in deep scene cnns. *arXiv preprint arXiv:1412.6856*, 2014.