Learning Non-Metric Visual Similarity for Image Retrieval

Abstract

Measuring visual (dis)similarity between two or more instances within a data distribution is a fundamental task in many applications, specially in image retrieval. Theoretically, non-metric distances are able to generate a more complex and accurate similarity model than metric distances, provided that the non-linear data distribution is precisely captured by the similarity model. In this work, we analyze a simple approach for deep learning networks to be used as an approximation of non-metric similarity functions and we study how these models generalize across different image retrieval datasets.

1 Introduction

For humans, deciding whether two images are visually similar or not is, to some extent, a natural task. However, in computer vision, this is a challenging problem and algorithms do not always succeed in matching pictures that contain similar-looking elements. This is mainly because of the well-known *semantic gap* problem, which refers to the difference or gap between low-level image pixels and high-level semantic concepts. Estimating visual similarity is a fundamental task that seeks to break this semantic gap by accurately evaluating how alike two or more pictures are. Visual similarity is crucial for many computer vision areas including image retrieval, image classification and object recognition, among others.

Given a query image, content-based image retrieval systems rank pictures in a dataset according to how similar they are with respect to the input. This can be broken into two fundamental tasks: 1) computing meaningful image representations that capture the most salient visual information from pixels and 2) measuring accurate visual similarity between these image representations to rank images according to a similarity score.

In the last years, several methods to represent visual information from raw pixels in images have been proposed, first by designing handcrafted features such as SIFT Lowe (2004), then by compacting these local features into a single global image descriptor using different techniques such as Fisher Vectors Perronnin et al. (2010) and more recently by extracting deep image representations from neural networks (Babenko et al. (2014)). However, once two images are described by feature vectors, visual similarity is commonly measured by computing a standard metric between them. Although regular distance metrics, such as Euclidean distance or cosine similarity, are fast and easy to implement, they do not take into account the possible interdependency within the dataset, which means that even if a strong nonlinear data dependency is occurring in the visual collection, they might not be able to capture it. This suggests that learning a similarity estimation directly from visual data can improve the performance on image retrieval tasks, provided that the likely nonlinearity dependencies within the dataset are precisely learned by the similarity function.

Visual similarity learning is closely related to distance metric learning. Traditionally, distance metric learning algorithms were based on linear metrics such as the Mahalanobis distance. However, if the visual data presents any nonlinear interdependency, better results are expected when using nonlinear approaches. According to some studies Tan et al. (2006), standard metric axioms are not valid for human perception of visual similarity and hence, visual similarity functions should not necessarily satisfy distance metric conditions. Deep learning-based similarity learning methods are mostly focused on learning an optimal mapping from pixels to a linear space in which Euclidean distance can be applied. Instead, we propose a simple approach based on neural networks to learn a non-metric similarity score in the feature space.

Figure 1: System overview. The feature extraction block computes visual representations of images whereas the visual similarity block estimates a similarity score using a neural network.

Figure 2: Siamese architectures (**left**) map pixels into high-quality vector representations. Our similarity network (**right**) learns a similarity function on top of the vector representations.

Figure 1 shows an overview of the proposed approach. By training a deep learning model, we can estimate a visual similarity function that outperforms methods based on standard metric computations. One convolutional neural network extracts image representations from input images, while a second neural network computes the visual similarity score. The visual similarity neural network is trained using both pairs of similar and dissimilar images in three stages. The output score of the similarity network can be directly applied as a similarity estimation to rank images in an image retrieval task. Experimental results on standard datasets show that our network is able to discriminate when a pair of images is similar or dissimilar and improve standard metrics score on top of that.

2   RELATED WORK

Content-Based Image Retrieval. Content-based image retrieval searches for images by considering their visual content. Given a query image, pictures in a collection are ranked according to their visual similarity with respect to the query. Early methods represent the visual content of images by a set of hand-crafted features, such as SIFT Lowe (2004). As a single image may contain hundreds of these features, aggregation techniques like bag-of-words (BOW) Sivic et al. (2003), Fisher Vectors Perronnin et al. (2010) or VLAD Jégou et al. (2010) encode local descriptors into a compact vector, thereby improving computational efficiency and scalability. Recently, because of the latest advancements on deep learning, features obtained from convolutional neural networks (CNN) have rapidly become the new state-of-the-art in image retrieval.

Deep Learning for Image Retrieval. Deep image retrieval extracts activations from CNNs as image representations. At first, some methods Babenko et al. (2014); Sharif Razavian et al. (2014); Wan et al. (2014); Liu et al. (2015) proposed to use representations from one of the last fully connected layers of networks pre-trained on the classification ImageNet dataset Russakovsky et al. (2015). When deeper networks such as GoogLeNet Szegedy et al. (2015) and VGG Simonyan & Zisserman (2014) appeared, some authors Babenko & Lempitsky (2015); Yue-Hei Ng et al. (2015); Sharif Razavian et al. (2014); Xie et al. (2015) showed that mid-layer representations obtained from the convolutional layers performed better in the retrieval task. Since then, there have been several attempts to aggregate these high-dimensional convolutional representations into a compact vector. For example, Gong et al. (2014); Yue-Hei Ng et al. (2015) compacted deep features by using VLAD, Mohedano et al. (2016) encoded the neural codes into an histogram of words, Babenko & Lempitsky (2015); Kalantidis et al. (2016) applied sum-pooling to obtain a compact representation and Razavian et al. (2016); Tolias et al. (2016) aggregated deep features by max-pooling them into a new vector. A different approach is to train the network to directly learn compact binary codes end-to-end Erin Liong et al. (2015); Lin et al. (2015). Finally, some authors have shown that fine-tunning the networks with similar data to the target task increases the performance significantly Babenko et al. (2014); Gordo et al. (2016); Radenović et al. (2016); Salvador et al. (2016).

All of these methods are focused on finding high quality features to represent visual content efficiently and visual similarity is computed by simply applying a standard metric distance. General metrics, such as Euclidean distance or cosine similarity, however, might be failing to consider the inner data structure of these visual representations. Learning a similarity function directly from data may help to capture the human perception of visual similarity in a better way.

Similarity Learning. Some of the most popular similarity learning work, such as OASIS Chechik et al. (2010) and MLR McFee & Lanckriet (2010), are based on linear metric learning by optimizing

the weights of a linear transformation matrix. Although linear methods are easier to optimize and less prone to overfitting, nonlinear algorithms are expected to achieve higher accuracy modeling the possible nonlinearities of data. Nonlinear similarity learning based on deep learning has been recently applied to many different visual contexts. In low-level image matching, CNNs have been trained to match pairs of patches for stereo matching Zagoruyko & Komodakis (2015); Luo et al. (2016) and optical flow Fischer et al. (2015); Thewlis et al. (2016). In high-level image matching, deep learning techniques have been proposed to learn low-dimensional embedding spaces in face verification Chopra et al. (2005), retrieval Wu et al. (2013); Wang et al. (2014), classification Hoffer & Ailon (2015); Qian et al. (2015); Oh Song et al. (2016) and product search Bell & Bala (2015), either by using siamese Chopra et al. (2005) or triplet Wang et al. (2014) architectures.

In general, these methods rely on learning a mapping from image pixels to a low dimensional target space to compute the final similarity decision by using a standard metric. They are designed to find the best projection in which a linear distance can be successfully applied. Instead of projecting the visual data into some linear space, that may or may not exist, our approach seeks to learn the non-metric visual similarity score itself. Similarly, Li et al. (2014) and Han et al. (2015) used a CNN to decide whether or not two input images are a match, applied to pedestrian reindentification and patch matching, respectively. In these methods, the networks are trained as a binary classification problem (i.e. same or different pedestrian/patch), whereas in an image retrieval ranking problem, a regression score is required. Inspired by the results of Wan et al. (2014), which showed that combining deep features with similarity learning techniques can be very beneficial for the performance of image retrieval systems, we propose to train a deep learning algorithm to learn non-metric similarities for image retrieval and improve results in top of high quality image representation methods.

3 LEARNING VISUAL SIMILARITY

3.1 DEFINITION

Visual similarity is the task that measures how related two images are by using their visual content. Given n samples in the training image collection I, for each image $I_i \in I$ with $i \in [1, n]$, a global d-dimensional representation $x_i \in \mathbb{R}^d$ is obtained as $x_i = f(I_i, w_f)$, where f is the function that maps images into global features and w_f is the set of parameters of f. We define $s_{i,j}$ as the similarity score which measures how alike two images I_i and I_j are. The higher $s_{i,j}$ is, the more similar I_i and I_j are. The aim is to learn a visual similarity function S that computes the similarity score from global image representations as:

$$s_{i,j} = S(x_i, x_j) = g(f(I_i, w_f), f(I_j, w_f), w_g)$$
$$s.t. \quad s_{i,j} > s_{i,k} \rightarrow I_i, I_j \text{ are more similar than } I_i, I_k \tag{1}$$

where g is a nonlinear function and w_g is the set of parameters to optimize.

Note that g does not have to be a metric in order to be a similarity function and thus, it is not required to satisfy the rigid constraints of metric axioms, i.e. non-negativity, identity of indiscernibles, symmetry and triangle inequality. Some non-metric similarity works such as Tan et al. (2006) suggest that these restrictions are not compatible with human perception. As an example, they showed that although a centaur might be visually similar to both a person and a horse, the person and the horse are not similar to each other. A possible explanation for this phenomenon is that when comparing two images, human beings may pay more attention to similarities and thus, similar portions of the images may be more discriminative than dissimilar parts. To overcome the issues associated with applying strong rigid constraints to visual similarity, we propose to learn the non-metric similarity function g using a neural network approach.

3.2 IMAGE REPRESENTATION

Here we describe the image representation method, f, we use. As this work aims to learn a non-metric similarity estimation from visual data, our efforts are not focused on improving existing image representation methods, but to learn how to compare them. Without loss of generality, we use the RMAC descriptor proposed in Tolias et al. (2016) as image representation, although any other image representation method can be considered as well.

Table 1: Network architectures. Fully connected layers (FC-{filters}) are always followed by a ReLU layer except for the last one. Training: 22.5 million pairs. Validation: 7.5 million pairs.

	Config	Params	Training Data		Validation Data	
			MSE	ρ	MSE	ρ
A	FC-1024, FC-1024, FC-1	2.1M	0.00021	0.946	0.00035	0.909
B	FC-4096, FC-4096, FC-1	21M	0.00008	0.978	0.00019	0.965
C	FC-8192, FC-8192, FC-1	76M	**0.00007**	**0.982**	**0.00012**	**0.974**
D	FC-4096, FC-4096, FC-4096, FC-1	38M	0.00009	0.978	0.00019	0.964

RMAC is a deep global image representation obtained from the last convolutional layer of a pre-trained CNN on ImageNet classification task Russakovsky et al. (2015). When an image is fed into the network, the last convolutional layer outputs a $W \times H \times K$ response, where K is the number of filters and W and H are the spatial width and height of the output, respectively, that depend on the network architecture as well as on the size of the input image. The response of the k-th filter of the last convolutional layer can be represented by Ω_k, a 2D tensor of size $W \times H$. If $\Omega_k(p)$ is the response at a particular position p, and R is a spatial region within the feature map, the regional feature vector f_R is defined as:

$$f_R = [f_{R,1} \ldots f_{R,k} \ldots f_{R,K}]^\top \tag{2}$$

where $f_{R,k} = \max_{p \in R} \Omega_k(p)$. Thus, f_R consists of the maximum activation of each filter inside the region R. Several regional features are extracted at different multi-scale overlapping regions. Each of these regional vectors is independently post-processed with ℓ2-normalization, PCA-whitening and ℓ2-normalization, as suggested in Jégou & Chum (2012). Finally, regional vectors are summed and ℓ2-normalized once again to obtain the final compact vector. The size of the final vector is K, which is independent of the size of the input image, its aspect ratio or the number of regions used.

3.3 SIMILARITY NETWORK

To compare two images and obtain a visual similarity score we learn the similarity function g by training a deep learning architecture. Given two input images I_i and I_j, we first extract their representations x_i and x_j, respectively, as explained in Section 3.2. The two K-dimensional global vectors are concatenated and fed into the similarity network, as shown in Figure 1. This process is different to the standard siamese architecture Chopra et al. (2005) because the latest maps images into vector representations and updates the shared weights according to the learning protocol and our approach trains and updates the similarity network on top of high-quality vector representations. Moreover, in the similarity network architecture, weights in the image representation block are not necessarily shared. Figure 2 shows the difference between both approaches.

The similarity network is composed by a set of fully connected layers, each one of them followed by a non-linear function, such as ReLU Krizhevsky et al. (2012). The input of the network is fixed to be of $1 \times K \times 2$ size, so the size of the first layer is $1 \times K \times 2 \times Ch$, where Ch is the number of channels. We consider hidden layers of size $1 \times Ch \times 2 \times Ch$. Finally, the output layer is of size $1 \times Ch \times 2 \times 1$ and it is not followed by a ReLU layer, as the output similarity score is expected to cover a full range of values, both positive and negative. The regression loss function, L, penalizes when the predicted score of the network is far away from an annotated similarity score, such as:

$$L(I_i, I_j) = |s_{i,j} - y_{i,j}| = |g(x_i, x_j, w_g) - y_{i,j}| \tag{3}$$

where $s_{i,j}$ is the network output and $y_{i,j}$ is the annotated score. Four configurations A-D with different number of filters Ch and number of hidden layers are proposed and tested during our experiments, as shown in Table 1.

3.4 TRAINING SIMILARITY

The visual similarity network is trained in three stages. In each stage the weights are initialized by the trained weights of the previous stage while the learned task gets progressively more difficult.

STAGE 1: STANDARD METRIC

In Stage 1, the network learns a standard similarity function based on the cosine similarity. We generate random pairs of vectors, x_i and x_j, and we assign the cosine similarity between them as

Figure 3: Misclassified pairs. (Upper) Lower row: (dissimilar) similar images in which the network score is (lower) higher than the cosine similarity.

Figure 4: mAP versus Δ. Rigid lines are Deep-SimH scores, dashed lines are cosine similarity scores.

the score label $y_{i,j}$:

$$y_{i,j} = \frac{x_i \cdot x_j}{\|x_i\|\|x_j\|} \tag{4}$$

In order to train the model in the full range of possible values, pairs are produced so that the cosine similarity is uniformly distributed within the training set.

STAGE 2: VISUAL SIMILARITY

In Stage 2, the basic similarity network learns to increase the similarity score when given two matching images and to decrease it when a pair of images is not a match. The weights in this training stage are initialized by the weights obtained during Stage 1. We now use pairs of image representation vectors x_i and x_j, randomly chosen from our training image dataset. The score label is set to:

$$y_{i,j} = \begin{cases} \frac{x_i \cdot x_j}{\|x_i\|\|x_j\|} + \Delta, & \text{if } x_i \text{ and } x_j \text{ are similar} \\ \frac{x_i \cdot x_j}{\|x_i\|\|x_j\|} - \Delta, & \text{otherwise} \end{cases} \tag{5}$$

where Δ is the margin parameter. Thus, the model learns to discriminate when a pair of images are similar (dissimilar) and assigns it a higher (lower) value than the standard score.

In this stage, the model learns how to compute a similarity score from examples of images that are known to be matching or non-matching. Therefore a relevant dataset to the final retrieval task should be used. Similarity between pairs might be decided using different techniques, such as image classes, score based on local features or manual labeling, among others. Without loss of generality, we consider two images as similar when they belong to the same class and as dissimilar when they belong to different classes.

STAGE 3: HARD EXAMPLES

In the Stage 3, the similarity network is refined by training it specifically by using *difficult pairs* of images. Previous works Gordo et al. (2016); Radenović et al. (2016) have shown that fine-tunning neural networks using difficult samples is very helpful in terms of performance. This is easy to understand: if the network is only trained by using *easy pairs* (e.g. a car and a dog), it will not be able to discriminate between *difficult pairs* (e.g. a car and a van). To choose the set of hard pairs we compute the scores of a random set of image pairs by using the network trained in Stage 2. Those pairs in which the network output is worse than the cosine similarity measure are selected as difficult pairs for retraining[1]. Examples of difficult image pairs can be seen in Figure 3.

---

[1] A worse score is a score that is lower in the case of a match and higher in the case of a non-match.

4 EXPERIMENTS

4.1 TESTING DATASETS

Our approach is evaluated on the standard image retrieval datasets described below.

Oxford5k Philbin et al. (2007): a dataset that consists of 5,062 images of 11 different Oxford landmarks. The query set contains 55 annotated images, 5 per landmark.

Paris6k Philbin et al. (2008): a datasets that consists of 6,412 images of 11 different Paris landmarks. The query set contains 55 annotated images, 5 per landmark.

Land5k: a validation subset of the Landmarks database Babenko et al. (2014). It consists of the 4,915 validation images from 529 classes. A random selection of 45 images is used as queries.

Oxford105k, **Paris106k**: the large-scale versions of Oxford5k and Paris6k, respectively. They include 100,000 distractor images from Flickr Philbin et al. (2007).

In both the Oxford5k and the Paris6k collections query images are cropped according to the region of interest provided by the authors of the datasets. Evaluation is performed by computing the mean Average Precision (mAP), using the provided ground truth and algorithms. For Landmarks5k we consider an image to be relevant to the query when it belongs to the same class.

4.2 TRAINING DATASETS

For the purposes of this work, having a training dataset as similar as possible to the final similarity task is essential. We create several versions of the training dataset to evaluate the effect of using different samples in the training process.

Landmarks Gordo et al. (2016): an automatically cleaned subset of the full Landmarks Babenko et al. (2014) dataset which officially contains about 49,000 images from 586 landmarks. However, due to broken URLs, we could only download 33,119 training images and 4,915 validation images. This dataset does not contain images from classes that overlap with Oxford5k and Paris6k datasets as they were manually removed.

Landmarks-extra500: the Landmarks collection plus 250 random images from each of the Oxford5k and Paris6k datasets. In total, it contains 33,619 training images.

Landmarks-extra: the Landmarks collection in addition to about 500 images from Oxford5k and 1,700 images from Paris6k classes. In total, it contains 35,342 training images belonging to 605 different landmarks. Note that query images are not added in any case and they remain unseen by the system.

4.3 EXPERIMENTAL DETAILS

Image Representation. To compute RMAC representations we use the VGG16 network Simonyan & Zisserman (2014), which has been previously pre-trained on the ImageNet dataset Russakovsky et al. (2015). Unless otherwise stated, we use the default values proposed in Tolias et al. (2016) to obtain 512-dimensional RMAC vectors. VGG16 network is used off-the-shelf without any retraining or fine-tunning performed on top of it. Experimental results have shown that RMAC representations are very sensitive to the PCA matrices used in the post-processing step. As we are keeping query images unseen by the system and not using them in the PCA matrices computation as in Tolias et al. (2016), our results are slightly different to theirs.

Visual Similarity Learning. Similarity learning is trained using almost a million of random pairs, of which half of the pairs are visual matches and the other half are non-matches. PCA whitening is done using Paris5k images. As RMAC representation performs better in high resolution images, we re-scale all the images up to 1024 pixels, keeping the original aspect ratio of the pictures. For the similarity network, four different configurations A-D (Table 1) are explored during our experiments. The network is optimized using backpropagation and stochastic gradient descent. We use a learning rate of 0.001, a batch size of 100, a weight decay of 0.0005 and momentum of 0.9.

Table 2: mAP when using different training configurations and Δ values.

	Landmarks			Landmarks-extra500			Landmarks-extra		
	Ox5k	Pa6k	La5k	Ox5k	Pa6k	La5k	Ox5k	Pa6k	La5k
Cosine	**0.665**	**0.638**	0.564	0.665	0.638	0.564	0.665	0.638	0.564
DeepCosine	0.638	0.596	0.549	0.638	0.596	0.549	0.638	0.596	0.549
OASIS	0.514	0.385	0.578	0.570	0.651	0.589	0.619	0.853	0.579
DeepSim (0.2)	0.658	0.460	0.669	0.717	0.654	0.671	0.718	0.757	0.668
DeepSimH (0.2)	0.655	0.503	0.697	**0.719**	0.677	0.693	0.786	0.860	0.662
DeepSimH (0.4)	0.637	0.504	0.737	0.703	0.701	0.745	0.794	0.878	0.706
DeepSimH (0.6)	0.613	0.514	0.776	0.703	**0.716**	0.776	0.789	0.885	0.735
DeepSimH (0.8)	0.600	0.511	**0.783**	0.685	0.710	**0.803**	**0.808**	**0.891**	**0.758**

Computational cost. Standard metrics are relatively fast and computationally cheap. Our visual similarity network involves the use of millions of parameters that inevitable increase the computational cost. However, it is still feasible to compute in a reasonable amount of time. In our experiments, training time is about 5 hours in a GeForce GTX 1080 GPU and testing time for a pair of images is 1.25 ms on average (0.35 ms when using cosine similarity).

5 RESULTS

5.1 ARCHITECTURE DISCUSSION

Four different configurations A-D for the similarity neural network are proposed. We compare the performance of each one during Stage 1, when the network is trained with the standard cosine similarity measurement. If s_l is the network score and y_l is the cosine similarity of the l-th pair with $l = 1..L$, we evaluate each network by computing the mean squared error, MSE, and the correlation coefficient, ρ, as:

$$MSE = \frac{1}{L}\sum_{l=1}^{L}(s_l - y_l)^2 \qquad\qquad \rho = \frac{1}{L-1}\sum_{l=1}^{L}\frac{s_l - \mu_s}{\sigma_s}\frac{y_l - \mu_y}{\sigma_y} \qquad (6)$$

where μ_s and σ_s are the mean and standard deviation of the vector of network scores s, and μ_y and σ_y are the mean and standard deviation of the vectors of cosine similarities y.

Results are shown in Table 1. Unsurprisingly, the configuration with bigger number of parameters, C, achieves the best MSE and ρ results, both in training and validation sets. However, the performance of networks B and D is very close to the performance of network C. As network B requires only 21 million parameters and network C requires 76 million parameters, we keep configuration B as our default architecture for the rest of the experiments.

5.2 EVALUATION OF THE SIMILARITY NETWORK

To evaluate our similarity network, we compute the mAP at each stage of the training process (Section 4.2). Results when using different training datasets can be found in Table 2. Cosine similarity is computed as a baseline. We denote as DeepCosine the results obtained after the first stage, when the network is trained to mimic cosine similarity. Naturally, DeepCosine performs worse than the cosine similarity, as it is an estimation of the cosine metric. DeepSim refers to the results obtained after the second stage, when the network is fine-tunned to learn visual similarity with random pairs of images. DeepSimH are the results after the last stage, when the network is trained by using both random and hard pairs of images. We compare our approach against the standard similarity learning algorithm OASIS Chechik et al. (2010).

Our similarity networks outperform OASIS in all the testing datasets. Moreover when using Landmarks-clean-extra as training dataset, results are boosted with respect to the standard metric, achieving improvements ranging from 20% (Oxford5k) to 40% (Pairs6k). When using a small subset of images from Oxford5k and Paris6k classes, i.e. Landmarks-clean-extra-500 dataset, our similarity networks also improve mAP with respect to the cosine similarity in the three testing datasets. This indicates that visual similarity can be learnt even when using a reduced subset of the target image domain. However, visual similarity does not transfer well across domains when no images

Table 3: mAP results for different state-of-the-art methods.

	Method	Similarity	Ox5k	Ox105k	Pa6k	Pa106k
Off-the-shelf	Babenko et al. (2014)	L2	0.435	0.392	-	-
	Sharif Razavian et al. (2014)	Averaged L2	0.322	-	0.495	-
	Wan et al. (2014)	OASIS	0.466	-	0.867	-
	Babenko & Lempitsky (2015)	Cosine	0.657	0.642	-	-
	Liu et al. (2015)	Inverted Index	-	-	0.812	-
	Yue-Hei Ng et al. (2015)	L2	0.593	-	0.59	-
	Kalantidis et al. (2016)	L2	0.708	0.653	0.797	0.722
	Mohedano et al. (2016)	Cosine	0.739	0.593	0.82	0.648
	Salvador et al. (2016)	Cosine	0.588	-	0.656	-
	Tolias et al. (2016)	Cosine	0.669	0.616	0.83	0.757
	Ours ($\Delta = 0.8$)	DeepSimH	**0.808**	**0.772**	**0.891**	**0.818**
Fine-tunning	Babenko et al. (2014)	L2	0.557	0.522	-	-
	Gordo et al. (2016)	Cosine	0.831	0.786	0.871	0.797
	Wan et al. (2014)	OASIS	0.783	-	**0.947**	-
	Radenović et al. (2016)	Cosine	0.77	0.692	0.838	0.764
	Salvador et al. (2016)	Cosine	0.71	-	0.798	-
	Ours ($\Delta = 0.8$)	DeepSimH	**0.882**	**0.821**	0.882	**0.829**

of the target domain are used during training. For example, when training with Landmarks-clean dataset, the visual similarity estimated using either OASIS and our DeepSim and DeepSimH only improves over cosine similarity in the Land5k testing scenario, as both training and testing images belongs to the same domain of image classes.

These results suggests that our network is able to learn whether two images are similar or not and improve the cosine similarity metric accordingly. Figure 4 shows how the mAP is affected when using DeepSimH network and choosing different values of Δ. Except when $\Delta = 0$ (i.e. visual similarity is not learned), mAP is always improved with respect to the standard cosine similarity metric.

5.3 COMPARISON WITH THE STATE OF THE ART

Finally, we compare our method against several state-of-the-art techniques (Table 3). As standard practice, works are split into two main groups: off-the-shelf and fine-tunning approaches. Off-the-shelf are techniques that extract visual representations by using CNNs trained on ImageNet dataset Russakovsky et al. (2015) without modifying the network. On the other hand, fine-tunning methods retrain the network to compute more accurate visual representation. For a fair comparison, we do not consider methods that apply query expansion or image re-ranking. When using off-the-shelf RMAC features, our DeepSimH approach outperforms previous methods in every dataset. To compare against fine-tunned methods, we compute RMAC vectors using the fine-tunned version of VGG16 proposed in Radenović et al. (2016) and training our DeepSimH exactly in the same way as in the off-the-shelf version. Accuracy is significantly improved when using our similarity network instead of the analogous cosine similarity method Radenović et al. (2016). DeepSimH achieves the best mAP precision in three out of four datasets, and comes second in the fourth.

6 CONCLUSIONS

We have presented a method for learning visual similarity directly from visual data. Instead of using a rigid metric distance, such as the standard cosine similarity, we propose to train a neural network model to learn a similarity estimation between a pair of visual representations previously extracted from input images. Our method outperforms state-of-the-art approaches based on rigid distances in standard image retrieval collection of images and experimental results showed that learning a non-metric visual similarity function is beneficial in image retrieval tasks provided that a small subset of images of the same domain are available during training. We end with some interesting open questions. Firstly, as the entirety of our similarity computation is now based on a network architecture, this opens the possibility of true end-to-end training for content based image retrieval. Another question concerns efficient computation of exact or approximate K-nearest neighbours based on the learned network similarity functions. These questions are the subject of planned future work.

REFERENCES

Artem Babenko and Victor Lempitsky. Aggregating local deep features for image retrieval. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 1269–1277, 2015.

Artem Babenko, Anton Slesarev, Alexandr Chigorin, and Victor Lempitsky. Neural codes for image retrieval. In *Proceedings of the IEEE European Conference on Computer Vision*, pp. 584–599, 2014.

Sean Bell and Kavita Bala. Learning visual similarity for product design with convolutional neural networks. *ACM Transactions on Graphics (TOG)*, 34(4):98, 2015.

Gal Chechik, Varun Sharma, Uri Shalit, and Samy Bengio. Large scale online learning of image similarity through ranking. *Journal of Machine Learning Research*, 11(Mar):1109–1135, 2010.

Sumit Chopra, Raia Hadsell, and Yann LeCun. Learning a similarity metric discriminatively, with application to face verification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 539–546, 2005.

Venice Erin Liong, Jiwen Lu, Gang Wang, Pierre Moulin, and Jie Zhou. Deep hashing for compact binary codes learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2475–2483, 2015.

Philipp Fischer, Alexey Dosovitskiy, Eddy Ilg, Philip Häusser, Caner Hazırbaş, Vladimir Golkov, Patrick van der Smagt, Daniel Cremers, and Thomas Brox. Flownet: Learning optical flow with convolutional networks. In *Proceedings of the IEEE International Conference on Computer Vision*, 2015.

Yunchao Gong, Liwei Wang, Ruiqi Guo, and Svetlana Lazebnik. Multi-scale orderless pooling of deep convolutional activation features. In *Proceedings of the IEEE European Conference on Computer Vision*, pp. 392–407, 2014.

Albert Gordo, Jon Almazán, Jerome Revaud, and Diane Larlus. Deep image retrieval: Learning global representations for image search. In *Proceedings of the IEEE European Conference on Computer Vision*, pp. 241–257, 2016.

Xufeng Han, Thomas Leung, Yangqing Jia, Rahul Sukthankar, and Alexander C Berg. Matchnet: Unifying feature and metric learning for patch-based matching. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3279–3286, 2015.

Elad Hoffer and Nir Ailon. Deep metric learning using triplet network. In *International Workshop on Similarity-Based Pattern Recognition*, pp. 84–92, 2015.

Hervé Jégou and Ondřej Chum. Negative evidences and co-occurences in image retrieval: The benefit of pca and whitening. In *Computer Vision–ECCV 2012*, pp. 774–787. Springer, 2012.

Hervé Jégou, Matthijs Douze, Cordelia Schmid, and Patrick Pérez. Aggregating local descriptors into a compact image representation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3304–3311, 2010.

Yannis Kalantidis, Clayton Mellina, and Simon Osindero. Cross-dimensional weighting for aggregated deep convolutional features. In *Proceedings of the IEEE European Conference on Computer Vision*, pp. 685–701, 2016.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pp. 1097–1105, 2012.

Wei Li, Rui Zhao, Tong Xiao, and Xiaogang Wang. Deepreid: Deep filter pairing neural network for person re-identification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 152–159, 2014.

Kevin Lin, Huei-Fang Yang, Jen-Hao Hsiao, and Chu-Song Chen. Deep learning of binary hash codes for fast image retrieval. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pp. 27–35, 2015.

Yu Liu, Yanming Guo, Song Wu, and Michael S Lew. Deepindex for accurate and efficient image retrieval. In *Proceedings of the 5th ACM on International Conference on Multimedia Retrieval*, pp. 43–50. ACM, 2015.

David G Lowe. Distinctive image features from scale-invariant keypoints. *International journal of computer vision*, 60(2):91–110, 2004.

Wenjie Luo, Alexander G Schwing, and Raquel Urtasun. Efficient deep learning for stereo matching. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 5695–5703, 2016.

Brian McFee and Gert R Lanckriet. Metric learning to rank. In *Proceedings of the 27th International Conference on Machine Learning (ICML-10)*, pp. 775–782, 2010.

Eva Mohedano, Kevin McGuinness, Noel E O'Connor, Amaia Salvador, Ferran Marqués, and Xavier Giró-i Nieto. Bags of local convolutional features for scalable instance search. In *Proceedings of the 2016 ACM on International Conference on Multimedia Retrieval*, pp. 327–331. ACM, 2016.

Hyun Oh Song, Yu Xiang, Stefanie Jegelka, and Silvio Savarese. Deep metric learning via lifted structured feature embedding. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4004–4012, 2016.

Florent Perronnin, Yan Liu, Jorge Sánchez, and Hervé Poirier. Large-scale image retrieval with compressed fisher vectors. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3384–3391, 2010.

J. Philbin, O. Chum, M. Isard, J. Sivic, and A. Zisserman. Object retrieval with large vocabularies and fast spatial matching. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2007.

J. Philbin, O. Chum, M. Isard, J. Sivic, and A. Zisserman. Lost in quantization: Improving particular object retrieval in large scale image databases. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2008.

Qi Qian, Rong Jin, Shenghuo Zhu, and Yuanqing Lin. Fine-grained visual categorization via multi-stage metric learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3716–3724, 2015.

Filip Radenović, Giorgos Tolias, and Ondřej Chum. Cnn image retrieval learns from bow: Unsupervised fine-tuning with hard examples. In *Proceedings of the IEEE European Conference on Computer Vision*, pp. 3–20, 2016.

Ali Sharif Razavian, Josephine Sullivan, Stefan Carlsson, and Atsuto Maki. Visual instance retrieval with deep convolutional networks. *ITE Transactions on Media Technology and Applications*, 4 (3):251–258, 2016.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision (IJCV)*, 115(3):211–252, 2015.

Amaia Salvador, Xavier Giró-i Nieto, Ferran Marqués, and Shin'ichi Satoh. Faster r-cnn features for instance search. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pp. 9–16, 2016.

Ali Sharif Razavian, Hossein Azizpour, Josephine Sullivan, and Stefan Carlsson. Cnn features off-the-shelf: an astounding baseline for recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pp. 806–813, 2014.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *CoRR*, 2014.

Josef Sivic, Andrew Zisserman, et al. Video google: A text retrieval approach to object matching in videos. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 1470–1477, 2003.

Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, and Andrew Rabinovich. Going deeper with convolutions. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1–9, 2015.

Xiaoyang Tan, Songcan Chen, Jun Li, and Zhi-Hua Zhou. Learning non-metric partial similarity based on maximal margin criterion. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, volume 1, pp. 168–145, 2006.

J. Thewlis, S. Zheng, P. Torr, and A. Vedaldi. Fully-trainable deep matching. In *Proceedings of the British Machine Vision Conference*, 2016.

Giorgos Tolias, Ronan Sicre, and Hervé Jégou. Particular object retrieval with integral max-pooling of cnn activations. In *Proceedings of the International Conference on Learning Representations*, 2016.

Ji Wan, Dayong Wang, Steven Chu Hong Hoi, Pengcheng Wu, Jianke Zhu, Yongdong Zhang, and Jintao Li. Deep learning for content-based image retrieval: A comprehensive study. In *Proceedings of the 22nd ACM international conference on Multimedia*, pp. 157–166. ACM, 2014.

Jiang Wang, Yang Song, Thomas Leung, Chuck Rosenberg, Jingbin Wang, James Philbin, Bo Chen, and Ying Wu. Learning fine-grained image similarity with deep ranking. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1386–1393, 2014.

Pengcheng Wu, Steven CH Hoi, Hao Xia, Peilin Zhao, Dayong Wang, and Chunyan Miao. Online multimodal deep similarity learning with application to image retrieval. In *Proceedings of the 21st ACM international conference on Multimedia*, pp. 153–162. ACM, 2013.

Lingxi Xie, Richang Hong, Bo Zhang, and Qi Tian. Image classification and retrieval are one. In *Proceedings of the 5th ACM on International Conference on Multimedia Retrieval*, pp. 3–10. ACM, 2015.

Joe Yue-Hei Ng, Fan Yang, and Larry S Davis. Exploiting local features from deep networks for image retrieval. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pp. 53–61, 2015.

Sergey Zagoruyko and Nikos Komodakis. Learning to compare image patches via convolutional neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4353–4361, 2015.