Overcoming Reasoning Shortcuts in Neurosymbolic Learning via Efficient Generative Proxies

Abstract

Symbol grounding, the task of linking high-dimensional sensory inputs to symbolic representations in neurosymbolic AI (NeSy), often suffers from *reasoning shortcuts*, where inputs are mapped to unintended concepts due to limited supervision. Reconstruction-based training can help mitigate these ambiguities, but its effectiveness depends strongly on the quality and capacity of the reconstruction model. In this work, we propose a new grounding framework, Efficient Generative Proxies (EGP), that cleanly integrates reconstruction-based training into a generative modeling perspective. EGP subsumes several existing grounding approaches as special cases. We further argue that the role of reconstruction should be to capture the underlying structure of the data rather than to faithfully reconstruct inputs. Accordingly, we design a reconstruction term that leverages the principle that similar inputs should correspond to similar concept labels, thereby substantially reducing grounding ambiguity. We also develop extensions that incorporate additional inductive biases through this reconstruction term, improving robustness in more complex tasks. We evaluate our approach on tasks susceptible to reasoning shortcuts from the *RSbench* benchmark, as well as on the multi-concept *ObjectMath* dataset, integrating EGP into state-of-the-art neurosymbolic learning frameworks. Experimental results demonstrate that EGP significantly improves grounding accuracy and effectively mitigates reasoning shortcuts across diverse settings.

1 Introduction

Neurosymbolic AI (NeSy) aims to integrate the adaptability of neural networks with the reasoning capabilities of symbolic logic. A common pattern in these systems is the use of neural models to ground symbolic reasoners on sub-symbolic inputs, such as pixels. This combination promises to improve interpretability and robustness across domains ranging from robotics to language-based reasoning (Yang et al., 2025; Bhuyan et al., 2024).

Despite these benefits, recent studies have revealed that NeSy grounding models are prone to *reasoning shortcuts* (Marconato et al., 2023; 2025), where the model learns unintended mappings that satisfy the symbolic constraints rather than capturing the correct semantics. For example, in a traffic scenario, a model might incorrectly identify a pedestrian as a red light because both imply the same "stop" action, thereby satisfying the logical knowledge while failing to learn the true visual concepts. Fundamentally, these shortcuts arise due to insufficient supervision, as the provided symbolic constraints often do not allow for identifying the unique, correct grounding among multiple valid solutions.

This failure mode is intrinsic to the standard discriminative training objective used in neurosymbolic learning. Typically, these methods maximize the likelihood of symbols that satisfy the constraint given the inputs. When the supervision signal is ambiguous, letting multiple configurations of symbols satisfy the symbolic constraints, this objective only forces the model to assign probability mass to any valid assignment, regardless of its semantic correctness. Consequently, grounding models often converge to distributions that maximize this likelihood but are incorrect, such as collapsing inputs of different classes into the same symbol. These methods fail because they do not fully consider the intrinsic structure of the input data. We refer to these

methods as lacking *perceptual grounding*, which ensures that the classifier's predictions are consistent with the structure of the input space. While adding a reconstruction-based objective can theoretically resolve these ambiguities by enforcing consistency between predicted symbols and the input, such methods have been shown unreliable in the neurosymbolic setting as reconstructing low-level details can obfuscate the signal relevant to the reasoning problem.

In this work, we introduce Efficient Generative Proxies (EGP), a framework aiming to overcome reasoning shortcuts by considering neurosymbolic learning from a generative modeling perspective but without the burden of full generation. EGP enables models to exploit the structure of the input data to resolve ambiguity. Rather than reconstructing inputs pixel-by-pixel, EGP utilizes a lightweight approximation of the generative likelihood to enforce that similar inputs yield similar symbols and distinct inputs yield distinct symbols. We essentially use the reconstruction term as a handle to provide various inductive biases to the grounding model. We demonstrate that this approach significantly improves the grounding accuracy of state-of-the-art methods on *RSbench* benchmark (Bortolotti et al., 2024) tasks and the multi-concept *ObjectMath* dataset. We also include extensive experiments to validate optimization strategies for EGP and further explore its ability to resolve reasoning shortcuts in different tasks.

We summarize our contributions as follows: 1) Using a generative modeling perspective, we derive a framework for neurosymbolic grounding that encompasses current state-of-the-art methods as well as some reasoning shortcut mitigation strategies in one unified objective. 2) We use our framework to provide perceptual grounding to neurosymbolic learners without any additional supervision. 3) We demonstrate how to use EGP in multi-concept domains and how to inject additional inductive biases to grounding models without observing labeled samples. 4) We conduct extensive evaluations and show that EGP is highly effective at improving grounding accuracy across multiple methods and benchmarks.

2 Related Work

Neurosymbolic AI (NeSy) aims to integrate the adaptability of neural networks with the reasoning capabilities of symbolic logic. This combination promises to improve interpretability (Tziafas & Kasaei, 2022; Padalkar et al., 2023; Zhang & Sheng, 2024) and robustness (Michel-Delétie & Sarker, 2024; Goel et al., 2024a;b; 2022; Mao et al., 2025) in robotics (Capitanelli & Mastrogiovanni, 2024; Wang et al., 2024a), language-based reasoning (Quan et al., 2025; Fang et al., 2024; Yang et al., 2025; Li et al., 2020) and various application domains such as life sciences, biomedical applications and IoT (Fitas, 2025; Hoehndorf et al., 2025). A common pattern in neurosymbolic systems is using neural models for grounding symbolic reasoners on sub-symbolic inputs. Prominent frameworks include DeepProbLog (Manhaeve et al., 2018), which combines probabilistic logic programming with deep learning, SATnet (Wang et al., 2019), which introduces a satisfiability solver in the learning process, Logic Tensor Networks (Badreddine et al., 2022), which utilize fuzzy logic, ABL (Dai et al., 2019) which utilizes abductive reasoning and Semantic Loss (Xu et al., 2018), which enables neural models to learn to satisfy symbolic constraints on their output.

Grounding models often suffer from reasoning shortcuts (Marconato et al., 2023; 2025), where the model learns unintended mappings that satisfy the symbolic constraints rather than capturing the correct semantics. Reasoning shortcuts arise due to insufficient supervision (Marconato et al., 2023), as the symbolic constraints do not have sufficient information to identify the correct grounding.

In a typical approach to neurosymbolic grounding (Li et al., 2024; Lymperopoulos & Liu, 2025), input-symbol pairs are treated independently, and a classifier is learned to classify the input to the true symbol class. The classifier is trained to predict symbols that satisfy symbolic constraints. These methods need special training techniques to overcome the issue of reasoning shortcuts. Then van Krieken et al. (2025b;a) show that reasoning shortcuts cannot be fully addressed under the independent assumption; they then propose to learn a proper distribution over valid grounding solutions but without identifying a single solution. Marconato et al. (2023) extensively studies strategies based on knowledge, data, or objectives for mitigating reasoning shortcuts. Particularly relevant is their experiment with reconstruction as an objective-based mitigation strategy, which yields no significant performance improvement, despite theoretical support. Another approach based on energy-based models (Sansone & Manhaeve, 2023) addressed some reasoning shortcuts, particularly ones related to degenerate solutions where all classes are collapsed in to one. However, this approach still relies

Figure 1: **Method Overview**. EGP is derived from a generative perspective on neurosymbolic learning that recovers common neurosymbolic approaches within it. The bottom panel shows a typical approach where a classifier using the independence assumption is trained to satisfy the symbolic constraint. In this example, the dataset can be satisfied by assigning the label 1 to samples of class 0 and 2, and the label 0 to samples of class 1, as well as by the correct assignments. The top panel shows the inherent structure of the input data, which we can use to approximate the generative likelihood. The right panel shows how EGP provides perceptual grounding, forcing the classifier to respect the input structure by maximizing an approximate generative likelihood of input pairs, without relying on reconstruction of low-level details. This eliminates the incorrect grounding as samples of class 0 and 2 have to belong to a different class. Through comparisons between samples across equations, EGP eliminates incorrect inferred labels (crossed out), as any model predicting those labels would violate the input structure.

on the semantic loss and is unable to resolve reasoning shortcuts due to merging some clusters. Finally, recent work (Andolfi & Giunchiglia, 2025) resorts to prototype learning, using labeled examples to overcome reasoning shortcuts. While observing ground truth labels can definitively resolve ambiguity and improve performance, it is not always feasible to obtain such data.

The grounding with symbolic constraints can be viewed as a special case of weakly supervised learning (Zhou, 2018). The theory (Wang et al., 2020) indicates that the ambiguity of grounding labels cannot be avoided. Therefore, extra information or an inductive bias is needed to disambiguate these labels (Marconato et al., 2023). In this work, we show that the input reconstruction provides a convenient handle for introducing inductive bias to achieve perceptual grounding.

3 Methods

In a grounding problem, the input $\mathbf{x}$ consists of a set of n input instances, $\mathbf{x} = (\mathbf{x}_1, \ldots, \mathbf{x}_n)$, where each instance $\mathbf{x}_i \in \mathbb{R}^d$ is a high-dimensional observation (e.g., an image). Corresponding to each input instance $\mathbf{x}_i$, there is an unobserved latent symbol $z_i \in \mathcal{Z}$, and let $\mathbf{z} = (z_1, \ldots, z_n)$ denote all symbols. From these symbols, there is an observed label y obtained from symbolic computation, $y = \phi(\mathbf{z})$.

Our *goal* is to learn a grounding model $p_\theta(\mathbf{z}|\mathbf{x})$ from a dataset $\mathcal{D} = \{(\mathbf{x}^{(s)}, y^{(s)})\}_{s=1}^{S}$. Note that the number n of input sequences and the constraint φ may vary with problems in the dataset. We neglect the problem index (s) in our discussion. If y uniquely determines $\mathbf{z}$, then we can recover $\mathbf{z}$, possibly via an expensive computation, and the problem is fundamentally supervised learning. In reality, however, y often cannot

uniquely determine $\mathbf{z}$ but can only exclude illegal configurations of $\mathbf{z}$. In this case, we will aim to infer $\mathbf{z}$ from the joint information in both y and $\mathbf{x}$ and then train the grounding model $p_\theta(\mathbf{z}|\mathbf{x})$.

3.1 Background

The discriminative approach learns $p_\theta(\mathbf{z}|\mathbf{x})$ by maximizing the conditional probability of y given $\mathbf{x}$:

$$\log p_\theta(y|\mathbf{x}) = \max_\theta \log \sum_{\mathbf{z} \in \mathcal{Z}} p(y|\mathbf{z}) p_\theta(\mathbf{z}|\mathbf{x}). \tag{1}$$

Here $p(y|\mathbf{z}) = \mathbb{1}[\varphi(\mathbf{z}) = y]$ takes value 1 if $\mathbf{z}$ is consistent with y or 0 otherwise. This formulation can be considered one type of weakly supervised learning and is equivalent to the semantic loss (Xu et al., 2018) .

Often the maximization problem is addressed by variational inference, where the true posterior $p(\mathbf{z}|y, \mathbf{x})$ is approximated by a variational distribution. For example, Li et al. (2024) and Lymperopoulos & Liu (2025) run MCMC sampling based predicted $\mathbf{z}$-s from $p_\theta(\mathbf{z}|\mathbf{x})$ to collect samples from the posterior. van Krieken et al. (2025a) maximizes the variational lower bound with a diffusion-based generative model.

Some work uses a decomposable grounding model $p_\theta(\mathbf{z}|\mathbf{x}) = \prod_i p_\theta(z_i|\mathbf{x}_i)$, which assumes that the grounding model p_θ is a classifier and classifies each $\mathbf{x}_i$ individually. In this case, p_θ is often forced to learn the distribution of an individual z_i. The distribution is a marginalization of all ambiguous configurations of $\mathbf{z}$, thus its accuracy is often much lower than that trained with true labels.

3.2 Generative perspective of Neurosymbolic Learning.

In our work, we learn a generative model $p(\mathbf{x}, y|\mathbf{z})$ from the data. This setup aligns with the assumed data generation procedure discussed by Marconato et al. (2023). In this approach, the model needs to consider the information about $\mathbf{x}$ when disambiguating $\mathbf{z}$. However, the major difficulty of this approach is that the generation of irrelevant details of $\mathbf{x}$ will obfuscate the inference about $\mathbf{z}$. In this work, we show that we can largely neglect the generation of low-level details and still learn a good grounding model.

Let the generative model be $p(\mathbf{x}, y, \mathbf{z}) = p(\mathbf{x}|\mathbf{z})p(y|\mathbf{z})p(\mathbf{z})$, where we assume that the target concept $\mathbf{z}$ generates observed inputs $\mathbf{x}$ and emits the weak label y. Then the log-likelihood of observed $\mathbf{x}$ and y can be bounded with the ELBO:

$$\log p(y, \mathbf{x}) = \log \sum_{z \in \mathcal{Z}} p(y|\mathbf{z})p(\mathbf{x}|\mathbf{z})p(\mathbf{z}) \geq \mathbb{E}_{q(\mathbf{z}|\mathbf{x},y)} \left[\log p(\mathbf{x}, y, \mathbf{z}) - \log q(\mathbf{z}|\mathbf{x}, y) \right] \tag{2}$$

Here $q(\mathbf{z}|\mathbf{x}, y)$ is the variational distribution.

To train the grounding model in this generative setup, we put it into the variational distribution:

$$q_\theta(\mathbf{z}|\mathbf{x}, y) = \frac{q_\theta(\mathbf{z}|\mathbf{x})p(y|\mathbf{z})}{Z_q}, \quad \text{where } Z_q = \sum_{\mathbf{z}' \in \mathcal{Z}} q_\theta(\mathbf{z}'|\mathbf{x})p(y|\mathbf{z}') \tag{3}$$

Here $q_\theta(\mathbf{z}|\mathbf{x})$ is the grounding model. We use q_θ instead of p_θ to avoid confusion with the model distribution denoted by p. This specification of the variational distribution gives the variational lower bound:

$$\mathcal{L}_{\text{ELBO}} = \mathbb{E}_{q_\theta(\mathbf{z}|\mathbf{x},y)} \left[\log \frac{\cancel{p(y|\mathbf{z})}p(\mathbf{x}|\mathbf{z})p(\mathbf{z})Z_q}{q_\theta(\mathbf{z}|\mathbf{x})\cancel{p(y|\mathbf{z})}} \right] \tag{4}$$

The rearranged lower bound is:

$$\mathcal{L}_{\text{ELBO}} = \underbrace{\log \left(\sum_{\mathbf{z}' \in \mathcal{Z}} q_\theta(\mathbf{z}'|\mathbf{x})p(y|\mathbf{z}') \right)}_{\text{Weak Supervision}} + \underbrace{\mathbb{E}_{q_\theta}[\log p_\theta(\mathbf{x}|\mathbf{z})]}_{\text{Reconstruction}} - \underbrace{\text{KL}[q_\theta(\mathbf{z}|\mathbf{x}, y)||p(\mathbf{z})]}_{\text{Regularization}} \tag{5}$$

The first term is from the normalization term Z_q, which is taken out of the expectation. Note that this term is the same as (1). We set the prior $p(\mathbf{z})$ to be non-informative, so the third term is a constant.

Our formulation largely resembles objective-based mitigation of reasoning shortcuts by Marconato et al. (2023) but has a clear generative understanding. The reconstruction term encourages the grounding model $q_\theta(\mathbf{z}|\mathbf{x})$ to propose samples that are informative for reconstruction; therefore, the reconstruction term collects information from the input and helps $q_\theta(\mathbf{z}|\mathbf{x})$ learn the correct grounding function.

From the perspective of variational inference, the approach above minimizes $KL[q_\theta(\mathbf{z}|\mathbf{x})p(y|\mathbf{z})||p(\mathbf{z},y|\mathbf{x})]$. An alternative approach is training the grounding model $p_\theta(\mathbf{z}|\mathbf{x})$ using samples $\mathbf{z}$ from the true posterior $p(\mathbf{z}|\mathbf{x}, y) \propto p(\mathbf{x}|\mathbf{z})p(y|\mathbf{z})p(\mathbf{z})$, then this alternative approach is equivalent to minimizing $KL[p(\mathbf{z}, y|\mathbf{x})||q_\theta(\mathbf{z}|\mathbf{x})p(y|\mathbf{z})]$. Here, $p(y|\mathbf{z})$ is included for completeness. The two approaches have a similar learning objective of approximating the posterior, but the second approach is easier to understand: as long as $p(\mathbf{z}, y|\mathbf{x})$ correctly samples correct $\mathbf{z}$ values, we can train a good grounding model $q_\theta(\mathbf{z}|\mathbf{x})$.

3.3 Reconstruction via Cluster-Based Generative Proxies

We show that there is substantial flexibility in designing the reconstruction term $p(\mathbf{x} \mid \mathbf{z})$ without explicitly modeling low-level details that are irrelevant to the target symbols. The key insight is that the generative model $p(\mathbf{x} \mid \mathbf{z})$ need not faithfully reconstruct $\mathbf{x}$, nor provide complete information about $\mathbf{z}$. Because $p(y \mid \mathbf{z})$ imposes strong constraints on $\mathbf{z}$, the reconstruction term only needs to provide complementary information that helps disambiguate label assignments consistent with y.

We design a reconstruction term in which $\mathbf{z}$ defines the cluster structure of $\mathbf{x}$, and this structure is then used to infer $\mathbf{z}$. Specifically, we define $p(\mathbf{x} \mid \mathbf{z}) = p(\mathbf{x} \mid C)$, where $C \in \{0,1\}^{b \times b}$ indicates whether each pair of instances originates from the same latent class, $C_{ij} = 1[z_i = z_j]$. From a generative perspective, if $z_i = z_j$, then $\mathbf{x}_i$ and $\mathbf{x}_j$ are generated from the same mixture component; otherwise, they are generated from different components. Importantly, the class label z_i itself does not specify which particular mixture component is used.

To stabilize training, we estimate the parameters associated with $p(\mathbf{z} \mid C)$ separately from the main objective. To capture the cluster structure of $\mathbf{x}$, we first map inputs into a low-dimensional embedding space and fit a Gaussian mixture model (GMM) with $|\mathcal{Z}|$ components in that space. The encoder can be trained using unsupervised representation learning techniques (Bengio et al., 2013; Ericsson et al., 2022). Since the decoder is deterministic, evaluating $p(\mathbf{x} \mid C)$ reduces to computing the likelihood of compressed encodings under the fitted GMM.

We approximate the reconstruction term in two steps: 1) ignore the constraint imposed by y inside the expectation; and 2) decompose the computation into instance pairs:

$$\mathbb{E}_{q_\theta(\mathbf{z}|\mathbf{x})p(y|\mathbf{z})}\left[p(\mathbf{x} \mid \mathbf{z})\right] \approx \sum_{\substack{i,j=1 \\ i \neq j}} \mathbb{E}_{q_\theta(\mathbf{z}|\mathbf{x})}\left[\log p(x_i, x_j \mid c_{ij})\right] \overset{\text{indp.}}{=} \sum_{\substack{i,j=1 \\ i \neq j}} \mathbb{E}_{q_\theta(z_i|\mathbf{x}_i)q_\theta(z_j|\mathbf{x}_j)}\left[\log p(x_i, x_j \mid c_{ij})\right]. \quad (6)$$

If we have the independence assumption, $q_\theta(\mathbf{z} \mid \mathbf{x}) = \prod_i q_\theta(z_i \mid \mathbf{x}_i)$, then the calculation in the last term has simpler calculation. In later training stages, most samples from q_θ satisfy the symbolic constraint imposed by y, so samples from q_θ are approximate samples from the true posterior. The exact computation of $p(\mathbf{x} \mid C)$ has all instances entangled and is hard to compute. The decomposition over instance pairs is a common approximation and greatly simplifies the computation.

With these approximations, the expectation admits a closed-form computation. The variational posterior of the consistency variable C_{ij} is

$$q_\theta(C_{ij} = 1 \mid \mathbf{x}) = \sum_{\ell \in \mathcal{Z}} q_\theta(z_i = \ell \mid \mathbf{x})q_\theta(z_j = \ell \mid \mathbf{x}) \overset{\text{indp.}}{=} \sum_{\ell \in \mathcal{Z}} q_\theta(z_i = \ell \mid \mathbf{x}_i)q_\theta(z_j = \ell \mid \mathbf{x}_j)$$

The independence assumption allows arbitrary pairing of instances, effectively augmenting training with diverse input pairs. Empirically, random instance pairs improves the performance of q_θ.

Figure 1 illustrates the overall EGP framework. EGP integrates seamlessly with standard neurosymbolic learning while enforcing perceptual grounding by encouraging the model to respect input structure, without modeling low-level details that may obscure semantic information.

Although our reconstruction term does not attempt to recover $\mathbf{x}$, modeling relationships among $\mathbf{z}$ is often sufficient to disambiguate symbol assignments consistent with y. With the true posterior providing sufficient information about symbols $\mathbf{z}$, maximizing the resulting variational lower bound therefore yields a strong grounding model $q_\theta(\mathbf{z} \mid \mathbf{x})$. Our design also decouples clustering from the main training objective and help stabilize the training procedure. An alternative would be to learn class-conditional generative components $p(\mathbf{x}_i \mid z_i = \ell)$ directly; however, this would require joint optimization of the generative and grounding models, increasing instability and complexity.

Extension to multi-concept domains.   We now extend EGP to multi-concept settings, where each input $\mathbf{x}_i$ is associated with a vector of symbols $\mathbf{z}_i \in \mathcal{Z}^K$. Correspondingly, C_{ij} becomes a K-dimensional vector $\mathbf{c}_{ij}$ where $c_{ij}^k = \mathbb{1}[z_i^k = z_j^k]$, which indicates a multi-view clustering structure of all $\mathbf{x}$. Our reconstruction term becomes:

$$\mathbb{E}_{q_\theta(\mathbf{z}|\mathbf{x})p(y|\mathbf{z})} \left[p(\mathbf{x} \mid \mathbf{z}) \right] \approx \sum_{\substack{i,j=1 \\ i \neq j}} \sum_{k=1}^{K} \mathbb{E}_{q_\theta(z_i^k, z_j^k|\mathbf{x})} \left[\log p(\mathbf{x}_i, \mathbf{x}_j \mid c_{ij}^k) \right]. \tag{7}$$

To capture the multi-view clustering structure, the encoder can be learned using disentangled representation learning techniques (Wang et al., 2022; 2024b). More generally, domain knowledge can be injected into encoder training via specialized objectives or data augmentation. For example, in block-stacking tasks depending on shape and color, separate encoders can be trained for color (e.g., reconstructing color histograms) and shape (e.g., grayscale reconstruction). Alternatively, one may learn a split latent space with adversarial constraints to prevent information leakage across components.

3.4   Combining EGP with Existing Methods

The first term of Eq. (5) coincides with the conditional MLE objective in Eq. (1), widely used in neurosymbolic learning. State-of-the-art methods such as SoftenSG (Li et al., 2024), A2G (Lymperopoulos & Liu, 2025), and NeSyDM (van Krieken et al., 2025a) optimize this objective using different techniques. Our framework recovers this objective within a broader formulation that additionally enforces perceptual grounding through the reconstruction term.

Different neurosymbolic methods can be instantiated in our framework in different ways. Methods assuming independent grounding (e.g., SoftenSG and A2G) can directly incorporate the reconstruction term during training. We refer to this approach as EGP-Direct. For methods such as NeSyDM, where computing the distribution $q_\phi(z_i|\mathbf{x}_i)$ is not possible, we provide an alternative method for optimizing the approximate reconstruction error in equation (6). We can indirectly optimize it by modifying the variational posterior used for sampling weak labels, ensuring sampled labels respect input structure. Since the correct labels definitely respect the input structure, this makes them more likely to be discovered during sampling. We refer to this version of our method as EGP-Sampling. We detail the modifications made to NeSyDM in the appendix.

Computational complexity.   Computing the reconstruction term involves pairwise comparisons, yielding $O(n^2)$ complexity per iteration for n inputs. In practice, we use stochastic optimization and randomly sample B pairs per iteration, reducing complexity to $O(B)$. This strategy is used in all experiments. When the independence assumption is removed, complexity depends on the specific inference method. EGP introduces additional overhead for encoder training and evaluation, but these costs are comparable to those of the neurosymbolic learner and are amortized across runs.

4   Experiments

In this section we use the challenging *RSbench* benchmark to evaluate the EGP method applied on multiple SOTA neurosymbolic models on three tasks with significant ambiguity in grounding. In our first experiment, we show how EGP significantly improves concept accuracy in these tasks across SOTA methods by resolving ambiguity using the input structure. In our second experiment, we conduct a closer analysis of how EGP improves neurosymbolic grounding. We examine two approaches for optimizing equation (6) when

Metric	SoftenSG	SoftenSG+EGP	A2G	A2G+EGP	NeSyDM	NeSyDM+EGP
ACC_y	0.964 ± 0.010	0.960 ± 0.009	0.961 ± 0.013	0.961 ± 0.005	0.994 ± 0.003	0.991 ± 0.003
$ACC_{\mathbf{z}}$	0.437 ± 0.003	$\mathbf{0.980 \pm 0.005}$	0.440 ± 0.005	$\mathbf{0.978 \pm 0.004}$	0.717 ± 0.008	$\mathbf{0.991 \pm 0.005}$
$ACC_{y,ood1}$	0.070 ± 0.003	$\mathbf{0.949 \pm 0.005}$	0.063 ± 0.006	$\mathbf{0.950 \pm 0.009}$	0.324 ± 0.049	0.266 ± 0.071
$ACC_{\mathbf{z},ood1}$	0.398 ± 0.002	$\mathbf{0.974 \pm 0.003}$	0.395 ± 0.007	$\mathbf{0.977 \pm 0.005}$	0.645 ± 0.031	$\mathbf{0.707 \pm 0.027}$

Table 1: Effect of EGP on methods in the MNAdd-Half dataset. EGP completely eliminates reasoning shortcuts in this dataset and as a result consistently improves grounding performance across methods. Bold indicates statistical significance.

combining with existing neurosymbolic methods, as discussed in section 3.4. We also provide evidence that the performance improvement originates from symbol labels of higher quality during inference. We further motivate EGP by reproducing the result by Marconato et al. (2023) showing that pixel-level reconstruction is not effective despite directly targeting reconstruction loss. We provide additional intuition and empirical results to explain the phenomenon. In our final experiment we explore the applicability of EGP beyond single-concept inputs by applying it to *ObjectMath*, a custom dataset similar to the *CLE4EVER* task in *RSbench*, but with modified data and reasoning to avoid ambiguity due to label permutations. There we demonstrate that EGP can significantly improve grounding performance in tasks with more than one concept per image without any additional supervision. We also show that EGP offers the opportunity to encode inductive biases into neurosymbolic learning to further boost grounding performance. Finally, we include an experiment where we vary the encoder used in EGP in the appendix, showing that EGP is robust to the choice of encoder training strategy.

4.1 Datasets and Baselines

In our first two experiments, we use the *RSbench* (Bortolotti et al., 2024) suite to evaluate EGP in tasks prone to ambiguity in grounding. We focus on two MNIST digit addition tasks, *MNAdd-Half* and *MNAdd-EvenOdd*, which are constructed such that multiple incorrect classifiers can achieve high accuracy on the final label y. We also evaluate on an instance *MN-Logic* from *RSbench*, where samples consist of MNIST digits of random 3-bit XOR formulas and their result. All these datasets also include additional out-of-distribution test-sets consisting of equations of the same digits, but in different digit combinations.

We incorporate EGP into 3 existing SOTA methods for neurosymbolic learning: SoftenSG (Li et al., 2024), A2G (Lymperopoulos & Liu, 2025) and NeSyDM (van Krieken et al., 2025a). In the former two, which use the independence assumption, we optimize the reconstruction term with their main objectives. We modify NeSyDM training to favor grounding accuracy by using early stopping based on prediction stability on a validation set. This tends to improve grounding performance without observing concept labels as it halts training after the model learns to satisfy the constraint but before it assigns probability to all possible incorrect solutions. SoftenSG and A2G do not require this modification as they converge to confident groundings by construction. We use early stopping on the final label prediction accuracy over the validation set for those. We repeat each experiment 4 times and report mean and standard deviation for each metric. In all our experiments, to obtain compact encoders we use N2D (McConville et al., 2019) trained only samples from the training set. Additional implementation details and experiments with alternate encoders are available in the appendix. We evaluate performance in terms of grounding concept accuracy ($ACC_{\mathbf{z}}$) and label accuracy (ACC_y). We refer to performance in the out-of-ditribution test sets as $ACC_{\mathbf{z},ood}$ and $ACC_{\mathbf{y},ood}$.

4.2 Resolving Grounding Ambiguity in *RSbench* Tasks.

In this experiment we evaluate EGP's performance when it is combined with SOTA neuralsymbolic learning methods that are based discriminative learning. Table 1 shows results across methods in the *MNAdd-Half* dataset. In this dataset, a model can merge digit classes while still satisfying all sums. EGP eliminates these ambiguities by forcing the classifier to respect the input structure and thus significantly improves performance across methods. However, NeSyDM generalizes poorly to unseen digit combinations as it models the joint

Metric	SoftenSG	SoftenSG+EGP	A2G	A2G+EGP	NeSyDM	NeSyDM+EGP
ACC_y	**0.920 ± 0.012**	0.721 ± 0.057	**0.918 ± 0.009**	0.715 ± 0.044	**0.958 ± 0.036**	0.910 ± 0.052
$ACC_{\mathbf{z}}$	0.014 ± 0.002	**0.456 ± 0.011**	0.013 ± 0.005	**0.461 ± 0.017**	0.156 ± 0.025	**0.455 ± 0.058**
$ACC_{y,ood1}$	0.043 ± 0.002	**0.232 ± 0.009**	0.046 ± 0.003	**0.233 ± 0.011**	0.000 ± 0.000	**0.013 ± 0.014**
$ACC_{\mathbf{z},ood1}$	0.019 ± 0.005	**0.463 ± 0.013**	0.016 ± 0.004	**0.459 ± 0.015**	0.141 ± 0.017	**0.313 ± 0.050**
$ACC_{y,ood2}$	0.007 ± 0.005	**0.459 ± 0.139**	0.009 ± 0.006	**0.453 ± 0.122**	0.002 ± 0.003	**0.074 ± 0.050**
$ACC_{\mathbf{z},ood2}$	0.045 ± 0.016	**0.539 ± 0.126**	0.043 ± 0.017	**0.576 ± 0.140**	0.082 ± 0.031	**0.364 ± 0.087**

Table 2: Effect of EGP on methods in the *MNAdd-EvenOdd* dataset. EGP consistently improves grounding performance across methods, but final prediction performance drops and grounding accuracy still remains relatively low. This is because the dataset by construction is highly ambiguous, even allowing a complete permutation of concept labels while still achieving high label prediction accuracy. EGP settles at a local minimum due to extreme ambiguity. Bold indicates statistical significance.

Metric	SoftenSG	SoftenSG+EGP	A2G	A2G+EGP	NeSyDM	NeSyDM+EGP
ACC_y	0.625 ± 0.217	**1.000 ± 0.000**	0.462 ± 0.091	**1.000 ± 0.000**	0.493 ± 0.022	**0.698 ± 0.018**
$ACC_{\mathbf{z}}$	0.375 ± 0.361	**1.000 ± 0.000**	0.580 ± 0.316	**1.000 ± 0.000**	0.679 ± 0.034	**0.813 ± 0.021**
$ACC_{y,ood1}$	0.750 ± 0.144	**1.000 ± 0.000**	0.383 ± 0.169	**1.000 ± 0.000**	**0.521 ± 0.132**	0.091 ± 0.040
$ACC_{\mathbf{z},ood1}$	0.750 ± 0.144	**1.000 ± 0.000**	0.365 ± 0.185	**1.000 ± 0.000**	0.363 ± 0.052	**0.707 ± 0.034**

Table 3: Effect of EGP on methods in the *MNLogic* dataset. As in *MNAdd-Half*, EGP completely eliminates reasoning shortcuts in this dataset and as a result consistently improves performance across methods. Bold indicates statistical significance.

probability of symbols and thus is less able to generalize to new symbol combinations. EGP provides no benefit in that case as the sampling-based strategy does not eliminate all incorrect symbolic solutions in this dataset. We further explore the differences between EGP implementations in the following section.

Table 2 shows methods' performance in the *MNAdd-EvenOdd* dataset. This dataset admits a large number of ambiguous solutions. Most notably, it is possible to achieve perfect label performance by permuting labels between even and odd digits (e.g. 0 to 5, 1 to 6, etc). It is easy to conclude that it is not possible to learn the correct grounding model based on the observed data. Baseline methods all manage to predict the correct sum with high accuracy but fail to correctly ground most samples. Across methods, EGP enables models to select the correct label about half the time, significantly improving performance. However, in this dataset label prediction performance with EGP is lower. This is due to the excessive ambiguity of this dataset that EGP alone cannot resolve.

Taking a closer look at the trained models we observe that the inferred label grounding accuracy during training converges to around 50% in both methods. Figure 2 shows the confusion matrix for a run of SoftenSG+EGP in this dataset. Despite the inductive bias provided by EGP, there is still too much ambiguity in the labels. While theoretically the model could choose one of the two label permutations and satisfy both the symbolic constraint and the EGP, instead it seems to settle at local minima where the clusters merged correspond to the label per-

Figure 2: SoftenSG+EGP confusion matrix in *MNAdd-EvenOdd*. EGP eliminates almost all reasoning shortcuts but due to the extreme ambiguity of the task, where full label permutations are allowed, the model converges to a local optimum where the permuted classes are merged. When observing even a single equation using the merged classes, EGP resolves the ambiguity.

Figure 3: **Comparison of EGP variants on SoftenSG in *MNAdd-Half*.** The left panel shows the value of the training loss for each SoftenSG variant. The middle panel shows the value of the approximate reconstruction term and the right panel the inferred label accuracy. Label accuracy is directly related to the final grounding accuracy of the trained model. In both EGP-Direct and in the sampling-based variant, EGP does not interfere with optimizing the weak supervision loss. In the direct computataion case, it also improves grounding accuracy. In this dataset, EGP-Sampling is unable to resolve all RSes, as it only compares digits within a sequence, which is insufficient in this case.

mutation that satisfies the symbolic constraints. The label prediction accuracy is then lower as the model tries to escape those minima unsuccessfully. While EGP seems to essentially eliminate all other incorrect groundings, it fails to prevent this one likely due to the high weak supervision loss incurred when models attempt to resolve it.

We further investigate this task by creating a variant of the dataset, *MNAdd-EvenOdd+*, where we add to the training set a single equation with digit combinations not present in the original task. We specifically add one equation involving digits (0,5), (1,6), (2,7), (3,8) and (4,9). We leave the validation and test sets the same. Crucially, these equations do not resolve the global permutation on their own, as a model can still satisfy all equations by inverting these pairs of symbols. Still, the added constraints imposed by these equations, namely penalizing cases where the model merges, rather than swaps, these clusters, is sufficient for EGP to take effect and resolve the ambiguity. In this task, SoftenSG+EGP achieves $ACC_{\mathbf{z}}$ of 0.913 $\pm$ 0.004 and ACC_y of 0.833 $\pm$ 0.013, significantly closing the gap with methods that use direct concept supervision (Andolfi & Giunchiglia, 2025) in a similar task. The baseline method SoftenSG still cannot resolve the ambiguity, achieving $ACC_{\mathbf{z}}$ of 0.014 $\pm$ 0.001 and ACC_y of 0.883 $\pm$ 0.004.

Table 3 shows results for the MNLogic Dataset. This dataset is simple in construction, as it only involves digits from the classes 0 and 1 of the MNIST dataset. Still, baseline methods struggle to learn the correct mapping, instead often merging the classes. EGP enables SoftenSG and A2G to perfectly solve the task, while it moderately improves the performance of NeSyDM, following the trend in previous datasets. This is due to the implementation of EGP on NeSyDM, which modifies the label sampling procedure to sample labels that minimize the EGP term for each observed equation independently. This provides less rich feedback to the model than the alternate implementation methods that can be easily applied across any two inputs in the dataset. While it may be possible to further modify the sampling procedure to consider the EGP between samples in a batch, we leave that investigation to future work.

4.3 Analysis of EGP Effect on Neurosymbolic Learning

In this experiment we examine how EGP helps alleviate ambiguity in neurosymbolic grounding in the *MNAdd-Half* dataset. Specifically, we examine two variants of EGP which correspond to two ways to optimize equation (6). The first is EGP-Direct, in which we optimize the approximate reconstruction term directly. The second is EGP-Sampling, in which we modify the label sampling procedure used during weakly supervised learning to sample labels that satisfy both the symbolic constraint and the EGP. As discussed in section 3.4, we use this approach to apply EGP to methods where directly computing $q_\theta(z_i|\mathbf{x}_i)$ is not possible, such as NeSyDM. Here we study it closer by combining it with SoftenSG instead, to facilitate a one-to-one comparison with EGP-Direct.

We focus on *MNAdd-Half* as it has two distinct incorrect solutions that aid in the analysis of EGP variants. Marconato et al. (2023) provide a detailed analysis but in short, one solution involves merging classes 2 and 4 and the other merges classes 1 and 3. The critical difference between the two is that samples of classes 2 and 4 appear in equations together (e.g. 2+4=6) whereas samples of 1 and 3 do not.

Figure 3 shows the training loss, the approximate reconstruction term and the grounding label accuracy over the three methods. In EGP-Direct, the training loss is the SoftenSG loss, which is a lower bound on equation (1), combined with our approximated reconstruction loss. In the other two cases it is exactly the SoftenSG lower bound. In all methods, there is an initial period of improvement where the model learns to satisfy some of the constraints. Then, improvement in the EGP-Direct variant is driven by the approximate reconstruction loss, as this continues to improve rapidly. This resolves all ambiguity as shown by the high inferred label accuracy. The only way for the model to both satisfy the constraint, and EGP-Direct, is to converge to the correct grounding. In contrast, the other two methods eventually converge to incorrect groundings, but their approximate reconstruction error deviates significantly.

Closer examination of the trained models shows that EGP-Sampling consistently fails due to the second incorrect solution, where digit classes 1 and 3 are merged. This is because digits of these classes never appear together in a sample and as such are never forced to have different labels under EGP-Sampling. The second incorrect solution is eliminated however, which explains the lower approximate reconstruction error in figure 3. Interestingly, SoftenSG with EGP-Sampling also underperforms NeSyDM, which should fall victim to the same shortcut but performs better in our previous experiment, though still not as the direct approach. This is likely due to NeSyDM modeling the joint distribution of symbols and having to distribute probability among fewer combinations. The baseline method consistently falls into one of the two failure modes, and its approximate reconstruction error increases rapidly, after the initial phase.

Finally, we use *MNAdd-Half* to provide additional insight on the result by Marconato et al. (2023) showing that pixel-level reconstruction is insufficient despite directly optimizing the reconstruction term in equation (5). In their experiment, they introduce an additional prediction head on the classifier which predicts a latent variable meant to capture stylistic information. We suspect this setup runs the risk of circumventing the neurosymbolic learner and carrying all information for reconstruction through the additional variable, thus eliminating any pressure on the grounding model to resolve the ambiguity. Therefore, we create an alternative setup where the decoder needs to learn to reconstruct digits directly from the predicted concepts, rather than having an alternate route for information. We use the gumbel softmax trick to propagate the reconstruction loss gradient to the encoder, which we train for grounding using SoftenSG. Additional details are available in the appendix.

Figure 4: Reconstruction of MNIST digits after training on *MNAdd-Half*. The decoder can reduce reconstruction error by producing ambiguous and fuzzy images, failing to constraint the neurosymbolic model from merging underlying concept classes.

Still, using direct estimation of the reconstruction loss in equation (5) fails to provide perceptual grounding, achieving ACC_y of 0.939 ± 0.013 and $ACC_{\mathbf{z}}$ of 0.435 ± 0.007, despite the reconstruction loss steadily decreasing and converging to a small value. Figure 4 provides some insight into why. The decoder is able to cheat by producing smeared out, faint digits that seem to balance the reconstruction loss due to an incorrect digit reconstruction, with loss due to low-level details. As a result, the encoder does not face significant pressure to resolve the ambiguity, and instead still merges classes 1 and 3 into the symbol 1, and permutes symbols 2 and 4, satisfying the reasoning constraints while achieving low reconstruction error.

Metric	SoftenSG	SoftenSG+EGP	SoftenSG+EGP*
ACC_y	0.858 ± 0.120	0.715 ± 0.042	0.988 ± 0.005
$ACC_{\mathbf{z}}$	0.602 ± 0.091	0.908 ± 0.010	0.970 ± 0.016

Table 4: SoftenSG variants in the multi-attribute *ObjectMath* dataset. SoftenSG+EGP* achieves near perfect performance as it leverages domain knowledge about concept-relevant features. SoftenSG+EGP achieves very high concept accuracy compared to the baseline method, but lower label prediction as the fully unsupervised multi-attribute EGP may not always capture the desired concept-related features.

In contrast, our approximated reconstruction error in EGP focuses on semantic information by first learning the inherent cluster structure of the input, and then forcing the grounding model to be consistent with it. This provides inductive bias that overcomes ambiguity in the weak supervision.

4.4 ObjectMath Dataset

In this experiment we evaluate the multi-concept version of EGP in the *ObjectMath* dataset. This dataset consists of images of 3 objects, where each object has one of three colors, one of two textures and one of three shapes. The reasoning problem is another arithmetic problem where each possible shape and color is assigned a number and the final result is computed by multiplying the attributes of each object and summing up the results. For each scene we observe the computation result as supervision. Due to commutativity of addition, and due to multiple attribute combinations resulting in the same result, the task is highly ambiguous.

To apply neurosymbolic learning with the independence assumption in this problem, we first run an object detection workflow to isolate images of objects in the scene. We implement 2 versions of EGP and apply them to SoftenSG to validate the efficacy of EGP in this domain. The first method, SoftenSG+EGP uses a split latent space autoencoder with a disentanglement objective to learn two distinct latent spaces capturing important features of each object. In the second version, SoftenSG+EGP*, we inject additional inductive biases in the form of specially trained encoders that capture the two relevant features of each object, namely color and shape. We then apply multi-concept EGP as normal in both methods. We use the EGP-Direct variant in both cases. Additional implementation details are available in the appendix.

Table 4 shows the results of this experiment. Both versions of EGP significantly boost grounding performance over the baseline, with the EGP* method achieving near-perfect performance. The label prediction accuracy of SoftenSG+EGP however is lower than the baseline approach. Examining the learned encoding more closely, one of the latent spaces tightly clusters objects around color, however the other space seems to separate spheres from the other shapes but not cylinders and cubes as effectively. As a result, EGP is uninformative in distinguishing the two shapes, providing less information to the classifier. Still, grounding accuracy is significantly higher than the baseline, making the trade-off favorable when grounding accuracy is primarily of interest. As a result, while EGP is effective when representation learning can disentangle features, injecting application-specific inductive biases in EGP when possible can yield even better performance.

5 Conclusion

In this work, we addressed the issue of insufficient supervision in neurosymbolic learning resulting in reasoning shortcuts, where grounding models learn unintended mappings that satisfy symbolic constraints but fail to capture correct underlying semantics due to insufficient supervision.

To overcome this, we introduced Efficient Generative Proxies, a framework that approaches neurosymbolic learning from a generative perspective without the pitfalls of pixel-by-pixel generation. By leveraging a lightweight approximation of the generative likelihood, EGP provides perceptual grounding by enforcing consistency, ensuring that semantically similar inputs yield similar symbolic predictions and distinct inputs yield distinct predictions. This approach provides the benefits of the generative approach, namely using the inherent structure of the input data to resolve ambiguities in supervision, without requiring the reconstruction of low-level details that can obfuscate the semantic signal. Furthermore, our framework naturally

incorporates typical neurosymbolic learning approaches within it. Our extensive experiments validate that integrating EGP into state-of-the-art neurosymbolic methods significantly improves concept grounding accuracy and effectively mitigates reasoning shortcuts across challenging tasks from the rsbench benchmark and a custom multi-concept ObjectMath dataset. Furthermore, we demonstrated that EGP is highly adaptable, allowing for the incorporation of domain-specific inductive biases to further enhance grounding performance in complex, multi-attribute environments. Finally, the EGP framework is flexible, providing a wide design space for perceptually grounding neurosymbolic learning models.

Despite the strong empirical results, EGP does have some limitations. Most importantly, EGP depends on pretrained encoders that preserve the semantic structure of the data. This can be reasonably easy to obtain when concepts dominate the input (e.g. MNIST digits). In more complex settings, this may not always be possible. However, EGP can still provide an advantage in practice by enabling the injection of additional inductive biases without the need for labeled data.

References

Luca Andolfi and Eleonora Giunchiglia. Right for the right reasons: Avoiding reasoning shortcuts via prototypical neurosymbolic ai. *arXiv preprint arXiv:2510.25497*, 2025.

Samy Badreddine, Artur d'Avila Garcez, Luciano Serafini, and Michael Spranger. Logic tensor networks. *Artificial Intelligence*, 303:103649, 2022.

Yoshua Bengio, Aaron Courville, and Pascal Vincent. Representation learning: A review and new perspectives. *IEEE transactions on pattern analysis and machine intelligence*, 35(8):1798–1828, 2013.

Bikram Pratim Bhuyan, Amar Ramdane-Cherif, Ravi Tomar, and TP Singh. Neuro-symbolic artificial intelligence: a survey. *Neural Computing and Applications*, 36(21):12809–12844, 2024.

Samuele Bortolotti, Emanuele Marconato, Tommaso Carraro, Paolo Morettin, Emile van Krieken, Antonio Vergari, Stefano Teso, and Andrea Passerini. A neuro-symbolic benchmark suite for concept quality and reasoning shortcuts. *Advances in neural information processing systems*, 37:115861–115905, 2024.

Alessio Capitanelli and Fulvio Mastrogiovanni. A framework for neurosymbolic robot action planning using large language models. *Frontiers in Neurorobotics*, 18:1342786, 2024.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pp. 1597–1607. PmLR, 2020.

Wang-Zhou Dai, Qiuling Xu, Yang Yu, and Zhi-Hua Zhou. Bridging machine learning and logical reasoning by abductive learning. *Advances in Neural Information Processing Systems*, 32, 2019.

Linus Ericsson, Henry Gouk, Chen Change Loy, and Timothy M Hospedales. Self-supervised representation learning: Introduction, advances, and challenges. *IEEE Signal Processing Magazine*, 39(3):42–62, 2022.

Meng Fang, Shilong Deng, Yudi Zhang, Zijing Shi, Ling Chen, Mykola Pechenizkiy, and Jun Wang. Large language models are neurosymbolic reasoners. In *Proceedings of the AAAI conference on artificial intelligence*, volume 38, pp. 17985–17993, 2024.

Ricardo Fitas. Neuro-symbolic ai for advanced signal and image processing: a review of recent trends and future directions. *IEEE Access*, 2025.

Shivam Goel, Yash Shukla, Vasanth Sarathy, Matthias Scheutz, and Jivko Sinapov. Rapid-learn: A framework for learning to recover for handling novelties in open-world environments. In *2022 IEEE International Conference on Development and Learning (ICDL)*, pp. 15–22. IEEE, 2022.

Shivam Goel, Panagiotis Lymperopoulos, Ravenna Thielstrom, Evan Krause, Patrick Feeney, Pierrick Lorang, Sarah Schneider, Yichen Wei, Eric Kildebeck, Stephen Goss, et al. A neurosymbolic cognitive architecture framework for handling novelties in open worlds. *Artificial Intelligence*, 331:104111, 2024a.

Shivam Goel, Yichen Wei, Panagiotis Lymperopoulos, Klára Churá, Matthias Scheutz, and Jivko Sinapov. Novelgym: A flexible ecosystem for hybrid planning and learning agents designed for open worlds. *arXiv preprint arXiv:2401.03546*, 2024b.

Robert Hoehndorf, Catia Pesquita, and Fernando Zhapa Camacho. Neuro-symbolic ai in life sciences. *Handbook on Neurosymbolic AI and Knowledge Graphs*, 2025.

Qing Li, Siyuan Huang, Yining Hong, Yixin Chen, Ying Nian Wu, and Song-Chun Zhu. Closed loop neural-symbolic learning via integrating neural perception, grammar parsing, and symbolic reasoning. In *International Conference on Machine Learning*, pp. 5884–5894. PMLR, 2020.

Zenan Li, Yuan Yao, Taolue Chen, Jingwei Xu, Chun Cao, Xiaoxing Ma, and Jian Lü. Softened symbol grounding for neuro-symbolic systems. *arXiv preprint arXiv:2403.00323*, 2024.

Panagiotis Lymperopoulos and Liping Liu. Act-to-ground: A framework for symbol grounding in planning domains. In *19th International Conference on Neurosymbolic Learning and Reasoning*, 2025.

Robin Manhaeve, Sebastijan Dumancic, Angelika Kimmig, Thomas Demeester, and Luc De Raedt. Deepproblog: Neural probabilistic logic programming. *Advances in neural information processing systems*, 31, 2018.

Jiayuan Mao, Joshua B Tenenbaum, and Jiajun Wu. Neuro-symbolic concepts. *arXiv preprint arXiv:2505.06191*, 2025.

Emanuele Marconato, Stefano Teso, Antonio Vergari, and Andrea Passerini. Not all neuro-symbolic concepts are created equal: Analysis and mitigation of reasoning shortcuts. *Advances in Neural Information Processing Systems*, 36:72507–72539, 2023.

Emanuele Marconato, Samuele Bortolotti, Emile van Krieken, Paolo Morettin, Elena Umili, Antonio Vergari, Efthymia Tsamoura, Andrea Passerini, and Stefano Teso. Symbol grounding in neuro-symbolic ai: A gentle introduction to reasoning shortcuts. *arXiv preprint arXiv:2510.14538*, 2025.

R McConville, R Santos-Rodríguez, RJ Piechocki, and I Craddock. N2d:(not too) deep clustering via clustering the local manifold of an autoencoded embedding. arxiv. *arXiv preprint arXiv:1908.05968*, 2019.

Cyprien Michel-Delétie and Md Kamruzzaman Sarker. Neuro-symbolic methods for trustworthy ai: a systematic review. *Neurosymbolic Artificial Intelligence*, 2024.

Parth Padalkar, Huaduo Wang, and Gopal Gupta. Nesyfold: Neurosymbolic framework for interpretable image classification. *arXiv preprint arXiv:2301.12667*, 2023.

Xin Quan, Marco Valentino, Danilo Carvalho, Dhairya Dalal, and André Freitas. Peirce: Unifying material and formal reasoning via llm-driven neuro-symbolic refinement. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 3: System Demonstrations)*, pp. 11–21, 2025.

Emanuele Sansone and Robin Manhaeve. A bayesian unification of self-supervised clustering and energy-based models. *arXiv preprint arXiv:2401.00873*, 2023.

Georgios Tziafas and Hamidreza Kasaei. Enhancing interpretability and interactivity in robot manipulation: A neurosymbolic approach. *arXiv preprint arXiv:2210.00858*, 2022.

Emile van Krieken, Pasquale Minervini, Edoardo Ponti, and Antonio Vergari. Neurosymbolic diffusion models. *arXiv preprint arXiv:2505.13138*, 2025a.

Emile van Krieken, Pasquale Minervini, Edoardo Ponti, and Antonio Vergari. Neurosymbolic reasoning shortcuts under the independence assumption. *arXiv preprint arXiv:2507.11357*, 2025b.

Chen Wang, Kaiyi Ji, Junyi Geng, Zhongqiang Ren, Taimeng Fu, Fan Yang, Yifan Guo, Haonan He, Xiangyu Chen, Zitong Zhan, et al. Imperative learning: A self-supervised neuro-symbolic learning framework for robot autonomy. *The International Journal of Robotics Research*, pp. 02783649251353181, 2024a.

Kaifu Wang, Qiang Ning, and Dan Roth. Learnability with indirect supervision signals. *Advances in Neural Information Processing Systems*, 33:9145–9155, 2020.

Po-Wei Wang, Priya Donti, Bryan Wilder, and Zico Kolter. Satnet: Bridging deep learning and logical reasoning using a differentiable satisfiability solver. In *International Conference on Machine Learning*, pp. 6545–6554. PMLR, 2019.

Xin Wang, Hong Chen, Yuwei Zhou, Jianxin Ma, and Wenwu Zhu. Disentangled representation learning for recommendation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 45(1):408–424, 2022.

Xin Wang, Hong Chen, Si'ao Tang, Zihao Wu, and Wenwu Zhu. Disentangled representation learning. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 46(12):9677–9696, 2024b.

Jingyi Xu, Zilu Zhang, Tal Friedman, Yitao Liang, and Guy Broeck. A semantic loss function for deep learning with symbolic knowledge. In *International conference on machine learning*, pp. 5502–5511. PMLR, 2018.

Xiao-Wen Yang, Jie-Jing Shao, Lan-Zhe Guo, Bo-Wen Zhang, Zhi Zhou, Lin-Han Jia, Wang-Zhou Dai, and Yu-Feng Li. Neuro-symbolic artificial intelligence: Towards improving the reasoning abilities of large language models. *arXiv preprint arXiv:2508.13678*, 2025.

Xin Zhang and Victor S Sheng. Neuro-symbolic ai: Explainability, challenges, and future trends. *arXiv preprint arXiv:2411.04383*, 2024.

Zhi-Hua Zhou. A brief introduction to weakly supervised learning. *National science review*, 5(1):44–53, 2018.

A   Formal Analysis of perceptual grounding for Reasoning shortcuts

To theoretically quantify the benefit of our proposed method, we adopt the analysis framework of Marconato et al. (2023). We analyze the number of deterministic Reasoning Shortcuts (RSs) that minimize the training objective. Let G denote the ground-truth concepts and Z denote the learned symbols. A neurosymbolic predictor learns a distribution $p_\theta(Z|X)$, which in the deterministic limit implies a mapping $\alpha : G \to Z$. Standard neurosymbolic learning admits any map α that satisfies the logical constraints β_K. Our method introduces a generative reconstruction term derived from unsupervised representations. To analyze its impact, we introduce the following assumption regarding the quality of the unsupervised clustering.

A.1   Assumption A4: Ideal Disentangled Clustering

We assume the unsupervised representation learning is sufficient to recover the equality of ground-truth concepts. Specifically, for a specific latent dimension or concept k, the generative model's posterior probability over the consistency variable $C_{ij}^{(k)}$ perfectly reflects ground-truth equality:

$$p(C_{ij}^{(k)} = 1 \mid x_i, x_j) \approx 1 \iff g_i^{(k)} = g_j^{(k)} \quad \text{and} \quad p(C_{ij}^{(k)} = 1 \mid x_i, x_j) \approx 0 \iff g_i^{(k)} \neq g_j^{(k)} \tag{8}$$

Under this assumption, maximizing the EGP term acts as a hard constraint on the mapping α. For any two inputs x_i, x_j generated by distinct ground-truth concepts $g_i^{(k)} \neq g_j^{(k)}$, the generative proxy forces the learned symbols to be distinct:

$$g^{(k)} \neq g'^{(k)} \implies \alpha_k(g^{(k)}) \neq \alpha_k(g'^{(k)}) \tag{9}$$

This imposes an injectivity constraint on the component-wise mapping α_k.

A.2   Counting Reasoning Shortcuts

Following Marconato et al. (2023), we count the number of deterministic maps $\alpha \in \mathcal{A}$ that minimize the learning objective.

Proposition 1 (Reduction of Reasoning Shortcuts via perceptual grounding) *Consider a learning task with prior knowledge K and logical label map β_K. Under Assumptions A1, A2 (from Marconato et al. (2023)), and A4 (Ideal Disentangled Clustering), the number of deterministic optima is restricted to those maps that are both logically consistent and injective on the concept factors.*

If the model is disentangled such that α factorizes into component-wise maps $(\alpha_1, \dots, \alpha_k)$, the count of optimal maps is given by:

$$N_{opt} = \sum_{\alpha \in \mathcal{A}} \underbrace{\mathbb{I} \left\{ \bigwedge_{g \in supp(G)} \beta_K(\alpha(g)) = \beta_K(g) \right\}}_{\text{Logical Consistency}} \cdot \prod_{j=1}^{k} \underbrace{\mathbb{I} \left\{ \bigwedge_{\substack{g,g' \in supp(G) \\ g_j \neq g_j'}} \alpha_j(g_j) \neq \alpha_j(g_j') \right\}}_{\text{perceptual grounding (Injectivity)}} \tag{10}$$

Without perceptual grounding, the count is dominated by the Logical Consistency term. As shown in Marconato et al. (2023), this allows for "many-to-one" mappings where distinct ground-truth concepts (e.g., distinct digits) are collapsed into a single symbol that satisfies the aggregate logic (e.g., a sum). This leads to a search space size proportional to $\prod_y |\mathcal{C}_y|^{|\mathcal{C}_y|}$.

Our method introduces the second term, which enforces injectivity. Consequently, the search space is reduced from the set of all valid surjective maps to the set of valid permutations, which is significantly smaller. Then, the logical consistency constraint is responsible for "selecting" permutations that satisfy the logical constraints. In many cases, this is sufficient to eliminate all reasoning shortcuts. In other cases, it significantly reduces them.

B Additional Experiment Details and Results

B.1 Varying EGP encoder

We use *MNAdd-Half* to validate EGP's sensitivity to the underlying encoder architecture. While our main experiments are derived using N2D (McConville et al., 2019), as it is specially designed to obtain clusterable embeddings, we repeat the experiment using a standard autoencoder and SimCLR Chen et al. (2020). We run these EGP variants with SoftenSG. We find that in our experiment, EGP is robust to the choice of encoder.

Metric	SoftenSG+EGP(AE)	SoftenSG+EGP(SimCLR)
ACC_y	0.944 ± 0.001	0.940 ± 0.005
ACC_c	0.971 ± 0.001	0.970 ± 0.002
$ACC_{y,ood1}$	0.938 ± 0.004	0.939 ± 0.005
$ACC_{c,ood1}$	0.969 ± 0.002	0.969 ± 0.003

Table 5: *MNAdd-Half* results with varying encoder method

B.2 Modifying NeSyDM with EGP

NeSyDM (van Krieken et al., 2025a) learns an expressive distribution over possible solutions to reflect the uncertainty due to reasoning shortcuts. Since it does not use the independence assumption, we are not able to directly apply EGP to the loss. Instead, we modify the variational posterior, responsible for sampling approximate labels, so that they satisfy the EGP. This indirectly optimizes EGP, as the model learns to place probability in symbol configurations that are consistent with the input structure. Adapting to our own notation, the NeSyDM posterior is: $p(\mathbf{z}^0|\mathbf{z}^t, \mathbf{x}, y) \propto p(\mathbf{z}^0|\mathbf{z}^t, \mathbf{x})r(\mathbf{z}^0|y)$, where $r_\beta(\tilde{\mathbf{z}}^0 \mid \mathbf{y}^0) \propto \exp\left(-\beta \sum_{i=1}^{Y} \mathbb{1}[\varphi(\tilde{\mathbf{z}}^0)_i \neq y_i^0]\right)$. Note that here the super-scripts correspond to the diffusion time dimension. NeSyDM uses large β, essentially sampling K samples from the model and keeping the ones that satisfy the most constraints. We modify the posterior by incorporating the EGP in the energy function of r. This results in $r_{\beta,\gamma}(\tilde{\mathbf{z}}^0 \mid \mathbf{y}^0, \mathbf{x}) \propto \exp\left(-\beta \sum_{i=1}^{Y} \mathbb{1}[\varphi(\tilde{\mathbf{z}}^0)_i \neq y_i^0] - \gamma \log p(\mathbf{x}_0, \mathbf{x}_1|c_{01})\right)$. Selecting γ is easy when β is large, as the only terms that survive the first term satisfy the constraint. Then the second term only needs to select the ones that satisfy the EGP. We use $\gamma = 1$ in all our experiments. In our experiments, $\mathbf{x}$ only contains 2 images, so this term suffices. Alternatively we can compute the term across all pairs, or pick some at random.

B.3 Analysis of Surrogate EGP.

EGP-Posterior Matching (PM) is a surrogate objective to equation (6) that aims to align the model's posterior $q_\theta(C_{i,j}|\mathbf{x}_i, \mathbf{x}_j)$ with that derived from the GMM. In our experiments performance between the two is similar in practice but EGP-PM may be simpler to implement and may interact better with some optimizers in some settings, as it is simply the binary cross entropy loss between the two distributions. The objective is:

$$L_{EGP-PM}(\mathbf{x}_i, \mathbf{x}_j) = BCE(q_\theta(c_{i,j}|\mathbf{x}_i, \mathbf{x}_j), p_{GMM}(c_{i,j}|\mathbf{x}_i, \mathbf{x}_j). \tag{11}$$

The first distribution is derived from the classifier using the independence assumption, as in equation (6). The latter is the collision probability computed in closed form for the GMM.

Figure 3 shows two plots illustrating single runs of SoftenSG with different implementations of EGP applied to it. EGP-Direct refers to the direct implementation of the EGP term in equation (6). EGP-PM refers to the posterior-matching version of EGP, where the probability of two inputs belonging to the same concept assigned by the model is matched to that of the GMM. Finally, EGP-Sampling refers to modifying the label sampling procedure during weakly-supervised learning to sample labels that optimize the EGP loss. The baseline method is SoftenSG. Crucially, EGP-Sampling naturally only considers inputs in the same input sequence, as labels across samples are sampled independently.

Figure 5: **Comparison of EGP variants on SoftenSG in *MNAdd-Half*.** Each panel shows the value of the EGP loss, the posterior matching BCE loss and the inferred label accuracy for different implementations of EGP during training. Label accuracy (right) refers to the quality of the labels sampled during inference and relates to the final performance of the trained model. EGP-Direct and EGP-PM both achieve high performance because they enforce prediction consistency across each training batch. Minimizing EGP-PM has a similar effect to minimizing EGP-Direct. EGP-Sampling indirectly minimizes the EGP loss as well, but only considers consistency within a sequence, which is insufficient in the MNAdd-Half dataset. Effective minimization of EGP-Direct is consistently associated with high quality labels.

As expected, EGP-Direct most directly minimizes the EGP loss. The surrogate EGP-PM loss behaves like an upper bound, as minimizing it ensures the EGP loss term remains low, while the opposite does not hold: Minimizing EGP-Direct eventually results to an increase in the EGP-PM loss value. This is because EGP-PM penalizes the model if it does not reflect the GMM's uncertainty over whether two samples belong in the same class, while EGP-Direct encourages high confidence regardless of the GMM's confidence. In short, we hypothesize that EGP-PM may enjoy improved training dynamics in some settings, as it uses the standard binary cross entropy loss and provides linear gradients to the model, whereas in EGP-Direct the gradient may vanish if the model is confidently wrong about two inputs belonging to the same concept.

B.4   Additional Experiment Details

Early stopping NeSyDM.   We notice in the original NeSyDM experiments that grounding accuracy peaks when the model reaches stable predictions (predicted groundings on the validation set change slowly over training epochs). As such in our experiments we perform early stopping in all variants of NeSyDM by early stopping based on the minimum fraction of validation samples that change labels in each epoch, smoothed over 5 epochs. Crucially, this does not require validation grounding labels.

MNIST EGP experiment settings.   We implement EGP with a convolutional autoencoder for feature extraction and UMAP dimensionality reduction, following the N2D method (McConville et al., 2019). We then fit a Gaussian Mixture Model (GMM) for EGP on the resulting latent space. The autoencoder architecture consists of an encoder with three convolutional layers (channels: $1 \rightarrow 16 \rightarrow 32 \rightarrow 64$) followed by a linear layer projecting to a 10-dimensional embedding space, and a symmetric decoder using transposed convolutions. The model was trained on the MNIST training set for 10 epochs using the Adam optimizer with learning rate 10^{-3} and mean squared error reconstruction loss, with a batch size of 256.

Following training, embeddings were extracted from all training samples (batch size 1000) and reduced to 5 dimensions using UMAP with $n_{\text{neighbors}} = 30$, min_dist $= 0.0$ (to promote compact clusters) and cosine distance metric. A GMM with 10 components and full covariance matrices was then fitted to the UMAP-reduced embeddings. The resulting model computes cluster assignment probabilities and joint log-densities for image pairs under same-cluster and different-cluster hypotheses.

Disentangled EGP Experimental Settings for ObjectMath   .

The disentangled EGP method extends the standard EGP pipeline with a dual-encoder architecture that produces two separate, disentangled embeddings (z_1 and z_2) from a shared convolutional base. The archi-

tecture processes 64×64 images through a shared encoder (channels: $C \rightarrow 16 \rightarrow 32 \rightarrow 64 \rightarrow 128$) followed by two separate linear heads producing unit-normalized embeddings of dimensions d_1 and d_2. The decoder reconstructs from the concatenated embedding $[z_1, z_2]$ using transposed convolutions.

Training employs a two-stage adversarial objective using the ObjectMath training set. The reconstruction loss (weight $\lambda_{\text{recon}} = 1.0$) can be either pixel-wise MSE or a histogram-based loss that compares sorted pixel values, ignoring spatial structure to focus on color distribution. The disentanglement loss (weight $\lambda_{\text{disent}} = 0.1$) is implemented via cross-prediction MLPs that attempt to predict one encoding from the other. The MLPs are trained to minimize prediction error, while the encoders are trained to maximize it (via a negative term in the loss), encouraging independence between z_1 and z_2. The total loss is $\mathcal{L} = \lambda_{\text{recon}}\mathcal{L}_{\text{recon}} - \lambda_{\text{disent}}\mathcal{L}_{\text{disent}}$. Training uses the Adam optimizer with learning rates 10^{-3} for the autoencoder and 10^{-4} for the cross-prediction MLPs, with a batch size of 256 for 10 epochs.

Following training, separate UMAP reducers and GMMs are fitted to each embedding stream. Both UMAP models use $n_{\text{neighbors}} = 30$, min_dist $= 0.0$, $n_{\text{components}} = 5$, cosine metric. Each GMM uses $n_{\text{components}} = 3$ with full covariance matrices. The resulting model computes cluster probabilities and joint log-densities independently for each embedding, enabling analysis of different semantic dimensions captured by z_1 and z_2.

EGP* implementation for ObjectMath Here we use a convolutional autoencoder with an encoder that progressively downsamples from 64×64 to 1×1 through four convolutional layers (channels: $C \rightarrow 16 \rightarrow 32 \rightarrow 64 \rightarrow 128$), followed by a linear projection to an embedding dimension. The decoder uses transposed convolutions to reconstruct the original image size, with a sigmoid activation for output normalization.

Training employs the Adam optimizer with learning rate 10^{-3} for 10 epochs with batch size 256. The reconstruction loss can be either standard pixel-wise MSE or a histogram-based loss that compares sorted pixel values across channels, effectively ignoring spatial structure to focus on color distribution. For the shape encoder we use regular image reconstruction over grayscale images instead. These loss variants enable training models that emphasize different aspects of the data (e.g., color-only or shape-only representations).

Following training, embeddings are extracted and reduced to 5 dimensions using UMAP with $n_{\text{neighbors}} = 30$, min_dist $= 0.0$, cosine metric, and random seed 42. A GMM with 3 components and full covariance matrices is fitted to the UMAP-reduced embeddings.

B.5   Reconstruction experiment details

Here the model is a VAE with a discrete latent space that processes sequences of images using the Gumbel-Softmax trick for differentiable discrete sampling. The model consists of an encoder that maps individual images to hidden representations, a predictor that outputs logits for discrete latents (one per image in the sequence), and a decoder that reconstructs images from sampled discrete latents.

Training employs a multi-objective loss combining reconstruction and the semantic loss. The reconstruction loss uses mean squared error between original and reconstructed images, where reconstructions are obtained by encoding images to logits, sampling discrete latents via soft Gumbel-Softmax (temperature T_{gumbel}), and decoding.

Training uses the Adam optimizer with learning rate 10^{-4}. Gumbel temperature undergoes exponential annealing:The Gumbel temperature decays from 1 to 0.1 with rate 0.99.