# Factorized linear discriminant analysis for phenotype-guided representation learning of neuronal gene expression data

## Abstract

A central goal in neurobiology is to relate the expression of genes to the structural and functional properties of neuronal types, collectively called their phenotypes. Single-cell RNA sequencing can measure the expression of thousands of genes in thousands of neurons. How to interpret the data in the context of neuronal phenotypes? We propose a supervised learning approach that factorizes the gene expression data into components corresponding to individual phenotypic characteristics and their interactions. This new method, which we call factorized linear discriminant analysis (FLDA), seeks a linear transformation of gene expressions that varies highly with only one phenotypic factor and minimally with the others. We further leverage our approach with a sparsity-based regularization algorithm, which selects a few genes important to a specific phenotypic feature or feature combination. We applied this approach to a single-cell RNA-Seq dataset of Drosophila T4/T5 neurons, focusing on their dendritic and axonal phenotypes. The analysis confirms results from the previous report but also points to new genes related to the phenotypes and an intriguing hierarchy in the genetic organization of these cells.

## 1 Introduction

The complexity of neural circuits is a result of many different types of neurons that specifically connect to each other. Each neuronal type has its own phenotypic traits, which together determine the role of the neuronal type in a neural circuit. Typical phenotypic descriptions of neurons include features such as dendritic and axonal laminations, electrophysiological properties, and connectivity (Sanes & Masland, 2015; Zeng & Sanes, 2017; Gouwens et al., 2019). However, the genetic programs behind these phenotypic characteristics are still poorly understood.

Recent progress in characterizing neuronal cell types and investigating their gene expression, especially with advances in high-throughput single-cell RNA-Seq (Zeng & Sanes, 2017), provides an opportunity to address this challenge. With massive data generated from single-cell RNA-Seq, we now face a computational problem: how to factorize the high-dimensional data into gene expression modules that are meaningful to neuronal phenotypes? Specifically, given phenotypic descriptions of neuronal types, such as their dendritic stratification and axonal termination, can one project the original data into a low-dimensional space corresponding to these phenotypic features and their interactions, and further extract genes critical to each of these components?

This problem can be approached by well-known methods with limitations. For instance, canonical correlation analysis (CCA) could find linear transformations of the data and the phenotypic features that maximally correlate with each other (Hotelling, 1936; Wang et al., 2015). However, this approach cannot factorize gene expressions according to individual features, making the result hard to interpret. Another approach to this problem is autoencoders and variants (Feng et al., 2014; Hinton & Salakhutdinov, 2006; Gala et al., 2019). It is challenging to understand the relationship between gene expressions and phenotypic features from autoencoders, as they are non-linear architectures.

Here we propose a new analysis method named factorized linear discriminant analysis (FLDA). Inspired by multi-way analysis of variance (ANOVA) (Fisher, 1918), this method factorizes data into components corresponding to phenotypic features and their interactions, and seeks a linear transfor-

Figure 1: Illustration of our approach. (A,B) In the example, cell types are jointly represented by two phenotypic features. If only some combinations of the two features are observed, one obtains a partial contingency table (B) instead of a complete one (A). (C) We seek linear projections of the data that separate the cell types in a factorized manner corresponding to the two features. Here $\boldsymbol{u}$, $\boldsymbol{v}$, and $\boldsymbol{w}$ are aligned with Feature 1, Feature 2, and the interaction of both features, with the projected coordinates $y$, $z$, and $s$ respectively.

mation that varies highly with one specific factor but not with the others. The linear nature of this approach makes it easy to interpret, as the weight coefficients directly inform the relative importance of each gene to each factor. We further introduce a sparse variant of the method, which constrains the number of genes contributing to each linear projection. We illustrate this approach by applying FLDA to a single-cell transcriptome dataset of T4/T5 neurons in Drosophila (Kurmangaliyev et al., 2019), focusing on two phenotypes: dendritic location and axonal lamination.

## 2 FACTORIZED LINEAR DISCRIMINANT ANALYSIS (FLDA)

Suppose that we are given gene expression data of single neurons which are typically very high-dimensional. These cells are classified into cell types, as a result of clustering in the high-dimensional space and annotations based on prior knowledge or verification outcome (Macosko et al., 2015; Tasic et al., 2016; Shekhar et al., 2016; Tasic et al., 2018; Peng et al., 2019). We know the phenotypic traits of each neuronal type, therefore each type can also be jointed defined by the phenotypic features. We want to find an interpretable low-dimensional embedding in which certain dimensions represent factors of phenotypic features or their interactions. This requires that variation along one of the axes in the embedding space causes the variation of only one factor. In reality, this is hard to satisfy due to noise in the data, and we relax the constraint by letting data projected along one axis vary largely with one factor while minimally with the others. In addition, we ask that cells classified as the same type are still close to each other in the embedding space, while cells of different types are far apart.

As a start, let us consider only two phenotypic features of neurons, dendritic stratification, and axonal termination, both of which can be described with discrete categories, such as different regions or layers in the brain (Oh et al., 2014; Euler et al., 2014; Sanes & Masland, 2015; Kurmangaliyev et al., 2019). Suppose that each cell type can be jointly represented by its dendritic location indexed as $i$ and axonal lamination indexed as $j$, with the number of cells within each cell type $n_{ij}$. This representation can be described using a contingency table (Figure 1A,B). Note here that we allow the table to be partially filled.

Let $\boldsymbol{x}_{ijk}(k \in 1, 2, ...n_{ij})$ represent the expression values of $g$ genes in each cell ($\boldsymbol{x}_{ijk} \in \mathbf{R}^g$). How to find linear projections $y_{ijk} = \boldsymbol{u}^T \boldsymbol{x}_{ijk}$ and $z_{ijk} = \boldsymbol{v}^T \boldsymbol{x}_{ijk}$ that are aligned with features $i$ and $j$ respectively (Figure 1C)? We first asked whether we could factorize, for example, $y_{ijk}$, with respect to components depending on features $i$ and $j$. Indeed, motivated by the linear factor models used in multi-way ANOVA and the idea of partitioning variance, we constructed an objective function as the following, and found $\boldsymbol{u}^*$ that maximizes the objective (see detailed analysis in Appendix A):

$$\boldsymbol{u}^* = \arg\max_{\boldsymbol{u} \in \mathbf{R}^g} \frac{\boldsymbol{u}^T \boldsymbol{N}_A \boldsymbol{u}}{\boldsymbol{u}^T \boldsymbol{M}_e \boldsymbol{u}} \tag{1}$$

When we have a complete table, and there are $a$ levels for the feature $i$ and $b$ levels for the feature $j$, we have

$$\boldsymbol{N}_A = \boldsymbol{M}_A - \lambda_1 \boldsymbol{M}_B - \lambda_2 \boldsymbol{M}_{AB} \tag{2}$$

where $\boldsymbol{M}_A$, $\boldsymbol{M}_B$, and $\boldsymbol{M}_{AB}$ are the covariance matrices explained by the feature $i$, the feature $j$, and the interaction of them. $\lambda_1$ and $\lambda_2$ are hyper-parameters controlling the relative weights of $\boldsymbol{M}_B$ and $\boldsymbol{M}_{AB}$ with respect to $\boldsymbol{M}_A$. $\boldsymbol{M}_e$ is the residual covariance matrix representing noise in gene expressions. Formal definitions of these terms are the following:

$$\boldsymbol{M}_A = \frac{1}{a-1} \sum_{i=1}^{a} \sum_{j=1}^{b} (\boldsymbol{m}_{i.} - \boldsymbol{m}_{..})(\boldsymbol{m}_{i.} - \boldsymbol{m}_{..})^T \tag{3}$$

$$\boldsymbol{M}_B = \frac{1}{b-1} \sum_{i=1}^{a} \sum_{j=1}^{b} (\boldsymbol{m}_{.j} - \boldsymbol{m}_{..})(\boldsymbol{m}_{.j} - \boldsymbol{m}_{..})^T \tag{4}$$

$$\boldsymbol{M}_{AB} = \frac{1}{(a-1)(b-1)} \sum_{i=1}^{a} \sum_{j=1}^{b} (\boldsymbol{m}_{ij} - \boldsymbol{m}_{i.} - \boldsymbol{m}_{.j} + \boldsymbol{m}_{..})(\boldsymbol{m}_{ij} - \boldsymbol{m}_{i.} - \boldsymbol{m}_{.j} + \boldsymbol{m}_{..})^T \tag{5}$$

$$\boldsymbol{M}_e = \frac{1}{N-ab} \sum_{i=1}^{a} \sum_{j=1}^{b} [\frac{1}{n_{ij}} \sum_{k=1}^{n_{ij}} (\boldsymbol{x}_{ijk} - \boldsymbol{m}_{ij})(\boldsymbol{x}_{ijk} - \boldsymbol{m}_{ij})^T] \tag{6}$$

where

$$\boldsymbol{m}_{..} = \frac{1}{ab} \sum_{i=1}^{a} \sum_{j=1}^{b} \boldsymbol{m}_{ij} \tag{7}$$

$$\boldsymbol{m}_{i.} = \frac{1}{b} \sum_{j=1}^{b} \boldsymbol{m}_{ij} \tag{8}$$

$$\boldsymbol{m}_{.j} = \frac{1}{a} \sum_{i=1}^{a} \boldsymbol{m}_{ij} \tag{9}$$

in which

$$\boldsymbol{m}_{ij} = \frac{1}{n_{ij}} \sum_{k=1}^{n_{ij}} \boldsymbol{x}_{ijk} \tag{10}$$

An analogous expression provides the linear projection $\boldsymbol{v}^*$ for the feature $j$, and $\boldsymbol{w}^*$ for the interaction of both features $i$ and $j$. Similar arguments can be applied to the scenario of a partial table to find $\boldsymbol{u}^*$ or $\boldsymbol{v}^*$ as the linear projection for the feature $i$ or $j$ (see Appendix B for mathematical details).

Note that $\boldsymbol{N}_A$ is symmetric and $\boldsymbol{M}_e$ is positive definite. Therefore the optimization problem is a generalized eigenvalue problem (Ghojogh et al., 2019). When $\boldsymbol{M}_e$ is invertible, $\boldsymbol{u}^*$ is the eigenvector associated with the largest eigenvalue of $\boldsymbol{M}_e^{-1} \boldsymbol{N}_A$. In general, if we want to embed $\boldsymbol{x}_{ijk}$ into a $d$-dimensional subspace aligned with the feature $i$ ($d < a$), we can take the eigenvectors with the $d$ largest eigenvalues of $\boldsymbol{M}_e^{-1} \boldsymbol{N}_A$, which we call the top $d$ factorized linear discriminant components (FLDs). Since multi-way ANOVA can handle contingency tables with more than two dimensions, our analysis can be easily generalized to more than two features.

## 3 SPARSITY-BASED REGULARIZATION OF FLDA

To select genes important to each phenotypic feature, we impose sparseness on the number of genes contributing to each axis. Briefly, we try to solve the following optimization problem:

$$\boldsymbol{u}^* = \arg\max_{\boldsymbol{u} \in \mathbf{R}^g} \frac{\boldsymbol{u}^T \boldsymbol{N}_A \boldsymbol{u}}{\boldsymbol{u}^T \boldsymbol{M}_e \boldsymbol{u}} \quad \text{subject to} \quad ||\boldsymbol{u}||_0 \leq l \tag{11}$$

from which the number of non-zero elements of $\boldsymbol{u}^*$ is less or equal to $l$.

This is also known as a sparse generalized eigenvalue problem. To solve it, we used a recently developed statistical approach, the truncated Rayleigh flow method (Rifle). The algorithm of Rifle is composed of two steps (Tan et al., 2018):

(1) obtain an initial vector $\boldsymbol{u}_0$ that is close to $\boldsymbol{u}^*$. We used the solution from the non-sparse FLDA as an initial estimate of $\boldsymbol{u}_0$.

(2) iteratively, perform a gradient ascent step on the objective function, and then execute a truncation step that preserves the $l$ entries of $\boldsymbol{u}$ with the largest values and sets the remaining entries to 0. Pseudo-code for this step is presented below:

---

**procedure** RIFLE($\boldsymbol{N}_A, \boldsymbol{M}_e, \boldsymbol{u}_0, l, \eta$)        $\triangleright \eta$ is the step size
     $t = 1$        $\triangleright t$ indicates the iteration number
     **while** not converge **do**        $\triangleright$ Converge when $\boldsymbol{u}_t \simeq \boldsymbol{u}_{t-1}$
         $\rho_{t-1} \leftarrow \frac{\boldsymbol{u}_{t-1}^T \boldsymbol{N}_A \boldsymbol{u}_{t-1}}{\boldsymbol{u}_{t-1}^T \boldsymbol{M}_e \boldsymbol{u}_{t-1}}$
         $\boldsymbol{C} \leftarrow \boldsymbol{I} + (\frac{\eta}{\rho_{t-1}})(\boldsymbol{N}_A - \eta_{t-1}\boldsymbol{M}_e)$
         $\boldsymbol{u}_t \leftarrow \frac{\boldsymbol{C}\boldsymbol{u}_{t-1}}{||\boldsymbol{C}\boldsymbol{u}_{t-1}||_2}$
         Truncate $\boldsymbol{u}_t$ by keeping the top $l$ entries of $\boldsymbol{u}$ with the largest values and setting the rest entries to 0
         $\boldsymbol{u}_t \leftarrow \frac{\boldsymbol{u}_t}{||\boldsymbol{u}_t||_2}$
         $t \leftarrow t + 1$
     **end while**
     **return** $\boldsymbol{u}_t$
**end procedure**

---

## 4 RELATED METHOD - LINEAR DISCRIMINANT ANALYSIS (LDA)

We name our method FLDA because its objective function has a similar format as that of linear discriminant analysis (LDA) (Fisher, 1936; McLachlan, 2004). LDA also models the difference among data organized in pre-determined classes. Formally, LDA solves the following optimization problem:

$$\boldsymbol{u}^* = \arg\max_{\boldsymbol{u} \in \mathbf{R}^g} \frac{\boldsymbol{u}^T \boldsymbol{\Sigma}_b \boldsymbol{u}}{\boldsymbol{u}^T \boldsymbol{\Sigma}_e \boldsymbol{u}} \tag{12}$$

where $\boldsymbol{\Sigma}_b$ and $\boldsymbol{\Sigma}_e$ are estimates of the between-class and within-class covariance matrices respectively.

Different from FLDA, the representation of these classes is not explicitly formulated as a contingency table composed of multiple features. The consequence is that, when applied to the example problem in which neuronal types are organized into a two-dimensional contingency table with phenotypic features $i$ and $j$, in general, axes from LDA are not aligned with these two phenotypic features.

However, in the example above, we can perform two separate LDAs for the two features. This allows the axes from each LDA to align with its specific feature. We call this approach "2LDAs". There are two limitations of this approach: first, it discards information about the component depending on the

Figure 2: Quantitative comparison among FLDA, LDA, and 2LDAs. (A) Illustration of data synthesis. See Appendix C for implementation details. Color bar indicates the expression values of the ten generated genes. (B) Normalized overall SNR metric of each analysis. The SNR values of FLDA and 2LDAs are normalized with respect to that of LDA. (C) Overall modularity score for each analysis. Error bars in (B,C) denote standard errors each calculated from 10 repeated simulations.

interaction of the two features which cannot be explained by a linear combination of them; second, it explicitly maximizes the segregation of cells with different feature levels which sometimes is not consistent with a good separation of cell type clusters.

# 5 EXPERIMENTS

## 5.1 DATASETS

In order to compare FLDA with LDA and the "2LDAs" approach and show the difference quantitatively, we created synthetic datasets. Four types of cells, each containing 25 examples, were generated from a Cartesian product of two features $i$ and $j$, organized in a 2x2 complete contingency table. Expressions of 10 genes were generated for these cells, in which the levels of Genes 1-8 were correlated with either the feature $i$, the feature $j$, or the interactions of them, and the levels of the remaining 2 genes were purely driven by noise (Figure 2A). Details of generating the data can be found in Appendix C, and analysis of these synthesized data is reported in Results.

To illustrate FLDA in analyzing single-cell RNA-Seq datasets for real problems of neurobiology, and demonstrate the merit of our approach in selecting a few important genes for each phenotype, we used a dataset of Drosophila T4/T5 neurons (Kurmangaliyev et al., 2019). T4 and T5 neurons are very similar in terms of general morphology and physiological properties, but they differ by the location of their dendrites in the medulla and lobula, two distinct brain regions. T4 and T5 neurons each contain four subtypes, with each pair of the four laminating their axons in a specific layer in the lobula plate (Figure 3A). Therefore, we can use two phenotypic features to describe these neurons: the feature $i$ indicates the dendritic location at the medulla or lobula; the feature $j$ describes the axonal lamination at one of the four layers (a/b/c/d) (Figure 3B). In this experiment, we focused on the dataset containing expression data of 17492 genes from 3833 cells collected at a defined time during brain development.

## 5.2 DATA PREPROCESSING

The T4/T5 neuron dataset was preprocessed as previously reported (Shekhar et al., 2016; Peng et al., 2019; Tran et al., 2019). Briefly, transcript counts within each column of the count matrix (genes×cells) were normalized to sum to the median number of transcripts per cell, resulting in the normalized counts Transcripts-per-median or $TPM_{gc}$ for Gene $g$ in Cell $c$. We used the log-transformed expression data $E_{gc} = \ln(TPM_{gc} + 1)$ for further analysis. We adopted a common approach in single-cell RNA-Seq studies that is based on fitting a relationship between mean and coefficient of variation (Chen et al., 2016; Pandey et al., 2018) to select highly variable genes, and performed FLDA on the expression data with only these genes. As the number of cells was less than the number of genes, we first performed principal component analysis (PCA) and kept principal

Figure 3: FLDA on the dataset of T4/T5 neurons. (A) T4/T5 neuronal types and their dendritic and axonal phenotypes. (B) T4/T5 neurons can be organized in a complete contingency table. Here $i$ indicates the dendritic location and $j$ indicates the axonal termination. (C) SNR metric of each discriminant axis. (D) Projection of the data into the three-dimensional space consisting of the discriminant axis for the feature $i$ (FLD$_i$) and the first and second discriminant axes for the feature $j$ (FLD$_{j1}$ and FLD$_{j2}$). (E-G) Projection of the data into the two-dimensional space made of FLD$_i$ and FLD$_{j1}$ (E), FLD$_{j1}$ and FLD$_{j2}$ (F), or FLD$_{j2}$ and FLD$_{j3}$ (the third discriminant axis for the feature $j$) (G). Different cell types are indicated by different colors as in (A) and (D).

components (PCs) explaining ∼99% of the total variance. In this experiment below, we set the hyper-parameters $\lambda$s in Equation (2) to 1.

## 5.3 METRICS

We included the following metrics to evaluate our method: We specified a metric of signal-to-noise ratio (SNR) to measure how well each discriminant axis separates cell types compared with noise estimated from the variance within cell type clusters; We defined explained variance (EV) for each discriminant axis to measure how much variance of the feature $i$ or $j$ is explained among the total variance explained by that axis; We calculated mutual information (MI) between each discriminant axis and each feature, to quantify how "informative" an axis is to a specific feature; Built on the calculation of MI, we included the modularity score which measures whether each discriminant axis depends on at most one feature (Ridgeway & Mozer, 2018). The implementation details of these metrics can be found in Appendix D.

## 6 RESULTS

To quantitatively compare the difference between FLDA and the alternative models of LDA and "2LDAs", we measured the proposed metrics from analyses of the synthesized datasets (Figure 2A). Given that the synthesized data were organized in a 2x2 contingency table, each LDA of the "2LDAs" approach could find only one dimension for the specific feature $i$ or $j$. Therefore, as a fair comparison, we only included the corresponding dimensions in FLDA (FLD$_i$ and FLD$_j$) and the top two linear discriminant components (LDs) in LDA. The overall SNR values normalized by

that of LDA and the overall modularity scores were plotted for data generated with different noise levels (Figure 2B,C). The SNR metric measures how well cell types are separated from each other and the modularity score quantifies whether each of the axes is best aligned with only one feature Ridgeway & Mozer (2018). In general, LDA has the highest SNR values but the lowest modularity scores because it explicitly maximizes the separation of cell type clusters but overlooks the alignment of LDs to the feature $i$ or $j$. By contrast, "2LDAs" achieves the highest modularity scores but the worst SNR metrics, because it tries to maximize the separation of cells with different feature levels, which is not necessarily consistent with maximizing the segregation of cell types. The SNR value of FLDA is close to that of LDA, and the modularity score of FLDA is similar to that of "2LDAs". To a certain extent, FLDA combines the merits of both LDA and "2LDAs", as it not only considers the alignment of axes to different features but also constrains the variance within cell types. The EV and MI metrics of FLDA, LDA, and "2LDAs" are shown in Tables 1 to 3, reporting good alignment of axes to either the feature $i$ or $j$ in FLDA and '2LDAs", but not in LDA.

A question of significance in neurobiology is whether the diverse phenotypes of neuronal cell types are generated by combinations of modular transcriptional programs, and if so, what is the gene signature for each of the programs. To illustrate the ability of our approach in addressing this problem, we applied FLDA to the dataset of Drosophila T4/T5 neurons. The T4/T5 neurons could be organized in a 2x4 contingency table, therefore, FLDA was able to project the expression data into a subspace of seven dimensions, with one FLD aligned with dendritic location $i$ (FLD$_i$), three FLDs aligned with axonal termination $j$ (FLD$_{j1-3}$), and the remaining three representing the interaction of both phenotypes (FLD$_{ij1-3}$). We ranked these axes based on their SNR metrics and found that FLD$_{j1}$, FLD$_i$, and FLD$_{j2}$ have much higher SNRs than the rest (Figure 3C). Indeed, data representations in the subspace consisting of these three dimensions show a clear separation of the eight neuronal types (Figure 3D). As expected, FLD$_i$ teases apart T4 from T5 neurons, whose dendrites are located at different brain regions (Figure 3E). Interestingly, FLD$_{j1}$ separates T4/T5 neurons into two groups, a/b vs c/d, corresponding to the upper or lower lobula place, and FLD$_{j2}$ divides them into another two, a/d vs b/c, indicating whether their axons laminate at the middle or lateral part of the lobula plate (Figure 3E,F). Unexpectedly, among these three dimensions, FLD$_{j1}$ has a much higher SNR than FLD$_i$ and FLD$_{j2}$, whose SNR values are similar. This suggests a hierarchical structure in the genetic organization of T4/T5 neurons: they are first separated into either a/b or c/d types, and subsequently divided into each of the eight subtypes. In fact, this exactly matches the sequence of their cell fate determination during development, as revealed in a previous genetic study (Pinto-Teixeira et al., 2018). Finally, the last discriminant axis of the axonal feature FLD$_{j3}$ separates the group a/c from b/d, suggesting its role in fine-tuning the axonal depth within the upper or lower lobula plate (Figure 3G). For this dataset, we also quantified the proposed metrics whose values are listed in Table 4.

To seek gene signatures for the discriminant components in FLDA, we applied the sparsity-based regularization to constrain the number of genes with non-zero weight coefficients. Here we set the number to 20, a reasonable number of candidate genes to be tested in a follow-up biological study. We extracted a list of 20 genes each for the axis of FLD$_i$ or FLD$_{j1}$. The relative importance of these genes to each axis is directly informed by their weight values (Figure 4A,C). Side-by-side, we plotted expression profiles of these genes in the eight neuronal types (Figure 4B,D). For both axes, the genes critical in separating cells with different feature levels are differentially expressed in corresponding cell types. On our gene lists, consistent with the original report (Kurmangaliyev et al., 2019), we found indicator genes for dendritic location such as $TfAP$-$2$, $dpr2$, $CG34155$, and $CG12065$, and those for axonal lamination such as $klg$, $bi$, $pros$. In addition, we found genes that were not reported in the previous study. For example, our results suggest that the genes $Thor$ and $pHCl$-$1$ are important to the dendritic phenotype, and $Lac$ and $Mip$ are critical to the axonal phenotype. These are promising genetic targets to be tested in biological experiments.

Finally, FLDA allowed us to examine the component that depends on the interaction of both features and identify its gene signature, which provides clues to transcriptional regulation of gene expressions in the T4/T5 neuronal types (Figures 5 and 6). For instance, $DIP$-$eta$ is exclusively expressed in T5c/d neurons, suggesting its expression is turned on only when the dendritic transcriptional program is set for T5 neurons and the axonal program is for c/d types. Oppositely, $Neto$ is selectively enriched in T4a/b neurons, indicating activation of its expression under the condition that the dendritic transcriptional program is set for T4 neurons and the axonal program is for a/b types. These are known as the "AND" and "NOR" logics in genetic programs (Sprinzak & Elowitz, 2005).

Figure 4: Critical genes extracted from the sparse algorithm. (A) Weight vector of the 20 genes selected for the dendritic phenotype (FLD$_i$). The weight value is indicated in the color bar with color indicating direction (red: positive and green: negative) and saturation indicating magnitude. (B) Expression patterns of the 20 genes from (A) in eight types of T4/T5 neurons. Dot size indicates the percentage of cells in which the gene was expressed, and color represents average scaled expression. (C) Weight vector of the 20 genes selected for the axonal phenotype (FLD$_{j1}$). Legend as in (A). (D) Expression patterns of the 20 genes from (C) in eight types of T4/T5 neurons. Dot size indicates the percentage of cells in which the gene was expressed, and color represents average scaled expression. Legend as in (B).

## 7    DISCUSSION

Single-cell RNA-Seq has generated a large amount of neuronal transcriptomic data (Macosko et al., 2015; Tasic et al., 2016; Shekhar et al., 2016; Tasic et al., 2018; Peng et al., 2019). However, neurons display a great variety of phenotypes, making it a challenging task to understand transcriptional programs behind these phenotypic features (Mak & Justman, 2017). Motivated by ANOVA, we developed FLDA to address this challenge. We illustrated FLDA focusing on two phenotypes of T4/T5 neurons in Drosophila, dendritic location and axonal termination. As multi-way ANOVA is applied to multiple factors, our approach can be easily generalized to more than two phenotypic features and applicable to additional characteristics such as electrophysiology and connectivity (Gouwens et al., 2019; Zeng & Sanes, 2017).

FLDA factorizes gene expression data into features and their interactions, and finds a linear projection of the data that varies with only one factor but not the others. This provides a modular representation aligned with the factors (Bengio et al., 2012). Ridgeway & Mozer (2018) argued that modularity together with explicitness could define disentangled representations. Our approach is linear, which presents an explicit mapping between gene expressions and phenotypic features, therefore our approach can potentially serve as a supervised approach to disentanglement (Kingma et al., 2014; Kulkarni et al., 2015; Karaletsos et al., 2016).

The linear nature of FLDA makes it extremely easy to interpret the representations, as the weight vector directly informs the relative importance of each gene. To allow the selection of a small set of critical genes, we leveraged our approach with sparse regularization. This makes FLDA especially useful to experimentalists who can take the list of genes and test them in follow-up genetic experiments. However, data other than gene expression may require non-linear representation learning. One way to deal with this is to use kernel tricks which are commonly used in machine learning (Hofmann et al., 2008). As a future direction, we also hope to generalize ideas from this work to deep learning models.

## 8 APPENDIX

### 8.1 A. OBJECTIVE FUNCTIONS

Here we derive the objective functions used in our analysis. Again if $\boldsymbol{x}_{ijk}(k \in 1, 2, ...n_{ij})$ represents the expression values of $g$ genes in each cell ($\boldsymbol{x}_{ijk} \in \mathbf{R}^g$)), we seek to find a linear projection $y_{ijk} = \boldsymbol{u}^T \boldsymbol{x}_{ijk}$ that is aligned with the feature $i$.

#### 8.1.1 INSPIRATION FROM ANOVA

We asked what is the best way to factorize $y_{ijk}$. Inspired by multi-way ANOVA (Fisher, 1918), we identified three components: one depending on the feature $i$, another depending on the feature $j$, and the last one depending on the interaction of both features. We therefore followed the procedures of ANOVA to partition sums of squares and factorize $y_{ijk}$ into these three components.

Let us first assume that all cell types defined by $i$ and $j$ contain the same number of cells. With cell types represented by a complete contingency table (Figure 1A), $y_{ijk}$ can be linearly factorized using the model of two crossed factors. Formally, the linear factorization is the following:

$$y_{ijk} = \mu + \alpha_i + \beta_j + (\alpha\beta)_{ij} + \epsilon_{ijk} \tag{13}$$

where $y_{ijk}$ represents the coordinate of the $k$th cell in the category defined by $i$ and $j$; $\mu$ is the average level of $y$; $\alpha_i$ is the component that depends on the feature $i$, and $\beta_j$ is the component that depends on the feature $j$; $(\alpha\beta)_{ij}$ describes the component that depends on the interaction of both features $i$ and $j$; $\epsilon_{ijk} \sim \mathcal{N}(0, \sigma^2)$ is the residual of this factorization.

Let us say that the features $i$ and $j$ fall into $a$ and $b$ discrete categories respectively. Then without loss of generality, we can require:

$$\sum_{i=1}^{a} \alpha_i = 0 \tag{14}$$

$$\sum_{j=1}^{b} \beta_j = 0 \tag{15}$$

$$\sum_{i=1}^{a} (\alpha\beta)_{ij} = \sum_{j=1}^{b} (\alpha\beta)_{ij} = 0 \tag{16}$$

Corresponding to these, there are three null hypotheses:

$$H_{01} : \alpha_i = 0 \tag{17}$$

$$H_{02} : \beta_j = 0 \tag{18}$$

$$H_{03} : (\alpha\beta)_{ij} = 0 \tag{19}$$

Here we want to reject $H_{01}$ while accepting $H_{02}$ and $H_{03}$ in order that $y_{ijk}$ is aligned with the feature $i$.

Next, we partition the total sum of squares. If the number of cells within each cell type category is $n$, and the total number of cells is $N$, then we have

$$\sum_{i=1}^{a}\sum_{j=1}^{b}\sum_{k=1}^{n}(y_{ijk}-\bar{y}_{...})^2 = bn\sum_{i=1}^{a}(\bar{y}_{i..}-\bar{y}_{...})^2 + an\sum_{j=1}^{b}(\bar{y}_{.j.}-\bar{y}_{...})^2$$
$$+ n\sum_{i=1}^{a}\sum_{j=1}^{b}(\bar{y}_{ij.}-\bar{y}_{i..}-\bar{y}_{.j.}+\bar{y}_{...})^2 + \sum_{i=1}^{a}\sum_{j=1}^{b}\sum_{k=1}^{n}(y_{ijk}-\bar{y}_{ij.})^2 \tag{20}$$

where $\bar{y}$ is the average of $y_{ijk}$ over the indices indicated by the dots. Equation (20) can be written as

$$SS_T = SS_A + SS_B + SS_{AB} + SS_e \tag{21}$$

with each term having degrees of freedom $N-1$, $a-1$, $b-1$, $(a-1)(b-1)$, and $N-ab$ respectively. Here $SS_A$, $SS_B$, $SS_{AB}$, and $SS_e$ are partitioned sum of squares for the factors $\alpha_i$, $\beta_j$, $(\alpha\beta)_{ij}$, and the residual.

ANOVA rejects or accepts a null hypothesis by comparing its mean square (the partitioned sum of squares normalized by the degree of freedom) to that of the residual. This is done by constructing F-statistics for each factor as shown below:

$$F_A = \frac{MS_A}{MS_e} = \frac{\frac{SS_A}{a-1}}{\frac{SS_e}{N-ab}} \tag{22}$$

$$F_B = \frac{MS_B}{MS_e} = \frac{\frac{SS_B}{b-1}}{\frac{SS_e}{N-ab}} \tag{23}$$

$$F_{AB} = \frac{MS_{AB}}{MS_e} = \frac{\frac{SS_{AB}}{(a-1)(b-1)}}{\frac{SS_e}{N-ab}} \tag{24}$$

Under the null hypotheses, the F-statistics follow the F-distribution. Therefore, a null hypothesis is rejected when we observe the value of a F-statistic above a certain threshold calculated from the F-distribution. Here we want $F_A$ to be large enough so that we can reject $H_{01}$, but $F_B$ and $F_{AB}$ to be small enough for us to accept $H_{02}$ and $H_{03}$. In other words, we want to maximize $F_A$ while minimizing $F_B$ and $F_{AB}$. Therefore, we propose maximizing an objective $L$:

$$L = F_A - \lambda_1 F_B - \lambda_2 F_{AB} \tag{25}$$

where $\lambda_1$ and $\lambda_2$ are hyper-parameters determining the relative weights of $F_B$ and $F_{AB}$ compared with $F_A$.

### 8.1.2 OBJECTIVE FUNCTIONS UNDER A COMPLETE CONTINGENCY TABLE

When the numbers of cells within categories defined by $i$ and $j$ ($n_{ij}$) are not all the same, the total sum of squares cannot be partitioned as in Equation (20). However, if we only care about distinctions between cell types instead of individual cells, we can use the mean value of each cell type cluster ($\bar{y}_{ij.}$) to estimate the overall average value ($\tilde{y}_{...}$), and the average value of each category $i$ ($\tilde{y}_{i..}$) or $j$ ($\tilde{y}_{.j.}$). Therefore, Equation (20) can be modified as the following:

$$\sum_{i=1}^{a}\sum_{j=1}^{b}[\frac{1}{n_{ij}}\sum_{k=1}^{n_{ij}}(y_{ijk}-\tilde{y}_{...})^2] = b\sum_{i=1}^{a}(\tilde{y}_{i..}-\tilde{y}_{...})^2 + a\sum_{j=1}^{b}(\tilde{y}_{.j.}-\tilde{y}_{...})^2$$
$$+ \sum_{i=1}^{a}\sum_{j=1}^{b}(\bar{y}_{ij.}-\tilde{y}_{i..}-\tilde{y}_{.j.}+\tilde{y}_{...})^2 + \sum_{i=1}^{a}\sum_{j=1}^{b}[\frac{1}{n_{ij}}\sum_{k=1}^{n_{ij}}(y_{ijk}-\bar{y}_{ij.})^2] \tag{26}$$

where

$$\bar{y}_{ij.} = \frac{\sum_{k=1}^{n_{ij}} y_{ijk}}{n_{ij}} \tag{27}$$

$$\tilde{y}_{i..} = \frac{\sum_{j=1}^{b} \bar{y}_{ij.}}{b} \tag{28}$$

$$\tilde{y}_{.j.} = \frac{\sum_{i=1}^{a} \bar{y}_{ij.}}{a} \tag{29}$$

$$\tilde{y}_{...} = \frac{\sum_{i=1}^{a} \sum_{j=1}^{b} \bar{y}_{ij.}}{ab} \tag{30}$$

If we describe Equation (26) as:

$$\tilde{SS}_T = \tilde{SS}_A + \tilde{SS}_B + \tilde{SS}_{AB} + \tilde{SS}_e \tag{31}$$

then following the same arguments, we want to maximize an objective function in the following format:

$$L = \frac{\frac{\tilde{SS}_A}{a-1} - \lambda_1 \frac{\tilde{SS}_B}{b-1} - \lambda_2 \frac{\tilde{SS}_{AB}}{(a-1)(b-1)}}{\frac{\tilde{SS}_e}{N-ab}} \tag{32}$$

### 8.1.3 OBJECTIVE FUNCTIONS UNDER A PARTIAL CONTINGENCY TABLE

When we have a representation of a partial table, we can no longer separate out the component that depends on the interaction of both features. Therefore, we use another model, a linear model of two nested factors, to factorize $y_{ijk}$, which has the following format:

$$y_{ijk} = \mu + \alpha_i + \beta_{j(i)} + \epsilon_{ijk} \tag{33}$$

Note that we now have $\beta_{j(i)}$ instead of $\beta_j + (\alpha\beta)_{ij}$. In this model, we identify a primary factor, for instance, the feature denoted by $i$ which falls into $a$ categories, and the other (indexed by $j$) becomes a secondary factor, the number of whose levels $b_i$ depends on the level of the primary factor. We merge the component depending on the interaction of both features into that of the secondary factor as $\beta_{j(i)}$.

Similarly, we have

$$\sum_{i=1}^{a} \sum_{j=1}^{b_i} [\frac{1}{n_{ij}} \sum_{k=1}^{n_{ij}} (y_{ijk} - \tilde{y}_{...})^2] = \sum_{i=1}^{a} [\sum_{j=1}^{b_i} (\tilde{y}_{i..} - \tilde{y}_{...})^2]$$
$$+ \sum_{i=1}^{a} \sum_{j=1}^{b_i} (\bar{y}_{ij.} - \tilde{y}_{i..})^2 + \sum_{i=1}^{a} \sum_{j=1}^{b_i} [\frac{1}{n_{ij}} \sum_{k=1}^{n_{ij}} (y_{ijk} - \bar{y}_{ij.})^2] \tag{34}$$

which can be written as

$$\tilde{SS}_T = \tilde{SS}_A + \tilde{SS}_B + \tilde{SS}_e \tag{35}$$

with degrees of freedom $N - 1$, $a - 1$, $M - a$, and $N - M$ for each of the terms, where $M$ is:

$$M = \sum_{i=1}^{a} b_i \tag{36}$$

Therefore, we want to maximize the following objective:

$$L = \frac{\frac{\tilde{SS}_A}{a-1} - \lambda \frac{\tilde{SS}_B}{M-a}}{\frac{\tilde{SS}_e}{N-M}} \tag{37}$$

## 8.2  B. FLDA WITH A PARTIAL CONTINGENCY TABLE

Here we provide the mathematical details of FLDA under the representation of a partial table. When we have a partial table, if the feature $i$ is the primary feature with $a$ levels, and the feature $j$ is the secondary feature with $b_i$ levels, then $N_A$ in Equation (1) is defined as follows:

$$N_A = M_A - \lambda M_{B|A} \tag{38}$$

where

$$M_A = \frac{1}{a-1} \sum_{i=1}^{a} \sum_{j=1}^{b_i} (m_{i.} - m_{..})(m_{i.} - m_{..})^T \tag{39}$$

$$M_{B|A} = \frac{1}{M-a} \sum_{i=1}^{a} \sum_{j=1}^{b_i} (m_{ij} - m_{i.})(m_{ij} - m_{i.})^T \tag{40}$$

and $M$ is defined as in Equation (36). Correspondingly, $M_e$ in Equation (1) is defined as:

$$M_e = \frac{1}{N-M} \sum_{i=1}^{a} \sum_{j=1}^{b} [\frac{1}{n_{ij}} \sum_{k=1}^{n_{ij}} (x_{ijk} - m_{ij})(x_{ijk} - m_{ij})^T] \tag{41}$$

and

$$m_{..} = \frac{1}{M} \sum_{i=1}^{a} \sum_{j=1}^{b_i} m_{ij} \tag{42}$$

$$m_{i.} = \frac{1}{b_i} \sum_{j=1}^{b_i} m_{ij} \tag{43}$$

The remaining mathematical arguments are the same as those for the complete table. In this scenario, because we don't observe all possible combinations of features $i$ and $j$, we cannot find the linear projection for the interaction of both features.

## 8.3  C. IMPLEMENTATION DETAILS OF DATA SYNTHESIS

To quantitatively compare FLDA with LDA and the "2LDAs" approach, we synthesized data of four cell types, each of which contained 25 cells. The four cell types were generated from a Cartesian product of two features $i$ and $j$, where $i \in \{0, 1\}$ and $j \in \{0, 1\}$. Expressions of 10 genes were generated for each cell. The expression value of the $h$th gene in the $k$th cell of the cell type $ij$, $g_{ijk}^h$ was defined as the following:

$$g_{ijk}^1 = i + \epsilon_{ijk} \tag{44}$$

$$g_{ijk}^2 = j + \epsilon_{ijk} \tag{45}$$

$$g_{ijk}^3 = i \wedge j + \epsilon_{ijk} \tag{46}$$

$$g_{ijk}^4 = i \vee j + \epsilon_{ijk} \tag{47}$$

$$g_{ijk}^5 = 2i + \epsilon_{ijk} \tag{48}$$

$$g_{ijk}^6 = 2j + \epsilon_{ijk} \tag{49}$$

$$g_{ijk}^7 = 2i \wedge j + \epsilon_{ijk} \tag{50}$$

$$g_{ijk}^8 = 2i \vee j + \epsilon_{ijk} \tag{51}$$

$$g_{ijk}^9 = \epsilon_{ijk} \tag{52}$$

$$g_{ijk}^{10} = 2 + \epsilon_{ijk} \tag{53}$$

where

$$i \wedge j = \begin{cases} 1, & \text{if } i = 1, j = 1 \\ 0, & \text{otherwise} \end{cases} \tag{54}$$

and

$$i \vee j = \begin{cases} 0, & \text{if } i = 0, j = 0 \\ 1, & \text{otherwise} \end{cases} \tag{55}$$

were interactions of the two features. Here $\epsilon_{ijk}$ was driven by Gaussian noise, namely,

$$\epsilon_{ijk} \sim \mathcal{N}(0, \sigma^2) \tag{56}$$

We synthesized datasets of 5 different $\sigma$ values ($\sigma \in \{0.2, 0.4, 0.6, 0.8, 1.0\}$). This was repeated 10 times and metrics for each $\sigma$ value were calculated as the average across the 10 repeats.

### 8.4 D. Implementation details of the metrics used in the study

We measured the following metrics in our experiments:

#### 8.4.1 Signal-to-Noise Ratio (SNR)

Because we care about the separation of cell types, we define the SNR metric as the ratio of the variance between cell types over the variance of the noise, which is estimated from within-cluster variance. For the entire embedding space, given $q$ cell types, if the coordinate of each cell is indicated by $c$, then we define the overall SNR metric as the following:

$$SNR_{overall} = \frac{tr(\Sigma_{p=1}^q n_p (\bar{c}_{p.} - \bar{c}_{..})(\bar{c}_{p.} - \bar{c}_{..})^T))}{tr(\Sigma_{p=1}^q \Sigma_{k=1}^{n_p} (c_{pk} - \bar{c}_{p.})(c_{pk} - \bar{c}_{p.})^T)} \tag{57}$$

where $\bar{c}_{p.}$ is the center of each cell type cluster, and $\bar{c}_{..}$ is the center of all data points.

Let $c$ denote the embedded coordinate along a specific dimension. The SNR metric for that axis is therefore:

$$SNR = \frac{\Sigma_{p=1}^{q} n_p (\bar{c}_{p.} - \bar{c}_{..})^2}{\Sigma_{p=1}^{q} \Sigma_{k=1}^{n_p} (c_{pk} - \bar{c}_{p.})^2} \tag{58}$$

### 8.4.2 EXPLAINED VARIANCE (EV)

We want to know whether the variation of a specific dimension is strongly explained by that of a specific feature. Therefore, we measure, for each axis, how much of the total explained variance is explained by the variance of the feature $i$ or $j$. Formally, given the embedded coordinate $y_{ijk}$, we calculate the EV as the following:

$$EV_i = \frac{\sum_{i=1}^{a} \sum_{j=1}^{b} n_{ij} (\bar{y}_{i..} - \bar{y}_{...})^2}{\sum_{i=1}^{a} \sum_{j=1}^{b} \sum_{k=1}^{n_{ij}} (y_{ijk} - \bar{y}_{...})^2} \tag{59}$$

$$EV_j = \frac{\sum_{i=1}^{a} \sum_{j=1}^{b} n_{ij} (\bar{y}_{.j.} - \bar{y}_{...})^2}{\sum_{i=1}^{a} \sum_{j=1}^{b} \sum_{k=1}^{n_{ij}} (y_{ijk} - \bar{y}_{...})^2} \tag{60}$$

where $\bar{y}$ is the average of $y_{ijk}$ over the indices indicated by the dots.

### 8.4.3 MUTUAL INFORMATION (MI)

The MI between a discriminant axis $\boldsymbol{u}$ and a feature quantifies how much information of the feature is obtained by observing data projected along that axis. It is calculated as the MI between data representations along the axis $\boldsymbol{y} = \boldsymbol{u}^T \boldsymbol{X}$ and feature labels of the data $\boldsymbol{f}$, where $\boldsymbol{X}$ is the original gene expression matrix:

$$
\begin{aligned}
I(\boldsymbol{y}, \boldsymbol{f}) &= H(\boldsymbol{y}) + H(\boldsymbol{f}) - H(\boldsymbol{y}, \boldsymbol{f}) \\
&= -\sum_{y \in Y} p(y) \log_2 p(y) - \sum_{f \in F} p(f) \log_2 p(f) - \sum_{y \in Y} \sum_{f \in F} p(y, f) \log_2 p(y, f)
\end{aligned} \tag{61}
$$

Here $H$ indicates entropy. To calculate $H(\boldsymbol{y})$ and $H(\boldsymbol{y}, \boldsymbol{f})$, we discretize $\boldsymbol{y}$ into 10 bins.

### 8.4.4 MODULARITY

Ridgeway & Mozer (2018) argued that in a modular representation, each axis should depend on at most a single feature. Following the arguments in their paper, the modularity score is computed as follows: we first calculate the MI between each feature and each axis ($m_{if}$ denotes the MI between one axis $i$ and one feature $f$). If an axis is perfectly modular, it will have high mutual information for only one feature and zeros for the others, we therefore compute a template $t_{if}$ as the following:

$$t_{if} = \begin{cases} \theta_i, & \text{if } f = \arg\max_g m_{ig} \\ 0, & \text{otherwise} \end{cases} \tag{62}$$

where $\theta_i = \max_g m_{ig}$. We then calculate the deviation from the template as:

$$\delta_i = \frac{\sum_f (m_{if} - t_{if})^2}{\theta_i^2 (N - 1)} \tag{63}$$

where $N$ is the number of features. The modularity score for the axis $i$ is $1 - \delta_i$. The mean of $1 - \delta_i$ over $i$ is defined as the overall modularity score.

REFERENCES

Yoshua Bengio, Aaron Courville, and Pascal Vincent. Representation Learning: A Review and New Perspectives. *arXiv:1206.5538 [cs]*, June 2012.

Hung-I. Harry Chen, Yufang Jin, Yufei Huang, and Yidong Chen. Detection of high variability in gene expression from single-cell RNA-seq profiling. *BMC Genomics*, 17 Suppl 7:508, August 2016. ISSN 1471-2164. doi: 10.1186/s12864-016-2897-6.

Thomas Euler, Silke Haverkamp, Timm Schubert, and Tom Baden. Retinal bipolar cells: Elementary building blocks of vision. *Nature Reviews Neuroscience*, 15(8):507–519, August 2014. ISSN 1471-0048. doi: 10.1038/nrn3783.

Fangxiang Feng, Xiaojie Wang, and Ruifan Li. Cross-modal Retrieval with Correspondence Autoencoder. In *Proceedings of the 22nd ACM International Conference on Multimedia*, MM '14, pp. 7–16, Orlando, Florida, USA, November 2014. Association for Computing Machinery. ISBN 978-1-4503-3063-3. doi: 10.1145/2647868.2654902.

R. A. Fisher. The Use of Multiple Measurements in Taxonomic Problems. *Annals of Eugenics*, 7 (2):179–188, 1936. ISSN 2050-1439. doi: 10.1111/j.1469-1809.1936.tb02137.x.

Ronald Aylmer Fisher. *The Correlation between Relatives on the Supposition of Mendelian Inheritance*. Royal Society of Edinburgh], 1918.

Rohan Gala, Nathan Gouwens, Zizhen Yao, Agata Budzillo, Osnat Penn, Bosiljka Tasic, Gabe Murphy, Hongkui Zeng, and Uygar Sümbül. A coupled autoencoder approach for multi-modal analysis of cell types. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d\textquotesingle Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 9267–9276. Curran Associates, Inc., 2019.

Benyamin Ghojogh, Fakhri Karray, and Mark Crowley. Eigenvalue and Generalized Eigenvalue Problems: Tutorial. *arXiv:1903.11240 [cs, stat]*, March 2019. Comment: 8 pages, Tutorial paper.

Nathan W. Gouwens, Staci A. Sorensen, Jim Berg, Changkyu Lee, Tim Jarsky, Jonathan Ting, Susan M. Sunkin, David Feng, Costas A. Anastassiou, Eliza Barkan, Kris Bickley, Nicole Blesie, Thomas Braun, Krissy Brouner, Agata Budzillo, Shiella Caldejon, Tamara Casper, Dan Castelli, Peter Chong, Kirsten Crichton, Christine Cuhaciyan, Tanya L. Daigle, Rachel Dalley, Nick Dee, Tsega Desta, Song-Lin Ding, Samuel Dingman, Alyse Doperalski, Nadezhda Dotson, Tom Egdorf, Michael Fisher, Rebecca A. de Frates, Emma Garren, Marissa Garwood, Amanda Gary, Nathalie Gaudreault, Keith Godfrey, Melissa Gorham, Hong Gu, Caroline Habel, Kristen Hadley, James Harrington, Julie A. Harris, Alex Henry, DiJon Hill, Sam Josephsen, Sara Kebede, Lisa Kim, Matthew Kroll, Brian Lee, Tracy Lemon, Katherine E. Link, Xiaoxiao Liu, Brian Long, Rusty Mann, Medea McGraw, Stefan Mihalas, Alice Mukora, Gabe J. Murphy, Lindsay Ng, Kiet Ngo, Thuc Nghi Nguyen, Philip R. Nicovich, Aaron Oldre, Daniel Park, Sheana Parry, Jed Perkins, Lydia Potekhina, David Reid, Miranda Robertson, David Sandman, Martin Schroedter, Cliff Slaughterbeck, Gilberto Soler-Llavina, Josef Sulc, Aaron Szafer, Bosiljka Tasic, Naz Taskin, Corinne Teeter, Nivretta Thatra, Herman Tung, Wayne Wakeman, Grace Williams, Rob Young, Zhi Zhou, Colin Farrell, Hanchuan Peng, Michael J. Hawrylycz, Ed Lein, Lydia Ng, Anton Arkhipov, Amy Bernard, John W. Phillips, Hongkui Zeng, and Christof Koch. Classification of electrophysiological and morphological neuron types in the mouse visual cortex. *Nat. Neurosci.*, 22(7):1182–1195, July 2019. ISSN 1546-1726. doi: 10.1038/s41593-019-0417-0.

G. E. Hinton and R. R. Salakhutdinov. Reducing the Dimensionality of Data with Neural Networks. *Science*, 313(5786):504–507, July 2006. ISSN 0036-8075, 1095-9203. doi: 10.1126/science. 1127647.

Thomas Hofmann, Bernhard Schölkopf, and Alexander J. Smola. Kernel methods in machine learning. *Ann. Statist.*, 36(3):1171–1220, June 2008. ISSN 0090-5364. doi: 10.1214/009053607000000677. Comment: Published in at http://dx.doi.org/10.1214/009053607000000677 the Annals of Statistics (http://www.imstat.org/aos/) by the Institute of Mathematical Statistics (http://www.imstat.org).

Harold Hotelling. RELATIONS BETWEEN TWO SETS OF VARIATES. *Biometrika*, 28(3-4): 321–377, December 1936. ISSN 0006-3444. doi: 10.1093/biomet/28.3-4.321.

Theofanis Karaletsos, Serge Belongie, and Gunnar Rätsch. Bayesian representation learning with oracle constraints. *arXiv:1506.05011 [cs, stat]*, March 2016. Comment: 16 pages, publishes in ICLR 16.

Durk P Kingma, Shakir Mohamed, Danilo Jimenez Rezende, and Max Welling. Semi-supervised Learning with Deep Generative Models. In Z. Ghahramani, M. Welling, C. Cortes, N. D. Lawrence, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 27*, pp. 3581–3589. Curran Associates, Inc., 2014.

Tejas D Kulkarni, William F. Whitney, Pushmeet Kohli, and Josh Tenenbaum. Deep Convolutional Inverse Graphics Network. In C. Cortes, N. D. Lawrence, D. D. Lee, M. Sugiyama, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 28*, pp. 2539–2547. Curran Associates, Inc., 2015.

Yerbol Z Kurmangaliyev, Juyoun Yoo, Samuel A LoCascio, and S Lawrence Zipursky. Modular transcriptional programs separately define axon and dendrite connectivity. *eLife*, 8:e50822, November 2019. ISSN 2050-084X. doi: 10.7554/eLife.50822.

Evan Z. Macosko, Anindita Basu, Rahul Satija, James Nemesh, Karthik Shekhar, Melissa Goldman, Itay Tirosh, Allison R. Bialas, Nolan Kamitaki, Emily M. Martersteck, John J. Trombetta, David A. Weitz, Joshua R. Sanes, Alex K. Shalek, Aviv Regev, and Steven A. McCarroll. Highly parallel genome-wide expression profiling of individual cells using nanoliter droplets. *Cell*, 161 (5):1202–1214, May 2015. ISSN 0092-8674. doi: 10.1016/j.cell.2015.05.002.

H. Craig Mak and Quincey Justman. Genotype-Phenotype Mapping Meets Single Cell Biology. *Cell Systems*, 4(1):1–2, January 2017. ISSN 24054712. doi: 10.1016/j.cels.2017.01.008.

Geoffrey McLachlan. *Discriminant Analysis and Statistical Pattern Recognition*. Wiley-Interscience, Hoboken, N.J, August 2004. ISBN 978-0-471-69115-0.

Seung Wook Oh, Julie A. Harris, Lydia Ng, Brent Winslow, Nicholas Cain, Stefan Mihalas, Quanxin Wang, Chris Lau, Leonard Kuan, Alex M. Henry, Marty T. Mortrud, Benjamin Ouellette, Thuc Nghi Nguyen, Staci A. Sorensen, Clifford R. Slaughterbeck, Wayne Wakeman, Yang Li, David Feng, Anh Ho, Eric Nicholas, Karla E. Hirokawa, Phillip Bohn, Kevin M. Joines, Hanchuan Peng, Michael J. Hawrylycz, John W. Phillips, John G. Hohmann, Paul Wohnoutka, Charles R. Gerfen, Christof Koch, Amy Bernard, Chinh Dang, Allan R. Jones, and Hongkui Zeng. A mesoscale connectome of the mouse brain. *Nature*, 508(7495):207–214, April 2014. ISSN 1476-4687. doi: 10.1038/nature13186.

Shristi Pandey, Karthik Shekhar, Aviv Regev, and Alexander F. Schier. Comprehensive Identification and Spatial Mapping of Habenular Neuronal Types Using Single-Cell RNA-Seq. *Curr. Biol.*, 28 (7):1052–1065.e7, April 2018. ISSN 1879-0445. doi: 10.1016/j.cub.2018.02.040.

Yi-Rong Peng, Karthik Shekhar, Wenjun Yan, Dustin Herrmann, Anna Sappington, Gregory S. Bryman, Tavé van Zyl, Michael Tri. H. Do, Aviv Regev, and Joshua R. Sanes. Molecular Classification and Comparative Taxonomics of Foveal and Peripheral Cells in Primate Retina. *Cell*, 176 (5):1222–1237.e22, February 2019. ISSN 0092-8674. doi: 10.1016/j.cell.2019.01.004.

Filipe Pinto-Teixeira, Clara Koo, Anthony Michael Rossi, Nathalie Neriec, Claire Bertet, Xin Li, Alberto Del-Valle-Rodriguez, and Claude Desplan. Development of Concurrent Retinotopic Maps in the Fly Motion Detection Circuit. *Cell*, 173(2):485–498.e11, April 2018. ISSN 0092-8674. doi: 10.1016/j.cell.2018.02.053.

Karl Ridgeway and Michael C Mozer. Learning Deep Disentangled Embeddings With the F-Statistic Loss. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 185–194. Curran Associates, Inc., 2018.

Joshua R. Sanes and Richard H. Masland. The types of retinal ganglion cells: Current status and implications for neuronal classification. *Annu. Rev. Neurosci.*, 38:221–246, July 2015. ISSN 1545-4126. doi: 10.1146/annurev-neuro-071714-034120.

Karthik Shekhar, Sylvain W. Lapan, Irene E. Whitney, Nicholas M. Tran, Evan Z. Macosko, Monika Kowalczyk, Xian Adiconis, Joshua Z. Levin, James Nemesh, Melissa Goldman, Steven A. McCarroll, Constance L. Cepko, Aviv Regev, and Joshua R. Sanes. COMPREHENSIVE CLASSIFICATION OF RETINAL BIPOLAR NEURONS BY SINGLE-CELL TRANSCRIPTOMICS. *Cell*, 166(5):1308–1323.e30, August 2016. ISSN 0092-8674. doi: 10.1016/j.cell.2016.07.054.

David Sprinzak and Michael B. Elowitz. Reconstruction of genetic circuits. *Nature*, 438(7067): 443–448, November 2005. ISSN 0028-0836, 1476-4687. doi: 10.1038/nature04335.

Kean Ming Tan, Zhaoran Wang, Han Liu, and Tong Zhang. Sparse generalized eigenvalue problem: Optimal statistical rates via truncated Rayleigh flow. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 80(5):1057–1086, 2018. ISSN 1467-9868. doi: 10.1111/rssb. 12291.

Bosiljka Tasic, Vilas Menon, Thuc Nghi Nguyen, Tae Kyung Kim, Tim Jarsky, Zizhen Yao, Boaz Levi, Lucas T. Gray, Staci A. Sorensen, Tim Dolbeare, Darren Bertagnolli, Jeff Goldy, Nadiya Shapovalova, Sheana Parry, Changkyu Lee, Kimberly Smith, Amy Bernard, Linda Madisen, Susan M. Sunkin, Michael Hawrylycz, Christof Koch, and Hongkui Zeng. Adult mouse cortical cell taxonomy revealed by single cell transcriptomics. *Nat. Neurosci.*, 19(2):335–346, February 2016. ISSN 1546-1726. doi: 10.1038/nn.4216.

Bosiljka Tasic, Zizhen Yao, Lucas T. Graybuck, Kimberly A. Smith, Thuc Nghi Nguyen, Darren Bertagnolli, Jeff Goldy, Emma Garren, Michael N. Economo, Sarada Viswanathan, Osnat Penn, Trygve Bakken, Vilas Menon, Jeremy Miller, Olivia Fong, Karla E. Hirokawa, Kanan Lathia, Christine Rimorin, Michael Tieu, Rachael Larsen, Tamara Casper, Eliza Barkan, Matthew Kroll, Sheana Parry, Nadiya V. Shapovalova, Daniel Hirschstein, Julie Pendergraft, Heather A. Sullivan, Tae Kyung Kim, Aaron Szafer, Nick Dee, Peter Groblewski, Ian Wickersham, Ali Cetin, Julie A. Harris, Boaz P. Levi, Susan M. Sunkin, Linda Madisen, Tanya L. Daigle, Loren Looger, Amy Bernard, John Phillips, Ed Lein, Michael Hawrylycz, Karel Svoboda, Allan R. Jones, Christof Koch, and Hongkui Zeng. Shared and distinct transcriptomic cell types across neocortical areas. *Nature*, 563(7729):72–78, November 2018. ISSN 1476-4687. doi: 10.1038/s41586-018-0654-5.

Nicholas M. Tran, Karthik Shekhar, Irene E. Whitney, Anne Jacobi, Inbal Benhar, Guosong Hong, Wenjun Yan, Xian Adiconis, McKinzie E. Arnold, Jung Min Lee, Joshua Z. Levin, Dingchang Lin, Chen Wang, Charles M. Lieber, Aviv Regev, Zhigang He, and Joshua R. Sanes. Single-cell profiles of retinal neurons differing in resilience to injury reveal neuroprotective genes. *bioRxiv*, pp. 711762, July 2019. doi: 10.1101/711762.

Weiran Wang, Raman Arora, Karen Livescu, and Jeff Bilmes. On Deep Multi-View Representation Learning. pp. 10, 2015.

Hongkui Zeng and Joshua R. Sanes. Neuronal cell-type classification: Challenges, opportunities and the path forward. *Nature Reviews Neuroscience*, 18(9):530–546, September 2017. ISSN 1471-0048. doi: 10.1038/nrn.2017.85.

# 9 ADDITIONAL INFORMATION

Table 1: MI and EV metrics measured from FLDA on the synthesized data

| Sigma | 0.2 | 0.4 | 0.6 | 0.8 | 1 |
|---|---|---|---|---|---|
| EV_i of FLD_i | 0.94915015 | 0.89798334 | 0.83949665 | 0.75799516 | 0.66325434 |
| EV_i of FLD_j | 0.03684044 | 0.04535285 | 0.02913673 | 0.01936836 | 0.01216407 |
| EV_j of FLD_i | 0.03665295 | 0.04499388 | 0.02981225 | 0.02231451 | 0.01190785 |
| EV_j of FLD_j | 0.94874927 | 0.89794858 | 0.82187076 | 0.74982447 | 0.65690059 |
| I(i, FLD_i) | 0.99360769 | 0.99308033 | 0.95913323 | 0.86075507 | 0.71272067 |
| I(i, FLD_j) | 0.49493103 | 0.29995192 | 0.13954508 | 0.07809956 | 0.0735689 |
| I(j, FLD_i) | 0.4643901 | 0.28223236 | 0.15676406 | 0.090115 | 0.07770875 |
| I(j, FLD_j) | 0.99298066 | 0.98740331 | 0.94179684 | 0.85538379 | 0.73796543 |

Table 2: MI and EV metrics measured from LDA on the synthesized data

| Sigma | 0.2 | 0.4 | 0.6 | 0.8 | 1 |
|---|---|---|---|---|---|
| EV_i of LD1 | 0.48776682 | 0.45116523 | 0.52330355 | 0.42727731 | 0.36337134 |
| EV_i of LD2 | 0.4769204 | 0.44081294 | 0.30780529 | 0.31653726 | 0.28491596 |
| EV_j of LD1 | 0.51329241 | 0.51243319 | 0.36741921 | 0.3870769 | 0.33454171 |
| EV_j of LD2 | 0.44470966 | 0.36777595 | 0.44296763 | 0.32343567 | 0.31095979 |
| I(i, LD1) | 0.69454784 | 0.61907025 | 0.62994902 | 0.49166244 | 0.40109236 |
| I(i, LD2) | 0.62289375 | 0.53809337 | 0.4029431 | 0.35690019 | 0.32147905 |
| I(j, LD1) | 0.69392081 | 0.63928958 | 0.50496945 | 0.46318049 | 0.38186588 |
| I(j, LD2) | 0.6015657 | 0.46221964 | 0.47571376 | 0.37019437 | 0.32035017 |

Table 3: MI and EV metrics measured from "2LDAs" on the synthesized data

| Sigma | 0.2 | 0.4 | 0.6 | 0.8 | 1 |
|---|---|---|---|---|---|
| EV_i of LD_i | 0.97822626 | 0.92099596 | 0.85186621 | 0.76552256 | 0.66916737 |
| EV_i of LD_j | 0.00520168 | 0.0094905 | 0.00939646 | 0.00952869 | 0.00696314 |
| EV_j of LD_i | 0.0052024 | 0.00949837 | 0.00899499 | 0.00894616 | 0.00682767 |
| EV_j of LD_j | 0.97847676 | 0.92212988 | 0.83392262 | 0.75588205 | 0.66316636 |
| I(i, LD_i) | 0.99360769 | 0.99508033 | 0.96055224 | 0.87531047 | 0.73704612 |
| I(i, LD_j) | 0.02950921 | 0.0507909 | 0.07132031 | 0.06210625 | 0.0596176 |
| I(j, LD_i) | 0.02903845 | 0.06752955 | 0.08387487 | 0.06548498 | 0.06164337 |
| I(j, LD_j) | 0.99298066 | 0.9901582 | 0.95036543 | 0.86578835 | 0.74189911 |

Table 4: Metrics measured from FLDA, LDA and "2LDAs" on the dataset of T4/T5 neurons

| Model | Axis | SNR | EV_i | EV_j | I(i, u) | I(j, u) | Modularity |
|---|---|---|---|---|---|---|---|
| FLDA | FLD_i | 47.4564008 | 0.94162107 | 2.09E-05 | 0.99569955 | 0.07323188 | 0.99459067 |
| | FLD_j_1 | 17.7680626 | 4.54E-07 | 0.97893759 | 0.01658397 | 0.99800712 | 0.99972387 |
| | FLD_j_2 | 13.6348569 | 0.00013746 | 0.9284645 | 0.021246 | 1.18348086 | 0.99967772 |
| | FLD_j_3 | 4.56306359 | 8.80E-06 | 0.81863597 | 0.005781 | 0.94962958 | 0.99996294 |
| LDA | LD1 | 48.1795978 | 5.90E-05 | 0.97886064 | 0.02388284 | 0.99721706 | 0.99942642 |
| | LD2 | 18.2363587 | 0.91313834 | 0.01478499 | 0.99070727 | 0.31637137 | 0.89802267 |
| | LD3 | 14.0169217 | 0.02411206 | 0.91574871 | 0.0954478 | 1.23712486 | 0.99404743 |
| | LD4 | 4.64123888 | 0.00255638 | 0.74248468 | 0.07747796 | 0.90405973 | 0.9926555 |
| 2LDAs | LD_i | 47.3372616 | 0.94562164 | 0.00209149 | 0.99404336 | 0.01173126 | 0.99986072 |
| | LD_j_1 | 17.4834949 | 0.00034269 | 0.97930546 | 0.00253984 | 1.00479664 | 0.99999361 |
| | LD_j_2 | 13.7035177 | 0.00166572 | 0.93166886 | 0.0050279 | 1.27791532 | 0.99998452 |
| | LD_j_3 | 4.57167846 | 0.00011007 | 0.82006091 | 0.0038557 | 1.06683083 | 0.99998694 |

Figure 5: Additional plots for FLDA on the dataset of T4/T5 neurons. (A, B) Projection of the original gene expression data into the two-dimensional space made of the first and second (FLD$_{ij1}$ and FLD$_{ij2}$) (A) or the second and third (FLD$_{ij2}$ and FLD$_{ij3}$) (B) discriminant axes for the component that depends on the combination of both features $i$ and $j$. Different cell types are indicated in different colors as in (B).

Figure 6: Additional plots for critical genes extracted from the sparse algorithm. (A) Weight vector of the 20 genes selected for the interaction of both dendritic and axonal features (FLD$_{ij1}$). The weight value is indicated in the color bar with color indicating direction (red: positive and green: negative) and saturation indicating magnitude. (B) Expression patterns of the 20 genes from (A) in eight types of T4/T5 neurons. Dot size indicates the percentage of cells in which the gene was expressed, and color represents average scaled expression.