On the Importance of Adaptive Data Collection for Extremely Imbalanced Pairwise Tasks

Abstract

Many pairwise classification tasks, such as paraphrase detection and open-domain question answering, naturally have extreme label imbalance (e.g., 99.99% of examples are negatives). In contrast, many recent datasets heuristically choose examples to ensure label balance. We show that these heuristics lead to trained models that generalize poorly: State-of-the art models trained on QQP and WikiQA have only 2.4% and 2.4% average precision, respectively, when evaluated on realistically imbalanced test data. We instead collect training data with active learning, using a BERT-based embedding model to efficiently retrieve uncertain points from a very large pool of unlabeled utterance pairs. By creating balanced training data with more informative negative examples, active learning greatly improves average precision to 32.5% on QQP and 20.1% and WikiQA.

1 Introduction

Many NLP tasks can be formulated as pairwise classification tasks with a natural extreme label imbalance (e.g., 99.99% of examples have the same label). In question deduplication (Iyer et al., 2017), the vast majority of pairs of questions from an online forum are not duplicates. In open-domain question answering (Yang et al., 2015; Lee et al., 2019), almost any randomly sampled document will not answer a given question. Random pairs of sentences from a diverse distribution will have no relation between them in natural language inference (Bowman et al., 2015), as opposed to an entailment or contradiction relationship.

While past work has recognized the importance of label imbalance in NLP (Lewis et al., 2004; Chawla et al., 2004), many recently released datasets are heuristically collected to ensure label balance, generally for ease of training. For instance,

Figure 1: In this diagram, we see two options for training and evaluation, and the standard framework and our pool-based active learning framework examined in this work.

the Quora Question Pairs (QQP) dataset (Iyer et al., 2017) was generated by mining non-duplicate questions that were heuristically determined to be near-duplicates. The SNLI dataset had crowd-workers generate inputs to match a specified label distribution (Bowman et al., 2015). In this work, we show that models trained on heuristically balanced datasets deal poorly with natural label imbalance at test time: They have very low average precision on realistically imbalanced test data created by taking all pairs of in-domain utterances.

Instead of heuristically producing static training datasets, we study adaptive data collection methods. In particular, we apply the pool-based active learning framework (Settles, 2009) to extremely imbalanced pairwise tasks. At train time, the system has *query access* to (i.e., the ability to label a limited subset of) a large unlabeled dataset formed by taking all utterance pairs from a set of training utterances. For example, in the question deduplication setting, we might have a budget to annotate pairs of questions as "duplicate" or "not duplicate," and wish to train a model on this data to find new duplicate pairs with high precision.

Data collection for extremely imbalanced pair-

wise tasks is challenging because the pool of unlabeled examples is very large (as it grows quadratically in the number of utterances) and very few of the examples are positive. We collect balanced training data using uncertainty sampling, an adaptive method that queries labels for examples on which a model trained on previously queried data has high uncertainty (Lewis and Gale, 1994). To lower the computational cost of searching for uncertain points, we propose combining active learning with a BERT embedding model for which uncertain points can be located efficiently using nearest neighbor search.

Empirically, we show that our use of adaptive data collection yields significant gains over static heuristics. Uncertainty sampling with our BERT embedding model achieves 32.5% and 20.1% average precision for QQP and WikiQA, respectively. In contrast, state-of-the-art models trained on the original heuristically collected data only have average precision of 2.4% and 2.4%, respectively.

2 Setting

In this work, we study binary classification with an input space $\mathcal{X}$ and output space $\{0, 1\}$. We assume the label y is a deterministic function of x, which we write $y(x)$. A classification model p_θ yields probability estimates $p_\theta(y \mid x)$ where $x \in \mathcal{X}$.

Our setting has two aspects: the way training data is collected via label queries (Section 2.1) and the way we evaluate the model $p_\theta(y \mid x)$ by measuring average precision (Section 2.2). This work focuses on pairwise tasks (Section 2.3), which enables efficient active learning (Section 4).

2.1 Data collection

In our setting, a system is given an unlabeled dataset $D_{\text{all}}^{\text{train}} \subseteq \mathcal{X}$. The system can query an input $x \in D_{\text{all}}^{\text{train}}$ and receive the corresponding label $y(x)$. The system is given a budget of n queries to build a labeled training dataset of size n.

2.2 Evaluation

Following standard practice for imbalanced tasks, we evaluate on precision, recall, and average precision (Lewis, 1995; Manning et al., 2008). A scoring function $S : \mathcal{X} \to \mathbb{R}$ (e.g., $S(x) = p_\theta(y = 1 \mid x)$) is used to rank examples x, where an ideal S assigns all positive examples $\{x : y(x) = 1\}$ a higher score than all negative examples $\{x : y(x) = 0\}$. Given a test dataset $D_{\text{all}}^{\text{test}} \subseteq \mathcal{X}$, define the number

of true positives, false positives, and false negatives of a scoring function S at a threshold γ as:

$$\text{TP}(S, \gamma) = \sum_{x \in D_{\text{all}}^{\text{test}}} \mathbf{1}[y(x) = 1 \wedge S(x) \geq \gamma] \quad (1)$$

$$\text{FP}(S, \gamma) = \sum_{x \in D_{\text{all}}^{\text{test}}} \mathbf{1}[y(x) = 0 \wedge S(x) \geq \gamma] \quad (2)$$

$$\text{FN}(S, \gamma) = \sum_{x \in D_{\text{all}}^{\text{test}}} \mathbf{1}[y(x) = 1 \wedge S(x) < \gamma]. \quad (3)$$

For any threshold γ, define the precision $P(S, \gamma)$ and recall $R(S, \gamma)$ of a scoring function S as:

$$\text{P}(S, \gamma) = \frac{\text{TP}(S, \gamma)}{\text{TP}(S, \gamma) + \text{FP}(S, \gamma)} \quad (4)$$

$$\text{R}(S, \gamma) = \frac{\text{TP}(S, \gamma)}{\text{TP}(S, \gamma) + \text{FN}(S, \gamma)}. \quad (5)$$

Let $\Gamma = \{S(x) : x \in D_{\text{all}}^{\text{test}}\}$ be the scores of the dataset. By sweeping over all values Γ in descending order, we trace out the precision-recall curve. The area under the precision recall curve or average precision (AP) is defined as:

$$\text{AP}(S) = \sum_{i=1}^{|\Gamma|} (\text{R}(S, \gamma_i) - \text{R}(S, \gamma_{i-1}))\text{P}(S, \gamma_i),$$
$$(6)$$

where $\gamma_0 = \infty$ and $\gamma_1 > \gamma_2 > \ldots \gamma_{|\Gamma|}$ and $\gamma_i \in \Gamma$.

Note that high precision requires very high accuracy when the task is extremely imbalanced. For example, if only one in $10,000$ examples in $D_{\text{all}}^{\text{test}}$ is positive and 50% precision at some recall is achieved, that implies 99.99% accuracy.

2.3 Pairwise tasks

In this work, we focus on "pairwise" tasks, meaning that the input space decomposes as $\mathcal{X} = \mathcal{X}_1 \times \mathcal{X}_2$. For instance, $\mathcal{X}_1$ could be questions and $\mathcal{X}_2$ could be paragraphs for open-domain question answering, and $\mathcal{X}_1 = \mathcal{X}_2$ could be questions for question deduplication. We create the unlabeled *all-pairs* training set $D_{\text{all}}^{\text{train}}$ by sampling $D_1^{\text{train}} \subseteq \mathcal{X}_1$ and $D_2^{\text{train}} \subseteq \mathcal{X}_2$, and define $D_{\text{all}}^{\text{train}} = D_1^{\text{train}} \times D_2^{\text{train}}$. We follow a similar procedure to form the all-pairs test set: $D_{\text{all}}^{\text{test}} = D_1^{\text{test}} \times D_2^{\text{test}}$ where $D_1^{\text{test}} \subseteq \mathcal{X}_1$ and $D_2^{\text{test}} \subseteq \mathcal{X}_2$. We ensure that the train and test sets are disjoint by ensuring $D_1^{\text{train}} \cap D_1^{\text{test}} = \varnothing$ and $D_2^{\text{train}} \cap D_2^{\text{test}} = \varnothing$.

Many pairwise tasks require high average precision on all-pairs test data. A question deduplication

system must compare a new question with all previously asked questions to determine if a duplicate exists. An open-domain question-answering system must search through all available documents for one that answers the question. In both cases, the all-pairs distribution is extremely imbalanced, as the vast majority of pairs are negatives, while standard datasets are artificially balanced.

3 Results training on heuristic datasets

In this section, we show that state-of-the-art models trained on two standard pairwise classification datasets—QQP and WikiQA—do not generalize well to our extremely imbalanced all-pairs test data. Both QQP and WikiQA were collected using static heuristics that attempt to find points $x \in \mathcal{X}$ that are more likely to be positive. These heuristics are necessary because uniformly sampling from $\mathcal{X}$ is impractical due to the label imbalance: if the proportion of positives is 10^{-4}, then random sampling would have to label 10,000 examples on average to find one positive example. Standard models can achieve high test accuracy on test data collected with these heuristics, but fare poorly when evaluated on all-pairs data derived from the data source (Section 3.2). Manual inspection confirms that these models often make surprising false positive errors (Section 3.3).

3.1 Experimental setup

3.1.1 Evaluation

We evaluate models on both in-distribution test data and our imbalanced all-pairs test data.

In-distribution evaluation. Let D_{pos} denote the set of all positive examples, and $D_{\text{statedneg}}$ denote the set of *stated negative examples*—negative examples in the original heuristically collected dataset. We define the stated test dataset $D_{\text{heur}}^{\text{test}}$ as $(D_{\text{pos}} \cup D_{\text{statedneg}}) \cap D_{\text{all}}^{\text{test}}$. We use task-specific evaluation metrics described in the next section.

All-pairs evaluation. All-pairs evaluation metrics depend on the label of every pair in $D_{\text{all}}^{\text{test}}$. We approximate these labels by imputing (possibly noisy) labels on all pairs using the available labeled data, as described in the next section.[1] In Section 3.3, we manually label examples to confirm our results from this automatic evaluation.

Computing the number of false positives $\text{FP}(S, \gamma)$ requires enumerating all negative examples in $D_{\text{all}}^{\text{test}}$, which is too computationally expensive with our datasets. To get an unbiased estimate of $\text{FP}(S, \gamma)$, we could randomly downsample $D_{\text{all}}^{\text{test}}$, but the resulting estimator has high variance. We instead propose a novel unbiased estimator that uses importance sampling. In particular, we combine counts of errors on a set of "nearby negative" examples $D_{\text{near}}^{\text{test}} \subseteq D_{\text{all}}^{\text{test}}$, pairs of similar utterances on which we expect more false positives to occur, and random negatives $D_{\text{rand}}^{\text{test}}$ sampled uniformly from negatives in $D_{\text{all}}^{\text{test}} \setminus D_{\text{near}}^{\text{test}}$. Details are provided in Appendix A.2.

3.1.2 Datasets

Quora Question Pairs (QQP). The task for QQP (Iyer et al., 2017) is to determine whether two questions are paraphrases. The non-paraphrase pairs in the dataset were chosen heuristically, e.g., by finding questions on similar topics. We impute labels on all question pairs by assuming that two questions are paraphrases if and only if they are equivalent under the transitive closure of the equivalence relation defined by the labeled paraphrase pairs.[2] We randomly partition all unique questions into train, dev, and test splits D_1^{train}, D_1^{dev}, and D_1^{test}, ensuring that no two questions that were paired (either in positive or negative examples) in the original dataset end up in different splits. Since every question is trivially a paraphrase of itself, we define $D_{\text{all}}^{\text{train}}$ as the set of *distinct* pairs of questions in D_1^{train}, and define $D_{\text{all}}^{\text{dev}}$ and $D_{\text{all}}^{\text{test}}$ analogously. For in-distribution evaluation, we report accuracy and F1 score on $D_{\text{heur}}^{\text{test}}$, as in Wang et al. (2019).

WikiQA. The task for WikiQA (Yang et al., 2015) is to determine whether a question is answered by a given sentence. The dataset only includes examples that pair a question with sentences from a Wikipedia article believed to be relevant based on click logs. We impute labels by assuming that question-sentence pairs not labeled in the dataset are negative. We partition the questions into D_1^{train}, D_1^{dev}, and D_1^{test}, following the original question-based split of the dataset, and define $D_2^{\text{train}} = D_2^{\text{dev}} = D_2^{\text{test}}$ to be the set of all sentences in the dataset. For all WikiQA models, we prepend the title of the source article to the sentence to give

---

[1] In practice, precision can be estimated by labeling predicted positives, and recall can be estimated with respect to a non-exhaustive set of known positives (Harman, 1992; Ji et al., 2011).

[2] Using the transitive closure increases the total number of positives from 149,263 to 228,548, so this adds many positives but does not overwhelm the original data.

Split	Positives	Total pairs	Ratio	Stated Neg.	Nearby Neg.
QQP					
Train	124,625	38B	1:300k	132,796	-
Dev	60,510	8.8B	1:150k	61,645	13.1M
Test	43,413	8.5B	1:190k	60,575	12.8M
WikiQA					
Train	1,040	56M	1:53k	19,320	-
Dev	140	7.8M	1:56k	2,593	29,511
Test	293	17M	1:57k	5,872	63,136

Table 1: Statistics of our QQP and WikiQA splits.

QQP	In-distribution		All pairs	
	Accuracy	F1	P@R20	AP
BERT	82.5%	77.3%	3.0%	2.4%
XLNet	83.0%	77.9%	1.7%	1.4%
RoBERTa	84.4%	80.2%	2.5%	2.0%
ALBERT	79.6%	73.0%	3.5%	1.9%

WikiQA	c-MAP	a-F1	P@R=20	AP
BERT	79.9%	45.9%	6.5%	2.4%
XLNet	80.5%	46.7%	1.0%	1.0%
RoBERTa	84.6%	53.6%	3.4%	2.3%
ALBERT	78.2%	41.8%	0.7%	0.9%

Table 2: State-of-the-art CONCAT models trained on heuristically collected data generalize to test data from the same distribution, but not to all-pairs data.

the model information about the sentence's origin, as in Lee et al. (2019).

For in-distribution evaluation, we report two evaluation metrics. Following standard practice, we report clean mean average precision (c-MAP), defined as MAP over "clean" test questions—questions that are involved in both a positive and negative example in $D_{\text{heur}}^{\text{test}}$ (Garg et al., 2020). We also report F1 score across all examples in $D_{\text{heur}}^{\text{test}}$ (a-F1), which unlike c-MAP evaluates knowing when a question has an answer. This introduces more label imbalance, as positives make up 6% of $D_{\text{heur}}^{\text{test}}$ but 12% of clean examples. The original WikiQA paper advocated a-F1 (Yang et al., 2015), but most subsequent papers do not report it (Shen et al., 2017; Yoon et al., 2019; Garg et al., 2020).

Data statistics. Table 1 shows dataset statistics. Models in this section are trained on the *stated training dataset* $D_{\text{heur}}^{\text{train}} \triangleq (D_{\text{pos}} \cup D_{\text{statedneg}}) \cap D_{\text{all}}^{\text{train}}$, the set of all positives and heuristic negatives in the train split. For all-pairs evaluation, both QQP and WikiQA have extreme label imbalance: Positive examples make up between 1 in 50,000 (WikiQA) and 1 in 200,000 (QQP) of the test examples.

3.1.3 Models

We train four state-of-the-art models that use BERT-base (Devlin et al., 2019), XLNet-base (Yang et al., 2019), RoBERTa-base (Liu et al., 2019), and ALBERT-base-v2 (Lan et al., 2020), respectively. As is standard, all models receive as input the concatenation of x_1 and x_2; we refer to these as concatenation-based (CONCAT) models. We train on binary cross-entropy loss for 2 epochs on QQP and 3 epochs on WikiQA, chosen to maximize dev all-pairs AP for RoBERTa. We report the average over three random seeds for training.

3.2 Evaluation results

As shown in Table 2, state-of-the-art models trained only on stated training data do well on balanced in-distribution test data but poorly on the extremely imbalanced all-pairs test data. On QQP, the best model gets 80.2% F1 on in-distribution test examples.[3] However, on all-pairs test data, the best model can only reach 3.5% precision at a modest 20% recall. On WikiQA, our best c-MAP of 84.6% is higher than the best previously reported c-MAP without using additional question-answering data, 83.6% (Garg et al., 2020). However, on all-pairs test data, the best model gets 6.5% precision at 20% recall. All-questions F1 on in-distribution data is also quite low, with the best model only achieving 53.6%. Since a-F1 evaluates on a more imbalanced distribution than c-MAP, this further demonstrates that state-of-the-art models deal poorly with test-time label imbalance. Compared with a-F1, all-pairs evaluation additionally shows that models make many mistakes when evaluated on questions paired with less related sentences; these examples should be easier to identify as negatives, but are missing from $D_{\text{heur}}^{\text{train}}$.

3.3 Manual verification of imputed negatives

Since our results depend on automatically imputed negative labels, we manually labeled putative false positive errors—false positives as defined by our imputed labels—to more accurately estimate precision. We focused on the best QQP model and random seed combination on the development set,

---

[3]On the GLUE QQP train/dev split, our RoBERTa implementation gets 91.5% dev accuracy. Our in-domain accuracy numbers are lower due to our more challenging train/test split, as discussed in Appendix A.4

QQP, CONCATBERT trained on $D_{\text{heur}}^{\text{train}}$

x_1: *"How do I overcome **seasonal affective disorder**?"*
x_2 :*"How do I solve **puberty problem**?"*

x_1: *"What will **10000** A.D be like?"*
x_2 :*"Does not introduction of new **Rs.2000** notes ease carrying black money in future?"*

x_1: *"Can a person with no Coding knowledge learn **Machine learning**?"*
x_2: *"How do I learn **Natural Language Processing**?"*

WikiQA, CONCATBERT trained on $D_{\text{heur}}^{\text{train}}$

x_1: *"where does **limestone** form?"*
x_2: *"Glacier cave . A **glacier cave** is a cave formed within the ice of a glacier ."*

x_1: *"what is **gravy** made of?"*
x_2: *"**Amaretto**. It is made from a base of apricot pits or almonds, sometimes both."*

Figure 2: Examples of confident false positives from the all-pairs test distribution for models trained on examples from the original QQP and WikiQA datasets. Bold highlights non-equivalent phrases.

which got 8.2% precision at 20% recall.[4] For this recall threshold, we manually labeled 50 randomly chosen putative false positives from $D_{\text{near}}^{\text{dev}}$, and 50 more from $D_{\text{rand}}^{\text{dev}}$. We confirmed that 72% and 92%, respectively, were real false positive errors. Based on these results, we estimate the true precision of the model to be 9.5%, still close to our original estimate of 8.2%. See Appendix A.3 for more details.

Figure 2 shows false positive predictions at 20% recall for the best QQP and WikiQA models. For QQP, models often make surprising errors on pairs of unrelated questions (first two examples), as well as questions that are somewhat related but distinct (third example). For WikiQA, models often predict a positive label when something in the sentence has the same type as the answer to the question, even if the sentence and question are unrelated.

4 Active learning for pairwise tasks

As shown above, training on heuristically collected balanced data leads to low average precision on all pairs. How can we collect training data that leads to high average precision? We turn to active learning, in which new data is chosen adaptively based on previously collected data. Adaptivity allows us to ignore the vast majority of obvious negatives

---

[4] By manual inspection, QQP had more borderline cases than WikiQA, so we focused on QQP.

(unlike random sampling) and iteratively correct the errors of our model (unlike static data collection) by collecting more data around the model's decision boundary.

4.1 Active learning

Formally, an active learning method takes in an unlabeled dataset $D_{\text{all}}^{\text{train}} \subseteq \mathcal{X}$. Data is collected in a series of $k > 1$ rounds. For the i^{th} round, we choose a batch $B_i \subseteq D_{\text{all}}^{\text{train}}$ of size n_i and observe the outcome as the labels $\{(x, y(x)) : x \in B_i\}$. The budget n is the total number of points labeled, i.e., $n = \sum_{i=1}^{k} n_i$. This process is adaptive because we can choose batch B_i based on the labels of the previous $i - 1$ batches. Static data collection corresponds to setting $k = 1$.

Uncertainty sampling. The main active learning algorithm we use is uncertainty sampling (Lewis and Gale, 1994). Uncertainty sampling first uses a static data collection method to select the *seed set* B_1. For the next $k-1$ rounds, uncertainty sampling trains a model on all collected data and chooses B_i to be the n_i unlabeled points in $D_{\text{all}}^{\text{train}}$ on which the model is most uncertain. For binary classification, the most uncertain points are the points where $p_\theta(y = 1 \mid x)$ is closest to $\frac{1}{2}$. Note that a brute force approach to finding B_i requires evaluating p_θ on every example in $D_{\text{all}}^{\text{train}}$, which can be prohibitively expensive. In balanced settings, it suffices to choose the most uncertain point from a small random subset of $D_{\text{all}}^{\text{train}}$ (Ertekin et al., 2007); however, this strategy works poorly in extremely imbalanced settings, as a small random subset of $D_{\text{all}}^{\text{train}}$ is unlikely to contain any uncertain points. In Section 4.2, we address this computational challenge with a bespoke model architecture.

Adaptive retrieval. We also use a related algorithm we call adaptive retrieval, which is like uncertainty sampling but queries the n_i unlabeled points in $D_{\text{all}}^{\text{train}}$ with highest $p_\theta(y = 1 \mid x)$ (i.e., pairs the model is most confident are positive). Adaptive retrieval can be seen as greedily maximizing the number of positive examples collected.

4.2 Modeling and implementation

We now fully specify our approach by describing our model, how we find pairs in the unlabeled pool $D_{\text{all}}^{\text{train}}$ to query, and how we choose the seed set B_1. In particular, a key technical challenge is that the set of training pairs $D_{\text{all}}^{\text{train}}$ is too large to enumerate, as it grows quadratically. We therefore require

an efficient way to locate the uncertain points in $D_{\text{all}}^{\text{train}}$. We solve this problem with a model architecture COSINEBERT that enables efficient nearest neighbor search (Gillick et al., 2019).

4.2.1 Model

Given input $x = (x_1, x_2)$, COSINEBERT embeds x_1 and x_2 independently and predicts $p_\theta(y = 1 \mid x)$ based on vector-space similarity. More precisely,

$$p_\theta(y = 1 \mid x) = \sigma \left(w \cdot \frac{e_\theta(x_1) \cdot e_\theta(x_2)}{\|e_\theta(x_1)\|\|e_\theta(x_2)\|} + b \right), \tag{7}$$

where σ is the sigmoid function, $w > 0$ and b are learnable parameters, and $e_\theta : \mathcal{X}_1 \cup \mathcal{X}_2 \to \mathbb{R}^d$ is a learnable embedding function. In other words, we compute the cosine similarity of the embeddings of x_1 and x_2, and predict y using a logistic regression model with cosine similarity as its only feature. We define e_θ as the final layer output of a BERT model (Devlin et al., 2019) mean-pooled across all tokens (Reimers and Gurevych, 2019).[5] Gillick et al. (2019) used a similar model for entity linking.

4.2.2 Finding points to query

Next, we show how to choose the batch B_i of points to query, given a model $p_\theta(y \mid x)$ trained on data from batches $B_1, \ldots, B_{i-1}$. Recall that uncertainty sampling chooses the points x for which for which $p_\theta(y = 1 \mid x)$ is closest to $\frac{1}{2}$, and adaptive retrieval chooses the points x with largest $p_\theta(y = 1 \mid x)$. Since the set of positives is very small compared to the size of $D_{\text{all}}^{\text{train}}$, the set of uncertain points can be found by finding points with the largest $p_\theta(y = 1 \mid x)$, thus filtering out the confident negatives, and then selecting the most uncertain from those.

To find points with largest $p_\theta(y = 1 \mid x)$, we leverage the structure of our model. Since $w > 0$, $p_\theta(y = 1 \mid x)$ is increasing in the cosine similarity of $e_\theta(x_1)$ and $e_\theta(x_2)$. Therefore, it suffices to find pairs (x_1, x_2) that are nearest neighbors in the embedding space defined by e_θ. In particular, for each $x_1 \in \mathcal{X}_1$, we use the Faiss library (Johnson et al., 2017) to retrieve a set $N(x_1)$ containing the m nearest neighbors in $\mathcal{X}_2$, and define $D_{\text{close}}^{\text{train}}$ to be the set of all pairs (x_1, x_2) such that

---

[5]Although WikiQA involves an asymmetric relationship between questions and sentences, we use the same encoder for both. This is no less expressive than using separate encoders for each, as the set of questions and set of sentences are disjoint. For asymmetric tasks like NLI where $\mathcal{X}_1 = \mathcal{X}_2$, we would need to use separate encoders for the $\mathcal{X}_1$ and $\mathcal{X}_2$.

Method	QQP		WikiQA	
	P@R20	AP	P@R20	AP
Random	4.7%	2.8%	1.3%	1.3%
Stated data	29.3%	15.4%	0.7%	2.2%
Static Ret.	49.2%	25.1%	13.9%	8.2%
Adapt. Ret.	59.1%	32.4%	27.1%	15.1%
Uncertainty	**60.2%**	**32.5%**	**32.4%**	**20.1%**

Table 3: Main results comparing different data collection strategies on all three datasets. The two active learning methods, adaptive retrieval and uncertainty sampling, greatly outperform other methods.

$x_2 \in N(x_1)$. We then iterate through $D_{\text{close}}^{\text{train}}$ to find either the most uncertain points (for uncertainty sampling) or points with highest cosine similarity (for adaptive retrieval). Note that this method only requires $|D_1^{\text{train}}| + |D_2^{\text{train}}|$ embedding calls, rather than $|D_1^{\text{train}}| \cdot |D_2^{\text{train}}|$, the requirement for jointly embedding all pairs.

4.2.3 Choosing the seed set

To choose the seed set B_1, we use the pre-trained BERT model as the embedding e_θ and select the n_1 pairs with largest $p_\theta(y = 1 \mid x)$. Recall that $w > 0$, so this amounts to choosing the pairs with highest cosine similarity.

5 Active learning experiments

5.1 Experimental details

We collect $n_1 = 2048$ examples in the seed set, and use $k = 10$ rounds of active learning for QQP and $k = 4$ for WikiQA, as WikiQA is much smaller. At round i, we query $n_i = n_1 \cdot (3/2)^{i-1}$ new labels. These choices imply a total labeling budget n of 232,100 for QQP and 16,640 for WikiQA. For both datasets, n is slightly less than $|D_{\text{heur}}^{\text{train}}|$ (257,421 for QQP and 20,360 for WikiQA), thus ensuring a meaningful comparison with training on heuristic data. The exponentially growing n_i helps us avoid wasting queries in early rounds, when the model is worse, and also makes training faster in the early rounds. We retrieve $m = 1000$ nearest neighbors per $x_1 \in \mathcal{X}_1$ for QQP and $m = 100$ for WikiQA. We run all active learning experiments with three different random seeds and report the mean. Training details are given in Appendix A.

5.2 Main results

We now compare the two active learning methods, adaptive retrieval and uncertainty sampling, with training on $D_{\text{heur}}^{\text{train}}$ and two other baselines.

Positives Found	QQP	WikiQA
Random sampling	1	1
Static retrieval	16,422	169
Adaptive retrieval	**103,181**	**757**
Uncertainty sampling	87,594	742
Total examples collected	232,100	16,640

Table 4: Number of positive points collected by different methods. All methods collect the same number of total examples (last row).

| Method | QQP | | WikiQA | |
	P@R20	AP	P@R20	AP
Strat. match	35.1%	19.0%	13.2%	8.5%
Strat. all pos.	41.6%	22.2%	13.7%	9.1%
Adapt. Ret.	59.1%	32.4%	27.1%	15.1%
Uncertainty	**60.2**%	**32.5**%	**32.4**%	**20.1**%

Table 5: Even though stratified sampling has access to oracle information, active learning performs better by collecting more informative negative examples.

Random sampling queries n pairs uniformly at random, which creates a very imbalanced dataset. Static retrieval queries the n most similar pairs using the pre-trained BERT embedding, similar to Section 4.2.3. Table 3 shows all-pairs evaluation for COSINEBERT trained on these datasets. The two active learning methods greatly outperform other methods: Uncertainty sampling gets 32.5% AP on QQP and 20.1% on WikiQA, while the best static data collection method, static retrieval, gets only 25.1% AP on QQP and 8.2% AP on WikiQA. Recall from Table 2 that CONCATBERT only achieved 2.4% AP on both QQP and WikiQA. Uncertainty sampling slightly outperforms adaptive retrieval on both datasets.

Achieving high precision across all pairs requires collecting both enough positive examples and useful negative examples. Compared to random sampling and static retrieval, active learning collects many more positive examples, as shown in Table 4. $D_{\text{heur}}^{\text{train}}$ contains all positive examples, but models trained on it still have low AP on all pairs. We conclude that the negative examples in $D_{\text{heur}}^{\text{train}}$ are insufficient for generalization to all pairs, while active learning chooses more useful negatives.

5.3 Manual verification of imputed negatives

As in Section 3.3, we manually labeled putative QQP false positives at the threshold where recall is 20% for COSINEBERT trained on either stated data or uncertainty sampling data. For each, we labeled 50 putative false positives from $D_{\text{near}}^{\text{dev}}$, and all putative false positives from $D_{\text{rand}}^{\text{dev}}$ (12 for stated data, 0 for uncertainty sampling).

COSINEBERT trained on $D_{\text{heur}}^{\text{train}}$. 67% (8 of 12) of the putative false positives on $D_{\text{rand}}^{\text{dev}}$ were actual errors, but only 36% of putative false positives on $D_{\text{near}}^{\text{dev}}$ were errors. This causes us to update our estimate of development set precision at 20% recall from 28.4% to 41.4%. Overall, this model

makes some more reasonable mistakes than the CONCATBERT model, though its precision is still not that high.

COSINEBERT model with uncertainty sampling. Only 32% of putative false positives from $D_{\text{near}}^{\text{dev}}$ were real errors, significantly less than the 72% for CONCATBERT trained on $D_{\text{heur}}^{\text{train}}$ ($p = 7 \times 10^{-5}$, Mann-Whitney U test). Our estimate of development set precision at 20% recall increases from 55.1% to 79.3%, showing that uncertainty sampling yields a much more precise model than our imputed labels indicate.

5.4 Comparison with stratified sampling

Next, we further confirm that having all the positive examples is not sufficient for high precision. In Table 5, we compare with two variants of stratified sampling, in which positive and negative examples are independently subsampled at a desired ratio (Attenberg and Provost, 2010). First, we randomly sample positive and negative training examples to match the number of positives and negatives collected by uncertainty sampling, the best active learning method for both datasets ("Strat. match" in Table 5). Second, we trained on all positive examples and added negatives to match the number of positives on QQP or match the active learning total budget on WikiQA ("Strat. all pos.").[6] For QQP, this yielded a slightly larger dataset than the first setting. Note that stratified sampling requires oracle information: It assumes it can sample uniformly from all positives, even though this set is not known before data collection begins. Nonetheless, stratified sampling trails uncertainty sampling by more than 10 AP points on both datasets. Since stratified sampling has access to all positives, active learning must be choosing more informative negative examples.

---

[6]This aligns better with the original WikiQA dataset, which has many more negatives than positives.

5.5 Training other models on collected data

Data collected with active learning and COSINEBERT is useful even when training a different model architecture. CONCATBERT trained on data collected with uncertainty sampling gets 8.9% AP on QQP, compared to 2.4% with stated data. However its performance is lower than 32.5%, the AP of COSINEBERT with uncertainty sampling. See Appendix B.1 for details.

5.6 Data efficiency

Adaptivity is crucial for getting high AP with less labeled data. Static retrieval, the best static data collection method, gets 21.9% dev AP on QQP with the full budget of 232,100 examples. Uncertainty sampling achieves a higher dev AP of 22.6% after collecting only 16,640 examples, for a $14\times$ data efficiency improvement. See Appendix B.2 for further analysis.

6 Discussion and related work

In this paper, we have studied how to collect training data that enables generalization to extremely imbalanced test data in pairwise tasks. State-of-the-art models trained on standard, heuristically collected datasets have very low average precision when evaluated on imbalanced test data, while active learning leads to much better average precision.

Gillick et al. (2019) propose a similar model for entity linking and mine hard negative examples, an approach related to adaptive retrieval. However, they have abundant labeled data, whereas we study data collection with a limited labeling budget.

Work in information retrieval often attempts to maximize precision across all pairs of test objects. Machine learning models are commonly used to re-rank candidate pairs from an upstream retriever (Chen et al., 2017; Nogueira and Cho, 2019), while our method learns embeddings to improve the initial retrieval step. Distant supervision has been used to train end-to-end retrieval models for question answering (Lee et al., 2019), but does not extend to other tasks like paraphrase detection.

Extreme label imbalance is an important challenge in many non-pairwise NLP tasks, including document classification (Lewis et al., 2004) and relation extraction (Zhang et al., 2017). Most prior work focuses on sampling a fixed training dataset (Chawla et al., 2004; Sun et al., 2009; Dendamrongvit and Kubat, 2009), whereas our work explores data collection. Attenberg and Provost (2010) find stratified sampling outperforms active learning in non-pairwise imbalanced tasks, primarily due to the difficulty of finding a useful seed set. We find pre-trained embeddings effective for seed set collection in pairwise tasks.

Zhang et al. (2019) found that the frequency of questions in QQP leaks information about the label. Evaluating on all pairs avoids such artifacts, as every test utterance appears in the same number of examples. Zhang et al. (2019) re-weight the original dataset to avoid these biases, but re-weighting cannot compensate for the absence of some types of negative examples, unlike active learning.

Many pairwise datasets are generated by asking crowdworkers to generate part or all of the input x (Bowman et al., 2015; Mostafazadeh et al., 2016). Having crowdworkers generate text increases the risk of introducing artifacts (Schwartz et al., 2017; Poliak et al., 2018), while our pool-based approach considers the entire distribution of utterance pairs.

We use active learning, specifically uncertainty sampling (Lewis and Gale, 1994), to create a balanced training set that leads to models that generalize to the full imbalanced distribution. Ertekin et al. (2007) argues that active learning is capable of providing balanced classes to the learning algorithm by selecting examples close to the decision boundary. Furthermore, active learning can generalize to the full distribution, both empirically (Settles, 2009; Yang and Loog, 2018) and theoretically (Balcan et al., 2007; Balcan and Long, 2013; Mussmann and Liang, 2018).

Finally, this paper addresses two central concerns in NLP today: How to construct fair but challenging tests of generalization (Geiger et al., 2019), and how to collect training data in a way that improves generalization. Evaluating on extremely imbalanced all-pairs data has several advantages over other tests of generalization. Our examples are realistic and natural, unlike adversarial perturbations (Ebrahimi et al., 2018; Alzantot et al., 2018), and diverse, unlike hand-crafted tests of specific phenomena (Glockner et al., 2018; Naik et al., 2018; McCoy et al., 2019). Since we allow querying the label of any training example, generalization to our test data is achievable, while out-of-domain generalization (Levy et al., 2017; Yogatama et al., 2019; Talmor and Berant, 2019) may be statistically impossible. Our work thus offers a natural, challenging, and practically relevant testbed to study both generalization and data collection.

References

M. Alzantot, Y. Sharma, A. Elgohary, B. Ho, M. Srivastava, and K. Chang. 2018. Generating natural language adversarial examples. In *Empirical Methods in Natural Language Processing (EMNLP)*.

J. Attenberg and F. Provost. 2010. Why label when you can search? alternatives to active learning for applying human resources to build classification models under extreme class imbalance. In *International Conference on Knowledge Discovery and Data Mining (KDD)*.

Maria-Florina Balcan, Andrei Broder, and Tong Zhang. 2007. Margin based active learning. In *International Conference on Computational Learning Theory*, pages 35–50. Springer.

Maria-Florina Balcan and Phil Long. 2013. Active and passive learning of linear separators under log-concave distributions. In *Conference on Learning Theory*, pages 288–316.

S. Bowman, G. Angeli, C. Potts, and C. D. Manning. 2015. A large annotated corpus for learning natural language inference. In *Empirical Methods in Natural Language Processing (EMNLP)*.

N. V. Chawla, N. Japkowicz, and A. R. Kolcz. 2004. Editorial: Special issue on learning from imbalanced data sets. *ACM SIGKDD Explorations Newsletter*, 6(1).

D. Chen, A. Fisch, J. Weston, and A. Bordes. 2017. Reading Wikipedia to answer open-domain questions. In *Association for Computational Linguistics (ACL)*.

S. Dendamrongvit and M. Kubat. 2009. Undersampling approach for imbalanced training sets and induction from multi-label text-categorization domains. In *PAKDD Workshop on New Frontiers in Applied Data Mining*.

J. Devlin, M. Chang, K. Lee, and K. Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Association for Computational Linguistics (ACL)*, pages 4171–4186.

J. Ebrahimi, A. Rao, D. Lowd, and D. Dou. 2018. Hotflip: White-box adversarial examples for text classification. In *Association for Computational Linguistics (ACL)*.

Seyda Ertekin, Jian Huang, Leon Bottou, and Lee Giles. 2007. Learning on the border: active learning in imbalanced data classification. In *Proceedings of the sixteenth ACM conference on Conference on information and knowledge management*, pages 127–136.

S. Garg, T. Vu, and A. Moschitti. 2020. TANDA: Transfer and adapt pre-trained transformer models for answer sentence selection. In *Association for the Advancement of Artificial Intelligence (AAAI)*.

A. Geiger, I. Cases, L. Karttunen, and C. Potts. 2019. Posing fair generalization tasks for natural language inference. In *Empirical Methods in Natural Language Processing (EMNLP)*.

D. Gillick, S. Kulkarni, L. Lansing, A. Presta, J. Baldridge, E. Ie, and D. Garcia-Olano. 2019. Learning dense representations for entity retrieval. In *Computational Natural Language Learning (CoNLL)*.

M. Glockner, V. Shwartz, and Y. Goldberg. 2018. Breaking NLI systems with sentences that require simple lexical inferences. In *Association for Computational Linguistics (ACL)*.

D. K. Harman. 1992. Overview of the first TREC text retrieval conference. In *Text Retrieval Conference*.

S. Ioffe and C. Szegedy. 2015. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International Conference on Machine Learning (ICML)*, pages 448–456.

Shankar Iyer, Nikhil Dandekar, and Kornél Csernai. 2017. First quora dataset release: Question pairs. https://www.quora.com/q/quoradata/First-Quora-Dataset-Release-Question-Pairs.

H. Ji, R. Grishman, and H. Trang Dang. 2011. Overview of the TAC 2011 knowledge base population track. In *Text Analytics Conference*.

Jeff Johnson, Matthijs Douze, and Hervé Jégou. 2017. Billion-scale similarity search with gpus. *arXiv preprint arXiv:1702.08734*.

Z. Lan, M. Chen, S. Goodman, K. Gimpel, P. Sharma, and R. Soricut. 2020. ALBERT: A lite BERT for self-supervised learning of language representations. In *International Conference on Learning Representations (ICLR)*.

K. Lee, M. Chang, and K. Toutanova. 2019. Latent retrieval for weakly supervised open domain question answering. In *Association for Computational Linguistics (ACL)*.

O. Levy, M. Seo, E. Choi, and L. Zettlemoyer. 2017. Zero-shot relation extraction via reading comprehension. In *Computational Natural Language Learning (CoNLL)*.

D. D. Lewis. 1995. Evaluating and optimizing autonomous text classification systems. In *ACM Special Interest Group on Information Retrieval (SIGIR)*.

D. D. Lewis, Y. Yang, T. G. Rose, and F. Li. 2004. Rcv1: A new benchmark collection for text categorization research. *Journal of Machine Learning Research (JMLR)*, 5.

David D Lewis and William A Gale. 1994. A sequential algorithm for training text classifiers. In *SIGIR'94*, pages 3–12. Springer.

Y. Liu, M. Ott, N. Goyal, J. Du, M. Joshi, D. Chen, O. Levy, M. Lewis, L. Zettlemoyer, and V. Stoyanov. 2019. RoBERTa: A robustly optimized BERT pretraining approach. *arXiv preprint arXiv:1907.11692*.

C. Manning, P. Raghavan, and H. Schütze. 2008. *Introduction to information retrieval*, volume 1. Cambridge University Press.

R. T. McCoy, E. Pavlick, and T. Linzen. 2019. Right for the wrong reasons: Diagnosing syntactic heuristics in natural language inference. In *Association for Computational Linguistics (ACL)*.

N. Mostafazadeh, N. Chambers, X. He, D. Parikh, D. Batra, L. Vanderwende, P. Kohli, and J. Allen. 2016. A corpus and cloze evaluation for deeper understanding of commonsense stories. In *North American Association for Computational Linguistics (NAACL)*.

Stephen Mussmann and Percy S Liang. 2018. Uncertainty sampling is preconditioned stochastic gradient descent on zero-one loss. In *Advances in Neural Information Processing Systems*, pages 6955–6964.

A. Naik, A. Ravichander, N. Sadeh, C. Rose, and G. Neubig. 2018. Stress test evaluation for natural language inference. In *International Conference on Computational Linguistics (COLING)*, pages 2340–2353.

R. Nogueira and K. Cho. 2019. Passage re-ranking with BERT. *arXiv preprint arXiv:1901.04085*.

A. Poliak, J. Naradowsky, A. Haldar, R. Rudinger, and B. V. Durme. 2018. Hypothesis only baselines in natural language inference. *arXiv preprint arXiv:1805.01042*.

N. Reimers and I. Gurevych. 2019. Sentence-BERT: Sentence embeddings using siamese BERT-networks. In *Empirical Methods in Natural Language Processing (EMNLP)*.

R. Schwartz, M. Sap, Y. Konstas, L. Zilles, Y. Choi, and N. A. Smith. 2017. The effect of different writing tasks on linguistic style: A case study of the ROC story cloze task. In *Computational Natural Language Learning (CoNLL)*.

Burr Settles. 2009. Active learning literature survey. Technical report, University of Wisconsin-Madison Department of Computer Sciences.

G. Shen, Y. Yang, and Z. Deng. 2017. Inter-weighted alignment network for sentence pair modeling. In *Empirical Methods in Natural Language Processing (EMNLP)*.

A. Sun, E. Lim, and ying Liu. 2009. On strategies for imbalanced text classification using svm: A comparative study. *Decision Support Systems*, 48(1).

A. Talmor and J. Berant. 2019. MultiQA: An empirical investigation of generalization and transfer in reading comprehension. In *Association for Computational Linguistics (ACL)*.

A. Wang, A. Singh, J. Michael, F. Hill, O. Levy, and S. R. Bowman. 2019. Glue: A multi-task benchmark and analysis platform for natural language understanding. In *International Conference on Learning Representations (ICLR)*.

Y. Yang, W. Yih, and C. Meek. 2015. WikiQA: A challenge dataset for open-domain question answering. In *Empirical Methods in Natural Language Processing (EMNLP)*, pages 2013–2018.

Yazhou Yang and Marco Loog. 2018. A benchmark and comparison of active learning for logistic regression. *Pattern Recognition*, 83:401–415.

Z. Yang, Z. Dai, Y. Yang, J. Carbonell, R. Salakhutdinov, and Q. V. Le. 2019. XLNet: Generalized autoregressive pretraining for language understanding. *arXiv preprint arXiv:1906.08237*.

D. Yogatama, C. de M. d'Autume, J. Connor, T. Kocisky, M. Chrzanowski, L. Kong, A. Lazaridou, W. Ling, L. Yu, C. Dyer, et al. 2019. Learning and evaluating general linguistic intelligence. *arXiv preprint arXiv:1901.11373*.

S. Yoon, F. Dernoncourt, D. S. Kim, T. Bui, and K. Jung. 2019. A compare-aggregate model with latent clustering for answer selection. In *Conference on Information and Knowledge Management (CIKM)*.

G. Zhang, B. Bai, J. Liang, K. Bai, S. Chang, M. Yu, C. Zhu, and T. Zhao. 2019. Selection bias explorations and debias methods for natural language sentence matching datasets. In *Association for Computational Linguistics (ACL)*.

Y. Zhang, V. Zhong, D. Chen, G. Angeli, and C. D. Manning. 2017. Position-aware attention and supervised data improve slot filling. In *Empirical Methods in Natural Language Processing (EMNLP)*.

A   Experimental details

A.1   Training details

At each round of active learning, we train for 2 epochs. We train without dropout, as dropout artificially lowers cosine similarities at training time. We apply batch normalization (Ioffe and Szegedy, 2015) to the cosine similarity layer to rescale the cosine similarities, as they often are very close to 1. We initialize w and b so that high cosine similarities correspond to the positive label, and constrain w to be nonnegative during training. We use a maximum sequence length of 128 word piece tokens. To compensate for BERT's low learning rate, we increased the learning rate on the w and b parameters by a factor of 10^4.

Below in Table 6, we show hyperparameters for training. Hyperparameters were tuned on the development set of QQP; we found these same hyperparameters also worked well for WikiQA, and so we did not tune them separately for WikiQA. In most cases, we used the default hyperparameters for BERT.

Hyperparameter	Value
Learning rate	2×10^{-5}
Training epochs	2
Weight decay	0
Optimizer	AdamW
AdamW Epsilon	1×10^{-6}
Batch size	16

Table 6: Hyperparameter choices for QQP and WikiQA

At the end of training, we freeze the embeddings e_θ and train the output layer parameters w and b to convergence, to improve uncertainty estimates for uncertainty sampling. This process amounts to training a two-parameter logistic regression model. We optimize this using (batch) gradient descent with learning rate 1 and $10,000$ iterations. When training this model, we normalize the cosine similarity feature to have zero mean and unit variance across the training dataset. Training this was very fast compared to running the embedding model.

Each experiment was conducted with a single GPU, most commonly a TITAN V or TITAN Xp. Running one complete uncertainty sampling experiment (i.e., 10 rounds of data collection and model training for QQP, 4 for WikiQA) on a machine with one TITAN V GPU takes about 9 hours for QQP and about 30 minutes for WikiQA. Recall that

COSINEBERT only adds two additional parameters, w and b, on top of a BERT model; we use the uncased BERT-base pre-trained model which has 110M parameters.

A.2   Evaluation details

To evaluate a given scoring function S at threshold γ on a test set $D_{\text{all}}^{\text{test}}$, we must compute the number of true positives $\text{TP}(S, \gamma)$, false positives $\text{FP}(S, \gamma)$, and false negatives $\text{FN}(S, \gamma)$. True positives and false negatives are computationally easy to compute, as they only require evaluating $S(x)$ on all the positive inputs x in $D_{\text{all}}^{\text{test}}$. However, without any structural assumptions on S, it is computationally infeasible to exactly compute the number of false positives, as that would require evaluating S on every negative example in $D_{\text{all}}^{\text{test}}$, which is too large to enumerate.

Therefore, we devise an approach to compute an unbiased, low-variance estimate of $\text{FP}(S, \gamma)$. Recall that this term is defined as

$$\text{FP}(S, \gamma) = \sum_{x \in D_{\text{all}}^{\text{test}}} \mathbf{1}[y(x) = 0 \wedge S(x) > \gamma] \quad (8)$$

$$= \sum_{x \in D_{\text{neg}}^{\text{test}}} \mathbf{1}[S(x) > \gamma] \quad (9)$$

where $D_{\text{neg}}^{\text{test}}$ denotes the set of all negative examples in $D_{\text{all}}^{\text{test}}$.

One approach to estimating $\text{FP}(S, \gamma)$ would be simply to randomly downsample $D_{\text{neg}}^{\text{test}}$ to some smaller set R, count the number of false positives in R, and then multiply the count by $|D_{\text{neg}}^{\text{test}}|/|R|$. This would be an unbiased estimate of $D_{\text{neg}}^{\text{test}}$, but has high variance when the rate of false positive errors is low. For example, if $|D_{\text{neg}}^{\text{test}}| = 10^{10}$, $|R| = 10^6$, and the model makes a false positive error on 1 in 10^6 examples in $D_{\text{neg}}^{\text{test}}$, then $\text{FP}(S, \gamma) = 10^4$. However, with probability

$$\left(1 - \frac{1}{10^6}\right)^{10^6} \approx 1/e \approx 0.368,$$

R will contain no false positives, so we will estimate $\text{FP}(S, \gamma)$ as 0. A similar calculation shows that the probability of having exactly one false positive in R is also roughly $1/e$, which means that with probability roughly $1 - 2/e \approx 0.264$, we will have at least two false positives in R, and therefore overestimate $\text{FP}(S, \gamma)$ by at least a factor of two.

To get a lower variance estimate $\hat{\text{FP}}(S, \gamma)$, we preferentially sample from likely false positives

and use importance weighting to get an unbiased estimate of $\mathrm{FP}(S, \gamma)$. In particular, we construct $D_{\mathrm{near}}^{\mathrm{test}}$ to be the pairs in $D_{\mathrm{all}}^{\mathrm{test}}$ with nearby pre-trained BERT embeddings, analogously to how we create the seed set in Section 4.2.3. Points with nearby BERT embeddings are likely to look similar are therefore are more likely to be false positives. Note that

$$\mathrm{FP}(S, \gamma) = \sum_{x \in D_{\mathrm{near}}^{\mathrm{test}}} \mathbf{1}[S(x) > \gamma]$$

$$+ \sum_{x \in D_{\mathrm{neg}}^{\mathrm{test}} \setminus D_{\mathrm{near}}^{\mathrm{test}}} \mathbf{1}[S(x) > \gamma] \qquad (10)$$

$$= \sum_{x \in D_{\mathrm{near}}^{\mathrm{test}}} \mathbf{1}[S(x) > \gamma]$$

$$+ w_{\mathrm{rand}} \cdot \mathbb{E}_{x \sim \mathrm{Unif}(D_{\mathrm{neg}}^{\mathrm{test}} \setminus D_{\mathrm{near}}^{\mathrm{test}})} \mathbf{1}[S(x) > \gamma], \qquad (11)$$

where we define $w_{\mathrm{rand}} = |D_{\mathrm{neg}}^{\mathrm{test}}| - |D_{\mathrm{near}}^{\mathrm{test}}|$.

We can compute the first term exactly, since $D_{\mathrm{near}}^{\mathrm{test}}$ is small enough to enumerate, and approximate the second term as

$$w_{\mathrm{rand}} \cdot \frac{1}{|D_{\mathrm{rand}}^{\mathrm{test}}|} \sum_{x \in D_{\mathrm{rand}}^{\mathrm{test}}} \mathbf{1}[S(x) > \gamma], \qquad (12)$$

where $D_{\mathrm{rand}}^{\mathrm{test}}$ is a uniformly random subset of $D_{\mathrm{neg}}^{\mathrm{test}} \setminus D_{\mathrm{near}}^{\mathrm{test}}$. Therefore, our final estimate is

$$\hat{\mathrm{FP}}(S, \gamma) = \sum_{x \in D_{\mathrm{near}}^{\mathrm{test}}} \mathbf{1}[S(x) > \gamma]$$

$$+ \frac{w_{\mathrm{rand}}}{|D_{\mathrm{rand}}^{\mathrm{test}}|} \sum_{x \in D_{\mathrm{rand}}^{\mathrm{test}}} \mathbf{1}[S(x) > \gamma]. \qquad (13)$$

A.3 Incorporating manual labels

In Section 3.3, we manually label examples that were automatically labeled as false positives, and use this to improve our estimates of the true model precision. We manually label randomly chosen putative false positives from both $D_{\mathrm{near}}^{\mathrm{dev}}$ and $D_{\mathrm{rand}}^{\mathrm{dev}}$, and use this to estimate the proportion of putative false positives in each set that are real false positives. Let $\hat{p}_{\mathrm{near}}$ denote the estimated fraction of putative false positives in $D_{\mathrm{near}}^{\mathrm{dev}}$ that are real false positives, and $\hat{p}_{\mathrm{rand}}$ be the analogous quantity for $D_{\mathrm{rand}}^{\mathrm{dev}}$. Our updated estimate $\hat{\mathrm{FP}}_{\mathrm{manual}}(S, \gamma)$ is then defined as

$$\hat{\mathrm{FP}}_{\mathrm{manual}}(S, \gamma) = \hat{p}_{\mathrm{near}} \sum_{x \in D_{\mathrm{near}}^{\mathrm{test}}} \mathbf{1}[S(x) > \gamma]$$

$$+ \frac{\hat{p}_{\mathrm{random}} \cdot w_{\mathrm{rand}}}{|D_{\mathrm{rand}}^{\mathrm{test}}|} \sum_{x \in D_{\mathrm{rand}}^{\mathrm{test}}} \mathbf{1}[S(x) > \gamma]. \qquad (14)$$

We then compute precision using $\hat{\mathrm{FP}}_{\mathrm{manual}}(S, \gamma)$ in place of $\hat{\mathrm{FP}}(S, \gamma)$.

A.4 Comparison with GLUE QQP data

For a few reasons, our QQP in-domain accuracy numbers are lower than those on the GLUE leaderboard, which has accuracies in the low 90's. First, our training set is smaller (257k examples versus 364k). Second, our split is more challenging because the model does not see the same questions or even same paraphrase clusters at training time and test time. Finally, our test set is more balanced (58% negative) than the GLUE QQP dev set (63% negative; test set balance is unknown). As a sanity check, we confirmed that our RoBERTa implementation can achieve 91.5% dev accuracy when trained and tested on the GLUE train/dev split, in line with previously reported results (Liu et al., 2019).

B Additional experimental results

B.1 Training other models on collected data

QQP Data	CosineBERT		ConcatBERT	
	P@R20	AP	P@R20	AP
Stated data	29.3%	15.4%	3.0%	2.4%
Static Ret.	49.2%	25.1%	4.6%	1.9%
Stratified	35.1%	19.0%	29.0%	16.4%
Uncertainty	**60.2**%	**32.5**%	23.6%	8.9%

Table 7: Comparison on QQP of CosineBERT with ConcatBERT. Data collected by active learning (using CosineBERT) is more useful for training ConcatBERT than stated data or static retrieval data. Stratified sampling here matches the label balance of the uncertainty sampling data.

Here, we demonstrate on QQP that data collected with active learning and CosineBERT is useful for training other models on the same task. Table 7 shows that ConcatBERT does better on data collected by active learning—using CosineBERT—compared to the original dataset or static retrieval. ConcatBERT performs best with stratified sampling; recall that this is not a comparable data collection strategy in our setting, as it requires oracle knowledge. CosineBERT outperforms ConcatBERT in all training conditions; we hypothesize that the cosine similarity structure helps it generalize more robustly to pairs of unrelated questions. However, CosineBERT trained on stated data does not do as well on WikiQA, as shown in Table 3.

B.2 Learning curves and data efficiency

(a) Average precision   (b) Positives collected

Figure 3: Uncertainty sampling compared with matching amounts of static retrieval data on QQP. (a) Average precision is higher for uncertainty sampling. Recall that uncertainty sampling uses static retrieval at the first iteration to create the seed set. (b) Percent of all collected data that is positive. Adaptivity helps uncertainty sampling collect more positives.

In Figure 3a, we plot average precision on the QQP dev set for our model after each round of uncertainty sampling. For comparison, we show a model trained on the same amount of data collected via static retrieval, the best-performing static data collection method. Uncertainty sampling leads to higher AP with much less data. For example, uncertainty sampling only needs to collect 16,640 examples to surpass the average precision of static retrieval collecting all 232,100 examples, for a $14\times$ data efficiency improvement. A big factor for the success of uncertainty sampling is its ability to collect many more positive examples than static retrieval, as shown in Figure 3b. Static retrieval collects fewer positives over time, as it exhausts the set of positives that are easy to identify. However, uncertainty sampling collects many more positives, especially after the first round of training, because it improves its embeddings over time.

B.3 Effect of seed set

Our method is robust to choice of the initial seed set for uncertainty sampling. We consider using stated data as the seed set, instead of data chosen via static retrieval. As shown in Figure 4, seeding with stated data performs about as well as static retrieval in terms of AP. Since the stated data artificially overrepresents positive examples, the model trained on stated data is initially miscalibrated—the points it is uncertain about are actually almost all negative points. Therefore, uncertainty sampling initially collects very few additional positive ex-

(a) Average precision   (b) Positives collected

Figure 4: Uncertainty sampling on QQP using different seed sets. Left: Seeding with stated data (one run) does similarly to seeding with retrieval (mean over three runs). Right: Seeding with stated data makes the model poorly calibrated—points it is uncertain about are initially very unlikely to be positive. However, over time the model corrects this behavior.

amples. Over time, adaptively querying new data helps correct for this bias.