LOCAL FEATURE SWAPPING FOR GENERALIZATION IN REINFORCEMENT LEARNING

ABSTRACT

Over the past few years, the acceleration of computing resources and research in deep learning has led to significant practical successes in a range of tasks, including in particular in computer vision. Building on these advances, reinforcement learning has also seen a leap forward with the emergence of agents capable of making decisions directly from visual observations. Despite these successes, the over-parametrization of neural architectures leads to memorization of the data used during training and thus to a lack of generalization. Reinforcement learning agents based on visual inputs also suffer from this phenomenon by erroneously correlating rewards with unrelated visual features such as background elements. To alleviate this problem, we introduce a new regularization technique consisting of channel-consistent local permutations (CLOP) of the feature maps. The proposed permutations induce robustness to spatial correlations and help prevent overfitting behaviors in RL. We demonstrate, on the OpenAI Procgen Benchmark, that RL agents trained with the CLOP method exhibit robustness to visual changes and better generalization properties than agents trained using other state-of-the-art regularization techniques.

1 INTRODUCTION

Advances made in deep learning have opened the way to many applications in computer vision such as classification, object recognition, or image segmentation. The powerful representation capabilities of deep neural networks paved the way for many successes in deep reinforcement learning with the design of agents able to take decisions directly from pixels (Mnih et al., 2013; 2015). However, the sensitivity of neural networks to the distribution of training data strongly affects their generalization abilities. Neural networks are intrinsically designed to memorize the data they are trained upon, since their fitting implies empirical risk minimization (Vapnik, 1992) (they minimize the empirical average prediction error over a large training dataset). Therefore, they are prone to prediction errors on unseen samples. RL agents also suffer from this handicap and tend to memorize training trajectories, rather than general skills and features leading to transferable policies. This phenomenon, usually known as overfitting, takes a double sense in RL. Generalization in RL implies the ability to generalize across states (as in supervised learning), but also across environments. It is only recently that several environments with different configurations for training and testing have emerged and received a lot of attention (Nichol et al., 2018; Justesen et al., 2018; Zhang et al., 2018a; Cobbe et al., 2019; 2020), shedding light on the generalization issue which remained mostly overlooked, and confirming the poor generalization ability of current algorithms.

Strategies to achieve good generalization and avoid overfitting in deep learning fall into three categories of regularization: explicit regularization (e.g., loss penalization, weight decay), implicit regularization via the architecture and optimization (e.g., dropout, batch-normalization, batch size selection, momentum, early stopping), or implicit regularization by enhancement of the input data (data augmentation). Direct application of these strategies to deep RL agents has demonstrated some improvements in agent generalization abilities in some environments, but much progress remains to be made to integrate RL systems in real-world applications. In this work, we address the observational overfitting issue introduced in Song et al. (2019) which considers a zero-shot generalization RL setting. An agent is trained on a specific distribution of environments (for example some levels of a platform video game) and tested on similar environments sharing the same high-level goal and dynamics but with different layouts and visual attributes (background or assets). We argue that a

structured stochastic permutation of features of an RL agent during training leads to state-of-the-art generalization performance for vision-based policies. We introduce an efficient regularization technique based on Channel-consistent LOcal Permutations (CLOP) of the feature maps that mitigates overfitting. We implement it as an intermediate layer in feed-forward neural networks, and demonstrate its effectiveness on several problems.

This paper is organized as follows. Section 2 presents the necessary background on generalization in supervised learning and reinforcement learning. Section 3 reviews recent work in the literature that allows for a critical look at our contribution and put it in perspective. Section 4 introduces the CLOP technique and the corresponding layer. Section 5 empirically evaluates agents using CLOP against state-of-the-art generalization methods and discusses their strengths, weaknesses, and variants. Section 6 summarizes and concludes this paper.

2   WHAT IS GENERALIZATION?

Generalization in supervised learning (SL). Let $\mathcal{X}$ be an input space of descriptors and $\mathcal{Y}$ an output space of labels. A SL problem is defined by a distribution $p(x, y)$ of elements of $\mathcal{X} \times \mathcal{Y}$, and a loss $\mathcal{L}(\hat{y}, y)$ which measures how different $\hat{y} \in \mathcal{Y}$ and $y \in \mathcal{Y}$ are. Then, for a given function f intended to capture the mapping from $\mathcal{X}$ to $\mathcal{Y}$ underlying the p distribution, one defines the (expected) risk as $\mathcal{R}(f) = \mathbb{E}_p[\mathcal{L}(f(x), y)]$. Since the true p is generally unknown, one cannot directly minimize the risk in search for the optimal f. Given a training set $\mathcal{S} = \{(x_i, y_i)\}_{i=1}^n$ of n items in $\mathcal{X} \times \mathcal{Y}$ drawn i.i.d. according to $p(x, y)$, empirical risk minimization (Vapnik, 1992) seeks to minimize $\mathcal{R}_\mathcal{S}(f) = 1/n \sum_{i=1}^n [\mathcal{L}(f(x_i), y_i)]$. The ability of f to generalize to unseen samples is then defined by the generalization gap $\mathcal{R}(f) - \mathcal{R}_\mathcal{S}(f)$, which is often evaluated by approaching $\mathcal{R}(f)$ as the empirical risk $\mathcal{R}_\mathcal{T}(f)$ over a test set $\mathcal{T} = \{(x_i, y_i)\}_{i=1}^{n'}$ also drawn i.i.d. from $p(x, y)$. Closing the generalization gap can be attempted through structural risk minimization, which modifies $\mathcal{R}_\mathcal{S}$ so as to include a *regularization* penalty into the optimization, or more generally by the introduction of inductive biases (Mitchell, 1980).

Reinforcement learning (RL). RL (Sutton & Barto, 2018) considers the problem of learning a decision making policy for an agent interacting over multiple time steps with a dynamic environment. At each time step, the agent and environment are described through a state $s \in \mathcal{S}$, and an action $a \in \mathcal{A}$ is performed ; then the system transitions to a new state s' according to probability $T(s'|s, a)$, while receiving reward $R(s, a)$. The tuple $M = (\mathcal{S}, \mathcal{A}, T, R)$ forms a Markov Decision Process (Puterman, 2014, MDP), which is often complemented with the knowledge of an initial state distribution $p_0(s)$. A decision making policy parameterized by θ is a function $\pi_\theta(a|s)$ mapping states to distributions over actions. Training a reinforcement learning agent consists in finding the policy that maximizes the discounted expected return: $J(\pi_\theta) = \mathbb{E}[\sum_{t=0}^\infty \gamma^t R(s_t, a_t)]$.

Generalization in RL. Departing from the rather intuitive definition of generalization in SL, the idea of generalization in RL may lead to misconceptions. One could expect a policy that generalizes well to perform well *across environments*. It seems important to disambiguate this notion and stress out the difference between generalization in the SL sense (which is a single MDP problem), and domain generalization or robustness. For instance, one could expect a policy that learned to play a certain level of a platform game to be able to play on another level, provided the key game features (e.g. platforms, enemies, treasures) remain similar enough and the game dynamics are the same. This type of generalization benchmark is typically captured by procedurally generated environments, such as Procgen (Cobbe et al., 2020). Finding a policy that yields a guaranteed minimal performance among a set of MDPs (sharing common state and action spaces) is the problem of solving Robust MDPs (Iyengar, 2005). Similarly, that of policy optimization over a distribution over MDPs (sharing common states and actions too) is that of domain generalization (Tobin et al., 2017). We argue that these problems are unrelated and much harder than vanilla generalization in RL. Robust MDPs induce a $\max_\pi \min_{T,R}$ problem, domain generalization is a $\max_\pi \mathbb{E}_{T,R}$ one, while vanilla generalization as understood in SL remains a $\max_\pi$ problem that we try to solve *for all states* within a single MDP (and not only the ones in the training set). Consequently, the ability to generalize in RL is a broader notion than structural risk minimization, which, unfortunately, uses the same name of generalization. In a given game, finding a policy that plays well on all levels is still solving the very same MDP. The underlying transition and reward models are the same and only the parts of the state space explored in each level are different. Note that these explored subsets of

the state space may have non-empty intersections (e.g. the final part of two different levels might be common) and the optimal distribution over actions for a given state is unique. In this work we focus on generalization as the problem of preventing overfitting (and thus reducing the generalization gap) within a single MDP.

Observational overfitting in RL. The inability to generalize might be caused by overfitting to the partially explored environment dynamics (Rajeswaran et al., 2017), or to some misleading signal that is correlated with progress but does not generalize to new levels (Machado et al., 2018; Song et al., 2019). Therefore, preventing observational overfitting in RL remains the ability to generalize across states, within the same MDP. Beyond the ability of RL agents to memorize good actions in explored states, it boils down to their ability to capture rules that extend to unencountered states, just as in structural risk minimization. As in SL, many policies might fit the observed data, but few might generalize to the true mechanisms of the underlying MDP. This is what Song et al. (2019) call the problem of *observational overfitting*, which they propose to capture through a framework where a unique latent state space is transformed into a variety of observation spaces. Observation functions are built by combining useful features with purely decorative and unimportant ones which vary from one observation function to the next. They suppose the observation functions are drawn from a certain distribution (over procedural generation parameters for instance) and define the corresponding distribution over MDPs. In turn, they define the risk and the generalization gap with respect to this distribution over MDPs. We slightly depart from their derivation and argue this distinction is unnecessary: what is being solved is the unique MDP defined by the underlying dynamics and the projection of latent states into observations. The risk is thus defined with respect to the distribution over observations induced by the distributions over initial states and observation functions. Overall, this allows capturing the problem of generalization gap minimization in RL and underpins the developments proposed in the remainder of this paper.

3 RELATED WORK

In the following paragraphs, we cover essential works which aim to improve the generalization abilities of neural networks in both supervised learning and reinforcement learning.

In supervised learning, the process of modifying a learning algorithm with the objective to reduce its test error while preserving its train error is known as *regularization* (Goodfellow et al., 2016). Direct, or explicit, regularization can be achieved by adding a regularizer term into the loss function, such as an L2 penalty on networks parameters (Plaut et al., 1986; Krogh & Hertz, 1992). A second, implicit, regularization strategy consists in feature-level manipulations like dropout (Srivastava et al., 2014), drop-connect (Wan et al., 2013) or batch-normalization (Ioffe & Szegedy, 2015). Regularization can also be achieved implicitly by directly augmenting the training data with perturbations such as adding Gaussian noise (Bishop, 1995), or, in the case of visual inputs, random cropping and flipping (Krizhevsky et al., 2012; Szegedy et al., 2017) or removing structured parts of the image (DeVries & Taylor, 2017). Another efficient augmentation strategy, called label smoothing (Szegedy et al., 2016), consists in penalizing overconfident predictions of neural networks by perturbing the labels. Combining perturbation of both inputs and outputs, Zhang et al. (2018c); Yun et al. (2019), produce synthetic data and labels using two different samples and their corresponding labels.

Many studies have highlighted the limited ability of RL agents to generalize to new scenarios (Farebrother et al., 2018; Packer et al., 2018; Zhang et al., 2018b; Song et al., 2019; Cobbe et al., 2019). Using saliency maps, Song et al. (2019) exhibit that RL agents trained from pixels in environments with rich and textured observations, such as platform video games (e.g. Sonic (Nichol et al., 2018)), focus on elements of the scenery correlated with in-game progress but which lead to poor generalization in later situations. One of the identified counter-measures to overfitting in RL consists in applying standard methods in supervised learning. Cobbe et al. (2019; 2020) demonstrated the contribution of classical supervised learning regularization techniques like weight decay, dropout, or batch-normalization to generalization in procedurally generated environments. Similar to data-augmentation in supervised learning, Raileanu et al. (2020); Laskin et al. (2020); Yarats et al. (2020) apply visual-data-augmentation on the observations provided by the environment to train robust agents. Igl et al. (2019) use a selective noise injection and information bottleneck to regularize their agent. Wang et al. (2020) propose mixreg, a direct application of mixup (Zhang et al., 2018c) in RL, combining two randomly sampled observations, and training the RL agent using their interpo-

lated supervision signal. Lee et al. (2019) use a random convolution layer ahead of the network architecture, to modify the color and texture of the visual observations during training. Tobin et al. (2017) tackle the sim-to-real problem, using domain randomization on visual inputs to bridge the gap between simulation and reality in robotics. Raileanu & Fergus (2021) dissociate the optimization process of the policy and value function represented by separate networks and introduce an auxiliary loss that encourages the representation to be invariant to task-irrelevant properties of the environment. Another recent strategy consists in learning representations that are invariant to visual changes. Higgins et al. (2017) use a two-stage learning process: first they extract disentangled representations from random observation and then they exploit these representations to train an RL agent. Zhang et al. (2020) use bisimulation metrics to quantify behavioral similarity between states and learn robust task-relevant representations. Wang et al. (2021b) extract, without supervision, the visual foreground to provide background invariant inputs to the policy learner.

Our work focuses on the *observational overfitting* situations, introduced by Song et al. (2019), where an agent overfits visual observations features that are irrelevant to the latent dynamics of the MDP. Our method approaches the augmentation of data by noise injection at the feature level, thus avoiding the computationally costly operations of high-dimensional image transformation in regular data augmentation. By directly modifying the encountered features' spatial localization, the CLOP layer aims to remove the correlations between spurious features and rewards.

4 CHANNEL-CONSISTENT LOCAL PERMUTATION LAYER

Three key intuitions underpin the proposal of the channel-consistent local permutation (CLOP) layer. 1) In many image-based decision making problems, **the important information is often spatially scarce and very localized**. The example of platform games is typical: most of the pixels are decorrelated from the MDP's objective. But this also applies to other games (e.g., driving, shooting) or environments such as image-based object manipulation. Consequently, most pixels don't convey useful information for an optimal policy and data augmentation should help disambiguate between informative and uninformative pixels. Specifically, we can expect that an image and its altered counterpart share the same reward value for the same action. Even if perturbing an image might mistakenly associate the wrong action to it, in most cases we expect noise injection in images to be beneficial for generalization since it creates synthetic images where most of the perturbed features were unimportant in the first place.
2) We refer to the process of modifying a $C \times H \times W$ image as data augmentation, whether this image is an input image or a set of feature maps produced by the C filters of a convolutional layer. We argue that **data augmentation in the latent space is more efficient for generalization in decision making than in the input space**. For example, it seems more useful for generalization to learn a rule stating that an enemy sprite's position is important for the action choice, than to learn this same rule based on independent pixels, which might lead to observational overfitting. The successive convolutional layers provide greater levels of abstraction on each image: the deepest layer is the highest level of abstraction and forms a latent description space of the input images, with abstract features, like whole-object positions. Consequently, to achieve generalization in RL, data augmentation should probably be done in the latent space, on the feature maps after the deepest convolutional layer, rather than in the input space.
3) **Good actions in a state probably remain good actions in closeby states in the latent space**. For example, if one has determined that jumping is a good action in a specific image, then it is likely that if the image's objects move very locally, jumping remains a good action in the corresponding new images. This idea is related to that of Rachelson & Lagoudakis (2010) who study the locality of action domination in the state space. Consequently, we conjecture that local shifts of features in the deepest feature maps (hence representing high-level concepts and objects, rather than raw pixels) might help generate synthetic samples that help the optimization process disambiguate between useful and unimportant information. In turn, we expect this data augmentation to help prevent the bare memorization of good trajectories and instead generalize to good decision making rules.

The CLOP technique transposes these intuitions into convolutional networks. We implement it as a regularization layer that we introduce after the deepest convolutional layer's feature maps. During training, it swaps the position of pixels in these feature maps, while preserving the consistency across channels, so as to preserve the positional consistency between feature maps. This swapping is performed sequentially in a random order among pixels, locally (each pixel is swapped with one

input: X of shape (N, C, H, W)
if training mode **then**
    $P = \{(h, w)\}_{h \in [1,H], w \in [1,W]}$
    for $(h, w) \in P$ drawn randomly without replacement
        $(h', w') \leftarrow$ draw a direct neighbor of (h, w)
        With proba α, swap$(X[:, :, h, w], X[:, :, h', w'])$
return X

Figure 1: Channel-consistent LOcal Permutation Layer (CLOP)

$\alpha = 0$ $\alpha = 0.2$ $\alpha = 0.4$ $\alpha = 0.6$ $\alpha = 0.8$ $\alpha = 1$

Figure 2: Examples of CLOP layer outputs with different values for α

of its neighbors), and with probability α. At evaluation time, the CLOP layer behaves like the identity function. Figure 1 illustrates this process and presents the pseudo-code. Since pixels are taken in a random order, a given pixel value might be "transported" far from its original position, with a small probability. Figure 2 illustrates the effect of varying values of α on the output of the layer. Since CLOP is applied after the deepest convolutional layer, each of the pixels in this image should be interpreted as a salient high-level feature in the input image, and the channels correspond to different filters. CLOP shuffles these descriptors while preserving channel consistency (no new colors are created in Figure 2) and neighborhoods (objects remain close to each other).

5 EXPERIMENTAL RESULTS AND DISCUSSION

This section first exhibits the CLOP method's effect on regularization in supervised learning and then demonstrates its efficiency in reinforcement learning. Hyperparameters, network architectures, and implementation choices are summarized in Appendix A and C.

5.1 SUPERVISED LEARNING

To assess the contribution of the CLOP layer in supervised learning, we first train a simple network (three convolutional layers followed by three linear layers) on the MNIST dataset (LeCun et al., 1998) and evaluate its generalization performance on the USPS (Hull, 1994) dataset, a slightly different digit classification dataset. Then, to confirm this performance evaluation on large-scale images, we train a VGG11 network (Simonyan & Zisserman, 2014) using the Imagenette dataset,[1] a subset of ten classes taken from Imagenet (Deng et al., 2009). In both experiments, the networks are trained using four configurations: with dropout in the dense part of the network, with batch-normalization between convolutions, with a CLOP layer after the last convolutional layer, and without any regularization. Results reported in Table 1 show that the CLOP layer allows the networks to generalize considerably better on USPS data than the unregularized network or when using dropout or batch-normalization. Note that testing on USPS implies both generalization as defined in Section 2, and *domain generalization* (Wang et al., 2021a), that is the ability to generalize to other input data distributions at test time. Likewise, applying the CLOP layer to a VGG11 improves generalization performance compared to the other methods, thus confirming the intuition that localized permutations at the feature level during training may improve generalization at testing.

---

[1]https://github.com/fastai/imagenette

Method	MNIST(train)	USPS(test)	Imagenette2 (train)	Imagenette2 (test)
Plain network	100 ± 0.0	81.6 ± 1.2	100 ± 0.0	74.7 ± 0.7
Dropout	99.7 ± 0.0	77.7 ± 1.4	100 ± 0.0	81.4 ± 0.6
Batch-norm	100 ± 0.0	65.6 ± 7.7	100 ± 0.0	82.4 ± 0.5
CLOP (ours)	99.9 ± 0.0	91.2 ± 2.4	100 ± 0.0	83.8 ± 0.4

Table 1: Comparison of train and test accuracies in supervised learning

(a) Coinrun   (b) Leaper

Figure 3: Example of levels heterogeneity on two Procgen environments

5.2 REINFORCEMENT LEARNING

We assess the regularization capability of our method in reinforcement learning on the OpenAI Procgen benchmark, commonly used to test the generalization of RL agents. Procgen is a set of 16 visual games, each allowing procedural generation of game levels. All environments use a discrete 15-dimensional action space and provide a $64 \times 64 \times 3$ image observations to the agent. Since all levels are procedurally generated, Procgen training and testing levels differ in many visual aspects like backgrounds, assets, or intrinsic level design (see Figure 3).

CLOP within PPO. In the following experiments, we train all agents with PPO (Schulman et al., 2017) and the hyperparameters recommended by Cobbe et al. (2020). As in many PPO implementations, our actor and critic share a common stem of first convolutional layers, extracting shared features. Since the critic's role is only to help estimate the advantage in states that are present in the replay buffer (in other words: since the critic won't ever be used to predict values elsewhere than on the states it has been trained on), overfitting of the critic is not a critical issue in PPO. An overfitting critic will provide an oracle-like supervision signal, which is beneficial to the actor optimization process without inducing overfitting in the policy. Therefore, we choose to append a CLOP layer only to the actor part of the agent's network, located immediately after the shared feature extractor part.

Comparison with classical supervised learning regularization methods. We first compare the performance of the data augmentation in the latent space performed by the CLOP layer with classical data augmentation methods that directly enhance inputs. Following the setup of Cobbe et al. (2020), we evaluate the zero-shot generalization of RL agents using the CLOP layer on three Procgen environments, setting the difficulty parameter to hard. All agents were trained during 200M steps on a set of 500 training levels and evaluated on 1000 different test levels. Figure 4 shows the average sum of rewards on the test levels obtained along training for all agents: the CLOP agents outperform classical data augmentation techniques. CLOP offers three significant advantages: asymptotic generalization performance is better, sample complexity is smaller (the agent needs fewer interactions

(a) Dodgeball   (b) Miner   (c) Chaser

Figure 4: Average sum of reward on test environments.

Game	PPO	Mixreg	Rand + FM	UCB-DraC	IBAC-SNI	RAD	IDAAC	CLOP (Ours)
Bigfish	4.3 ± 1.2	7.1 ± 1.6	0.6 ± 0.8	9.2 ± 2.0	0.8 ± 0.9	9.9 ± 1.7	$\underline{18.5 \pm 1.2}$	$\mathbf{19.2 \pm 4.6}$
BossFight	9.1 ± 0.1	8.2 ± 0.7	1.7 ± 0.9	7.8 ± 0.6	1.0 ± 0.7	7.9 ± 0.6	$\mathbf{9.8 \pm 0.6}$	$\underline{9.7 \pm 0.1}$
CaveFlyer	5.5 ± 0.4	$\underline{6.1 \pm 0.6}$	5.4 ± 0.8	5.0 ± 0.8	$\mathbf{8.0 \pm 0.8}$	5.1 ± 0.6	5.0 ± 0.6	5.0 ± 0.3
Chaser	$\underline{6.9 \pm 0.8}$	5.8 ± 1.1	1.4 ± 0.7	6.3 ± 0.6	1.3 ± 0.5	5.9 ± 1.0	6.8 ± 1.0	$\mathbf{8.7 \pm 0.2}$
Climber	6.3 ± 0.4	6.9 ± 0.7	5.3 ± 0.7	6.3 ± 0.6	3.3 ± 0.6	6.9 ± 0.8	$\mathbf{8.3 \pm 0.4}$	$\underline{7.4 \pm 0.3}$
CoinRun	9.0 ± 0.1	8.6 ± 0.3	$\underline{9.3 \pm 0.4}$	8.8 ± 0.2	8.7 ± 0.6	9.0 ± 0.8	$\mathbf{9.4 \pm 0.1}$	9.1 ± 0.1
Dodgeball	3.3 ± 0.4	1.7 ± 0.4	0.5 ± 0.4	$\underline{4.2 \pm 0.9}$	1.4 ± 0.4	2.8 ± 0.7	3.2 ± 0.3	$\mathbf{7.2 \pm 1.2}$
FruitBot	$\underline{28.5 \pm 0.2}$	27.3 ± 0.8	24.5 ± 0.7	27.6 ± 0.4	24.7 ± 0.8	27.3 ± 1.8	27.9 ± 0.5	$\mathbf{29.8 \pm 0.3}$
Heist	2.7 ± 0.2	2.6 ± 0.4	2.4 ± 0.6	3.5 ± 0.4	$\mathbf{9.8 \pm 0.6}$	4.1 ± 1.0	3.5 ± 0.2	$\underline{4.5 \pm 0.2}$
Jumper	5.4 ± 0.1	6.0 ± 0.3	5.3 ± 0.6	6.2 ± 0.3	3.6 ± 0.6	$\mathbf{6.5 \pm 0.6}$	$\underline{6.3 \pm 0.2}$	5.6 ± 0.2
Leaper	6.5 ± 1.1	5.3 ± 1.1	6.2 ± 0.5	4.8 ± 0.9	6.8 ± 0.6	4.3 ± 1.0	$\underline{7.7 \pm 1.0}$	$\mathbf{9.2 \pm 0.2}$
Maze	5.1 ± 0.2	5.2 ± 0.5	$\underline{8.0 \pm 0.7}$	6.3 ± 0.1	$\mathbf{10.0 \pm 0.7}$	6.1 ± 1.0	5.6 ± 0.3	5.9 ± 0.2
Miner	8.4 ± 0.4	9.4 ± 0.4	7.7 ± 0.6	9.2 ± 0.6	8.0 ± 0.6	9.4 ± 1.2	$\underline{9.5 \pm 0.4}$	$\mathbf{9.8 \pm 0.3}$
Ninja	6.5 ± 0.1	6.8 ± 0.5	6.1 ± 0.8	6.6 ± 0.4	$\mathbf{9.2 \pm 0.6}$	$\underline{6.9 \pm 0.8}$	6.8 ± 0.4	5.8 ± 0.4
Plunder	6.1 ± 0.8	5.9 ± 0.5	3.0 ± 0.6	8.3 ± 1.1	2.1 ± 0.8	$\underline{8.5 \pm 1.2}$	$\mathbf{23.3 \pm 1.4}$	5.4 ± 0.7
StarPilot	36.1 ± 1.6	32.4 ± 1.5	8.8 ± 0.7	30.0 ± 1.3	4.9 ± 0.8	33.4 ± 5.1	$\underline{37.0 \pm 2.3}$	$\mathbf{40.9 \pm 1.7}$

Table 2: Average returns on Procgen games. Bold: best agent; underlined: second best.

steps to reach high performance levels) and computational complexity is negligible. Interestingly, other regularization methods based on pixel-block disturbance, such as cutout or cutout-color, despite being somehow related to the CLOP layer but applied at the input image level, often even decrease the baseline performance. The CLOP layer also outperforms dropout, another feature-level manipulation method. Compared to dropout, the CLOP layer randomly shifts features from their original position instead of completely removing them. The persistence of these features in the feature map but in other positions appears to help to prevent spurious correlations with the reward signal. Overall, empirical validation confirms that the CLOP layer has a significant impact on generalization, helping prevent observational overfitting by decorrelating features that are irrelevant to the task (such as background elements) from the policy's output.

Comparison with reinforcement learning regularization methods. We also compare the performance of the CLOP layer with current state-of-the-art regularization methods specifically designed for reinforcement learning. Following the protocol proposed by Raileanu et al. (2020), we conducted a set of experiments on the easy setting of all environments available in Procgen. All agents were trained during 25M steps on 200 training levels and their performance is compared on the entire distribution of levels. We report the average sum of rewards for all environments in Table 2. The CLOP layer outperforms other state-of-the-art methods on 7 out of the 16 Procgen environments, sometimes by a large margin. Compared to these methods, the CLOP layer offers a direct and easy way to augment the RL agent's ability to generalize to unseen environments, with the benefit of being entirely complementary with each of them.

CLOP improves both performance and generalization gap. Table 3 reports the gains obtained by the CLOP layer in terms of performance on training levels, testing levels and generalization gap, compared to PPO, after 25M steps of training on all Procgen games. The full training plots are reported in Appendix B. The CLOP layer systematically improves the generalization gap (of 30% on average and up to 50% on StarPilot). It also has a notable effect on both the training and the generalization absolute performance. On all games but three (CaveFlyer, Ninja, and Plunder), the training performance is at least equivalent (10 games), and sometimes much better (BigFish, Chaser, Leaper) with the CLOP layer, both in training speed and asymptotical performance. The CLOP layer's generalization absolute performance is also better on all but the same three games,[2] with a significantly greater advantage in number of games. It reaches significantly better generalization performance on 11 games and equivalent performance on 2 games (Coinrun, Jumper).

Influence of the permutation rate. The CLOP layer has a single tunable hyperparameter α, corresponding to the probability of accepting a candidate permutation between pixels during the forward pass. Figure 5 reports the effect of varying this hyperparameter on three environments where the CLOP layer improved generalization. Interestingly, large values of α do not prevent the agent from learning. In some cases (Figure 5c), it might even lead to improved performance. Since permutations occur locally, a high probability of swapping does not imply the risk of generating latent states that are too far off from the original latent state (and would thus harm overall training performance).

---

[2]since the generalization gap is still reduced, we conjecture it is a matter of convergence of the training process, rather than of generalization ability

Game	PPO train	PPO test	PPO gap	CLOP train	CLOP test	CLOP gap
bigfish	18.1 ± 4.0	4.3 ± 1.2	13.9 ± 2.8	$+48.0\%$	$+344.4\%$	-39.1%
bossfight	10.3 ± 0.6	9.1 ± 0.1	1.4 ± 0.6	$+1.9\%$	$+6.2\%$	-31.6%
caveflyer	7.8 ± 1.4	5.5 ± 0.4	2.4 ± 1.1	-15.4%	-7.9%	-32.8%
chaser	8.0 ± 1.2	6.9 ± 0.8	1.5 ± 0.7	$+18.8\%$	$+26.7\%$	-32.3%
climber	10.2 ± 0.4	6.3 ± 0.4	4.0 ± 0.4	-5.9%	$+16.6\%$	-38.6%
coinrun	10.0 ± 0.0	9.0 ± 0.1	1.1 ± 0.0	-0.4%	$+1.5\%$	-22.0%
dodgeball	10.8 ± 1.7	3.3 ± 0.4	7.5 ± 1.6	$+8.2\%$	$+117.7\%$	-37.5%
fruitbot	31.5 ± 0.5	28.5 ± 0.2	3.3 ± 0.5	$+0.0\%$	$+4.3\%$	-39.4%
heist	8.8 ± 0.3	2.7 ± 0.2	6.3 ± 0.4	$+5.1\%$	$+66.4\%$	-23.2%
jumper	8.9 ± 0.4	5.4 ± 0.1	3.8 ± 0.3	-0.6%	$+3.4\%$	-7.2%
leaper	7.1 ± 1.6	6.5 ± 1.1	0.7 ± 0.7	$+39.1\%$	$+41.1\%$	-0.7%
maze	9.9 ± 0.1	5.1 ± 0.2	4.9 ± 0.3	-1.5%	$+14.9\%$	-15.0%
miner	12.7 ± 0.2	8.4 ± 0.4	4.7 ± 0.3	$+0.9\%$	$+17.4\%$	-34.6%
ninja	9.6 ± 0.3	6.5 ± 0.1	3.2 ± 0.2	-16.6%	-10.4%	-28.1%
plunder	8.9 ± 1.7	6.1 ± 0.8	2.8 ± 1.0	-23.1%	-11.0%	-47.9%
starpilot	44.7 ± 2.4	36.1 ± 1.6	10.5 ± 1.7	$+2.1\%$	$+13.3\%$	-50.4%

Table 3: Performance on training and testing levels, and generalization gap after 25M steps.

(a) Bigfish   (b) Dodgeball   (c) Chaser

Figure 5: Influence of the α parameter on test performance.

Figures 6c and 6d (see next paragraph) illustrate this risk. Another desirable property of this parameter is that performance does not seem to be too sensitive to it. Any non-zero value seems to permit generalization. Consequently, using the CLOP layer does not require fine hyperparameter tuning.

Locality and channel-consistency are crucial features for generalization. Figure 6 illustrates the effect of a forward pass through the CLOP layer without these components on a handcrafted, three-channel (RGB) feature map on the Leaper game (Figure 6b). Although there is a non-zero probability that CLOP sends a pixel's content arbitrarily far from its original position, the output of the layer retains an interpretable shape from a human perspective (Figure 6c). In contrast, Figure 6d illustrates the output if the permutations are not local anymore and can send any pixel's content anywhere in the image in a single permutation. Similarly, Figure 6e shows how loosing the channel-consistency feature creates new colors in the image by recombining unrelated features together. As discussed in Section 4, both these behaviors seem undesirable for proper generalization in RL. We performed an ablation study to assess the respective influence of these two components. Figure 7 reports the performance drop on testing environments when they are turned off, and shows that both the locality and channel-consistency properties of CLOP are beneficial to generalization. Interestingly, non-local permutations and channel-inconsistent permutations still provide better generalization than plain PPO. Such image modifications are agnostic to the feature maps spatial structure. But since irrelevant features (e.g., background) can be swapped without consequences, and since these features concern a majority of pixels, with high probability these modifications still generate samples that preserve the useful semantic information. However, whenever useful feature pixels are swapped without locality, this semantic information is made ambiguous between actual experience samples and augmented data, that might induce different action choices. This confirms the general idea that data augmentation helps generalization in RL, but that improved performance comes from preserving spatial knowledge (length, width, and channel-wise) in the latent space. We also used Grad-Cam (Selvaraju et al., 2017) to produce visual explanations of the importance of these two factors. Figure 8 shows the areas of the image that were most important for the agent's policy.[3] We can observe that an agent trained using a CLOP layer stripped of the local permutation feature focuses

---

[3]Full videos available at `https://bit.ly/3D9fyIK`.

| (a) Original input | (b) Feature map | (c) CLOP | (d) No locality | (e) No consistency |

Figure 6: Applying the CLOP layer ($\alpha = 0.5$). Ablation of the locality and consistency properties.

| (a) Bigfish | (b) Dodgeball | (c) Chaser |

Figure 7: Ablation study on the locality and consistency properties

| (a) CLOP | (b) No locality | (c) CLOP | (d) No locality | (e) CLOP | (f) No locality |

Figure 8: Saliencies induced by the locality property ($\alpha = 0.5$)

on a spread-out portion of the image, while the full CLOP agent displays very focused saliency areas. The policies of the PPO agents, or those of the CLOP agents with local but channel-inconsistent permutations, display much more focused saliency maps too, despite having lower performance than the full CLOP agents. This underlines a limit of saliency map interpretation: focussing on specific pixels is important but it is the combination of these pixel values that makes a good decision and this process is more intricate than solely concentrating on important parts of the image.

6 CONCLUSION

In this work, we introduce the Channel-consistent LOcal Permutations (CLOP) technique, intended to improve generalization properties of convolutional neural networks. This stems from an original perspective on observational overfitting in image-based reinforcement learning. We discuss why observational overfitting is a structural risk minimization problem that should be tackled at the level of abstract state representation features. To prevent RL agents from overfitting their decisions to in-game progress indicators and, instead, push informative, causal variables into the policy features, we implement CLOP as a feed-forward layer and apply it to the deepest feature maps. This corresponds to performing data augmentation at the feature level while preserving the spatial structure of these features. The CLOP layer implies very simple operations that induce a negligible overhead cost. Agents equipped with a CLOP layer set a new state-of-the-art reference on the Procgen generalization benchmark. Although generalization in RL is a broad topic that reaches out well beyond observational overfitting, the approach taken here endeavors to shed new light and proposes a simple and low-cost original solution to this challenge, hopefully contributing a useful tool to the community.

REFERENCES

Christopher M Bishop. *Neural networks for pattern recognition*. Oxford university press, 1995.

Karl Cobbe, Oleg Klimov, Chris Hesse, Taehoon Kim, and John Schulman. Quantifying generalization in reinforcement learning. In *International Conference on Machine Learning*, pp. 1282–1289. PMLR, 2019.

Karl Cobbe, Chris Hesse, Jacob Hilton, and John Schulman. Leveraging procedural generation to benchmark reinforcement learning. In *International conference on machine learning*, pp. 2048–2056. PMLR, 2020.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Terrance DeVries and Graham W Taylor. Improved regularization of convolutional neural networks with cutout. *arXiv preprint arXiv:1708.04552*, 2017.

Lasse Espeholt, Hubert Soyer, Remi Munos, Karen Simonyan, Vlad Mnih, Tom Ward, Yotam Doron, Vlad Firoiu, Tim Harley, Iain Dunning, et al. Impala: Scalable distributed deep-rl with importance weighted actor-learner architectures. In *International Conference on Machine Learning*, pp. 1407–1416. PMLR, 2018.

Jesse Farebrother, Marlos C Machado, and Michael Bowling. Generalization and regularization in dqn. *arXiv preprint arXiv:1810.00123*, 2018.

Ian Goodfellow, Yoshua Bengio, and Aaron Courville. Deep learning, 2016.

Irina Higgins, Arka Pal, Andrei Rusu, Loic Matthey, Christopher Burgess, Alexander Pritzel, Matthew Botvinick, Charles Blundell, and Alexander Lerchner. Darla: Improving zero-shot transfer in reinforcement learning. In *International Conference on Machine Learning*, pp. 1480–1490. PMLR, 2017.

Jonathan J. Hull. A database for handwritten text recognition research. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 16(5):550–554, 1994.

Maximilian Igl, Kamil Ciosek, Yingzhen Li, Sebastian Tschiatschek, Cheng Zhang, Sam Devlin, and Katja Hofmann. Generalization in reinforcement learning with selective noise injection and information bottleneck. *Advances in Neural Information Processing Systems*, 32:13978–13990, 2019.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International conference on machine learning*, pp. 448–456. PMLR, 2015.

Garud N Iyengar. Robust dynamic programming. *Mathematics of Operations Research*, 30(2): 257–280, 2005.

Niels Justesen, Ruben Rodriguez Torrado, Philip Bontrager, Ahmed Khalifa, Julian Togelius, and Sebastian Risi. Illuminating generalization in deep reinforcement learning through procedural level generation. In *NeurIPS Workshop on Deep Reinforcement Learning*, 2018.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Advances in neural information processing systems*, 25:1097–1105, 2012.

Anders Krogh and John A Hertz. A simple weight decay can improve generalization. In *Advances in neural information processing systems*, pp. 950–957, 1992.

Misha Laskin, Kimin Lee, Adam Stooke, Lerrel Pinto, Pieter Abbeel, and Aravind Srinivas. Reinforcement learning with augmented data. *Advances in Neural Information Processing Systems*, 33, 2020.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Kimin Lee, Kibok Lee, Jinwoo Shin, and Honglak Lee. Network randomization: A simple technique for generalization in deep reinforcement learning. In *International Conference on Learning Representations*, 2019.

Marlos C Machado, Marc G Bellemare, Erik Talvitie, Joel Veness, Matthew Hausknecht, and Michael Bowling. Revisiting the arcade learning environment: Evaluation protocols and open problems for general agents. *Journal of Artificial Intelligence Research*, 61:523–562, 2018.

Tom M Mitchell. *The need for biases in learning generalizations*. Department of Computer Science, Laboratory for Computer Science Research . . . , 1980.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*, 2013.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.

Alex Nichol, Vicki Pfau, Christopher Hesse, Oleg Klimov, and John Schulman. Gotta learn fast: A new benchmark for generalization in rl. *arXiv preprint arXiv:1804.03720*, 2018.

Charles Packer, Katelyn Gao, Jernej Kos, Philipp Krähenbühl, Vladlen Koltun, and Dawn Song. Assessing generalization in deep reinforcement learning. *arXiv preprint arXiv:1810.12282*, 2018.

David C Plaut, Steven J Nowlan, and Geoffrey E Hinton. Experiments on learning by back propagation. Technical Report CMU-CS-86-126, Carnegie-Mellon University, 1986.

Martin L Puterman. *Markov decision processes: discrete stochastic dynamic programming*. John Wiley & Sons, 2014.

Emmanuel Rachelson and Michail G. Lagoudakis. On the locality of action domination in sequential decision making. In *11th International Symposium on Artificial Intelligence and Mathematics*, 2010.

Roberta Raileanu and Rob Fergus. Decoupling value and policy for generalization in reinforcement learning. *arXiv preprint arXiv:2102.10330*, 2021.

Roberta Raileanu, Max Goldstein, Denis Yarats, Ilya Kostrikov, and Rob Fergus. Automatic data augmentation for generalization in deep reinforcement learning. *arXiv preprint arXiv:2006.12862*, 2020.

Aravind Rajeswaran, Kendall Lowrey, Emanuel Todorov, and Sham Kakade. Towards generalization and simplicity in continuous control. *arXiv preprint arXiv:1703.02660*, 2017.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE international conference on computer vision*, pp. 618–626, 2017.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

Xingyou Song, Yiding Jiang, Stephen Tu, Yilun Du, and Behnam Neyshabur. Observational overfitting in reinforcement learning. In *International Conference on Learning Representations*, 2019.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *The journal of machine learning research*, 15(1):1929–1958, 2014.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2818–2826, 2016.

Christian Szegedy, Sergey Ioffe, Vincent Vanhoucke, and Alexander A Alemi. Inception-v4, inception-resnet and the impact of residual connections on learning. In *Thirty-first AAAI conference on artificial intelligence*, 2017.

Josh Tobin, Rachel Fong, Alex Ray, Jonas Schneider, Wojciech Zaremba, and Pieter Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *2017 IEEE/RSJ international conference on intelligent robots and systems (IROS)*, pp. 23–30. IEEE, 2017.

Vladimir Vapnik. Principles of risk minimization for learning theory. In *Advances in neural information processing systems*, pp. 831–838, 1992.

Li Wan, Matthew Zeiler, Sixin Zhang, Yann Le Cun, and Rob Fergus. Regularization of neural networks using dropconnect. In *International conference on machine learning*, pp. 1058–1066. PMLR, 2013.

Jindong Wang, Cuiling Lan, Chang Liu, Yidong Ouyang, and Tao Qin. Generalizing to unseen domains: A survey on domain generalization. In *Proceedings of the Thirtieth International Joint Conference on Artificial Intelligence*, pp. 4627–4635, 2021a.

Kaixin Wang, Bingyi Kang, Jie Shao, and Jiashi Feng. Improving generalization in reinforcement learning with mixture regularization. In *NeurIPS*, 2020.

Xudong Wang, Long Lian, and Stella X Yu. Unsupervised visual attention and invariance for reinforcement learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6677–6687, 2021b.

Denis Yarats, Ilya Kostrikov, and Rob Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. In *International Conference on Learning Representations*, 2020.

Sangdoo Yun, Dongyoon Han, Seong Joon Oh, Sanghyuk Chun, Junsuk Choe, and Youngjoon Yoo. Cutmix: Regularization strategy to train strong classifiers with localizable features. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 6023–6032, 2019.

Amy Zhang, Nicolas Ballas, and Joelle Pineau. A dissection of overfitting and generalization in continuous reinforcement learning. *arXiv preprint arXiv:1806.07937*, 2018a.

Amy Zhang, Rowan Thomas McAllister, Roberto Calandra, Yarin Gal, and Sergey Levine. Learning invariant representations for reinforcement learning without reconstruction. In *International Conference on Learning Representations*, 2020.

Chiyuan Zhang, Oriol Vinyals, Remi Munos, and Samy Bengio. A study on overfitting in deep reinforcement learning. *arXiv preprint arXiv:1804.06893*, 2018b.

Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. In *International Conference on Learning Representations*, 2018c.

A NETWORK ARCHITECTURE AND TRAINING HYPER-PARAMETERS

A.1 SUPERVISED LEARNING

We used a simple network for the MNIST-USPS experiment, composed of a convolutional feature extractor:

- Conv2D(filters=32, kernel=5×5, stride=1, padding=2, activation=ReLU)

- Max Pooling(filters=2×2, stride=2)
- Conv2D(filters=64, kernel=5×5, stride=1, padding=2, activation=ReLU)
- Max Pooling(filters=2×2, stride=2)
- Conv2D(filters=128, kernel=3×3, stride=1, padding=2, activation=ReLU)

followed by a two hidden layer MLP:

- Dense(nb_neurons=512, activation=ReLU)
- Dense(nb_neurons=100, activation=ReLU)
- Dense(nb_neurons=10, activation=Linear)

The dropout and the CLOP layers where added between the feature extractor and the classifier. For the batch-normalization configuration, we added batch-normalization layers after each convolutional layer. We trained all networks for 30 epochs with Adam, a learning rate $lr = 5 \cdot 10^{-4}$, and a cosine annealing schedule.

For the Imagenette experiment, we used Pytorch's implementation of VGG11, replacing the output layer to match the ten classes. When testing our method, we removed the dropout layers from the fully connected part of the network and added a CLOP layer between the last convolutional layer and the first fully connected one. We trained all networks on 90 epochs with Adam, a learning rate $lr = 5 \cdot 10^{-4}$, and a cosine annealing schedule.

A.2 REINFORCEMENT LEARNING

We based our implementation of PPO on the one proposed by Hojoon Lee available at: `https://github.com/joonleesky/train-procgen-pytorch`. We used an IMPALA (Espeholt et al., 2018) architecture on all agents, with a CLOP layer added to the actor part only for our CLOP agents. Figure 9 illustrates CLOP agent's architecture. Values of α used for each environment are reported in Table 4.

Game	alpha
Bigfish	0.6
StarPilot	0.3
FruitBot	0.3
BossFight	0.3
Ninja	0.3
Plunder	0.3
CaveFlyer	0.3
CoinRun	0.3
Jumper	0.3
Chaser	0.8
Climber	0.3
Dodgeball	0.6
Heist	0.3
Leaper	0.8
Maze	0.3
Miner	0.3

Figure 9: CLOP layer within the IMPALA architecture Table 4: Values of α

B   FULL RESULTS OF CLOP AGENTS ON PROCGEN

Figure 10 and Table 5 display the performance of CLOP agents and PPO on training and testing levels for all Procgen games (easy setting, 25M training steps).

Game	PPO train	PPO test	PPO gap	CLOP train	CLOP test	CLOP gap
bigfish	18.1 ± 4.0	4.3 ± 1.2	13.9 ± 2.8	26.9 ± 2.0	19.2 ± 1.6	8.5 ± 1.7
bossfight	10.3 ± 0.6	9.1 ± 0.1	1.4 ± 0.6	10.6 ± 0.6	9.7 ± 0.1	0.9 ± 0.7
caveflyer	7.8 ± 1.4	5.5 ± 0.4	2.4 ± 1.1	6.6 ± 0.5	5.0 ± 0.3	1.6 ± 0.4
chaser	8.0 ± 1.2	6.9 ± 0.8	1.5 ± 0.7	9.6 ± 1.0	8.7 ± 0.2	1.0 ± 0.8
climber	10.2 ± 0.4	6.3 ± 0.4	4.0 ± 0.4	9.6 ± 0.2	7.4 ± 0.3	2.5 ± 0.3
coinrun	10.0 ± 0.0	9.0 ± 0.1	1.1 ± 0.0	9.9 ± 0.1	9.1 ± 0.1	0.9 ± 0.2
dodgeball	10.8 ± 1.7	3.3 ± 0.4	7.5 ± 1.6	11.7 ± 1.5	7.2 ± 1.2	4.7 ± 0.9
fruitbot	31.5 ± 0.5	28.5 ± 0.2	3.3 ± 0.5	31.6 ± 1.0	29.8 ± 0.3	2.0 ± 0.9
heist	8.8 ± 0.3	2.7 ± 0.2	6.3 ± 0.4	9.3 ± 0.4	4.5 ± 0.2	4.8 ± 0.4
jumper	8.9 ± 0.4	5.4 ± 0.1	3.8 ± 0.3	8.9 ± 0.3	5.6 ± 0.2	3.4 ± 0.2
leaper	7.1 ± 1.6	6.5 ± 1.1	0.7 ± 0.7	9.9 ± 0.2	9.2 ± 0.2	0.7 ± 0.2
maze	9.9 ± 0.1	5.1 ± 0.2	4.9 ± 0.3	9.7 ± 0.1	5.9 ± 0.2	4.1 ± 0.4
miner	12.7 ± 0.2	8.4 ± 0.4	4.7 ± 0.3	12.8 ± 0.1	9.8 ± 0.3	3.0 ± 0.3
ninja	9.6 ± 0.3	6.5 ± 0.1	3.2 ± 0.2	8.0 ± 0.5	5.8 ± 0.4	2.3 ± 0.2
plunder	8.9 ± 1.7	6.1 ± 0.8	2.8 ± 1.0	6.8 ± 1.0	5.4 ± 0.7	1.4 ± 0.7
starpilot	44.7 ± 2.4	36.1 ± 1.6	10.5 ± 1.7	45.6 ± 2.8	40.9 ± 1.7	5.2 ± 4.0

Table 5: Performance on training and testing levels, and generalization gap after 25M steps

Figure 10: Train and test learning curves in easy mode

Experiment	Number of epochs/steps	Time by experiment	Number of experiment repetitions
5.1 MNIST and USPS	30	2 minutes	20
5.1 Imagenette2	90	40 minutes	10
5.2 Hard (for each environment)	200M	22 hours	3
5.2 Easy (for each environment)	25M	2h40	5

Table 6: Experimental setup

C REPRODUCIBILITY

All the experiments from Section 5 were run on a desktop machine (Intel i9, 10th generation processor, 32GB RAM) with a single NVIDIA RTX 3080 GPU. Details about each experiments are reported in Table 6.

In a general context of data efficient machine learning research, it seems relevant to underline that each subfigure in Figure 4 evaluated 7 regularization methods, over 3 repetitions. Overall, this required an order of $7 \times 3 \times 22 = 462$ computing hours (around 20 days) for a single subfigure on a high-end desktop machine. The experimental protocol used to select the three games reported in Figure 4 relies on the results obtained on the easy mode of Procgen (Figure 10 and Table 2), on a random sampling of hard mode games, and on limited training length results on hard mode games.

Besides this information, we provide the full source code of our implementation and experiments, along with the data files of experimental results we obtained.