WHAT TO DO IF SPARSE REPRESENTATION LEARNING FAILS UNEXPECTEDLY?

ABSTRACT

Learning physical equations from data is essential for scientific discovery and engineering modeling. However, most of the existing methods rely on two rules: (1) learn a sparse representation to fit data and (2) check if the loss objective function satisfies error thresholds. This paper illustrates that such conditions are far from sufficient. Specifically, we show that sparse non-physical approximations exist with excellent fitting accuracy, but fail to adequately model the situation. To fundamentally resolve the data-fitting problem, we propose a physical neural network (PNN) utilizing "Range, Inertia, Symmetry, and Extrapolation" (RISE) constraints. RISE is based on a complete analysis for the generalizability of data properties for physical systems. The first three techniques focus on the definition of physics in space and time. The last technique of extrapolation is novel based on active learning without an inquiry, using cross-model validation. We validate the proposed PNN-RISE method via a synthetic dataset, power system dataset, and mass-damper system dataset. Numerical results show the universal capability of the PNN-RISE approach to quickly identify the hidden physical models without local optima, opening the door for the fast and highly accurate discovery of the physical laws or systems with external loads.

1 INTRODUCTION

Internet of Everything (IoE) connects new devices into an intelligent web at an unprecedented speed. If utilized systematically, IoE can create much more efficient productivity via coordinated effort among humans, processes, data, and things (Li et al., 2020). Among various analytical frameworks, dynamic data-driven applications systems (DDDAS) naturally interweaves diversified information via dynamic and data-driven analysis to assimilate the system model for a wide range of applications (Blasch et al., 2018), thus significantly increasing the performance of the simulation model and the application model. The simulation model in DDDAS usually incorporates physical methods (Nasiakou et al., 2018; Chowdhury & Subramani, 2020) which provides a structure for model-based and data-driven coordination. However, many of the physical laws in the web of IoE can be unknown. The laws of the web of IoE remain to be discovered manually or automatically to benefit society.

The most economically efficient way to discover the physical law is to use machine learning to analyze the pattern behind the data stream, which is an important topic of artificial intelligence (Sahoo et al., 2018; Udrescu & Tegmark, 2020). In previous studies, such as symbolic regression (Petersen, 2019), the sparsity representation is used to measure the accountability of physics (Brunton et al., 2016). The underlying assumption is that sparsity can ensure physical exactness due to parsimonious principle (Li, 2013). While low complexity of learning models is a necessary condition for for enhancing the understanding of physical laws (Schölkopf et al., 2002; Blasch et al., 2021), there is not a universal sufficient condition to solve model recovery problem with a guarantee. Therefore, one approach is to add additional conditions to ensure a physical recovery, e.g., near-zero fitting errors (Brunton et al., 2016; Champion et al., 2019; Petersen, 2019) or/and cross validation (Sahoo et al., 2018; Kim et al., 2020).

However, it can be observed that different machine learners easily fit the available data with a sparse but wrong model. Such a case can happen even with cross-validation.

The overfitting should challenge the directions of many researchers in physical system discovery, who believe that only the true physical laws can achieve sparse recovery with a perfect fit. To

resolve the problem, we first eliminate non-physical local optima of the neural network (NN) by discarding all the non-physical parameters, i.e., model parameters indirectly related to the physical representation. The process is novel as existing NN-based methods require certain non-physical parameters to control the representation sparsity (Liu & Laili, 2018; Petersen, 2019). We show how to design a NN with pure physical parameters, entitled a *physical neural network* (PNN). The key of PNN is to enforce activation to physical weights for sparse selection, completely removing the non-physical parameters and local optima.

In training the PNN, there can still be local optimum solutions, bus actual knowledge can enhance model fidelity. For obtaining the ground truth, physical systems' examination can be used to extract common and universal properties. Subsequently, the PNN is restricted to systematically obey the physical and system properties. Specifically, constraints based on the physical distance and physical symmetry are embedded in the training function to quantify the spatial relationship enforced by physical law. Furthermore, as physical systems evolve over time, inertial property for physical systems are extracted and updated. In general, the regularization from physical laws focuses the learning/optimization towards a more meaningful fitness understanding of the given data.

Although the two designs of PNN and physics constraints aim to obtain the physical laws via fitting existing data, the incorporation of physical laws' biggest impact is its capability to achieve zero fitting errors even beyond the training data range. Unfortunately, it will be costly if not impossible to conduct active learning for every Internet of Things (IoT) system due to its scale. To provide the "free lunch" of adding the extrapolation capability of PNN, we create an new learning method for cross-model validation based on probabilistic estimates with physical kernels. Specifically, we propose a physically meaningful forecast to identify out-of-sample points with a confidence level. Then, the results are integrated as a weak supervision for learning the exact physics for extrapolation, in addition to the physical constrained PNN. Together, PNN-RISE uses the PNN container to include the RISE principles, enforcing the recovered function to satisfy constraints on *range (R), inertia (I), symmetry (S), and extrapolation (E)*. And, it is worth highlighting that the extrapolation technique is a brand-new technique for active learning without an inquiry. Empirically, extensive validations show that the PNN-RISE outperforms the state-of-the-art methods. Consistently, scenarios with or without each constraint in RISE validate the approach. Furthermore, for each constraint, we quantify its strength with different levels, highlighting that loose constraints are enough to obtain high accuracy in the proposed PNN.

In summary, the contributions in Fig. 1 are (1) showing that the sparse recovery with low training and testing errors does not ensure physical law recovery, (2) reducing the possibilities of local optima significantly by eliminating non-physical parameters in learning model selection and design, (3) proposing four physical principles to completely characterize physical systems via constrained learning, and (4) creating a novel learning method for physical systems extrapolation as probabilistic forecasting out-of-sample cross-model validation (FOCV).

Figure 1: The proposed framework.

2 RELATED WORK

Physical System Identification. To recover system information, supervised learning can be used to approximate input-output relationships for inferences, e.g., regression and classification (Huang et al., 2006; Hornik et al., 1990). These regression and classification tools show good numerical performance in non-physical and physical applications, including computer vision for images and

videos (Lu & Weng, 2007; Wang et al., 2017a; Karpathy et al., 2014), natural language processing for texts (Nadkarni et al., 2011; Hirschberg & Manning, 2015), and speech processing for audio (Yu & Deng, 2016; Abdel-Hamid et al., 2014). Additionally, deep neural networks (DNNs) boost the image classification accuracy (Hinton et al., 2006; Krizhevsky et al., 2012) by using latent layers to extract nonlinear features hidden in image data. While boosting makes machine learning useful for non-physical systems, physical system applications require the accuracy to be much higher for operation or control, e.g., near 100% for Six Sigma performance Walshe et al. (2010), so that system operators can safely operate the system to avoid outages or cascading failures (Chung et al., 2018; Liu et al., 2017). Even worse, many supervised learning approaches are black boxes that lack physical interpretability for reliable operations, accountability for control, as well as certifiability for performance standards (Manitsas et al., 2012; Zamzam & Sidiropoulos, 2020; Shareef et al., 2013; Mestav et al., 2018; Du & Li, 2019; Hu et al., 2020; Karami & Mohammadi, 2008; Müller et al., 2010; Baghaee et al., 2017).

Therefore, some works find utilizing contextual information improves physical-system identification where they assume a good knowledge of physical basis and sufficient measurements across the system (Yu et al., 2017; Chen et al., 2020). Similarly, (Brunton et al., 2016; Champion et al., 2019) assume prior symbols are known in a dictionary and introduce sparse regression to select symbols. However, these assumptions are too limiting in that for most complex systems, it would be difficult to know all the physical basis responses ahead of time. For example, the dictionary assumption can hardly be generalized to complex structured systems like multi-energy systems (Wang et al., 2017b) and biology systems (Tarca et al., 2007), etc. that are subject to external disturbances resulting from changing environmental condition.

One ad-hoc approach (Schmidt & Lipson, 2009; Petersen, 2019) uses a genetic algorithm search for the symbolic basis without prior knowledge, but the problem is NP-hard without any guarantee on recovering the governing physical laws from empirical data. Therefore, it is important to investigate whether the sparsity technique and a small modeling error are sufficient to claim the success of learning the physical model. Additionally, how can analytical techniques ensure exact physics learning for all systems, or domain-specific systems?

Constrained Machine Learning. There are many applications of constrained machine learning (CML) in different systems. For example, (Small et al., 2011) restricts the weight vectors with domain knowledge in the support vector machine. (Li et al., 2021) proposes constrained adversarial machine learning to enable the generation of adversarial examples under physical constraints. In deep learning applicartions, (Zhao et al., 2019) employs constraints from conservation law to restrict the output variables of artificial neural networks. (Velloso & Van Hentenryck, 2020; Fioretto et al., 2020a) solve optimal power flow problems using deep learning with physical constraints, where the output variables of a DNN are constrained to guarantee a feasible solution. (Tran et al., 2020) restricts the input to DNN into different groups to guarantee privacy. Among these studies, (Fioretto et al., 2020b) proposes a general framework to optimize DNN with constraints using Lagrangian duality, where the constraints on the output are added. These CML methods can solve their own problems effectively; however, there is a need for general principles to embed the physical constraints systematically with efficient solutions.

Data Forecasting. To enhance physical robustness, we propose to conduct cross-model validation based on forecasting out-of-sample data to enrich the training dataset. The FOCV approach provides cooperative opportunities utilizing and updating physical-modeling knowledge (e.g., laws) as well as real-time data for responsive control. For previous forecasting methods, autoregressive moving average (ARMA) and autoregressive integrated moving average (ARIMA) predict the evolving variables based on their lagged values (Gilbert, 2005). To capture nonlinear correlations in the short-term and long-term, there are many deep learning-based methods, e.g., recurrent Neural Network (RNN), long short-term memory (LSTM), bidirectional LSTM (BiLSTM), gated recurrent units (GRUs), and variational autoencoder (VAE) (Zeroual et al., 2020). To forecast the result with confidence, methods like Gaussian process (GP) (Quinonero-Candela & Rasmussen, 2005), Quantile Regression (Maciejowska et al., 2016) and deep learning-based models (Salinas et al., 2020) afford an efficient way to predict distributions for the future data. Since the uncertainty evaluation is important to integrate the forecast data into the physical learning process, probabilistic methods are presented to estimate probability density functions in the proposed FOCV.

3 METHODS

The PNN-RISE approach is to understand the reason why a "good" sparse fitting is not physical verifiable, to design physical principles to guide the fitting internally based on a flexible physical NN structure, and to create a cost-free active learning method for extrapolation at unseen operating points.

3.1 A "GOOD" SPARSE FITTING CAN FAIL

Symbolic regression (SR) is a common approach to find equation operators ($\{+, -, \times, /\}$) and expressions like ($x^2, \cos(x)$), etc. Existing papers show that if the following three conditions are satisfied, SR is capable to find the true equation.

- Apply the sparse regularization (Brunton et al., 2016; Sahoo et al., 2018; Champion et al., 2019; Petersen, 2019; Kim et al., 2020).
- Achieve zero training error (Brunton et al., 2016; Champion et al., 2019; Petersen, 2019).
- Utilize cross validation to avoid overfitting (Sahoo et al., 2018; Kim et al., 2020).

However, we observe that SR methods are prone to non-physical solutions even when all three assumptions are satisfied. For example, to learn the function $y = x_1x_2 + x_2x_3$ from data, different SR methods can easily get trapped in local optima. To see if these observation is special, we test different cases, where Fig. 2 shows a table summary of four different cases, with integer coefficients or not. We also test different numbers for multiplication and summation. From all the examples, one can see that the recovered objective has sparse coefficients and negligible error (loss objective $\mathcal{L}$) at non-desirable local optimums. To make the realistic case study rather than toy examples, we use a power system case study and visualize the objective surface in Fig. 3 (left). In a small parameter range, there are points achieving the global optimum or local optima that are very close to the global optimum. However, only one of them is the physical ground truth. For example, one can go from the red point to a non-physical solution with an error close to zero, even when the sparsity regularization is enforced. Therefore, we can see that "good" sparse fitting is insufficient to avoid overfitting. Thus, we need to avoid overfitting for physical systems not only by **choosing sparse learning models**, but also new ways to constrain the learning process and avoid non-physical solutions.

Solutions	Case 1	Case 2	Case 3	Case 4
Physical Truth	$y = x_1x_2 + x_2x_3$ $\mathcal{L} = 0.00$	$y = 0.1x_1x_2 + 0.3x_2x_3$ $\mathcal{L} = 0.00$	$y = x_1x_2x_3 + x_2{}^2x_3$ $\mathcal{L} = 0.00$	$y = x_1x_2 + x_2x_3 + x_1x_3$ $\mathcal{L} = 0.00$
Local Optimum 1	$y = 0.0024x_1x_2 + 2.0793x_1^{0.4945}x_2x_3^{0.4723}$ $\mathcal{L} = 0.002$	$y = -1.3192x_1^{0.6051}x_2^{0.3718}x_3^{0.3445} + 1.1166x_1^{0.3569}x_2^{0.8011}x_3^{0.6605}$ $\mathcal{L} = 0.003$	$y = 6.2041x_1^{0.4331}x_2x_3^{0.9930}$ $8.2098x_1^{0.4833}x_2x_3^{0.9993}$ $\mathcal{L} = 0.021$	$y = 1.8595x_1^{0.7805}x_2^{0.6445}x_3^{0.6502} + 0.3481x_1^{0.4670}x_2^{-0.5860}x_3^{0.3862} + 2.2448x_1^{0.1563}x_2^{0.7454}x_3^{0.7202}$ $\mathcal{L} = 0.002$
Local Optimum 2	$y = 1.5205x_1^{0.4126}x_2^{0.9995}x_3^{0.3445} + 0.9600x_1^{0.5369}x_2^{0.9920}x_3^{0.5693}$ $\mathcal{L} = 0.001$	$y = -2.6189x_1^{0.1352}x_2^{0.6277}x_3^{0.5121} + 1.4484x_1^{0.2075}x_2^{0.8744}x_3^{0.6692}$ $\mathcal{L} = 0.003$	$y = 10.4416x_1^{0.7975}x_2x_3^{0.9997} - 9.8486x_1x_2^{0.6719}x_3^{0.9996}$ $\mathcal{L} = 0.003$	$y = 1.8902x_1^{0.6901}x_2^{0.4758}x_3^{0.7413}$ $1.0969x_1^{0.6724}x_2^{0.8458}x_3^{0.5806}$ $1.0300x_1^{0.1140}x_2^{0.2962}x_3^{0.9306}$ $\mathcal{L} = 0.002$
Near Global Optimum	$y = x_1x_2 + x_2^{0.9900}x_3^{0.9900}$ $\mathcal{L} = 0.026$	$y = 0.0990x_1x_2 + 0.3100x_2^{0.9900}x_3^{0.9900}$ $\mathcal{L} = 0.004$	$y = x_2^{1.9800}x_3 + x_1^{0.9900}x_2^{0.9900}x_3^{0.9900}$ $\mathcal{L} = 0.056$	$y = x_1x_2 + x_2x_3 + x_1^{0.9900}x_3^{0.9900}$ $\mathcal{L} = 0.018$

Figure 2: Absolute mismatches between the recovered functions and the physical ground truth.

3.2 PROPOSED METHOD: PHYSICAL NEURAL NETWORK WITH WEIGHT ACTIVATION

For complex physical systems, the governing functions are formed by basic operations such as additive and multiplicative accumulations of variables. For example, the topology of power system can be represented as a graph, where the interaction between different nodes along the lines is represented by polynomials of the voltages for power flow (Yu et al., 2017). To combine the benefit of universal approximation and the freedom to choose activation function, we propose to use a NN as a container to learn the representation of physical equations, and thus call it a physical neural network (PNN), denoted as f. To train f, the training data set is $\{\boldsymbol{x}_i, \boldsymbol{y}_i\}_{i=1}^N$, where $\boldsymbol{x}_i$ and $\boldsymbol{y}_i$ are the i^{th} input and output of f, and N is the number of training samples.

To construct the physical equation in PNN, the key is to develop a sparse selection mechanism to automatically select part of the variables to join summation, abstraction, multiplication, and division.

Figure 3: (Left:) Illustration of the possible saddle point, local optimum, and global optimum in physical equation learning. We observe that local optima can perform numerically as well as the global optimum (ground truth equation) since there is always a set of diversified equations to perfectly fit limited data. (Right:) Visualization of the layer design equation 3.

For sparse selection, some existing work utilizes sparse regularization like LASSO (least absolute shrinkage and selection operator) for the weight updates (Kim et al., 2020), introduces extra neural network modules like gates (Liu & Laili, 2018), or conducts symbolic generators (Petersen, 2019). In general, they demand the quantification of extra hyper-parameters (i.e., the LASSO penalty) or parameters (i.e., parameters in gates or symbolic generators), which significantly increases the possibility of local optima.

In order to address the problem towards limiting local optima, we advocate the design philosophy: enforce activation functions on weights for the sparse selection of features. Thus, no extra parameters are added, and the searching is only for physical parameters. To elaborate on our design, we need to answer (1) which parameters need to be activated and (2) how to enforce the activation. For parameter activation, we start from the basic symbolic operations in neural networks, e.g., multiplications and divisions in the following forms.

$$z_j = \Pi_i^N x_i^{p_{ij}}, \tag{1}$$

where z_j is the j^{th} element of the layer next to the input. x_i is the i^{th} element of the input vector variable $\boldsymbol{x}$ and p_{ij} is the index number of x_i. Note $p_{ij} \in \{-K, \cdots, -1, 0, 1, \cdots, K\}$, where the positive integer represents the multiplication, the possibility of 0 corresponds to the sparsity, and the negative integer represents the division. Then, each z_j is a more complex symbol for the next operation. According to Equation (1), p_{ij} is the optimization variable. To accommodate p_{ij} into a neural network, we use logarithm and exponential operators to achieve a linear summation format (Trask et al., 2018),

$$z_j = \exp\big(\sum_{i=1}^N p_{ij} \ln(x_i)\big). \tag{2}$$

Thus, the linear layer with weights p_{ij} needs to be activated for arithmetic operations and sparsity. Considering the target integer range of p_{ij}, it's vital to know how to control the values for parameter enforcement activation. Thus, we first show how to enforce $p_{ij} \in \{-1, 0, 1\}$. Since tanh function can restrict the output value to be in $[-1, 1]$, we can utilize a positive scaling factor c_1 and tanh to activate some free and optimizable parameter w_{ij} such that $tanh(c_1 w_{ij}) \in \{-1, 1\}$, where the scaling is to make sure the output is very close to the target -1 or 1. Subsequently, the network needs to enforce 0 for sparsity. Following the same procedure, we create another sigmoid function to achieve $\sigma(c_2 w_{ij}^{'}) \in \{0, 1\}$, where σ is the sigmoid function, c_2 is the positive scaling factor, and $w_{ij}^{'}$ is another optimizable parameter. To summarize, we have:

$$p_{ij} = \tanh(c_1 w_{ij}) \cdot \sigma(c_2 w_{ij}^{'}), \tag{3}$$

where $p_{ij} \in (-1, 1)$. The visualized in Fig. 3 (right) shows that the multiplication of tanh and sigmoid functions not only generates a smooth optimization surface but also naturally results in

limited parameters. After such a design, we have a third linear layer to achieve $y_k = \sum_j m_{jk} z_j$, where m_{jk} denote the layer weights for linear weighted summation. Since the summation and abstraction are incorporated into the linear layer, we complete the function $\boldsymbol{y} = f(\boldsymbol{x})$. Using such a design as a basic unit, we can extend from $\{-1, 0, 1\}$ to $\{-K, \cdots, -1, 0, 1, \cdots, K\}$ for different physical systems.

Such a design intelligently converts the non-convex multiplication to a convex form of linear summation, which is efficient for NN training. Based on this design, we show the following property of our PNN to guarantee the finding of stationary points in the optimization.

Theorem 1 (Biconvexity of PNN). *PNN is biconvex on the parameters of the logarithm layer and the linear summation layer. Then, the searching algorithm can find the stationary points of PNN.*

Proof. First, we define the biconvexity as follows (Gorski et al., 2007).

Definition 1 (Biconvexity). *A function $\phi : A \times B \to \mathbb{R}$ is called biconvex if $f(a, b)$ is convex in a for fixed $b \in B$, and $f(a, b)$ is convex in b for fixed $a \in A$.*

Then, we prove PNN is biconvex. Recall for the PNN function $\boldsymbol{y} = f(\boldsymbol{x})$, the k^{th} element can be written as: $y_k = \sum_j m_{jk} z_j = \sum_j m_{jk} \exp\left(\sum_{i=1}^N p_{ij} \ln(x_i)\right)$. $\forall j, k$, if m_{jk} is known, we need to prove the convexity of f with respect to $p_{ij}, \forall 1 \le i \le N$.

Since the linear combination $\sum_{i=1}^N p_{ij} \ln(x_i)$ is convex with respect to p_{ij}, and the exponential function is convex, the convex function composition implies that $\exp\left(\sum_{i=1}^N p_{ij} \ln(x_i)\right)$ is convex with respect to p_{ij}. Therefore, $\forall j, k$, if m_{jk} is known, the function $y_k = \sum_j m_{jk} \exp\left(\sum_{i=1}^N p_{ij} \ln(x_i)\right)$ is convex with respect to $p_{ij}, \forall 1 \le i \le N$. On the other hand, $\forall i, j$, if p_{ij} is known, $y_k = \sum_j m_{jk} \exp\left(\sum_{i=1}^N p_{ij} \ln(x_i)\right)$ is a linear combination of m_{jk}. Therefore, y_k is convex with respect to m_{jk} given p_{ij}.

Therefore, PNN function $\boldsymbol{y} = f(\boldsymbol{x})$ is biconvex with respect to the logarithm layer and the linear summation layer. The biconvexity can lead to an efficient alternate convex search (ACS) (Gorski et al., 2007) to seek for optimal solutions. Namely, ACS will fix one part of parameters to search for the other part iteratively. Due to biconvexity, in each iteration, ACS will solve a convex problem. Then, Corollary 4.10 in (Gorski et al., 2007) guarantees that the searched points will converge to stationary points of $f(\boldsymbol{x})$. $\qquad\square$

Theorem 1 indicates that we can find the stationary points (i.e., saddle points, local optima, and global optima) of the PNN. However, the following questions arises: (1) can we find the global optima? (2) according to our discovery in Section 3.1, can the found global optima represent the true physics? In the next section, we show the design of embedding physical principles to PNN to both obtain global optima and guarantee the physical meaning of the global optima. Especially, we propose sound theories to support our ideas in Theorem 2.

3.3 EMBED PHYSICAL PRINCIPLES VIA CONSTRAINING PNN

After providing a flexible design to reduce the parameter space for limiting possibilities of local optimums, we need comprehensive principles to avoid non-physical local optimum in Sec 3.1. If constraints derived from these principles can be convex, they will be even more beneficial in solving or reducing the issue of non-physical local optimums.

For physical systems, two important perspectives are physical existence and systematic behaviors. As the components are physically located, there are geographical or electrical distances, etc. Therefore, one common constraint through physical systems is the symmetric (S) property, e.g., a branch connecting two components represents a common coupling. In addition to the coupling terms, the links between different components also have their physical limitations, leading to a range (R) constraint. At the system level, the physical system will continue making an impact to the environment, leading to an inertia (I) concept, which is the momentum from a physical object results because physical systems typically have natural inertia, whether it is strong or weak. For man-made systems, there could be additional artificial inertia due to factors such as guaranteeing stability for sustainable operation, e.g., in power systems. Finally, such inertia does not only live in the temporal space

but also in the input/output data space. For example, the physical equations are typically continuous functions. These concepts open the door to investigate the data range beyond the training and testing data. Such generalized inertia leads an important extrapolation (E) property across different physical systems to forecast information yet to be observed but representative of plausible scenarios. .

Figure 4: RISE Principals for Physical Laws.

The constraints based on different properties of physical systems are called RISE concept by combing their initials. For illustrating the completeness of these principles, Fig. 4 presents the relationship among the four RISE concepts. This subsection introduces the first three to constrain the NN structure in Subsection 3.2; while Subsection 3.4, introduces the FOCV method for physical system extrapolation.

Range (R): Shape Constraint on Physical Parameters: While local optima generate many possible parameters to minimize the prediction error, the true physical parameters of corresponding features usually yield specific shapes. For example, the range of power line admittance (reciprocal of impedance) of power distribution systems can be specified with voltage level and line materials. In addition to the bound on value range of independent parameters, there can also be shape constraints on the conditional relationships among parameters, e.g., longer lines have larger resistance than shorter lines. Such a rule specified by the physical shape constraint function can filter out many local optima even with low errors. In order to enforce the learned physical parameters W_p within the constraint, a customized gate function is proposed to filter the weights, as shown in the first subplot of Fig. 4.

$$g'(W_p) = \begin{cases} \lfloor g_p \rfloor, & \text{for } g(W_p) \leq \lfloor g_p \rfloor, \\ g(W_p), & \text{for } \lfloor g_p \rfloor \leq g(W_p) \leq \lceil g_p \rceil, \\ \lceil g_p \rceil, & \text{for } g(W_p) \geq \lceil g_p \rceil, \end{cases} \tag{4}$$

where $g(\cdot)$ is a function of physical weights W_p to represent the type of shape constraint. For example, $g(\cdot)$ is linear if the constraint is on a specific value range of independent parameters, where $\lfloor g_p \rfloor$ and $\lceil g_p \rceil$ are the lower and upper bounds, and $g'(W_p)$ are the constrained weights.

Symmetry (S): Constraints on Physical Couplings: For physical systems with multiple outputs, there are variable couplings among different outputs, e.g., one term is contained in two outputs. Let's use the power system as an example. A certain amount of power flowing from one place to another means that the same amount of power will be subtracted and added simultaneously at the two places. Based on our observations, most of the local optima of NN do not satisfy such a rule. Thus, the property (the third subplot of Fig. 4) is embedded by minimizing

$$L_{Mutual} = \|W_p - W_p^T\|_2 + \|\text{rank}(W_{p_i}) - N_{mutual}\|_0. \tag{5}$$

The first term is an l^2 norm penalty on the symmetry of the recovered physical parameters and the second term is to further ensure that the number of mutual terms N_{mutual} satisfies the system property, e.g., the power system equation has $N_{mutual} = 2$, because the two nodes are connected by one power line.

Inertia (I): Constraints on Physical Tendency: For physical systems, the states are typically continuous and cannot change suddenly, leading to physical inertia. Such a property can be embedded by bounding the outputs of two adjacent time slots, shown in the second subplot of Fig. 4. To ensure the partial convexity, the Euclidean norm is modeled as a penalty in loss function.

$$L_{Inertia} = \|f(\boldsymbol{x}_{t+1}) - f(\boldsymbol{x}_t)\|_2. \tag{6}$$

3.4 MODEL BOOSTING: CROSS MODEL VALIDATION FOR PHYSICAL EXACTNESS AT UNKNOWN DATA REGION

Subsections 3.2 and 3.3 show how to avoid overfitting by considering the NN-based model design and fitness of data to the physical laws. However, all these designs must be within the training data range. *What will happen beyond the training data range, e.g., a new operation point of physical systems unseen in the past?* Actually, determining the performance region is the most useful part for physical systems modeling after understanding the physical laws, e.g., for universal data fitting at arbitrary points. For example, Fig. 5 shows three globally optimal or near globally optimal lines (red, blue, and green) that can fit data equally well within the training dataset. These three lines can represent the problem in Subsection 3.1 as well. One way to avoid the selection dilemma is to conduct an active inquiry out of the historical data range for a selection. For example, Fig. 5 illustrates that a few out-of-sample data points in grey can regularize the learning to the ground truth (dotted black line). However, the costs of such an inquiry can be quite expensive as one inquiry may not be enough. Also, given the numerous networks that the internet of everything (IoE) has, it is infeasible and sometimes impossible to conduct an inquiry for out-of-sample estimation. Therefore, *how can a learning approach* avoid any cost of active learning but still explore the generalization capability via some alternative active learning?

Figure 5: Illustration of out-of-sample forecasting to boost the learning model.

Extrapolation (E): Constraints on Physical Validation at Unknown Regions: To conduct active learning freely and without an inquiry cost, we propose to implement physically meaningful forecasts via a probabilistic model for data points that do not exist in the historical data points. Such a learning objective will be combined with the learning method in the previous subsections to provide another level of physical guidance. Specifically, an ensemble of forecasts is conducted not only for the mean but also for the variance, as the forecast ability decreases when the inquiry point is far away from the data range. For such a probabilistic forecast, another important design is to embed the physical form into the forecast so that the forecast model can cross-validate the learning models. Thus, we propose to utilize Gaussian Process (GP), which not only has computational efficiency in probabilistic forecasts but also provides the flexibility to embed physical forms into its kernel function. The forecasting process is shown in the last subplot of Fig. 4.

For training the GP, the data in represented as $\{\boldsymbol{x}_i, \tilde{\boldsymbol{x}}_i\}_{i=1}^N$, where $\boldsymbol{x}_i$ represents the input samples and $\tilde{\boldsymbol{x}}_i$ represents a sample point k-step later than $\boldsymbol{x}_i$. Based on such data, GP assumes prior function values in a Bayesian framework, e.g., $p(\boldsymbol{g}|\boldsymbol{x}_1, \cdots, \boldsymbol{x}_N) = \mathcal{N}(\boldsymbol{0}, K)$, where $\boldsymbol{g}$ is a vector of latent function values, $\mathcal{N}$ represents normal distribution, and K is a kernelized covariance matrix. In particular, we can add different kernel mappings to calculate K based on our priors of the physical knowledge. For example, for power systems, the polynomial of order 2 is often utilized to represent the relationship between voltages and powers (Yu et al., 2017). Using data with kernel knowledge, we obtain a predicting function $g^\star$ via Bayes rule:

$$p(\boldsymbol{g}^\star) = \frac{1}{p(\tilde{\boldsymbol{x}})} \int p(\tilde{\boldsymbol{x}}|\boldsymbol{g})p(\boldsymbol{g}, \boldsymbol{g}^\star)d\boldsymbol{g}. \tag{7}$$

Based on the Gaussianity, Equation (7) has a closed-form solution $g^\star$. Based on $g^\star$, the goal is to predict the k-step later points for any input sample. Specifically, one can plug-in the input data $\boldsymbol{x}$ and obtain the distribution of the k-step points $p(\boldsymbol{g}^\star(\boldsymbol{x}))$. Thus, the GP-based forecasting not only brings the forecast point $\tilde{\boldsymbol{x}}_k$, e.g., the mean of $p(\boldsymbol{g}^\star(\boldsymbol{x}))$, but also the confidence level α_k based on

the standard deviation. Similarly, we can obtain $\tilde{\boldsymbol{y}}_k$ and β_k, where $\tilde{\boldsymbol{y}}_k$ is the forecast point for the output data $\boldsymbol{y}_k$ and β_k is the corresponding confidence level. Fig. 5 illustrates the results of GP, where the forecast points have smaller uncertainty if they are closer to the dataset boundary.

With the forecast results from above, we can add $\tilde{\boldsymbol{x}}_k$ ($\tilde{\boldsymbol{y}}_k$) to the training data set, like active learning. However, our method is different as active learning, which is associated with a cost. With the cost, active learning can provide a highly accurate label. But, our new data points are always associated with confidence bounds. The good news is that the FOCV method can provide infinite data points without a cost. Therefore, different than active learning, FOCV uses all the data points with unequal weights, e.g., the inverse of confidence level, to achieve model selection. Therefore, we propose an integral-based regularization for extrapolation:

$$L_{Extrapol} = \frac{1}{\alpha_k \beta_k} \sum_{k=1}^{K} (\tilde{\boldsymbol{y}_k} - f(\tilde{\boldsymbol{x}}_k))^2. \tag{8}$$

With extrapolation (E), the proposed methods complete the derivation of RISE. It's important to note that in RISE, the factors are decoupled out of the PNN. Furthermore, the factors can be relaxed into a convex form, which significantly increases the probability of finding the global optima. Specifically, Theorem 2 highlights the regularization can lead to strong convexity over a set of closed and convex regions of the parameter space, i.e., the piecewise strong convexity.

Theorem 2 (Piecewise strong convexity of PNN with regularization). *With inertia and symmetry regularization, the loss function of the proposed PNN is piecewise strongly convex in the parameter space.*

Proof. For the simplicity of later derivations, we denote W as the set of all parameters in PNN. Then, we denote $l(W)$ as the loss function, i.e., mean square error, of the PNN. The range constraint (R) and the extrapolation constraint (E) are included in the loss function as they are included in the PNN representation. Subsequently, the inertia (I) and symmetry (S) regularizations help to define $l_1(W) = l(W) + \lambda(L_{Inertia} + L_{Mutual})$ as the regularized loss function for training, where λ is a positive penalty term.

The second derivative of the regularized loss function can help to determine the convexity. We write the second derivative as follows:

$$\frac{d^2}{dt^2}|_{t=0} l_1(W + tX) = \frac{d^2}{dt^2}|_{t=0} l(W + tX) + \lambda h(W), \tag{9}$$

where $h(W)$ is the second derivative of $L_{Inertia} + L_{Mutual}$. For inertia, Equation (6) has a quadratic form and is convex. For symmetry in Equation (5), the l^0 norm can be relaxed to l^1 norm in optimization. Thus, regularization is convex and $h(W)$ is a positive value.

However, due to the non-convexity of neural network, the first term $\frac{d^2}{dt^2}|_{t=0} l(W + tX)$ is generally not positive semi-definite. The following lemma in (Milne, 2018) proves a lower bound for $\frac{d^2}{dt^2}|_{t=0} l(W + tX)$ with respect to the loss value of l.

Lemma 1. *Suppose $||\boldsymbol{y}_i||_2 \leq r$ for all $1 \leq i \leq N$, where r is a positive value. The second derivative of l in direction X satisfies:*

$$\frac{d^2}{dt^2}|_{t=0} l(W + tX) > -\sqrt{2} H(H-1)||W||_\star^{H+1}||X||_2^2 r l(W)^{1/2}, \tag{10}$$

where H is the number of hidden layers in a neural network, $|| \cdot ||_\star$ is a defined norm such that $||W||_\star = \max_{0 \leq i \leq H} ||W_i||_2$.

According to Lemma 1, the second derivative of l is lower-bounded by a term that depends on l value. Then, for regions with small loss values, the positive value $h(W)$ helps to restrict $\frac{d^2}{dt^2}|_{t=0} l_1(W + tX)$ to a positive number, which determines the shape of the region to be convex. Mathematically, we define the region $U(\lambda, \theta)$, where $\lambda > \theta > 0$, by

$$U(\lambda, \theta) = \{W | l(W)^{1/2} ||W||_\star^{H-1} < \frac{(\lambda - \theta) h(W)}{\sqrt{2} H(H+1) r ||X||_2^2}\}. \tag{11}$$

It's obvious that $\forall W \in U(\lambda, \theta), \frac{d^2}{dt^2}|_{t=0} l_1(W + tX) > 0$. Namely, within the region of $U(\lambda, \theta)$, the regularized loss function is strongly convex.

In general, $U(\lambda, \theta)$ is not a convex set since there are many local optima points that are disconnected and have small l values. However, according to measure theory, we can utilize a set of closed convex sets to completely cover $U(\lambda, \theta)$, leading to piecewise strong convexity of PNN over these closed convex sets. □

The piecewise strong convexity from convex regularization of RISE guarantees that (1) we can find the global optimal point for each sub-regions, and (2) the global optima satisfy RISE constraints for physical parameters.

4 EXPERIMENTS

4.1 DATA PREPARATION

In experiments, we first use synthetic datasets for illustration and introduce real physical system datasets of power systems and mass-damper systems as the underlying physical systems for model training and comparison. In particular, the dataset descriptions are as follows.

Synthetic dataset. In order to visualize the learning performance, we generate random samples of x from Gaussian distribution $\mathcal{N}(0, 1)$, and obtain the outputs by $y = c_1 x_1 x_2 + c_2 x_1^2$.

Power system datasets. IEEE provides standard power system models, including the grid topology, parameters, and generation models, etc., for simulations. The model files and the simulation platform, MATPOWER (MATPOWER community, 2020), are based on MATLAB. For simulations, the load files are need as the inputs to the systems. Thus, we introduce power consumption data from PJM Interconnection LLC (PJM Interconnection LLC, 2018). Such load files contain hourly power consumption in 2017 for the PJM RTO regions. With the above data, MATPOWER produces the system states of voltages and nodal power injections. Then, we utilize the voltage as input and the nodal power as the output to learn the physical mapping, for which the true physical function is used for evaluations (Yu et al., 2017). To diversify the system types, we utilize the mass-damper system and aerodynamic system to further validate our results.

Motion dynamics dataset: mass dampers of in-plane wind turbine. The physical equation of the mass-damper system is representative of aircraft motion for analysis of system dynamics (van der Schaft, 2017; McRuer et al., 2014). Moreover, the active tuned mass dampers are implemented to control in-plane blade vibrations (Fitzgerald et al., 2013). Using MATLAB, we simulate the dynamic process of the mass-damper system with 10 nodes and obtain the measurements of velocity and momentum for the test of physical equation discovery.

Aerodynamic dataset: aircraft weight estimation. The aircraft sensor data is collected from the aircraft simulation in MATLAB and the corresponding aerodynamic model is illustrated in (Chen et al., 2018). In this case, the goal is to recover the aerodynamic model of gross weight and angle of attack in a cambered airfoil.

4.2 PERFORMANCE EVALUATION METRIC

Prediction error: One can evaluate the modeling accuracy and extrapolation capacity of the PNN via calculating the mean square error (MSE) of the output in the testing dataset. Specifically, we define $\tilde{Y} \in \mathbb{R}^{N \times d_2}$ and $Y \in \mathbb{R}^{N \times d_2}$ as the model predicted data matrix and the true data matrix, where N is the number of samples. MSE can be calculated $MSE(\tilde{Y}, Y) = \frac{||\tilde{Y} - Y||_2}{N \times d_2}$. Later, we plan to utilize other metrics to evaluate the performance of our model (Blasch & Sung, 2021). **Physical exactness (PhyE)**: To evaluate how much physics PNN extracts, we propose a metric PhyE to compare the extracted values and the true values. **Robustness to noise ratio (RNR)**: We propose RNR to average all results under different signal-to-noise ratios. **Training time and testing time**: We utilize the training and testing time to evaluate the model efficiency.

4.3 BENCHMARK METHODS AND TESTING SCENARIOS

The following benchmark methods are used for comparison: (1) support vector regression (SVR) (Yu et al., 2017), (2) deep residual network (Resnet) (He et al., 2016), (3) sparse identification of nonlinear dynamics (SINDy) (Brunton et al., 2016; Champion et al., 2019), and equation learner (EQL$^{\div}$) (Sahoo et al., 2018). Different scenarios are generated for testing: S_1 denotes the regular setup of dataset size and noise level (independent Gaussian noise with zero mean and 0.01 standard deviation); S_2 denotes a noisy setup with noises of 0.1 standard deviation; S_3 denotes a data-limited setup with 10% samples of original dataset. The results are summarized in Table 1. Although other methods can have low errors in some testing cases, they can not maintain the good performance as PNN-RISE does for all the datasets. Especially, EQL$^{\div}$ and SINDy's performance deteriorates when the problem size becomes larger, e.g., power system datasets with data from many nodes. While SVR is robust against noises, it can not recover the nonlinear physical function exactly to further decrease the learning error. In this case, the proposed method shows low learning error and a stable performance in both noisy and data-limited scenarios. Moreover, the performance of physical function recovery is compared in Fig. 7(left). The bar plot shows the recovery rates (percentage of runs that correctly recover the ground truth symbolic expression) and the line plot with shades shows the recovery accuracy of the corresponding physical parameters. While EQL$^{\div}$ easily fails in large power system cases, the proposed PNN-RISE has high success rate in true function recovery, merely trapped into local optima. For the recovery of physical parameters, PNN-RISE not only has higher average accuracy but also has lower standard deviation than EQL$^{\div}$.

S^*	Data	SVR	Resnet	SINDy	EQL$^{\div}$	PNN-RISE
	Sythetic	0.003 ± 0.00	0.005 ± 0.00	$\mathbf{0.001 \pm 0.00}$	0.003 ± 0.00	$\mathbf{0.001 \pm 0.00}$
	PS 1**	0.006 ± 0.00	0.01 ± 0.00	0.004 ± 0.00	0.007 ± 0.00	$\mathbf{0.001 \pm 0.00}$
S_1	PS 2**	0.05 ± 0.01	0.02 ± 0.01	0.03 ± 0.02	0.07 ± 0.05	$\mathbf{0.01 \pm 0.01}$
	Motion	0.002 ± 0.00	0.003 ± 0.00	0.006 ± 0.00	$\mathbf{0.001 \pm 0.00}$	$\mathbf{0.001 \pm 0.00}$
	Aero	$\mathbf{0.003 \pm 0.00}$	0.005 ± 0.00	0.008 ± 0.01	$\mathbf{0.003 \pm 0.00}$	$\mathbf{0.002 \pm 0.00}$
	Sythetic	0.004 ± 0.00	0.007 ± 0.00	$\mathbf{0.002 \pm 0.00}$	0.006 ± 0.00	$\mathbf{0.001 \pm 0.00}$
	PS 1	0.005 ± 0.00	0.01 ± 0.00	0.007 ± 0.00	0.009 ± 0.00	$\mathbf{0.001 \pm 0.00}$
S_2	PS 2	0.06 ± 0.03	0.04 ± 0.02	0.09 ± 0.04	0.10 ± 0.02	$\mathbf{0.01 \pm 0.01}$
	Motion	0.003 ± 0.00	0.005 ± 0.00	0.009 ± 0.00	$\mathbf{0.001 \pm 0.00}$	$\mathbf{0.001 \pm 0.00}$
	Aero	$\mathbf{0.003 \pm 0.00}$	0.02 ± 0.01	0.01 ± 0.00	0.004 ± 0.00	$\mathbf{0.003 \pm 0.00}$
	Sythetic	0.006 ± 0.00	0.010 ± 0.00	0.002 ± 0.00	0.008 ± 0.00	$\mathbf{0.001 \pm 0.00}$
	PS 1	0.008 ± 0.02	0.02 ± 0.00	0.004 ± 0.00	0.01 ± 0.00	$\mathbf{0.003 \pm 0.00}$
S_3	PS 2	0.07 ± 0.03	0.04 ± 0.01	0.03 ± 0.02	0.07 ± 0.05	$\mathbf{0.02 \pm 0.01}$
	Motion	0.004 ± 0.00	0.007 ± 0.00	0.006 ± 0.00	$\mathbf{0.001 \pm 0.00}$	$\mathbf{0.001 \pm 0.00}$
	Aero	$\mathbf{0.003 \pm 0.00}$	0.007 ± 0.00	0.01 ± 0.00	$\mathbf{0.003 \pm 0.00}$	$\mathbf{0.002 \pm 0.00}$

* Test different scenarios.
** IEEE 8-bus power system and Utility feeder power system.

Table 1: Performances of mapping rule recovery on different datasets. The comparison is based on different testing scenarios.

4.4 ABLATION STUDY FOR PHYSICAL CONSTRAINTS

Figure 6: Synthetic dataset: visualization of the function recovery with RISE constraints.

In order to show the performance of using different physical constraints, we provide an ablation study of the proposed NN. First, we use the synthetic example to visualize the effect of constraints. The left-hand side of Fig. 6 compares the local optimum (transparent gray surface) learned by NN with the true function (solid gray surface). Though there are some overlaps, the large gap between the two surfaces causes large errors for generalization. By adding constraints, we observe in the middle of Fig. 6 that the variable coupling constraint rotates and stretches the surface to the correct shape like the maximum and minimum values of the surface. On the other hand, the parameter range constraint smoothes the surface of the local optimum. Together, the constraints push the recovered function (cyan surface) towards the ground truth, where the overlap in Fig. 6 (right) shows the physical exactness in not only feature components but also the corresponding parameters.

Figure 7: (Left:) Performance comparison of EQL and the proposed PNN-RISE on physical function recovery. (Right:) Compare the mean square errors (MSE) in different test scenarios with embedding different constraints.

Subsequently, Fig. 7 (right) presents the learning results on power system datasets (IEEE 8-bus system). The performance is evaluated in different test scenarios: 1) regular data acquisition, 2) limited input range (voltages within $[0.98, 1.01]$ for training data and $[0.90, 1.10]$ for testing), 3) out-of-scale invariants in a governing function, and 4) limited data amount. In general, adding physical constraints boosts the performance in different testing scenarios. Especially, the constraint on mutual variables significantly reduces the learning error by pushing the features and parameters to be symmetric for multiple-output problems. When the data amount is very limited to train NN efficiently, the bound on the inertia of system outputs in time sequence can improve the function recovery.

4.5 ILLUSTRATION OF THE EFFECTIVENESS OF FORECASTING-BASED PHYSICS LEARNING

To illustrate the effectiveness of our model boosting algorithm enhanced by GP forecasting, we utilize 200 samples for training and propose to forecast $\{500, 1000, 1500, 2000\}$ samples out of the training dataset. Also, we consider different SNRs in $\{50, 100, 150\}$. Then, the forecast samples are integrated into our PNN model and other benchmark models for result comparisons. Fig. 8 demonstrates the result, i.e., MSE, with respect to the forecast points. Due to the space limit, we only show results of GP-based PNN and GP-based Resnet for comparisons. The patterns of results for other benchmark methods are similar to GP-based Resent.

We observe that firstly, GP-based PNN performs much better than GP-based Resnet, which is consistent to observations in the previous subsections. Secondly, as the number of forecast data points increases, the prediction MSE value generally decreases for both PNN model and Resnet model. This implies that our GP forecasting can produce accurate forecast points, suitable for all prediction models. Subsequently, when the number is larger than 500, the results don't show a significant improvement. The reason is that forecast points far from the training set boundary are with low confidence. Thus, they don't have a big impact on learning results.

5 CONCLUSION

The tremendous expansion of internet of everything (IoE) brings intelligent connections among different devices to coordinate resources. However, the lack of physical understanding makes it hard for planning, monitoring, and control of IoE. To learn the governing physical equations from data,

Figure 8: The results of GP-based PNN and GP-based Resnet for different systems.

the paper first presents a fundamental challenge for data-driven methods like symbolic regression and sparse regression. Namely, data-driven only methods cannot guarantee to find the exact physics, as there are many low-complexity expressions to perfectly fit the data. To resolve the issue of finding the underlying physical laws, we propose a complete set of principles to define physical constraints to restrict the search space. Under these constraints, an efficient physical neural network (PNN-RISE) is proposed to achieve constrained neural network learning. Finally, the FOCV supports the scenario when (partial) physical constraints are unknown. As physical constraints aim to maintain accurate performance out of samples, the forecast of data beyond the training dataset enhances model robustness as an intelligent integration significantly improves the model with few extra costs. Results on four data sets demonstrate the superior performance of the FOCV methods.

REFERENCES

Ossama Abdel-Hamid, Abdel-rahman Mohamed, Hui Jiang, Li Deng, Gerald Penn, and Dong Yu. Convolutional neural networks for speech recognition. *IEEE/ACM Transactions on audio, speech, and language processing*, 2014.

H. R. Baghaee, M. Mirsalim, G. B. Gharehpetian, and H. A. Talebi. Three-phase AC/DC power-flow for balanced/unbalanced microgrids including wind/solar, droop-controlled and electronically-coupled distributed energy resources using radial basis function neural networks. *IET Power Electronics*, 2017.

Erik Blasch and James Sung. Standards for the artificial intelligence community. *Automatic Target Recognition XXXI*, 2021.

Erik Blasch, Sai Ravela, and Alex Aved. Handbook of dynamic data driven applications systems. *Springer*, 2018.

Erik Blasch, Tien Pham, Chee-Yee Chong, Wolfgang Koch, Henry Leung, Dave Braines, and Tarek Abdelzaher. Machine learning/artificial intelligence for sensor data fusion–opportunities and challenges. *IEEE Aerospace and Electronic Systems Magazine*, 2021.

Steven L Brunton, Joshua L Proctor, and J Nathan Kutz. Discovering governing equations from data by sparse identification of nonlinear dynamical systems. *Proceedings of the national academy of sciences*, 2016.

Kathleen Champion, Bethany Lusch, J Nathan Kutz, and Steven L Brunton. Data-driven discovery of coordinates and governing equations. *Proceedings of the National Academy of Sciences*, 2019.

Sida Chen, Shigeru Imai, Wennan Zhu, and Carlos A Varela. Towards learning spatio-temporal data stream relationships for failure detection in avionics. In *Handbook of Dynamic Data Driven Applications Systems*, pp. 97–121. Springer, 2018.

Zhao Chen, Yang Liu, and Hao Sun. Physics-informed learning of governing equations from scarce data. *arXiv preprint*, 2020.

Rohit Chowdhury and Deepak N Subramani. Physics-driven machine learning for time-optimal path planning in stochastic dynamic flows. *International Conference on Dynamic Data Driven Application Systems*, 2020.

Hwei-Ming Chung, Wen-Tai Li, Chau Yuen, Wei-Ho Chung, Yan Zhang, and Chao-Kai Wen. Local cyber-physical attack for masking line outage and topology attack in smart grid. *IEEE Transactions on Smart Grid*, 2018.

Yan Du and Fangxing Li. Intelligent multi-microgrid energy management based on deep neural network and model-free reinforcement learning. *IEEE Transactions on Smart Grid*, 2019.

Ferdinando Fioretto, Terrence WK Mak, and Pascal Van Hentenryck. Predicting AC optimal power flows: combining deep learning and lagrangian dual methods. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2020a.

Ferdinando Fioretto, Pascal Van Hentenryck, Terrence WK Mak, Cuong Tran, Federico Baldo, and Michele Lombardi. Lagrangian duality for constrained deep learning. *arXiv preprint*, 2020b.

Breiffni Fitzgerald, Biswajit Basu, and Søren RK Nielsen. Active tuned mass dampers for control of in-plane vibrations of wind turbine blades. *Structural Control and Health Monitoring*, 20(12): 1377–1396, 2013.

Kenneth Gilbert. An ARIMA supply chain model. *Management Science*, 2005.

Jochen Gorski, Frank Pfeuffer, and Kathrin Klamroth. Biconvex sets and optimization with biconvex functions: a survey and extensions. *Mathematical methods of operations research*, 66(3):373–407, 2007.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2016.

Geoffrey E Hinton, Simon Osindero, and Yee-Whye Teh. A fast learning algorithm for deep belief nets. *Neural computation*, 2006.

Julia Hirschberg and Christopher D Manning. Advances in natural language processing. *Science*, 2015.

Kurt Hornik, Maxwell Stinchcombe, and Halbert White. Universal approximation of an unknown mapping and its derivatives using multilayer feedforward networks. *Neural networks*, 1990.

X. Hu, H. Hu, S. Verma, and Z. L. Zhang. Physics-guided deep neural networks for power flow analysis. *arXiv preprint*, 2020.

Guang-Bin Huang, Lei Chen, Chee Kheong Siew, et al. Universal approximation using incremental constructive feedforward networks with random hidden nodes. *IEEE Transactions Neural Networks*, 2006.

A. Karami and M. S. Mohammadi. Radial basis function neural network for power system load-flow. *International Journal of Electrical Power & Energy Systems*, 2008.

Andrej Karpathy, George Toderici, Sanketh Shetty, Thomas Leung, Rahul Sukthankar, and Li Fei-Fei. Large-scale video classification with convolutional neural networks. *Proceedings of the IEEE conference on Computer Vision and Pattern Recognition*, 2014.

Samuel Kim, Peter Y Lu, Srijon Mukherjee, Michael Gilbert, Li Jing, Vladimir Čeperić, and Marin Soljačić. Integration of neural network-based symbolic regression in deep learning for scientific discovery. *IEEE Transactions on Neural Networks and Learning Systems*, 2020.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Advances in neural information processing systems*, 2012.

Jiangnan Li, Yingyuan Yang, Jinyuan Stella Sun, Kevin Tomsovic, and Hairong Qi. Conaml: Constrained adversarial machine learning for cyber-physical systems. *Proceedings of the ACM Asia Conference on Computer and Communications Security*, 2021.

Xiaoxia Li, Wei Li, Qiang Yang, Wenjun Yan, and Albert Y. Zomaya. Edge-computing-enabled unmanned module defect detection and diagnosis system for large-scale photovoltaic plants. *IEEE Internet of Things Journal*, 2020.

Yifeng Li. Sparse representation for machine learning. *Advances in Artificial Intelligence*, pp. 352–357, 2013.

Anji Liu and Yuanjun Laili. Balance gate controlled deep neural network. *Neurocomputing*, 2018.

Yanli Liu, Dongxu Lu, Liangchen Deng, Tianyuan Bai, Kai Hou, and Yuan Zeng. Risk assessment for the cascading failure of electric cyber-physical system considering multiple information factors. *IET Cyber-Physical Systems: Theory & Applications*, 2017.

Dengsheng Lu and Qihao Weng. A survey of image classification methods and techniques for improving classification performance. *International journal of Remote Sensing*, 2007.

Katarzyna Maciejowska, Jakub Nowotarski, and Rafał Weron. Probabilistic forecasting of electricity spot prices using factor quantile regression averaging. *International Journal of Forecasting*, 2016.

E. Manitsas, R. Singh, B. C. Pal, and G. Strbac. Distribution System State Estimation Using An Artificial Neural Network Approach for Pseudo Measurement Modeling. *IEEE Transactions on Power Systems*, 2012.

MATPOWER community. MATPOWER. 2020. `https://matpower.org/`.

Duane T McRuer, Dunstan Graham, and Irving Ashkenas. *Aircraft dynamics and automatic control*, volume 740. Princeton University Press, 2014.

Kursat Rasim Mestav, Jaime Luengo-Rozas, and Lang Tong. State estimation for unobservable distribution systems via deep neural networks. In *2018 IEEE Power & Energy Society General Meeting*. IEEE, 2018.

Tristan Milne. Piecewise strong convexity of neural networks. *arXiv:1810.12805*, 2018.

H. H. Müller, M. J. Rider, and C. A. Castro. Artificial neural networks for load flow and external equivalents studies. *Electric power systems research*, 2010.

Prakash M Nadkarni, Lucila Ohno-Machado, and Wendy W Chapman. Natural language processing: an introduction. *Journal of the American Medical Informatics Association*, 2011.

Antonia Nasiakou, Miltiadis Alamaniotis, Lefteri H Tsoukalas, and Manolis Vavalis. Dynamic data driven partitioning of smart grid using learning methods. *Springer*, 2018.

Brenden K Petersen. Deep symbolic regression: Recovering mathematical expressions from data via risk-seeking policy gradients. *arXiv preprint*, 2019.

PJM Interconnection LLC. Metered load data. 2018. `https://dataminer2.pjm.com/feed/hrl_load_metered/definition`.

Joaquin Quinonero-Candela and Carl Edward Rasmussen. A unifying view of sparse approximate gaussian process regression. *The Journal of Machine Learning Research*, 2005.

Subham Sahoo, Christoph Lampert, and Georg Martius. Learning equations for extrapolation and control. *International Conference on Machine Learning*, 2018.

David Salinas, Valentin Flunkert, Jan Gasthaus, and Tim Januschowski. Deepar: probabilistic forecasting with autoregressive recurrent networks. *International Journal of Forecasting*, 2020.

Michael Schmidt and Hod Lipson. Distilling free-form natural laws from experimental data. *Science*, 2009.

Bernhard Schölkopf, Alexander J Smola, Francis Bach, et al. Learning with kernels: support vector machines, regularization, optimization, and beyond. *MIT press*, 2002.

H. Shareef, A. Mohamed, and A. A. Ibrahim. An image processing based method for power quality event identification. *International Journal of Electrical Power & Energy Systems*, 2013.

Kevin Small, Byron C Wallace, Carla E Brodley, and Thomas A Trikalinos. The constrained weight space SVM: learning with ranked features. In *International Conference on Machine Learning*, 2011.

Adi L Tarca, Vincent J Carey, Xue-wen Chen, Roberto Romero, and Sorin Drăghici. Machine learning and its applications to biology. *PLoS computational biology*, 2007.

Cuong Tran, Ferdinando Fioretto, and Pascal Van Hentenryck. Differentially private and fair deep learning: A lagrangian dual approach. *arXiv preprint*, 2020.

Andrew Trask, Felix Hill, Scott Reed, Jack Rae, Chris Dyer, and Phil Blunsom. Neural arithmetic logic units. *arXiv preprint*, 2018.

Silviu-Marian Udrescu and Max Tegmark. AI feynman: A physics-inspired method for symbolic regression. *Science Advances*, 2020.

Arjan van der Schaft. Modeling of physical network systems. *Systems & Control Letters*, 2017.

Alexandre Velloso and Pascal Van Hentenryck. Combining deep learning and optimization for security-constrained optimal power flow. *arXiv preprint*, 2020.

Kieran Walshe, Gill Harvey, and Pauline Jas. *Connecting knowledge and performance in public services: From knowing to doing*. Cambridge University Press, 2010.

Fei Wang, Mengqing Jiang, Chen Qian, Shuo Yang, Cheng Li, Honggang Zhang, Xiaogang Wang, and Xiaoou Tang. Residual attention network for image classification. *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2017a.

Jianxiao Wang, Haiwang Zhong, Ziming Ma, Qing Xia, and Chongqing Kang. Review and prospect of integrated demand response in the multi-energy system. *Applied Energy*, 2017b.

Dong Yu and Li Deng. Automatic speech recognition. *Springer*, 2016.

Jiafan Yu, Yang Weng, and Ram Rajagopal. Robust mapping rule estimation for power flow analysis in distribution grids. *North American Power Symposium*, 2017.

Ahmed Samir Zamzam and Nicholas D Sidiropoulos. Physics-aware neural networks for distribution system state estimation. *IEEE Transactions on Power Systems*, 2020.

Abdelhafid Zeroual, Fouzi Harrou, Abdelkader Dairi, and Ying Sun. Deep learning methods for forecasting covid-19 time-series data: A comparative study. *Chaos, Solitons & Fractals*, 2020.

Wen Li Zhao, Pierre Gentine, Markus Reichstein, Yao Zhang, Sha Zhou, Yeqiang Wen, Changjie Lin, Xi Li, and Guo Yu Qiu. Physics-constrained machine learning of evapotranspiration. *Geophysical Research Letters*, 2019.

A APPENDIX

You may include other additional sections here.