DIFER: Differentiable Automated Feature Engineering

Anonymous[1]

[1]Anonymous Institution

Abstract   Feature engineering, a crucial step of machine learning, aims to construct useful features from raw data to improve model performance. In recent years, great efforts have been devoted to Automated Feature Engineering (AutoFE) to replace expensive human labor. However, all existing methods treat AutoFE as an optimization problem over a discrete feature space, leading to the problems of feature explosion and computational inefficiency. Unlike previous work, we perform AutoFE in a continuous vector space and propose a differentiable method called DIFER in this paper. Specifically, we first propose an evolutionary framework to search for better features iteratively. In each feature evolution step, we introduce a feature optimizer based on the encoder-predictor-decoder, which maps features into the continuous vector space via the encoder, optimizes the embedding along the gradient direction induced by the predictor, and recovers better features from the optimized embedding by the decoder. Extensive experiments on classification and regression datasets demonstrate that DIFER can significantly outperform the state-of-the-art AutoFE method in terms of both model performance and computational efficiency. The implementation of DIFER is avaialable on `https://anonymous.4open.science/r/DIFER-3FBC/`.

1 Introduction

More data beats clever algorithms, but better data beats more data. Feature engineering, the process of constructing features from raw data, directly determines the upper bound of machine learning algorithms. However, it requires considerable domain knowledge to construct features. Also, huge computational resources are needed to evaluate and then filter features. Thus, it is a cost-intensive task to find useful and meaningful features.

Recently, the AutoFE (Automated Feature Engineering) methods that search for useful features without any human intervention have received more and more attention. AutoFE formalizes feature construction as applying transformations (e.g., arithmetic operators) to the raw features. The *expansion-reduction* algorithm (Kanter and Veeramachaneni, 2015; Lam et al., 2017) iteratively applies all transformations to each feature and selects the features based on the model performance. Without expert guidance, such a brute-force method consumes significant computational resources for feature evaluation due to the exponentially growing feature space. To reduce the cost, learning-based AutoFE methods are proposed. TransGraph (Khurana et al., 2018) trains a Q-learning agent to decide the transformation. Due to applying each action (i.e., transformation) to all features, TransGraph also suffers from the feature explosion problem. LFE (Nargesian et al., 2017) trains an MLP (Multi-Layer Perceptron) to recommend the most likely useful transformation for each feature. However, it does not support the composition of transformations. NFS (Chen et al., 2019) generates a feature transformation sequence for each raw feature under the guidance of an RNN controller. Although NFS can achieve SOTA (state-of-the-art) performance, the computational efficiency is still low. An inherent cause of inefficiency for the existing approaches is the fact that AutoFE is treated as an optimization problem over a discrete space.

In this paper, we address the AutoFE problem from a different perspective and propose the first gradient-based approach called DIFER (DIfferentiable automated Feature EngineeRing). We first propose an evolutionary framework to generate better features iteratively. Then, in each feature evolution step, we propose a tree-like structure called *parse tree* to represent constructed features

flexibly, and leverage a feature optimizer based on the encoder-predictor-decoder. Specifically, instead of searching in the discrete feature space, the encoder maps the traversal string of the parse tree into a continuous vector space. Constructing a better feature is equivalent to generating better embedding in the continuous vector space. The following predictor takes the feature embedding as input, predicts its performance score, and directly optimizes the embedding by gradient descent along the score direction. The optimized embedding is further decoded as a better feature in the discrete space.

Extensive experimental results on both classification and regression tasks reveal that DIFER is not only effective but also efficient. Compared to the SOTA approach, DIFER achieves better performance on 22 out of 25 datasets with 40 times fewer feature evaluations. Moreover, DIFER can be effective when using different machine learning algorithms.

To summarize, our main contributions can be highlighted as follows:

- We propose a feature evolution framework to search for better features iteratively.

- To represent constructed features, we design the *parse tree* structure, which is more flexible and expressive than the commonly-used sequence representation.

- We introduce a novel feature optimizer based on the encoder-predictor-decoder for feature evolution and thus can achieve differentiable AutoFE. To our best knowledge, DIFER is the first differentiable AutoFE method.

- Extensive experimental results on a variety of tasks demonstrate that DIFER outperforms the state-of-the-art AutoFE approach in terms of both model performance and computational efficiency.

2 Related work

Feature engineering aims to transform raw data into features that can better express the nature of the problem. Recently, feature engineering has gradually shifted from leveraging human knowledge to automated methods. Existing AutoFE approaches can be divided into three categories.

Heuristic Approaches: Deep Feature Synthesis (DFS), the component of Data Science Machine (Kanter and Veeramachaneni, 2015), first enumerates all transformations on all features and then performs feature selection directly based on the improvement of model performance. One Button Machine (Lam et al., 2017) adopts a similar approach. However, this *expansion-reduction* approach suffers from a severe computational performance bottleneck due to the huge feature evaluation overhead. To avoid enumerating the entire feature space, Cognito (Khurana et al., 2016) introduces a tree-like exploration of feature space and presents handcrafted heuristics traversal strategies such as breadth-first search and depth-first search. AutoFeat (Horn et al., 2019) iteratively subsamples features using beam search. However, heuristic approaches cannot learn from past experiences and thus has a low search efficiency.

Learning-Based Approaches: To explore feature space efficiently, learning-based AutoFE methods have been proposed. LFE (Nargesian et al., 2017) trains an MLP and recommends the most likely useful transformation for each raw feature. However, it does not support transformation composition and works only for classification tasks. TransGraph (Khurana et al., 2018) trains a Q-learning agent to decide which transformation should be applied. Due to performing each transformation on all features, TransGraph suffers from feature explosion and low computational efficiency.

NAS-Based Approaches: Neural Architecture Search (Elsken et al., 2019) has aroused significant research interests in the field of AutoML (He et al., 2020). The reinforcement learning-based NAS method (Zoph and Le, 2017) views the structure of a neural network as a variable-length string. Then, it uses a recurrent network as the controller to generate such strings and trains the controller with policy gradient. This approach can be adopted into AutoFE. For instance, NFS (Chen et al., 2019), the current SOTA AutoFE method, utilizes several RNN-based controllers to generate transformation sequences for each raw feature. However, evaluating enormous sequences results

in substantial computational overhead. Most importantly, due to the side effects of reducing binary transformations to unary ones, NFS cannot generate complex features like $\frac{A+B}{C-D}$.

To improve the computational efficiency of NAS, differentiable methods have been proposed. DARTS (Liu et al., 2018) relaxes the categorical choice to a softmax over all possible operations, leading to a differentiable learning objective. NAO (Luo et al., 2018) maps the discrete architecture space to a continuous hidden space and optimizes existing architectures in the continuous space.

The differentiable NAS methods bring more inspiration to AutoFE. In this paper, we propose the first differentiable AutoFE method called DIFER, which can efficiently construct useful low-order and high-order features with much fewer feature evaluations.

3 Methodology

3.1 Problem Formulation

Let $D = \langle F, y \rangle$ be a dataset with a target vector y and n d-dimensional instances $F = \{f_1, \cdots, f_d\}$, where $f_i \in \mathcal{R}^n$ is the i-th raw feature. We denote the performance of the machine learning model M that is learned from D and measured by an evaluation metric L (e.g., F1-score or mean squared error) as $L_M(F, y)$. Without loss of generality, the lower L_M indicates better model performance.

Furthermore, we apply the composition of transformations $t \in \mathcal{R}^n \times \cdots \times \mathcal{R}^n \to \mathcal{R}^n$ to features for constructing new features. Let o denote the arity of the transformation t, we construct a new feature $f_i = t\left(f_{i_1}, \cdots, f_{i_o}\right)$, where f_{i_j} denotes the j-th input of t to construct f_i for $j \in \{1, \cdots, o\}$. For example, we use the composition of the unary transformation *square* and the binary transformation *divide* to construct *BMI* (Body Mass Index) by *divide* (*weight*, *square* (*height*)) with the raw features *weight* and *height*.

Given a set of transformations with different arities $T = \{t_1, \cdots, t_m\}$, we define the feature space F^T as follows: $\forall f_i \in F^T$, f_i satisfies any of the following conditions:

- $f_i \in F$

- $\exists t \in T,\ f_i = t\left(f_{i_1}, \cdots, f_{i_o}\right)$, where $f_{i_1}, \cdots, f_{i_o} \in F^T$

Formally, let $\alpha(f_i)$ denote the *order* of the feature $f_i \in F^T$, $\alpha(f_i)$ can be defined as:

$$\alpha(f_i) = \begin{cases} 1 + \max_j \alpha\left(f_{i_j}\right) & f_i = t(f_{i_1}, \cdots, f_{i_o}) \\ 0 & f_i \in F \end{cases} \tag{1}$$

Therefore, the goal of AutoFE is to find the set of constructed features F^* that can achieve the best performance:

$$F^* = \arg\min_{\hat{F}} L_M(F \cup \hat{F}, y), \text{ s.t. } \hat{F} \subset F^T \tag{2}$$

In practice, we limit the order of features and search in the feature space $F_k^T = \{f \mid f \in F^T \wedge \alpha(f) \le k\}$ since the size of the original space is infinite (i.e., $|F^T| = \aleph_0$). We explore the feature space F_k^T and search for top features ranked by the performance metric $L_M(F \cup \{f\}, y)$ as F^*.

3.2 Overview of DIFER

As shown in Figure 1a, we propose an evolutionary framework to achieve AutoFE. The population initialization step constructs feature set F_{cand} by randomly sampling features from F_k^T. We train a machine learner from scratch using each sampled feature and evaluate the model performance on the validation set as the performance score of the feature. Then, we can get the score set $S_{\text{cand}} = \{L_M(F \cup \{f\}, y) \mid f \in F_{\text{cand}}\}$. In each feature evolution step, we first select top-d features from F_{cand} according to S_{cand}. To enhance the diversity of evolution, we take two different approaches to generate new features at the same time. One way is to perform gradient-based optimization based

(a) Feature evolution framework.

(b) Feature optimization.

(c) Co-training of feature optimizer.

Figure 1: Overview of DIFER.

on the feature optimizer and add $d/2$ optimized features to F_{cand} (i.e., exploitation). The other way is to add $d/2$ randomly-generated features to F_{cand} for exploration. The process of feature evolution is repeated until a maximum number of iterations is reached. After the feature evolution step, we select top features from F_{cand} and add them to the original dataset. The number of added features is adaptively determined with an early-stopping mechanism. When the model performance no longer increases with a specific patience (i.e., 3), we stop adding features to the original dataset.

Figure 1b illustrates the gradient-directed feature optimizer, which consists of an encoder, a predictor, and a decoder. Due to its flexibility in the optimization of complex feature transformation, such feature optimizer is suitable for the AutoFE problem.

Figure 2: Parse tree and post-order traversal strings of the feature $\frac{min\_max(BloodPressure)}{\sqrt{|Pregnancies|\cdot Insulin}}$ in *PimaIndian*.

3.3 Feature Representation

As shown in Figure 2, we design a tree-like structure called *parse tree* to represent constructed features. Compared with the sequence representation in NFS (Chen et al., 2019) and NAO (Luo et al.,

2018), the parse tree is more flexible and expressive, which can represent complex n-ary feature transformation operation like $\frac{A+B}{C-D}$. The internal node in the parse tree indicates the transformation and the leaf node indicates the raw feature. We employ reversible post-order traversal to convert the parse tree into equivalent traversal string x as input to the encoder. Let x_r denote each token in the traversal string, where $r \in \{1 \cdots |x|\}$. Note that the relationship between the parse tree and the traversal string is one-to-many. When there are transformations where the input order is meaningless (e.g. $mul(a, b) == mul(b, a)$), the same parse tree can be converted into multiple equivalent strings. This nature can be viewed as a way of data augmentation when training the feature optimizer. Due to the fixed arity of each transformation, the optimized traversal string can be recovered to a parse tree with no ambiguity. The translation process can be found in Appendix A.

3.4 Feature Optimizer

The major component of DIFER is the feature optimizer consisting of the encoder ψ_e, the performance predictor ψ_p, and the decoder ψ_d.

Encoder. The encoder $\psi_e \in \mathcal{X} \rightarrow \mathcal{E}$ maps the post-order traversal string $x \in \mathcal{X}$ into a continuous space $\mathcal{E}$. We use LSTM (Long Short-Term Memory) (Hochreiter and Schmidhuber, 1997) as the encoder, which can take variable-length sequences as input. By the sum-pooling technique, the sum of all hidden states $H_x = \{h_1, h_2, \cdots, h_{|x|}\}$ of the LSTM as its continuous representation e_x.

Predictor. The predictor $\psi_p \in \mathcal{E} \rightarrow \mathcal{R}$ is a 5-layer fully-connected MLP. It maps the continuous representation e_x into its score s_x measured by $L_M(F \cup \{f\}, y)$.

Decoder. We employ an LSTM with the attention mechanism (Bahdanau et al., 2015) as the decoder $\psi_d \in \mathcal{E} \rightarrow \mathcal{X}$, which takes e_x as the initial hidden state and all hidden states H_x in the encoder as the input of each timestamp. The decoder maps the embedding to the discrete feature space, i.e., the post-order traversal string of the optimized feature.

Co-Training. To train the optimizer efficiently, we propose a co-training method based on a joint loss. The training dataset is the initial evaluated population $\langle F_{\text{cand}}, S_{\text{cand}} \rangle$. As shown in Figure 1c, we design a joint loss function that takes both the performance prediction loss $\mathcal{L}_{pp}$ and the structure reconstruction loss $\mathcal{L}_{rec}$ into account. The value of the hyperparameter λ that balances $\mathcal{L}_{pp}$ and $\mathcal{L}_{rec}$ is determined adaptively (see Appendix B).

$$\mathcal{L} = \lambda \mathcal{L}_{pp} + \mathcal{L}_{rec}, \text{ where } \mathcal{L}_{pp} = \sum_x \left(s_x - \psi_p \left(\psi_e \left(x \right) \right) \right)^2 \text{ and } \mathcal{L}_{rec} = -\sum_x \sum_{r=1}^{|x|} \log P_{\psi_d}(x_r | \psi_e(x)) \quad (3)$$

3.5 Feature Optimization

After the convergence of the feature optimizer, we directly optimize the feature embedding in the continuous space by performing gradient descent and then decode the optimized embedding into a new feature.

Starting from the constructed feature x, we optimize e_x to get a new embedding in the continuous space along the gradient direction induced by ψ_p:

$$e_{x'} = \sum_{h_r \in H_x} \left(h_r - \eta \frac{\partial \psi_p}{\partial h_r} \right) \quad (4)$$

However, due to the nature that the corresponding parse tree of a feature may have several equivalent post-order traversal strings $X = \{x^{(1)}, x^{(2)}, \cdots x^{(n)}\}$, the strings in X are highly similar in the continuous space. The neighborhood of X in the continuous space can be represented as follows:

$$\exists \epsilon, \forall x^{(i)} \in X, \|e_{x^{(i)}} - \frac{1}{n} \sum_{x^{(j)} \in X} e_{x^{(j)}} \|_2 \leq \epsilon \quad (5)$$

After one step of gradient descent, $e_{x'}$ may still be in the neighborhood of X. Thus, we may get the same decoded parse tree. We call η in Equation (4) the evolution rate. Increasing the evolution rate η brutally can solve this problem to some extent (Luo et al., 2018). However, a large evolution rate would violate the preconditions of gradient descent, resulting in no guarantee that $\psi_p(x + \Delta x) < \psi_p(x)$.

Multi-step gradient descent. To address this problem, we propose a straightforward but effective strategy. Specifically, we apply the optimization process in Equation (4) multiple times with a small evolution rate η until we get new parse trees. As a result, the number of times the optimization process (i.e., steps of gradient descent) is adaptively determined. We refer to the overall process as feature optimization.

4 Experiments

4.1 Experimental Setting

As with the SOTA method NFS (Chen et al., 2019), we use 25 public datasets from OpenML (Vanschoren et al., 2014), UCI repository (Dua and Graff, 2017), and Kaggle (2021). There are 15 classification (C) datasets and 10 regression (R) datasets that have various numbers of features (5 to 10936) and instances (100 to 30000). In all experiments, we set the max order k to 5 except in RQ3 and utilize 9 transformation functions totally:

- Unary transformation: *logarithm*, *abs root*, *min-max normalization*, and *reciprocal*

- Binary transformation: *addition*, *subtraction*, *multiplication*, *division*, and *modulo*

All experiments are run using Tesla K80 (GPU) and Intel(R) Xeon(R) CPU E5-2630 v2 instances. To evaluate the AutoFE method, we use the performance metric $(1 - (relative\ absolute\ error))$ (Shcherbakov et al., 2013) for the regression task and *f1-score* for the classification task. 5-fold cross validation using random stratified sampling is employed and the average result is reported. Except that different ML algorithms are used in RQ4, we utilize Random Forest as default.

In the initialization step of DIFER, we randomly select 512 features as the initial population. Both the encoder and decoder of the feature optimizer are implemented as a one-layer LSTM. We empirically set the embedding size of each token in the traversal string and the size of the hidden state to 512. The predictor is a 5-layer MLP where the number of hidden units in each layer is 1024. To train the feature optimizer, we choose the Adam optimizer (Kingma and Ba, 2014) with a learning rate of 0.001 and a weight decay of 0.0001. The number of epochs is 400, and the batch size is 128. Early stopping is employed with a patience of 10.

In each feature evolution iteration, the value of d is empirically set to be the minimum between top 20% of the initial population size and the total number of original features. The feature evolution runs until the number of feature evaluations reaches the upper limit of 4096. When optimizing the feature embedding in Equation (4), we perform gradient descent with an evolution rate η of 0.0001. Moreover, we use the same hyperparameters for all datasets. The robustness experiments with different hyperparameters can be found in Appendix C.

4.2 Effectiveness of DIFER (RQ1)

In this subsection, we demonstrate the effectiveness of DIFER. We compare DIFER on 25 datasets with the SOTA and baseline methods, including: (a) Base: raw dataset without any transformation; (b) Random: randomly applying transformations to each raw feature; (c) DFS (Kanter and Veeramachaneni, 2015): a well-known *expansion-reduction* method; (d) AutoFeat (Horn et al., 2019): a popular Python library for automated feature engineering and selection; (e) LFE (Nargesian et al., 2017): recommend the most promising transformation for each feature using MLP; (f) NFS (Chen et al., 2019): the SOTA AutoFE method that achieves better performance than other existing approaches (e.g., Khurana et al. (2018)). The experimental settings of these methods, such as the set of transformations, the max feature order, and the evaluation metrics are the same as DIFER.

Table 1: Comparison between DIFER and the existing AutoFE methods ([†] the results obtained using the open-sourced code, Inst. is short for Instance, Feat. is short for Feature, *Err.* indicates failure such as out of memory when running the open-source code, $|\hat{F}|$ denotes the number of features added into the original dataset by DIFER).

Dataset	Source	C/R	Inst.\Feat.	Base	Random	DFS[†]	AutoFeat[†]	NFS[†]	DIFER	$|\hat{F}|$
Openml_586	OpenML	R	1000\25	0.6617	0.6511	0.6501	0.7278	0.7401	**0.7683**	20
Openml_589	OpenML	R	1000\25	0.6484	0.6422	0.6356	0.6864	0.7141	**0.7727**	20
Openml_607	OpenML	R	1000\50	0.6344	0.6285	0.6388	0.6699	0.6870	**0.6918**	38
Openml_616	OpenML	R	500\ 50	0.5747	0.5714	0.5717	0.6027	0.5915	**0.6554**	8
Openml_618	OpenML	R	1000\50	0.6267	0.6167	0.6343	0.6324	0.6400	**0.6603**	32
Openml_620	OpenML	R	1000\25	0.6336	0.6178	0.6263	0.6874	0.6749	**0.7442**	12
Openml_637	OpenML	R	1000\25	0.5136	0.5268	0.5191	0.5763	0.5693	**0.6343**	13
AP-omentum-ovary	OpenML	C	275\10936	0.7636	0.7100	0.7250	*Err.*	0.8640	**0.8726**	491
Bikeshare DC	Kaggle	R	10886\11	0.8200	0.8436	0.8214	0.8498	0.9746	**0.9813**	6
Housing Boston	UCIrvine	R	506\13	0.4336	0.4446	0.3412	0.4688	**0.5013**	0.4944	1
Airfoil	UCIrvine	R	1503\5	0.4962	0.5733	0.4346	0.5955	0.6163	**0.6242**	4
PimaIndian	UCIrvine	C	768\8	0.7566	0.7566	0.7501	0.7631	0.7839	**0.7865**	1
SpectF	UCIrvine	C	267\44	0.7750	0.8277	0.7906	0.8161	0.8501	**0.8612**	9
German Credit	UCIrvine	C	1001\24	0.7410	0.7550	0.7490	0.7600	**0.7818**	0.7770	1
Ionosphere	UCIrvine	C	351\34	0.9233	0.9344	0.9175	0.9117	0.9516	**0.9770**	1
Credit Default	UCIrvine	C	30000\25	0.8037	0.8060	0.8059	0.8060	0.8049	**0.8096**	5
Messidor_features	UCIrvine	C	1150\19	0.6584	0.6878	0.6724	0.7359	0.7461	**0.7576**	10
Wine Quality Red	UCIrvine	C	999\12	0.5317	0.5641	0.5478	0.5241	**0.5841**	0.5824	6
Wine Quality White	UCIrvine	C	4900\12	0.4941	0.4930	0.4882	0.5023	0.5150	**0.5155**	9
SpamBase	UCIrvine	C	4601\57	0.9102	0.9237	0.9102	0.9237	0.9296	**0.9339**	1
Credit-a	UCIrvine	C	690\6	0.8377	0.8449	0.8188	0.8391	0.8652	**0.8826**	5
Fertility	UCIrvine	C	100\9	0.8530	0.8300	0.7500	0.7900	0.8700	**0.9098**	3
Hepatitis	UCIrvine	C	155\6	0.7860	0.8300	0.8258	0.7677	0.8774	**0.8839**	6
Megawatt1	UCIrvine	C	253\37	0.8890	0.8973	0.8773	0.8893	0.9130	**0.9171**	29
gisette	UCIrvine	C	2100\5000	0.9261	0.8710	0.7410	*Err.*	0.9590	**0.9635**	19
Avg. Eval. Num.								160,000	4,096	

Table 1 shows the comparison results between DIFER and the existing methods. Moreover, since LEF can only deal with the classification task and the source code is not available, we directly use the best results reported in the original paper (Nargesian et al., 2017). The comparison results between DIFER and LEF are shown in Table 3a. From Table 1 and Table 3a, we can observe that:

- The comparison results show that DIFER achieves the best performance in all but four cases. Although NFS greatly outperforms the baseline methods, DIFER still achieves an average improvement of 2.57% over NFS. For regression tasks, DIFER can even achieve a maximum improvement of 11.42%.

- DIFER can handle datasets with various numbers of instances and features for both regression and classification tasks and achieve performance improvement on all datasets with an average of 10.72% over Base and an average of 9.55% over Random.

- With the benefit of searching in the continuous vector space, DIFER addresses the feature explosion problem while preserving the entire space, and achieves highly competitive performance even on large datasets such as *Credit Default* (with size 30000×25) and *AP-omentum-ovary* (with size 275×10936).

4.3 Efficiency of DIFER (RQ2)

As mentioned above, the main computational bottleneck of AutoFE is the process of feature evaluation. Although the training of feature optimizer introduces an additional computation overhead, the feature optimizer is trained only once and the training overhead is much lower than the feature evaluation overhead, especially in the case of big datasets. Thus, we use the number

Dataset	LFE*	NFS†	DIFER	$|\hat{F}|$
Credit-a	0.771	0.8652	**0.8826**	5
Feritility	0.873	0.8700	**0.9098**	3
Hepatitis	0.831	0.8774	**0.8839**	6
Ionosphere	0.932	0.95160	**0.9770**	1
Megawatt1	0.894	0.9130	**0.9171**	29
SpamBase	**0.947**	0.9296	0.9339	1

Table 3a: Comparison between DIFER, LFE, and NFS (* the results reported in the paper, $|\hat{F}|$ denotes the number of features added into the original dataset by DIFER).

Figure 3b: Comparison between NFS and DIFER. The number of feature evaluations is restricted to 3500.

(a) Proportion of low/high order features generated by DIFER.

(b) Effect of the high-order feature space.

Figure 4: Effectiveness of high-order features.

of feature evaluations to measure computational efficiency. It is noteworthy that all experiments in RQ1 are conducted without the limitation of computational resources. From the perspective of computational efficiency, DIFER achieves better performance than NFS by using 40 times fewer feature evaluations while still achieving significant performance improvement.

Figure 3b shows the comparison results between NFS and DIFER with a restricted number of feature evaluations . For NFS, there is no improvement compared to the Base method on the datasets such as OpenML_618. Thus, we only show the performance improvement of DIFER on such datasets. From Figure 3b, we can see that the advantage of DIFER is more significant. DIFER achieves an average performance improvement of 6.89%, doubling the improvement in RQ1.

4.4 Effectiveness of High-Order Features (RQ3)

To evaluate the ability of exploring the high-order feature space, we conduct two experiments:

1. Analyze the features generated by DIFER during the search process and investigate whether DIFER can indeed search for the high-order features.

2. Choose the max order k from 0 to 6, where $k = 0$ means the raw dataset without any feature transformation. Then, we analyze the performance curve by varying k.

Table 2: Statistics on the performance of DIFER with different machine learning algorithms on classification (C) and regression (R) tasks.

Task	Algorithm	Avg Impr	Min/Max Impr
C	LogisticRegression	5.95%	1.01% / 15.94%
	LinearSVC	13.98%	3.17% / 22.32%
	XGBoost	6.90%	0.30% / 27.98%
	LightGBM	7.69%	0.16% / 32.63%
R	LassoRegression	14.61%	1.22% / 66.66%
	LinearSVR	32.72%	13.21% / 96.98%
	XGBoost	13.47%	3.20% / 67.06%
	LightGBM	15.46%	4.75% / 71.92%

We define the feature whose order is less/larger than $k/2$, as the low/high-order feature. Figure 4a shows the number of low/high-order features generated by DIFER with $k = 5$ for each dataset. High-order features take a considerable average proportion of 80.9%, confirming that DIFER exploits the entire feature space F_k^T instead of its subspace F_i^T where $i < k$.

Besides, we choose five representative datasets from a variety of domains, normalize the performance of DIFER for each dataset, plot the performance curve with the increasing max order in Figure 4b, and draw the following conclusions:

- The overall performance of DIFER stably increases with the max order k. However, when k increases to 5, performance improvement become insignificant.

- For most datasets, sufficient performance improvement can be already achieved with $k = 2$. There is no need to set an excessively large max order in practice.

4.5 Different Machine Learning Algorithms (RQ4)

To further investigate whether DIFER is general for different machine learning algorithms, we utilize the commonly-used algorithms, including:

- LogisticRegression (Hosmer Jr et al., 2013), LinearSVC (Cortes and Vapnik, 1995), XGBoost (Chen and Guestrin, 2016), and LightGBM (Ke et al., 2017) for classification.

- LassoRegression (Tibshirani, 1996), LinearSVR (Smola and Schölkopf, 2004), XGBoost (Chen and Guestrin, 2016), and LightGBM (Ke et al., 2017) for regression.

We conduct experiments on all datasets and the performance statistics are shown in Table 2. Compared to the Base method, DIFER achieves significant improvement under different algorithms. For instance, LinearSVR with DIFER even achieves an average improvement of 32.72% across 25 datasets and a max improvement of 96.98% in *Airfoil*.

5 Conclusion and Future Work

In this work, we proposed DIFER, to the best of our knowledge, the first differentiable AutoFE method. DIFER leverages an encoder-predictor-decoder-based feature optimizer, which maps features into the continuous vector space via the encoder, optimizes the embedding along the gradient direction induced by the predictor, and recovers better features from the optimized embedding by the decoder. Moreover, based on the feature optimizer, we proposed a feature evolution framework to search for better features iteratively. Experimental results show that DIFER is effective on both classification and regression tasks and can outperform the existing AutoFE methods in terms of both prediction performance and computational efficiency.

The transformation operations in DIFER are for numerical features. For future work, we plan to automatically search for transformations for different feature types (i.e., numerical and categorical).

References

Bahdanau, D., Cho, K., and Bengio, Y. (2015). Neural machine translation by jointly learning to align and translate. In *3rd International Conference on Learning Representations, ICLR 2015*.

Chen, T. and Guestrin, C. (2016). Xgboost: A scalable tree boosting system. In *Proceedings of the 22nd acm sigkdd international conference on knowledge discovery and data mining*, pages 785–794.

Chen, X., Lin, Q., Luo, C., Li, X., Zhang, H., Xu, Y., Dang, Y., Sui, K., Zhang, X., Qiao, B., et al. (2019). Neural feature search: A neural architecture for automated feature engineering. In *2019 IEEE International Conference on Data Mining (ICDM)*, pages 71–80. IEEE.

Cortes, C. and Vapnik, V. (1995). Support-vector networks. *Machine learning*, 20(3):273–297.

Dua, D. and Graff, C. (2017). UCI machine learning repository.

Elsken, T., Metzen, J. H., Hutter, F., et al. (2019). Neural architecture search: A survey. *J. Mach. Learn. Res.*, 20(55):1–21.

Goyal, P., Dollár, P., Girshick, R., Noordhuis, P., Wesolowski, L., Kyrola, A., Tulloch, A., Jia, Y., and He, K. (2017). Accurate, large minibatch sgd: Training imagenet in 1 hour. *arXiv preprint arXiv:1706.02677*.

He, X., Zhao, K., and Chu, X. (2020). Automl: A survey of the state-of-the-art. *Knowledge-Based Systems*, page 106622.

Hochreiter, S. and Schmidhuber, J. (1997). Long short-term memory. *Neural computation*, 9(8):1735–1780.

Horn, F., Pack, R., and Rieger, M. (2019). The autofeat python library for automated feature engineering and selection. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pages 111–120. Springer.

Hosmer Jr, D. W., Lemeshow, S., and Sturdivant, R. X. (2013). *Applied logistic regression*, volume 398. John Wiley & Sons.

Kaggle (2021). Kaggle datasets.

Kanter, J. M. and Veeramachaneni, K. (2015). Deep feature synthesis: Towards automating data science endeavors. In *2015 IEEE international conference on data science and advanced analytics (DSAA)*, pages 1–10. IEEE.

Ke, G., Meng, Q., Finley, T., Wang, T., Chen, W., Ma, W., Ye, Q., and Liu, T.-Y. (2017). Lightgbm: A highly efficient gradient boosting decision tree. In *Advances in neural information processing systems*, pages 3146–3154.

Khurana, U., Nargesian, F., Samulowitz, H., Khalil, E., and Turaga, D. (2016). Automating feature engineering. *Transformation*, 10(10):10.

Khurana, U., Samulowitz, H., and Turaga, D. (2018). Feature engineering for predictive modeling using reinforcement learning. In *Thirty-Second AAAI Conference on Artificial Intelligence*.

Kingma, D. and Ba, J. (2014). Adam: A method for stochastic optimization. *International Conference on Learning Representations*.

Lam, H. T., Thiebaut, J.-M., Sinn, M., Chen, B., Mai, T., and Alkan, O. (2017). One button machine for automating feature engineering in relational databases. *arXiv preprint arXiv:1706.00327.*

Liu, H., Simonyan, K., and Yang, Y. (2018). Darts: Differentiable architecture search. In *International Conference on Learning Representations.*

Luo, R., Tian, F., Qin, T., Chen, E., and Liu, T.-Y. (2018). Neural architecture optimization. In *Advances in neural information processing systems*, pages 7816–7827.

Nargesian, F., Samulowitz, H., Khurana, U., Khalil, E. B., and Turaga, D. S. (2017). Learning feature engineering for classification. In *IJCAI*, pages 2529–2535.

Shcherbakov, M. V., Brebels, A., Shcherbakova, N. L., Tyukov, A. P., Janovsky, T. A., and Kamaev, V. A. (2013). A survey of forecast error measures. *World Applied Sciences Journal*, 24(24):171–176.

Smola, A. J. and Schölkopf, B. (2004). A tutorial on support vector regression. *Statistics and computing*, 14(3):199–222.

Tibshirani, R. (1996). Regression shrinkage and selection via the lasso. *Journal of the Royal Statistical Society: Series B (Methodological)*, 58(1):267–288.

Vanschoren, J., van Rijn, J. N., Bischl, B., and Torgo, L. (2014). Openml: Networked science in machine learning. *SIGKDD Exploration Newsletter*, 15(2):49–60.

Zoph, B. and Le, Q. V. (2017). Neural architecture search with reinforcement learning. In *ICLR 2017.*