ON THE UNCOMPUTABILITY OF PARTITION FUNCTIONS IN ENERGY-BASED SEQUENCE MODELS

ABSTRACT

In this paper, we argue that energy-based sequence models backed by expressive parametric families can result in uncomputable and inapproximable partition functions. Among other things, this makes model selection — and therefore learning model parameters — not only difficult, but generally *undecidable*. The reason is that there are no good deterministic or randomized estimates of partition functions. Specifically, we exhibit a pathological example where under common assumptions, *no* useful importance sampling estimates of the partition function can guarantee to have variance bounded below a rational number. As alternatives, we consider sequence model families whose partition functions are computable (if they exist), but at the cost of reduced expressiveness. Our theoretical results suggest that statistical procedures with asymptotic guarantees and sheer (but finite) amounts of compute are not the only things that make sequence modeling work; computability concerns must not be neglected as we consider more expressive model parametrizations.

1 INTRODUCTION

Modeling discrete sequences is central to natural language processing and bioinformatics. Many common parametric sequence models $\tilde{p}$ are (or can be cast as) *energy-based* (LeCun et al., 2006): they yield a weight $\tilde{p}(\boldsymbol{x})$ for any given string $\boldsymbol{x}$. Although energy-based models (EBMs) of sequences need not represent probability distributions, they have been proposed as such to counter the inexpressivity of autoregressive sequence models (Bakhtin et al., 2021; Lin et al., 2021, §4.1). EBMs with finite **partition functions** $Z_{\tilde{p}} \triangleq \sum_{\boldsymbol{x}} \tilde{p}(\boldsymbol{x}) \in \mathbb{R}_{>0}$ define distributions $p(\boldsymbol{x}) \triangleq \tilde{p}(\boldsymbol{x})/Z_{\tilde{p}}$ over strings, which are often queried under the principle of probabilistic inference (Ghahramani, 2015).[1]

Energy-based sequence models are often parametrized as neural models. Each parameter vector $\boldsymbol{\theta}$ in some parametric neural network family $\boldsymbol{\Theta} \subseteq \mathbb{R}^d$ identifies a parametric model $\tilde{p}_{\boldsymbol{\theta}}$, which then defines a parametric distribution over strings $p_{\boldsymbol{\theta}}$, assuming $Z_{\tilde{p}_{\boldsymbol{\theta}}}$ exists (Chen et al., 2018). Contemporary neural networks have been shown to be very powerful. In particular, some popular parametric neural sequence model families, such as RNNs (Siegelmann & Sontag, 1995) and Transformers (Bhattamishra et al., 2020; Pérez et al., 2021), have been formally shown to recognize recursively enumerable languages: given *any* Turing machine M, there is a parameter vector $\boldsymbol{\theta} \in \boldsymbol{\Theta}$ such that the parametrized sequence model $N_{\boldsymbol{\theta}}$ recognizes the same language as M does. In other words, these sequence model families are **Turing-complete**.

It is therefore intuitive that energy-based sequence models, backed by such powerful neural networks, form expressive families of string distributions (§3.1): for *any* decision algorithm M, there is a parameter vector $\boldsymbol{\theta}_M$ in a Turing-complete parametric family $\boldsymbol{\Theta}$, such that $p_{\boldsymbol{\theta}_M}$ exists, and $p_{\boldsymbol{\theta}_M}(\boldsymbol{x})$ is high if and only if M accepts $\boldsymbol{x}$. It would seem assuring to work with such expressive family of sequence distributions, $\boldsymbol{\Theta}$: assuming the true string probabilities indeed can be computed in polytime, $\boldsymbol{\Theta}$ is well-specified. Moreover, one may assume that given we can sample from $p_{\boldsymbol{\theta}_M}$, we would be able to use consistent estimators to find $\boldsymbol{\theta}' \in \boldsymbol{\Theta}$, where $\boldsymbol{\theta}' \approx \boldsymbol{\theta}_M$.

Unfortunately, we find that with such an expressive distribution family $\boldsymbol{\Theta}$, whether the identifiability assumption holds — required for most consistent estimators — itself is **undecidable** (Turing, 1937).

---

[1]Many popular energy-based sequence models compute *normalized* probabilities directly (*i.e.*, $\tilde{p}(\boldsymbol{x}) = p(\boldsymbol{x})$) (Jelinek, 1980; Katz, 1987; Bengio et al., 2003; Brown et al., 2020, *inter alia*). This makes both training and querying with string prefixes much easier, at the cost of expressiveness (Lin et al., 2021).

	exact	asymptotic
deterministic	✗ (Theorem 2)	✓ (§5; but no useful guarantee in finite time)
randomized	✗ (Lemma 1)	✓ but suspected to be useless in general; also
✗ for rejection sampling (Theorem 5) and
✗ for importance sampling (Theorem 6)

Table 1: Summary of negative results: Can randomized (or deterministic) exact (or asymptotic) estimates accurately approximate EBM partition functions for efficiently computable (i.e., polytime) weighted languages?

Moreover, model selection on *any* held-out data is also undecidable. Even worse, as long as a parametric family Θ' contains one specific vector $\theta' \in \Theta$, model selection will not be possible for Θ' either — even when Θ' itself is not necessarily expressive. We construct one such 'pathological' distribution $p_{\theta'}$ as a Transformer EBM.

These negative results stem from the uncomputability and inapproximability of Z. A main technical contribution of this paper is that there is no algorithm (either deterministic or randomized) that can approximate Z well. Since statistical procedures are also algorithms, common randomized estimates are not useful in this scenario, either — however, we will see that for less expressive model families, such incomputability issues do not arise. Our negative results are summarized in Table 1. To ensure that model selection is still possible (such that we can compare different parameter vectors with confidence), we have no choice but to resort to less expressive string distributions.

The paper is structured as follows. In §2 we review definitions and known results of weighted languages, sequence model families, and formalize concepts of weighted Turing machines, EC-complete parametric families, and computable estimates. In §§3–5 we describe our main technical results: there exist pathological EBM sequence models that have uncomputable partition functions, which cannot be approximated well under stochastic estimates, and do not have asymptotic estimates that have any good guarantees. In §6 we that argue our negative results make model selection impossible for expressive model families, and discuss why common estimation methods fail. Finally, we discuss three 'palliative' parametrization choices in §7, which all guarantee computable partition functions, at the cost of expressiveness.

2 BACKGROUND

2.1 ENERGY-BASED SEQUENCE MODELS

Energy-based models (EBMs) of sequences (LeCun et al., 2006; Rosenfeld et al., 2001; Sandbank, 2008; Huang et al., 2018; Bakhtin et al., 2021) are a family of discrete sequence models. Given a string $\boldsymbol{x} \in V^*$ over a finite vocabulary V, an EBM $\tilde{p}$ computes string **weight** $\tilde{p}(\boldsymbol{x})$, but not the (normalized) string **probability** $p(\boldsymbol{x}) = \tilde{p}(\boldsymbol{x})/\sum_{\boldsymbol{x}} \tilde{p}(\boldsymbol{x})$. In this work, we focus on EBMs whose weight is efficiently computable, i.e., polytime in the length of $\boldsymbol{x}$. Following Bakhtin et al. (2021) and Lin et al. (2021), we wish to use our EBMs as probability distributions; this requires normalization. While EBMs are often intractable to normalize (e.g., the Ising model), the infinite domain of finite strings opens the door to *uncomputable* probabilities, which invite the impossibility of model selection and comparison.

2.2 WEIGHTED LANGUAGES

EBMs give weights to strings. Here we formally characterize these weighted strings as a *weighted language*. An unweighted language $L \subseteq V^*$ is a set of finite strings $\boldsymbol{x}$ over a finite vocabulary V. A **weighted language** $\tilde{p}$ is a function $\tilde{p} : V^* \to \mathbb{R}_{\geq 0}$.[2] In this work, we discuss Boolean languages, such that $V = \mathbb{B} \triangleq \{\mathbf{0}, \mathbf{1}\}$. We also focus on weighted languages where distributions over strings exist. We say a weighted language $\tilde{p}$ is **normalizable** when $Z_{\tilde{p}} \triangleq \sum_{\boldsymbol{x} \in \mathbb{B}^*} \tilde{p}(\boldsymbol{x}) \in \mathbb{R}_{>0}$: the sum over all possible strings is finite and positive. $Z_{\tilde{p}}$ is also called the **partition function** of $\tilde{p}$.[3] We can then normalize $\tilde{p}$ into a **distribution** p over $\mathbb{B}^*$ such that $p(\boldsymbol{x}) = \tilde{p}(\boldsymbol{x})/Z_{\tilde{p}}$, and thereby $\sum_{\boldsymbol{x} \in \mathbb{B}^*} p(\boldsymbol{x}) = 1$.

---

[2] With a slight abuse of notation, we define support($\tilde{p}$) $\triangleq \{\boldsymbol{x} : \tilde{p}(\boldsymbol{x}) > 0\}$.

[3] We use the convention that $Z_{\tilde{p}}$ is the partition function of $\tilde{p}$, and $Z_{\tilde{q}}$ of $\tilde{q}$, etc. The subscript is omitted in unambiguous cases.

The **efficiently computable (weighted) languages** (EC; Lin et al., 2021) are those weighted languages $\tilde{p}$, where a string's weight (which must be non-negative) is a polytime function of the string. Weighted languages defined by most EBM sequence models fall into this class, since they score every string in finite time (and usually in polytime); and the scores ultimately are computed by some algorithm.

By definition, string weights of an EC language can be obtained as a side product from a Turing machine that recognizes x (in polytime). However, Lin et al. (2021) did not precisely describe how a Turing machine maps input string x to its (rational) weight $\tilde{p}(x)$ in finite time. In this work, such a construction (out of many possible ones) is necessary, as we need to show that this string weighting can be done by parametric sequence model families (see Appendix A).

2.3 Locally normalized distributions

A popular subclass of weighted languages is **locally normalized weighted languages** (LN), where conditional local distributions given prefix $\hat{x}$: $p(\cdot \mid \hat{x})$ can be computed in finite time. Since they automatically define a distribution over strings, we use the term **locally normalized distributions** interchangeably. If $p(\cdot \mid \hat{x})$ can be computed in polynomial time, we call such distributions **efficiently locally normalized distributions** (ELN) — this is the weighted language class of most autoregressive models, just as its superset EC is the weighted language class of most energy-based sequence models.

Locally normalized distributions over sequences have $\tilde{p}(x) = p(x)$, and $Z = \sum_{x \in \mathbb{B}^*} \tilde{p}(x) = 1$. They are **consistent**: the probability that a string is infinitely long under such distributions is zero. Equivalently, given any $\epsilon > 0$, we can approximate Z with a finite sum of string weights:

Proposition 1 (Consistency of LN distributions (Booth & Thompson, 1973; Chen et al., 2018)). *Let $p \in$ LN be a locally normalized distribution over strings. All strings of a given length or longer have their probabilities bounded. That is, for all positive real numbers ϵ, there is a length n at which all strings x of length at least n have $p(x) < \epsilon$.*

The consistency property of locally normalized distributions implies that they have an exact sampling procedure that almost surely terminates in finite time. Therefore, they (and in particular ELN distributions) are an attractive choice as proposal distributions in parameter estimation procedures that alternate between expectation and maximization steps (Dempster et al., 1977).

2.4 EC-complete parametric families

We have introduced energy-based sequence models (§2.1) and their characterization as weighted languages (§2.2). However, in the practice of machine learning, we usually do not work with literal implementations of Turing machines directly. Instead, the most common models of computation are neural network models, such as RNNs and Transformers. Those computational models are usually not described in terms of explicit state transitions, which makes their correspondence with state-machine-based abstractions of computation (*e.g. halting* on a string) less obvious.

To connect neural sequence models to formal language classes, we adopt the definition of **sequence model families** from Pérez et al. (2021). A sequence model family is a set of **seq-to-seq** models $\mathbf{N} = \{N_{\theta} : \theta \in \Theta\}$, where every $N_{\theta} \in \mathbf{N}$ **recognizes** language L_{θ} if and only if the seq-to-seq model N_{θ}, paired with **embedding function** $f : \mathbb{B} \to \mathbb{Q}^d$, **initial states** $s \in \mathbb{Q}^d$, and polytime termination decision function $g : \mathbb{Q}^d \to \mathbb{B}$, *accepts* every string $x \in L_{\theta}$. And we define N_{θ} to **accept** $x = [x_1 \ldots x_T] \in \mathbb{B}^*$ if and only if there exists $r \in \mathbb{N}$, such that N_{θ} upon input embeddings $[f(x_1) \ldots f(x_T)]$, produces output embeddings $\boldsymbol{y}_r$ at the r-th time step, where $g(\boldsymbol{y}_r) = 1$.

RNNs (Siegelmann & Sontag, 1995) and Transformers (Pérez et al., 2021) are powerful formal language recognizers under our definition of sequence model families. Specifically, both can simulate computations in a universal Turing machine, with finite-length parameter vectors. Those model families are known as **Turing-complete sequence model families**: sequence model families for which every recursively enumerable language L is recognized by some seq-to-seq model within the family.

This work discusses *weighted* languages. Just as we extend the definition of Turing machines to weighted Turing machines, we also extend the definition of sequence model families. We therefore define **EC-complete parametric families**, as a sequence model counterpart of the weighted language class EC. Formally, a parametric family Θ is EC-complete if given any $\tilde{p} \in$ EC (as a description of a weighted Turing machine), we can construct a parameter vector $\theta \in \Theta$ such that there exist polytime functions

$w_p : \mathbb{Q}^d \to \mathbb{N} \cup \{0\}$ and $w_q : \mathbb{Q}^d \to \mathbb{N} \cup \{0\}$, where whenever on input $\boldsymbol{x} = [x_1 \ldots x_T]$, if $g(\boldsymbol{y}_r) = 1$ for some output embeddings $\boldsymbol{y}_r$ (that is, $N_{\boldsymbol{\theta}}$ accepts $\boldsymbol{x}$ in r time steps), $w_P(\boldsymbol{y}_r)/w_q(\boldsymbol{y}_r) = \tilde{p}(\boldsymbol{x})$.

We show that with a slight modification to positional embeddings, the family of arbitrary precision, hard attention Transformers defined in Pérez et al. (2021) is EC-complete:[4]

Theorem 1. *The class of one-encoder-layer four-decoder-layer Transformer networks with positional encodings $(n, 1/n, 1/n^2, 2^n)$ is EC-complete.*

Proof sketch. We extend the construction from Pérez et al. (2021), adding an additional layer to accumulate the string weight over time steps. □

2.5 Estimates

A main result of this work is that partition functions in an EC-complete family are uncomputable. Moreover, randomness does not help estimation; and correct asymptotic estimates are not useful. We define these estimates here in order to discuss the power of different estimates concretely.

Let $\boldsymbol{\Theta}$ be a parametric family. We say function $f : \boldsymbol{\Theta} \to \mathbb{Q}$ is an **exact estimate** if there exists a weighted deterministic Turing machine that takes $\boldsymbol{\theta}$ as input, then upon halting outputs $f(\boldsymbol{\theta}) \in \mathbb{Q}$ in finite time.

Many estimation procedures are *anytime algorithms*: they do not have a predetermined runtime, and they can be stopped at any time before completion to produce a valid output. Output quality of an anytime algorithm may improve with increased runtime. Moreover, many of these algorithms have asymptotic guarantees, in that their outputs are optimal in some sense (*e.g.*, consistency) in the limit. We capture these algorithms with **asymptotic estimates**: a function $f(\boldsymbol{\theta})$ is an asymptotic estimate if there exists a weighted Turing machine that takes both $\boldsymbol{\theta}$ and an index i as input, then outputs a value $f_{\tilde{p},i} \in \mathbb{Q}$ in finite time, such that the outputs converge toward $f(\boldsymbol{\theta})$ as i increases toward infinity.

We now extend both exact and asymptotic estimates to the stochastic case, where we compute the estimates using randomized algorithms instead of deterministic ones. As is conventional for randomized algorithms, we assume the use of probabilistic Turing machines. Probabilistic Turing machines have access to an infinitely long random tape. The tape describes an infinite binary sequence from tossing a fair two-sided coin infinitely many times.[5] We define a **randomized exact estimate f** as a weighted Turing machine with two input tapes — the random tape $\tau \in \mathbb{B}^{\mathbb{N}}$, and an input tape that has $\boldsymbol{\theta}$ — and outputs $f(\boldsymbol{\theta}, \tau)$ in finite time. Likewise, we say $\mathbf{f}_{\boldsymbol{\theta},i}$ is a **randomized asymptotic estimate** if there exists a function $f(\boldsymbol{\theta}) \in \mathbb{R}$ and a weighted Turing machine that takes $(\boldsymbol{\theta}, i), \tau$ on two input tapes, so that for all random Boolean tapes $\tau \in \mathbb{B}^{\mathbb{N}}$, we converge with $\lim_{i \to \infty} f_{\boldsymbol{\theta},i,\tau} = f(\boldsymbol{\theta})$. Many Monte Carlo estimates can be seen as randomized asymptotic estimates, including rejection sampling and importance sampling estimates.

3 Expressiveness and uncomputability: pathological EBMs

3.1 Expressive sequence distributions

To illustrate the uncomputability issues of energy-based models, we construct families of string distributions that are **expressive**: they require the full power of an EC-complete sequence model family.

We define $\tilde{p}_{M,k} \in \mathcal{G}_k$ to be a weighted language, parametrized by (M, k), where a) M is a deterministic Turing machine that takes an empty string as input ('input-free'); and b) $k \in \mathbb{Q}_{>0}$. Let $L_{\text{TM}} \subseteq \mathbb{B}^*$ be a prefix-free Boolean language of computation sequences of a Turing machine — that is, encodings of the trace of the Turing machine's operations. We define

$$\tilde{p}_{M,k}(\boldsymbol{x}) = \begin{cases} 1/3^{|\boldsymbol{x}|+1} + k & \text{if } \boldsymbol{x} \in L_{\text{TM}}, \text{ and } \boldsymbol{x} \text{ encodes a valid accepting} \\ & \text{trace of } M. \\ 1/3^{|\boldsymbol{x}|+1} & \text{otherwise.} \end{cases} \tag{1}$$

---

[4]All proofs omitted from the main text are included in the appendices. Proof sketches for major theorems are in the main text.

[5]Formally speaking, we define a probability space $(\Omega, \mathcal{A}, \mathbb{P})$ where $\Omega = \mathbb{B}^{\mathbb{N}}$ is our sample space, $\mathcal{A} = \{A : A \in \mathcal{P}(\Omega), \text{all strings in } A \text{ share the same prefix} \in \mathbb{B}^*\}$ is our event space, and $\mathbb{P}(A) = 2^{-n}$ where n is the length of longest shared prefix of A is our probability function (Stroock, 2014).

The weighted language $\tilde{p}_{M,k}$ can weight any string x of length n in time $O\big(\text{poly}(n)\big)$ by simulating x on M. That is, $\tilde{p} \in$ EC (§2.2). We also know that for any (deterministic) machine M, the language's partition function $Z_{\tilde{p}_{M,k}}$ exists, and it must equal either 1 or $1 + k$, since there is either one halting trace ($Z_{\tilde{p}_{M,k}} = 1 + k$), or none ($Z_{\tilde{p}_{M,k}} = 1$). Therefore, each $\tilde{p} \in \mathcal{G}_k$ defines a string distribution.

Since for all $k \in \mathbb{Q}_{>0}$, $\mathcal{G}_k \subset$ EC, all weighted languages $\tilde{p}_{M,k}$ have an equivalent parameter vector $\theta_{M,k}$ in any EC-complete family Θ. Also, since each $\mathcal{G}_k$ is a bijection between the set of all input-free Turing machines and a subset of Θ, it follows that there is no exact estimate (§2.5) of the partition function of any EC-complete family (*e.g.*, Transformer EBMs (Theorem 1)), by a reduction from HALT (Sipser, 2013):

Theorem 2. *Let Θ be a parametric* EC-*complete sequence model family. And let $\Theta_k \subset \Theta$ be bijective with $\mathcal{G}_k$. There is no $k \in \mathbb{Q}_{>0}$ for which there exists an exact estimate $\hat{Z}_k$ that takes as input $\theta \in \Theta_k$ as input, and computes $\hat{Z}_k(\theta) = Z_{\tilde{p}_\theta}$ in finite time.*

Proof sketch. Θ_k contains parametric vectors for all input-free Turing machines M. For any of these weighted languages, knowing the exact value of $Z_{\tilde{p}_{M,k}} \in \{1, k + 1\}$ is enough of deciding whether M halts (M halts iff $Z_{\tilde{p}_{M,j}} = k + 1$). Since HALT is undecidable for input-free Turing machines, the algorithm $\hat{Z}_k$ cannot exist. □

We note that the uncomputability of partition functions in other expressive model families, where Turing completeness also arises (Kempe et al., 2004; Chiang & Riley, 2020).

3.2 An EBM whose partition function is uncomputable

Theorem 2 states there is no estimate that 'works' for a subset of parameter vectors. While every $\mathcal{G}_k$ is much smaller than its superset EC, $\mathcal{G}_k$ is still (countably) infinite. Here under the assumption that ZFC is consistent, we construct *one* weighted language $\tilde{b} \in \mathcal{G}_1$ (for simplicity; it holds for arbitrary k), where $Z_{\tilde{b}}$ is uncomputable:

Theorem 3. *Assuming ZFC axioms and that assuming they is consistent, there exists $\tilde{b} \in \mathcal{G}_1$ such that (a) $Z_{\tilde{b}} = c \in \{1, 2\}$ exists, but (b) there is no proof of $Z_{\tilde{b}} = c$.*

Proof sketch. If there were a proof $Z_{\tilde{b}} = 1$ then we proved ZFC is consistent, which is impossible under Gödel's 2nd incompleteness theorem (Jech, 1994). If there were a proof $Z_{\tilde{b}} = 2$, then we proved ZFC is not consistent, which violated our assumption. □

The existence of $\tilde{b}$ suggests that if there is an algorithm that approximates $Z_{\tilde{p}}$, *and* produces a witness of its approximation quality, then this algorithm will not work on *any* set of parameter vectors that can parametrize $\tilde{b}$ — even when this algorithm may work for some subsets of Θ. This is useful in allowing us to show negative results regarding finite subsets of Θ. Below is one such example:

Corollary 1. *Assuming ZFC axioms and assuming they are consistent, there exists $\theta \in \Theta$ such that $Z_{\tilde{p}_\theta} \in \mathbb{Q}_{>0}$ exists, but there is no algorithm $\hat{Z}_{\text{proof}}$ that takes $\theta \in \Theta$ as input, and outputs a set of strings $\{x_n : n < N\}, N \in \mathbb{N}$ where*

- *there is a proof that $\sum_{n=1}^{N} \tilde{p}_\theta(x) \geq \frac{1}{2} Z_{\tilde{p}_\theta}$; or*
- *there is a proof that $\sum_{n=1}^{N} \tilde{p}_\theta(x) < \frac{1}{2} Z_{\tilde{p}_\theta}$.*

Corollary 1 states that there exists a 'problematic EBM' — namely $\tilde{b}$ — where we cannot guarantee to well approximate its partition function, by accumulating finitely many string weights, regardless of the manner of accumulation (*i.e.*, how we choose strings) or the number of strings we enumerate over. We discuss this in further details in §2.5.

4   No randomized algorithm can estimate Z accurately.

We've shown by Theorem 2 that for an EC-complete family, there are no exact estimates than can get Z perfectly right. In this section, we show that no randomized exact estimate for this is unbiased. Further, there isn't even an estimate whose bias is within some multiplicative factor ϵ, regardless of the variance's magnitude.

Lemma 1. *Let* Θ *be an* EC-*complete parametric family. There is no multiplicative factor* $\epsilon \in \mathbb{Q}_{>1}$ *for which every* $\theta \in \Theta$ *can have its partition function approximated with* $\hat{\mathbf{Z}}_\epsilon(\theta)$ *within a factor of* ϵ *— with probability greater than* 2/3. *That is, we cannot have*

$$P\left((1/\epsilon)\, Z_{\tilde{p}_\theta} \leq \hat{\mathbf{Z}}_\epsilon(\theta) \leq \epsilon Z_{\tilde{p}_\theta}\right) > 2/3. \tag{2}$$

Proof sketch. Because $\hat{\mathbf{Z}}_\epsilon$ computes an estimate in finite time, it can only use finitely many distinct random tape segments. We therefore derandomize $\hat{\mathbf{Z}}_\epsilon$ by enumerating finitely many 'random' tapes, and can always return correct answer, given the 2/3 success probability assumption, and would be able to decide HALT, making use of distributions in $\mathcal{G}_{\epsilon^2}$. $\square$

Taken together, Theorem 2 and Lemma 1 state that no exact estimate $\hat{Z}$ — whether randomized or deterministic — can approximate Z with good confidence. In Theorem 4 below, we will make an even stronger claim: regardless of the dispersion magnitude, it is impossible to bound the mean of random exact estimates of Z to within any (computable) multiplicative factor. The theorem is based on the observation that for any estimate whose variance and absolute third moment are finite and computable, the sample mean distribution of $\hat{\mathbf{Z}}$ over N samples converges to a normal distribution at rate $O(\sqrt{N})$. As the sample size gets *large enough*, the normal approximation becomes *good enough* to establish a confidence interval. Therefore, if we could bound $\mathbb{E}\left[\hat{\mathbf{Z}}\right]$ within some multiplicative bound of Z, we could use the confidence interval to build another randomized exact estimate $\hat{\mathbf{Z}}'$ that guarantees a multiplicative bound of Z with probability greater than 2/3, which contradicts Lemma 1 by implying a general algorithm to decide HALT.

Theorem 4. *Let* Θ *be an* EC-*complete parametric family. There is no multiplicative bound* $\epsilon \in \mathbb{Q}_{>1}$ *such that there exists a randomized exact estimate* $\hat{\mathbf{Z}}_\epsilon$ *that guarantees* $1/\epsilon \leq \mathbb{E}[\hat{\mathbf{Z}}_\epsilon(\theta)]/Z_{\tilde{p}_\theta} \leq \epsilon$, *for every* $\theta \in \Theta$ *where* $\tilde{p}_\theta$ *is normalizable.*

Proof sketch. We invoke the Berry–Esseen theorem to quantify the rate of convergence. The theorem depends on the finiteness of the third absolute moment, which we show to be the case by determinization. $\square$

5 COMMON ASYMPTOTIC ESTIMATES DO NOT GIVE USEFUL GUARANTEES

Let's now recap the progress we've made so far. We've shown that no (deterministic) exact estimate can get Z exactly right in general (Theorem 2), lest it need to solve HALT. Further, no randomized exact estimate can approximate it within any given relative tolerance, with good confidence (Theorem 4).

But what about *asymptotic* estimates? We do know there are correct asymptotic estimates of Z. For example, consider the following asymptotic estimate $\hat{Z}(\theta)$ backed by a weighted Turing machine that takes $\theta \in \Theta$ and $i \in \mathbb{N}$ as inputs, and returns $f_{\theta,i} \triangleq \sum_{x:x \in \mathbb{B}^*, |x| \leq i} \tilde{p}_\theta(x)$. We have $\lim_{i\to\infty} \hat{Z}_{\theta,i} = Z_{\tilde{p}_\theta}$, so $\hat{Z}$ is asymptotically correct. However, $\hat{Z}_{\text{asym}}$ does not have a convergence rate guarantee: for any $i \in \mathbb{N}$, $\|\hat{Z}_{\theta,i} - Z_{\tilde{p}_\theta}\|$ is uncomputable. We also do not know how much can we improve our estimate when we increment i. As Corollary 1 suggests, we likely cannot have such a guarantee.

In this section, we formalize such intuition for two popular asymptotic estimates: rejection and importance sampling methods. Specifically, we show that any parametric family that is able to parametrize $\tilde{b}$ from §3.2 cannot have provably useful locally normalized distributions (§2.3) as proposal distributions.

5.1 REJECTION SAMPLING ESTIMATE OF Z CANNOT BE GUARANTEED TO BE POSSIBLE.

Rejection sampling (Owen, 2013) is a commonly used exact sampling method, applicable even when we cannot sample from an unnormalized distribution $\tilde{p}$. We instead sample from an easy-to-sample distribution q, then stochastically reject samples, to ensure the probability a sample x is kept is proportional to $\tilde{p}(x)$.

For rejection sampling to work, the candidate q's support must contain the target $\tilde{p}$'s entire support, so that all true points can be sampled. We also need some finite constant c so that cq envelops $\tilde{p}$:

$$\exists c \in \mathbb{R}_{>0} \text{ such that } \forall x \in \mathbb{B}^*, \frac{\tilde{p}(x)}{q(x)} \leq c.$$

We will show that for certain EBMs, one cannot formally guarantee the existence of an eligible q.

Theorem 5. *Using ZFC as our axiom set and assuming they are consistent, then there exists a normalizable EC weighted language $\tilde{p}$, where there does not exist a consistent locally normalized proposal distribution $q \in$ LN, and $c_q \in \mathbb{Q}_{>0}$, such that it can be proven $\forall \boldsymbol{x} \in \mathbb{B}^*$, $\tilde{p}(\boldsymbol{x})/q(\boldsymbol{x}) < c_q \neq \infty$.*

Proof sketch. Let $\tilde{p} = \tilde{b}$. If there were such q and c_q, we could in finite time prove $Z_{\tilde{p}} = 1$ or $Z_{\tilde{p}} = 2$, which contradicts Theorem 3. □

Theorem 5 implies that there is no way of ensuring rejection sampling works, not only for any EC-complete families, but also for any parametric family that can parametrize $\tilde{b}$.

5.2 Importance sampling estimate of Z cannot be guaranteed to be effective.

Similar to the case of rejection sampling, one cannot guarantee an importance-sampling estimate of Z to be 'good' — in this case, we mean that there cannot be a proof that the importance sampling variance is finite, regardless of the sample size.

We first formalize importance sampling estimates of Z in the manner of randomized asymptotic estimates (§2.5). We define

$$\hat{\boldsymbol{Z}}^q_{\boldsymbol{\theta},N} = \frac{1}{N} \sum_{n=1}^{N} \frac{\tilde{p}_{\boldsymbol{\theta}}(\boldsymbol{x}^{(n)})}{q(\boldsymbol{x}^{(n)})}$$

to be an N-sample importance sampling estimate of $Z_{\tilde{p}_{\boldsymbol{\theta}}}$ under q, so $\boldsymbol{x}^{(1)} \ldots \boldsymbol{x}^{(N)}$ are samples from $q \in$ LN.

We generally want to minimize the variance of $\hat{\boldsymbol{Z}}^q_{\boldsymbol{\theta},N}$ under q: $\mathrm{Var}_q\left(\hat{\boldsymbol{Z}}^q_{\boldsymbol{\theta},N}\right)$ (Owen & Zhou, 2000). And we certainly do not want $\mathrm{Var}_q\left(\hat{\boldsymbol{Z}}^q_{\boldsymbol{\theta},N}\right) = \infty$. Unfortunately, for certain EBMs, we cannot guarantee there is a good locally normalized proposal distribution that has finite variance:

Theorem 6. *Let $\boldsymbol{\Theta}$ be an EC-complete parametric family. Assuming ZFC axioms and assuming they are consistent, there exists $\boldsymbol{\theta} \in \boldsymbol{\Theta}$ where there does not exist a consistent locally normalized "proposal" distribution $q \in$ LN such that it can be proven $\mathrm{Var}_q\left(\hat{\boldsymbol{Z}}^q_{\boldsymbol{\theta},N}\right) < c \neq \infty$, where $c \in \mathbb{Q}_{>0}$.*

Proof sketch. Proven in a manner similar to the proof of Theorem 5. □

6 Uncomputable Z causes parameter estimation problems

Theorems 2 and 3 state that it is generally impossible to estimate partition functions in an expressive parametric family, such as certain subsets of an EC-complete family. Here we show how parameter estimation is made difficult as well: parameter identifiability is formally undecidable for an EC-complete family. Model selection is not possible, either.

6.1 Parameter identifiability under EC-complete families is undecidable

Consistency of many estimators relies upon the condition of parameter identifiability (Lehmann & Casella, 2006) — two different parameter vectors should define different string distributions. But we in general cannot ascertain whether this condition holds, even for finite subsets of an EC-complete family:

Theorem 7. *Let $\boldsymbol{\Theta}$ be an EC-complete family. There is no algorithm that takes $\boldsymbol{\theta}_1 \in \boldsymbol{\Theta}$, $\boldsymbol{\theta}_2 \in \boldsymbol{\Theta}$ as input, and decides whether $\tilde{p}_{\boldsymbol{\theta}_1}$ and $\tilde{p}_{\boldsymbol{\theta}_2}$ are the same weighted language.*

6.2 Model selection is generally impossible for EC-complete sequence model families

Theorem 7 suggests that consistency guarantees of common estimators do not hold, when used to estimate parameter vectors from $\boldsymbol{\Theta}$. Nonetheless, such 'off-label' use of consistent estimators in an expressive parametric family is quite common — one usually just selects the best model $\boldsymbol{\theta}^*$

among finitely many candidates (say $\{\boldsymbol{\theta}_1 \ldots \boldsymbol{\theta}_N\}$) that achieves highest held-out likelihood: $\boldsymbol{\theta}^* = \arg\max_{\boldsymbol{\theta}_n:1 \leq n \leq N} \prod_{\boldsymbol{x} \in \mathcal{D}} p_{\boldsymbol{\theta}_n}(\boldsymbol{x})$, where $\mathcal{D}$ is a set of strings.

However, Theorem 8 implies that model selection is generally impossible for EC-complete sequence model families:

Theorem 8. *For any $\tilde{p} \in$ EC and for any EC-complete family $\boldsymbol{\Theta}$, there is no algorithm $\textsc{better}_{\tilde{p}}$ that takes two parameter vectors $\boldsymbol{\theta}_1 \in \boldsymbol{\Theta}$, $\boldsymbol{\theta}_2 \in \boldsymbol{\Theta}$, and returns YES if $\mathrm{KL}(p||p_{\boldsymbol{\theta}_1}) \geq \mathrm{KL}(p||p_{\boldsymbol{\theta}_2})$, and NO otherwise, where $p, p_{\boldsymbol{\theta}_1}, p_{\boldsymbol{\theta}_2}$ are string distributions defined by $\tilde{p}, \tilde{p}_{\boldsymbol{\theta}_1}, \tilde{p}_{\boldsymbol{\theta}_2}$ respectively.*

7 PALLIATIVE ALTERNATIVES

What is a practitioner to do, given that this class of models is unlearnable in general? We identify three palliative choices that restrict the family of EBMs. Each cripples the model $\tilde{p}$ in its own way, affording computability at the cost of expressiveness.

The choice of triage infuses the model with an inductive bias; we must tailor our models based on our prior beliefs about the problem domain. After all, while C++ is Turing-complete, programmers worldwide write C++ programs that fill their need and terminate.

Restricting support$(\tilde{p})$ **to be finite.** If $\tilde{p}$ only assigns non-zero weights to finitely many strings, then $Z_{\tilde{p}}$ is a finite sum of rational numbers, and is also rational. Here, sampling-based inference and estimation methods return to their usefulness. One way to ensure support$(\tilde{p})$ is finite is by upper-bounding the maximum string length (*e.g.*, Bakhtin et al. (2021)). An obvious downside of the finite-support restriction is that we cannot deal with longer strings.

Autoregressive parametrization of $\tilde{p}$. An alternative choice is to confine ourselves to autoregressive models, *i.e.*, locally normalized string distributions (§2.3). Under an autoregressive model p, $Z_p = 1$ by definition. We also note that any (unnormalized) distribution $\tilde{p}$ obtained by removing probability mass from p will have a *computable* partition function, as long as $\tilde{p} \in$ EC:

Theorem 9. *Let p be any LN weighted language. Any $\tilde{p} \in$ EC where $\tilde{p}(\boldsymbol{x}) \leq p(\boldsymbol{x})$ has a computable $Z_{\tilde{p}}$.*

Proof sketch. We construct an algorithm that approximates $Z_{\tilde{p}}$ to any arbitrary error level in finite time, exploiting the consistency property of p (Proposition 1). $\qquad\square$

Theorem 9 implies that conditionalization operations on p, which remove strings from the support of p to get weighted language $\tilde{p}$, result in a computable $Z_{\tilde{p}}$ (as long as we can decide which strings are removed); and such a $\tilde{p}$ is therefore not subjected to the limitations of Theorem 4.

Unlike the 'finite support' fix, an autoregressively parametrized (or subsequently conditionalized) $\tilde{p}$ can have an infinite support. A conditionalized $\tilde{p}$ can have an intractable (although computable) partition function, however; and they are still subject to the expressive limitations imposed on LN languages: namely there is an EC language whose string weight rankings cannot be honored by any of such conditionalized $\tilde{p}$ (Lin et al., 2021).

$\tilde{p}$ as low tree-width factor graph grammars. Finally, we may limit ourselves to weighted languages defined by low-treewidth factor graph grammars (Chiang & Riley, 2020). Factor graph grammars is a generalization of factor graphs, which cover many classes of graphical sequence models, such as n-gram, HMM, and whole-sentence language models (Jelinek, 1980; Kuhn et al., 1994; Rosenfeld et al., 2001), linear CRF models (Lafferty et al., 2001), and weighted FSAs in general (Dreyer & Eisner, 2009): a factor graph grammar describes a (possibly infinite) set of factor graphs, generated from a hyperedge replacement graph grammar.

Assuming that an FGG G contains at most one n-observed-node factor graph for all $n \in \mathbb{N}$, it then defines a weighted language $\tilde{p}_G(\boldsymbol{x}) = \prod_{\psi \in \Psi_{|\boldsymbol{x}|}} \psi$, where **factor** ψ is a positive function of nodes. The treewidth of an FGG $W(G)$ is the maximum number of nodes any ψ can be a function of.

If $Z_{\tilde{p}_G} \in \mathbb{R}$ exists, it can be computed exactly in $O\big(\mathrm{poly}(|G| \exp(W(G) + 1))\big)$ following Chiang & Riley (2020). Exact computation of $Z_{\tilde{p}_G}$ may be manageable as long as $W(G)$ is small, which would

allow us to exactly compute held-out data likelihood, and also train with a (marginalized) MLE objective function. However, a small $W(G)$ implies $\tilde{p}$ cannot be expressive: such a grammar cannot capture phenomena like logical coherence (Cook, 1971).

8 RELATED WORK

Turing completeness of formal languages and associated uncomputability issues emerge repeatedly in computer science. For example, Turing completeness may emerge as an unwanted side effect in programming languages, since it implies undecidability. One of the best known examples is the Turing completeness of the C++ grammar (Veldhuizen, 2003; Josh, 2013), which makes both parsing and compiling C++ programs undecidable. Similar problems exist for Java (Grigore, 2016) and Haskell with (unrestricted) instance declarations (Wansbrough, 1998). Another example is the (possibly inadvertently introduced) Turing completeness of the page fault handling mechanism on modern computer systems, which raises security concerns in the context of trusted computing (Bangert et al., 2013). In these cases, Turing completeness implies that there is no general algorithm that decides a system's behavior given its current state.

Our work is not the first to discuss the consequences of computability in machine learning: assuming we can acquire training data from an oracle, under a standard supervised learning setting it is possible (Lathrop, 1996). Ben-David et al. (2019) described a scenario where identifying a high-probability finite subset from a distribution is equivalent to proving the continuum hypothesis. Agarwal et al. (2020) extended the definition of PAC learnability (Valiant, 1984) to require computable learners. By contrast, we are focused on the computability of energy-based models for sequences, such as a language model as a component of a larger system for automatic speech recognition. Designing an appropriate, efficient loss functional is a challenge that several prior works have compared (see Appendix C).

9 CONCLUSION

Energy-based models are posed as an efficient tool for decision problems, circumventing probabilities and expensive normalization (LeCun et al., 2006). Extending this vision to generic sequence models, though, is impossible. We've shown that as energy-based sequence models become more powerful, the partition function becomes uncomputable — even when we are restricted to polytime-computable weighted languages. *A priori*, there is no way to identify the parameter settings that will have uncomputable partition functions. Exact estimates, even if randomized, are uncomputable. Asymptotic estimates, on the other hand are either useless or difficult to create. We find that learning an energy-based sequence model also requires solving HALT, despite the array of tools tailored to training EBMs.

This paper may be seen as a response to Lin et al. (2021), who posture energy-based models as a more powerful alternative to autoregressive sequence models. Autoregressive sequence models, after all, have wide adoption and empirical successes (Radford et al., 2019; Brown et al., 2020). By contrast, more general neural energy-based sequence models have not caught on. Why not, when Lin et al. (2021) state that all you lose is the ability to sample? We show that the class is too broad: unless we bound the treewidth of the associated graph, thereby eliminating Turing completeness, we substitute inefficiency (i.e., superpolynomial growth in the number of parameters) with uncomputability. Energy-based sequence models, even with polytime score functions, push us from the frying pan into the fire.

Energy-based models permit arbitrarily complex functions to parametrize themselves. This high expressivity suggests the ability to model the complex sequence phenomena with which natural language abounds. But even when scoring a string can be done efficiently, probabilistic reasoning over these models—including model combination and comparison—can be literally uncomputable. The halting problem hides like minefields in the parameter space Θ. Without somehow hampering the model by choice, it may inadvertently suffer further. This result is independent of the amount of training data.

Lin et al. (2021) raise the question, '*Are there model families that win on all fronts?*'. To this, we answer that EBMs are not such a family. In attempting to leverage expressive models, we introduce the risk of uncomputable distributions over strings.

REFERENCES

Sushant Agarwal, Nivasini Ananthakrishnan, Shai Ben-David, Tosca Lechner, and Ruth Urner. On learnability wih computable learners. In Aryeh Kontorovich and Gergely Neu (eds.), *Proceedings of the 31st International Conference on Algorithmic Learning Theory*, volume 117 of *Proceedings of Machine Learning Research*, pp. 48–60. PMLR, 08 Feb–11 Feb 2020. URL `https://proceedings.mlr.press/v117/agarwal20b.html`.

S. Arora and B. Barak. *Computational Complexity: A Modern Approach*. Cambridge University Press, 2006. ISBN 978-0-521-42426-4. URL `https://theory.cs.princeton.edu/complexity/book.pdf`.

Anton Bakhtin, Yuntian Deng, Sam Gross, Myle Ott, Marc'Aurelio Ranzato, and Arthur Szlam. Residual energy-based models for text generation. *JMLR*, 22(40):1–41, 2021. URL `http://jmlr.org/papers/v22/20-326.html`.

Julian Bangert, S. Bratus, Rebecca Shapiro, and Sean W. Smith. The page-fault weird machine: Lessons in instruction-less computation. In *WOOT*, 2013.

Shai Ben-David, Pavel Hrubeš, Shay Moran, Amir Shpilka, and Amir Yehudayoff. Learnability can be undecidable. *Nature Machine Intelligence*, 1(1):44–48, 2019.

Yoshua Bengio, Réjean Ducharme, Pascal Vincent, and Christian Janvin. A neural probabilistic language model. *J. Mach. Learn. Res.*, 3(null):1137–1155, March 2003. ISSN 1532-4435.

Andrew C. Berry. The accuracy of the Gaussian approximation to the sum of independent variates. *Transactions of the American Mathematical Society*, 49(1):122–136, 1941. ISSN 00029947. URL `http://www.jstor.org/stable/1990053`.

Satwik Bhattamishra, Arkil Patel, and Navin Goyal. On the computational power of Transformers and its implications in sequence modeling. In *Proceedings of the 24th Conference on Computational Natural Language Learning*, pp. 455–475, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.conll-1.37. URL `https://aclanthology.org/2020.conll-1.37`.

T.L. Booth and R.A. Thompson. Applying probability measures to abstract languages. *IEEE Transactions on Computers*, C-22(5):442–450, 1973. doi: 10.1109/T-C.1973.223746.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. 2020. URL `https://arxiv.org/abs/2005.14165`.

Yining Chen, Sorcha Gilroy, Andreas Maletti, Jonathan May, and Kevin Knight. Recurrent neural networks as weighted language recognizers. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pp. 2261–2271, New Orleans, Louisiana, June 2018. Association for Computational Linguistics. doi: 10.18653/v1/N18-1205. URL `https://aclanthology.org/N18-1205`.

David Chiang and Darcey Riley. Factor graph grammars. In *NeurIPS*, 2020.

Stephen A. Cook. The complexity of theorem-proving procedures. In *Proceedings of the Third Annual ACM Symposium on Theory of Computing*, STOC '71, pp. 151–158, New York, NY, USA, 1971. Association for Computing Machinery. ISBN 9781450374644. doi: 10.1145/800157.805047. URL `https://doi.org/10.1145/800157.805047`.

Arthur P Dempster, Nan M Laird, and Donald B Rubin. Maximum likelihood from incomplete data via the EM algorithm. *Journal of the Royal Statistical Society: Series B (Methodological)*, 39(1):1–22, 1977.

Markus Dreyer and Jason Eisner. Graphical models over multiple strings. In *Proceedings of the 2009 Conference on Empirical Methods in Natural Language Processing*, pp. 101–110, Singapore, August 2009. Association for Computational Linguistics. URL `https://aclanthology.org/D09-1011`.

Jason Eisner. Expectation semirings: Flexible EM for finite-state transducers. In Gertjan van Noord (ed.), *Proceedings of the ESSLLI Workshop on Finite-State Methods in Natural Language Processing (FSMNLP)*, Helsinki, August 2001. URL `http://cs.jhu.edu/~jason/papers/#eisner-2001-fsmnlp`. Extended abstract (5 pages).

Jenny Rose Finkel, Alex Kleeman, and Christopher D. Manning. Efficient, feature-based, conditional random field parsing. In *Proceedings of ACL-08: HLT*, pp. 959–967, Columbus, Ohio, June 2008. Association for Computational Linguistics. URL `https://aclanthology.org/P08-1109`.

Zoubin Ghahramani. Probabilistic machine learning and artificial intelligence. *Nature*, 521(7553): 452–459, 2015.

Radu Grigore. Java generics are turing complete. *CoRR*, abs/1605.05274, 2016. URL `http://arxiv.org/abs/1605.05274`.

Geoffrey E. Hinton. Training products of experts by minimizing contrastive divergence. *Neural Comput.*, 14(8):1771–1800, August 2002. ISSN 0899-7667. doi: 10.1162/089976602760128018. URL `https://doi.org/10.1162/089976602760128018`.

Y. Huang, A. Sethy, K. Audhkhasi, and B. Ramabhadran. Whole sentence neural language models. In *ICASSP*, April 2018. doi: 10.1109/ICASSP.2018.8461734. URL `https://ieeexplore.ieee.org/document/8461734`.

Thomas Jech. On Gödel's second incompleteness theorem. *Proceedings of the American Mathematical Society*, 121(1):311–313, 1994. doi: 10.2307/2160398.

Frederick Jelinek. Interpolated estimation of Markov source parameters from sparse data. In *Proc. Workshop on Pattern Recognition in Practice, 1980*, 1980.

Josh. Parsing c is literally undecidable, Aug 2013. URL `https://blog.reverberate.org/2013/08/parsing-c-is-literally-undecidable.html`.

S. Katz. Estimation of probabilities from sparse data for the language model component of a speech recognizer. *IEEE Transactions on Acoustics, Speech, and Signal Processing*, 35(3):400–401, 1987. doi: 10.1109/TASSP.1987.1165125.

André Kempe, Jean-Marc Champarnaud, and Jason Eisner. A note on join and auto-intersection of n-ary rational relations. In *Proc. Eindhoven FASTAR Days*, number 04-40, pp. 64–78. Citeseer, 2004.

T. Kuhn, H. Niemann, and E.G. Schukat-Talamazzini. Ergodic hidden markov models and polygrams for language modeling. In *Proceedings of ICASSP '94. IEEE International Conference on Acoustics, Speech and Signal Processing*, volume i, pp. I/357–I/360 vol.1, 1994. doi: 10.1109/ICASSP.1994.389282.

John D. Lafferty, Andrew McCallum, and Fernando Pereira. Conditional random fields: Probabilistic models for segmenting and labeling sequence data. In *ICML*, 2001.

Richard H. Lathrop. On the learnability of the uncomputable. In *ICML*, 1996.

Yann LeCun, Sumit Chopra, Raia Hadsell, Marc'Aurelio Ranzato, and Fu-Jie Huang. A tutorial on energy-based learning. In G. Bakir, T. Hofman, B. Schölkopf, A. Smola, and B. Taskar (eds.), *Predicting Structured Data*. MIT Press, 2006. URL `http://yann.lecun.com/exdb/publis/pdf/lecun-06.pdf`.

Erich L Lehmann and George Casella. *Theory of point estimation*. Springer, 2006. URL `https://link.springer.com/book/10.1007%2Fb98854`.

Chu-Cheng Lin, Aaron Jaech, Xin Li, Matthew R. Gormley, and Jason Eisner. Limitations of autoregressive models and their alternatives. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 5147–5173, Online, June 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.naacl-main.405. URL `https://aclanthology.org/2021.naacl-main.405`.

Zhuang Ma and Michael Collins. Noise contrastive estimation and negative sampling for conditional models: Consistency and statistical efficiency. In *EMNLP*, 2018. URL `https://www.aclweb.org/anthology/D18-1405.pdf`.

Tomas Mikolov, M. Karafiát, L. Burget, J. Cernocký, and S. Khudanpur. Recurrent neural network based language model. In *INTERSPEECH*, 2010.

Art B. Owen. *Monte Carlo theory, methods and examples*. 2013.

Art B. Owen and Yi Zhou. Safe and effective importance sampling. *Journal of the American Statistical Association*, 95:135–143, 2000.

Jorge Pérez, Pablo Barceló, and Javier Marinkovic. Attention is Turing-complete. *Journal of Machine Learning Research*, 22(75):1–35, 2021. URL `http://jmlr.org/papers/v22/20-302.html`.

Alec Radford, Jeff Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. 2019. URL `https://d4mucfpksywv.cloudfront.net/better-language-models/language-models.pdf`.

Ronald Rosenfeld, Stanley Chen, and Xiaojin Zhu. Whole-sentence exponential language models: A vehicle for linguistic-statistical integration. *Computer Speech & Language*, 15(1):55–73, January 2001. URL `https://doi.org/10.1006/csla.2000.0159`.

Ben Sandbank. Refining generative language models using discriminative learning. In *EMNLP*, 2008. URL `https://www.aclweb.org/anthology/D08-1006.pdf`.

H.T. Siegelmann and E.D. Sontag. On the computational power of neural nets. *Journal of Computer and System Sciences*, 50(1):132–150, 1995. ISSN 0022-0000. doi: https://doi.org/10.1006/jcss.1995.1013. URL `https://www.sciencedirect.com/science/article/pii/S0022000085710136`.

Michael Sipser. *Introduction to the Theory of Computation*. Course Technology, Boston, MA, third edition, 2013. ISBN 113318779X.

Noah A. Smith and Jason Eisner. Contrastive estimation: Training log-linear models on unlabeled data. In *Proceedings of the 43rd Annual Meeting of the Association for Computational Linguistics (ACL'05)*, pp. 354–362, Ann Arbor, Michigan, June 2005. Association for Computational Linguistics. doi: 10.3115/1219840.1219884. URL `https://aclanthology.org/P05-1044`.

Daniel W. Stroock. *An Introduction to Markov Processes*, volume 230 of *Graduate Texts in Mathematics*. Springer, Heidelberg, 2 edition, 2014. ISBN 978-3-642-40522-8. doi: 10.1007/978-3-642-40523-5.

A. M. Turing. On Computable Numbers, with an Application to the Entscheidungsproblem. *Proceedings of the London Mathematical Society*, s2–42(1):230–265, 01 1937. ISSN 0024-6115. doi: 10.1112/plms/s2-42.1.230. URL `https://doi.org/10.1112/plms/s2-42.1.230`.

L. G. Valiant. A theory of the learnable. *Commun. ACM*, 27(11):1134–1142, November 1984. ISSN 0001-0782. doi: 10.1145/1968.1972. URL `https://doi.org/10.1145/1968.1972`.

Todd L. Veldhuizen. C++ templates are Turing complete. Technical report, 2003.

Keith Wansbrough. Instance declarations are universal, 1998. URL `https://www.lochan.org/keith/publications/undec.html`.

Adam B. Yedidia and S. Aaronson. A relatively small Turing machine whose behavior is independent of set theory. *ArXiv*, abs/1605.04343, 2016.

A   Weighted Turing machines

We extend the definition of Turing machines into **weighted Turing machines** as follows. A weighted Turing machine M is described as a 7-tuple $(Q, \Sigma, \delta, q_{\text{init}}, F, \texttt{update\_num}, \texttt{update\_denom})$, where the first 5 components $(Q, \Sigma, \delta, q_{\text{init}}, F)$ have definitions following that of standard Turing machines. The last two additions are weight-update functions: both $\texttt{update\_num}$ and $\texttt{update\_denom}$ have signature $Q \to \mathcal{A}$, where $\mathcal{A} \triangleq \{\textsc{same}, \textsc{carry}\}$.

At the end of time step i, assuming the current state is q, we define

$$\text{NUM}_i = \begin{cases} \text{NUM}_{i-1} & \text{if } \texttt{update\_num}(q) = \textsc{same} \\ 2^i + \text{NUM}_{i-1} & \text{if } \texttt{update\_num}(q) = \textsc{carry} \end{cases}$$

and similarly,

$$\text{DENOM}_i = \begin{cases} \text{DENOM}_{i-1} & \text{if } \texttt{update\_denom}(q) = \textsc{same} \\ 2^i + \text{DENOM}_{i-1} & \text{if } \texttt{update\_denom}(q) = \textsc{carry}. \end{cases}$$

To keep our proof of model family capacity brief, we (arbitrarily) define that $\forall q \in F \cup \{q_{\text{init}}\}$, $\texttt{update\_num}(q) = \texttt{update\_denom}(q) = \textsc{same}$. Finally, upon arriving at a halting state $\in F$ in r time steps, we say $\text{NUM}_r/\text{DENOM}_r$ is the weight of an input $x \in \mathbb{B}^*$ under M, if $\text{NUM}_r/\text{DENOM}_r$ is a rational number.[6]

B   Proofs of Theorems from Main Text

Theorem 1. *The class of one-encoder-layer four-decoder-layer Transformer networks with positional encodings $(n, 1/n, 1/n^2, 2^n)$ is EC-complete.*

Proof. To model all weighted Turing machines defined in §2.2, we extend the Turing-complete one-encoder-layer three-decoder-layer Transformer network construction introduced by Pérez et al. (2021) with one additional layer. We also modify the original positional embedding function $\text{pos} : \mathbb{N} \to \mathbb{Q}^d$ to include a new component. In this proof, we let

$$\text{pos}(i) = [0, \ldots, 0, 1, i, 1/i, 1/i^2, 2^i]$$

instead of $\text{pos}(i) = [0, \ldots, 0, 1, i, 1/i, 1/i^2]$ as in Pérez et al. (2021).

For the sake of clarity, our construction is a 'stack-on' construction: the encoder layer and the first 3 decoder layers are largely identical to the design of Pérez et al. (2021), with the only difference being necessary changes to accommodate our one additional positional embeddings component.[7] It may be possible to strengthen our results by showing that one-encoder-layer **three**-decoder-layer Transformer networks with the original positional embeddings — the parametrization family Pérez et al. (2021) showed to be Turing-complete — are EC-complete as well, with a more involved construction. We leave such an improvement as future work.

We claim our fourth layer of the decoder has output $\boldsymbol{y}_r = \boldsymbol{y}_r' + \boldsymbol{w}_r$, where

- $\boldsymbol{y}_r'$ is a zero-padded version of the original Transformer output embeddings from Pérez et al. (2021). $\boldsymbol{y}_r'$ is of the form

$$[[\![q^r]\!], [\![s^r]\!], m^{(r-1)}, 0, \ldots, 0]$$

  where $[\![q^r]\!]$ denotes an one-hot vector of size $|Q|$ where the q^r-th component is 1 (again following the notation of Pérez et al. (2021)).

---

[6]When $\text{NUM}_r/\text{DENOM}_r$ is not a rational number (because $\text{DENOM}_r = 0$), we say the weight of input string x is undefined. However, we do not encounter that in this work: all strings in an EC language have rational weights. In any case, we only require that our family *contain* weighted Turing machines that return rational numbers, not that they be the only members.

[7]Since we increase the output embeddings' dimension by 1, we also need to pad all matrices in the original construction by additional zero columns/rows, such that our new positional embeddings' new component has no effect on any computation in the encoder layer, and the first 3 decoder layers.

- And $\boldsymbol{w}_r$ is of the form

$$[\mathbf{0}_q, \mathbf{0}_s, 0, \text{NUM}_r, \text{DENOM}_r, 0, \dots, 0] \tag{3}$$

where $\text{num}_r \in \mathbb{N} \cup \{0\}$ and $\text{DENOM}_r \in \mathbb{N} \cup \{0\}$ are defined in §2.2.

Now we describe how $\boldsymbol{w}_r$ can be computed from $[\boldsymbol{y}'_0 \dots \boldsymbol{y}'_r]$ using the attention mechanism, with the help of our new positional embeddings. Specifically, we want to show that we can construct feedforward networks Q_4, K_4, and V_4 such that

$$\boldsymbol{y}_i = \text{Att}\big(Q_4(\boldsymbol{y}''_i), K_4(\mathbf{Y}''_i), V_4(\mathbf{Y}''_i)\big)$$

where $\boldsymbol{y}''_i = \boldsymbol{y}'_i + \text{pos}(i)$, $\mathbf{Y}' = [\boldsymbol{y}'_1 \dots \boldsymbol{y}'_i]$, and $\mathbf{Y}''_i = \mathbf{Y}' + [\text{pos}(1), \dots, \text{pos}(i)]$. We let $Q_4(\boldsymbol{y}'') = [0, \dots, 0, 1, 0, 0, 0, 0]$ be a constant vector, and $K_4(\mathbf{Y}''_i) = \mathbf{Y}''_i$. Finally, we let $V_4(\mathbf{Y}''_i) = [\mathbf{0}_q, \mathbf{0}_s, 0, \mathbb{I}(\texttt{update\_num}(q^i) = \text{CARRY})2^i, \mathbb{I}(\texttt{update\_denom}(q^i) = \text{CARRY})2^i, 0, \dots, 0]$.

Q_4 is a constant function (such that it always attends to the unity component of $\mathbf{Y}''_i$), so it can be implemented as a single-layer feedforward network. K_4 is the identity function, which can also be implemented as a single-layer feedforward network. V_4 on the hand can be implemented as a fixed-size feedforward network, with the piecewise-linear sigmoidal function σ: in the case of DENOM_i, the network would first project q^i to $\boldsymbol{a} = [\mathbb{I}(\texttt{update\_denom}(q^i) = \text{CARRY}), \mathbb{I}(\texttt{update\_denom}(q^i) = \text{SAME})]$ (using the one-hot $[\![q^i]\!]$ segment from $\boldsymbol{y}'_i$), multiply it by $\boldsymbol{b} = [2^i, 0]$ (with the help of nonlinearity from σ), and put $\boldsymbol{a} \otimes \boldsymbol{b}$ at the position of DENOM_i in equation (3). The component at NUM_i in equation (3) can be computed likewise.

Given any position $r \in \mathbb{N}$, we have

$$\boldsymbol{y}_r = \text{Att}(Q_4(\boldsymbol{y}''_r), K_4(\mathbf{Y}''_r), V_4(\mathbf{Y}''_r)) = [\mathbf{0}_q,$$
$$\mathbf{0}_s,$$
$$0,$$
$$\frac{1}{r}\sum_{i=1}^{r} \mathbb{I}(\texttt{update\_num}(q^i) = \text{CARRY})2^i,$$
$$\frac{1}{r}\sum_{i=1}^{r} \mathbb{I}(\texttt{update\_denom}(q^i) = \text{CARRY})2^i,$$
$$0,$$
$$\dots,$$
$$0].$$

Let $\texttt{extract\_avg\_num}(\boldsymbol{y}_r)$ be an affine transformation that extracts the $(|Q| + |\Sigma| + 2)^{\text{nd}}$ component from $\boldsymbol{y}_r$, and $\texttt{extract\_avg\_denom}(\boldsymbol{y}_r)$ be an affine transformation that extracts the $(|Q| + |\Sigma| + 3)^{\text{rd}}$ component from $\boldsymbol{y}_r$, we have

$$\frac{\texttt{extract\_avg\_num}(\boldsymbol{y}_r)}{\texttt{extract\_avg\_denom}(\boldsymbol{y}_r)} = \frac{\sum_{i=1}^{r} \mathbb{I}(\texttt{update\_num}(q^i) = \text{CARRY})2^i}{\sum_{i=1}^{r} \mathbb{I}(\texttt{update\_denom}(q^i) = \text{CARRY})2^i}$$
$$= \frac{\text{NUM}_r}{\text{DENOM}_r}$$

which is the weight of input $\boldsymbol{x} = [x_1 \dots x_T]$ as we defined in §2.2. $\qquad\square$

Theorem 2. *Let $\boldsymbol{\Theta}$ be a parametric EC-complete sequence model family. And let $\boldsymbol{\Theta}_k \subset \boldsymbol{\Theta}$ be bijective with $\mathcal{G}_k$. There is no $k \in \mathbb{Q}_{>0}$ for which there exists an exact estimate $\hat{Z}_k$ that takes as input $\boldsymbol{\theta} \in \boldsymbol{\Theta}_k$ as input, and computes $\hat{Z}_k(\boldsymbol{\theta}) = Z_{\tilde{p}_{\boldsymbol{\theta}}}$ in finite time.*

Proof. We can reduce HALT to computing our partition function. For the sake of contradiction, let us assume that for some $k \in \mathbb{Q}_{>0}$, the exact estimate $\hat{Z}$ exists. Our reduction from HALT of input-free Turing machines is as follows: Given any deterministic input-free Turing machine M, we build a

weighted deterministic Turing machine: M' (Appendix A). M' takes as input $\boldsymbol{x} \in \mathbb{B}^*$, and outputs weight $1/3^{|\boldsymbol{x}|+1} + k$ when $\boldsymbol{x}$ is an accepting trace of M'. Otherwise, M' outputs weight $1/3^{|\boldsymbol{x}|+1}$.

M' always returns a weight for $\boldsymbol{x}$ in polytime. By the assumptions of EC-complete families (§2.4), we can build a parameter vector $\boldsymbol{\theta} \in \boldsymbol{\Theta}$ such that $\tilde{p}_{M'} = \tilde{p}_{\boldsymbol{\theta}}$. Since from the definitions of $\mathcal{G}_k$ we know $\tilde{p}_{M'} = \tilde{p}_{M,k}$, we have $\boldsymbol{\theta} \in \boldsymbol{\Theta}_k$.

We have thus completed our reduction: if $\hat{Z}_k$ existed, we could decide whether any given input-less deterministic Turing machine M halts, by first constructing the weighted Turing machine M', then the corresponding $\boldsymbol{\theta}$. By our assumption, $\hat{Z}_k(\tilde{p}_{\boldsymbol{\theta}}) = k + 1$ if and only if $\exists \boldsymbol{x} \in \mathbb{B}^*$ that is an accepting path of M', which is true if and only if M halts for some finite steps. Since whether M halts is undecidable, we have arrived at a contradiction (Turing, 1937; Sipser, 2013). Therefore for all $k \in \mathbb{Q}$, the algorithm $\hat{Z}_k$ does not exist. □

Theorem 3. *Assuming ZFC axioms and that assuming they is consistent, there exists $\tilde{b} \in \mathcal{G}_1$ such that (a) $Z_{\tilde{b}} = c \in \{1, 2\}$ exists, but (b) there is no proof of $Z_{\tilde{b}} = c$.*

Proof. Our proof hinges on Gödel's second incompleteness theorem: no consistent axiomatic system which includes Peano arithmetic (*e.g.*, ZFC) can prove its own consistency. We construct a Turing machine M_b that enumerates all provable propositions under ZF, and halts if only if M_b proves the proposition $1 = 0$. One such M_b with $7,918$ states has been built by Yedidia & Aaronson (2016).[8]

M_b is an input-free deterministic Turing machine. We construct a weighted Turing machine M' from M_b, in the manner of the proof of Theorem 2. We let M' return weight $1 + 1/3^{|\boldsymbol{x}|+1}$, in the case M_b halts with trace $\boldsymbol{x}$. M' returns a weight in polytime, and therefore defines a weighted language $\tilde{b} \in \mathcal{G}_1 \subset \text{EC}$. We know from the definitions of $\mathcal{G}_1$ that $Z_{\tilde{b}}$ is either 1 or 2.

Assume to the contrary that there exists a proof that $Z_{\tilde{b}} = 1$. Then we know M_b did not halt. And therefore the proof would also imply that ZFC is consistent, which violates Gödel's second incompleteness theorem. On the other hand, if there were a proof that $Z_{\tilde{b}} = 2$, it would imply M_b halted and ZFC is not consistent. We therefore arrive at a contradiction. □

Corollary 1. *Assuming ZFC axioms and assuming they are consistent, there exists $\boldsymbol{\theta} \in \boldsymbol{\Theta}$ such that $Z_{\tilde{p}_{\boldsymbol{\theta}}} \in \mathbb{Q}_{>0}$ exists, but there is no algorithm $\hat{Z}_{\text{proof}}$ that takes $\boldsymbol{\theta} \in \boldsymbol{\Theta}$ as input, and outputs a set of strings $\{\boldsymbol{x}_n : n < N\}, N \in \mathbb{N}$ where*

- *there is a proof that $\sum_{n=1}^{N} \tilde{p}_{\boldsymbol{\theta}}(\boldsymbol{x}) \geq 1/2 Z_{\tilde{p}_{\boldsymbol{\theta}}}$; or*
- *there is a proof that $\sum_{n=1}^{N} \tilde{p}_{\boldsymbol{\theta}}(\boldsymbol{x}) < 1/2 Z_{\tilde{p}_{\boldsymbol{\theta}}}$.*

Proof. Assuming to the contrary that $\hat{Z}_{\text{proof}}$ existed. We construct $\boldsymbol{\theta} \in \boldsymbol{\Theta}$ such that $\forall \boldsymbol{x} \in \mathbb{B}^*$, $\tilde{p}_{\boldsymbol{\theta}}(\boldsymbol{x}) = \tilde{b}(\boldsymbol{x})$. Either proof resulting from $\hat{Z}_{\text{proof}}(\boldsymbol{\theta})$: $\{\boldsymbol{x}_n : n < N\}$ can be used to prove or disprove the consistency of ZFC. □

Lemma 1. *Let $\boldsymbol{\Theta}$ be an EC-complete parametric family. There is no multiplicative factor $\epsilon \in \mathbb{Q}_{>1}$ for which every $\boldsymbol{\theta} \in \boldsymbol{\Theta}$ can have its partition function approximated with $\hat{\mathbf{Z}}_\epsilon(\boldsymbol{\theta})$ within a factor of ϵ — with probability greater than $2/3$. That is, we cannot have*

$$P\left((1/\epsilon) Z_{\tilde{p}_{\boldsymbol{\theta}}} \leq \hat{\mathbf{Z}}_\epsilon(\boldsymbol{\theta}) \leq \epsilon Z_{\tilde{p}_{\boldsymbol{\theta}}}\right) > 2/3. \tag{2}$$

Proof. In this proof, we make use of the distribution family $\mathcal{G}_{\epsilon^2}$ (§3.1). We assume to the contrary that a multiplicative bound ϵ satisfying equation 2 exists. Recall that our assumptions state that $P\left(1/\epsilon \leq \hat{\mathbf{Z}}_\epsilon(\boldsymbol{\theta})/Z_{\tilde{p}_{\boldsymbol{\theta}}} \leq \epsilon\right) > 2/3$.[9] Let M be an input-free Turing machine. And let $\tilde{p}_{\boldsymbol{\theta}} = \tilde{p}_{M,\epsilon^2} \in \mathcal{G}_{\epsilon^2}$ where $\boldsymbol{\theta} \in \boldsymbol{\Theta}$. if a Turing machine M halts, $Z_{\tilde{p}_{M,\epsilon^2}} = 1 + \epsilon^2$; therefore, $P\left((1 + \epsilon^2)1/\epsilon \leq \hat{\mathbf{Z}}_\epsilon(\boldsymbol{\theta}) \leq (1 + \epsilon^2)\epsilon\right) > 2/3$. Similarly, if M does not halt, we have $Z_{\tilde{p}_{M,\epsilon^2}} = 1$;

---

[8]Subsequent efforts have led to a construction of M_b with 748 states: https://turingmachinesimulator.com/shared/vgimygpuwi.

[9]As is common, e.g., in defining the complexity class BPP (see Arora & Barak 2006), the fraction $2/3$ is arbitrary. Any proportion bounded away from $1/2$ will work.

therefore, $P\left(\frac{1}{\epsilon} \leq \hat{\mathbf{Z}}_\epsilon(\boldsymbol{\theta}) \leq \epsilon\right) > \frac{2}{3}$. By combining the two conditions, we know that $\mathbb{I}(M \text{ halts}) = \mathbb{I}(\hat{\mathbf{Z}}_\epsilon(\boldsymbol{\theta}) \geq \epsilon + \frac{1}{\epsilon} \wedge \hat{\mathbf{Z}}_\epsilon(\boldsymbol{\theta}) > \epsilon) = \mathbb{I}(\hat{\mathbf{Z}}_\epsilon(\boldsymbol{\theta}) \geq \epsilon + \frac{1}{\epsilon})$.

Therefore, given $(\frac{1}{\epsilon}) Z_{\tilde{p}_{\boldsymbol{\theta}}} \leq \hat{\mathbf{Z}}_\epsilon(\boldsymbol{\theta}) \leq \epsilon Z_{\tilde{p}_{\boldsymbol{\theta}}}$, we can decide if M halts by checking if $\hat{\mathbf{Z}}_\epsilon(\boldsymbol{\theta}) \geq \epsilon + \frac{1}{\epsilon}$. Since the condition $(\frac{1}{\epsilon}) Z_{\tilde{p}_{\boldsymbol{\theta}}} \leq \hat{\mathbf{Z}}_\epsilon(\boldsymbol{\theta}) \leq \epsilon Z_{\tilde{p}_{\boldsymbol{\theta}}}$ only holds $\frac{2}{3}$ of all time, we then derandomize the randomized $\hat{\mathbf{Z}}_\epsilon$ to get a deterministic estimate: recall that a randomized exact estimate finishes computation in finite time, regardless of the content of the random tape τ. There, there are only finitely many finitely long possible 'random' sequences that $\hat{Z}_\epsilon$ will read, which we can enumerate. More concretely:

$$\begin{aligned} P\big(\hat{\mathbf{Z}}_\epsilon(\boldsymbol{\theta}) \geq \epsilon + \frac{1}{\epsilon}\big) &= \mathbb{E}_\tau \left[\mathbb{I}(\hat{Z}_\epsilon(\boldsymbol{\theta}, \tau) \geq \epsilon + \frac{1}{\epsilon}) \right] \\ &= \sum_{\tau \in \mathbb{B}^{m_{\boldsymbol{\theta}, \epsilon}}} \frac{1}{2^{m_{\boldsymbol{\theta}, \epsilon}}} \mathbb{I}(\hat{Z}_\epsilon(\boldsymbol{\theta}, \tau) \geq \epsilon + \frac{1}{\epsilon}) \end{aligned} \qquad (4)$$

where $m_{\boldsymbol{\theta}, \epsilon} \in \mathbb{N}$ is the maximum prefix length of the random tape that $\hat{Z}_\epsilon(\boldsymbol{\theta}, \tau)$ will use on any $\tau \in \mathbb{B}^{\mathbb{N}}$. Again $m_{\boldsymbol{\theta}, \epsilon}$ is guaranteed to exist because of our assumption $\hat{Z}_\epsilon(\boldsymbol{\theta}, \tau)$ ends in finite time. Since equation (4) is a finite sum of computable functions, it is also computable.

From the computability of equation (4), it follows that we can derive a deterministic algorithm from $\hat{\mathbf{Z}}_\epsilon$ that decides whether an arbitrary input-free Turing machine halts, which is not possible. Therefore, there is no $\epsilon \in \mathbb{Q}_{>1}$, such that the randomized exact estimate $\hat{\mathbf{Z}}_\epsilon$ satisfies the multiplicative bound $P(\frac{1}{\epsilon} \leq \hat{\mathbf{Z}}_\epsilon(G)/Z \leq \epsilon) > \frac{2}{3}$ for all $\boldsymbol{\theta} \in \boldsymbol{\Theta}$. $\qquad \square$

To show this contradiction, we invoke the Berry–Esseen theorem (Berry, 1941, *inter alia*), a tighter version of the central limit theorem. It specifies not simply the *fact* of the sample mean's convergence to a normal distribution, but also the *rate* of this convergence. As the rate is measured in terms of the third absolute moment, let us first show a lemma that key estimands of the distribution are computable in finite time. Every randomized exact estimate $\mathbf{f}$ is guaranteed to have a finite and computable variance, and it will also have a finite and computable third absolute moment. More formally, the lemma is:

Lemma 2. *Let $\mathbf{f}(\boldsymbol{\theta})$ be a randomized exact estimate (§2.5). These three quantities are finite and computable:*

- *The mean $\mu = \mathbb{E}_\tau[\mathbf{f}(\boldsymbol{\theta})]$,*
- *The variance $\sigma^2 = \mathbb{E}_\tau[(\mathbf{f}(\boldsymbol{\theta}) - \mathbb{E}_\tau[\mathbf{f}(\boldsymbol{\theta})])^2]$, and*
- *The third absolute moment $\beta_3 = \mathbb{E}_\tau[|\mathbf{f}(\boldsymbol{\theta}) - \mathbb{E}_\tau[\mathbf{f}(\boldsymbol{\theta})]|^3]$.*

Proof. Similar to the proof of Lemma 1, the key idea of this proof is that while the set of all random tapes $\mathbb{B}^{\mathbb{N}}$ is uncountably infinite (as can be seen from Cantor's diagonalization argument), the randomized Turing machine behind $\mathbf{f}$: $f(\boldsymbol{\theta}, \tau)$ can only make use of some finite-length prefix of τ, which implies that both the variance and third absolute moment can be computed as a finite sum of rational numbers. We show our result for the mean; we omit the similar proofs for the variance and third absolute moment.

Observe that the mean adds up finitely many rational terms:

$$\mathbb{E}_\tau\left[\mathbf{f}(\boldsymbol{\theta})\right] = \mathbb{E}_{\tau \in \mathbb{B}^{\mathbb{N}}}\left[f(\boldsymbol{\theta}, \tau)\right] = \sum_{\tau \in \mathbb{B}^m} \frac{1}{2^m} f(\boldsymbol{\theta}, \tau) \in \mathbb{Q},$$

where m is the (finite) greatest length of random tape used by f. The finite-time assumption requires that this greatest length must exist.

We can therefore compute the mean $\mathbb{E}_\tau[\mathbf{f}]$ by the following algorithm:

1. First, determine m by trying all possible maximum lengths. For each $i \in \mathbb{N}$ beginning from $i = 1$, we attempt to simulate $f(\boldsymbol{\theta}, \tau)$ on every *finite* 'random tape' $\tau \in \mathbb{B}^i$. If the probabilistic Turing machine computing $f(\boldsymbol{\theta}, \tau)$ moves beyond position i on τ, then we know that $m > i$. We terminate this simulation, then increment our counter $i \leftarrow i + 1$ and attempt simulation again. Otherwise, we terminate with the conclusion that $m = i$.
2. Having computed the maximum length m in the previous step, we can compute the finite summation $\sum_{\tau \in \mathbb{B}^m} \frac{1}{2^m} f(\boldsymbol{\theta}, \tau)$ in finite time.

This algorithm constructively completes the proof: the mean is computable in finite time. $\quad\square$

Theorem 4. *Let* Θ *be an* EC-*complete parametric family. There is no multiplicative bound* $\epsilon \in \mathbb{Q}_{>1}$ *such that there exists a randomized exact estimate* $\hat{\mathbf{Z}}_\epsilon$ *that guarantees* $1/\epsilon \le \mathbb{E}[\hat{\mathbf{Z}}_\epsilon(\theta)]/Z_{\tilde{p}_\theta} \le \epsilon$*, for every* $\theta \in \Theta$ *where* $\tilde{p}_\theta$ *is normalizable.*

Proof. We will show by contradiction that if the bound ϵ were to exist, then we could solve the halting problem by a derandomization procedure similar to that in Lemma 1. For the sake of contradiction, assume that some multiplicative factor $\epsilon \in \mathbb{Q}_{>1}$ admits a randomized exact estimate $\hat{\mathbf{Z}}_\epsilon$, where for every normalizable $\theta \in \Theta$, we can bound the relative error of $\hat{\mathbf{Z}}_\epsilon$:

$$\frac{1}{\epsilon} \le \frac{\mathbb{E}[\hat{\mathbf{Z}}_\epsilon(\theta)]}{Z_{\tilde{p}_\theta}} \le \epsilon.$$

We again make use of the distribution family $\mathcal{G}_{\epsilon^2}$ (§3.1). Let Θ_{ϵ^2} be the bijection from $\mathcal{G}_{\epsilon^2}$ onto Θ. If such a factor ϵ exists, then from our multiplicative bound assumption, we know for any $\tilde{p}_{M,\epsilon^2} \in \mathcal{G}_\epsilon$ and its corresponding parametric model $\tilde{p}_\theta$, the behavior of the expected value depending on whether M halts: if yes, then $(1 + \epsilon^2)1/\epsilon \le \mathbb{E}\left[\hat{\mathbf{Z}}_\epsilon(\theta)\right] \le (1 + \epsilon^2)\epsilon$; meanwhile if no, then $1/\epsilon \le \mathbb{E}\left[\hat{\mathbf{Z}}_\epsilon(\theta)\right] \le \epsilon$. In either case, for any $Z' \in (\mathbb{E}[\hat{\mathbf{Z}}_\epsilon(\theta)] - 1/\epsilon, \mathbb{E}[\hat{\mathbf{Z}}_\epsilon(\theta)] + 1/\epsilon)$, deciding whether $Z' > 1/\epsilon$ is equivalent to deciding whether M halts:

$$\mathbb{I}(Z' > 1/\epsilon) = \mathbb{I}(M \text{ halts}). \tag{5}$$

We can now construct an estimate of the partition function from finite samples. Let $\hat{\mathbf{Z}}'_{\epsilon,N}(\theta) \triangleq \sum_{i=1}^N \hat{\mathbf{Z}}_\epsilon^{(i)}(\theta)/N$ be the sample mean of $\hat{Z}_\epsilon(\theta, \tau)$ over N i.i.d. random tapes τ_i. Because $\hat{Z}_\epsilon(\theta, \tau)$ can be computed in finite time, the mean can be computed by simulating the N independent runs of $\hat{Z}_\epsilon(\theta, \tau_i)$ on a single random tape τ.

A well-known result is that the sample mean $\hat{\mathbf{Z}}'_{\epsilon,N}(\theta)$ is an unbiased estimator of the population mean: $\mathbb{E}[\hat{\mathbf{Z}}'_{\epsilon,N}(\theta)] = \hat{\mathbf{Z}}_\epsilon(\theta)$, regardless of the number of samples N. We will use this as the mean in the next paragraph.

From Lemma 2, we know that both the variance σ^2 and the third absolute moment β_3 of $\hat{\mathbf{Z}}_{\epsilon,N}(\theta)$ are positive and rational. We can now invoke the Berry–Esseen theorem to provide bounds on our randomized exact estimate. Taking F as the cumulative distribution function of the zero-centered variable $\frac{\hat{\mathbf{Z}}'_{\epsilon,N}(\theta)\sqrt{N}-\mathbb{E}[\hat{\mathbf{Z}}'_{\epsilon,N}(\theta)]}{\sigma}$, we have:

$$\sup_{z\in\mathbb{R}} |F(z) - \Phi(z)| \le K\frac{\beta_3}{\sigma^3\sqrt{N}}, \tag{6}$$

where K is a constant whose value is known to be less than 0.8 and Φ is the standard normal CDF. Intuitively, equation (6) claims that as N approaches infinity, the distribution of the sample mean $\hat{\mathbf{Z}}'_{\epsilon,N}(\theta)$ approaches a Gaussian centered at the true value $\mathbb{E}[\hat{\mathbf{Z}}'_{\epsilon,N}(\theta)] = \mathbb{E}[\hat{\mathbf{Z}}_\epsilon(\theta)]$ with variance σ^2/N. The error in this approximation to the CDF is bounded below $O(1/\sqrt{N})$.

This result can help us reason about the counterexample distributions in $\mathcal{G}_{\epsilon^2}$. For every counterexample distribution $\tilde{p} \in \mathcal{G}_{\epsilon^2}$, and its corresponding parameter vector $\theta \in \Theta_{\epsilon^2}$, there are a minimum number of samples $N_{\tilde{p}}$ and a positive factor $\lambda_{\tilde{p}}$ such that for samples with at least $N_{\tilde{p}}$ elements, the interval $\mu \pm \nu$ is contained within the interval $\mathbb{E}[\hat{\mathbf{Z}}_\epsilon(\theta)] \pm 1/2\epsilon$, where $\mu \triangleq \hat{\mathbf{Z}}'_{\epsilon,N_{\tilde{p}}}(\theta)$, and $\nu \triangleq \lambda_{\tilde{p}} \cdot \sigma/\sqrt{N}$. This in turn means that $P(\mathbb{E}[\hat{\mathbf{Z}}_\epsilon(\theta)] - 1/2\epsilon \le \hat{\mathbf{Z}}'_{\epsilon,N_{\tilde{p}}}(\theta) \le \mathbb{E}[\hat{\mathbf{Z}}_\epsilon(\theta)] + 1/2\epsilon) > 2/3$. Since $\mathbb{I}(\hat{\mathbf{Z}}'_{\epsilon,N_{\tilde{p}}}(\theta) > 1/\epsilon) = \mathbb{I}(M \text{ halts})$ by equation (5), We therefore have a randomized exact estimate $\mathbb{I}(\hat{\mathbf{Z}}'_{\epsilon,N_{\tilde{p}}}(\theta) > 1/\epsilon)$ that is correct with probability $> 2/3$. But this is impossible: by a derandomization method similar to that in the proof of Lemma 1, we would have a deterministic algorithm that takes as input an arbitrary input-free Turing machine M, builds both $\tilde{p}_{M,\epsilon^2} \in \mathcal{G}_{\epsilon^2}$ and then $\theta \in \Theta_{\epsilon^2}$, and finally uses θ to decide whether M halts. Therefore, our assumption must be wrong: no value of $\epsilon \in \mathbf{Q}_{>1}$ can bound the error of $\hat{\mathbf{Z}}_\epsilon$. $\quad\square$

Theorem 5. *Using ZFC as our axiom set and assuming they are consistent, then there exists a normalizable EC weighted language $\tilde{p}$, where there does not exist a consistent locally normalized proposal distribution $q \in$ LN, and $c_q \in \mathbb{Q}_{>0}$, such that it can be proven $\forall x \in \mathbb{B}^*$, $\tilde{p}(x)/q(x) < c_q \neq \infty$.*

Proof. By contradiction; let $\tilde{p} = \tilde{b}$, where $\tilde{b}$ is first introduced in §3.2. Assume that there exists $q \in$ LN where it is proven that $\forall x \in \mathbb{B}^*$, $\tilde{p}(x)/q(x) < c < \infty$, where $c \in \mathbb{Q}_{>0}$.

We can either prove ZFC is consistent, or is inconsistent, as follows:

1. By our assumptions, $q \in$ LN scores every string x as $q_\theta(x) f(\theta) \in \mathbb{Q}_{>0}$. Also, because q is consistent and locally normalized, there exists $n \in \mathbb{N}$ such that we can prove $\forall x \in \mathcal{X}_{>n}\{x : x \in \mathbb{B}^*, |x| > n\}$, $q(x) < 1/c$ (Proposition 1). We will just prove the existence of n constructively by enumerating the strings in $\mathbb{B}^*$ in increasing length. Let the complement set $\mathcal{X}_{\leq n} = \mathbb{B}^* - \mathcal{X}_{>n}$.
2. The proof then examines the finitely many strings in $\mathcal{X}_{\leq n}$.
   (a) If any of these strings x' has $\tilde{b}(x') > 1$, then we know x' encodes an accepting trace of M_b (§3.2). Therefore, M_b halts, which implies there is a proof of the inconsistency of ZFC.
   (b) If none of these strings $\in \mathcal{X}_{\leq n}$ has $\tilde{b}(x) > 1$, then we know there is also no string $x'' \in \mathcal{X}_{>n}$, such that $\tilde{b}(x'') > 1$. This is because of our assumption $c \geq \tilde{b}(x)/q(x)$, which in turn means that $\tilde{b}(x)$ is less than 1 on these long strings $\mathcal{X}_{>n}$. Therefore, M_b does not halt, which implies there is a proof of the consistency of ZFC.

Assuming ZFC is consistent, neither a proof of ZFC, or a disproof of ZFC, is possible. We have therefore therefore arrived at a contradiction. Therefore, q does not exist. □

Theorem 6. *Let Θ be an EC-complete parametric family. Assuming ZFC axioms and assuming they are consistent, there exists $\theta \in \Theta$ where there does not exist a consistent locally normalized "proposal" distribution $q \in$ LN such that it can be proven $\mathrm{Var}_q\left(\hat{\mathbf{Z}}_{\theta,N}^q\right) < c \neq \infty$, where $c \in \mathbb{Q}_{>0}$.*

Proof. let $\tilde{p} = \tilde{b}$, where $\tilde{b}$ is first introduced in §3.2. Assume that there exists $q \in$ LN where it is proven that $\mathrm{Var}_q(\hat{\mathbf{Z}}_{\theta,N}^q) = k < c \in \mathbb{Q}_{<0} \neq \infty$.

We have

$$\mathrm{Var}_q(\hat{\mathbf{Z}}_{\theta,N}^q)$$
$$\triangleq \frac{1}{N}\left\{\sum_{x \in \mathbb{B}^*}\left[\left(\frac{\tilde{p}_\theta(x)}{q(x)}\right)^2 q(x)\right] - Z_{\tilde{p}_\theta}\right\}$$
$$= Z_{\tilde{p}_\theta}^2/N\left(\sum_{x \in \mathbb{B}^*}\frac{p_\theta^2(x)}{q(x)} - 1\right)$$
$$= k,$$

where $p_\theta(x) \triangleq \frac{\tilde{p}_\theta(x)}{Z_{\tilde{p}_\theta}}$. After some manipulation, we have

$$\sum_{x \in \mathbb{B}^*}\frac{p_\theta^2(x)}{q(x)} = \underbrace{\frac{Nk + Z_{\tilde{p}_\theta}^2}{Z_{\tilde{p}_\theta}^2}}_{=s \leq Nk+1}.$$

Since $\forall x \in \mathbb{B}^*$, $\frac{p_\theta^2(x)}{q(x)} \geq 0$, we have

$$\forall x \in \mathbb{B}^*, \frac{p_\theta^2(x)}{q(x)} \leq s; \tag{7}$$

in particular, if x' encodes a halting trace of M_b, from §3.1 we know

$$p_\theta(x) = \frac{\tilde{p}_\theta(x)}{Z_{\tilde{p}_\theta}}$$
$$= \frac{1 + (\frac{1}{3})^{|x|+1}}{2}$$
$$> 1/2. \tag{8}$$

Combining equations (7) and (8), we have for any accepting trace $\boldsymbol{x}'$ of M_b,

$$\frac{1}{4q(\boldsymbol{x}')} < \frac{p_{\boldsymbol{\theta}}^2(\boldsymbol{x})}{q(\boldsymbol{x})} \le s.$$

After some more arrangement, we have for any accepting trace $\boldsymbol{x}'$ of M_b,

$$q(\boldsymbol{x}') \ge {}^1\!/\!{}_{4s} \ge \frac{1}{4(Nk+1)} \ge \frac{1}{4(Nc+1)} > 0$$

for any halting trace $\boldsymbol{x}'$ of M_b.

As in the proof of Theorem 5, the existence of such a q allows us to either prove or disprove the consistency of ZFC. For the sake of completeness, we include a proof sketch below:

1. By our assumptions, $q \in \text{LN}$ scores every string $\boldsymbol{x}$ as $q_{\boldsymbol{\theta}}(\boldsymbol{x}) f(\boldsymbol{\theta}) \in \mathbb{Q}_{>0}$. Also, because q is consistent and locally normalized, there exists $n \in \mathbb{N}$ such that we can prove $\forall \boldsymbol{x} \in \mathcal{X}_{>n}\{\boldsymbol{x} : \boldsymbol{x} \in \mathbb{B}^*, |\boldsymbol{x}| > n\}, q(\boldsymbol{x}) < \frac{1}{4(Nc+1)}$ (Proposition 1). We will just prove the existence of n constructively by enumerating the strings in $\mathbb{B}^*$ in increasing length. Let the complement set $\mathcal{X}_{\le n} = \mathbb{B}^* - \mathcal{X}_{>n}$.
2. The proof then examines the finitely many strings in $\mathcal{X}_{\le n}$.
   (a) If any of these strings $\boldsymbol{x}'$ has $\tilde{p}_{\boldsymbol{\theta}}(\boldsymbol{x}') > 1$, then we know $\boldsymbol{x}'$ encodes an accepting trace of M_b (§3.2). Therefore, M_b halts, which implies there is a proof of the inconsistency of ZFC.
   (b) If none of these strings $\in \mathcal{X}_{\le n}$ has $\tilde{p}_{\boldsymbol{\theta}}(\boldsymbol{x}) > 1$, then we know there is also no string $\boldsymbol{x}'' \in \mathcal{X}_{>n}$, such that $\tilde{p}_{\boldsymbol{\theta}}(\boldsymbol{x}'') > 1$, since $\tilde{p}_{\boldsymbol{\theta}}(\boldsymbol{x}') > 1 \iff \tilde{b}(\boldsymbol{x}') > 1 \iff M_b$ halts; and we have already shown that for any accepting trace $\boldsymbol{x}'$ of M_b, $q(\boldsymbol{x}') \ge {}^1\!/\!{}_{4(Nc+1)}$. Therefore, M_b does not halt, which implies there is a proof of the consistency of ZFC.

Assuming ZFC is consistent, neither a proof of ZFC, or a disproof of ZFC, is possible. We have therefore therefore arrived at a contradiction. Therefore, such a q does not exist. □

Theorem 7. *Let $\boldsymbol{\Theta}$ be an EC-complete family. There is no algorithm that takes $\boldsymbol{\theta}_1 \in \boldsymbol{\Theta}$, $\boldsymbol{\theta}_2 \in \boldsymbol{\Theta}$ as input, and decides whether $\tilde{p}_{\boldsymbol{\theta}_1}$ and $\tilde{p}_{\boldsymbol{\theta}_2}$ are the same weighted language.*

Proof. Assuming to the contrary that such an algorithm DISTINCT exists. We would be able to reduce HALT of input-free Turing machines to DISTINCT: we first construct $\boldsymbol{\theta}_1 \in \boldsymbol{\Theta}$ such that $\tilde{p}_{\boldsymbol{\theta}_1}(\boldsymbol{x}) = {}^1\!/\!{}_3{}^{|\boldsymbol{x}|+1}$. We then construct $\boldsymbol{\theta}_2 \in \boldsymbol{\Theta}$ such that $\tilde{p}_{\boldsymbol{\theta}_2} = \tilde{p}_{M,1} \in \mathcal{G}_1$ (§3.1). DISTINCT$(\boldsymbol{\theta}_1, \boldsymbol{\theta}_2)$ is YES if and only if M halts. □

Theorem 8. *For any $\tilde{p} \in \text{EC}$ and for any EC-complete family $\boldsymbol{\Theta}$, there is no algorithm BETTER$_{\tilde{p}}$ that takes two parameter vectors $\boldsymbol{\theta}_1 \in \boldsymbol{\Theta}$, $\boldsymbol{\theta}_2 \in \boldsymbol{\Theta}$, and returns YES if $\text{KL}(p\|p_{\boldsymbol{\theta}_1}) \ge \text{KL}(p\|p_{\boldsymbol{\theta}_2})$, and NO otherwise, where $p, p_{\boldsymbol{\theta}_1}, p_{\boldsymbol{\theta}_2}$ are string distributions defined by $\tilde{p}, \tilde{p}_{\boldsymbol{\theta}_1}, \tilde{p}_{\boldsymbol{\theta}_2}$ respectively.*

Proof. By contradiction; assume that for some $\tilde{p} \in \text{EC}$, BETTER$_{\tilde{p}}$ exists. We know there exists a weighted Turing machine (also denoted as $\tilde{p}$) that on any string $\boldsymbol{x}$, terminates in $O(\text{poly}(|\boldsymbol{x}|))$ and outputs $\tilde{p}(\boldsymbol{x})$ (Appendix A).

We show how we can reduce from HALT to BETTER$_{\tilde{p}}$. Given any arbitrary input-less Turing machine M, we can define a new weighted Turing machine $\tilde{p}'_M$ that on input string $\boldsymbol{x}$, $\tilde{p}'$ first simulates $\tilde{p}$ on it and keeps a record of $\tilde{p}(\boldsymbol{x})$ somewhere on the tape. $\tilde{p}'$ then verifies whether $\boldsymbol{x}$ is an encoded accepting trace of M. If $\boldsymbol{x}$ is indeed an encoded accepted trace of M, $\tilde{p}'$ outputs $\tilde{p}(\boldsymbol{x}) + 1$. Otherwise $\tilde{p}'$ outputs $\tilde{p}(\boldsymbol{x})$.

Let $\boldsymbol{\theta}_1 \in \boldsymbol{\Theta}$ parametrize $\tilde{p}'$, and let $\boldsymbol{\theta}_2 \in \boldsymbol{\Theta}$ parametrize $\tilde{p}$, such that $\tilde{p}_{\boldsymbol{\theta}_1}(\boldsymbol{x}) = \tilde{p}'(\boldsymbol{x}), \tilde{p}_{\boldsymbol{\theta}_2}(\boldsymbol{x}) = \tilde{p}(\boldsymbol{x}), \forall \boldsymbol{x} \in \mathbb{B}^*$.

We know that $\text{KL}(p\|p) = 0$ for any distribution p. BETTER$_{\tilde{p}}(\boldsymbol{\theta}_1, \boldsymbol{\theta}_2)$ returns YES if and only if $\text{KL}(p\|p_{\boldsymbol{\theta}_1}) = 0 \ge \text{KL}(p\|p_{\boldsymbol{\theta}_2})$, which implies that $\tilde{p}_{\boldsymbol{\theta}_2}$ and $\tilde{p}_{\boldsymbol{\theta}_1}$ define the same distribution, which in turn implies that $\forall \boldsymbol{x} \in \mathbb{B}^*, \tilde{p}(\boldsymbol{x}) = \tilde{p}'(\boldsymbol{x})$, and that M never halts. Similarly, BETTER$_{\tilde{p}}(\boldsymbol{\theta}_1, \boldsymbol{\theta}_2)$ returns NO if and only if M halts. We have thus completed our reduction from HALT; and therefore algorithm BETTER$_{\tilde{p}}$ does not exist for all $\tilde{p} \in \text{EC}$. □

Theorem 9. *Let p be any LN weighted language. Any $\tilde{p} \in \text{EC}$ where $\tilde{p}(\boldsymbol{x}) \le p(\boldsymbol{x})$ has a computable $Z_{\tilde{p}}$.*

Proof. We prove Theorem 9 by constructing an algorithm $\hat{Z}_{\tilde{p}} : \mathbb{Q}_{>0} \to \mathbb{Q}_{>0}$ that approximates $Z_{\tilde{p}}$ within any desired positive rational error ϵ: namely $|\hat{Z}_{\tilde{p}}(\epsilon) - Z_{\tilde{p}}| \le \epsilon$.

Let $\hat{Z}_n = \sum_{\ell=1}^n \sum_{\boldsymbol{x}:|\boldsymbol{x}|=\ell} p(\boldsymbol{x})$. We first observe that $\lim_{n\to\infty} Z_n = 1$ by Proposition 1. In other words, $\lim_{n\to\infty} 1 - \hat{Z}_n = 0$, or equivalently, given any $\epsilon > 0$, there exists $n \in \mathbb{N}$ such that for all $n' > n, n' \in \mathbb{N}$, $(1 - \hat{Z}_{n'}) < \epsilon$.

Therefore, given any $\epsilon > 0$, $\exists n \in \mathbb{N}$ that divides $\mathbb{B}^*$ in two sets: $\mathcal{X}_{\ge n} = \{\boldsymbol{x} : \boldsymbol{x} \in \mathbb{B}^*, |\boldsymbol{x}| \ge n\}$, where $\sum_{\boldsymbol{x} \in \mathcal{X}_{\ge n}} p(\boldsymbol{x}) < \epsilon$, and $\mathcal{X}_{<n} = \mathbb{B}^* - \mathcal{X}_{\ge n}$. We are guaranteed to find n by enumerating all candidates from $\mathbb{N}$.

We can thus implement $\hat{Z}_{\tilde{p}}$ as the following program: given $\epsilon \in \mathbb{Q}_{>0}$, we first find the smallest $n \in \mathbb{N}$, and partition $\mathbb{B}^*$ into two sets $\mathcal{X}_{<n}, \mathcal{X}_{\ge n}$ as we described in the previous paragraph. We then return $\hat{Z}_{\tilde{p}}(\epsilon) = \sum_{\boldsymbol{x} \in \mathcal{X}_{<n}} \tilde{p}(\boldsymbol{x})$.

We argue that $\hat{Z}_{\tilde{p}}$ is a computable function. We first repeat that since $n \in \mathbb{N}$ exists, we will find n in finite time, simply by enumerating. And since the set $\mathcal{X}_{<n} \subset \mathbb{B}^*$ is finite, $\hat{Z}_{\tilde{p}}(\epsilon) = \sum_{\boldsymbol{x} \in \mathcal{X}_{<n}} \tilde{p}(\boldsymbol{x})$ can computed in finite time (under our assumption $p' \in \text{EC}$, $\forall \boldsymbol{x} \in \mathbb{B}^*$, $\tilde{p}(\boldsymbol{x})$ can be computed in time $O(\text{poly}(|\boldsymbol{x}|))$). Since the program we described above terminates in finite time, $\hat{Z}_{\tilde{p}}$ is a computable function.

We then argue $|\hat{Z}_{\tilde{p}}(\epsilon) - Z_{\tilde{p}}| \le \epsilon$. Assuming to the contrary that $|\hat{Z}_{\tilde{p}}(\epsilon) - Z_{\tilde{p}}| > \epsilon$, we have $Z_{\tilde{p}} > \epsilon + \hat{Z}_{\tilde{p}}(\epsilon)$, since $\hat{Z}_{\tilde{p}}(\epsilon) \le Z_{\tilde{p}}$. The inequality can further be rewritten as $Z_{\tilde{p}} = \sum_{\boldsymbol{x} \in \mathcal{X}_{\ge n}} \tilde{p}(\boldsymbol{x}) + \sum_{\boldsymbol{x} \in \mathcal{X}_{<n}} \tilde{p}(\boldsymbol{x}) > \epsilon + \hat{Z}_{\tilde{p}}(\epsilon)$. Since $\hat{Z}_{\tilde{p}}(\epsilon) = \sum_{\boldsymbol{x} \in \mathcal{X}_{<n}} \tilde{p}(\boldsymbol{x})$, we arrive at $\sum_{\boldsymbol{x} \in \mathcal{X}_{\ge n}} \tilde{p}(\boldsymbol{x}) > \epsilon$. But we already know $\epsilon > \sum_{\boldsymbol{x} \in \mathcal{X}_{\ge n}} p(\boldsymbol{x}) \ge \sum_{\boldsymbol{x} \in \mathcal{X}_{\ge n}} p(\boldsymbol{x}) \ge \sum_{\boldsymbol{x} \in \mathcal{X}_{\ge n}} \tilde{p}(\boldsymbol{x})$, arriving at a contradiction. Therefore $|\hat{Z}_{\tilde{p}}(\epsilon) - Z_{\tilde{p}}| \le \epsilon$. $\square$

C COMMON TRAINING STRATEGIES FOR EBMS AND THEIR DEFICIENCIES FOR SEQUENCE MODELS

With the plethora of learning strategies for EBMs, it is untenable to point out the deficiency in each. Table C.1 gives a handful of examples; none share the four properties we desire:

1. Global normalization (without which the model would be in LN)
2. Support over infinite languages (of finite strings)
3. Unbounded treewidth in the function assigning weights to strings
4. Estimator consistency (*i.e.*, asymptotic guarantee to recover the true parameters).

Technique	Energy-based (i.e., globally normalized)	Infinite language support	Scoring function has unbounded treewidth	Consistency
Noise-contrastive estimation (Ma & Collins (2018); used in Lin et al. (2021); Bakhtin et al. (2021))	✓	✗	✓	✓
MLE with variable elimination in factor graph grammars (Chiang & Riley (2020); used in Eisner (2001); Finkel et al. (2008) *inter alia*)	✓	✓	✗	✓
MLE with autoregressive parametrization (Mikolov et al., 2010)	✗	✓	✓	✓
Contrastive divergence (Hinton, 2002)	✓	✓	✓	✗
Contrastive estimation (Smith & Eisner, 2005)	✓	✓	✓	✗

Table C.1: Deficiencies of some common alternatives to overly expressive EBMs.