DEEP AUTOAUGMENT

ABSTRACT

While recent automated data augmentation works lead to state-of-the-art results, their design spaces and the derived data augmentation strategies still incorporate strong human priors. In this work, instead of selecting a set of hand-picked default augmentations alongside the searched data augmentations, we propose a fully automated approach for data augmentation search called **Deep AutoAugment** (DeepAA). DeepAA progressively builds a multi-layer data augmentation pipeline from scratch by adding augmentation layers one at a time until reaching convergence. For each augmentation layer, the policy is optimized to maximize the cosine similarity between the gradients of the original and augmented data.Our experiments show that DeepAA improves significantly over previous state-of-the-art automated data augmentation methods. On CIFAR-10 and CIFAR-100, we achieve accuracies of 97.56% and 84.02% with Wide-ResNet-28-10 which are 0.1% and 0.5% better than the previous state-of-the-art. On ImageNet, we achieve an accuracy of 78.3% with ResNet-50 which is 0.7% higher than the previous best method.

1 INTRODUCTION

State-of-the-art results in image classification rely on data augmentation (DA) since it effectively regularizes the model by increasing the number and the diversity of data points (Goodfellow et al., 2016; Zhang et al., 2017). A large body of data augmentation transformations has been proposed (Inoue, 2018; Zhang et al., 2018; DeVries & Taylor, 2017; Yun et al., 2019; Hendrycks et al., 2020; Yan et al., 2020) to improve the model performance. While applying a set of well designed augmentation transformations could help yield considerable performance enhancement, manually selecting high-quality augmentation transformations and determining how they should be combined still require strong domain expertise and prior knowledge of the dataset of interest. With the recent trend of automated machine learning, data augmentation search flourished in the image domain (Cubuk et al., 2019; 2020; Ho et al., 2019; Lim et al., 2019; Hataya et al., 2020; Li et al., 2020; Liu et al., 2021), which yields significant performance improvement over standard data augmentation.

Although the data augmentation policy in previous works (Cubuk et al., 2019; 2020; Ho et al., 2019; Lim et al., 2019; Hataya et al., 2020; Li et al., 2020), contain multiple transformations applied sequentially, only 1 or 2 transformations of each sub-policy are found through searching, while the rest transformation are hand-picked and applied by default in addition to the found policy (Figure 1(A)). For CIFAR-10/100, flip with 50% probability, pad-and-crop and Cutout with a 16x16 patch are the default augmentations used in combination with the searched policy. For ImageNet, an Inception-style (Szegedy et al., 2015) transformations is applied in addition to the searched augmentation policy, which involves flip with 50% probability, random distortion of colors and resize-and-crop with aspect ratio chosen randomly between 3/4 and 4/3. In this sense, we believe that the previous automated methods are not entirely automated, as they are still built upon hand-crafted default augmentations.

Interestingly, several recent works (LingChen et al., 2020; Müller & Hutter, 2021) showed that even with simple uniform augmentation policy, when combined with the default augmentations, they can still achieve similar performance. The natural question then becomes: 1) Whether the search configurations (search a shallow policy and combine it with the default augmentation) is optimal enough? 2) Can we achieve better performance by fully automate the data augmentation search without using the default augmentation policy? 3) How many layers should an augmentation policy have? In this work, we answer those questions by proposing Deep AutoAugment (DeepAA), a multi-layer data augmentation search method which aims to remove the need of hand-crafted

Figure 1: (A) Existing automated data augmentation methods (shallow augmentation search layers followed by hand-picked transformations). (B) Deep AutoAugment (deep augmentation search stages without hand-picked transformations).

default transformations (Figure 1(B)). DeepAA fully automates the data augmentation by searching a deep data augmentation policy on an expanded set of transformations that includes the widely adopted search space as well as the default transformations (*e.g.* flips, Cutout and crop), leading to a total of 139 different transformations. We formulate the learning objective as maximizing the cosine similarity of gradients between augmented data and a batch of original data. We treat the data augmentation search as a process of stacking data augmentation stages progressively, which effectively reduced the search dimension.

We evaluate the performance of DeepAA on three datasets CIFAR-10, CIFAR-100, and ImageNet, and compare the results with automated data augmentation search methods including AutoAugment (AA) (Cubuk et al., 2019), PBA (Ho et al., 2019), Fast AutoAugment (FastAA) (Lim et al., 2019), Faster AutoAugment (Faster AA) (Hataya et al., 2020), DADA (Li et al., 2020) and RandAugment (RA) (Cubuk et al., 2020), UniformAugment (UA) (LingChen et al., 2020), TrivialAugment (TA) (Müller & Hutter, 2021). Our results show that DeepAA achieves better performance on CIFAR-10, CIFAR-100 on Wide-ResNet-28-10 and ImageNet on ResNet-50 and ResNet-200 without using any default augmentations.

We summarize our main contributions below:

- We propose Deep AutoAugment (DeepAA), a *fully automated* data augmentation search method that finds a multi-layer data augmentation policy from scratch.
- We formulate data augmentation search as a *gradient matching* problem. We show that cosine similarity is an effective metrics for data augmentation search.
- We address the issue of *exponential growth* of the search space dimensionality by incrementally adding augmentations based on the data distribution transformed by all the previous augmentation stages.
- Our experiment results show that DeepAA outperforms existing automated data augmentation methods without using any default augmentations.

2 RELATED WORK

Automated Data Augmentation. Automating data augmentation policy design has recently emerged as a promising paradigm for data augmentation. The pioneer work on automated data augmentation was proposed in AutoAugment (Cubuk et al., 2019), where the search is performed under reinforcement learning framework. AutoAugment requires to train the neural network repeatedly, which takes thousands of GPU hours to converge. Subsequent works (Lim et al., 2019; Li et al., 2020; Liu et al., 2021) aim at reducing the computation cost. Fast AutoAugment (Lim et al., 2019) treats data augmentation as inference time density matching which can be implemented efficiently

with Bayesian optimization. Differentiable Automatic Data Augmentation (DADA) (Li et al., 2020) further reduces the computation cost through a reparameterized Gumbel-softmax distribution (Jang et al., 2017). RandAugment (Cubuk et al., 2020) introduces a simplified search space containing two interpretable hyperparameters, which can be optimized simply by grid search. Although many automated data augmentation methods have been proposed, the use of default augmentations still imposes strong domain knowledge. DeepAA is proposed to address this constraint that is shared across state-of-the-arts.

Gradient Matching. Our work is also related to gradient matching. In (Du et al., 2018), the authors showed that the cosine similarity between the gradient of different tasks provides a signal to detect when an auxiliary loss is helpful to the main loss. In (Wang et al., 2020), the authors proposed to use cosine similarity as the training signal to optimize the data usage via weighting data points. A similar approach was proposed in (Müller et al., 2021), which uses the gradient inner product as a per-example reward for optimizing data distribution and data augmentation under the reinforcement learning framework. Our approach also utilizes the cosine similarity to guide the data augmentation search. Our implementation of cosine similarity is different from the above in that: 1) we propose a Jacobian-vector product form to backpropagate through the cosine similarity, which is computational and memory efficient and does not require computing higher order derivative; and 2) we propose a sampling scheme that effectively allows the cosine similarity to grow with added augmentation stages.

3 DEEP AUTOAUGMENT

In this section, we first describe our motivation of formulating augmentation policy search as a gradient matching problem, and discuss the challenges of policy search when the augmentation layers become deep. We then introduce the search space of the augmentation policies followed by presenting DeepAA in detail.

3.1 MOTIVATION

Data augmentation can be viewed as a process of filling missing data points in the dataset with the same data distribution (Hataya et al., 2020). By augmenting a single data point for multiple times, we expect the resulting data distribution to be close to the full dataset under a certain type of transformation. For example, by augmenting a single image with proper color jittering, we obtain a batch of augmented images which has similar distributions of lighting conditions as the full dataset. As the distribution of augmented data gets closer to the full dataset, the gradient of the augmented data should be steered towards a batch of original data sampled from the dataset. In DeepAA, we formulate the search of the data augmentation policy as a gradient matching problem, which manages to steer the gradient to a batch of original data by augmenting a single image for multiple times. We construct the augmented training batch by augmenting a single training data point for multiple times following the augmentation policy. We construct a validation batch by sampling a batch of original data from the validation set. We expect that by augmentation, the gradient of augmented training batch can be steered towards the gradient of the validation batch. The intuition is that an effective data augmentation fills the missing data points in the training set, thus steering the training gradient towards the validation gradient.

Another challenge for data augmentation search is that the search space can be prohibitively large with deep augmentation depth $(K \geq 5)$. This was not a problem in previous works, where the augmentation policies is shallow $(K \leq 2)$. For example, in AutoAugment Cubuk et al. (2019), each sub-policy contains $K = 2$ transformations to be applied sequentially, and the search space of AutoAugment contains 16 image operations and 10 discrete magnitude levels. The resulting number of combinations of transformations in AutoAugment is roughly $(16 \times 10)^2 = 25,600$, which is handled well in previous research. However, by discarding the default augmentation pipeline and search for data augmentations from scratch, it requires deeper augmentation layers in order to perform well. For a data augmentation with $K = 5$ sequentially applied transformations, the number of sub-policies is $(16 \times 10)^5 \approx 10^{11}$, which is prohibitively large for the following two reasons: First, it becomes less likely to encounter a good policy by exploration, as stacking more transformations could easily lead to a overly strong transformations. Second, the dimension of parameters in the policy also grows with K, making it harder to optimize. Instead of searching for sub-policies, we

propose to build up the full data augmentation by progressively stacking augmentation layers, where each augmentation layer is optimized on top of the data distribution transformed by all previous layers. This avoids sampling sub-policies from a large search space, and the parameters of the policy is reduced to $\mathbb{T}$ for each augmentation layer.

3.2 SEARCH SPACE

Let $\mathbb{O}$ denote the set of augmentation operations (e.g. identity, rotate, brightness, e.t.c), m denote an operation magnitude in the set $\mathbb{M}$, x denote an image sampled from the space $\mathcal{X}$. We define the set of transformations as the set of operations with a fixed magnitude, that is $\mathbb{T} := \{t | t = o(\cdot ; m), o \in \mathbb{O} \text{ and } m \in \mathbb{M}\}$. By this definition, every t is a map $t : \mathcal{X} \to \mathcal{X}$, and there are $|\mathbb{T}| = |\mathbb{M}| \cdot |\mathbb{O}|$ possible transformations. In previous works (Cubuk et al., 2019; Lim et al., 2019; Li et al., 2020; Hataya et al., 2020), a data augmentation policy $\mathcal{P}$ consists of several sub-policies. As explained above, the size of candidate sub-policies grows exponentially with depth K. Therefore, in this work, instead of searching for sub-policies, we propose a practical method that builds up the full data augmentation by progressively stacking augmentation layers. The final data augmentation policy hence consists of K layers of sequentially applied policy $\mathcal{P} = \{\mathcal{P}_1, \cdots, \mathcal{P}_K\}$. Policy $\mathcal{P}_k$ is optimized conditioned on the data distribution augmented by all previous $k - 1$ layers of policies, thus we write the policy as a conditional distribution $\mathcal{P}_k := p_{\theta_k}(n | \{\mathcal{P}_1, \cdots, \mathcal{P}_{k-1}\})$ where n denotes the indices of transformations in $\mathbb{T}$. With some abuse of notations, We use a simplified notation as p_{θ_k} to replace $p_{\theta_k}(n | \{\mathcal{P}_1, \cdots, \mathcal{P}_{k-1}\})$ for clarity.

3.3 SEARCH STRATEGY

In this subsection, we formulate data augmentation search as a gradient direction matching problem. We derive the optimization algorithm for a single layer policy. We then tackle the challenges for multi-layer policy scenario by progressive optimizing and stacking policies based on the data augmented by all previous layers.

3.3.1 AUGMENTATION POLICY SEARCH VIA GRADIENT MATCHING

Let's augment a single data point x for multiple times following distribution p_θ. The resulting average gradient of such augmentation is denoted as $g(x, \theta)$ which is a function of data x and distribution parameters θ. Denote v as the gradients of a batch of original data. As discussed above, we optimize the policy by maximizing the cosine similarity between the gradients of the augmented data and a batch of original data, as follows:

$$\theta = \arg\max_\theta \ \text{cosineSimilarity}(v, g(x, \theta)) \tag{1}$$

$$= \arg\max_\theta \ \frac{v^T \cdot g(x, \theta)}{\|v\| \cdot \|g(x, \theta)\|}$$

where $\|\cdot\|$ denotes the L2-norm. The parameters of the distribution can be updated via gradient ascent:

$$\theta \leftarrow \theta + \eta \nabla_\theta \text{cosineSimilarity}(v, g(x, \theta)) \tag{2}$$

3.3.2 POLICY SEARCH FOR ONE LAYER

We start with the case where the data augmentation policy only contains a single augmentation layer, i.e., $\mathcal{P} = \{p_\theta\}$. Let $L(x; w)$ denote the classification loss of data x where $w \in \mathbb{R}^D$ represents the flattened weights of the neural network. Consider applying augmentation on a single sample x following the distribution p_θ, the resulting averaged gradient can be calculated analytically by averaging all possible transformations in $\mathbb{T}$ with the corresponding probability $p(\theta)$:

$$g(x; \theta) = \sum_{n=1}^{|\mathbb{T}|} p_\theta(n) \nabla_w L(t_n(x); w) \tag{3}$$

$$= G(x) \cdot p_\theta$$

where $G(x) = \left[\nabla_w L(t_1(x); w), \cdots, \nabla_w L(t_{|\mathbb{T}|}(x); w) \right]$ is a $D \times |\mathbb{T}|$ Jacobian matrix, and $p_\theta = [p_\theta(1), \cdots, p_\theta(|\mathbb{T}|)]^T$ is a $|\mathbb{T}|$ dimensional Categorical distribution. The gradient w.r.t. the cosine similarity in Eqn. (11) can be derived as:

$$\nabla_\theta \, \text{cosineSimilarity}(v, g(x; \theta)) = \nabla_\theta p_\theta \cdot r, \tag{4}$$

where

$$r = G(x)^T \left(\frac{v}{\|g(\theta)\|} - \frac{v^T g(\theta)}{\|g(\theta)\|^2} \cdot \frac{g(\theta)}{\|g(\theta)\|} \right) \tag{5}$$

We interpret r as a reward for each transformation. Note that ∇_θ in Eq. (4) only operates on p_θ, but not r. Given the Jacobian-vector product form in Eq. (9), it can be implemented efficiently without explicitly calculating and storing the Jacobian matrix by autodiff libraries such as TensorFlow (Abadi et al., 2016).

3.3.3 CHALLENGES FOR MULTIPLE LAYER POLICY SEARCH

The above derivation is based on that $g(\theta)$ can be computed analytically by Eq. (3). However, for K ($K \geq 2$), it becomes impractical to compute the average gradient of augmented data given that we need to average the gradient of all $|\mathbb{T}|^K$ possible sub-policies and the resulting policy $\mathcal{P}$ is a high dimension distribution.

To efficiently search for a multi-layer augmentation policy, we model it as a process that incrementally changes the distribution of a dataset. For example with a K layer policy $\mathcal{P} = \{\mathcal{P}_1, \cdots, \mathcal{P}_K\}$, the policy $\mathcal{P}_k$ modifies the data distribution on top of the data distribution augmented by previous $k-1$ layers. Therefore the policy at the kth layer is a distribution $\mathcal{P}_k = p_{\theta_k}(n)$ conditioned on the policies $\mathcal{P}_1, \cdots, \mathcal{P}_{k-1}$, and each one is a $|\mathbb{T}|$ dimensional Categorical distribution. With this definition, we can modify the Jacobian matrix at the kth layer by averaging over the previous $k-1$ layers of policies as

$$G(x)^k = \sum_{n_{k-1}=1}^{|\mathbb{T}|} \cdots \sum_{n_1=1}^{|\mathbb{T}|} p_{\theta_{k-1}}(n_{k-1}) \cdots p_{\theta_1}(n_1) [\nabla_w L((t_1 \circ t_{n_{k-1}} \cdots \circ t_{n_1})(x); w), \cdots, \tag{6}$$
$$\nabla_w L((t_{|\mathbb{T}|} \circ t_{n_{k-1}} \circ \cdots \circ t_{n_1})(x); w)] \,,$$

where G^k is a $D \times |\mathbb{T}|$ matrix. By using the Monte Carlo method we get an estimated of G^k as:

$$\tilde{G}^k(x) = \sum_{\tilde{n}_{k-1} \sim p_{\theta_k}} \cdots \sum_{\tilde{n}_1 \sim p_{\theta_1}} [\nabla_w L((t_1 \circ t_{\tilde{n}_{k-1}} \cdots \circ t_{\tilde{n}_1})(x); w), \cdots, \tag{7}$$
$$\nabla_w L((t_{|\mathbb{T}|} \circ t_{\tilde{n}_{k-1}} \circ \cdots \circ t_{\tilde{n}_1})(x); w)] \,.$$

where $\tilde{n}_{k-1} \sim p_{\theta_{k-1}}(n), \cdots, \tilde{n}_1 \sim p_{\theta_1}(n)$. Following the above notations, the average gradient at the kth layer can be estimated by the Monte Carlo method:

$$\tilde{g}(x; \theta_k) = \sum_{\tilde{\tilde{n}}_k \sim p_{\theta_k}} \cdots \sum_{\tilde{n}_1 \sim p_{\theta_1}} \nabla_w L \left((t_{\tilde{n}_K} \circ \cdots \circ t_{\tilde{n}_1})(x); w \right) \,. \tag{8}$$

Therefore, the reward at the kth layer can be expressed as:

$$\tilde{r}^k(x) = \left(\tilde{G}^k(x) \right)^T \left(\frac{v}{\|\tilde{g}_k(x; \theta_k)\|} - \frac{v^T \tilde{g}_k(x; \theta_k)}{\|\tilde{g}_k(x; \theta_k)\|^2} \cdot \frac{\tilde{g}_k(x; \theta_k)}{\|\tilde{g}_k(x; \theta_k)\|} \right) \,. \tag{9}$$

We found that it helps to stability to the optimization by encouraging the transformations that performs good with high confidence, while discouraging the transformation that showed large uncertainty for different images. One effective way of doing so this is to penalize the average reward by its standard deviations, that is

$$r^k = r_m^k - c \cdot r_v^k \,, \tag{10}$$

where $r_m^k = E_x\{\tilde{r}^k(x)\}$ and $r_v^k = \sqrt{E_x\{(\tilde{r}^k(x) - r_m^k)^2\}}$ are estimated by Monte Carlo method.

We set parameter $c = 1.0$ that controls the degree of penalization throughout the paper. The resulting updating formula for policy $\mathcal{P}_k$ ($k \geq 2$) is expressed as:

$$\theta \leftarrow \theta_k + \eta \nabla_{\theta_k} \, \text{cosineSimilarity}(v, g(\theta_k)) \,, \tag{11}$$

where

$$\nabla_\theta \, \text{cosineSimilarity}(v, g^k(x; \theta)) = \nabla_\theta p_{\theta_k} \cdot r^k \,. \tag{12}$$

4 EXPERIMENTS AND ANALYSIS

Benchmarks and Baselines. We evaluate the performance of DeepAA on three standard benchmarks: CIFAR-10, CIFAR-100, ImageNet, and compare it against a baseline based on standard augmentations (i.e., flip left-righ, pad-and-crop for CIFAR-10/100, and Inception-stype preprocesing (Szegedy et al., 2015) for ImageNet) as well as eight existing automatic augmentation methods including (1) AutoAugment (AA) (Cubuk et al., 2019), (2) PBA (Ho et al., 2019), (3) Fast AutoAugment (Fast AA) (Lim et al., 2019), (4) Faster AutoAugment (Hataya et al., 2020), (5) DADA (Li et al., 2020), (6) RandAugment (RA) (Cubuk et al., 2020), (7) UniformAugment (UA) (LingChen et al., 2020), and (8) TrivialAugment (TA) (Müller & Hutter, 2021).

Search Space. We set up the operation set $\mathbb{O}$ such that it contains 16 commonly used operations (identity, shear-x, shear-y, translate-x, translate-y, rotate, solarize, equalize, color, posterize, contrast, brightness, sharpness, autoContrast, invert, Cutout) as well as two operations (flips and crop) that are used as the default operations in the aforementioned existing automatic augmentation methods. Among the operations in $\mathbb{O}$, 11 operations are associated with magnitudes. We then discretize the range of magnitudes into 12 uniformly spaced levels and treat each operation with a discrete magnitude as an independent transformation. Therefore, we have a total of $|\mathbb{T}| = 139$ transformations in our search space. The list of operations and the range of magnitudes are summarized in Table 7 in the Appendix.

4.1 PERFORMANCE ON CIFAR-10 AND CIFAR-100

Policy Search. Following (Cubuk et al., 2019), we conduct the augmentation policy search based on Wide-ResNet-40-2 (Zagoruyko & Komodakis, 2016). We train the network on a subset of 4,000 randomly selected samples from CIFAR-10. We then update the policy parameters θ_k $(k = 1, 2, \cdots, K)$ for 512 iterations for each of the K augmentation layers. We use the Adam optimizer (Kingma & Ba, 2014) and set the learning rate to 0.025 for policy updating.

Policy Evaluation. Using the publicly availabel repository of Fast AutoAugment (Lim et al., 2019), we evaluate the found augmentation policy on both CIFAR-10 and CIFAR-100 using Wide-ResNet-28-10 and Shake-Shake-2x96d models. The evaluation configurations are kept consistent with that of Fast AutoAugment.

Results. In Table 1, we report the Top-1 test accuracy on CIFAR-10/100 for Wide-ResNet-28-10 and Shake-Shake-2x96d, respectively. The reported results of DeepAA are the average of four independent runs with different initializations. We also show the 95% confidence interval of the mean accuracy. As shown, on CIFAR-10, DeepAA consistently outperforms the baseline as well as existing automatic augmentation methods on both Wide-ResNet-28-10 and Shake-Shake-2x96d. Similarly, on CIFAR-100, DeepAA achieves the best accuracy on Wide-ResNet-28-10. In particular, DeepAA achieve a test accuracy of 84.02% on Wide-ResNet-28-10. This is 0.48% higher than the previous state-of-the-art.

	Baseline	AA	PBA	FastAA	FasterAA	DADA	RA	UA	TA [1]	DeepAA
CIFAR-10										
WRN-28-10	96.1	97.4	97.4	97.3	97.4	97.3	97.3	97.33	97.46	**97.56 ± 0.14**
Shake-Shake (26 2x96d)	97.1	98.0	98.0	98.0	98.0	98.0	98.0	98.1	98.05	**98.11 ± 0.12**
CIFAR-100										
WRN-28-10	81.2	82.9	83.3	82.7	82.7	82.5	83.3	82.82	83.54	**84.02 ± 0.18**
Shake-Shake (26 2x96d)	82.9	**85.7**	84.7	85.1	85.0	84.7	-	-	-	85.19 ± 0.28

Table 1: Top-1 test accuracy (%) on CIFAR-10/100 for Wide-ResNet-28-10 and Shake-Shake-2x96d. The reported results of DeepAA are averaged over four independent runs with different initializations with 95% confidence interval.

---

[1] We compare with TA using RA's parameter space.

Figure 2: Top-1 test accuracy (%) on ImageNet of DeepAA-simple, DeepAA, baseline, and existing automatic augmentation methods on ResNet-50.

4.2 PERFORMANCE ON IMAGENET

Policy Search. We conduct the augmentation policy search based on ResNet-18 (He et al., 2016). We train the network on a subset of $200,000$ randomly selected samples from ImageNet for 30 epochs. We use the same search settings as in CIFAR-10.

Policy Evaluation. We evaluate the performance of the found augmentation policy on ResNet-50 and ResNet-200 based on the public repository of Fast AutoAugment (Lim et al., 2019). The parameters for training are identical to the configuration of (Lim et al., 2019; Müller & Hutter, 2021).

Results. The performance of our proposed method on ImageNet is presented in Table 2. As shown, DeepAA consistently outperforms the baseline as well as existing automatic augmentation methods on both ResNet-50 and ResNet-200. In particular, DeepAA achieve a test accuracy of 78.30% and 81.32% on ResNet-50 and ResNet-200 respectively, which is 0.67% and 0.72% higher than the previous state-of-the-arts.

	Baseline	AA	Fast AA	Faster AA	DADA	RA	UA	TA[2]	DeepAA
ResNet-50	76.3	77.6	77.6	76.5	77.5	77.6	77.63	77.55	**78.30 ± 0.14**
ResNet-200	78.5	80.0	80.6	-	-	-	80.4	-	**81.32 ± 0.17**

Table 2: Top-1 test accuracy (%) on ImageNet for ResNet-50 and ResNet-200. The reported results of DeepAA are averaged over four independent runs with different initializations with 95% confidence interval.

4.3 UNDERSTANDING DEEPAA

Effectiveness of Augmentation Policy Search. One advantage of DeepAA is the proposed augmentation policy search method based on gradient matching. To examine its effectiveness, we factor out the impact coming from multiple augmentation layers, and conduct an experiment to search for a single layer of augmentation policy based on it. When evaluating the searched policy, we apply the default augmentation in addition to the searched policy. We refer to this variant as DeepAA-simple. Figure 2 compares the Top-1 test accuracy on ImageNet using ResNet-50 between DeepAA-simple, DeepAA, and existing automatic augmentation methods. While there is 0.22% performance drop compared to DeepAA, *with a single augmentation layer*, DeepAA-simple significantly outperforms other methods.

Policy Search Cost. Table 3 compares the policy search time on CIFAR-10/100 and ImageNet in GPU hours. DeepAA searches for a 5-layer data augmentation policy that outperforms other automated data augmentation methods within accepted amount of time. Note that the multi-layer search space in DeepAA is much larger than the search space of existing automatic augmentation methods, since we search for the a deeper data augmentation policy from scratch.

Impact of the Number of Augmentation Layers. Another advantage of DeepAA is its multi-layer search space that can *go beyond* two layers which existing automatic augmentation methods are designed upon. To examine the impact of the number of augmentation layers on the performance

---

[2]We compare TA using RA's parameter space and evaluate on images of size 224x224.

Dataset	AA	PBA	Fast AA	Faster AA	DADA	RA	DeepAA
CIFAR-10/100	5000	5	3.5	0.23	0.1	25	9
ImageNet	15000	-	450	2.3	1.3	5000	96

Table 3: Policy search time on CIFAR-10/100 and ImageNet in GPU hours. Note that DeepAA is performed in the multi-layer search space that is much larger than the search space of existing automatic augmentation methods.

of DeepAA, we conduct an experiment with different numbers of augmentation layers. Table 4 and Table 5 show the performance on CIFAR-10/100 and ImageNet respectively with increasing number of augmentation layers. As shown, for CIFAR-10/100, the performance gradually improves when more augmentation layers are added until we reach five layers. The performance does not improve when the sixth layer is added. For ImageNet, we have the similar observation where the performance stops improving when more than five augmentation layers are included.

	1 layer	2 layers	3 layers	4 layers	5 layers	6 layers
CIFAR-10	96.3 ± 0.21	96.6 ± 0.18	96.9 ± 0.12	97.4 ± 0.14	$\mathbf{97.56 \pm 0.14}$	$\mathbf{97.6 \pm 0.12}$
CIFAR-100	80.9 ± 0.31	81.7 ± 0.24	82.2 ± 0.21	83.7 ± 0.24	$\mathbf{84.02 \pm 0.18}$	$\mathbf{84.0 \pm 0.19}$

Table 4: Top-1 test accuracy (%) of DeepAA on CIFAR-10 and CIFAR-100 for different numbers of augmentation layers. The reported results are averaged over four independent runs with different initializations with 95% confidence interval.

	1 layer	3 layers	5 layers	7 layers
ImageNet	75.27 ± 0.19	78.18 ± 0.22	$\mathbf{78.30 \pm 0.14}$	$\mathbf{78.30 \pm 0.14}$

Table 5: Top-1 test accuracy (%) of DeepAA on ImageNet with ResNet-50 for different numbers of augmentation layers. The reported results are averaged over four independent runs with different initializations with 95% confidence interval.

Identification of the Optimal Number of Augmentation Layers. Given the results obtained from the previous experiment, a natural question to ask is whether it is possible to automatically identify the optimal number of augmentation layers for DeepAA. To shed light on the answer to this question, Figure 3 illustrates the distributions of operations in the searched policy for CIFAR-10/100 and ImageNet respectively. Shown in Figure 3(a), the augmentation converges to the *identity* transformation at the sixth augmentation layer, which is a natural indication of the end of the augmentation pipeline. Additionally, the distribution of the magnitude of each operation can be found in Figure 4 in the Appendix. Shown in Figure 3(b), we have the similar observation where the *identity* transformation dominates in the sixth augmentation layer. These observations match our Top-1 test accuracies listed in Table 4 and Table 5. Additionally, the distribution of the magnitude of each operation can be found in Figure 5 in the Appendix.

Validity of Optimizing Gradient Matching. Finally, we want to demonstrate the validity of optimizing gradient matching for automatic data augmentation as we claim throughout this work. To do so, we obtain a batch of augmented data by augmenting a single randomly sampled image for 512 times following k layers of augmentation policy. We then sample a batch of 64 original images within the same class as the augmented one. The cosine similarity is calculated between the gradients of the augmented image batch and original image batch. We report the cosine similarity over 64 independent runs. As shown in Table 6, for CIFAR-10/100, the value of cosine similarity gradually increases when more augmentation layers are added and converges to 0.771 when five layers are added. Further adding more layers does not change the cosine similarity value. For ImageNet, we have the similar observation where the cosine similarity value stops increasing when more than five augmentation layers are included. These results again match our Top-1 test accuracies listed in Table 4 and Table 5.

(a) Operation distribution
for CIFAR-10/100

(b) Operation distribution
for ImageNet

Figure 3: The distribution of operations at each layer of the policy for CIFAR-10/100 and ImageNet. The probability of each operation (e.g., rotate) is summed up over all 12 discrete intensity levels of the corresponding transformation.

	1 layer	2 layers	3 layers	4 layers	5 layers	6 layers
CIFAR-10/100	0.728 ± 0.019	0.741 ± 0.017	0.760 ± 0.016	0.763 ± 0.015	$\mathbf{0.771 \pm 0.014}$	$\mathbf{0.771 \pm 0.014}$
ImageNet	0.641 ± 0.012	0.695 ± 0.014	0.718 ± 0.014	0.726 ± 0.013	$\mathbf{0.730 \pm 0.013}$	$\mathbf{0.730 \pm 0.014}$

Table 6: The average cosine similarity over the course of searching for CIFAR-10/100 and ImageNet with 75% confidence interval calculated from 64 independent samples.

5 CONCLUSION

In this work, we propose Deep AutoAugment (DeepAA), a fully automated multi-layer data augmentation search method without using hand-picked default transformations. DeepAA formulates data augmentation search as a gradient direction matching problem, which maximize the cosine similarity between a batch of augmented data and a batch of original data. We address the issue of high dimensionality by incrementally adding augmentation. A Monte Carlo sampling scheme is proposed to effectively optimize the data augmentaion policy. Our experiment results show that DeepAA outperforms previous state-of-the-art automated data augmentation methods.

Reproducibility Statement: We carefully explain our experiment settings to be as straightforward to readers as possible. The evaluation of the found data augmentation policy is based the public repository of Fast AutoAugment. We believe our results can be readily reproduced. Our implementation will be made public.

REFERENCES

Martin Abadi, Paul Barham, Jianmin Chen, Zhifeng Chen, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Geoffrey Irving, Michael Isard, Manjunath Kudlur, Josh Levenberg, Rajat Monga, Sherry Moore, Derek G. Murray, Benoit Steiner, Paul Tucker, Vijay Vasudevan, Pete Warden, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. Tensorflow: A system for large-scale machine learning. In *OSDI*, 2016.

Ekin D Cubuk, Barret Zoph, Dandelion Mane, Vijay Vasudevan, and Quoc V Le. Autoaugment: Learning augmentation strategies from data. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 113–123, 2019.

Ekin D Cubuk, Barret Zoph, Jonathon Shlens, and Quoc V Le. Randaugment: Practical automated data augmentation with a reduced search space. In *NeurIPS*, pp. 702–703, 2020.

Terrance DeVries and Graham W Taylor. Improved regularization of convolutional neural networks with cutout. *arXiv preprint arXiv:1708.04552*, 2017.

Yunshu Du, Wojciech M Czarnecki, Siddhant M Jayakumar, Mehrdad Farajtabar, Razvan Pascanu, and Balaji Lakshminarayanan. Adapting auxiliary losses using gradient similarity. *arXiv preprint arXiv:1812.02224*, 2018.

Ian Goodfellow, Yoshua Bengio, Aaron Courville, and Yoshua Bengio. *Deep learning*. MIT press Cambridge, 2016.

Ryuichiro Hataya, Jan Zdenek, Kazuki Yoshizoe, and Hideki Nakayama. Faster autoaugment: Learning augmentation strategies using backpropagation. In *European Conference on Computer Vision*, pp. 1–16. Springer, 2020.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Dan Hendrycks, Norman Mu, Ekin D Cubuk, Barret Zoph, Justin Gilmer, and Balaji Lakshminarayanan. Augmix: A simple data processing method to improve robustness and uncertainty. *ICLR*, 2020.

Daniel Ho, Eric Liang, Xi Chen, Ion Stoica, and Pieter Abbeel. Population based augmentation: Efficient learning of augmentation policy schedules. In *International Conference on Machine Learning*, pp. 2731–2741. PMLR, 2019.

Hiroshi Inoue. Data augmentation by pairing samples for images classification. *arXiv preprint arXiv:1801.02929*, 2018.

Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with gumbel-softmax. *ICLR*, 2017.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Yonggang Li, Guosheng Hu, Yongtao Wang, Timothy Hospedales, Neil M Robertson, and Yongxin Yang. Differentiable automatic data augmentation. In *European Conference on Computer Vision*, pp. 580–595. Springer, 2020.

Sungbin Lim, Ildoo Kim, Taesup Kim, Chiheon Kim, and Sungwoong Kim. Fast autoaugment. *NeurIPS*, 2019.

Tom Ching LingChen, Ava Khonsari, Amirreza Lashkari, Mina Rafi Nazari, Jaspreet Singh Sambee, and Mario A Nascimento. Uniformaugment: A search-free probabilistic data augmentation approach. *arXiv preprint arXiv:2003.14348*, 2020.

Aoming Liu, Zehao Huang, Zhiwu Huang, and Naiyan Wang. Direct differentiable augmentation search. *arXiv preprint arXiv:2104.04282*, 2021.

Samuel Müller, André Biedenkapp, and Frank Hutter. In-loop meta-learning with gradient-alignment reward. *arXiv preprint arXiv:2102.03275*, 2021.

Samuel G Müller and Frank Hutter. Trivialaugment: Tuning-free yet state-of-the-art data augmentation. *arXiv preprint arXiv:2103.10158*, 2021.

Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, and Andrew Rabinovich. Going deeper with convolutions. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1–9, 2015.

Xinyi Wang, Hieu Pham, Paul Michel, Antonios Anastasopoulos, Jaime Carbonell, and Graham Neubig. Optimizing data usage via differentiable rewards. In *International Conference on Machine Learning*, pp. 9983–9995. PMLR, 2020.

Shen Yan, Huan Song, Nanxiang Li, Lincan Zou, and Liu Ren. Improve unsupervised domain adaptation with mixup training. In *arXiv preprint arXiv: 2001.00677*, 2020.

Sangdoo Yun, Dongyoon Han, Seong Joon Oh, Sanghyuk Chun, Junsuk Choe, and Youngjoon Yoo. Cutmix: Regularization strategy to train strong classifiers with localizable features. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 6023–6032, 2019.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. In *British Machine Vision Conference 2016*. British Machine Vision Association, 2016.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning requires rethinking generalization. *ICLR*, 2017.

Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. *ICLR*, 2018.

A APPENDIX

Operation	Magnitude
Identity	-
ShearX	[-0.3, 0.3]
ShearY	[-0.3, 0.3]
TranslateX	[-0.45, 0.45]
TranslateY	[-0.45, 0.45]
Rotate	[-30, 30]
AutoContrast	-
Invert	-
Equalize	-
Solarize	[0, 256]
Posterize	[4, 8]
Contrast	[0.1, 1.9]
Color	[0.1, 1.9]
Brightness	[0.1, 1.9]
Sharpness	[0.1, 1.9]
Flips	-
Cutout	16 (60)
Crop	-

Table 7: List of all images operations in the search space and the corresponding range of magnitudes. Note that some operations do not use magnitude parameters. We add flip and crop to the search space which were found in the default augmentation pipeline in previous researches. Flips operates by randomly flipping the images with 50% probability. In line with previous works, crop denotes pad-and-crop and resize-and-crop transforms for CIFAR10/100 and ImageNet respectively. We set Cutout magnitude to 16 for CIFAR10/100 dataset to be the same as the Cutout in the default augmentation pipeline. We set Cutout magnitude to 60 pixels for ImageNet which is the upper limit of the magnitude used in AA (Cubuk et al., 2019).

Figure 4: The distribution of discrete magnitudes of each augmentation transformation in each layer of the policy for CIFAR-10/100. The x-axis represents the discrete magnitudes and the y-axis represents the probability. The magnitude is discretized to 12 levels with each transformation having its own range. A large absolute value of the magnitude corresponds to high transformation intensity. Note that we do not show identity, autoContrast, invert, equalize, flips, Cutout and crop because they do not have intensity parameters.

Figure 5: The distribution of discrete magnitudes of each augmentation transformation in each layer of the policy for ImageNet. The x-axis represents the discrete magnitudes and the y-axis represents the probability. The magnitude is discretized to 12 levels with each transformation having its own range. A large absolute value of the magnitude corresponds to high transformation intensity. Note that we do not show identity, autoContrast, invert, equalize, flips, Cutout and crop because they do not have intensity parameters.