Distributional Reinforcement Learning for Multi-Dimensional Reward Functions

Abstract

A growing trend for value-based reinforcement learning (RL) algorithms is to capture more information than scalar value functions in the value network. One of the most well-known methods in this branch is distributional RL, which models return distribution instead of scalar value. In another line of work, hybrid reward architectures (HRA) in RL have studied to model source-specific value functions for each source of reward, which is also shown to be beneficial in performance. To fully inherit the benefits of distributional RL and hybrid reward architectures, we introduce Multi-Dimensional Distributional DQN (MD3QN), which extends distributional RL into multi-dimensional random variables and has the capability of modeling the joint return distribution from multiple reward sources. As a by-product of joint distribution modeling, MD3QN can capture not only the randomness in returns for each source of reward, but also the rich correlation between the randomness of different sources. We prove the convergence for the joint distributional Bellman operator and build our empirical algorithm by minimizing the Maximum Mean Discrepancy between joint return distribution and its Bellman target. In experiments, our method accurately models the joint return distribution in environments with richly correlated reward functions, and outperforms previous RL methods utilizing multiple reward functions in the control setting.

1 Introduction

Making value network capture more information than scalar value functions is a growing trend in value-based reinforcement learning, which helps the agent gain more knowledge about the environment and has great potentials to improve the sample efficiency of RL agents. In the early stage of deep reinforcement learning, DQN (Mnih et al., 2013) uses the scalar output of the neural network to represent value functions. As value-based RL algorithms evolve, distributional RL algorithms start to use neural networks to approximate return distributions for each state-action pair, and take action based on the expectation of return distributions. By capturing the randomness in return as auxiliary tasks, distributional RL agents can gain more knowledge about the environment and learn better representations to avoid state aliasing (Bellemare et al., 2017). Distributional RL algorithms including C51 (Bellemare et al., 2017), QR-DQN (Dabney et al., 2018b), IQN (Dabney et al., 2018a), FQF (Yang et al., 2019) and MMDQN (Nguyen et al., 2020) achieve substantial performance gain compared to DQN.

In another line of work, HRA (Van Seijen et al., 2017) and RD^2 (Lin et al., 2020) consider the setting where multiple reward sources exist in the environment and modify the value network to model source-specific value function for each reward source. In these works, the outputs of value networks can be interpreted as multiple source-specific value functions, and the agent takes action based on the sum of all source-specific value functions. Similar to return distribution, estimating the source-specific value functions can be seen as auxiliary tasks, which serve as additional supervision

for how the total reward is composed and enable the agent to learn better representations. Several previous works support that it is beneficial to model source-specific value functions (Boutilier et al., 1995; Sutton et al., 2011a; Van Seijen et al., 2017; Lin et al., 2020).

Towards providing more supervision signals and enabling agents to gain more knowledge about the environment, we propose to capture the correlated randomness in source-specific returns. Specifically, we consider the source-specific returns from all sources of rewards as a multi-dimensional random variable, and capture its joint distribution to model the randomness of returns from different sources. This provides an informative learning target for our agent. The framework is general and can be extended to capture the correlated randomness of other types of random variables than rewards. For example, we can capture the correlation between achieving different goals in goal-conditioned reinforcement learning (Schaul et al., 2015), or visiting different states in successor representation (Kulkarni et al., 2016). In this paper, we focus on the method for learning joint return distribution of given source-specific rewards and leave the extension to more general settings for future work.

Following existing works on distributional RL, we study the convergence of the Bellman operator and propose an empirical algorithm to approximate the Bellman operator. First, we define the joint distributional Bellman operator, and prove its convergence under the Wasserstein metric. We correct a misunderstanding in existing works on distributional RL, and argue that we can use other metrics than the Wasserstein metric over joint distribution as training losses to approximate the Bellman operator. To derive an empirical algorithm, our proposed method (MD3QN) approximates the joint distributional Bellman operator by minimizing the Maximum Mean Discrepancy (MMD) loss over joint return distributions and its Bellman target. MMD holds desirable properties that, it is a metric over joint distribution and its square can be unbiasedly optimized with batch samples. This enables our algorithm to approximate the Bellman operator accurately when the number of samples goes to infinity and the loss is minimized to zero.

In experiments on Atari games and other environments with pixel inputs, our method accurately models the multi-dimensional joint distribution from multiple reward sources. Moreover, our algorithm outperforms previous work HRA which also separately models different sources of reward on Atari game environments.

Our contributions can be summarized as follows:

- We propose the first distributional RL algorithm that learns a joint distribution model for source-specific returns as multi-dimensional random variables.

- We establish convergence results for the joint distributional Bellman operator, and propose an empirical algorithm to approximate this Bellman operator by minimizing MMD loss over joint return distribution and its Bellman target.

- Empirically, our method outperforms previous RL algorithms utilizing multiple reward sources, and accurately models the joint return distribution for all sources of rewards.

2   Background

2.1   Notations and Problem Setting

Since our work considers multiple reward sources exist in the environment, our problem setting is slightly different from the traditional RL setting in reward function. We consider a Markov Decision Process with multiple reward sources defined by $(\mathcal{S}, \mathcal{A}, P, \boldsymbol{R}, \rho_0, \gamma)$, where $\mathcal{S}$ is the set of states, $\mathcal{A}$ is the finite set of actions, $P : \mathcal{S} \times \mathcal{A} \to \mathcal{P}(\mathcal{S})$ denotes the transition probability, $\boldsymbol{R} : \mathcal{S} \times \mathcal{A} \to \mathcal{P}(\mathbb{R}^N)$ denotes the reward function for a total of N reward sources, $\rho_0 : \mathcal{P}(\mathcal{S})$ denotes the distribution of initial state S_0, $\gamma \in (0, 1)$ is the discount factor. Given a policy $\pi : \mathcal{S} \to \mathcal{P}(\mathcal{A})$, a trajectory is generated by $s_0 \sim \rho_0$, $a_t \sim \pi(s_t)$, $s_{t+1} \sim P(s_t, a_t)$ and $\boldsymbol{r}_t = [r_{t,1}, r_{t,2}, ..., r_{t,N}]^\top \sim \boldsymbol{R}(s_t, a_t)$. We use $r_t = \sum_{n=1}^N r_{t,n}$ to denote the total reward received at time t. The goal for reinforcement learning algorithms is to find the optimal policy π which maximizes the expected total return from all sources, given by $J(\pi) = \mathbb{E}_\pi[\sum_{t=0}^\infty \gamma^t \sum_{n=1}^N r_{t,n}]$.

Next we describe value-based reinforcement learning algorithms in a general framework. In DQN, the value network $Q(s, a; \theta)$ captures the scalar value function, where θ is the parameters of the value

network. θ_0 is the initial value of θ. In i-th iteration, the training objective for θ_i is[1]

$$L(\theta_i) = \mathbb{E}_{s_t,a_t,\boldsymbol{r}_t,s_{s+1}}[(Q(s_t, a_t; \theta_i) - y_i)^2], \tag{1}$$

$$\text{where } y_i = r_t + \gamma \max_{a'} Q(s_{t+1}, a'; \theta_{i-1}), \tag{2}$$

and $s_t, a_t, \boldsymbol{r}_t, s_{t+1}$ is are sampled from the replay memory.

2.2 Distributional RL

In distributional RL algorithms such as C51, IQN and MMD-DQN, $\mu(s, a; \theta)$ captures the return distribution for each state action pair (s, a). In i-th iteration, the training objective for θ_i is

$$L(\theta_i) = \mathbb{E}_{s_t,a_t,\boldsymbol{r}_t,s_{t+1}}[d(\mu(s_t, a_t; \theta_i), \eta_i)], \tag{3}$$

$$\text{where } \eta_i = (f_{r_t,\gamma})_{\#}\,\mu(s_{t+1}, a'; \theta_{i-1}), a' = \arg\max_{a'} \mathbb{E}_{Z \sim \mu(s_{t+1},a';\theta_{i-1})}[Z]. \tag{4}$$

Here $f_{r,\gamma}(x) := r + \gamma \cdot x$. Given a probability distribution $\nu \in \mathcal{P}(\mathbb{R})$, $f_{\#}\nu \in \mathcal{P}(\mathbb{R})$ is the pushforward measure defined by $f_{\#}\nu(A) = \nu(f^{-1}(A))$ for all Borel sets $A \subseteq \mathbb{R}$ and a measurable function $f : \mathbb{R} \to \mathbb{R}$ (Rowland et al., 2018b). d is some distributional metric different in each method. In C51 d is KL divergence, in MMDQN d is Maximum Mean Discrepancy, while in QR-DQN and IQN d is Wasserstein metric, which is optimized approximately via quantile regression loss.

2.3 Hybrid Reward Architecture

HRA (Van Seijen et al., 2017) proposes the hybrid architecture to separately model the value function for each reward source. With multiple reward sources, we use $\boldsymbol{Q} : (\mathbb{R}^N)^{\mathcal{S} \times \mathcal{A}}$ and $Q_n : \mathbb{R}^{\mathcal{S} \times \mathcal{A}}$ to denote the vectored value function and the n-th value function respectively.

The loss used by HRA is given by:

$$L(\theta_i) = \mathbb{E}_{s_t,a_t,\boldsymbol{r}_t,s_{t+1}}[\|\boldsymbol{Q}(s_t, a_t; \theta_i) - \boldsymbol{y}_i\|_2^2], \tag{5}$$

$$\text{where } y_{i,n} = r_{t,n} + \gamma Q_n(s_{t+1}, a'; \theta_{i-1}), a' = \arg\max_{a'} Q_n(s_{t+1}, a'; \theta_{i-1}). \tag{6}$$

RD^2 (Lin et al., 2020) uses the similar hybrid architecture, which also learns the value function separately for each reward source, but with slight differences with HRA in how the next action a' is computed. The loss used by RD^2 is given by

$$L(\theta_i) = \mathbb{E}_{s_t,a_t,\boldsymbol{r}_t,s_{t+1}}[\|\boldsymbol{Q}(s_t, a_t; \theta_i) - \boldsymbol{y}_i\|_2^2], \tag{7}$$

$$\text{where } \boldsymbol{y}_i = \boldsymbol{r} + \gamma \boldsymbol{Q}(s_{t+1}, a'; \theta_{i-1}), a' = \arg\max_{a'} \sum_{n=1}^{N} Q_n(s_{t+1}, a'; \theta_{i-1}). \tag{8}$$

3 Hybrid Reward Distributional Reinforcement Learning

In this paper, we propose to capture the correlated randomness from multiple reward sources, forcing the agent to gain more knowledge about the environment and learn better representations. Specifically, we consider the joint distribution of returns from different reward sources. First, we introduce the joint distributional bellman operator and establish its convergence. We correct the misunderstanding in existing work (Bellemare et al., 2017; Nguyen et al., 2020), that we must use the same metric for proving convergence and as training loss. We illustrate that, once the convergence of the Bellman operator is proved under a certain metric, we can use other metrics than the metric for proving convergence, as training loss to approximate the Bellman operator. Second, we introduce an empirical algorithm, which approximates the Bellman operator through stochastic optimization with deep neural networks. Inspired by MMDQN (Nguyen et al., 2020), we introduce a temporal difference loss based on Maximum Mean Discrepancy over joint return distributions. Finally, we give full implementation details of our method, including network architectures and algorithms.

---

[1] In practical implementations, the iterative process is approximated by substituting θ_{i-1} by the parameter of the target network which tracks the exponential moving average of the online network parameters θ_i.

3.1 Definitions and Settings

We consider the joint return under policy π as a random vector $\boldsymbol{Z}^\pi(s,a)$ composed of N random variables $\boldsymbol{Z}^\pi(s,a) = (Z_1^\pi(s,a), \cdots, Z_N^\pi(s,a))^\top$:

$$\boldsymbol{Z}^\pi(s,a) = \sum_{t=0}^\infty \gamma^t \boldsymbol{r}_t, \tag{9}$$

$$\text{where } s_0 = s, a_0 = a, \boldsymbol{r}_t \sim R(\cdot|s_t, a_t), s_{t+1} \sim P(\cdot|s_t, a_t), a_{t+1} \sim \pi(\cdot|s_{t+1}). \tag{10}$$

Here $Z_i^\pi(s,a)$ denotes the i-th dimension of $\boldsymbol{Z}^\pi(s,a)$, which is the random variable of the i-th source of discounted return. Here the random variables of different sources of discounted return can be correlated. We denote the distribution of $\boldsymbol{Z}^\pi$ as $\boldsymbol{\mu}^\pi = \text{Law}(\boldsymbol{Z}^\pi)$, and the distribution of i-th random variable Z_i^π as $\mu_i^\pi = \text{Law}(Z_i^\pi)$, where $\boldsymbol{\mu}^\pi \in \mathcal{P}(\mathbb{R}^N)^{\mathcal{S} \times \mathcal{A}}$ and $\mu_i^\pi \in \mathcal{P}(\mathbb{R})^{\mathcal{S} \times \mathcal{A}}$. We let $\boldsymbol{\mu} \in \mathcal{P}(\mathbb{R}^N)^{\mathcal{S} \times \mathcal{A}}$ to denote arbitrary joint distribution over all state-action pairs, and the goal of our algorithm is to let the joint distribution $\boldsymbol{\mu}$ to be as close to the joint distribution $\boldsymbol{\mu}^\pi$ as possible in policy evaluation setting, i.e. to model the real joint return distribution.

To measure how close two N-dimensional joint distributions are, we adopt the Wasserstein metric W_p. For two joint distributions $\nu_1, \nu_2 \in \mathcal{P}(\mathbb{R}^N)$, the p-Wasserstein metric $W_p(\nu_1, \nu_2)$ on Euclidean distance d is given by:

$$W_p(\nu_1, \nu_2) = \left(\inf_{f \in \Gamma(\nu_1, \nu_2)} \int_{\mathbb{R}^N \times \mathbb{R}^N} d(x,y)^p f(x,y) d^N x d^N y \right)^{1/p}, \tag{11}$$

where $\Gamma(\nu_1, \nu_2)$ is the collection of all distributions with marginal distributions ν_1 and ν_2 on the first and second N random variables respectively. The Wasserstein distance can be interpreted as the minimum moving distance to move all the mass from distribution ν_1 to distribution ν_2.

We further define the supremum-p-Wasserstein distance on $\mathcal{P}(\mathbb{R}^N)^{\mathcal{S} \times \mathcal{A}}$ by

$$\bar{d}_p(\boldsymbol{\mu}_1, \boldsymbol{\mu}_2) := \sup_{s,a} W_p(\boldsymbol{\mu}_1(s,a), \boldsymbol{\mu}_2(s,a)), \tag{12}$$

where $\boldsymbol{\mu}_1, \boldsymbol{\mu}_2 \in \mathcal{P}(\mathbb{R}^N)^{\mathcal{S} \times \mathcal{A}}$.

We will use $\bar{d}_p$ to establish the convergence of the joint distributional Bellman operator.

3.2 Convergence of the Joint Distributional Bellman Operator

We define the joint distributional Bellman evaluation operator $\mathcal{T}^\pi$ as

$$\mathcal{T}^\pi \boldsymbol{\mu}(s_t, a_t) \overset{D}{:=} \int_{\mathcal{S}} \int_{\mathcal{A}} \int_{\mathbb{R}^N} (f_{\boldsymbol{r}_t, \gamma})_\# \boldsymbol{\mu}(s_{t+1}, a_{t+1}) R(d\boldsymbol{r}_t|s_t, a_t) \pi(da_{t+1}|s_{t+1}) P(ds_{t+1}|s_t, a_t), \tag{13}$$

where $f_{\boldsymbol{r}, \gamma}(\boldsymbol{x}) = \boldsymbol{r} + \gamma \boldsymbol{x}$, where $\boldsymbol{x}, \boldsymbol{r} \in \mathbb{R}^N$ and $f_\# \boldsymbol{\mu}$ is the pushforward measure which is a N-dimensional extension of the pushforward measure defined in Rowland et al. (2018b). The below theorem shows that $\mathcal{T}^\pi$ is a γ-contraction operator on $\bar{d}_p$.

Theorem 1 *For two joint distributions $\boldsymbol{\mu}_1$ and $\boldsymbol{\mu}_2$, we have*

$$\bar{d}_p(\mathcal{T}^\pi \boldsymbol{\mu}_1, \mathcal{T}^\pi \boldsymbol{\mu}_2) \leq \gamma \bar{d}_p(\boldsymbol{\mu}_1, \boldsymbol{\mu}_2). \tag{14}$$

We consider the following scenario: initially we have a joint distribution $\boldsymbol{\mu}_0 \in \mathcal{P}(\mathbb{R}^N)^{\mathcal{S} \times \mathcal{A}}$ over all state-action pairs, and by iteratively applying the Bellman evaluation operator, we get $\boldsymbol{\mu}_{i+1} = \mathcal{T}^\pi \boldsymbol{\mu}_i$. According to Banach's fixed point theorem, operator $\mathcal{T}^\pi$ has a unique fixed point, which is $\boldsymbol{\mu}^\pi$ by definition. The distance between $\boldsymbol{\mu}_i$ and $\boldsymbol{\mu}^\pi$ decays as i increases. We have the following proposition:

Proposition 1 *If $\boldsymbol{\mu}_{i+1} = \mathcal{T}^\pi \boldsymbol{\mu}_i$, then as $i \to \infty$, $\boldsymbol{\mu}_i \to \boldsymbol{\mu}^\pi$.*

We also provide contraction proof on the expectation of the optimality operator. The joint distributional Bellman optimality operator $\mathcal{T}$ is defined as

$$\mathcal{T}\boldsymbol{\mu}(s_t, a_t) \overset{D}{:=} \int_{\mathcal{S}} \int_{\mathbb{R}^N} (f_{\boldsymbol{r}_t, \gamma})_{\#} \boldsymbol{\mu}(s_{t+1}, a') R(d\boldsymbol{r}_t | s_t, a_t) P(ds_{t+1} | s_t, a_t), \tag{15}$$

$$\text{where } a' \in \arg\max_{a'} \mathbb{E}_{\boldsymbol{Z} \sim \boldsymbol{\mu}(s_{t+1}, a')} \sum_{n=1}^{N} Z_n \text{ and } Z_n \text{ is the } n\text{-th element in } \boldsymbol{Z}. \tag{16}$$

Theorem 2 *For two joint distributions $\boldsymbol{\mu}_1$ and $\boldsymbol{\mu}_2$, we have*

$$||(\mathbb{E}_{\sum})(\mathcal{T}\boldsymbol{\mu}_1) - (\mathbb{E}_{\sum})(\mathcal{T}\boldsymbol{\mu}_2)||_\infty \leq \gamma ||(\mathbb{E}_{\sum})\boldsymbol{\mu}_1 - (\mathbb{E}_{\sum})\boldsymbol{\mu}_2||, \tag{17}$$

where the operator $\mathbb{E}_{\sum}$ is defined by $\left(\mathbb{E}_{\sum}\right)\boldsymbol{\mu}(s,a) = \mathbb{E}_{\boldsymbol{Z} \sim \boldsymbol{\mu}(s,a)} \sum_{n=1}^{N} Z_n$ for any (s,a), and Z_n is the n-th element in $\boldsymbol{Z}$. The operator $\mathbb{E}_{\sum}$ converts the joint distribution over all state-action pairs to the corresponding total expected returns over all state-action pairs.

Proposition 2 *If $\boldsymbol{\mu}_{i+1} = \mathcal{T}\boldsymbol{\mu}_i$, then as $i \to \infty$, $\mathbb{E}_{\boldsymbol{Z} \sim \boldsymbol{\mu}_i(s,a)} \sum_{n=1}^{N} Z_n \to Q^*(s,a)$ for all (s,a).*

Proposition 2 can be interpreted as follows: as we iteratively apply the joint distributional Bellman optimality operator, the expected total return of the joint distribution $\boldsymbol{\mu}_i$ will converge to optimal value function. We refer the readers to the appendix for detailed proofs for all the lemmas, theorems, and propositions.

There is a common misunderstanding in existing work that we must use the same metric to prove convergence and as training loss (Bellemare et al., 2017; Nguyen et al., 2020). We clarify that the metric for proving convergence and the metric for training loss play different roles, and are not necessarily the same metric. For example, supremum Cramer distance is used to prove the contraction property of the projected Bellman operator in C51 (Rowland et al., 2018a). The contraction property leads to the convergence property. KL-divergence is used to approximate the projected operator in C51 (Bellemare et al., 2017). With infinite sampled transitions and expressive value networks, we can approximate the projected operator exactly when the KL-divergence over current distribution and its Bellman target is minimized. This may partially explain why replacing KL-divergence with Crame loss does not lead to improvement in performance (Bellemare et al., 2019).

3.3 Optimizing MMD as approximation for Bellman Operater

In practical algorithms, the joint distribution $\boldsymbol{\mu}_i(s,a)$ is represented by deep neural network $\boldsymbol{\mu}(s,a;\theta_i)$ which outputs joint distribution for each state-action pair with parameter θ_i. In the $(i+1)$-th iteration, we can only adapt the parameter θ_{i+1} of the model, and cannot directly apply the Bellman operator as in the tabular case. Moreover, we only have sampled transitions, rather the environment dynamics model P. It is desirable to choose a loss that is compatible with stochastic optimization, as an approximation for the Bellman operator.

We achieve this by minimizing the Maximum Mean Discrepancy (MMD) between joint distribution $\boldsymbol{\mu}_{i+1}$ and $\mathcal{T}\boldsymbol{\mu}_i$, which is defined as the equation below.

$$\text{MMD}^2(p, q; k) = \mathbb{E}_{x,x' \sim p} k(x, x') - 2\mathbb{E}_{x \sim p, y \sim q} k(x, y) + \mathbb{E}_{y,y' \sim q} k(y, y'), \tag{18}$$

where $k(\cdot, \cdot)$ is some kernel function and MMD is defined upon k, and each pair of random variable $(x, x'), (x, y), (y, y')$ are independent. In our scenario, we use $\text{MMD}^2(\boldsymbol{\mu}_{i+1}(s,a), \mathcal{T}\boldsymbol{\mu}_i(s,a))$ as the temporal difference loss. The reason why we choose MMD as the objective function is that MMD is both a metric on distribution and easy to optimize with sampled transitions. The original paper of MMD (Gretton et al., 2012) proves that MMD is a metric on distribution when kernel k is characteristic, from which we can prove that

$$\boldsymbol{\mu}_{i+1} = \mathcal{T}\boldsymbol{\mu}_i \iff \forall (s,a) \in \mathcal{S} \times \mathcal{A}, \text{MMD}^2(\boldsymbol{\mu}_{i+1}(s,a), \mathcal{T}\boldsymbol{\mu}_i(s,a); k) = 0, \tag{19}$$

when the kernel k is characteristic. If the MMD metric is optimized to zero and the appropriate kernel is selected, Z_{i+1} is the result of exactly applying the joint distributional Bellman operator. We refer readers to Section 3.4 where we detail how we choose our kernel function.

Next, we establish the method to optimize $\text{MMD}^2(\boldsymbol{\mu}_{i+1}(s,a), \mathcal{T}\boldsymbol{\mu}_i(s,a))$ with transition samples. Note that we use $\boldsymbol{\mu}(s,a;\theta_i)$ to represent $\boldsymbol{\mu}_i(s,a)$, so the temporal difference loss can also be written as $\text{MMD}^2(\boldsymbol{\mu}(s,a;\theta_{i+1}), \mathcal{T}\boldsymbol{\mu}(s,a;\theta_i))$. We use equation (18) to estimate the gradient of this squared MMD loss with respect to parameter θ_{i+1}. Specifically, the first term in equation (18) can be unbiasedly estimated by drawing multiple independent samples from joint distribution $\boldsymbol{\mu}(s,a;\theta_{i+1})$; the second term of equation (18) can be unbiasedly estimated by drawing independent samples from joint distribution $\boldsymbol{\mu}(s,a;\theta_{i+1})$ and from $\mathcal{T}\boldsymbol{\mu}(s,a;\theta_i)$. From transition sample $(s,a,\boldsymbol{r},s')$, we can prove that by computing the action $a' = \arg\max_{a'}(E_{\sum})\boldsymbol{\mu}(s',a';\theta_i)$ which is the action that maximizes expected return in state s', samples from $f_{\boldsymbol{r},\gamma}(\mu(s',a';\theta_i))$ follows the distribution $\mathcal{T}\boldsymbol{\mu}(s,a;\theta_i)$, and the complete proof is provided in the proof section of the appendix. For the third term in equation (18), it has no gradient with respect to the parameter θ_{i+1}, and we can safely ignore it during optimization. In summary, the temporal difference loss MMD^2 can be optimized without bias by transition samples, and Algorithm 1 summarizes the above analysis and shows details on how our method computes the gradient estimates of the temporal difference loss MMD^2.

Algorithm 1 Gradient estimation of MMD^2 loss by transition samples

---

Require: Number of samples M, kernel k, discount factor $\gamma \in (0,1)$
Require: Joint distribution network $\boldsymbol{\mu}(s,a;\theta)$
Input: Transition sample $(s,a,\boldsymbol{r},s')$
Input: Online network parameter θ, target network parameter θ'
Output: Gradient estimation of MMD with respect to θ

1: $a' \leftarrow \arg\max_{a'} \frac{1}{M}\sum_{m=1}^{M}\sum_{n=1}^{N}(\boldsymbol{Z}_m)_n$, where $\boldsymbol{Z}_{1:M} \overset{i.i.d.}{\sim} \boldsymbol{\mu}(s',a';\theta')$.
2: Sample $\boldsymbol{Z}_{1:M} \overset{i.i.d.}{\sim} \boldsymbol{\mu}(s,a;\theta)$
3: Sample $\boldsymbol{Z}_{1:M}^{next} \overset{i.i.d.}{\sim} \boldsymbol{\mu}(s',a';\theta')$
4: $\boldsymbol{Y_i} \leftarrow \boldsymbol{r} + \gamma\boldsymbol{Z}_i^{next}$, for every $1 \le i \le M$
5: $\text{MMD}^2 \leftarrow \sum_{1 \le i \le M}\sum_{1 \le j \le M, j \ne i}\left[k(\boldsymbol{Z}_i,\boldsymbol{Z}_j) - 2k(\boldsymbol{Z}_i,\boldsymbol{Y}_j) + k(\boldsymbol{Y}_i,\boldsymbol{Y}_j)\right]$
6: **return** $\nabla_\theta \text{MMD}^2$

3.4 Network Architecture and Implementation Details

For a given state-action pair (s,a), we use the value network of DQN (Mnih et al., 2013) to compute the low-dimensional (512d) embedding of state s, and replace the final layer of DQN network to output a vector with $M \times N \times |\mathcal{A}|$ dimensions, representing M samples from the joint return distribution from N reward sources for every action.

We follow the kernel selection in MMDQN (Nguyen et al., 2020) and apply the Gaussian kernel function with mixed bandwidth[2].

$$k(x,x') = \sum_{i=1}^{B} k_{b_i}(x,x'), \tag{20}$$

$$\text{where } k_b(x,x') = e^{-\frac{\|x-x'\|_2^2}{b}}. \tag{21}$$

It is worth noting that when the bandwidth $b_i > 0$ is too small or too large, the kernel function converges to 0 or 1 respectively and the gradients for MMD converge to zero. We choose the value of bandwidth b_i with diverse ranges, to make sure that all scales of reward don't suffer from gradient vanishing.

4 Related Work

Distributional RL algorithms propose to model the entire distribution, rather than the expectation, of the random variable return. C51 (Bellemare et al., 2017) is the first distributional RL algorithm, and establishes the convergence of distributional RL algorithms based on the contraction property

---

[2]Guassian kernel proved to be characteristic (Gretton et al., 2012), so the MMD distance with Gaussian kernel is a metric. It follows that when we use Gaussian kernels with mixed bandwidth, equation (19) still holds.

of the distributional Bellman operator. To approximate such an operator with sample transitions, different distributional algorithms employ different losses over distribution, along with different parameterization for distribution. C51 uses KL-divergence as loss and categorical distribution as parameterization. QR-DQN (Dabney et al., 2018b) takes quantile regression as surrogate loss for the Wasserstein metric, and approximates a set of quantile values with fixed probabilities. IQN (Dabney et al., 2018a) and FQF (Yang et al., 2019) extend QR-DQN to learn with sampled probabilities and self-adjusted probabilities. The current SOTA method in distributional RL is MMDQN (Nguyen et al., 2020), which takes MMD loss with a non-parametric approach by modeling deterministic samples from return distribution. Our method extends the theoretical work of C51, and the empirical algorithm of MMDQN to multi-dimensional returns. While distributional RL algorithms focus on capturing the randomness in return, our method first proposes to capture the correlation between different randomness from different reward sources.

HRA (Van Seijen et al., 2017) proposes a hybrid architecture to separately model the value functions for different sources of rewards. Their work provides empirical justification that learning with hybrid rewards can improve sample efficiency. HRA is built upon the Horde architecture (Sutton et al., 2011b), which trains a separate general value function (GVF) for each pseudo-reward function. The Horde architecture uses a large number of GVFs to model general knowledge about the environment. Previous works on reward decomposition also demonstrate that it is beneficial to learn with multiple reward functions (Lin et al., 2020). Based on HRA, our method further considers the correlated randomness in hybrid-source returns with a joint distribution model.

By modeling the joint return distribution, we provide an informative target to learn, which can be seen as auxiliary tasks. Previous works in RL have constructed various auxiliary tasks to learn better representations, such as methods based on temporal structures (Aytar et al., 2018) and local spatial structures (Anand et al., 2019). Compared with these methods, our method does not entirely focus on learning better state representations. The learned joint distribution is also beneficial to risk-sensitive tasks (Zhang et al., 2020). Besides, our method for learning the joint distribution of multi-dimensional random variables is general, and can be further combined with goal-conditioned RL (Schaul et al., 2015) or successor representation (Kulkarni et al., 2016) to capture correlated randomness in achieving different goals or visiting different states.

5   Experimental Results

In our experiments, we provide empirical results to answer the following questions:

- On policy evaluation settings, can MD3QN accurately model the joint distribution of multiple reward sources?

- On policy optimization settings, can MD3QN learn a better policy compared to HRA and distributional RL algorithm on environments with multiple reward sources?

To answer the first question, we design a maze environment with a rich way to generate correlated sources of rewards, and compare the joint distribution predicted by our method with the true joint distribution Z^π. The detailed setting of the environment and results is shown in Section 5.1.

To answer the second question, we use several Atari games with multiple reward sources, and provide training curve results of MD3QN compared to previous work HRA which deals with multiple reward sources. The detailed setting of the environment and results is shown in Section 5.2.

5.1   Modeling joint return distribution for multiple reward sources

In this experiment, we validate the capacity of MD3QN to model the joint return distribution for multiple sources of rewards on the policy evaluation setting with pixel inputs. The experiment is performed on the maze environments with rich reward correlation signals described as follows.

Figure 1 illustrates three maze environments with different reward correlation properties. The agent (represented by the triangle) is initially located at a specific position in the maze, and the policy π is a fixed policy to uniformly choose one direction at random and try to move. If the agent is blocked

(a)   (b)   (c)

Figure 1: Observation of initial states in maze environments. (a): maze environment "maze-exclusive" with two exclusive sources of rewards. (b): maze environment "maze-identical" with two positively correlated sources of rewards. (c): maze environment "maze-multireward" with four correlated sources of rewards.

by the walls in that direction[3], or the agent is trying to return to a previous position, the move has no effect, otherwise, the agent moves in that direction for one block. Each color of the square in the maze represents one source of reward. When the agent reaches the position with reward, it receives a reward of the source aligned with the color of the square[4]. The rules described above are general enough to enable the design of diversely correlated sources of rewards detailed below.

Figure 1(a) shows a maze environment with two exclusive sources of rewards. Once the agent obtains a reward from one side, it cannot obtain the reward from the other side. Figure 1(b) shows a maze environment with two positively correlated sources of rewards, where the agent either gets no reward or gets both of the red and green rewards. Figure 1(c) shows a maze environment with four correlated sources of rewards. In these three environments, the agent needs to capture the negative correlation, positive correlation, and the complex correlation in multi-dimensional rewards respectively to precisely model the joint return distribution.

On each of the three mazes, we train the MD3QN agent for 5 iterations (1.25M frames) to model the joint distribution of all reward sources, and compare the prediction of joint distribution by the model to the samples from the true distribution Z^π on the initial state of the maze. The results are shown in Figure 2, where each point in the figure is a sample representing one possibility of future discounted return in each reward source. The result shows that MD3QN accurately models the joint return distribution from different sources of reward. It is also worth noting that the observation for the agent is based on pixels, computed by downsampling the image in Figure 1 to the size of 84×84, which requires the agent to extract information on high-dimensional inputs.

5.2 Performance on Atari Games

In this experiment, we compare MD3QN algorithm with Hybrid Reward Architecture (HRA) (Van Seijen et al., 2017) on Atari games from Arcade Learning Environment (Bellemare et al., 2013). Our implementation of MD3QN is built upon the Dopamine framework (Castro et al., 2018). The hyperparameter settings used by MD3QN and HRA, and the environment settings are detailed in the appendix.

We use four Atari games with multiple sources of rewards: Gopher, MsPacman, UpNDown, and Pong. In all of these four games, the primitive rewards can be extracted from multiple sources of rewards:

- In Gopher, the agent gets +80 reward for killing a monster and gets +20 reward for removing holes on the ground.

- In MsPacman, the agent gets {+200, +400, +800, +1600} reward for killing a monster and gets +10 reward for eating beans.

---

[3]Colored walls can only be passed in one way, where yellow walls can be passed from the top or from the left, and red walls can be passed from the bottom or from the right.

[4]More detailed description of how reward is set in these three environments is provided in the appendix.

Figure 2: Comparison between samples from joint distribution by MD3QN and samples from the true distribution Z^π in three maze environments. The number of samples is set to be 200. (a): the result of "maze-exclusive" environment. (b): the result of "maze-identical" environment. (c): the result of "maze-multireward" environment of orange and blue reward sources. (d): the result of "maze-multireward" environment of green and red reward sources.

Figure 3: Performance of MD3QN on Atari games compared to HRA.

- In UpNDown, the agent gets +400 reward for killing an enemy car, +100 reward for reaching a flag, and +10 reward for being alive.

- In Pong, the agent gets +1 reward for winning a round, and gets -1 reward for losing a round.

We split the primitive rewards into multiple sources of reward according to how rewards are composed described above, and meanwhile keeping the total reward not changed. The training curves of HRMMD compared to HRA are shown in Figure 3.

We also provide case studies for joint distributional modeling by MD3QN on Atari games in the appendix. In both Gopher with positive-correlated sources of reward and Pong with independent sources of reward, MD3QN correctly captures the correlation between different reward sources.

6   Conclusions

In this work, we have proposed Multi-Dimensional Distributional DQN (MD3QN), a distributional RL method that learns a multi-dimensional joint return distribution for multiple sources of rewards. The effectiveness of our method is verified on pixel-input environments in terms of both the quality of modeled joint distribution, and the final performance of learnt policies.

In the future, it is possible to extend our framework to model the correlated randomness in achieving different goals with goal-conditioned RL, and in visiting different states with successor representation. We will leverage such informative modeling of the environment in terms of goals and successor states to develop novel RL algorithms in our future work.

References

Anand, A., Racah, E., Ozair, S., Bengio, Y., Côté, M.-A., and Hjelm, R. D. (2019). Unsupervised state representation learning in atari. In *Advances in Neural Information Processing Systems*, pages 8769–8782.

Aytar, Y., Pfaff, T., Budden, D., Paine, T., Wang, Z., and de Freitas, N. (2018). Playing hard exploration games by watching youtube. In *Advances in Neural Information Processing Systems*, pages 2930–2941.

Bellemare, M. G., Dabney, W., and Munos, R. (2017). A distributional perspective on reinforcement learning. In *International Conference on Machine Learning*, pages 449–458. PMLR.

Bellemare, M. G., Naddaf, Y., Veness, J., and Bowling, M. (2013). The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47:253–279.

Bellemare, M. G., Roux, N. L., Castro, P. S., and Moitra, S. (2019). Distributional reinforcement learning with linear function approximation. In Chaudhuri, K. and Sugiyama, M., editors, *Proceedings of the Twenty-Second International Conference on Artificial Intelligence and Statistics*, volume 89 of *Proceedings of Machine Learning Research*, pages 2203–2211. PMLR.

Boutilier, C., Dearden, R., Goldszmidt, M., et al. (1995). Exploiting structure in policy construction. In *IJCAI*, volume 14, pages 1104–1113.

Castro, P. S., Moitra, S., Gelada, C., Kumar, S., and Bellemare, M. G. (2018). Dopamine: A Research Framework for Deep Reinforcement Learning.

Dabney, W., Ostrovski, G., Silver, D., and Munos, R. (2018a). Implicit quantile networks for distributional reinforcement learning. In *International conference on machine learning*, pages 1096–1105. PMLR.

Dabney, W., Rowland, M., Bellemare, M., and Munos, R. (2018b). Distributional reinforcement learning with quantile regression. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32.

Gretton, A., Borgwardt, K. M., Rasch, M. J., Schölkopf, B., and Smola, A. (2012). A kernel two-sample test. *The Journal of Machine Learning Research*, 13(1):723–773.

Kulkarni, T. D., Saeedi, A., Gautam, S., and Gershman, S. J. (2016). Deep successor reinforcement learning. *arXiv preprint arXiv:1606.02396*.

Lin, Z., Yang, D., Zhao, L., Qin, T., Yang, G., and Liu, T.-Y. (2020). Rd^2: Reward decomposition with representation decomposition. *Advances in Neural Information Processing Systems*, 33.

Mnih, V., Kavukcuoglu, K., Silver, D., Graves, A., Antonoglou, I., Wierstra, D., and Riedmiller, M. (2013). Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*.

Nguyen, T. T., Gupta, S., and Venkatesh, S. (2020). Distributional reinforcement learning via moment matching. *arXiv preprint arXiv:2007.12354*.

Rowland, M., Bellemare, M., Dabney, W., Munos, R., and Teh, Y. W. (2018a). An analysis of categorical distributional reinforcement learning. In Storkey, A. and Perez-Cruz, F., editors, *Proceedings of the Twenty-First International Conference on Artificial Intelligence and Statistics*, volume 84 of *Proceedings of Machine Learning Research*, pages 29–37. PMLR.

Rowland, M., Bellemare, M. G., Dabney, W., Munos, R., and Teh, Y. W. (2018b). An analysis of categorical distributional reinforcement learning.

Schaul, T., Horgan, D., Gregor, K., and Silver, D. (2015). Universal value function approximators. In *International conference on machine learning*, pages 1312–1320. PMLR.

Sutton, R. S., Modayil, J., Delp, M., Degris, T., Pilarski, P. M., White, A., and Precup, D. (2011a). Horde: A scalable real-time architecture for learning knowledge from unsupervised sensorimotor interaction. In *The 10th International Conference on Autonomous Agents and Multiagent Systems-Volume 2*, pages 761–768.

Sutton, R. S., Modayil, J., Delp, M., Degris, T., Pilarski, P. M., White, A., and Precup, D. (2011b). Horde: A scalable real-time architecture for learning knowledge from unsupervised sensorimotor interaction. In *The 10th International Conference on Autonomous Agents and Multiagent Systems - Volume 2*, AAMAS '11, page 761–768, Richland, SC. International Foundation for Autonomous Agents and Multiagent Systems.

Van Seijen, H., Fatemi, M., Romoff, J., Laroche, R., Barnes, T., and Tsang, J. (2017). Hybrid reward architecture for reinforcement learning. *arXiv preprint arXiv:1706.04208*.

Yang, D., Zhao, L., Lin, Z., Qin, T., Bian, J., and Liu, T.-Y. (2019). Fully parameterized quantile function for distributional reinforcement learning. In Wallach, H., Larochelle, H., Beygelzimer, A., d'Alché-Buc, F., Fox, E., and Garnett, R., editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc.

Zhang, J., Bedi, A. S., Wang, M., and Koppel, A. (2020). Cautious reinforcement learning via distributional risk in the dual domain.