COUNTERING ADVERSARIAL IMAGES USING INPUT TRANSFORMATIONS

ABSTRACT

This paper investigates strategies that defend against adversarial-example attacks on image-classification systems by transforming the inputs before feeding them to the system. Specifically, we study applying image transformations such as bit-depth reduction, JPEG compression, total variance minimization, and image quilting before feeding the image to a convolutional network classifier. Our experiments on ImageNet show that total variance minimization and image quilting are very effective defenses in practice, in particular, when the network is trained on transformed images. The strength of those defenses lies in their non-differentiable nature and their inherent randomness, which makes it difficult for an adversary to circumvent the defenses. *Our best defense eliminates* 60% *of strong white-box and* 90% *of strong black-box attacks by a variety of major attack methods.*

1 INTRODUCTION

As the use of machine intelligence increases in security-sensitive applications (Bojarski et al., 2016; Amodei et al., 2015), robustness has become a critical feature to guarantee the reliability of deployed machine-learning systems. Unfortunately, recent research has demonstrated that existing models are not robust to small, adversarially designed perturbations of the input (Biggio et al., 2013; Szegedy et al., 2014; Goodfellow et al., 2015; Kurakin et al., 2016a; Cisse et al., 2017a). Instances of this type of perturbation have been deployed to attack image classification services (Liu et al., 2016), speech recognition systems (Cisse et al., 2017a), and robot vision (Melis et al., 2017). The existence of these *adversarial examples* has motivated proposals for approaches that increase the robustness of learning systems to such examples (Papernot et al., 2016; Kurakin et al., 2016a; Cisse et al., 2017b).

The robustness of machine learning models to adversarial examples depends both on the properties of the model (*i.e.*, Lipschitzness) and on the nature of the problem considered, *e.g.*, on the input dimensionality and the Bayes error of the problem (Fawzi et al., 2015; 2016). Consequently, *defenses* that aim to increase robustness against adversarial examples fall in one of two main categories. The first category comprises *model-specific* strategies that enforce model properties such as invariance and smoothness via the learning algorithm or regularization schemes (Shaham et al., 2015; Kurakin et al., 2016a; Cisse et al., 2017b), potentially exploiting knowledge about the adversary's attack strategy (Goodfellow et al., 2015). The second category of defenses are *model-agnostic*: they try to remove adversarial perturbations from the input. For example, in the context of image classification, adversarial perturbations can be partly removed via JPEG compression (Dziugaite et al., 2016) or image re-scaling (Lu et al., 2017). Hitherto, none of these defenses has been shown to be very effective. Specifically, model-agnostic defenses appear too simple to remove adversarial perturbations from input images sufficiently. By contrast, model-specific defenses make strong assumptions about the nature of the adversary (*e.g.*, on the norm that the adversary minimizes or on the number of iterations it uses to generate the perturbation). Consequently, they do not satisfy Kerckhoffs (1883) principle: the adversary can alter its attack to circumvent such model-specific defenses.

In this paper, we focus on increasing the effectiveness of model-agnostic defense strategies by developing approaches that (1) remove the adversarial perturbations from input images, (2) maintain sufficient information in input images to correctly classify them, and (3) are still effective in settings in which the adversary has information on the defense strategy being used. We explore transformations based on image cropping and rescaling, bit-depth reduction, JPEG compression (Dziugaite et al., 2016), total variance minimization (Rudin et al., 1992), and image quilting (Efros & Free-

man, 2001). We show that these defenses can be surprisingly effective against existing attacks, in particular when the convolutional network is trained on images that are transformed in a similar way. The image transformations are good at countering the (iterative) fast gradient sign method (Kurakin et al., 2016a), Deepfool (Moosavi-Dezfooli et al., 2016), and the Carlini & Wagner (2017) attack, even in white-box settings in which the model architecture and parameters are public. Our strongest defenses are based on total variation minimization and image quilting: these defenses are non-differentiable and inherently random, which makes it difficult for an adversary to get around them. *Our best defenses eliminate* 60% *of white-box attacks and* 90% *of black-box attacks by four major attack methods that perturb pixel values by* 8% *on average.*

2 PROBLEM DEFINITION

We study defenses against non-targeted adversarial examples for image-recognition systems. Let $\mathcal{X} = [0, 1]^{H \times W \times C}$ be the image space. Given an image classifier $h(\cdot)$ and a source image $\mathbf{x} \in \mathcal{X}$, a *non-targeted*[1] *adversarial example* of $\mathbf{x}$ is a perturbed image $\mathbf{x}' \in \mathcal{X}$ such that $h(\mathbf{x}) \neq h(\mathbf{x}')$ and $d(\mathbf{x}, \mathbf{x}') \leq \rho$ for some dissimilarity function $d(\cdot, \cdot)$ and $\rho \geq 0$. Ideally, $d(\cdot, \cdot)$ measures the perceptual difference between $\mathbf{x}$ and $\mathbf{x}'$ but, in practice, the Euclidean distance $d(\mathbf{x}, \mathbf{x}') = \|\mathbf{x} - \mathbf{x}'\|_2$ or the Chebyshev distance $d(\mathbf{x}, \mathbf{x}') = \|\mathbf{x} - \mathbf{x}'\|_\infty$ is most commonly used.

Given a set of N images $\{\mathbf{x}_1, \ldots, \mathbf{x}_N\}$ and a target classifier $h(\cdot)$, an *adversarial attack* aims to generate $\{\mathbf{x}'_1, \ldots, \mathbf{x}'_N\}$ such that each $\mathbf{x}'_n$ is an adversarial example for $\mathbf{x}_n$. The *success rate* of an attack is measured by the proportion of predictions that was altered by an attack: $\frac{1}{N} \sum_{n=1}^{N} \mathbb{1}[h(\mathbf{x}_n) \neq h(\mathbf{x}'_n)]$. The success rate is generally measured as a function of the magnitude of the perturbations performed by the attack, using the *normalized L_2-dissimilarity*:

$$\frac{1}{N} \sum_{n=1}^{N} \frac{\|\mathbf{x}_n - \mathbf{x}'_n\|_2}{\|\mathbf{x}_n\|_2}. \tag{1}$$

A strong adversarial attack has a high success rate whilst its normalized L_2-dissimilarity is low.

In most practical settings, an adversary does not have direct access to the model $h(\cdot)$ and has to do a *black-box* attack. However, prior work has shown successful attacks by transferring adversarial examples generated for a separately-trained model to an unknown target model (Liu et al., 2016). Therefore, we investigate both the black-box and the more difficult *white-box* attack setting, in which the adversary knows the model architecture, the model parameters, and the defense strategy.

A *defense* is an approach that aims make the prediction on an adversarial example $h(\mathbf{x}')$ equal to the prediction on the corresponding clean example $h(\mathbf{x})$. In this study, we focus on *image-transformation defenses* $g(\mathbf{x})$ that perform prediction via $h(g(\mathbf{x}'))$. Ideally, $g(\cdot)$ is a complex, non-differentiable, and potentially stochastic function: this makes it difficult for an adversary to attack the prediction model $h(g(\mathbf{x}))$ even when the adversary knows both $h(\cdot)$ and $g(\cdot)$.

3 ADVERSARIAL ATTACKS

One of the first successful attack methods is the **fast gradient sign method** (FGSM; Goodfellow et al. (2015)). Let $\ell(\cdot, \cdot)$ be the differentiable loss function that was used to train the classifier $h(\cdot)$, *e.g.*, the cross-entropy loss. The FGSM adversarial example corresponding to a source input $\mathbf{x}$ is:

$$\mathbf{x}' = \mathbf{x} + \epsilon \cdot \text{sign}\left(\nabla_{\mathbf{x}} \ell(\mathbf{x}, h(\mathbf{x}))\right), \tag{2}$$

for some $\epsilon > 0$ that governs the perturbation magnitude. A stronger variant of this attack, called **iterative FGSM** (I-FGSM; Kurakin et al. (2016b)), iteratively applies the FGSM update:

$$\mathbf{x}^{(m)} = \mathbf{x}^{(m-1)} + \epsilon \cdot \text{sign}\left(\nabla_{\mathbf{x}^{(m-1)}} \ell(\mathbf{x}^{(m-1)}, h(\mathbf{x}))\right), \tag{3}$$

where $m = 1, \ldots, M$; $\mathbf{x}^{(0)} = \mathbf{x}$; and $\mathbf{x}' = \mathbf{x}^{(M)}$. The number of iterations M is set such that $h(\mathbf{x}') \neq h(\mathbf{x})$. Both FGSM and I-FGSM approximately minimize the Chebyshev distance between the inputs and the adversarial examples they generate.

---

[1]Given a target class c, a *targeted adversarial example* $\mathbf{x}'$ is an example that satisfies $h(\mathbf{x}') = c$. We do not consider targeted attacks in this study.

Figure 1: Adversarial images and corresponding perturbations at five levels of normalized L_2-dissimilarity for all four attacks.

Alternative attacks aim to minimize the Euclidean distance between the input and the adversarial example instead. For instance, assuming $h(\cdot)$ is a binary classifier, **DeepFool** (Moosavi-Dezfooli et al., 2016) projects $\mathbf{x}$ onto a linearization of the decision boundary defined by $h(\cdot)$ for M iterations:

$$\mathbf{x}^{(m)} = \mathbf{x}^{(m-1)} - \epsilon \cdot \frac{h(\mathbf{x}^{(m-1)})}{\|\nabla_{\mathbf{x}^{(m-1)}} h(\mathbf{x}^{(m-1)})\|_2^2} \nabla_{\mathbf{x}^{(m-1)}} h\left(\mathbf{x}^{(m-1)}\right), \tag{4}$$

where $\mathbf{x}^{(0)}$ and $\mathbf{x}'$ are defined as in I-FGSM. The multi-class variant of DeepFool performs the projection onto the nearest class boundaries. The linearization performed in DeepFool is particularly well suited for ReLU-networks, as these represent piecewise linear class boundaries.

Carlini-Wagner's L_2 attack (CW-L2; Carlini & Wagner (2017)) is an optimization-based attack that combines a differentiable surrogate for the model's classification accuracy with an L_2-penalty term. Let $Z(\mathbf{x})$ be the operation that computes the logit vector (*i.e.*, the output before the softmax layer) for an input $\mathbf{x}$, and $Z(\mathbf{x})_k$ be the logit value corresponding to class k. The untargeted variant of CW-L2 finds a solution to the unconstrained optimization problem

$$\min_{\mathbf{x}'} \left[\|\mathbf{x} - \mathbf{x}'\|_2^2 + \lambda_f \max \left(-\kappa, Z(\mathbf{x}')_{h(\mathbf{x})} - \max\{Z(\mathbf{x}')_k : k \neq h(\mathbf{x})\} \right) \right], \tag{5}$$

where κ denotes a margin parameter, and where the parameter λ_f trades off the perturbation norm and the hinge loss of predicting a different class. We perform the minimization over $\mathbf{x}'$ using the Adam optimizer (Kingma & Ba, 2014) for 100 iterations with an initial learning rate of 0.001.

All of the aforementioned attacks enforce that $\mathbf{x}' \in \mathcal{X}$ by clipping values between 0 and 1. Figure 1 shows adversarial images produced by all four attacks at five normalized L_2-dissimilarity levels.

4 DEFENSES

Adversarial attacks alter particular statistics of the input image in order to change the model prediction. Indeed, adversarial perturbations $\mathbf{x} - \mathbf{x}'$ have a particular structure, as illustrated by Figure 1. We design and experiment with image transformations that alter the structure of these perturbations, and investigate whether the alterations undo the effects of the adversarial attack. We investigate five image transformations: (1) image cropping and rescaling, (2) bit-depth reduction, (3) JPEG compression, (4) total variance minimization, and (5) image quilting.

4.1 IMAGE CROPPING-RESCALING, BIT-DEPTH REDUCTION, AND COMPRESSION

We first introduce three simple image transformations: image cropping-rescaling, bit-depth reduction, and JPEG compression and de-compression (Dziugaite et al., 2016). *Image cropping-rescaling* has the effect of altering the spatial positioning of the adversarial perturbation, which is important in making attacks successful. Following He et al. (2016), we crop and rescale images at training time as part of the data augmentation. At test time, we average predictions over random image crops. *Bit-depth reduction* perform a simple type of quantization that can removes small (adversarial) variations in pixel values from an image; we reduce images to 3 bits in our experiments. *JPEG compression* (Dziugaite et al., 2016) removes small (adversarial) perturbations in a similar way; we perform compression at quality level 75 (out of 100).

Figure 2: Illustration of total variance minimization and image quilting applied to an original and an adversarial image (produced using I-FGSM with $\epsilon = 0.03$, corresponding to a normalized L_2-dissimilarity of 0.075). From left to right, the columns correspond to: (1) no transformation, (2) total variance minimization, and (3) image quilting. From top to bottom, rows correspond to: (1) the original image, (2) the corresponding adversarial image produced by I-FGSM, and (3) the absolute difference between the two images above. Difference images were multiplied by a constant scaling factor to increase visibility.

4.2 TOTAL VARIANCE MINIMIZATION

An alternative way of removing adversarial perturbations is via a compressed sensing approaches that combine pixel dropout with total variation minimization (Rudin et al., 1992). This approach randomly selects a small set of pixels, and reconstructs the "simplest" image that is consistent with the selected pixels. The reconstructed image does not contain the adversarial perturbation because these perturbations tend to be small and localized.

Specifically, we first select a random set of pixels by sampling a Bernoulli random variable $X(i, j, k)$ for each pixel location (i, j, k); we maintain a pixel when $X(i, j, k) = 1$. Next, we use total variation minimization to constructs an image $\mathbf{z}$ that is similar to the (perturbed) input image $\mathbf{x}$ for the selected set of pixels, whilst also being "simple" in terms of total variation by solving:

$$\min_{\mathbf{z}} \|(1 - X) \odot (\mathbf{z} - \mathbf{x})\|_2 + \lambda_{\mathrm{TV}} \cdot \mathrm{TV}_p(\mathbf{z}). \tag{6}$$

Herein, $\odot$ denotes element-wise multiplication, and $\mathrm{TV}_p(\mathbf{z})$ represents the L_p-total variation of $\mathbf{z}$:

$$\mathrm{TV}_p(\mathbf{z}) = \sum_{k=1}^{K} \left[\sum_{i=2}^{N} \|\mathbf{z}(i, :, k) - \mathbf{z}(i - 1, :, k)\|_p + \sum_{j=2}^{N} \|\mathbf{z}(:, j, k) - \mathbf{z}(:, j - 1, k)\|_p \right]. \tag{7}$$

The total variation (TV) measures the amount of fine-scale variation in the image $\mathbf{z}$, as a result of which TV minimization encourages removal of small (adversarial) perturbations in the image. The objective function (6) is convex in $\mathbf{z}$, which makes solving for $\mathbf{z}$ straightforward. In our implementation, we set $p = 2$ and employ a special-purpose solver based on the split Bregman method (Goldstein & Osher, 2009) to perform total variance minimization efficiently.

The effectiveness of TV minimization is illustrated by the images in the middle column of Figure 2: in particular, note that the adversarial perturbations that were present in the background for the non-transformed image (see bottom-left image) have nearly completely disappeared in the TV-minimized adversarial image (bottom-center image). As expected, TV minimization also changes image structure in non-homogeneous regions of the image, but as these perturbations were not adversarially designed we expect the negative effect of these changes to be limited.

Figure 3: Top-1 classification accuracy of ResNet-50 *tested* on transformed adversarial images produced by four attacks using five image transformations *in a white-box setting*: (1) cropping-rescaling, (2) bit-depth reduction, (3) JPEG compression, (4) total variance minimization, and (5) image quilting. The dotted line shows the top-1 accuracy of the ResNet-50 model on non-adversarial images, providing an upper bound on the effectiveness of a defense. Higher is better.

4.3 IMAGE QUILTING

Image quilting (Efros & Freeman, 2001) is a non-parametric technique that synthesizes images by piecing together small patches that are taken from a database of image patches. The algorithm places appropriate patches in the database for a predefined set of grid points, and computes minimum graph cuts (Boykov et al., 2001) in all overlapping boundary regions to remove edge artifacts.

Image quilting can be used to remove adversarial perturbations by constructing a patch database that only contains patches from "clean" images (without adversarial perturbations); the patches used to create the synthesized image are selected by finding the K nearest neighbors (in pixel space) of the corresponding patch from the adversarial image in the patch database, and picking one of these neighbors uniformly at random. The motivation for this defense is that the resulting image only consists of pixels that were not modified by the adversary — the database of real patches is unlikely to contain the structures that appear in adversarial images.

The right-most column of Figure 2 illustrates the effect of image quilting on adversarial images. Whilst interpretation of these images is more complicated due to the quantization errors that image quilting introduces, it is interesting to note that the absolute differences between quilted original and the quilted adversarial image appear to be smaller in non-homogeneous regions of the image. This suggests that TV minimization and image quilting lead to inherently different defenses.

5 EXPERIMENTS

We performed four experiments to test the efficacy of our defenses. The first experiment considers white-box attacks: it applies the defenses on adversarial images before using them as input into a convolutional network trained to classify "clean" images. The second experiment focuses on a black-box setting, employing convolutional networks that were trained on transformed images. The third experiment combines our defenses with ensembling and model transfer. The fourth experiment compares our defenses against prior work in a white-box setting. Code to reproduce our results is available at http://www.anonymized.com.

Figure 4: Top-1 classification accuracy of ResNet-50 *trained and tested* on transformed adversarial images produced by four attacks using five image transformations *in a black-box setting*: (1) cropping-rescaling, (2) bit-depth reduction, (3) JPEG compression, (4) total variance minimization, and (5) image quilting. The dotted line represents the top-1 accuracy of the ResNet-50 model on non-adversarial images, providing an upper bound on the effectiveness of a defense. Higher is better.

5.1 EXPERIMENTAL SETUP

We performed experiments on the ImageNet image classification dataset. The dataset comprises 1.2 million training images and $50,000$ test images that correspond to one of $1,000$ classes. Our adversarial images are produced by attacking a ResNet-50 model (He et al., 2016). We evaluate our defense strategies against the four adversarial attacks presented in Section 3. We measure the strength of an adversary in terms of its normalized L_2-dissimilarity and report classification accuracies as a function of the normalized L_2-dissimilarity. To produce adversarial images like those in Figure 1, we set the normalized L_2-dissimilarity for each of the attacks as follows:

- *FGSM.* Increasing the step size ϵ increases the normalized L_2-dissimilarity.

- *I-FGSM.* We fix $M = 10$, and increase ϵ to increase the normalized L_2-dissimilarity.

- *DeepFool.* We fix $M = 5$, and increase ϵ to increase the normalized L_2-dissimilarity.

- *CW-L2.* We fix $\kappa = 0$ and $\lambda_f = 10$, and multiply the resulting perturbation by an appropriately chosen $\epsilon \geq 1$ to alter the normalized L_2-dissimilarity.

We fixed the hyperparameters of our defenses in all experiments: specifically, we set pixel dropout probability $p = 0.5$ and the regularization parameter of the total variation minimizer $\lambda_{\text{TV}} = 0.03$. We use a quilting patch size of 5×5 and use the nearest neighbor patch (*i.e.* $K = 1$) for experiments in Sections 5.2 and 5.3, and select patches from one of $K = 10$ nearest neighbors in a database of $1,000,000$ patches for all other experiments. In the cropping defense, we sample 30 crops of size 90×90 from the 224×224 input image, rescale the crops to 224×224, and average the model predictions.

5.2 WHITE BOX: IMAGE TRANSFORMATIONS AT TEST TIME

Figure 3 shows the top-1 accuracy of a ResNet-50 tested on transformed adversarial images as a function of the adversary strength for each of the four attacks. Each plot shows results for five

	Quilting				TVM + Quilting				Cropping + TVM + Quilting			
	RN50	RN101	DN169	Iv4	RN50	RN101	DN169	Iv4	RN50	RN101	DN169	Iv4
No Attack	70.07	72.56	70.18	73.01	72.38	74.74	73.10	**75.55**	72.14	74.53	72.92	75.10
FGSM	65.45	68.50	65.96	67.53	65.70	68.77	67.09	69.19	66.65	69.75	67.86	**70.37**
I-FGSM	65.59	68.72	66.16	69.29	65.84	69.10	67.32	71.05	67.03	70.14	68.20	**71.52**
DeepFool	65.20	68.73	65.86	68.70	65.80	69.34	67.40	71.03	67.11	70.49	68.62	**71.47**
CW-L2	64.11	67.72	65.00	68.14	63.99	68.20	66.08	70.13	65.31	69.14	66.96	**70.50**

Table 1: Top-1 classification accuracy of ensemble and model transfer defenses (columns) against four black-box attacks (rows). The four networks we use to classify images are ResNet-50 (RN50), ResNet-101 (RN101), DenseNet-169 (DN169), and Inception-v4 (Iv4). Adversarial images are generated by running attacks against the ResNet-50 model, aiming for an average normalized L_2-dissimilarity of 0.06. Higher is better. The best defense against each attack is typeset in boldface.

different transformations we apply to the images at test time (*viz.*, image cropping-rescaling, bit-depth reduction, JPEG compression, total variation minimization, and image quilting). The dotted line shows the classification error of the ResNet-50 model on images that are not adversarially perturbed, *i.e.*, it gives an upper bound on the accuracy that defenses can achieve.

In line with the results reported in the literature, the four adversaries successfully attack the ResNet-50 model in nearly all cases (FGSM has a slightly lower favorable attack rate of $80-90\%$) when the input images are not transformed. The results also show that the proposed image transformations are capable of partly eliminating the effect of the attacks. In particular, ensembling 30 predictions over different, random image crops is very efficient: these predictions are correct for $40-60\%$ of the images (note that 76% is the highest accuracy that one can expect to achieve). This result suggests that adversarial examples are susceptible to changes in the location and scale of the adversarial perturbations. While not as effective, image transformations based on total variation minimization and image quilting also successfully defend against adversarial examples from all four attacks: applying these transformations allows us to classify $30-40\%$ of the images correctly. This result suggests that total variation minimization and image quilting can successfully remove part of the perturbations from adversarial images. In particular, the accuracy of the image-quilting defense hardly deteriorates as the strength of the adversary increases. However, the quilting transformation does severely impact the model's accuracy on non-adversarial images.

5.3 BLACK BOX: IMAGE TRANSFORMATIONS AT TRAINING AND TEST TIME

The high relative performance of image cropping-rescaling in 5.2 may be partly explained by the fact that the convolutional network was trained on randomly cropped-rescaled images[2], but not on any of the other transformations. This implies that independent of whether an image is adversarial or not, the network is more robust to image cropping-rescaling than it is to those transformations. The results in Figure 3 suggest that this negatively affects the effectiveness of these defenses, even if the defenses are successful in removing the adversarial perturbation. To investigate this, we trained ResNet-50 models on transformed ImageNet training images. Explicitly, we adopt the standard data augmentation from He et al. (2016), but apply bit-depth reduction, JPEG compression, TV minimization, or image quilting on the resized image crop before feeding it to the network. We measure the classification accuracy of the resulting networks on the same adversarial images as before. Note that this implies we move from a white-box to a black-box setting.

We present the results of these experiments in Figure 4. Training convolutional networks on images that are transformed in the same way as at test time, indeed, dramatically improves the effectiveness of all transformation defenses. In our experiments, the image-quilting defense is particularly effective against strong attacks: it successfully defends against $80-90\%$ of all four attacks, even when the normalized L_2-dissimilarity of the attack approaches 0.08.

5.4 BLACK BOX: ENSEMBLING AND MODEL TRANSFER

We evaluate the efficacy of (1) ensembling different defenses and (2) "transferring" attacks to different network architectures (in a black-box setting). Specifically, we measured the accuracy of four

---

[2]We trained the ResNet-50 model using the data-augmentation scheme of He et al. (2016).

networks using ensembles of defenses on adversarial images generated to attack a ResNet-50; the four networks we consider are ResNet-50, ResNet-101, DenseNet-169 (Huang et al., 2017), and Inception-v4 (Szegedy et al., 2017). Details describing our ensembling approaches are described in the supplemental material. The results of our experiments are presented in Table 1.

The results show that gains of $1-2\%$ in classification accuracy can be achieved by ensembling different defenses, whereas transferring attacks to different convolutional network architectures can lead to an improvement of $2-3\%$. Inception-v4 performs best in our experiments, but this may be partly due to that network having a higher accuracy even in non-adversarial settings (He et al., 2016). Our best black-box defense achieves a top-1 accuracy of approximately 71% against all four defenses: the attacks only deteriorate the accuracy of our image classifiers by about 6% by combining cropping, TV minimization, image quilting, and model transfer to Inception-v4.

5.5 WHITE BOX: IMAGE TRANSFORMATIONS AT TRAINING AND TEST TIME

The previous experiments have demonstrated the relative effectiveness of image transformations against black box adversarial attacks and against white box attacks when the target network is trained with usual data-augmentation procedures. We now test the robustness of our proposals against white box attacks where the target system (a ResNet-50) is trained on the same type of transformations used to defend against adversarial examples at test time (e.g., cropping, JPEG, TVM, quilting, etc.).

While one can expect that the use of the transformations both at training and testing time improves the performance of the model on legitimate examples, the behavior of the different defenses against white box attacks in this setting is more surprising. Indeed, bit-depth reduction and JPEG compression are poor defenses in this setting unless the norm of the perturbation is minimal (i.e., when normalized dissimilarity is smaller than 0.01). This observation is consistent across the various defenses. In contrast, cropping, TVM, and quilting are more robust and classify correctly more than 50% of the adversarial images when the L_2-dissimilarity is not larger than 0.03. Figure 5 displays the accuracy curves of each method across a range of L_2-dissimilarities for the various attacks we use.

Defending against white box attacks is a particularly challenging task. As we show in the next section, image transformations are a good candidate in this setting compared to the best existing methods, especially when the attack considered is iterative such as I-FGSM or Deepfool.

5.6 COMPARISON WITH PRIOR WORK

In a final set of experiments, we compare our defenses with prior work. The image transformations we propose in this work are model agnostic. However, we compare them with *ensemble adversarial training* (the current most efficient learning based defense) for the sake of completeness. Ensemble adversarial training fits the parameters of a given model by generating adversarial examples using an ensemble of pre-trained models. Therefore, the adversarial examples seen during training are diverse and do not overfit the decision boundaries of the model. In our experiments, we used the model released by Tramèr et al. (2017), which is an Inception-Resnet-v2 (Szegedy et al., 2016) trained with an ensemble of pre-trained models comprising an Inception-Resnet-v2 and an Inception-v3 against adversarial examples generated by FGSM. We compare it to a ResNet-50 using either *cropping ensemble, TVM, and quilting*. We use both one step and iterative attacks to assess the robustness of the compared approaches. The results are displayed in Table 2.

While ensemble adversarial training works better on FGSM attacks (which it uses at training time), it is vastly outperformed by each of the transformation-based defenses on the iterative attacks. In particular, when the attack used is Deepfool, TVM and cropping are about $\times 25$ more robust. In the same setting, quilting is $\times 20$ more robust than ensemble adversarial training. Additionally, when combining cropping, TVM and quilting, the accuracy on white box attacks with Deepfool increases to $\mathbf{51.51}\%$. In comparison, ensemble adversarial training only achieves $\mathbf{1.74}\%$ for the same attack. It is also worth noting that image transformations are orthogonal and complementary to adversarial training for defending against adversarial examples. One could combine both strategies to improve upon each of them. We leave this for future works.

	Cropping	TVM	Quilting	Ensemble Training (Tramèr et al., 2017)
No Attack	65.41	66.29	69.66	**80.3**
FGSM	49.52	31.37	39.55	**69.15**
I-FGSM	**43.89**	40.99	33.22	5.07
DeepFool	**44.92**	44.69	34.54	1.74
CW-L2	41.06	**48.41**	30.51	22.23

Table 2: Top-1 classification accuracy on images perturbed using white-box attacks against cropping-rescaling, total variation minimization, and image quilting on a ResNet-50 model, and ensemble adversarial training on Inception-v4. Adversarial images are generated by running attacks against the respective model, aiming for an average normalized L_2-dissimilarity of 0.06. The best defense against each attack is typeset in boldface.

Figure 5: Top-1 classification accuracy of ResNet-50 *trained and tested* on transformed adversarial images produced by four attacks using five image transformations *in a white-box setting*: (1) cropping-rescaling, (2) bit-depth reduction, (3) JPEG compression, (4) total variance minimization, and (5) image quilting. The dotted line represents the top-1 accuracy of the ResNet-50 model on non-adversarial images, providing an upper bound on the effectiveness of a defense. Higher is better.

6 DISCUSSION

The results from this study suggest there exists a range of image transformations that have the potential to remove adversarial perturbations while preserving the visual content of the image: one merely has to train the convolutional network on images that were transformed in the same way. A critical property that governs which image transformations are most effective *in practice* is whether an adversary can incorporate the transformation in its attack. For instance, median filtering likely is a weak remedy because one can backpropagate through the median filter, which is sufficient to perform any of the attacks described in Section 3. A strong input-transformation defense should, therefore, be non-differentiable and randomized. Our two best defenses possess both these properties:

1. Both total variation minimization and image quilting are difficult to differentiate through. Specifically, total variation minimization involves solving a complex minimization of a function that is inherently random. Image quilting involves a discrete variable that selects the patch from the database, which is a non-differentiable operation, and the graph-cut opti-

mization complicates the use of differentiable approximations akin to the Gumbel-softmax approximation (Maddison et al., 2017).

2. Both total variation minimization and image quilting give rise to *randomized* defenses. Total variation minimization randomly selects the pixels it uses to measure reconstruction error on when creating the denoised image. Following Efros & Freeman (2001), our implementation of image quilting randomly selects one of the K nearest neighbors uniformly at random. The inherent randomness of our defenses makes it difficult for an adversary to attack the model: it implies the adversary has to find a perturbation that alters the prediction for the entire distribution of images that could be used as input, which is harder than perturbing a single image (Moosavi-Dezfooli et al., 2017).

Our results with white-box attacks suggest that randomness is particularly crucial in developing strong defenses. Therefore, we surmise that total variation minimization, image quilting, and related methods (Dong et al., 2011) are stronger defenses than deterministic denoising procedures such as bit-depth reduction, JPEG compression, or non-local means (Buades, 2005). Defenses based on total variation minimization and image quilting also have an advantage over adversarial-training approaches (Kurakin et al., 2016a): an adversarially trained network is differentiable, which implies that it can be attacked using the methods in Section 3. An additional disadvantage of adversarial training is that it focuses on a particular attack; by contrast, transformation-based defenses generalize well across attack methods because they are model-agnostic.

While our study focuses exclusively on image classification, we expect similar defenses to be useful in other domains for which successful attacks have been developed, such as semantic segmentation and speech recognition (Cisse et al., 2017a; Zhang et al., 2017). In speech recognition, for example, total variance minimization can be used to remove perturbations from waveforms, and one could develop "spectrogram quilting" techniques that reconstruct a spectrogram by concatenating "spectrogram patches" along the temporal dimension. We leave such extensions to future work.

REFERENCES

Dario Amodei, Rishita Anubhai, Eric Battenberg, Carl Case, Jared Casper, Bryan Catanzaro, Jingdong Chen, Mike Chrzanowski, Adam Coates, Greg Diamos, et al. Deep Speech 2: End-to-end speech recognition in English and Mandarin. *arXiv preprint arXiv:1512.02595*, 2015.

Battista Biggio, Igino Corona, Davide Maiorca, Blaine Nelson, Nedim Šrndić, Pavel Laskov, Giorgio Giacinto, and Fabio Roli. Evasion attacks against machine learning at test time. In *Proc. ECML*, pp. 387–402, 2013.

Mariusz Bojarski, Davide Del Testa, Daniel Dworakowski, Bernhard Firner, Beat Flepp, Prasoon Goyal, Lawrence D Jackel, Mathew Monfort, Urs Muller, Jiakai Zhang, et al. End-to-end learning for self-driving cars. *arXiv preprint arXiv:1604.07316*, 2016.

Yuri Boykov, Olga Veksler, and Ramin Zabih. Fast approximate energy minimization via graph cuts. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 23(11):1222–1239, 2001.

Antoni Buades. A non-local algorithm for image denoising. *Proc. CVPR*, 2005.

Nicholas Carlini and David A. Wagner. Towards evaluating the robustness of neural networks. In *IEEE Symposium on Security and Privacy*, pp. 39–57, 2017.

Moustapha Cisse, Yossi Adi, Natalia Neverova, and Joseph Keshet. Houdini: Fooling deep structured prediction models. *arXiv preprint arXiv:1707.05373*, 2017a.

Moustapha Cisse, Piotr Bojanowski, Edouard Grave, Yann Dauphin, and Nicolas Usunier. Parseval networks: Improving robustness to adversarial examples. *arXiv preprint arXiv:1704.08847*, 2017b.

Weisheng Dong, Lei Zhang, and Guangming Shi. Centralized sparse representation for image restoration. 2011.

Gintare Karolina Dziugaite, Zoubin Ghahramani, and Daniel Roy. A study of the effect of JPG compression on adversarial images. *arXiv preprint arXiv:1608.00853*, 2016.

Alexei Efros and William Freeman. Image quilting for texture synthesis and transfer. In *Proc. SIGGRAPH*, pp. 341–346, 2001.

Alhussein Fawzi, Omar Fawzi, and Pascal Frossard. Analysis of classifiers' robustness to adversarial perturbations. *arXiv preprint arXiv:1502.02590*, 2015.

Alhussein Fawzi, Seyed-Mohsen Moosavi-Dezfooli, and Pascal Frossard. Robustness of classifiers: From adversarial to random noise. In *Advances in Neural Information Processing Systems*, pp. 1632–1640, 2016.

Tom Goldstein and Stanley Osher. The split Bregman method for L1-regularized problems. *SIAM J. Img. Sci.*, 2(2):323–343, April 2009.

Ian Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *Proc. ICLR*, 2015.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proc. CVPR*, pp. 770–778, 2016.

Gao Huang, Zhuang Liu, Kilian Weinberger, and Laurens van der Maaten. Densely connected convolutional networks. *Proc. CVPR*, 2017.

Auguste Kerckhoffs. La cryptographie militaire. *Journal des sciences militaires*, IX:5–83, 161–191, 1883.

Diederik Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *CoRR*, abs/1412.6980, 2014.

Alexey Kurakin, Ian Goodfellow, and Samy Bengio. Adversarial machine learning at scale. *arXiv preprint arXiv:1611.01236*, 2016a.

Alexey Kurakin, Ian J. Goodfellow, and Samy Bengio. Adversarial examples in the physical world. *CoRR*, abs/1607.02533, 2016b.

Yanpei Liu, Xinyun Chen, Chang Liu, and Dawn Song. Delving into transferable adversarial examples and black-box attacks. *CoRR*, abs/1611.02770, 2016.

Jiajun Lu, Hussein Sibai, Evan Fabry, and David Forsyth. No need to worry about adversarial examples in object detection in autonomous vehicles. *arXiv preprint arXiv:1707.03501*, 2017.

Chris Maddison, Andriy Mnih, and Yee-Whye Teh. The concrete distribution: A continuous relaxation of discrete random variables. *Proc. ICLR*, 2017.

Marco Melis, Ambra Demontis, Battista Biggio, Gavin Brown, Giorgio Fumera, and Fabio Roli. Is deep learning safe for robot vision? adversarial examples against the icub humanoid. *CoRR*, abs/1708.06939, 2017.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, and Pascal Frossard. Deepfool: A simple and accurate method to fool deep neural networks. In *Proc. CVPR*, pp. 2574–2582, 2016.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, Omar Fawzi, and Pascal Frossard. Universal adversarial perturbations. In *Proc. CVPR*, 2017.

Nicolas Papernot, Patrick McDaniel, Xi Wu, Somesh Jha, and Ananthram Swami. Distillation as a defense to adversarial perturbations against deep neural networks. In *IEEE Symposium on Security and Privacy*, pp. 582–597. IEEE, 2016.

Leonid Rudin, Stanley Osher, and Emad Fatemi. Nonlinear total variation based noise removal algorithms. *Physica D*, 60:259–268, 1992.

Uri Shaham, Yutaro Yamada, and Sahand Negahban. Understanding adversarial training: Increasing local stability of neural nets through robust optimization. *arXiv preprint arXiv:1511.05432*, 2015.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *Proc. ICLR*, 2014.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2818–2826, 2016.

Christian Szegedy, Sergey Ioffe, Vincent Vanhoucke, and Alexander Alemi. Inception-v4, Inception-ResNet and the impact of residual connections on learning. In *Proc. AAAI*, pp. 4278–4284, 2017.

Florian Tramèr, Alexey Kurakin, Nicolas Papernot, Dan Boneh, and Patrick D. McDaniel. Ensemble adversarial training: Attacks and defenses. *CoRR*, abs/1705.07204, 2017.

Guoming Zhang, Chen Yan, Xiaoyu Ji, Taimin Zhang, Tianchen Zhang, and Wenyuan Xu. Dolphinatack: Inaudible voice commands. *arXiv:1708.09537*, 2017.