GENERATIVE FEATURE MATCHING NETWORKS

ABSTRACT

We propose a non-adversarial feature matching-based approach to train generative models. Our approach, Generative Feature Matching Networks (GFMN), leverages pretrained neural networks such as autoencoders and ConvNet classifiers to perform feature extraction. We perform an extensive number of experiments with different challenging datasets, including Imagenet. Our experimental results demonstrate that, due to the expressiveness of the features from pretrained Imagenet classifiers, even by just matching first order statistics, our approach can achieve state-of-the-art results for challenging benchmarks such as CIFAR10 and STL10.

1 INTRODUCTION

One of the key research focus in unsupervised learning is the training of generative methods that can model the observed data distribution. Good progress has been made in recent years with the advent of new approaches such as generative adversarial networks (GANs) (Goodfellow et al., 2014) and variational autoencoders (VAE) (Kingma & Welling, 2013) which use deep neural networks as building blocks. Both methods have advantages and disadvantages, and a significant number of recent works focus on addressing their issues (Radford et al., 2016; Salimans et al., 2016; Kingma et al., 2016; Arjovsky et al., 2017; Chen et al., 2018). While the main disadvantage of VAEs is the generation of blurred images, the main issue with GANs is the training instability due to the adversarial learning.

Feature matching has been explored to improve the stability of GANs (Salimans et al., 2016; Warde-Farley & Bengio, 2017). The key idea in feature matching GANs (FM-GANs) is to use the discriminator network as a feature extractor, and guide the generator to generate data that matches the feature statistics of the real data. Concretely, the objective function of the generator in FM-GAN consists in minimizing the mean squared error of the average features of a minibatch of generated data and a minibatch of real data. The features are extracted from one single layer of the discriminator. FM-GAN is somewhat similar to methods that use maximum mean discrepancy (MMD) (Gretton et al., 2006; 2012). However, while in FM-GAN the objective is to match the mean of the extracted features, in MMD-based generative models (Li et al., 2015; Dziugaite et al., 2015), one normally aims to match all the moments of the two distributions using a Gaussian kernel. Although MMD-based generative models have strong theoretical guarantees, these models normally perform much worse than GANs on challenging benchmarks (Li et al., 2017).

In this work, we focus on answering the following research question: can we train a generative model by performing feature matching on features extracted from a pretrained neural network? In other words, we would like to know if adversarial training of the feature extractor together with the generator is a requirement for training effective generators. Towards answering this question, we propose Generative Feature Matching Networks (GFMN), a new feature matching-based approach to train generative models that uses features from pretrained neural networks. Some interesting properties of the proposed method include: (1) the loss function is directly correlated to the generated image quality; (2) mode collapsing in not an issue; (3) the same pretrained feature extractor can be used across different datasets; and (4) both supervised (classifiers) and unsupervised (autoencoder) models can be used as feature extractors.

We perform an extensive number of experiments with different challenging datasets, including ILSVRC2012 (henceforth Imagenet) (Russakovsky et al., 2015). We demonstrate that, due to the expressiveness of the features from pretrained Imagenet classifiers, even by just matching first order statistics, our approach can achieve state-of-the-art results for challenging benchmarks such as

CIFAR10 and STL10. Moreover, we show that the same feature extractor is effective across different datasets. The main contributions of this work can be summarized as follows: (1) We propose a new effective feature matching-based approach to train generative models that does not use adversarial learning, have stable training and achieves state-of-the-art results; (2) We propose an ADAM-based moving average method that allows effective training with small minibatches; (3) Our extensive quantitative and qualitative experimental results demonstrate that pretrained autoencoders and DCNN classifiers can be effectively used as feature extractors for the purpose of learning generative models.

2 GENERATIVE FEATURE MATCHING NETWORKS

2.1 THE METHOD

Let G be the generator implemented as a neural network with parameters θ, and let E be a pretrained neural network with L hidden layers. Our proposed approach consists in training G by minimizing the following loss function:

$$\min_{\theta} \sum_{j=1}^{M} ||\mathbb{E}_{x \sim p_{data}} E_j(x) - \mathbb{E}_{z \sim \mathcal{N}(0,I_{n_z})} E_j(G(z;\theta))||^2 \tag{1}$$

where: $||.||^2$ is the L_2 loss; x is a real data point sampled from the data generating distribution p_{data}; $z \in \mathbb{R}^{n_z}$ is a noise vector sampled from the normal distribution $\mathcal{N}(0, I_{n_z})$; $E_j(x)$, denotes the output vector/feature map of the hidden layer j from E; $M \leq L$ is the number of hidden layers used to perform feature matching.

In practice, we train G by sampling mini-batches of true data and generated (*fake*) data and optimizing the parameters θ using stochastic gradient descent (SGD) with backpropagation. The network E is used for the purpose of feature extraction only and is kept fixed during the training of G.

2.2 AUTOENCODER FEATURES

A natural choice of unsupervised method to train a feature extractor is the autoencoder framework. The decoder part of an AE consists exactly in an image generator that uses features extracted by the encoder. Therefore, by design, the encoder network should be a good feature extractor for the purpose of generation.

Let E and D be the encoder and the decoder networks with parameters ϕ and ψ, respectively. We pretrain the autoencoder using mean squared error (MSE):

$$\min_{\phi,\psi} \mathbb{E}_{p_{data}} ||x - D(E(x;\phi);\psi)||^2$$

or the Laplacian pyramid loss (Ling & Okada, 2006):

$$\text{Lap}_1(x, x') = \sum_j 2^{-2j} |L^j(x) - L^j(x')|_1$$

where $L^j(x)$ is the j-th level of the Laplacian pyramid representation of x. The Laplacian pyramid loss provides better signal for learning the high frequencies of the images and overcome some of the known issues of the blurry images that one would get with a simple MSE loss. Bojanowski et al. (2018) recently demonstrated that the Lap_1 loss produces better results than L_2 loss for both auto-encoders and generative models.

Another attractive feature of the autoencoder framework is that the decoder network can be used to initialize the parameters of the generator, which can make the training of the generator easier by starting in a region closer to the data manifold. We use this option in our experiments and show that it leads to significantly better results.

2.3 CLASSIFIER FEATURES

Different past work have shown the usefulness and power of the features extracted from deep convolutional nets (DCNNs) pretrained on classification tasks (Yosinski et al., 2014). In particular, features from DCNNs pretrained on ImageNet (Russakovsky et al., 2015) have demonstrated an incredible value for a different number of tasks. In this work, we perform experiments where we use

different DCCNs pretrained on Imagenet to play the role of the feature extractor E. Our hypothesis is that Imagenet-based features are powerful enough to allow the successful training of (cross-domain) generators by feature matching.

2.4 Matching Features with ADAM Moving Average

In order to train with the feature matching loss, one would need big mini-batches which would result in slowing down the training. We propose instead to keep a moving average of the means on real and generated data. One way of implementing the moving average would be by replacing the loss given in Equation equation 1 by:

$$\min_{\theta} \sum_{j=1}^{M} v_j^{\top} \left(\frac{1}{N} \sum_{k=1}^{N} E_j(x_k) - \frac{1}{N} \sum_{k=1}^{N} E_j(G(z_k; \theta)) \right) \tag{2}$$

where v_j is a moving average on Δ_j, the difference of the means of the features extracted by the j-th layer of E: $\Delta_j = \frac{1}{N} \sum_{k=1}^{N} E_j(x_k) - \frac{1}{N} \sum_{k=1}^{N} E_j(G(z_k; \theta))$, Hence we have the following update on v_j, with a rate α:

$$v_{j,\text{new}} = (1 - \alpha) * v_{j,\text{old}} + \alpha * \Delta_j, \forall j = 1 \dots M$$

Note that the moving average is a gradient descent update on the following loss:

$$\min_{v_j} \frac{1}{2} ||v_j - \Delta_j||^2, \tag{3}$$

hence, writing the gradient update with learning rate α we have:

$$v_{j,\text{new}} = v_{j,\text{old}} - \alpha * (v_{j,\text{old}} - \Delta_j) = (1 - \alpha) v_{j,\text{old}} + \alpha * \Delta_j.$$

With this interpretation of the moving average we propose to get a better estimate of the moving average using the Adam optimizer Kingma & Ba (2015) on the loss of the moving average given in Equation equation 3, i.e:

$$v_{j,\text{new}} = v_{j,\text{old}} - \alpha ADAM((v_{j,\text{old}} - \Delta_j))$$

This moving average formulation allows us to use small mini-batches and provides better results.

3 Related work

Features from deep convolutional neural nets (DCNN) pretrained on ImageNet have been used frequently to perform transfer learning in many computer vision tasks (Huh et al., 2016). Some previous work have also used DCNN features in the context of image generation and transformation. Dosovitskiy & Brox (2016) combines feature based loss with adversarial loss to improve image quality of variational autoencoders (VAE) (Kingma & Welling, 2013). Johnson et al. (2016) proposes a feature based loss that uses features from different layers of the VGG-16 neural network and is effective for image transformation task such as style transfer and super-resolution. Johnson et al. (2016) confirms the findings of Mahendran & Vedaldi (2015) that the initial layers of the network are more related to content while the last layers are more related to style.

Our proposed approach is closely related to the recent body of work on MMD-based generative models (Li et al., 2015; Dziugaite et al., 2015; Li et al., 2017; Bikowski et al., 2018; Ravuri et al., 2018). In fact, our method is a type of MMD where we (only) match the first moment of the transformed data. Among the approaches reported in the literature, the closest to our method is the Generative Moment Matching Network + Autoencoder (GMMN+AE) proposed by Li et al. (2015). In GMMN+AE, the objective is to train a generator G that maps from a prior uniform distribution to the latent code learned by a pretrained AE. To generate a new image, one sample a noise vector z from the prior, maps it the AE latent space using G, then use the (frozen) decoder to map from the AE latent space to the image space. One key difference in our approach is that our generator G maps from the z space directly to the data space, such as in GANs (Goodfellow et al., 2014). Additionally the dimensionality of the feature space that we use to perform distribution matching is orders of magnitude larger than the dimensionality of the latent code normally used in GMMN+AE. (Li et al., 2017) demonstrate that GMMN+AE is not competitive with GANs for challenging datasets such as CIFAR10. Recent MMD-based generative models have demonstrated state-of-the-art results with the

use of adversarial learning to train the MMD kernel as a replacement of the fixed Gaussian kernel in GMMN (Li et al., 2017; Bikowski et al., 2018). Additionally, Ravuri et al. (2018) recently proposed a method to perform online learning of the moments while training the generator. Our proposed method differs from these previous approaches where we use a frozen pretrained feature extractor to perform moment matching.

Bojanowski et al. (2018) proposed the GLO model, a generative approach that jointly optimizes the model parameters and the noise input vectors z. Bojanowski et al. (2018) obtain competitive results for CelebA and LSUN datasets without using adversarial training . Bojanowski et al. (2018) also demonstrated that the Laplacian pyramid loss is an effective way to improve the performance of non-adversarial methods that use reconstruction loss. Our work relates also to plug and play generative models of Nguyen et al. (2017) where a pre-trained classifier is used to sample new images, using MCMC sampling methods.

Our work is also related to AE-based generative models variational autoencoder (VAE) (Kingma & Welling, 2013), adversarial autoencoder (AAE) (Makhzani et al., 2016) and Wasserstein auto-encoder (WAE) (Tolstikhin et al., 2018). While in VAE and WAE a penalty is used to impose a prior distribution on the hidden code vector of the AE, in AAE an adversarial training procedure is used for that purpose. In our method, the aim is to get a generative model out of a pretrained autoencoder. We fix the pretrained encoder to be the discriminator in a GAN like setting.

Another recent line of work that involves the use of AEs in generative models consists in applying AEs to improve GANs stability. Zhao et al. (2017) proposed an energy based approach where the discriminator is replaced by an autoencoder. (Warde-Farley & Bengio, 2017) augments the training loss of the GAN generator by including a feature reconstruction loss term that is computed as the mean squared error of a set of features extracted by the discriminator and their reconstructed version. The reconstruction is performed using an AE trained on the features extracted by the discriminator for the real data.

4 EXPERIMENTS AND RESULTS

4.1 EXPERIMENTAL SETUP

Datasets: We evaluate our proposed approach on MNIST (LeCun et al., 1998) (60k training, 10k test images, 10 classes), CIFAR10 (Krizhevsky, 2009) (50k training, 10k test images, 10 classes), STL10 (Coates et al., 2011) (5K training, 8k test images, 100k unlabeled, 10 classes), CelebA (Liu et al., 2015) (200k images) and different portions of Imagenet (Russakovsky et al., 2015) datasets. MNIST and STL10 images are rescaled to 32×32, while CelebA and Imagenet images are rescaled to 64×64. CelebA images are center cropped to 160×160 before rescaling.

GFMN Generator: In our experiments with all datasets but Imagenet, our generator G uses a DCGAN like architecture (Radford et al., 2016). For CIFAR10, STL10 and CelebA, we use two extra layers as commonly used in previous works (Mroueh & Sercu, 2017; Gulrajani et al., 2017). For Imagenet, we use a Resnet-based generator such as the one in (Miyato et al., 2018). More details about the architectures can be found in Appendix A.2.

Autoencoder Features: For most AE experiments, we use an encoder network whose architecture is similar to the discriminator in DCGAN (strided convolutions). We use batch normalization and ReLU non-linearity after each convolution. We set the latent code size as 8, 128, 128, and 512 for MNIST, CIFAR10, STL10 and CelebA, respectively. To perform feature extraction, we get the output of each ReLU in the network as well as the output of the very last layer, the latent code. Additionally, we also perform some experiments where the encoder uses a VGG13 architecture. The decoder network D uses a network architecture similar to our generator G. More details in Appendix A.2.

Classifier Features: We perform our experiments on classifier features with VGG19 (Simonyan & Zisserman, 2014) and Resnet18 networks (He et al., 2016) which we pretrained using the whole Imagenet dataset with 1000 classes. More details about the pretrained Imagenet classifiers can be found in Appendices A.2 and A.3.

GFMN Training: We train GFMN with ADAM optimizer and keep most of the hyperparameters fixed for the different datasets. We use $n_z = 100$ and minibatch size 64. When using autoencoder

features, we set the learning rate to 5×10^{-6} when G is initialized with D, and to 5×10^{-5} when it is not. When using features from Imagenet classifiers, we set set the learning rate to 1×10^{-4}. We use ADAM moving average (Sec. 2.4) in all reported experiments.

4.2 EXPERIMENTAL RESULTS

4.2.1 AUTOENCODER FEATURES AND GENERATOR INITIALIZATION

In this section we present experimental results on the use of pretrained encoders as feature extractors. The first two rows of results in Tab. 1 show GFMN performance in terms of Inception Score (IS) (Salimans et al., 2016) and Fréchet Inception Distance (FID) (Heusel et al., 2017) for CIFAR10 in the case where the (DCGAN-like) encoder is used as feature extractor. The use of a pretrained decoder D to initialize the generator gives a significant boost in both IS and FID. A visual comparison that corroborates the quantitative results can be found in Appendix A.5. In Figs. 1a, 1b and 1c, we present random samples generated by GFMN when trained with MNIST, CIFAR10 and CelebA datasets, respectively. For each dataset, we train its respective AE using the (unlabeled) training set.

Table 1: CIFAR10 results for GFMN with different feature extractors.

Feature Extractor	Pre-trained On	# features	Initialize G	Inception Score	FID (5K/50K)
Encoder	CIFAR10	60K	$\times$	3.76 ± 0.04	96.5 / 92.5
			$\checkmark$	4.43 ± 0.05	73.9 / 69.6
Encoder (VGG13)	CIFAR10 Imagenet	244K	$\checkmark$	4.60 ± 0.06	60.8 / 56.5
			$\checkmark$	4.90 ± 0.07	59.9 / 55.5
Resnet18	Imagenet	544K	$\times$	7.03 ± 0.11	35.7 / 31.1
			$\checkmark$	7.25 ± 0.07	32.2 / 27.4
VGG19	Imagenet	296K	$\times$	7.42 ± 0.09	27.5 / 22.8
			$\checkmark$	7.71 ± 0.06	26.9 / 22.4
VGG19 + Resnet18	Imagenet	832K	$\times$	7.67 ± 0.08	23.5 / 19.0
			$\checkmark$	$\mathbf{7.99 \pm 0.06}$	$\mathbf{23.1 / 18.5}$

(a) MNIST   (b) CIFAR10   (c) CelebA

Figure 1: Generated samples from GFMN using pretrained encoder as feature extractor.

4.2.2 (CROSS-DOMAIN) CLASSIFIER FEATURES

The last six rows in Tab. 1 present the IS and FID for our best configurations that use Imagenet pretrained VGG19 and Resnet18 as feature extractors. We can see that there is a large boost in performance when Imagenet classifiers are used as feature extractors instead of autoencoders. Despite the classifiers are trained in data from a different domain (Imagenet vs. CIFAR10), the classifier features are significantly more effective. In all cases, the use of initialized generator improves the results. However, the improvements are much less significant when compared to the one obtained for the encoder feature extractor. We perform an additional experiment where we use simultaneously VGG19 and Resnet18 as feature extractors, which increases the number of features to 832K. This last configuration gives the best performance for both CIFAR10 and STL10. Figures 2b and 2c show random samples from the GFMN$^{VGG19+Resnet18}$ model, where no init. of the generator is used.

(a) CIFAR10 (Real)	(b) CIFAR10	(c) STL
(d) CIFAR10 (1 layer)	(e) CIFAR10 (5 layers)	(f) CIFAR10 (9 layers)

Figure 2: Generated samples from GFMN that uses as feature extractor a VGG-19 net pretrained on Imagenet. (2a) is a sample from the (real) CIFAR10 dataset. (2d – 2f) show the impact of using different number of layers to perform feature matching.

In Tab. 2, we report IS and FID for increasing number of layers (i.e. number of features) in our extractors VGG19 and Resnet18. We select up to 16 layers for VGG19 and 17 layers for Resnet18, which means that we excluded the output of fully connected layers. Using more layers dramatically improves the performance of both feature extractors, reaching (IS) peak performance when the maximum number of layers is used. The results in Tab. 1 are better than the ones in Tab. 2 because, for the former, we trained the models for a longer number of epochs. All models in Tab. 2 are trained for 391K generator updates, while VGG19 and Resnet18 models in Tab. 1 are trained for 1.17M updates (we use small learnin rates). Note that for both feature extractors, the features are ReLU activation outputs. As a result, the encodings may be quiet sparse. Figs. 2d, 2e and 2f show generated images when 1, 3, and 9 layers are used for feature matching, respectively (More in Appendix A.7).

In order to check if the number of features is the main factor for the performance, we performed an experiment where we trained an autoencoder whose encoder network uses a VGG13 architecture. This encoder produces a total of 244K features. We pretrained the autoencoder we both CIFAR10 and Imagenet datasets, so that we can also compare the impact of the autoencoder training set size. The results for this experiment are in the 3rd and 4th rows of Tab. 1 (Encoder (VGG13)). Although there is some improvement on both IS and FID, specially when using the Encoder pretrained with Imagenet, the boost is not comparable with the one obtained by using a VGG19 classifier. In other words, features from classifiers are significantly more informative than autoencoder features for the purpose of training generators by feature matching.

4.2.3 TRAINING STABILITY AND ADAM MOVING AVERAGE

A key contribution in this work is the introduction of the ADAM-based moving average, which allows a stable training when using small minibatches. In Fig. 3 we show a visual comparison of generated samples from GFMN when using *regular moving average* vs. *ADAM moving average*, in the three cases the minibatch size is 64. Regular moving average leads to poor results with both AE features and classifier features. When using AE features, the training with the reg. mov. average is even more challenging and the quality of generated images tends to degrade quickly over few training epochs. Fig. 4 shows the evolution of the generator loss per epoch with some generated examples for

Table 2: Impact of the number of layers/features used for feature matching (1K=2^{10}).

	VGG19			**Resnet18**		
# layers	**# features**	**IS**	**FID (5K / 50K)**	**# features**	**IS**	**FID (5K / 50K)**
1	64K	3.59 ± 0.05	176.0 / 172.9	64K	3.47 ± 0.04	189.3 / 185.4
3	160K	5.13 ± 0.04	86.2 / 81.9	192K	3.91 ± 0.03	102.2 / 98.1
5	208K	5.94 ± 0.08	60.4 / 55.9	320K	4.72 ± 0.05	86.9 / 82.5
7	240K	6.49 ± 0.07	46.6 / 42.2	384K	5.27 ± 0.04	76.6 / 72.1
9	264K	7.03 ± 0.07	37.8 / 33.3	448K	5.35 ± 0.06	65.7 / 61.4
11	280K	7.37 ± 0.06	32.5 / 28.0	480K	6.28 ± 0.07	55.3 / 50.9
13	290K	7.27 ± 0.09	31.4 / 26.9	512K	6.25 ± 0.07	47.3 / 42.4
15	294K	7.24 ± 0.07	**29.9 / 25.5**	528K	6.43 ± 0.08	43.3 / 38.7
16/17	296K	**7.44 ± 0.09**	32.3 / 27.6	544K	**6.92 ± 0.08**	**35.3 / 30.8**

an experiment where ADAM moving average is used. There is a clear correlation between the quality of generated images and the loss. Moreover, mode collapsing was not observed in our experiments.

(a) AE Features - Mov. Avrg.   (b) VGG19 - Mov. Avrg.   (c) VGG19 - ADAM Mov. Avrg.

Figure 3: GFMN generated samples when using *regular moving average* vs. *ADAM moving average*.

Figure 4: Loss as a function of training epochs with example of generated faces.

4.2.4 IMAGENET EXPERIMENTS

In order to evaluate the performance of GFMN for an even more challenging dataset, we trained GFMN^{VGG19} with different portions of the Imagenet dataset. Fig. 5a shows some (cherry picked) images generated by GFMN^{VGG19} trained on the Imagenet subset that contains different dogs breeds (same as used in Zhao et al. (2017)). The results are quite impressive given that we perform unconditional generation. Fig. 5b presents (randomly sampled) images generated by GFMN^{VGG19} trained with the Daisy portion of Imagenet. More results can be found in Appendix A.1.

4.2.5 COMPARISON WITH STATE-OF-THE-ART APPROACHES

In Tab. 3, we compare GFMN results with different adversarial and non-adversarial approaches for CIFAR10 and STL10. The table includes results for recent models that, like ours, use a DCGAN-like (or CNN) architecture in the generator. Despite using a frozen cross-domain feature extractor, GFMN outperforms the other systems in terms of FID for both datasets, and achieves the best IS for CIFAR10.

(a) Dogs   (b) Daisy

Figure 5: Generated samples from GFMN when using regular moving average instead of ADAM moving average.

We performed additional experiments with a WGAN-GP architecture where: (1) the discriminator is a VGG19 or a Resnet18; (2) the disciminator is pretrained on Imagenet; (3) the generator is pretrained on CIFAR10 through autoencoding. The objective of the experiment is to evaluate if WGAN-GP can benefit from DCNN classifiers pretrained on Imagenet. Although we tried different hyperparameter combinations, we were not able to successfully train WGAN-GP with VGG19 or Resnet18 discriminators. More details about this experiment in Appendix A.8.

Table 3: Inception Score and FID of different generative models for CIFAR10.

Model	CIFAR 10		STL 10	
	IS	FID (5K/50K)	IS	FID (5K/50K)
Real data	11.24±.12	7.8 / 3.2	26.08±.26	8.08 / 4.0
No Adversarial Training				
GMMN-D (Li et al., 2017)	3.47±.03			
GMMN-C (Li et al., 2017)	3.94±.04			
VAE (Lucic et al., 2017)	-	155.7 / -		
(ours) GFMN$^{VGG+Resnet}$	7.67 ± 0.08	23.5 / 19.0	8.45 ± 0.09	36.2 / 18.8
(ours) GFMN$^{VGG+Resnet}_{Ginit}$	**7.99 ± 0.06**	**23.1 / 18.5**	8.23 ± 0.13	**34.8 / 18.1**
Adversarial Training & Online Moment Learning Methods				
ALI (Dumoulin et al., 2017)	5.34±.05			
BEGAN (Berthelot et al., 2017)	5.62			
MMD GAN (Li et al., 2017)	6.17±.07			
MMD$_{dist}$ GAN (Bikowski et al., 2018)	6.39±.04	40.2 / -		
WGAN (Miyato et al., 2018)	6.41±.11	42.6 / -	7.57±.10	64.2
MMD$_{rq}$ GAN (Bikowski et al., 2018)	6.51±.03	39.9 / -		
WGAN-GP (Miyato et al., 2018)	6.68±.06	40.2 / -	8.42±.13	55.1 / -
SN-GANs (Miyato et al., 2018)	7.58±.12	25.5 / -	**8.79±.14**	43.2 / -
MoLM-1024 (Ravuri et al., 2018)	7.55±.08	25.0 / 20.3		
MoLM-1536 (Ravuri et al., 2018)	7.90±.10	23.3 / 18.9		

5 CONCLUSION

In this work, we introduced Generative Feature Matching Networks, an effective non-adversarial approach to train generative models. GFMNs are demonstrated to achieve state-of-the-art results

while avoiding the challenge of defining and training an adversarial discriminator. Our feature extractors can be easily obtained and provide for a robust and stable training of our generators. Some interesting open questions include: what type of feature extractors other than classifiers and auto-encoders are good for GFMN? What architecture designs are better suited for the purpose of feature extraction in GFMN?

REFERENCES

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein generative adversarial networks. In *Proc. of ICML*, pp. 214–223, 2017.

David Berthelot, Tom Schumm, and Luke Metz. BEGAN: boundary equilibrium generative adversarial networks. *CoRR*, 2017. URL http://arxiv.org/abs/1703.10717.

Mikoaj Bikowski, Dougal J. Sutherland, Michael Arbel, and Arthur Gretton. Demystifying MMD GANs. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=r1lUOzWCW.

Piotr Bojanowski, Armand Joulin, David Lopez-Paz, and Arthur Szlam. Optimizing the latent space of generative networks, 2018. URL https://openreview.net/forum?id=ryj38zWRb.

Liqun Chen, Shuyang Dai, Yunchen Pu, Erjin Zhou, Chunyuan Li, Qinliang Su, Changyou Chen, and Lawrence Carin. Symmetric variational autoencoder and connections to adversarial learning. In *Proceedings of the Twenty-First International Conference on Artificial Intelligence and Statistics*, pp. 661–669, 2018.

Adam Coates, Andrew Ng, and Honglak Lee. An analysis of single-layer networks in unsupervised feature learning. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pp. 215–223, 2011.

Alexey Dosovitskiy and Thomas Brox. Generating images with perceptual similarity metrics based on deep networks. In D. D. Lee, M. Sugiyama, U. V. Luxburg, I. Guyon, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 29*, pp. 658–666. Curran Associates, Inc., 2016.

Vincent Dumoulin, Ishmael Belghazi, Ben Poole, Alex Lamb, Martin Arjovsky, Olivier Mastropietro, and Aaron Courville. Adversarially learned inference. In *ICLR*, 2017.

Gintare Karolina Dziugaite, Daniel M. Roy, and Zoubin Ghahramani. Training generative neural networks via maximum mean discrepancy optimization. In *Proceedings of the Thirty-First Conference on Uncertainty in Artificial Intelligence*, pp. 258–267, 2015. URL http://dl.acm.org/citation.cfm?id=3020847.3020875.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Proc. of NIPS*, pp. 2672, 2014.

Arthur Gretton, Karsten M. Borgwardt, Malte Rasch, Bernhard Schölkopf, and Alexander J. Smola. A kernel method for the two-sample-problem. In *Proceedings of the 19th International Conference on Neural Information Processing Systems*, pp. 513–520, 2006. URL http://dl.acm.org/citation.cfm?id=2976456.2976521.

Arthur Gretton, Karsten M. Borgwardt, Malte J. Rasch, Bernhard Schölkopf, and Alexander Smola. A kernel two-sample test. *Journal of Machine Learning Research*, 13:723–773, 2012. URL http://dl.acm.org/citation.cfm?id=2188385.2188410.

Ishaan Gulrajani, Faruk Ahmed, Martín Arjovsky, Vincent Dumoulin, and Aaron C. Courville. Improved training of wasserstein gans. *CoRR*, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, Günter Klambauer, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a nash equilibrium. *CoRR*, abs/1706.08500, 2017. URL http://arxiv.org/abs/1706.08500.

Mi-Young Huh, Pulkit Agrawal, and Alexei A. Efros. What makes imagenet good for transfer learning? *CoRR*, abs/1608.08614, 2016.

Justin Johnson, Alexandre Alahi, and Li Fei-Fei. Perceptual losses for real-time style transfer and super-resolution. In *European Conference on Computer Vision*, 2016.

Diederik Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *ICLR*, 2015.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Diederik P Kingma, Tim Salimans, Rafal Jozefowicz, Xi Chen, Ilya Sutskever, and Max Welling. Improved variational inference with inverse autoregressive flow. In D. D. Lee, M. Sugiyama, U. V. Luxburg, I. Guyon, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 29*, pp. 4743–4751. 2016.

Alex Krizhevsky. Learning multiple layers of features from tiny images. pp. 60, 2009.

Y. LeCun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Chun-Liang Li, Wei-Cheng Chang, Yu Cheng, Yiming Yang, and Barnabas Poczos. MMD GAN: Towards deeper understanding of moment matching network. In *Advances in Neural Information Processing Systems*, pp. 2203–2213. 2017. URL http://papers.nips.cc/paper/6815-mmd-gan-towards-deeper-understanding-of-moment-matching-network.pdf.

Yujia Li, Kevin Swersky, and Richard Zemel. Generative moment matching networks. In *Proceedings of the International Conference on International Conference on Machine Learning*, pp. 1718–1727, 2015. URL http://dl.acm.org/citation.cfm?id=3045118.3045301.

H. Ling and K. Okada. Diffusion distance for histogram comparison. In *Computer Vision and Pattern Recognition*, 2006.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of International Conference on Computer Vision (ICCV)*, 2015.

Mario Lucic, Karol Kurach, Marcin Michalski, Sylvain Gelly, and Olivier Bousquet. Are gans created equal? a large-scale study. *CoRR*, abs/1711.10337, 2017.

Aravindh Mahendran and Andrea Vedaldi. Understanding deep image representations by inverting them. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2015, Boston, MA, USA, June 7-12, 2015*, pp. 5188–5196, 2015. URL https://doi.org/10.1109/CVPR.2015.7299155.

Alireza Makhzani, Jonathon Shlens, Navdeep Jaitly, and Ian Goodfellow. Adversarial autoencoders. In *International Conference on Learning Representations*, 2016. URL http://arxiv.org/abs/1511.05644.

Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=B1QRgziT-.

Youssef Mroueh and Tom Sercu. Fisher GAN. In *Proceedings of NIPS*, 2017.

Anh Nguyen, Jeff Clune, Yoshua Bengio, Alexey Dosovitskiy, and Jason Yosinski. Plug & play generative networks: Conditional iterative generation of images in latent space. In *Conference on Computer Vision and Pattern Recognition*, pp. 3510–3520, 2017. URL https://doi.org/10.1109/CVPR.2017.374.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. In *ICLR*, 2016. URL `http://arxiv.org/abs/1511.06434`.

Suman V. Ravuri, Shakir Mohamed, Mihaela Rosca, and Oriol Vinyals. Learning implicit generative models with the method of learned moments. In *Proceedings of the 35th International Conference on Machine Learning*, pp. 4311–4320, 2018. URL `http://proceedings.mlr.press/v80/ravuri18a.html`.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. Imagenet large scale visual recognition challenge. *Int. J. Comput. Vision*, 115(3):211–252, December 2015. ISSN 0920-5691. doi: 10.1007/s11263-015-0816-y. URL `http://dx.doi.org/10.1007/s11263-015-0816-y`.

Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. In *Proc. of NIPS*, pp. 2226–2234, 2016.

K. Simonyan and A. Zisserman. Very deep convolutional networks for large-scale image recognition. *CoRR*, abs/1409.1556, 2014.

Ilya Tolstikhin, Olivier Bousquet, Sylvain Gelly, and Bernhard Schoelkopf. Wasserstein auto-encoders. In *International Conference on Learning Representations*, 2018. URL `https://openreview.net/forum?id=HkL7n1-0b`.

David Warde-Farley and Yoshua Bengio. Improving generative adversarial networks with denoising feature matching. In *Proceedings of ICLR*, 2017. URL `https://openreview.net/forum?id=S1X7nhsxl`.

Jason Yosinski, Jeff Clune, Yoshua Bengio, and Hod Lipson. How transferable are features in deep neural networks? In *Proceedings of the 27th International Conference on Neural Information Processing Systems - Volume 2*, NIPS'14, 2014.

Junbo Jake Zhao, Michaël Mathieu, and Yann LeCun. Energy-based generative adversarial network. In *Proceedings of ICLR*, 2017. URL `http://arxiv.org/abs/1609.03126`.

A APPENDIX

A.1 GFMN Applied to Imagenet

We trained GFMN^{VGG19} with different portions of the Imagenet dataset using images of size 64x64. Although we adopted this image size due to speedup and memory efficient purposes, GFMN is also effective to generate images of larger sizes. Fig. 6 shows (randomly sampled) images generated by GFMN^{VGG19} trained with the following Imagenet portions: pizza (Fig. 6a), daisy (Fig. 6b), breeds of dogs (Fig. 6c) and Persian cats (Fig. 6d). Note that in this experiment the generators are trained from scratch, there is not initialization of the generators. While *pizza*, *daisy* and *Persian cats* consist in single Imagenet classes, the *breeds of dogs* portion (same as use in Zhao et al. (2017)) consists in multiple classes and therefore is a more challenging task since we doing unconditional generation. For the experiments with Imagenet, we use a Resnet generator similar to the one used by Miyato et al. (2018).

A.2 Neural Network Architectures

In Tables 4 and 5 we detail the neural net architectures used in our experiments. In both DCGAN-like generator and discriminator, an extra layer is added when using images of size 64x64. In VGG19 architecture, after each convolution, we apply batch normalization and ReLU. The Resnet generator is used for Imagenet experiments only.

(a) Pizza

(b) Daisy

(c) Dogs (all breeds)

(d) Persian Cat

Figure 6: Random samples from GFMN models using different portions of Imagenet as training set. A VGG19 pretrained on Imagenet is use as feature extractor. Images are generated in size 64x64.

$z \in \mathbb{R}^{100} \sim \mathcal{N}(0, I)$
dense $\rightarrow 4 \times 4 \times 512$
4×4, stride=2 Deconv BN 256 ReLU
4×4, stride=2 Deconv BN 128 ReLU
4×4, stride=2 Deconv BN 64 ReLU
3×3, stride=1 Conv 3 BN 64 ReLU
3×3, stride=1 Conv 3 BN 64 ReLU
3×3, stride=1 Conv 3 Tanh

DCGAN like Generator

ResBlock

$z \in \mathbb{R}^{100} \sim \mathcal{N}(0, I)$
dense, $4 \times 4 \times 1024$
ResBlock up 512
ResBlock up 256
ResBlock up 128
ResBlock up 164
BN, ReLU, 3×3 conv 3
Tanh

Resnet Generator

Table 4: Generators

RGB image $x \in \mathbb{R}^{m \times m \times 3}$
$\begin{bmatrix} 3 \times 3, & 64 \\ 3 \times 3, & 64 \end{bmatrix} \times 1$
maxpool
$\begin{bmatrix} 3 \times 3, & 128 \\ 3 \times 3, & 128 \end{bmatrix} \times 1$
maxpool
$\begin{bmatrix} 3 \times 3, & 256 \\ 3 \times 3, & 256 \end{bmatrix} \times 2$
maxpool
$\begin{bmatrix} 3 \times 3, & 512 \\ 3 \times 3, & 512 \end{bmatrix} \times 2$
maxpool
$\begin{bmatrix} 3 \times 3, & 512 \\ 3 \times 3, & 512 \end{bmatrix} \times 2$
maxpool
FC $\rightarrow$ 1000, softmax

VGG19

RGB image $x \in \mathbb{R}^{m \times m \times 3}$
4×4,stride=2 Conv 64 ReLU
3×3,stride=1 Conv 64 ReLU
3×3,stride=1 Conv 64 ReLU
4×4,stride=2 Conv 128 ReLU
4×4,stride=2 Conv 256 ReLU
dense (FC) $\rightarrow$ 100

DCGAN like Encoder

RGB image $x \in \mathbb{R}^{m \times m \times 3}$
7×7 conv, 64, stride 2
3×3 max pool, stride 2
$\begin{bmatrix} 3 \times 3, & 64 \\ 3 \times 3, & 64 \end{bmatrix} \times 2$
$\begin{bmatrix} 3 \times 3, & 128 \\ 3 \times 3, & 128 \end{bmatrix} \times 2$
$\begin{bmatrix} 3 \times 3, & 256 \\ 3 \times 3, & 256 \end{bmatrix} \times 2$
$\begin{bmatrix} 3 \times 3, & 512 \\ 3 \times 3, & 512 \end{bmatrix} \times 2$
average pool
FC $\rightarrow$ 1000, softmax

Resnet18

Table 5: Feature extractor architectures. $m = 32$ for MNIST, CIFAR10 and STL10. $m = 64$ for CelebA and Imagenet

A.3 PRETRAINING OF IMAGENET CLASSIFIERS

Both VGG19 and Resnet18 networks are trained with SGD with fixed 10^{-1} learning rate, 0.9 momentum term, and weight decay set to 5×10^{-4}. We pick models with best *top 1* accuracy on the validation set over 100 epochs of training; 29.14% for VGG19 (image size 32x32), and 39.63% for Resnet18 (image size 32x32). When training the classifiers we use random cropping and random horizontal flipping for data augmentation. When using VGG19 and Resnet18 as feature extractors in GFMN, we use features from the output of each ReLU that follows a conv. layer, for a total of 16 layers for VGG and 17 for Resnet18.

A.4 QUANTITATIVE EVALUATION METRICS

We evaluate our models using two quantitative metrics: Inception Score (IS) (Salimans et al., 2016) and Fréchet Inception Distance (FID) (Heusel et al., 2017). We followed the same procedure used in previous work to calculate IS (Salimans et al., 2016; Miyato et al., 2018; Ravuri et al., 2018). For each trained generator, we calculate the IS for randomly generated 5000 images and repeat this procedure 10 times (for a total of 50K generated images) and report the average and the standard deviation of the IS.

We compute FID using two sample sizes of generated images: 5K and 50K. In order to be consistent with previous works (Miyato et al., 2018; Ravuri et al., 2018) and be able to directly compare our quantitative results with theirs, the FID is computed as follows:

- CIFAR10: the statistics for the real data are computed using the 50K training images. This (real data) statistics are used in the FID computation of both 5K and 50K samples of generated images. This is consistent with both Miyato et al. (2018) and Ravuri et al. (2018) procedure to compute FID for CIFAR10 experiments.

- STL10: when using 5K generated images, the statistics for the real data are computed using the set of 5K (labeled) training images. This is consistent with the FID computation of Miyato et al. (2018). When using 50K generated images, the statistics for the real data are computed using a set of 50K images randomly sampled from the unlabeled STL10 dataset.

FID computation is repeated 3 times and the average is reported. There is very small variance in the FID results.

A.5   GENERATOR INITIALIZATION

The use a of pretrained decoder D to initialize the generator gives a good boost in performance when the feature extractor is the decoder from a pretrained autoencoder (See sec. 4.2.1). In Fig. 7, we show a visual comparison that demonstrates the effect of using the pretrained decoder D to initialize the generator. The generators for the images in the first row (7a, 7b, 7c) were not initialized, while the generators for the images in the second row (7d, 7e, 7f) were initialized. For the three datasets, we can see a significant improvement in image quality when the generator is initialized with the decoder. We use the Laplacian pyramid loss to train CIFAR10 and CelebA AEs. However, L2 loss gives results almost as good as Lap1 loss.

(a) MNIST (no G init.)   (b) CIFAR10 (no G init.)   (c) CelebA (no G init.)

(d) MNIST (G init.)   (e) CIFAR10 (G init.)   (f) CelebA (G init.)

Figure 7: Generated samples from GFMN using pretrained encoder as feature extractor. Visual comparison of models generated without (top row) and with (bottom row) initialization of the generation.

A.6   CROSS-DOMAIN AUTOENCODER FEATURE EXTRACTORS

The experimental results in Sec. 4.2.2 demonstrate that cross-domain feature extractors based on DCNNs classifiers are very successful. For instance, we successfully used a VGG19 pretrained on Imagenet to train a GFMN generator for the CelebA dataset. Here, we investigate the impact of the pretraining of autoencoder-based feature extractors in a cross-domain setting. The objective is to further verify if GFMN is dependent on pretraining the autoencoder feature extractors on the same training data where the generator is trained. In Tab. 6, we show the results for different combinations of cross-domain feature extractors and G initialization for STL10 and CIFAR10. The subscript indicates which dataset was used for pretraining. We can see in Tab. 6 that, CIFAR10 using E_{STL} and D_{STL} has similar performance (even better IS) to using E_{CIFAR} and D_{CIFAR}. There is a performance drop when using E_{CIFAR} and D_{CIFAR} to train a STL10 generator. We believe this drop is related to the training set size. STL10 contains 100K (unlabeled) training examples while CIFAR10 contains 50K training images.

A.7   IMPACT OF THE NUMBER OF LAYERS USED FOR FEATURE EXTRACTION

Figure 8 shows generated images from generators that were trained with a different number of layers employed to feature matching. In all the results in Fig.8, the VGG19 network was used to perform feature extraction. We can see a significant improvement in image quality when more layers are used.

Table 6: Cross-domain results for STL10 and CIFAR10 autoencoder features.

G Train. Data	Feat. Extractor	G Initialization	IS	FID (5K)
STL10	E_{STL}	D_{STL}	4.74±0.12	69.80
	E_{CIFAR}	D_{CIFAR}	4.05±0.08	74.80
CIFAR10	E_{CIFAR}	D_{CIFAR}	4.47±0.08	71.47
	E_{STL}	D_{STL}	4.53±0.09	73.74

Better results are achieved when 11 or more layers are used, which corroborates the quantitative results in Tab. 2.

(a) 1 Layer   (b) 3 Layers   (c) 5 Layers

(d) 7 Layers   (e) 9 Layers   (f) 11 Layers

(g) 13 Layers   (h) 15 Layers   (i) 16 Layers

Figure 8: Generated images from generators trained with a different number of VGG19 layers for feature extraction.

A.8 PRETRAINED GENERATOR/DISCRIMINATOR IN WGAN-GP

The objective of the experiments presented in this section is to evaluate if WGAN-GP can benefit from DCNN classifiers pretrained on Imagenet. In the experiments, we used a WGAN-GP architecture

where: (1) the discriminator is a VGG19 or a Resnet18; (2) the disciminator is pretrained on Imagenet; (3) the generator is pretrained on CIFAR10 through autoencoding. Although we tried different hyperparameter combinations, we were not able to successfully train WGAN-GP with VGG19 or Resnet18 discriminators. Fig. 9 shows some examples of images generated by the unsuccessfully trained models.

(a) VGG19 D (b) VGG19 D and G Init.

Figure 9: Generated images by WGAN-GP with pretrained VGG19 as a discriminator.