Learning to Make Analogies by Contrasting Abstract Relational Structure

Abstract

Analogical reasoning has been a principal focus of various waves of AI research. Analogy is particularly challenging for machines because it requires relational structures to be represented such that they can be flexibly applied across diverse domains of experience. Here, we study how analogical reasoning can be induced in neural networks that learn to perceive and reason about raw visual data. We find that the critical factor for inducing such a capacity is not an elaborate architecture, but rather, careful attention to the choice of data and the manner in which it is presented to the model. The most robust capacity for analogical reasoning is induced when networks learn analogies by contrasting abstract relational structures in their input domains, a training method that uses only the input data to force models to learn about important abstract features. Using this technique we demonstrate capacities for complex, visual and symbolic analogy making and generalisation in even the simplest neural network architectures.

1 Introduction

The ability to make analogies – that is, to flexibly map familiar relations from one domain of experience to another – is a fundamental ingredient of human intelligence and creativity (Gentner, 1983; Hofstadter, 1996; Hummel & Holyoak, 1997; Lovett & Forbus, 2017). As noted, for instance, by Holyoak & Thagard (1995), analogies gave Roman scientists a deeper understanding of sound when they leveraged knowledge of a familiar source domain (water waves in the sea) to better understand the structure of an unfamiliar target domain (acoustics). The Romans 'aligned' relational principles about water waves (periodicity, bending round corners, rebounding off solids) to phenomena observed in acoustics, in spite of the numerous perceptual and physical differences between water and sound. This flexible alignment, or mapping, of relational structure between source and target domains, independent of perceptual congruence, is a prototypical example of analogy making.

It has proven particularly challenging to replicate processes of analogical thought in machines. Many classical or symbolic AI models lack the flexibility to apply predicates or operations across diverse domains, particularly those that may have never previously been observed. It is natural to consider, however, whether the strengths of modern neural network-based models can be exploited to solve difficult analogical problems, given their capacity to represent stimuli at different levels of abstraction and to enable flexible, context-dependent computation over noisy and ambiguous inputs.

In this work we demonstrate that well-known neural network architectures can indeed learn to make analogies with remarkable generality and flexibility. This ability, however, is critically dependent on a method of training we call *learning analogies by contrasting abstract relational structure* (LABC). We show that simple architectures can be trained using this approach to apply abstract relations to never-before-seen source-target domain mappings, and even to entirely unfamiliar target domains.

Our work differs from previous computational models of analogy in two important ways. First, unlike previous neural network models of analogy, we optimize a single model to perform both stimulus representation and cross-domain mapping jointly. This allows us to explore the potential benefit of interactions between perception, representation and inter-domain alignment, a question of some debate in the analogy literature (Forbus et al., 1998). Second, we do not instantiate an explicit cognitive theory or analogy-like computation in our model architecture, but instead use this theoretical insight to inform the way in which the model is trained.

Figure 1: **Example visual analogies.** In the left analogy puzzle, the model must identify a relation (`OR`) on a particular domain (`shape colour`) in the sequence in the source (panel$_3$ = `OR` (panel$_1$, panel$_2$)), and apply it to a different domain (`shape type`) in order to find the candidate answer panel that correctly completes the sequence in the target sequence.

2 ANALOGIES AS HIGH-LEVEL PERCEPTION AND STRUCTURE MAPPING

Perhaps the best-known explanation of human analogical reasoning is the Structure Mapping Theory (SMT) (Gentner, 1983). SMT emphasizes the distinction between two means of comparing domains of experience; analogy and similarity. Two domains are similar if they share many *attributes* (i.e. properties that can be expressed with a one-place predicate like `BLUE(sea)`), whereas they are analogous if they share few attributes but many relations (i.e. properties expressed by many-place predicates like `BENDS-AROUND(sea, solid-objects)`). SMT assumes that our perceptions can be represented as collections of attributes and structured relations, and that these representations do not necessarily depend on the subsequent mappings that use them.

The High-Level Perception (HLP) theory of analogy (Chalmers et al., 1992; Mitchell, 1993) instead construes analogy as a function of tightly-interacting perceptual and reasoning processes, positing that the creation of stimulus representations and the alignment of those representations are mutually dependent. For example, when making an analogy between the sea and acoustics, we might represent certain perceptual features (the fact that the sea appears to be moving) and ignore others (the fact that the sea looks blue), because the particular comparison that we make depends on location and direction, and not on colour.

In this work we aim to induce flexible analogy making in neural networks by drawing inspiration from both SMT and HLP. The perceptual and domain-comparison components of our models are connected and jointly optimised end-to-end, which, as posited by HLP, reflects a high degree of interaction between perception and domain comparison. On the other hand, the key insight of this paper, LABC, is directly motivated by SMT. We find that LABC greatly enhances the ability of our networks to resolve analogies in a generalisable way by encouraging them to compare inputs at the more abstract level of relations rather than the less abstract level of attributes. LABC organizes the training data such that the inference and mapping of relational structure is essential for good performance. This means that problems cannot be resolved by considering mere similarity of attributes, or even less appropriately, via spurious surface-level statistics or memorization.

3 VISUAL ANALOGY PROBLEMS

Our first experiments involve greyscale visual scenes similar to those previously applied to test both human reasoning ability (Raven, 1983; Geary et al., 2000) and reasoning in machine learning models (Bongard, 1967; Fleuret et al., 2011; Barrett et al., 2018). Each scene is composed of a *source sequence*, consisting of three *panels* (distinct images), a target sequence, consisting of two panels, and four candidate answer panels (Fig. 1). In the source sequence a relation r is instantiated, where r is one of four possible relations from the set $R = \{$ `XOR` , `OR` , `AND` , `Progression` $\}$. Models

must then consider the two panels in the target sequence, together with the four candidate answer panels, to determine which answer panel best completes the target sequence – by analogy with the source sequence – so that r is also instantiated.

The notion of *domain* is critical to analogy. In the present task, a relation can be instantiated in one of seven different domains: `line type` , `line colour` , `shape type` , `shape colour` , `shape size` , `shape quantity` and `shape position` (see Fig. 1 for examples). Within a panel of a given domain, the attributes present in the scene (such as the colour of the shapes or the positions of the lines) can take one of 10 possible *values*. A question in the dataset is therefore defined by a relation r, a domain d_s on which r is instantiated in the source sequence, a set of values for the source-domain $v_1^s \cdots v_3^s$, a target domain d_t, values for the target-domain $v_1^t \cdots v_3^t$, the position $k \in \{1 \cdots 4\}$ of the correct answer among the answer candidate panels and whatever is instantiated in the three incorrect candidate answer panels $c_i, i \neq k$. Note, however, that the values of certain domain attributes that are not relevant to a given question (such as the colour of shapes in the `shape quantity` domain) still have to be selected, and can vary freely. Thus, despite the small number of latent factors involved, the space of possible questions is of the order of ten million.

The interplay between relations, domains and values makes it possible to construct questions that require increasing degrees of abstraction and analogy-making. The simplest case involves a relation r, a domain $d_s == d_t$, and values $v_i^s == v_i^t$ that are common to both source and target sequences (Fig 2a). To solve such a question a model must identify a candidate answer panel that results in a copy of the source sequence in the target sequence. This does not seem to require any meaningful understanding of r, nor any particular analogy-making. Somewhat greater abstraction and analogy-making is required for questions involving a single domain ($d_s == d_t$), but different values in the source and target sequence $v_i^s \neq v_i^t$ (Fig 2b). In this case the model must learn that, in a given domain, the relation r can apply to a range of different values. Finally, in the full analogy questions considered in this study, the relation r can be instantiated on different domains in the source and target sequences (i.e. $d_t \neq d_s$; Fig 2c). These questions require a sensitivity to the idea that a single relation r can be applied in different (but related) ways to different domains of experience.

3.1 METHODS

Our model consisted of a simple perceptual front-end – a convolutional neural network (CNN) – which provided input for a recurrent neural network (RNN) by producing embeddings for each image panel independently. The RNN processed the source sequence embeddings, the target sequence embeddings, and a *single* candidate embedding, to produce a scalar score. Four such passes (one for each source-target-candidate set) produced four scalar scores, quantifying how the model evaluated the suitability of the particular candidate. Finally, a softmax was computed across the scores to select the model's 'answer'. Further model details are in the appendix.

Contrasting answer candidates in visual analogy problems   Neural networks are prone to solving visual classification problems by exploiting superficial pixel-level statistics, resulting in models that do not generalize in robust, human-like ways (Szegedy et al., 2013). According to Gentner's SMT, however, analogies are not resolved by comparing surface-level attributes (least of all, pixels), but rather the abstract relational structure of two domains.

In the default setting of our data generator – the *normal training* regime – for a question involving source domain d_s, target domain d_t and relation r, the candidate answers can contain any (incorrect) values chosen at random from d_t. This setting allows the model to find any available method to arrive at the correct answer consistently over the course of its training experience. We can instead train the model to contrast abstract relational structure – the LABC regime – simply by adjusting the incorrect answer candidates c_i in the training data such that solutions based on superficial input attributes can perform at best at chance. Incorrect answers are selected from d_t such that each answer c_i completes a decoy relation $\hat{r}_i \neq r$ with the target sequence. LABC ensures that, during training, models have no alternative but to first observe a relation r in the source domain and consider and complete the same relation in the target domain - i.e. to execute a full analogical reasoning step. [1]

---

[1] It is important to note that that LABC as described here relies on our understanding of the underlying data-generating process; we demonstrate its application that does not require such understanding in Sec. 5.3.

Figure 2: **(a), (b), (c) Three types of visual reasoning questions.** Each question requires a different degree of analogy making, with the question on the right demanding the most fluid and abstract application of the underlying relation. **(d) Learning by contrasting.** When learning by contrasting, each answer choice instantiates a relational structure in the target sequence, forcing the network to consider the source sequence to infer the correct structure.

3.2 EXPERIMENT 1: NOVEL DOMAIN TRANSFER

A key aspect of analogy-making is the process of comparing or aligning two domains. We can measure how well models acquire this ability by testing them on analogies involving unfamiliar source domain $\rightarrow$ target domain transfers. For each of the seven possible target domains d_t we randomly selected a source domain $d_s \neq d_t$, yielding a test set of seven domain transfer pairs $[d_s \rightarrow d_t]$. Our models were then trained on questions involving one of the remaining $7 \times 7 - 7 = 42$ domain transfer pairs. For a test question involving domains d_s and d_t, each model was therefore familiar with d_s and d_t but had not been trained to make an analogy from d_s to d_t.

We found that a network can indeed learn to apply relations by analogy involving novel domain transfers, but that this ability crucially relies on learning by contrasting. The effect is strong; for the most focused test questions involving semantically plausible (contrasting) candidate answers the model trained by contrasting achieves 83% accuracy (depending on the held-out domain), versus 58% for a model trained with randomly-chosen candidate answers.

3.3 EXPERIMENT 2: NOVEL TARGET DOMAIN

Humans can use analogies to better understand comparatively unfamiliar domains, as in the Roman explanation of acoustics by analogy with the sea. To capture this scenario, we held out two domains (`line type` and `shape colour` , chosen at random) from the model's training data, and ensured

that each test question involved one of these domains. To make any sense of the test questions, a model must therefore (presumably) learn to represent the relations in the dataset (i.e. how to detect and apply that relation in source and target domains) in a sufficiently general way that this knowledge can be applied to completely novel domains. Any model that resolves such problems successfully must therefore exploit any (rudimentary) perceptual similarity between the test domain and the domains that were observed during training. For instance, the process of applying a relation in the `shape colour` domain may recruit similar feature detectors to those required when applying it to the `line colour` domain.

Surprisingly, we found that the network can indeed learn to make sense of the unfamiliar target domains in the test questions, although again this capacity is boosted by LABC (Fig 3b). Accuracy in the LABC condition on the most focused (contrasting) test questions is lower than in the Experiment 1 ($\sim 80\%$, depending on the held-out domain), but well above the model trained with random answer candidates ($\sim 60\%$). Interestingly, a model trained on contrasting candidate answer (LABC) performs somewhat worse on test questions with random answers than a model trained in the normal (random answer) regime, although this deficit can be largely recovered by interleaving random-answer and contrasting candidates during training.

3.3.1 EXPERIMENT 3: NOVEL DOMAIN VALUES

Another way in which a domain can be unfamiliar to a network is if it involves attributes whose values have not been observed during training. Since each of the seven (source and target) domains our analogy problems permits 10 values, we can measure *interpolation* by withholding values 1, 3, 5, 7 and 9 and measure *extrapolation* by withholding values 6, 7, 8, 9 and 10. To extrapolate effectively, a model must therefore be able to resolve questions at test time involving lines or shapes that are darker, larger, more-sided or simply more numerous than those in its training questions.

In the case of interpolation, we found that a model trained with random candidates performs very poorly on the more challenging contrasting test questions (Fig 3c 45% vs 93% for LABC), which suggests that models trained in the normal regime overfit to a strategy that bears no resemblance to human-like analogical reasoning. We verified this hypothesis by running an analysis where we presented only the target domain sequence and candidate answers to the model. After a long period of training in the normal regime, this 'source-blind' model achieved 97% accuracy, which confirms that it indeed finds short-cut solutions that do not require analogical mapping. In contrast, the accuracy of the source-blind model in the LBAC condition converged at 32%.

We also found, somewhat surprisingly, that LBAC results in a (modest) improvement in how well models can extrapolate to novel input values (Fig 3c); a model trained on questions with both contrasting and random candidate answers performs significantly better than the normal model on the test questions with contrasting candidate answers (62% vs. 43%), and mantains comparable performance on test questions with random candidate answers (45% vs. 44%).

3.4 CONCLUSION

These results demonstrate that LABC increases the ability of models to generalize beyond the distribution of their training data. This effect is observed for the prototypical analogical processes involving novel domain mappings and unfamiliar target domains (Experiments 1 & 2). Interestingly, it also results in moderate improvements to how well models extrapolate to perceptual input outside the range of their training experience (Experiment 3).

4 EMERGENT RELATIONAL REPRESENTATIONS

In order to gain insights into the mechanisms that support this generalisation we analysed neural activity in models trained with LABC compared to models that were not. First, we took the RNN hidden state activity just prior to the input of the candidate panel. For a model trained via LABC, we found that these activities clustered according to relation type (e.g. `progression`) more-so than domain (e.g., `shape colour`) (Fig 4a). In contrast, for models trained normally the relation-based clusters overlapped to a greater extent (Fig 4b). Thus, presenting answer candidates during training that were plausible at the relational level (LABC) seemed to encourage the model to represent

Figure 3: **Results of the three experiments in the visual analogy domain for a network that learns from random candidate answers, by contrasting abstract structures or both types of question interleaved.** Bar heights depict the means across eight seeds in each condition; standard errors were < 0.01 for each condition (not shown – see the appendix Table 1 for the values)

Figure 4: **LABC supports emergent relational representations.** Principle component analysis (PCA) (right) and t-SNE analysis (left) of RNN hidden states. Each dot represents a (64-dimensional) state coloured according to the relation type and domain of the corresponding question.

relations more explicitly, which could in turn explain its capacity to generalise by analogy to novel domains.

5 SYMBOLIC ANALOGY PROBLEMS

Many of the most important studies of analogy in AI involve symbolic or numerical patterns (Hofstadter, 1996), and various neural models of semantic cognition more generally also operate on discrete, feature-based representations of input concepts (Rogers & McClelland, 2004; Devereux et al., 2018). To verify our findings about LABC in this setting, we implemented a symbolic analogy task based on discrete, feature-based stimuli. This more controlled domain also us allows to show that the process of constructing appropriate incorrect answer candidates can be learned in a proposal model that is trained jointly with a model that learns to contrast the candidates, which widens the potential applications of LABC to task settings where we lack a clear understanding of the underlying abstract relational structure (Sec 5.3).

In our task, inputs are D-dimensional vectors v of discrete, integer-valued features (analogous to semantic properties such as *furry* or *carnivorous* in previous work). Across any set $V : v \in V$ of stimuli, each feature dimension then corresponds to a domain (the domains of skin-type or dietary habits in the present example). To simulate a space of abstract relational structures on these domains, we simply take a set F whose elements f are common mathematical functions operating on sets: `MIN`, `MAX`, `ARGMIN`, `ARGMAX`, `SUM` and `RANGE`. Abstract relations in this context can then be stated, for instance, as `SUM(1, 2, 3; 6)`. Given a function f defining such a relationship, a set V of stimulus vectors, and a random choice of domain d, we can compute a (D-dimensional) answer vector $a_{[V,d,f]}$ as the result of applying f to d on V (i.e. executing f on the d-th dimension of each $v \in V$ and returning the result).

It is now simple to randomly construct an analogy question in this setting. We select a function f, source d_s and target d_t domains at random, randomly generate source V_s and target V_t stimuli. We then apply f to V_s on d_s and to V_t on d_t to generate the source and target domain solutions, $a_{[V_s,d_s,f]}$ and $a_{[V_t,d_t,f]}$, respectively. The inputs V_s, d_s, $a_{[V_s,d_s,f]}$, V_t and v_t are passed to the model, together with a $d \times k$ matrix of alternative answer choices that includes $a_{[V_t,d_t,f]}$ (k is a fixed number of choices, four in the visual analogies presented previously). We then require the model to select which of these alternatives is the true completion of the analogy $a_{[V_t,d_t,f]}$.

As in the visual analogy tasks, to resolve such a question the model must detect an abstract relationship in the input domain d_s, that explains the connection between the source stimuli V_s and the answer vector $a_{[V_s,d_s,f]}$. Once this achieved, the model must evaluate the function f that describes this relationship on the source domain d_t with sufficient accuracy that it can identify the result of that evaluation $a_{[V_t,d_t,f]}$ in the context of k distracting alternative (incorrect) answers.

We study generalization in this task by restricting the particular ordered domain mappings $d_s \rightarrow d_t$ that are observed in the training and test set; for example, aligning structure from domain 3 to domain 1 may be required in the test set, but may have never been seen before in the training set. While we withhold particular alignments (e.g., $3 \rightarrow 1$), we ensure that all dimensions are aligned 'out-of' ($3 \rightarrow$) and 'into' ($\rightarrow 1$) at least once in the training set. Note that this setup is directly analogous to the 'Novel Domain Transfer' experiment in the visual analogy problems (Sec. 3.2).

5.1 METHODS

The high level model structure was similar to that of the previous experiments: candidates and their context were processed independently to produce scores, which we put through a softmax and trained with a cross-entropy loss. See appendix for further details.

Learning symbolic analogies by contrasting   Producing appropriate candidate answers C to train by contrasting abstract relational structures (LABC) is straightforward. For a problem involving function f, we sample functions $\hat{f} \sim F \setminus \{f\}$ at random and populate C with the $c_{\hat{f}}$, where $c_{\hat{f}} = \hat{f}(V_t)$. In other words, $c_{\hat{f}}$ adheres to *some* relational structure, but just not the structure apparent in the source set. Thus, to determine which candidate is correct, the model necessarily has to first infer the particular relational structure of the source set.

5.2 EXPERIMENT 1: NOVEL DOMAIN TRANSFER

We replicated the main findings of the visual analogy task (Experiment 1, section 3.2): models trained without LABC performed at just above chance, whereas models trained with LABC achieved accuracies of just under 90%. We note that we tested models with candidates generated using the functions in F not equal to the function used to define the relation in the source set. If instead we were to generate random vectors as candidates, the models could simply learn and embed all possible $f \in F$ into their weights, and choose the correct answer by process of elimination; any candidate that does not satisfy $f(V_t)$ for any f is necessarily an incorrect candidate. This method does not require any analogical reasoning, since the model can outright ignore the relation instantiated in the source set, which is precisely a type of back-door solution characteristic of neural network approaches. These results are intuitive at first glance – a model that cannot use back-door solutions, and instead is required to be more discerning at training time will perform better at test time. However, this intuition is less obvious when testing demands *novel domain transfer*. In other words, it is not obvious that a

Figure 5: **Structure alignment and mapping on symbolic, numeric data**. In this task a particular structure is implemented as a set-function, which in the depicted example is $f = \min$. For example, the "answer" a_1 could denote the minimum size from the sizes in the source symbolic vector set. The model must then evaluate the minimum for the "aligned" domain, which in the depicted case is *intensity*. In this depicted example the candidate does not adhere to this structure, so it would be an incorrect candidate. The correct candidate would look like the answer vector to the right of the image.

model that has learned to discern the various functions in F would necessarily be able to flexibly apply the functions in ways never-before-seen, as is demanded in the test set.

5.3 EXPERIMENT 2: NOVEL DOMAIN TRANSFER WITH AUTOMATIC LABC METHODS

We explored ways to replicate the results of Experiment 1 without hand-crafting the candidate answers. For our first method, we began by uniformly sampling integer values for the $c \in C$ from within some range $(0, 64)$, rather than computing them as $\hat{f}(V_t)$ for some $\hat{f} \in F$. As mentioned previously, such a method should encourage back-door memorization based solutions, since for most candidates, $c \neq \hat{f}(V_t)$ for any $\hat{f} \in F$. To counter this, we randomly generated a set of candidates, performed a forward pass with each, selected the top-k scalar scores produced by the model, and backpropagated gradients *only* through these k candidates. Intuitively, this forces the model to train on only those candidates that are maximally confusing. Thus, we rely on random generation to chose our contrasting candidates, and rely on the model itself to sub-select them from within the randomly generated pool. This method improves performance from chance (25%) to approximately 77%.

It is possible that this top-k method simply relies on a random sampling to stumble on the candidates that would have otherwise been hand-crafted. Indeed, for more difficult problems (involving real images, for example) a random generator cannot be guaranteed to produce anything resembling data from the underlying data distribution, making this method less suitable. We replicated the top-k experiment, but actively excluded any randomly generated candidate that satisfied $c = \hat{f}(V_t)$ for some $\hat{f} \in F$. This dropped performance to approximately 43%, confirming this intuition, but interestingly, still improving baseline performance drastically.

And so, we turned to another method for generating candidates that did not depend on random generation. Instead we used a *generator* model, which was otherwise identical to the model used to solve the task, except whose input consisted only of the target set V_t, and whose output was a proposed candidate vector c. This candidate vector was then passed along to the original model, which was tasked with solving the analogy problem as before. The generator model was trained to *maximize* the score given by the analogy model; in other words, it was trained to produce maximally confusing candidates. The overall objective therefore resembled a two-player minimax game:

$$\min_\theta \max_\phi \mathcal{L}(f_\theta(S_1, a_1, S_2, a_2, g_\phi(S_2)))$$

where f_θ is the analogy model and g_ϕ is the candidate proposal model.[2] Using this method to propose candidates improved the model's test performance from chance (25%) to approximately 62%.

---

[2]We show here only a single candidate, but in practice the proposal model produced 8 candidates

6   DISCUSSION

Our experiments demonstrated that comparatively simple neural networks can learn to make analogies with visual and symbolic inputs, but this is critically contingent on the way in which they are trained; during training, the correct answers should be contrasted with alternative incorrect answers that are plausible at the level of relations rather than simple perceptual attributes. This is consistent with the SMT of human analogy-making, which highlights the importance of inter-domain comparison at the level of abstract relational structures. At the same time, in the visual analogy domain, our model also reflects the idea of analogy as closely intertwined with perception itself. We find that models that are trained by contrasting to reason better by analogy are, perhaps surprisingly, also better able to extrapolate to a wider range of input values. Thus, learning to make better analogies also seems to improve the ability of models to perceive and represent their raw experience.

Recent discussion in the literature has questioned whether neural networks can generalise in systematic ways to data drawn from outside the training distribution (Lake & Baroni, 2018). Our results show that neural networks are not fundamentally limited in this respect. Rather, the capacity needs to be coaxed out through careful learning. The data with which these networks learn, and the manner in which they learn it, are of paramount importance. Such a lesson is not new; indeed, the task of one-shot learning was thought to be difficult, if not impossible to perform using neural networks, but was nonetheless "solved" using appropriate training objectives, models, and optimization innovations (e.g., (Santoro et al., 2016; Finn et al., 2017)). The insights presented here may guide promising, general purpose approaches to obtain similar successes in flexible, generalisable abstract reasoning.

Earlier work on analogical reasoning in AI and cognitive science employed constructed symbolic stimuli or pre-processed perceptual input (Carbonell (1981); Hummel & Holyoak (1997); Holyoak & Thagard (1989); Mitchell (1993); Hofstadter (1996); Larkey & Love (2003) inter alia; see Gentner & Forbus (2011) for a full review). More recently, Reed et al. (2015) learn an analogy model on top of pre-trained visual embeddings of geometric figures and rendered graphics, while Mikolov et al. (2013) show how analogies can be made via non-parametric operations on vector-spaces of text-based word representations. While the input to our visual analogy model is less naturalistic than these latter cases, this permits clear control over the semantics of training or test data when designing and evaluating hypotheses. Our study is nonetheless the only that we are aware to demonstrates such flexible, generalisable analogy making in neural networks learning end-to-end from raw perception. It is therefore a proof of principle that even very basic neural networks have the potential for strong analogical reasoning and generalization.

As discussed in Sec. 5.3, in many machine-learning contexts it may not be possible to know exactly what a 'good quality' negative example looks like. The experiments there show that, in such cases, we might still achieve notable improvements in generalization via methods that learn to play the role of teacher by presenting alternatives to the main (student) model, as per Shafto et al. (2014). This underlines the fact that, for established learning algorithms involving negative examples such as (noise) contrastive estimation (Smith & Eisner, 2005; Gutmann & Hyvärinen, 2010) or negative sampling (Mikolov et al., 2013), the way in which negative examples are selected can be critical. It may also help to explain the power of methods like self-play (Silver et al., 2016), in which a model is encouraged to continually challenge itself by posing increasingly difficult learning challenges.

Analogies as the functions of the mind   To check whether a plate is *on a table* we can look at the space above the table, but to find out whether a picture is on a wall or a person is on a train, the equivalent check would fail. A single *on* function operating in the same way on all input domains could not explain these entirely divergent outcomes of function evaluation. On the other hand, it seems implausible that our cognitive system encodes the knowledge underpinning these apparently distinct applications of the *on* relation in entirely independent representations. The findings of this work argue instead for a different perspective; that a single concept of *on* is indeed exploited in each of the three cases, but that its meaning and representation is sufficiently abstract to permit flexible interaction with, and context-dependent adaptation to, each particular domain of application. If we equate this process with analogy-making, then analogies are something like the functions of the mind. We believe that greater focus on analogy may be critical for replicating human-like cognitive processes, and ultimately human-like intelligent behaviour, in machines. It may now be time to revisit the insights from past waves of AI research on analogy, while bringing to bear the tools, perspectives and computing power of the present day.

REFERENCES

Ali M Ali. The use of positive and negative examples during instruction. *Journal of instructional development*, 5(1):2–7, 1981.

David Barrett, Felix Hill, Adam Santoro, Ari Morcos, and Timothy Lillicrap. Measuring abstract reasoning in neural networks. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, pp. 511–520, 2018.

Mikhail M Bongard. The problem of recognition. *Fizmatgiz, Moscow*, 1967.

Jaime G Carbonell. A computational model of analogical problem solving. In *IJCAI*, volume 81, pp. 147–152, 1981.

David J Chalmers, Robert M French, and Douglas R Hofstadter. High-level perception, representation, and analogy: A critique of artificial intelligence methodology. *Journal of Experimental & Theoretical Artificial Intelligence*, 4(3):185–211, 1992.

Barry J Devereux, Alex D Clarke, and Lorraine K Tyler. Integrated deep visual and semantic attractor neural networks predict fmri pattern-information along the ventral object processing pathway. *bioRxiv*, pp. 302406, 2018.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. *arXiv preprint arXiv:1703.03400*, 2017.

François Fleuret, Ting Li, Charles Dubout, Emma K Wampler, Steven Yantis, and Donald Geman. Comparing machines and humans on a visual categorization test. *Proceedings of the National Academy of Sciences*, 2011.

Kenneth D Forbus, Dedre Gentner, Arthur B Markman, and Ronald W Ferguson. Analogy just looks like high level perception: Why a domain-general approach to analogical mapping is right. *Journal of Experimental & Theoretical Artificial Intelligence*, 10(2):231–257, 1998.

David C Geary, Scott J Saults, Fan Liu, and Mary K Hoard. Sex differences in spatial cognition, computational fluency, and arithmetical reasoning. *Journal of Experimental child psychology*, 77 (4):337–353, 2000.

Dedre Gentner. Structure-mapping: A theoretical framework for analogy. *Cognitive science*, 7(2): 155–170, 1983.

Dedre Gentner and Kenneth D Forbus. Computational models of analogy. *Wiley interdisciplinary reviews: cognitive science*, 2(3):266–276, 2011.

Michael Gutmann and Aapo Hyvärinen. Noise-contrastive estimation: A new estimation principle for unnormalized statistical models. In *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, pp. 297–304, 2010.

Douglas R Hofstadter. Fluid concepts and creative analogies. 1996.

Keith J Holyoak and Paul R Thagard. A computational model of analogical problem solving. *Similarity and analogical reasoning*, 242266, 1989.

Keith James Holyoak and Paul Thagard. *Mental leaps*. 1995.

John E Hummel and Keith J Holyoak. Distributed representations of structure: A theory of analogical access and mapping. *Psychological review*, 104(3):427, 1997.

Brenden Lake and Marco Baroni. Generalization without systematicity: On the compositional skills of sequence-to-sequence recurrent networks. In *International Conference on Machine Learning*, pp. 2879–2888, 2018.

Levi B Larkey and Bradley C Love. Cab: Connectionist analogy builder. *Cognitive Science*, 27(5): 781–794, 2003.

Andrew Lovett and Kenneth Forbus. Modeling visual problem solving as analogical reasoning. *Psychological review*, 124(1):60, 2017.

Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space. *arXiv preprint arXiv:1301.3781*, 2013.

Melanie Mitchell. *Analogy-making as perception: A computer model*. Mit Press, 1993.

Robert G Morrison, Keith J Holyoak, and Bao Troung. Working-memory modularity in analogical reasoning. In *Proceedings of the Annual Meeting of the Cognitive Science Society*, volume 23, 2001.

Jiang Qiu, Hong Li, Antao Chen, and Qinglin Zhang. The neural basis of analogical reasoning: An event-related potential study. *Neuropsychologia*, 46(12):3006–3013, 2008.

John C Raven. Manual for raven's progressive matrices and vocabulary scales. *Standard Progressive Matrices*, 1983.

Scott E Reed, Yi Zhang, Yuting Zhang, and Honglak Lee. Deep visual analogy-making. In *Advances in neural information processing systems*, pp. 1252–1260, 2015.

Timothy T Rogers and James L McClelland. *Semantic cognition: A parallel distributed processing approach*. MIT press, 2004.

Adam Santoro, Sergey Bartunov, Matthew Botvinick, Daan Wierstra, and Timothy Lillicrap. Meta-learning with memory-augmented neural networks. In *International conference on machine learning*, pp. 1842–1850, 2016.

Florian Schroff, Dmitry Kalenichenko, and James Philbin. Facenet: A unified embedding for face recognition and clustering. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 815–823, 2015.

Patrick Shafto, Noah D Goodman, and Thomas L Griffiths. A rational account of pedagogical reasoning: Teaching by, and learning from, examples. *Cognitive psychology*, 71:55–89, 2014.

David Silver, Aja Huang, Chris J Maddison, Arthur Guez, Laurent Sifre, George Van Den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, et al. Mastering the game of go with deep neural networks and tree search. *nature*, 529(7587):484, 2016.

Harvey F Silver. *Compare & contrast: Teaching comparative thinking to strengthen student learning*. ASCD, 2010.

Linsey Smith and Dedre Gentner. The role of difference-detection in learning contrastive categories. In *Proceedings of the Annual Meeting of the Cognitive Science Society*, volume 36, 2014.

Noah A. Smith and Jason Eisner. Contrastive estimation: Training log-linear models on unlabeled data. In *ACL*, 2005.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Kilian Q Weinberger and Lawrence K Saul. Distance metric learning for large margin nearest neighbor classification. *Journal of Machine Learning Research*, 10(Feb):207–244, 2009.

Jia-Jie Zhu and José Bento. Generative adversarial active learning. *arXiv preprint arXiv:1702.07956*, 2017.

7 MODEL DETAILS

7.1 VISUAL ANALOGY PROBLEMS

The CNN was 4-layers deep, with 32 kernels per layer, each of size 3×3 with a stride of 2. Thus, each layer downsampled the image by half. Each panel in a question was 80×80 pixels, and greyscale. The panels were presented one at a time to the CNN to produce 9 total embeddings (3 for the source sequence, 2 for the target sequence, and 4 for each candidate). We then used these embeddings to compile 4 distinct inputs for the RNN. Each input was comprised of the source sequence embeddings, the target sequence embeddings, and a *single* candidate embedding, for a total of 6 embeddings per RNN-input sequence. We passed these independently to the RNN (with 64 hidden units), whose final output was then passed through a linear layer to produce a single scalar. 4 such passes (one for each source-target-candidate sequence) produced 4 scalar scores, denoting the model's evaluation of the suitability of the particular candidate for the analogy problem. Finally, a softmax was computed across the scores to select the model's "answer". We used a cross entropy loss function and the Adam optimizer with a learning rate of $1e^{-4}$.

7.2 SYMBOLIC ANALOGY PROBLEMS

A given input consisted of a set of vectors 16-dimensional vectors. This set included 8 vectors comprising S_1, one vector d_1, 8 vectors comprising S_2, and 8 vectors comprising the set of candidate vectors C. Vectors were given a single digit binary variable tag to denote whether they were members of the source or target set (augmenting their size to 17-dimensions).

We employed a parallel processing architecture, similar to the visual analogy experiments, with a Relation Network (128 unit, 3 layer MLP with ReLU non-linearities for the g_θ function and a similar 2-layer MLP for the f_ϕ function) replacing the RNN core. Thus, a single model processed (S_1, d_1, S_2, c_n), with c_n being a different candidate vector from C for each parallel pass. The model's output was a single scalar denoting the score assigned to the particular candidate c_n – these scores were then passed through a softmax, and training proceeded using a cross entropy loss function. We used batch sizes of 32 and the Adam optimizer with a learning rate of $3e^{-4}$.

8 SUPPLEMENTARY RESULTS

		LABC (Train)	Normal (Train)	Mix (Train)	LABC (Contrasting)	Normal (Contrasting)	Mix (Contrasting)	LABC (Normal)	Normal (Normal)	Mix (Normal)
Extrapolation	Mean	0.94	0.95	0.94	0.62	0.43	0.56	0.45	0.44	0.39
	Std	0.005	0.007	0.005	0.02	0.009	0.012	0.01	0.01	0.04
Interpolation	Mean	0.94	0.97	0.94	0.93	0.45	0.89	0.65	0.89	0.87
	Std	0.003	0.003	0.003	0.004	0.004	0.008	0.01	0.006	0.01
Novel Domain Transfer	Mean	0.88	0.83	0.85	0.87	0.48	0.88	0.7	0.82	0.79
	Std	0.015	0.01	0.015	0.005	0.02	0.009	0.01	0.01	0.02
Novel Domain (shape colour)	Mean	0.87	0.84	0.85	0.78	0.50	0.80	0.51	0.61	0.58
	Std	0.007	0.008	0.007	0.004	0.02	0.006	0.02	0.01	0.02
Novel Domain (line type)	Mean	0.87	0.85	0.86	0.76	0.45	0.75	0.5	0.57	0.54
	Std	0.006	0.004	0.006	0.02	0.01	0.02	0.02	0.02	0.01

Table 1: **Results for the visual analogy task**.

9 FURTHER DISCUSSION AND RELATED WORK

It is interesting to consider to what extent the effects reported in this work can transfer to a wider class of learning and reasoning problems beyond classical analogies. The importance of teaching concepts (to humans or models) by contrasting with negative examples is relatively established in both cognitive science (Shafto et al., 2014; Smith & Gentner, 2014) and educational research (Silver, 2010; Ali, 1981). Our results underline the importance of this principle when training modern neural networks to replicate human-like cognitive processes and reasoning from raw perceptual input. In cases where expert understanding of potential data exists, for instance in the case of active learning with human interaction, it provides a recipe for achieving more robust representations leading to far greater powers of generalization. We should aspire to select as negative examples those examples that are plausible considering the most abstract principles that describe the data.

A further notable property of our trained networks is the fact they can resolve analogies (even those involving with unfamiliar input domains) in a single rollout (forward pass) of a recurrent network. This propensity for fast reasoning has an interesting parallel with the fast and instinctive way in which humans can execute visual analogical reasoning (Morrison et al., 2001; Qiu et al., 2008).

9.1 DISTANCE METRIC APPROACHES

LBC shares similarities with distance metric approaches such as the large-margin nearest neighbor classifier (LMNN) (Weinberger & Saul, 2009), the triplet loss (Schroff et al., 2015), and others. In these approaches the goal is to transform inputs such that the distance between input embeddings from the same class is small, while the distance between input embeddings from different classes is large. Given these improved embeddings, classification can proceed using off-the-shelf classification algorithms, such as k-nearest neighbors. We note that these approaches emphasize the form of the loss function and the quality of the resultant input embeddings on subsequent classification. However, the goal of LBC is not to induce better classification *per se*, as it is in these methods. Instead, the goal is to induce out-of-distribution generalisation by virtue of improved abstract understanding of the underlying problem. It is unclear, for example, whether the embeddings produced by LMNN or the triplet loss are naturally amenable to this kind of generalisation, and as far as we are aware, it has not beed tested. Nonetheless, LBC places a critical focus on the nature, or quality of the data comprising the incorrect classes, and is agnostic to the exact nature of the loss function. Thus, it is possible to use previous approaches (e.g., LMNN or triplet loss, etc.) in conjunction with LBC, which we do not explore. LBC also shares similarities to recent generative adversarial active learning approaches (Zhu & Bento, 2017). However, these approaches do not explicitly point to the effects of the quality of incorrect samples to out-of-distribution generalisation, nor are we aware of any experiments that test abstract generalisation using networks trained with generative samples.