Learning what you can do before doing anything

Abstract

Intelligent agents are able to learn and understand the action spaces of other agents simply by observing them act. Such representations can help them to quickly learn to predict the effects of their own actions on the environment and plan complex interaction sequences. Current deep learning methods can capture the structured representations needed for such predictive capabilities, but only when given abundant, action-labeled data. We propose an unsupervised method to learn representations of an agent's action space purely from visual observations, i.e., video. Our method uses stochastic future prediction to learn a latent variable that captures (i) the dynamic properties of scenes while being minimally sensitive to static scene content and (ii) the compositional structure of actions, reflecting the fact that the changes they induce can be composed to produce a cumulative effect on the environment. We show the applicability of our method to synthetic settings and its potential to capture action spaces in complex, realistic visual settings. Our learned representations perform comparably to existing supervised methods on tasks such as action-conditioned video prediction and visual servoing, while requiring orders of magnitude fewer action-labeled videos.

1 Introduction

Agents behaving in real-world environments rely on perception to judge what actions they can take and what effect these actions will have. Purely perceptual learning may play an important role in how these action representations are acquired and used. Consider an infant that is first learning to walk. From around 10 months of age, infants rapidly progress from crawling, to irregular gaits with frequent falling, and finally to reliable locomotion (Adolph et al. (2012)). But before they first attempt to walk, infants have extensive sensory exposure to adults walking. Unsupervised learning from sensory experience of this type appears to play a critical role in how humans acquire representations of actions before they can reliably reproduce the corresponding behaviour (Ullman et al. (2012)). Infants need to relate the set of motor primitives they can generate to the action spaces exploited by adults (Dominici et al. (2011)), and a representation acquired by observation may allow an infant to more efficiently learn to produce natural, goal-directed walking behavior.

Reinforcement learning (RL) provides an alternative to the unsupervised learning approach as it implicitly discovers an agent's action space and the consequences of its actions. Recent breakthroughs in RL suggest that end-to-end training can be used to learn mappings between sensory input and actions (Mnih et al. (2015); Lillicrap et al. (2016); Levine et al. (2016a;b)). However, these methods are sample inefficient and the action representations learned in this way cannot be easily generalized to new agents with a different control interface. Unsupervised methods for sensorimotor learning may facilitate learning from passively collected data, as well as make it easier to reuse action representations between systems with different effectors and goals. The representations learned by unsupervised methods are invariant to these choices because the model does not have access to motor commands or goals during training. This property may also be useful for imitation learning, where ground truth actions are often hard or impossible to collect other than by visual observation (Finn et al. (2017); Pathak et al. (2018)).

In this work, we evaluate the proposal that learning *what you can do before doing anything* can lead to action space representations that make subsequent learning more efficient. As for an infant, such a representation can be used as the basis for later learning of goal-directed behavior (Marblestone et al.

Figure 1: Two sequences starting from different initial states but changing according to the same actions. Without requiring labels, our model learns to represent the action in sequences like these identically. We train a representation z to capture the dynamics of the scene and its compositional structure: applying (z_1 and z_2) should have the same effect as applying the composed representation ($g(z_1, z_2)$). These properties capture the fact that effector systems, such as a robot arm, use the same composable action space in many different states.

(2016)). This representation is analogous to the representations in the parietal and premotor areas of cortex, which include populations of neurons that represent the structure of actions produced both by the self and by others (Rizzolatti et al. (1996); Romo et al. (2004)) and that are critical for reliably producing flexible, voluntary motor control (see Kandel et al. (2012), Chapter 38).

In contrast to most approaches to unsupervised learning of dynamics, which focus on learning the statistical structure of the environment, we focus on disentangling action information from the instantaneous state of the environment (Fig. 1). We base our work on recent stochastic video prediction methods (Babaeizadeh et al. (2018); Denton & Fergus (2018); Lee et al. (2018)) and impose two properties on the latent representation. First, the representation is trained to be *minimal*, i.e. containing minimal information about the current world state. This forces the representation to focus on dynamic properties of the sensory input. A similar objective has been used in previous work to constrain the capacity of video prediction models (Denton & Birodkar (2017)). Second, the representation is trained to be *composable*, so that the cumulative effect of subsequent actions can be efficiently computed from individual action representations (Fig. 1). As the composed representation does not have access to the static content of the middle frame, a representation is composable only if the individual action representations are disentangled from the static content. Taken together, this model leads to a representation of sensory dynamics that captures the structure of the agent's actions.

We make the following three contributions. First, we introduce a method for unsupervised learning of an agent's action space by training the latent representation of a stochastic video prediction model for the desiderata of minimality and composability. Second, we show that our method learns a representation of actions that is independent of scene content on (i) a simulated 1DoF robot and (ii) the BAIR robot pushing dataset (Ebert et al. (2017)). Finally, we demonstrate that the learned representation can be used for action-conditioned video prediction and visual servoing, while requiring orders of magnitude fewer action-labeled videos than extant supervised methods.

2 RELATED WORK

Learning structured and minimal representations. Several groups have recently shown how an adaptation of the variational autoencoder (VAE, Kingma & Welling (2014); Rezende et al. (2014)) can be used to learn representations that are minimal in the information-theoretic sense. Alemi et al. (2017) showed that the Information Bottleneck (IB) objective function (Tishby et al. (1999); Shwartz-Ziv & Tishby (2017)) can be optimized with a variational approximation that takes the form of a VAE with an additional weighting hyperparameter. In parallel, Higgins et al. (2017) showed that a similar formulation can be used to produce disentangled representations. The connection between disentaglement and minimality of representations was further clarified by Burgess et al. (2018). In this work, we apply the IB principle to temporal models to enforce minimality of the representation.

Several groups have proposed methods to learn disentangled representations of static content and pose from video (Denton & Birodkar (2017); Tulyakov et al. (2018)). Jaegle et al. (2018) learn a

motion representation by enforcing that the motion acts on video frames as a group-theoretic action. In contrast, we seek a representation that disentangles the motion from the static pose.

Thomas et al. (2017) attempt to learn a disentangled representation of controllable factors of variation. While the goals of their work are similar to ours, their model relies on active learning and requires an embodied agent with access to the environment. In contrast, our model learns factors of variation purely from passive temporal visual observations, and thus can be applied even if access to the environment is costly or impossible.

Unsupervised learning with video data. Several recent works have exploited temporal information for representation learning. Srivastava et al. (2015) used the Long Short-Term Memory (LSTM, Hochreiter & Schmidhuber (1997)) recurrent neural network architecture to predict future frames. The representation learned by the architecture was useful for action recognition. Vondrick et al. (2016) showed that architectures using convolutional neural networks (CNNs) can be used to predict actions and objects several seconds into the future. Recently, work such as Finn et al. (2016); Villegas et al. (2017); Denton & Birodkar (2017) has adopted various modifications of the convolutional LSTM architecture (Xingjian et al. (2015)) for the task of video prediction and have shown that the resulting representations are useful for a variety of tasks.

Others have explored applications of video prediction models to RL and control (Weber et al. (2017); Ha & Schmidhuber (2018); Wayne et al. (2018)). Chiappa et al. (2017) and Oh et al. (2015) propose models that predict the consequences of actions taken by an agent given its control output. Similar models have been used to control a robotic arm (Agrawal et al. (2016); Finn & Levine (2017); Ebert et al. (2017)). The focus of this work is on learning action-conditioned predictive models. In contrast, our focus is on the unsupervised discovery of the space of possible actions from video data.

Our model is inspired by methods for stochastic video prediction that, given a sequence of past frames, capture the multimodal distribution of future images (Goroshin et al. (2015); Henaff et al. (2017)). We use the recently proposed recurrent latent variable models based on the variational autoencoder (Babaeizadeh et al. (2018); Denton & Fergus (2018); Lee et al. (2018)). We develop these methods and propose a novel approach to unsupervised representation learning designed to capture an agent's action space.

Sensorimotor representations. There is a long history of work developing sensorimotor representations for applications in reinforcement learning and robotics. Previous work in this domain has primarily focused on introducing hand-crafted abstractions and hierarchies to make sensorimotor mappings more generalizable. Methods for aggregating low-level controls into higher-level representations on which planning and RL can be performed are well-studied in the robotics literature: notable examples include the options framework for hierarchical RL (Sutton et al. (1999); Bacon et al. (2017)), dynamic motion primitives for manipulation (Schaal et al. (2005); Schaal (2006); Niekum et al. (2015)), and recent work that abstracts a learned policy away from low-level control and perception to ease simulation-to-real transfer (Clavera & Abbeel (2017); Müller et al. (2018)). Other work has learned to separate robot-instance specific controls from task-related skills through modular policies, but this work does not enforce any structure onto the intermediate representation and requires extensive interaction with the environment (Devin et al. (2017)).

3 APPROACH

In this section, we describe our architecture for learning an action representation that is *minimal* and *composable*. In Sec. 3.1, we describe a variational video prediction model similar to that of Denton & Fergus (2018) that provides us with a framework for learning a latent representation z_t at time t of the change between the past and the current frames. No labeled actions are considered at this stage. In Sec. 3.2, we introduce an unsupervised method for imposing composability of the latent that allows us to recover a structured representation. To verify that the learned representation corresponds to the executed control, we show that we can learn a bijective mapping between the latent representation and the control output executed at that time using a small number of labeled data points (Sec. 3.3). In the experimental section, we describe how the learned bijective mapping can be used for tasks such as action-conditioned video prediction (Sec. 4.1) and visual servoing (Sec. 4.2).

Figure 2: **Left**: Illustration of architecture showing one step of the stochastic video prediction model. *(a)* During training, the latent variable z_t is estimated with the approximate inference network (MLP$_{\text{infer}}$, CNN$_e$) from the current and previous image. *(b)* At test time, we use the prior distribution $p(z) \sim \mathcal{N}(0, I)$ to produce z_t. Future frames are estimated by passing z_t together with images x_{t-1} through the generative network (LSTM, CNN$_d$). Refer to Appendices A and B for architectural details. **Right**: Composability training. Latent samples z are concatenated pairwise and passed through the composition network MLP$_{\text{comp}}$ that defines a distribution over ν in the trajectory space. A sampled value of ν is decoded into an image through the same generative network (LSTM and CNN$_d$, not shown) and matched to the final image in the composed sequence.

3.1 VIDEO PREDICTION MODEL

At the core of our method is a recurrent latent variable model for video prediction based on a temporal extension of the VAE proposed by Chung et al. (2015). We consider the generative model shown in Fig. 2 (left). At each timestep t, the model outputs a latent variable $z_t \sim p(z) = \mathcal{N}(0, I)$ associated with this timestep. Given a history of frames $\mathbf{x}_{1:t-1}$ and latent samples $\mathbf{z}_{2:t}$, the generative distribution over possible next frames is given by $x_t \sim p_\theta(x_t|\mathbf{x}_{1:t-1}, \mathbf{z}_{2:t}) = \mathcal{N}(\mu_\theta(\mathbf{x}_{1:t-1}, \mathbf{z}_{2:t}), I)$. In practice, we generate the next frame by taking the mean of the conditional distribution: $\hat{x}_t = \mu_\theta(\mathbf{x}_{1:t-1}, \mathbf{z}_{2:t})$.

To optimize the log-likelihood of this generative model, we introduce an additional network approximating the posterior of the latent variable $z_t \sim q_\phi(z_t|x_t, x_{t-1}) = \mathcal{N}(\mu_\phi(x_t, x_{t-1}), \sigma_\phi(x_t, x_{t-1}))$. We can optimize the model using the variational lower bound of the log-likelihood in a formulation similar to the original VAE. However, as has been shown recently by Alemi et al. (2018), the standard VAE formulation does not constrain the amount of information contained in the latent variable z. To overcome this, and to learn a minimal representation of z, we reformulate the standard VAE objective in terms of the Information Bottleneck (IB) (Shwartz-Ziv & Tishby (2017)).

IB minimizes the mutual information, I, between the action representation, z_t, and input frames, $\mathbf{x}_{t-1:t}$, while maximizing the ability to reconstruct the frame x_t as measured by the mutual information between (z_t, x_{t-1}) and x_t:

$$\max_{p_\theta, q_\phi} I((z_t, x_{t-1}), x_t) - \beta_z I(z_t, x_{t-1:t}). \tag{1}$$

The two components of the objective are balanced with a Lagrange multiplier β_z. When the value of β_z is higher, the model learns representations that are more efficient, i.e. minimal in the information-theoretic sense. We use this property to achieve our first objective of *minimality* of z.

The variational IB (Alemi et al. (2017)) provides a variational approximation of the IB objective, that simply takes the form of the original VAE objective with an additional constant β_z. Aggregating over a sequence of frames, the video prediction objective for our model is given by:

$$\mathcal{L}_{\theta, \phi}^{pred}(\mathbf{x}_{1:T}) = \sum_{t=1}^{T} \left[\mathbb{E}_{q_\phi(\mathbf{z}_{2:t}|\mathbf{x}_{1:t})} \log p_\theta(x_t|\mathbf{x}_{1:t-1}, \mathbf{z}_{2:t}) - \beta_z D_{KL}(q_\phi(z_t|\mathbf{x}_{t-1:t})||p(z)) \right]. \tag{2}$$

The full derivation of the variational lower bound is given in the appendix of Denton & Fergus (2018)[1]. The full model for one prediction step is shown in the left part of Fig. 2.

---

[1]Denton & Fergus (2018) use the objective with β_z, but formulate this objective in terms of the original VAE.

3.2 LEARNING ACTION REPRESENTATIONS WITH COMPOSABILITY

Given a history of frames, the latent variable z_t represents the distribution over possible next frames. It can thus be viewed as a representation of possible changes between the previous and the current frame. We will associate the latent variable z_t with the distribution of such changes. In video data of an agent executing actions in an environment, the main source of change is the agent itself. Our model is inspired by the observation that a natural way to represent z_t in such settings is by the agents' actions at time t. In this section, we describe an objective that encourages the previously described model (Sec. 3.1) to learn action representations.

To encourage *composability*, we use the procedure illustrated in Fig. 2 (right). We define an additional random variable $\nu_t \sim q_\zeta(\nu_t|z_t, z_{t-1}) = \mathcal{N}(\mu_\zeta(z_t, z_{t-1}), \sigma_\zeta(z_t, z_{t-1}))$ that is a representation of the trajectory $z_{t-1:t}$. The process of composing latent samples into a single trajectory can be repeated several times in an iterative fashion, where the generative model q_ζ observes a trajectory representation ν_{t-1} and the next latent z_t to produce the composed trajectory representation[2] $\nu_t \sim q_\zeta(\nu_t|\nu_{t-1}, z_t)$. The generative model q_ζ is parameterized with a multilayer perceptron, $\mathrm{MLP_{comp}}$.

We want ν to encode entire trajectories, but we also require it to have minimal information about individual latent samples. We can encourage these two properties by again using the IB objective:

$$\max_{p_\theta, q_{\phi,\zeta}} I((\nu_t, x_1), x_t) - \beta_\nu I(\mathbf{z}_{2:t}, \nu_t). \tag{3}$$

We maximize this objective using the following procedure. Given a trajectory of T frames, we use $\mathrm{MLP_{infer}}$ to retrieve the action representations z. Next, we generate a sequence of trajectory representations ν_t, each of which is composed from C consecutive action representations $\mathbf{z}_{t-C:t}$. We obtain $T_C = \lfloor T/C \rfloor$ such representations. Finally, we use ν_t to produce the corresponding frames $\hat{x}_t = q_\phi(x_t|x_{t-C}, \nu_t)$. The variational approximation to (3) that we use to impose composability takes the following form:

$$\mathcal{L}_{\theta,\phi,\zeta}^{comp}(\mathbf{x}_{1:T}) = \sum_{t=1}^{T_C} \left[\mathbb{E}_{q_{\phi,\zeta}(\nu_{1:t}|\mathbf{x}_{1:T})} \log p_\theta(x_{t \times T_c}|\mathbf{x}_{1:(t-1) \times T_C}, \nu_{1:t}) \right.$$
$$\left. - \beta_\nu D_{KL}(q_{\phi,\zeta}(\nu_t|\mathbf{x}_{(t-1) \times T_C:t \times T_C})||p(\nu)) \right], \tag{4}$$

where the prior distribution over ν is given by the unit Gaussian $\nu \sim p(\nu) = \mathcal{N}(0, I)$.

The objective above encourages the model to find a minimal representation for the trajectories ν. As the trajectories are composed from only the action representations z, this encourages z to assume a form suitable for efficient composition. This allows us to recover an action representation that is *composable*. Our overall training objective is the sum of the two objectives:

$$\mathcal{L}_{\theta,\phi,\zeta}^{total} = \mathcal{L}_{\theta,\phi,\zeta}^{comp} + \mathcal{L}_{\theta,\phi}^{pred}. \tag{5}$$

3.3 GROUNDING THE CONTROL MAPPING

Our approach allows us to learn a latent representation z that is minimal and disentangled from the content of previous images. To use such a learned representation for control, we want to know which action u a certain sample z corresponds to, or vice versa. To determine this correspondence, we learn a simple bijective mapping from a small number of action-annotated frame sequences. We train the bijection using two lightweight multilayer perceptrons, $\hat{z}_t = \mathrm{MLP_{lat}}(u_t)$ and $\hat{u}_t = \mathrm{MLP_{act}}(z_t)$. Note that only the $\mathrm{MLP_{lat}}$ and $\mathrm{MLP_{act}}$ networks are trained in this step, as we *do not* propagate the gradients into the video prediction model. Because we do not have to re-train the video prediction model, this step requires far less data than models with full action supervision (Section 4.2).

We note that standard image-based representations of motion, e.g., optical flow, do not directly form a bijection with actions in most settings. For example, the flow field produced by a reacher (as in Fig. 3) rotating from 12 o'clock to 9 o'clock is markedly different from the flow produced by rotating from 3 o'clock to 12 o'clock, even though the actions producing the two flow fields are identical (a 90 degree counter-clockwise rotation in both cases). In contrast, our representation easily learns a bijection with the true action space.

---

[2]To allow the generative model to distinguish between individual action representations z and trajectory representations ν, we concatenate them with a binary indicator set to 0 for z and 1 for ν.

Figure 3: Transplantation of action representations z from one sequence to another. **Top**: the reacher dataset. The previous frame is superimposed onto each frame to illustrate the movement. **Bottom**: the BAIR dataset. For visualization purposes, the previous and the current position of the end effector are annotated in each frame (red and blue dots, respectively). For each dataset, we run the approximate inference network MLP_{infer} on the donor sequence (top) to get the corresponding action representation z. We then use this sequence of representations z together with a different conditioning image sequence to produce the recipient sequence (bottom). If the action representation is disentangled from static content, the movement in both sequences will be synchronous. We encourage the reader to view additional generated videos at: `www.tinyurl.com/ya6df9yl`.

4 EMPIRICAL EVALUATION

For evaluation, we consider tasks that involve regression from the latent variable to actions and vice versa: action conditioned video prediction and visual servoing (see Fig. 4, left). By learning a bijection between the latent variable, z, and the actions, u, we show that our model finds a representation of actions that is completely disentagled from the static scene content. We also validate that our approach requires orders of magnitude fewer labels than supervised approaches. We conduct experiments on a simple simulated reacher dataset and the real-world Berkeley AI Research (BAIR) robot pushing dataset from Ebert et al. (2017). Refer to Appendix B for the exact architectural parameters.

Datasets. The reacher dataset consists of sequences of a 1DoF reacher arm rotating counter-clockwise with random angular distances between consecutive images. We simulate it using OpenAI's Roboschool environment (Klimov & Schulman (2018)). The actions u are encoded as relative angles between images, and constrained to the range $u \in [0°, 40°]$. The dataset consists of $100\,000$ training and 4000 test sequences. The BAIR robot pushing dataset comprises $44\,374$ training and 256 test sequences of 30 frames each from which we randomly crop out subsequences of 15 frames. We define actions, u, as differences in the spatial position of the end effector in the horizontal plane[3].

Baselines. We compare to the original model of Denton & Fergus (2018) that does not use the proposed composability objective. To obtain an upper bound on our method's performance we also compare to fully supervised approaches that train with action annotations: our implementations are based on Oh et al. (2015) for the reacher dataset and the more complex Finn & Levine (2017) for the BAIR dataset. For visual servoing we use a model based on the approach of Agrawal et al. (2016) that learns the forward and inverse dynamics with direct supervision.

Metrics. In case of the action-conditioned video prediction we use the absolute angular position (obtained using a simple edge detection algorithm, see Appendix D) for the reacher dataset and the change of end effector position (obtained via manual annotation) for the BAIR dataset. We choose these metrics as they capture the direct consequences of applied actions, as opposed to more commonly used visual appearance metrics like PSNR or SSIM. For visual servoing in the reacher environment we measure the angular distance to the goal state at the end of servoing.

4.1 ACTION-CONDITIONED VIDEO PREDICTION

To verify that our model can recover a disentangled representation of actions, we show that the learned representation allows to conduct two semantic operations. First, we show that it is possible to

---

[3]The original dataset provides two additional discrete actions: gripper closing and lifting. However, we found that, in this dataset, the spatial position in the horizontal plane explains most of the variance in the end effector position and therefore ignore the discrete actions in this work.

		Reacher	BAIR
Method		Abs. Error [in deg]	Rel. Error [in px]
Start State		90.1 ± 51.8	-
Random		26.6 ± 21.5	-
Denton & Fergus		22.6 ± 17.7	3.6 ± 4.0
Ours		$\mathbf{2.9 \pm 2.1}$	$\mathbf{3.0 \pm 2.1}$
Supervised		2.6 ± 1.8	2.0 ± 1.3

Figure 4: **Left**: Illustration of how the learned representation can be used for (a) action-conditioned prediction by inferring the latent variable, z_t, from the action, and (b) visual servoing by solving the control problem in latent space through iterated rollouts and then mapping the latent variable to robot control actions, u_t. **Right**: Action-conditioned video prediction results (mean $\pm$ standard deviation across predicted sequences). The supervised baseline is taken from Oh et al. (2015) for the reacher dataset and Finn & Levine (2017) for BAIR.

transplant the action representations z from a given sequence into one with a different initial state. While the content of the scene changes, the executed actions should remain the same. Second, we show how our model can be used for *action-conditioned* video prediction. Given a ground truth sequence annotated with actions u, we infer the representations z directly from u using MLP_{lat}. The inferred representations are fed into the generative model p_θ and the resulting sequences are compared to the original sequence. Qualitative results are shown in Fig. 3, with additional results in Figs. 8, 9 and 10 in the Appendix and at www.tinyurl.com/ya6df9yl.

The quantitative results in Fig. 4 (right) show that on the reacher dataset the model trained with composability objective learns a representation corresponding to robot actions. The model compares favorably to the fully supervised model, which observes many more sequences annotated with actions. Denton & Fergus (2018) performs the task only slightly better than random guessing. This shows that it is infeasible to infer the latent z_t learned by the baseline model given only the action u_t.

On the BAIR dataset, our model performs better than the baseline of Denton & Fergus (2018) , reducing the difference between the best unsupervised method and the supervised baseline by $30\,\%$. This is reflected in qualitative results as frames generated by the baseline model often contain artifacts such as blurriness when the arm is moving or ghosting effects with two arms present in the scene (Figs. 9 and 10 in the Appendix, videos at www.tinyurl.com/ya6df9yl). These results demonstrate the promise of our approach in settings involving more complex, real-world interactions.

4.2 VISUAL SERVOING

To demonstrate that the learned action representation is useful for control, we use it to drive visual servoing. The objective of visual servoing is to move an agent from a start state to a goal state, given by images x_0 and x_{goal}, respectively. We use a servoing algorithm similar to that of Finn & Levine (2017), but plan trajectories in the latent space z instead of true actions u. We use MLP_{act} to retrieve the actions that correspond to a planned trajectory.

Our visual servoing approach, based on Model Predictive Control (MPC), is described in Appendix C. The controller plans the trajectory by performing a number of rollouts and iteratively refines its predictions using the Cross Entropy Method (CEM, Rubinstein & Kroese (2004)). We select the rollout whose final state is closest to the goal and execute its first action. The distance is measured in image space using the cosine distance between VGG16 representations (Simonyan & Zisserman (2015)). Servoing terminates once the goal is reached or the maximum steps are executed.

Fig. 5 (left) shows qualitative results of a servoing rollout in the reacher environment. The agent not only reaches the target but also plans accurate trajectories at each intermediate time step. The trajectory planned in the latent space can be correctly decoded into actions, u, which further supports the claim that a representation of actions is learned. In Fig. 5 (right), we measure the data efficiency of our method and both baseline approaches that fully rely on action-label supervision during training. Most notably, our model substantially outperforms the baselines in the low-data regime where only a few action-labeled training sequences are used. We observed a similar trend in the accuracy of action-conditioned prediction. This is because our method can leverage the unsupervised pre-training. With access to more training examples our model still performs on par with both supervised baselines.

Figure 5: Visual servoing on the reacher task. **Left**: Planned and executed servoing trajectories. Each of the first five rows shows the trajectory re-planned at the corresponding timestep. The first image of each sequence (highlighted in red) is the current state of the system, and the images to the right of it show the model prediction with the lowest associated cost. The target state (the reacher pointing to the upper left) is shown superimposed over each image. **Right**: Data efficiency measured as final distance to the goal after servoing, shown as a function of the number of videos used in training. Each point represents a model trained to convergence on a dataset with a restricted number of action-annotated videos. See Tab. 1 of the Appendix for more detail.

Figure 6: Visualization of the learned latent space structure, z, on the reacher dataset. Each point depicts a sampled value of z for 1000 different frame pairs from the dataset. We plot the projection of z onto the first two principal components of the data. Each point is colored by the value of the ground truth rotation, in radians, depicted in the two images used to infer z for that point. **Left**: Our method learns a latent space with a clear correspondence to the ground truth actions. **Right**: The latent space learned by the baseline model has no discernible correspondence to the ground truth actions. In the Appendix, Fig. 12 further investigates why the baseline fails to produce disentangled representations.

4.3 LEARNED STRUCTURE OF THE ACTION REPRESENTATIONS

To inspect the structure that our model learns, we visualize samples from the latent space, z, on the reacher dataset in Fig. 6. To find the two-dimensional subspace with maximal variability, we conducted Principal Component Analysis (PCA) on the means of the distributions generated by $\text{MLP}_{\text{infer}}$. We note that the first PCA dimension captures 99% of the variance, which can be explained by the fact that the robot in consideration has one degree of freedom. We can see that while the baseline without composability training fails to learn a representation disentangled from the static content, our method correctly recovers the structure of possible actions of the robot.

5 CONCLUSION

We have shown a way of learning the structure of an agent's action space from visual observations by imposing the properties of minimality and composability on a latent variable for stochastic video prediction. This strategy offers a data-efficient alternative to approaches that rely on fully supervised action-conditioned methods. The resulting representation can be used for a range of tasks, such as action-conditioned video prediction and visual servoing. It captures meaningful structure in synthetic settings and achieves promising results in realistic visual settings.

REFERENCES

Karen Adolph, Whitney Cole, Meghana Komati, Jessie Garciaguirre, Daryaneh Badaly, Jesse Linge-man, Gladys Chan, and Rachel Sotsky. How do you learn to walk? thousands of steps and dozens of falls per day. Psychological Science, 23(11):1387—-1394, 2012.

Pulkit Agrawal, Ashvin V Nair, Pieter Abbeel, Jitendra Malik, and Sergey Levine. Learning to poke by poking: Experiential learning of intuitive physics. In Proceedings of Neural Information Processing Systems, 2016.

Alexander Alemi, Ben Poole, Ian Fischer, Joshua Dillon, Rif A. Saurous, and Kevin Murphy. Fixing a broken ELBO. In Proceedings of International Conference on Machine Learning, 2018.

Alexander A Alemi, Ian Fischer, Joshua V Dillon, and Kevin Murphy. Deep variational information bottleneck. In Proceedings of International Conference on Learning Representations, 2017.

Mohammad Babaeizadeh, Chelsea Finn, Dumitru Erhan, Roy H. Campbell, and Sergey Levine. Stochastic variational video prediction. In Proceedings of International Conference on Learning Representations, 2018.

Pierre-Luc Bacon, Jean Harb, and Doina Precup. The option-critic architecture. In Proceedings of AAAI Conference on Artificial Intelligence, 2017.

Christopher P Burgess, Irina Higgins, Arka Pal, Loic Matthey, Nick Watters, Guillaume Desjardins, and Alexander Lerchner. Understanding disentangling in β-VAE. arXiv:1804.03599, 2018.

Silvia Chiappa, Sébastien Racanière, Daan Wierstra, and Shakir Mohamed. Recurrent environment simulators. In Proceedings of International Conference on Learning Representations, 2017.

Junyoung Chung, Kyle Kastner, Laurent Dinh, Kratarth Goel, Aaron C Courville, and Yoshua Bengio. A recurrent latent variable model for sequential data. In Proceedings of Neural Information Processing Systems, 2015.

Ignasi Clavera and P Abbeel. Policy transfer via modularity. In Proceedings of IEEE/RSJ International Conference on Intelligent Robots and Systems, 2017.

Emily Denton and Vighnesh Birodkar. Unsupervised learning of disentangled representations from video. In Proceedings of Neural Information Processing Systems, pp. 4417–4426, 2017.

Emily Denton and Rob Fergus. Stochastic Video Generation with a Learned Prior. In Proceedings of International Conference on Machine Learning, 2018.

Coline Devin, Abhishek Gupta, Trevor Darrell, Pieter Abbeel, and Sergey Levine. Learning mod-ular neural network policies for multi-task and multi-robot transfer. In Proceedings of IEEE International Conference on Robotics and Automation, 2017.

Nadia Dominici, Yuri Ivanenko, Germana Cappellini, Andrea d'Avella, Vito Mondì, Marika Cicchese, Adele Fabiano, Tiziana Silei, Ambrogio Di Paolo, Carlo Giannini, Richard Poppele, and Francesco Lacquaniti. Locomotor primitives in newborn babies and their development. Science, 334(6058): 977—-979, 2011.

Frederik Ebert, Chelsea Finn, Alex X Lee, and Sergey Levine. Self-supervised visual planning with temporal skip connections. In Conference on Robotic Learning, 2017.

Chelsea Finn and Sergey Levine. Deep visual foresight for planning robot motion. In Proceedings of IEEE International Conference on Robotics and Automation, 2017.

Chelsea Finn, Ian Goodfellow, and Sergey Levine. Unsupervised learning for physical interaction through video prediction. In Proceedings of Neural Information Processing Systems, 2016.

Chelsea Finn, Tianhe Yu, Tianhao Zhang, Pieter Abbeel, and Sergey Levine. One-shot visual imitation learning via meta-learning. In Conference on Robotic Learning, 2017.

Ross Goroshin, Michael F Mathieu, and Yann LeCun. Learning to linearize under uncertainty. In Proceedings of Neural Information Processing Systems, 2015.

David Ha and Jurgen Schmidhuber. World models. arXiv:1803.10122, 2018.

Mikael Henaff, Junbo Zhao, and Yann LeCun. Prediction under uncertainty with error-encoding networks. arXiv:1711.04994, 2017.

Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-VAE: Learning basic visual concepts with a constrained variational framework. In Proceedings of International Conference on Learning Representations, 2017.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. Neural computation, 9(8): 1735–1780, 1997.

Andrew Jaegle, Stephen Phillips, Daphne Ippolito, and Kostas Daniilidis. Understanding image motion with group representations. In Proceedings of International Conference on Learning Representations, 2018.

Justin Johnson, Alexandre Alahi, and Li Fei-Fei. Perceptual losses for real-time style transfer and super-resolution. In Proceedings of European Conference on Computer Vision, 2016.

Eric R. Kandel, James H. Schwartz, Thomas M. Jessell, Steven A. Siegelbaum, and A. J. Hudspeth (eds.). Principles of Neural Science. McGraw-Hill Education, 5 edition, 2012.

Diederik P Kingma and Max Welling. Auto-encoding variational Bayes. In Proceedings of International Conference on Learning Representations, 2014.

Oleg Klimov and John Schulman. Roboschool: Open-source software for robot simulation, 2018. URL https://blog.openai.com/roboschool.

Alex X. Lee, Richard Zhang, Frederik Ebert, Pieter Abbeel, Chelsea Finn, and Sergey Levine. Stochastic adversarial video prediction. arXiv:1804.01523, 2018.

Sergey Levine, Chelsea Finn, Trevor Darrell, and Pieter Abbeel. End-to-end training of deep visuomotor policies. The Journal of Machine Learning Research, 17(1):1334–1373, 2016a.

Sergey Levine, Peter Pastor, Alex Krizhevsky, and Deirdre Quillen. Learning hand-eye coordination for robotic grasping with large-scale data collection. In International Symposium on Experimental Robotics. Springer, 2016b.

Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. In Proceedings of International Conference on Learning Representations, 2016.

Adam H Marblestone, Greg Wayne, and Konrad P Kording. Toward an integration of deep learning and neuroscience. Frontiers in computational neuroscience, 10:94, 2016.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A. Rusu, Joel Veness, Marc G. Bellemare, Alex Graves, Martin Riedmiller, Andreas K. Fidjeland, Georg Ostrovski, Stig Petersen, Charles Beattie, Amir Sadik, Ioannis Antonoglou, Helen King, Dharshan Kumaran, Daan Wierstra, Shane Legg, and Demis Hassabis. Human-level control through deep reinforcement learning. Nature, 518:529–533, 02 2015.

Matthias Müller, Alexey Dosovitskiy, Bernard Ghanem, and Vladen Koltun. Driving policy transfer via modularity and abstraction. Conference on Robotic Learning, 2018.

Scott Niekum, Sarah Osentoski, George Konidaris, Sachin Chitta, Bhaskara Marthi, and Andrew G Barto. Learning grounded finite-state representations from unstructured demonstrations. The International Journal of Robotics Research, 34(2):131–157, 2015.

Junhyuk Oh, Xiaoxiao Guo, Honglak Lee, Richard Lewis, and Satinder Singh. Action-conditional video prediction using deep networks in atari games. In Proceedings of Neural Information Processing Systems, 2015.

Deepak Pathak, Parsa Mahmoudieh, Guanghao Luo, Pulkit Agrawal, Dian Chen, Yide Shentu, Evan Shelhamer, Jitendra Malik, Alexei A Efros, and Trevor Darrell. Zero-shot visual imitation. In Proceedings of International Conference on Learning Representations, 2018.

Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. In Proceedings of International Conference on Machine Learning, 2014.

Giacomo Rizzolatti, Luciano Fadiga, Vittorio Gallese, and Leonardo Fogassi. Premotor cortex and the recognition of motor actions. Cognitive Brain Research, 3(2):131 – 141, 1996.

Ranulfo Romo, Adrián Hernández, and Antonio Zainos. Neuronal correlates of a perceptual decision in ventral premotor cortex. Neuron, 41(1):165–173, 2018/05/18 2004.

Reuven Y. Rubinstein and Dirk P. Kroese. The Cross-Entropy Method: A Unified Approach to Combinatorial Optimization, Monte-Carlo Simulation and Machine Learning. Springer-Verlag New York, 2004.

Stefan Schaal. Dynamic Movement Primitives - A Framework for Motor Control in Humans and Humanoid Robotics. Springer Tokyo, 2006.

Stefan Schaal, Jan Peters, Jun Nakanishi, and Auke Ijspeert. Learning movement primitives. In Paolo Dario and Raja Chatila (eds.), Robotics Research. Springer Berlin Heidelberg, 2005.

Ravid Shwartz-Ziv and Naftali Tishby. Opening the black box of deep neural networks via information. arXiv:1703.00810, 2017.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. In Proceedings of International Conference on Learning Representations, 2015.

Nitish Srivastava, Elman Mansimov, and Ruslan Salakhudinov. Unsupervised learning of video representations using LSTMs. In Proceedings of International Conference on Machine Learning, 2015.

Richard S. Sutton, Doina Precup, and Satinder Singh. Between MDPs and semi-MDPs: A framework for temporal abstraction in reinforcement learning. Artificial Intelligence, 112:181–211, 1999.

Valentin Thomas, Jules Pondard, Emmanuel Bengio, Marc Sarfati, Philippe Beaudoin, Marie-Jean Meurs, Joelle Pineau, Doina Precup, and Yoshua Bengio. Independently controllable features. arXiv:1708.01289, 2017.

N. Tishby, F. C. Pereira, and W. Bialek. The information bottleneck method. Allerton Conference on Communication, Control, and Computing, 1999.

Sergey Tulyakov, Ming-Yu Liu, Xiaodong Yang, and Jan Kautz. MoCoGAN: Decomposing motion and content for video generation. In Proceedings of IEEE Conference on Computer Vision and Pattern Recognition, 2018.

Shimon Ullman, Daniel Harari, and Nimrod Dorfman. From simple innate biases to complex visual concepts. Proceedings of the National Academy of Sciences, 109(44):18215–18220, 2012.

Ruben Villegas, Jimei Yang, Seunghoon Hong, Xunyu Lin, and Honglak Lee. Decomposing motion and content for natural video sequence prediction. In Proceedings of International Conference on Learning Representations, 2017.

Carl Vondrick, Hamed Pirsiavash, and Antonio Torralba. Anticipating visual representations from unlabeled video. In Proceedings of IEEE Conference on Computer Vision and Pattern Recognition, 2016.

Greg Wayne, Chia-Chun Hung, David Amos, Mehdi Mirza, Arun Ahuja, Agnieszka Grabska-Barwinska, Jack W. Rae, Piotr Mirowski, Joel Z. Leibo, Adam Santoro, Mevlana Gemici, Malcolm Reynolds, Tim Harley, Josh Abramson, Shakir Mohamed, Danilo Jimenez Rezende, David Saxton, Adam Cain, Chloe Hillier, David Silver, Koray Kavukcuoglu, Matthew Botvinick, Demis Hassabis, and Timothy P. Lillicrap. Unsupervised predictive memory in a goal-directed agent. arXiv:1803.10760, 2018.

Theophane Weber, Sébastien Racanière, David P. Reichert, Lars Buesing, Arthur Guez, Danilo Jimenez Rezende, Adrià Puigdomènech Badia, Oriol Vinyals, Nicolas Heess, Yujia Li, Razvan Pascanu, Peter Battaglia, David Silver, and Daan Wierstra. Imagination-augmented agents for deep reinforcement learning. In Proceedings of Neural Information Processing Systems, 2017.

Shi Xingjian, Zhourong Chen, Hao Wang, Dit-Yan Yeung, Wai-Kin Wong, and Wang-chun Woo. Convolutional LSTM network: A machine learning approach for precipitation nowcasting. In Proceedings of Neural Information Processing Systems, 2015.

A STOCHASTIC VIDEO PREDICTION

We use an architecture similar to SVG-FP of Denton & Fergus (2018). Input images x_t are encoded using a convolutional neural network $\text{CNN}_e(\cdot)$ to produce a low-dimensional representation $\text{CNN}_e(x_t)$; output image encodings can be decoded with a neural network with transposed convolutions $\text{CNN}_d(\cdot)$. We use a Long Short-Term Memory network $\text{LSTM}(\cdot, \cdot)$ for the generative network $\mu_\theta(x_{t-1}, z_t) = \text{CNN}_d(\text{LSTM}(\text{CNN}_e(x_{t-1}), z_t))$, and a multilayer perceptron $\text{MLP}_{\text{infer}}$ for the approximate inference network $[\mu_\phi(x_t, x_{t-1}), \sigma_\phi(x_t, x_{t-1})] = \text{MLP}_{\text{infer}}(\text{CNN}_e(x_t), \text{CNN}_e(x_{t-1}))$.

During training, our model first observes K past input frames. From these, the model generates $K - 1$ corresponding latents $z_{2:K}$ and predicts $K - 1$ images $\hat{\mathbf{x}}_{2:K} = \mu_\theta(\mathbf{x}_{1:K-1}, \mathbf{z}_{2:K})$. The model generates $T - K$ further future images: $\hat{\mathbf{x}}_{K+1:T} = \mu_\theta(\hat{\mathbf{x}}_{1:T-1}, \mathbf{z}_{1:T})$. At test time, latents z_t are sampled from the prior $\mathcal{N}(0, I)$, and the model behaves identically otherwise. We show samples from the stochastic video prediction model in Fig. 7.

Unlike in Denton & Fergus (2018), the generating network p_θ does not observe ground truth frames $\mathbf{x}_{K+1:T-1}$ in the future during training but autoregressively takes its own predicted frames $\hat{\mathbf{x}}_{K+1:T-1}$ as inputs. This allows the network LSTM to generalize to observing the generated frame encodings $\text{LSTM}(\text{CNN}_e(x_{t-1}), z_t)$ at test time when no ground truth future frames are available. We use a recurrence relation of the form $\text{LSTM}(\text{LSTM}(x_{t-2}, z_{t-1}), z_t)$. To overcome the generalization problem, Denton & Fergus (2018) instead re-encode the produced frames with a recurrence relation of the form $\text{LSTM}(\text{CNN}_e(\text{CNN}_d(\text{LSTM}(x_{t-2}, z_{t-1}))), z_t)$. Our approach omits the re-encoding, which saves a considerable amount of computation.

B EXPERIMENTAL PARAMETERS

For all experiments, we condition our model on five images and roll out ten future images. We use images with a resolution of 64×64 pixels. The dimension of the image representation is $\dim(g(x)) = 128$, and the dimensions of the learned representation are $\dim(z) = \dim(\nu) = 10$. For the reacher dataset, we use the same architecture as Denton & Fergus (2018) for the f, g and LSTM networks. For the BAIR dataset, we do not use f, g and use the same model as Lee et al. (2018) for LSTM. The $\text{MLP}_{\text{infer}}$ has two hidden layers with 256 and 128 units, respectively. The $\text{MLP}_{\text{comp}}, \text{MLP}_{\text{lat}}$, and MLP_{act} networks each have two hidden layers with 32 units. The number of latent samples z used to produce a trajectory representation ν is $C = 4$. For all datasets, $\beta_z = 10^{-2}, \beta_\nu = 10^{-8}$ We use the leaky ReLU activation function in the g, f, and MLP networks. We optimize the objective function using the Adam optimizer with parameters $\beta_1 = 0.9, \beta_2 = 0.999$ and a learning rate of 2×10^{-4}.

We found the following rule for choosing both bottleneck parameters β_z, β_ν to be both intuitive and effective in practice: they should be set to the highest value at which samples from the approximate inference q produce high-quality images. If the value is too high, the latent samples will not contain enough information to specify the next image. If the value is too low, the divergence between the approximate inference and the prior will be too large and therefore the samples from the prior will be of inferior quality. We note that the problem of determining β is not unique to this work and occurs in all stochastic video prediction methods, as well as VIB and β-VAE.

C VISUAL SERVOING

We use Algorithm 1 for visual servoing. At each time step, we initially sample M latent sequences $\boldsymbol{z}_0$ from the prior $\mathcal{N}(0, I)$ and use the video prediction model to retrieve M corresponding image sequences $\boldsymbol{\tau}$, each with K frames. We define the cost of an image trajectory as the cosine distance between the VGG16 (Simonyan & Zisserman (2015)) feature representations of the target image and the final image of each trajectory. This is a perceptual distance, as in Johnson et al. (2016). In the update step of the Cross Entropy Method (CEM) algorithm, we rank the trajectories based on their cost and fit a diagonal Gaussian distribution to the latents $\boldsymbol{z}'$ that generated the M' best sequences. We fit one Gaussian for each prediction time step $k \in K$. After sampling a new set of latents $\boldsymbol{z}_{n+1}$ from the fitted Gaussian distributions we repeat the procedure for a total of N iterations.

Table 1: Distance to the goal at the end of servoing (mean $\pm$ standard deviation). The two lower methods are supervised and observe many more action-labeled datapoints than our method does.

Reacher			
Method	Distance [deg]		
Training Sequences	100	1000	10 000
Start Position	——————— 97.8 ± 23.7 ———————		
Random	——————— 27.0 ± 26.8 ———————		
Denton & Fergus (2018)	20.9 ± 13.0	15.5 ± 13.1	14.1 ± 10.7
Ours	$\mathbf{2.0 \pm 2.2}$	$\mathbf{2.2 \pm 1.8}$	$\mathbf{1.6 \pm 1.0}$
Agrawal et al. (2016)	32.7 ± 21.7	3.6 ± 3.1	2.0 ± 1.5
Oh et al. (2015)	21.8 ± 12.9	2.6 ± 2.6	1.8 ± 1.5

Table 2: Hyperparameters for the visual servoing experiments. We sample an angle uniformly from the angle difference range to create each subsequent image in a sequence.

Servoing Parameters	
Servoing timesteps (T)	5
Servoing horizon (K)	5
# servoing sequences (M)	10
# refit sequences (M')	3
# refit iterations (N)	4
Angle difference range	$[0°, 40°]$

Finally, we pick the latent sequence corresponding to the best rollout of the last iteration and map its first latent sample to the output control action using the learned mapping: $u^* = \mathrm{MLP}_{\mathrm{act}}(z_{N,0}^*)$. This action is then executed in the environment. The action at the next time step is chosen using the same procedure with the next observation as input. The algorithm terminates when the specified number of servoing steps T has been executed.

Algorithm 1 Visual Servoing with Video Prediction Model

Require: Video prediction model $\hat{x}_{t:t+K} = \mu_\theta(x_{1:t-1}, z_{2:t+K})$
Require: Start and goal images i_0 and i_{goal}
1: **for** $t = 1 \ldots T$ **do**
2:     Initialize latents from prior: $\boldsymbol{z}_0 \sim \mathcal{N}(0, I)$
3:     **for** $n = 0 \ldots N$ **do**
4:         Rollout prediction model for K steps, obtain M future sequences $\boldsymbol{\tau} = \hat{\boldsymbol{x}}_{t:t+K}$
5:         Compute cosine distance between final and goal image: $c(\tau) = \cos(\hat{x}_{t+K}, i_{\mathrm{goal}})$
6:         Choose M' best sequences, refit Gaussian distribution: $\boldsymbol{\mu}_{n+1}, \boldsymbol{\sigma}_{n+1} = \mathrm{fit}(\boldsymbol{z}_n^j)$
7:         Sample new latents from updated distribution: $\boldsymbol{z}_{n+1} \sim \mathcal{N}(\boldsymbol{\mu}_{n+1}, \boldsymbol{\sigma}_{n+1})$
8:     **end for**
9:     Map first latent of best sequence to action: $u^* = \mathrm{MLP}_{\mathrm{act}}(z_{N,0}^*)$
10:     Execute u^* and observe next image
11: **end for**

The parameters used for our visual servoing experiments are listed in Tab. 2.

D   ANGLE DETECTION ALGORITHM

We employ a simple, hand-engineered algorithm to quickly retrieve the absolute angle values from the images of the reacher environment. First we convert the input to a gray scale image and run a simple edge detector to obtain a binary image of the reacher arm. We smooth out noise by morphological opening. We compute the Euclidean distance to the image center for all remaining non-zero pixels and locate the reacher tip at the pixel closest to the known reacher arm length. This gives us the absolute reacher arm angle.

To evaluate the accuracy of our angle detection algorithm, we estimated the angle for all images of the simulated training dataset and compare it to ground truth. A histogram of the angle errors of our algorithm is displayed in Fig. 11. All errors are below 10 degrees and the majority are smaller than 5 degrees. This suggests the output of this model is of a suitable quality to serve as surrogate ground truth. A second approach that used a neural network to regress the angle directly from the pixels achieved similar performance. We attribute the errors to the discretization effects at low image resolutions – it is impossible to achieve accuracy below a certain level due to the discretization.

Figure 7: Typical sequences sampled from the stochastic video prediction model. In the past, the samples z are generated from the approximate inference distribution and match the ground truth exactly. In the future, z is sampled from the prior, and correspond to various possible futures. These three sequences are different plausible continuations of the same past sequence, which shows that the model is capable of capturing the stochasticity of the data.

Figure 8: Typical action-conditioned prediction sequences on the reacher dataset. Each example shows **(1) top**: the ground truth sequence, **(2) middle**: our predictions, **(3) bottom:** predictions of the baseline model (Denton & Fergus (2018)). To illustrate the motion, we overlay the previous position of the arm in each image (transparent arm). Our method produces sequences that are perfectly aligned with the ground truth. The baseline never matches the ground truth motion and is only slightly better than executing random actions. We encourage the reader to view the additional generated videos at: www.tinyurl.com/ya6df9yl

Figure 9: Failure cases of the baseline model on trajectory transplantation. Each example shows **(1) top**: the ground truth sequence, **(2) middle**: our predictions, **(3) bottom:** predictions of the baseline model (Denton & Fergus (2018)). The position of the end effector at the current (blue) and previous (red) timestep is annotated in each frame. The baseline often produces images with two different robot arms and other artifacts. We encourage the reader to view the additional generated videos at: `www.tinyurl.com/ya6df9yl`

True

Generated, Ours

Generated, Denton & Fergus

True

Generated, Ours

Generated, Denton & Fergus

True

Generated, Ours

Generated, Denton & Fergus

Figure 10: Baseline failure cases on action-conditioned video prediction. Each example shows **(1) top**: ground truth sequence, **(2) middle**: our predictions, **(3) bottom:** Denton & Fergus (2018) baseline. The previous and the current position of the end effector are annotated in each frame. The baseline often produces images with two different robot arms and other artifacts present. We encourage the reader to view additional generated videos at: `www.tinyurl.com/ya6df9yl`

Figure 11: Error histogram of the angle detection algorithm on the reacher training set. The output of this algorithm is used as a form of surrogate ground truth to evaluate model performance.

Figure 12: Visualization of the structure of the learned latent space of the baseline model without composability training on the reacher dataset. The visualization is done in the same manner as in Fig. 6. Here, action representations z_t are shown as a function of the absolute angle (α) of the reacher arm at time $t-1$ and the relative angle between the reacher at time t and $t-1$. We see that the encoding of action learned by the baseline is entangled with the absolute position of the reacher arm. While this representation can be used to predict the consequences of actions given the previous frame, it is impossible to establish a bijection between u_t and z_t as the correspondence depends on the previous frame x_{t-1}. Moreover, it is impossible to compose two samples of such a z without access to the intermediate frame. This representation is *minimal*, as it is a linear transformation (a rotation) of the known optimal representation u_t (the ground truth actions). This suggests that composability plays an important role in learning a disentangled representation of actions.